

# PATENT SPECIFICATION

(11) 1 568 845

1 568 845

(21) Application No. 3309/77 (22) Filed 27 Jan. 1977  
(31) Convention Application No. 660 310  
(32) Filed 23 Feb. 1976 in  
(33) United States of America (US)  
(44) Complete Specification published 4 June 1980  
(51) INT CL<sup>3</sup> F02M 25/06, 29/04  
(52) Index at acceptance F1B 2K



(19)

## (54) CARBURETOR FOR MIXING A VAPORIZED LIQUID FUEL WITH AIR FOR AN INTERNAL COMBUSTION ENGINE

5 (71) We, FORD MOTOR COMPANY LIMITED, of Eagle Way, Brentwood, Essex CM13 3BW, a British Company, do hereby declare the invention for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

10 The present invention relates to a carburettor for mixing a vaporized liquid fuel with air for an internal combustion engine. The present invention is particularly concerned with the delivery and metering of a vaporised liquid fuel in an air stream to provide a combustible air/fuel mixture for an internal combustion engine. Reference is made to our copending application (Serial No. 1,568,843) No. 2874/77 which discloses a fuel delivery and metering system.

15 It is well known in the prior art to provide a fuel in liquid form to a moving air stream for delivery to the combustion chambers of an internal combustion engine. The prior art systems generally have utilized mechanical or electromechanical fuel delivery and metering apparatus to provide metered quantities of liquid fuel in proximity to, and in some cases into, the combustion chambers of internal combustion engines. The prior art has also taught that a quantity of liquid fuel may be added to a quantity of moving air upstream from, and for ultimate delivery to, a plurality of combustion chambers through a plurality of intake manifold conduits. The advent of 20 U.S. mandated internal combustion engine exhaust emissions standards has resulted in the adoption of techniques to substantially reduce the quantity of pollutants produced by an internal combustion engine. One technique to reduce the quantity of atmospheric pollutants generated by an internal combustion engine has been the use of an exhaust gas catalyst.

25 Exhaust gas catalysts which operate upon the three principal pollutants, carbon monoxide (CO), hydrocarbons (HC), and the oxides of nitrogen (NO<sub>x</sub>) are generally ex-

50 pensive devices. In addition, these devices require that the input gases be within a fairly tightly controlled and constrained range of chemical constituents. The economically most practical such devices require that the input gases have a gross chemical composition which very closely approximates stoichiometric conditions.

55 The advent of U.S. mandated internal combustion engine exhaust emissions standards has also prompted detailed analysis of the internal combustion as a converter of chemical energy to mechanical power (i.e., as a power source) as a source of atmospheric pollutants. It has been determined that the conventional fuel metering and delivery systems which have been designed to utilize a liquid fuel petroleum product are generally not capable of providing the degree of control of the air/fuel ratio of the combustion mixture (which generates the exhaust gases) so that the objective of the exhaust gas catalyst is caused to be more difficult to achieve. This problem is due in part to non-uniform distribution of the liquid fuel within the intake manifold of the engine. Even in those fuel systems which deliver liquid fuel to the intake ports of the engine, manifold "wetting" can cause the air/fuel ratio to vary from cylinder to cylinder resulting in non-optimum exhaust gas chemistry. Additionally, with a liquid fuel, ignition and flame front propagation problems leading to increased generation of pollutants are encountered. It has been suggested that this difficulty may be overcome by the use of vaporized liquid fuel.

60 70 75 80 85 90 The typical liquid fuel used in internal combustion engines is gasoline. Gasoline may be expected to be completely vaporized at temperatures of about 425°F. As is known, commercially available gasoline is comprised of a substantial number of petroleum product fractions, each of which has a separate vaporization temperature. With commercially available gasoline however, the vaporization temperatures do not exceed about 425°F. In order to achieve the benefits of a vaporized

liquid fuel system, it is necessary to maintain the liquid fuel in a vaporized state until the fuel is delivered to the internal combustion engine combustion chambers.

5 According to prior art techniques for delivering vaporized liquid fuel to an air stream for mixture therewith and delivery to the combustion chambers of an internal combustion engine, the vaporized liquid fuel 70

10 may be indiscriminately allowed to contact relatively cool engine components. This contact can be expected to cause substantial amounts of vaporized liquid fuel condensation. To the extent that the vaporized liquid 75

15 fuel may be allowed to condense within the fuel and air delivery system, the ability to accurately control the air/fuel ratio of the combustion mixture at a desired ratio is lost. It is therefore a specific object of the present 80

20 invention to provide apparatus for promoting the mixing of vaporized liquid fuel with air while reducing direct contact between the vaporized liquid fuel and any relatively cool engine parts.

25 Since it is known that the dew point for a mixture of vaporized fuel mixed with air is substantially lower than the dew point of the raw or unmixed vaporized liquid fuel, it is a further and specific object of the present 85

30 invention to provide a means for rapidly intermixing a vaporized liquid fuel with air.

According to the invention there is provided a carburettor for mixing a vaporized liquid fuel with air to establish a combustible air/fuel mixture for delivery to an internal combustion engine comprising:—

35 metering venturi means adapted to generate, in use, a low pressure zone having a pressure indicative of the rate of air flow therethrough;

40 vapor delivery nozzle means situated within the low pressure zone defined by said venturi means and having a vapor delivery orifice operative to deliver a stream of vaporized liquid fuel to the low pressure zone in response to air flow therethrough;

45 air swirl inducing means situated downstream from said venturi means operative to cause air flowing through said venturi means to acquire a component of motion at an angle to the direction of flow whereby air flowing therethrough may become a swirling air mass;

50 said air swirl inducing means including means defining an aperture in alignment with the vapor delivery nozzle operative to permit a stream of vaporized liquid fuel issuing from said delivery nozzle to pass therethrough without substantial contact with the air swirl inducing means; and mixing section means downstream from said swirl inducing means

55 for fluid communication with the engine;

60 said mixing section means having surface wall portions operative to define a mixing space whereby the swirling air mass and the vaporized liquid fuel may be mixed to establish a combustible air/fuel mixture prior to

65 introduction into the engine;

said swirling air mass being operative to prevent contact between the vaporized liquid fuel and the surface wall portions of the mixing section means.

70 Further according to the invention there is provided:—

75 a carburettor for establishing an air/fuel mixture for delivery to the intake manifold of an internal combustion engine having a throttle valve body for controlling the rate of delivery of the combustible mixture to the engine mixture to the engine, the carburettor including a metering venturi means operative to generate a low pressure zone upon passage of air therethrough, the zone having a pressure indicative of the rate of air passage, therethrough, including:—

80 vapor delivery nozzle means for fluid communication with a source of vaporized liquid fuel;

85 said nozzle means having a vapor delivery orifice situated within the low pressure zone and arranged to provide a stream of vaporized fuel into, and in the direction of air flow through, the low pressure zone; and

90 swirl means situated downstream from the metering venturi means operative to induce swirling of any air mass flowing through the metering venturi means;

95 said swirl means including defining an unobstructed vapor aperture in alignment with said vapor delivery nozzle means operative to permit a stream of vaporized liquid fuel to pass therethrough while avoiding any substantial contact between the vapor stream and said swirl means.

100 The invention will now be described with reference to the accompanying drawings, in which:—

105 Figure 1 illustrates a vaporized liquid fuel delivery and metering system with which the present invention is of utility;

110 Figure 2 illustrates the present invention in association with a vapor delivery nozzle arranged within an otherwise conventional metering venturi; and

115 Figure 3 illustrates the swirl inducing member of the present invention in a perspective view.

120 Referring now to the drawing wherein like numerals designate like structure throughout the various views thereof, Figure 1 illustrates a vaporized liquid fuel delivery and metering system 10 with which the present invention is of utility. The vaporized liquid fuel delivery and metering system 10 is arranged to provide a combustible mixture to the intake manifold 12 of an internal combustion engine 14. Internal combustion engine 14 is provided with combustion by-product exhaust gas conduit means 16. Intake manifold 12 is provided with throttle valve body 17. As illustrated, internal combustion engine 14, intake manifold 12, throttle valve body 17 and exhaust gas con-

125

130

duit means 16 are substantially conventional. For purposes of illustration, it will be considered that internal combustion engine 14 is of the type adapted for installation and use in powering an automotive vehicle, not shown.

System 10 is arranged to receive liquid fuel from a conventional liquid fuel reservoir or tank, not shown, through conduit 18. Conduit 18 communicates with intermediate liquid fuel reservoir 20. The communication between conduit 18 and intermediate reservoir 20 may be controlled, for example, by a pivoted float valve 22 in the conventional manner. As will be appreciated, liquid fuel could be pumped through conduit 18 by conventional pumping means such as the conventional mechanical or electrical fuel pump normally used in automotive vehicles.

Liquid fuel contained in intermediate reservoir 20 may be provided by coarse liquid fuel delivery means 24 to primary heating means 26. Coarse liquid fuel delivery means 24 may include for example, an electrical or mechanical liquid pump 28 and a liquid control valve 30. An auxiliary heating means 32 is arranged in fluid serial flow relationship with respect to the primary heating means 26 so that fuel provided from intermediate reservoir 20 would flow serially through the primary heating means 26 and thence through auxiliary heating means 32. The heating means are shown to be communicated via conduits 34 to a vapor storage reservoir 36.

As illustrated in Figure 1, the primary and auxiliary heating means 26, 32 are connected in serial fluid flow relationship. In order for efficient operation of the auxiliary heating means 32, it should be designed for relatively low fuel flow consonant with operation of the associated engine at idle. As such, however, the auxiliary heating means 32 could present a high impedance to fluid flow and could impede engine operation under high fuel consumption conditions. It is therefore contemplated that the primary and auxiliary heating means could be connected in parallel fluid flow. It is also contemplated to provide a fluid by-pass valve downstream from primary heating means 26 and upstream from the auxiliary heating means 32 to place the primary heating means 26 in direct fluid communication with the vapor reservoir 36 when the auxiliary heating means 32 are not required as a vapor supply source.

Vapor reservoir 36 is communicated by way of conduit 38 with carburetor means 40 according to the present invention. As used herein "carburetor" means the apparatus according to the present invention for mixing fuel with air to establish a combustible air/fuel mixture. As illustrated in Figure 1, the vapor delivery nozzle 42 of vapor delivery conduit 38 is positioned within the low pres-

sure zone formed by the metering venturi means 44 of the carburetor means 40. A movable pindle 46 is situated within the vapor delivery nozzle 42 and is controlled by servomechanism means 48. Carburetor means 40 includes mixing section 47 which inter-communicates the metering venturi means 44 with the throttle body 17 upstream from the intake manifold 12. The operation and structure of carburetor means 40 and fuel delivery nozzle means 42 is described hereinbelow with reference to Figures 2 and 3.

Servomechanism 48 may be, for example, a conventional servomotor operated electrically or by electromechanical means. Servomechanism 48 receives an input command signal from servomechanism control means 50. As here illustrated, servomechanism control means 50 are arranged to be responsive to an exhaust gas sensor 52 which may be for example, a titania exhaust gas sensor according to United States Letters Patent 3,886,785. According to Figure 1, fuel delivery and metering system 10 is also provided with vapor temperature control means 54. Temperature control means 54 are arranged to be responsive to the vapor temperature in vapor delivery conduit 38 in order to control an exhaust gas flow diverter valve 56. Valve 56 is operative to control the heating of primary heating means 26.

Referring now to Figure 2, the carburetor means 40 according to the present invention is shown. Carburetor means 40 is provided with means defining a substantially conventional metering venturi 44. Vapor conduit 38 is provided with vapor delivery nozzle 42 which is situated within the metering venturi 44 of the carburetor means 40. Vapor conduit 38 is arranged to place the orifice of vapor delivery nozzle 42 within the low pressure region established by the metering venturi 44. In the preferred embodiment, metering venturi 44 is arranged to define an air flow passage which is rapidly convergent on its upstream side and gradually divergent on its downstream side. The terms "upstream" and "downstream" relate to the direction of intake air flow which is illustrated by arrow A. Swirl inducing means 214 is situated downstream from metering venturi 44 upstream from mixing section 47. Swirl inducing means 214 is described more fully hereinbelow with reference to Figure 3. A mixing region 215 is disposed downstream from swirl inducing means 214 within mixing section 47.

As a coarse measure of air/fuel ratio control, the ratio of the area of the metering venturi 44 in the plane of the orifice of vapor delivery nozzle 42 when compared to the area of the orifice of the vapor delivery nozzle 42 should be slightly less than that which would produce the desired air/fuel ratio. We have determined that the air/fuel ratio is approximately equal to seven tenths (.7) of

the ratio of the air delivery area compared to fuel delivery area. This relationship is an approximation and is based on air at 70°F. and commercially available gasoline, as the fuel, vaporized at 400°F. By modulating the actual area of fuel delivery through use of a movable pintle and needle valve, for example, the actual air/fuel ratio may be modulated and a desired air/fuel ratio may be precisely attained. In view of the fact that fuel vapor is provided to the moving air stream with substantially the same pressure differential through the orifice of vapor delivery nozzle 42 as is experienced by the air stream in flowing from the upstream side of metering venturi 44 to the plane of the orifice of nozzle 42 and is delivered to the low pressure region defined by the air stream moving through metering venturi 44, the mass of vaporized liquid fuel can be precisely controlled to match the mass of air being consumed by the associated engine to maintain a preselected and desired air/fuel ratio for all mass ratios of air flow.

Referring now to Figures 2 and 3, the swirl inducing means 214 are illustrated in a perspective view. Air swirl inducing means 214 are comprised of a substantially annular insert member having a solid rim portion 216 and a plurality of upstanding fin members 218. Fin members 218 are connected at their radially inwardmost point by a further substantially annular rim 220 which is arranged to define a circular aperture 222 at the central portion of swirl inducing means 214. Aperture 222 is sized and positioned with respect to vapor delivery nozzle 42 to permit the unhindered passage of a vapor stream from vapor delivery nozzle 42 through the air swirl inducing means 214 without contact of the vapor stream with swirl inducing means 214. Fin members 218 are cooperative to induce a swirling movement of the air stream as it passes over the fin members 218 into mixing region 215 of the mixing section 47. This swirl is operative to promote intermixing of the vapour stream from vapor delivery nozzle 42 with the air passing through the mixing region 215. Further, and more importantly, the swirl is operative to prevent the vapor stream from coming into contact with the side walls of the mixing section 47 to thereby further reduce any opportunity for contact of the vaporized liquid fuel with a relatively cooler surface and resultant condensation.

With reference to Figures 1 and 2, mixing section 47 is shown to be vertically disposed above the throttle valve body 17 and is operative to provide an unobstructed mixture flow conduit therebetween. It will be appreciated that the vertical orientation of mixing section 47 is arbitrary and for purposes of illustration. Mixing section 47, in an automotive installation could also be disposed horizontally across the top of engine 14.

The "raw" vaporized fuel will have a dew point dependent upon the various fractions which make up the vapor. However, the fuel vapor per se can begin to condense as its temperature drops below the temperature of complete vaporization, for example 425°F. The dew point of an air/fuel mixture having a vaporized liquid fuel such as gasoline is approximately 125°F. (at atmospheric pressure), again depending upon the fuel fractions present in the fuel vapor. As the pressure drops to subatmospheric levels, the dew point of the fuel vapor within the air/fuel mixture will be further lowered. Thus, once the fuel vapor has been mixed with air, the dew point of the fuel vapor will drop dramatically. The condensation problem is therefore substantially lessened and contact with engine components will not have an adverse effect on the vapor form of the fuel. Additionally, the high vapor inlet temperatures and the short residence time of the vapor in the region downstream from air swirl inducing means 214 will virtually preclude any opportunity for condensation to occur.

The precise area of the orifice of fuel delivery nozzle 42 may be varied by the movement of pintle 46 in order to vary the area of the fuel delivery nozzle and hence the quantity of vaporized liquid fuel being provided to the engine through vapor delivery conduit 38. A throttle valve situated within throttle valve body 17 may be operative to vary the rate of delivery of the combustible air/fuel mixture to the intake manifold of engine 14 from the carburetor means 40. The throttle valve may be operated in the conventional manner. As discussed hereinabove, the throttle valve will not cause or promote any substantial amounts of vaporized fuel condensation since it will be positioned below the mixing section 47 and hence sufficiently downstream from vapor delivery nozzle 42 to be in the mixture where the dew point of the vaporized fuel has been lowered. Additionally, the throttle valve will normally be at a relatively elevated temperature due to its proximity to the heated components of the engine 14. Preferably, the orifice of vapor delivery nozzle 42 will be placed within the region defined by metering venturi 44 at or within the zone of maximum depression (minimum pressure) in order to provide the greatest pressure differential across the orifice. However, accurate placement within the low pressure zone is not critical since the vapor pressure is referenced to substantially the same pressure as exists upstream from the metering venturi 44 and the size of the minimum pressure zone defined in the direction of flow (arrow A) is variable.

**WHAT WE CLAIM IS:—**

1. A carburetor for mixing a vaporized liquid fuel with air to establish a combustible

air/fuel mixture for delivery to an internal combustion engine comprising:—		
metering venturi means adapted to generate, in use, a low pressure zone having a pressure indicative of the rate of air flow therethrough;	55	
vapor delivery nozzle means situated within the low pressure zone defined by said venturi means and having a vapor delivery orifice operative to deliver a stream of vaporized liquid fuel to the low pressure zone in response to air flow therethrough;	60	
air swirl inducing means situated downstream from said venturi means operative to cause air flowing through said venturi means to acquire a component of motion at an angle to the direction of flow whereby air flowing therethrough may become a swirling air mass;		
said air swirl inducing means including means defining an aperture in alignment with the vapor delivery nozzle operative to permit a stream of vaporized liquid fuel issuing from said delivery nozzle to pass therethrough without substantial contact with the air swirl inducing means; and	65	
mixing section means downstream from said swirl inducing means for fluid communication with the engine;		
said mixing section means having surface wall portions operative to define a mixing space whereby the swirling air mass and the vaporized liquid fuel may be mixed to establish a combustible air/fuel mixture prior to introduction into the engine;	70	
said swirling air mass being operative to prevent contact between the vaporized liquid fuel and the surface wall portions of the mixing section means.	75	
2. A carburettor according to Claim 1, wherein said air swirl inducing means comprise a plurality of fin members arranged about the aperture defining means.	80	
3. A carburettor according to Claim 2, wherein said means defining an aperture comprise:	85	
an outer rim portion; and an inner annular rim having an aperture extending therethrough in a vapor flow direction;		
said plurality of fin members being attached to said outer rim portion and said inner apertured rim.	90	
4. A carburetor for establishing an air/fuel	95	
mixture for delivery to the intake manifold of an internal combustion engine having a throttle valve body for controlling the rate of delivery of the combustible mixture to the engine, the carburetor including a metering venturi means operative to generate a low pressure zone upon passage of air therethrough, the zone having a pressure indicative of the rate of air passage therethrough, including:	100	
vapor delivery nozzle means for fluid communication with a source of vaporized liquid fuel;		
said nozzle means having a vapor delivery orifice situated within the low pressure zone and arranged to provide a stream of vaporized fuel into, and in the direction of air flow through, the low pressure zone; and		
swirler means situated downstream from the metering venturi means operative to induce swirling of any air mass flowing through the metering venturi means;		
said swirler means including means defining an unobstructed vapor aperture in alignment with said vapor delivery nozzle means operative to permit a stream of vaporized liquid fuel to pass therethrough while avoiding any substantial contact between the vapour stream and said swirler means.		
5. A carburetor according to Claim 4, including further:		
mixing section means having side wall portions downstream from said swirler means operative to define an unobstructed mixing zone and further operative to communicate any air flowing through said metering venturi with the throttle valve body;		
said swirler means cooperative with said mixing section means to promote mixing of the vaporized liquid fuel with the swirling air mass while the swirling air mass constrains the vaporized liquid fuel stream to prevent contact of the vaporized liquid fuel stream with the side wall portions of the mixing section means.		
6. A carburetor for mixing a vaporized liquid fuel with air substantially as hereinbefore described with reference to and as shown in the accompanying drawings.		

PETER ORTON,  
Chartered Patent Agent.

This drawing is a reproduction of  
the Original on a reduced scale

