

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2013301351 B2**

(54) Title
Device for evaporating a volatile fluid

(51) International Patent Classification(s)
A01M 1/20 (2006.01) **A61L 9/03** (2006.01)

(21) Application No: **2013301351** (22) Date of Filing: **2013.08.08**

(87) WIPO No: **WO14/023967**

(30) Priority Data

(31)	Number	(32)	Date	(33)	Country
	1214166.9		2012.08.08		GB

(43) Publication Date: **2014.02.13**

(44) Accepted Journal Date: **2017.06.29**

(71) Applicant(s)
Reckitt & Colman (Overseas) Limited

(72) Inventor(s)
Duffield, Paul;Piercy, Ellen;Tyson, Larry;Walsh, Steve

(74) Agent / Attorney
Shelston IP Pty Ltd., Level 21, 60 Margaret Street, Sydney, NSW, 2000, AU

(56) Related Art
**DATABASE WPI 41-48, Week 198406 Thomson Scientific, London, GB; AN
1984-034449 XP002716398, & JP S58 225595
GB 2315031**



- (51) **International Patent Classification:**
A01M 1/20 (2006.01) *A61L 9/03* (2006.01)
- (21) **International Application Number:**
PCT/GB2013/052120
- (22) **International Filing Date:**
8 August 2013 (08.08.2013)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
1214166.9 8 August 2012 (08.08.2012) GB
- (71) **Applicant:** RECKITT & COLMAN (OVERSEAS) LIMITED [GB/GB]; 103-105 Bath Road, Slough, Berkshire SL1 3UH (GB).
- (72) **Inventors:** DUFFIELD, Paul; Reckitt Benckiser (Brands) Limited, Dansom Lane, Hull HU8 7DS (GB). PIERCY, Ellen; 25 Frith Avenue, Delamere, Cheshire CW8 2JB (GB). TYSON, Larry; c/o ExosNPD, Unit 105, The Mayford Centre, Mayford Green, Woking, Surrey GU22 0PP (GB). WALSH, Steve; 24 Stoneleigh Court, Frimley, Surrey GU16 8XH (GB).
- (74) **Agents:** CARLIN, Robert et al.; Reckitt Benckiser Corporate Services Limited, Dansom Lane, Hull HU8 7DS (GB).


(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

(54) **Title:** DEVICE FOR EVAPORATING A VOLATILE FLUID



(57) **Abstract:** An assembly for evaporating a volatile fluid is described, the assembly comprising a device (1) and a refill (2) which are detachable from one another: wherein the device comprises a magnetic induction coil (103) configured to operate with an alternating current passed therethrough; and wherein the refill comprises a reservoir (201) for the volatile fluid, a volatile fluid transport means (203) to draw the fluid from the reservoir, and at least one susceptor (204) arranged to heat the volatile fluid transport means when said alternating current is passed through the induction coil. Refills, devices and methods of operation are also described.

Device for Evaporating a Volatile Fluid

The present invention relates to a device for evaporating a volatile fluid, for example a fragrance, pesticide, or a medicament.

5

Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

10

Devices are known for emitting volatile liquids into an atmosphere. In one known device, described in US Patent Publication No. 2002/0146243, a device having a housing is provided with a container for the volatile liquid, a wick extending from the container and an annular electrical heater located in the vicinity of the distal end of the wick to accelerate the evaporation of the volatile liquid from the wick. The container and wick are conventionally provided as a removable

15

refill and the device uses a positive temperature coefficient (PTC) thermistor as the electrical heater. The device also has an electric plug by which it is plugged into a wall socket.

20

However, the heater must be run at a high temperature in order to sufficiently heat the volatile liquid within the wick. Further, the position of the heater within the housing means that the heater heats the wick as well as the surrounding device housing which provides two distinct drawbacks. Firstly, high levels of power consumption are required to get the electrical heater up to a satisfactory operating temperature to heat the wick to the temperature at which the volatile liquid can be emanated. Secondly, the mass of such an electrical heater and the surrounding device housing typically holds residual heat for a prolonged period after power to the heater has ceased, as such if there is an appetite to modify the operation of the device, particularly to address anti-habitation concerns associated with the emanated volatile liquid, such known devices are inherently slow to respond as removing power from the heater does not appreciably slow the emanation rate due to the residual heat.

25

30

Another known device can be found in International Publication No. WO 2005/112510, which describes an induction heating apparatus for the dissemination of volatile liquids. The device has a base module and a separate reservoir containing the volatile liquid. The base module has an upwardly-projecting cylindrical portion within which is a primary induction coil. The base of the reservoir has a recess which fits over the cylindrical portion of the base, around which is a secondary induction coil composed of a short-circuited wire coil. When current is passed through the primary coil, the secondary coil heats up and thus heats the liquid to increase the rate of evaporation. However, this device heats all of the volatile liquid in the reservoir, resulting in a device which is slow to reach the ideal operating temperature and operates with high levels of

35

power consumption. Further, the device will continue to emit vapour after it has been switched off as the liquid in the reservoir will retain considerable residual heat and will take quite some time to cool. Furthermore, if the volatile liquid is a fragrance, heating the entire reservoir can degrade the quality of the fragrance over the life of the refill.

5

According to a first aspect of the present invention, there is provided an assembly for evaporating a volatile fluid, the assembly comprising a device and a refill which are detachable from one another:

wherein the device comprises an induction coil;

10

and wherein the refill comprises a reservoir for the volatile fluid, a volatile fluid transport means to draw the fluid from the reservoir, and wherein the volatile fluid transport means has at least one susceptor arranged to heat the volatile fluid transport means when an alternating current is passed through the induction coil.

15

Unless the context clearly requires otherwise, throughout the description and the claims, the words "comprise", "comprising", and the like are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense; that is to say, in the sense of "including, but not limited to".

20

In the context of the present invention the term volatile fluid transport means is used herein to refer to any physical fluid transport conduit that permits the fluid to flow away from the reservoir toward the susceptor(s) without the assistance of gravity or powered means, in other words relying on capillary action, osmotic transfer, wicking action or the like to transport the fluid.

25

Therefore the volatile fluid transport means in the present invention may be a fibrous substance such as a cellulose wick or the like or the volatile fluid transport means could be a porous substance such as ceramic wick or the like. Alternatively the volatile fluid transport means may be a gel matrix or the like, and in this arrangement the reservoir and the volatile fluid transport means may be made from the same material and/or may be substantially integral with each other.

30

Preferably the volatile fluid transport means protrudes through a cap in the refill to extend into the environment surrounding the refill distal from the reservoir. At least one of said magnetic susceptors may be provided in contact with the volatile fluid transport means in a distal portion thereof between the cap and the distal end of said means.

35

With this arrangement, the susceptor(s) does not need to be connected to any part of the device, only to the volatile fluid transport means in the refill. This means that no electrical connection needs to pass through the reservoir to the susceptor(s) eliminating the possibility of a resultant fluid leakage path.

- Since the energy input to the assembly can be effectively targeted to heat the susceptor(s) within the induced magnetic field, only the susceptor(s) and the surrounding fluid in the volatile fluid transport means is heated rather than the energy being wasted as heat elsewhere in the refill and/or device as with the prior art assemblies. Further, as the susceptor(s) is a simple, low-cost component, it can be cost efficiently provided as part of a refill.
- 5

- 3 -

In a preferred arrangement each refill may be provided with at least one susceptor having heating characteristics which are optimised for the specific fluid contained in the refill, without the need for user intervention or complex control. For instance, it may be preferable to make the device as inexpensively as possible, therefore, one option to facilitate inexpensive manufacture would be to provide the device without any user-operable controls which permit a variation of its operating parameters such that the device operates in accordance with a single set of operating parameters. In this arrangement the length and/or mass and/or composition of the susceptor(s) in the refill may be varied to tune the heat achieved when the susceptor(s) is located within the induced magnetic field during use to the evaporation temperature of the volatile fluid. By way of example, where the volatile fluid is a fragrance composition fragrances are generally composed of a combination of top notes, middle notes and base notes. Top notes represent the most volatile part of the fragrance composition, these notes are usually perceived first by a human nose and include the "light" or "fresh" olfactive notes of the composition. The middle notes typically represent the "heart" of the mixture as they often provide the majority of the fragrance. The base notes are typically the least volatile part of the mixture and includes the heaviest molecules such as the notes that provide "rich" or "deep" olfactive notes of the composition. Due to their weight and size the base notes usually linger for the longest period. A fragrance mixture is typically made up of 10% top notes, 60% middle notes and 30% base notes. However, if it is desired to sell a fragrance made up predominantly of top notes it would be possible to deploy a refill containing a susceptor that heats to a relatively low temperature to ensure that the highly volatile top notes do not flash off to impart a user-desirable lifetime to the refill. Conversely if it is desired to sell a fragrance made up predominantly of base notes it would be possible to deploy a refill containing a susceptor(s) that heats to a relatively high temperature to ensure that the less volatile base notes are evaporated at a satisfactory rate to be noticeable by the user as well as imparting a user-desirable lifetime to the refill, i.e. a refill that will not last too long and risk clogging or blocking the volatile fluid transport means.

Furthermore, this preferred arrangement would make it permissible to market refills containing markedly different formulations for use with the same device. For instance, when evaporating fragrance formulations the preferred operating temperature may be in the order of 55-85°C depending on the ratio of top, middle and base notes thereof, whereas for a pest control formulation much higher operating temperatures are generally required, typically in the order of 120-140°C. Accordingly an assembly according to the present invention may provide a user with a much simpler and inexpensive solution to emanate volatile fluids; simpler as the device can be left in situ and the desired refill may be changed by the user without the user having to communicate to the device that the refill contains a different formulation; inexpensive as a user need only purchase one device to emanate a wide variety of refills containing different

- 4 -

formulations and the device need not have expensive nor complex refill recognition components to determine the device operating parameters.

Although one option to facilitate inexpensive manufacture of a device would be to provide the device without any user-operable controls which permit a variation of its operating parameters, it may be preferable to provide the device with basic user-operable controls which permit limited variation of the operating parameters, say between 2-4 predetermined operating parameters since some users may wish to change the intensity of the evaporated volatile fluid depending of the type of volatile fluid, the size of the space the fluid is being emanated into, etc.

Alternatively where producing the device as inexpensively as possible is less of a concern the device may be provided with one or more user-controllable inputs to permit the user to alter one or more operating parameters of the device to provide the user with a multitude of options to impart an emanation performance of the volatile fluid that they desire.

A further benefit of the assembly according to the present invention is that the mass of the components being heated is lower than hitherto available assemblies such that there will be a reduced amount of residual heat in said heated components during use and once the input energy to the assembly stops. This is particularly advantageous for several reasons, firstly, this improves the safety of the assembly during operation since only a small proportion of the device and/or refill will be heated thus making the assembly cool to the touch during use. Secondly, if there is the need to vary the emanation rate of the volatile fluid it is possible to rapidly cease emanation of the volatile fluid by removing the input power to the induction coil and/or modifying the duty cycle to impart a rapid cool down of the susceptor. For instance, when concerned with addressing anti-habituation during fragrance emanation it is necessary to allow a user's olfactive receptors to become non-saturated with the particular fragrance molecule(s) and this can only be achieved by ceasing the emanation of those fragrance molecule(s) and/or emanating a different fragrance. The ability of the device of the present invention to achieve rapid cool-down facilitates more rapid attenuation of the saturated olfactive receptors.

Preferably the susceptor(s) is magnetic, this allows the susceptor to be heated largely (predominately) by magnetic hysteresis, although some secondary eddy current heating may occur.

To provide the device with a stable maximum operating temperature, the susceptor(s), if magnetic, may comprise a material with a stable Curie temperature, for instance 150°C. When the magnetic susceptor(s) is heated beyond this temperature, the susceptor(s) will become paramagnetic and no longer be susceptible to hysteresis heating until such time it cools down

- 5 -

back below its Curie temperature. By selecting a magnetic susceptor(s) with a low and stable Curie temperature, it is possible to prevent the temperature of the volatile liquid in the volatile fluid transport means exceeding a predetermined level, even if for some reason excess power is supplied to the induction coil.

5

The susceptor(s) is preferably provided in direct contact with the volatile fluid transport means. In some embodiments the susceptor(s) may be at least partially embedded within the volatile fluid transport means. Alternatively or additionally, the susceptor(s) may surround a portion of the volatile fluid transport means. Most preferably however, the susceptor(s) is entirely embedded

10

One advantage of enclosing/embedding the susceptor(s) entirely within the volatile fluid transport means is that the heat emitted from the susceptor(s) is more effectively transferred to the adjacent fluid in the volatile fluid transport means, and not to the entirety of the volatile fluid transport means to some or all of the fluid reservoir. This is advantageous as where the volatile fluid is a fragrance, a medicament, a pest control material or an active pharmaceutical ingredient, heating the entire reservoir can degrade the quality of the fluid over the life of the refill which is clearly undesirable.

15

20

Enclosing the susceptor(s) entirely within the volatile fluid transport means also minimises the potential for injury as the susceptor is less accessible and therefore is less likely to be accidentally touched during use.

25

To ensure the heat generation within the susceptor(s) is as efficient as possible, the susceptor(s) may be at least partially located inside the induction coil during the operation of the assembly.

In a preferred embodiment the refill is provided with a single susceptor.

30

Alternatively the refill may be provided with a more than one susceptor. In this arrangement by increasing the number of susceptors it is possible to increase the amount of heat generated within the same device operating parameters relative to when only a single susceptor is present. For example, where under fixed device operating parameters one magnetic susceptor is heated to 80°C it is surprisingly found that if two identical susceptors are in the induced field rather than both heating to 80°C they will both heat to 90°C. Furthermore, it is surprisingly found that if three identical susceptors are in the induced field rather than both heating to 80°C or 90°C they will both heat to 105°C. Whilst not wishing to be bound by the following proposed hypothesis, the inventor of the present invention suspects that the presence of multiple susceptors within the

35

- 6 -

induced field focuses the field to the inside of the coil which decreases the area over which the field is spread thus increasing the magnetic focus and efficiency thereof.

5 In some embodiments, the device may further comprise a control unit to control the operation of the induction coil. In such an embodiment, the device may further comprise a feedback coil configured to interact with a magnetic field generated by the induction coil. In this arrangement the control unit may be configured to process an output from the feedback coil and, from this output, vary one or more operating parameters of the induction coil. The feedback coil is preferably configured to be capable of changing its output, in use, when a susceptor(s) is within
10 the magnetic field of the induction coil.

Preferably the feedback coil in may be configured, in use, to change its output when one property of a susceptor is changed from refill to refill, for example if the shape or mass or material or surface area of the susceptor changes. The control unit may then be configured to interpret the
15 change in output from the feedback coil to determine what type of refill is within the magnetic field of the induction coil, and from this, automatically vary a property of the induction coil to apply the appropriate heating regime to each particular refill.

To ensure the control unit is as simple as possible, thus as inexpensive as possible, the assembly
20 is preferably configured such that the feedback coil only has to change its output in response to a change of a single property of the susceptor from refill to refill, therefore, it is preferred for refills configured to be used with such a device to have three of the following susceptor properties fixed and one of the following susceptor properties variable for detection of this variance by the feedback coil, wherein said susceptor properties are: shape; mass; material and surface area.

25 The provision of a feedback coil could also be used to prevent the susceptor(s) from getting too hot during use. As the susceptor(s) gets hot, the output from the feedback coil changes. The control unit could be configured to interpret a high temperature of the susceptor(s) based on this output, and from this, automatically vary a property of the induction coil to cool the susceptor.

30 A further use for the feedback coil the device could be to ensure that the device is operating as efficiently as possible, in this preferred arrangement the control unit monitors the output of the feedback coil to alter the duty cycle as required to ensure the current supplied through the induction coil is optimised to the particular susceptor(s) in proximity with the induction coil.

35 Examples of the device operating parameters which may be varied by the control unit may be the maximum amplitude, the frequency, or the duty cycle of the current being passed through the induction coil.

- 7 -

Alternatively or additionally, the device may be provided with mechanical or electromechanical means that are operable by the control unit to physically move the refill such that the susceptor is moved relative to the induced magnetic field of the induction coil. Alternatively or additionally, the device may be provided with mechanical or electromechanical means that are operable by the control unit to physically move the induction coil within the device housing such that the induced magnetic field is moved relative to the susceptor in the refill.

Preferably, the alternating current passed through the induction coil may be set at a frequency greater than 20 KHz. Frequencies above this threshold are particularly effective when the susceptor is magnetic so as to allow the induction coil to more effectively heat up the susceptor by hysteresis. More preferably, the alternating current passed through the induction coil may be set at a frequency greater than 100 KHz. Even more preferably, the alternating current passed through the induction coil may be set at a frequency greater than 150 KHz.

In some embodiments, the device may further comprise multiple reservoirs each having their own volatile fluid transport means and susceptor.

The presence of the multiple reservoirs allows more than one type of volatile fluid to be dispensed by the device by the single induction coil simultaneously.

Alternatively the device may be provided with more than one induction coil, each induction coil being associated with a separate refill whereby, in use, the induced magnetic field from one induction coil surrounds the susceptor(s) in only one refill, this may permit alternate emanation of the volatile fluid from each respective refill, this may be especially preferably when the volatile fluids are fragrances.

In other embodiments, the device may further comprise an additional susceptor configured to heat an area around the induction coil. The purpose of this additional susceptor is to ensure that the components around the induction coil are appropriately heated, for instance the core of the induction coil or members which support the induction coil, such to avoid any volatile fluid which evaporates from the one or more volatile fluid transport means from condensating onto these components.

According to a second aspect of the present invention, there is provided a refill for attaching to a device for evaporating a volatile fluid, wherein the refill comprises a reservoir for the volatile fluid, and a volatile fluid transport means to draw the fluid from the reservoir, wherein the volatile fluid

- 8 -

transport means also has at least one susceptor arranged to heat the volatile fluid transport means when the refill is exposed to a changing magnetic field.

- According to a third aspect of the present invention, there is provided therefore a device for
- 5 evaporating a volatile fluid from a detachable refill of volatile fluid comprising a reservoir for the volatile fluid, and a volatile fluid transport means to draw the fluid from the reservoir, wherein the volatile fluid transport means also has at least one susceptor; wherein the device comprises a magnetic induction coil configured to induce a magnetic field.
- 10 According to a fourth aspect of the present invention, there is provided a method for evaporating a volatile fluid, comprising the steps of locating a refill comprising a reservoir for the volatile fluid, a volatile fluid transport means to draw the fluid from the reservoir toward at least one susceptor in a device comprising a magnetic induction coil configured to operate with an alternating current passed therethrough to induce a magnetic field;
- 15 generating a magnetic field through said induction coil by passing an AC current therethrough; said locating of the refill in the device being such that the at least one susceptor is at least partially within the generated magnetic field;
- and evaporating the volatile fluid by said at least one susceptor being heated by the changing magnetic field from the induction coil to evaporate the volatile fluid from the volatile fluid transport
- 20 means.

- The device may further comprise a control unit and/or a feedback coil and the method may comprise the control unit controlling the operation of the induction coil. The method may further comprise the control unit processing an output from the feedback coil and, from this output,
- 25 varying one or more operating parameters of the induction coil.

- The feedback coil may be configured, in use, to change its output when one property of a susceptor is changed from refill to refill, for example if the shape or mass or material or surface area of the susceptor changes. The method may further comprise the control unit being
- 30 configured to interpret the change in output from the feedback coil to determine what type of refill is within the magnetic field of the induction coil, and from this, automatically vary a property of the induction coil to apply the appropriate heating regime to each particular refill.

- As the susceptor(s) gets hot, the output from the feedback coil changes. The method may further
- 35 comprise the control unit interpreting the output of the feedback coil to determine a high temperature of the susceptor(s) and automatically varying a property of the induction coil to cool the susceptor.

- 9 -

A further use for the feedback coil in the device could be to ensure that the device is operating as efficiently as possible. The method may further comprise the control unit monitoring the output of the feedback coil to alter the duty cycle as required to ensure the current supplied through the induction coil is optimised to the particular susceptor(s) in proximity with the induction coil.

5

The method may comprise the control unit may comprises the steps of the control unit varying one or more of the operating parameters of the induction coil by varying one or more of: the maximum amplitude; the frequency; the duty cycle.

10 The method preferably includes the step of the device being operated to pass an alternating current through the induction coil with a frequency greater than 20 KHz to more effectively heat up the susceptor by magnetic hysteresis, and preferably greater than 100 KHz, and more preferably at a frequency of 150KHz.

15 Preferably, substantially all of the material in the reservoir is configured to be evaporated within 5 hours of continuous actuation of the induction coil.

More preferably, substantially all of the material in the reservoir is configured to be evaporated within 3 hours of continuous actuation of the induction coil.

20

The invention will now be described, by example only, with reference to the accompanying drawings in which:

25 Figure 1 shows a block diagram of an embodiment of the present invention.

Figure 2 shows in more detail one example of the electronic circuitry used in the embodiment shown in Figure 1.

30 Figure 3 shows in more detail a further example of the electronic circuitry used in the embodiment shown in Figure 1.

Figures 4A and 4B show an example layout of the invention, when configured as a device and a refill.

35

Figures 5A - 5C show another example layout of the invention which uses a gel stick type delivery system.

- 10 -

Figures 6A – 6C show a further example layout of the invention which uses a pod type delivery system.

Figure 7 shows hysteresis loops for two different susceptor materials.

5

Figure 1 shows a device 1 and a refill 2. The device 1 comprises a power source 101 connected to electronic circuitry 102. Making up a part of this electronic circuitry is an induction coil 103 and an optional feedback coil 104.

10 The refill 2 is a separate component to the device 1. The refill 2 comprises a reservoir 201, which holds volatile fluid 202. The refill 2 also comprises a fluid transport means 203 illustrated here as a wick which contains a susceptor 204. The susceptor is preferably in, or at least partially in, the wick. The wick 203 should extend beyond the reservoir 201 so that the fluid 205 which evaporates from the wick 203 can pass to the exterior of both the device 1 and the refill 2.

15

The power source 101 of the device 1 may for example be a connection to a mains supply, a connection to a USB docking station, or a battery.

20

The circuit diagrams shown in Figures 2 and 3 are examples of self-resonant/self-oscillating zero voltage switched (ZVS) converter circuits. Such circuits are well known in the art.

25

The ZVS circuits shown are configured to provide a high frequency magnetic field across a induction coil L₂ (approximately 200 KHz). In figure 2, the circuit is located between a line supply L_S and a ground connection L_G. Connected to the line supply L_S is the power source 101, which provides the line supply L_S with AC current. On the line supply L_S is a diode D1. The circuitry also comprises the feedback coil 104, the induction coil 103, three capacitors C2;C3;C4, two resistors R1;R3, and two transistors Q2;Q3.

30

The component layout in Figure 3 is similar to that of Figure 2, except for the addition of a system microcontroller unit (MCU) or control unit, with its own power supply which feeds off the line supply L_S, and which is adapted from the line supply L_S by conventional power stepping electronics which are not shown, an additional resistor R1, an additional capacitor C1, and first and second extra diodes D2 and D3. Preferably the additional capacitor C1 is polarised, and preferably the second additional diode D3 is a Schottky diode. The purpose of the MCU in Figure 3 is to control the duty cycle of the ZVS converter, and hence the power being delivered through the induction coil 103.

35

- 11 -

In each of Figures 2 and 3, the capacitor C4 is the resonating capacitor of the ZVS circuit. The high frequency voltage present at a collector Q3 is coupled by capacitor C4 to a rectifying and regulating network comprising diodes D3 and D2, and the capacitor C1. In the case of Figure 3, the smoothed and regulated voltage present across capacitor C1 is used to power low voltage sections of the circuit including the MCU.

Operation of the invention as shown in Figure 1-3 will now be described.

Prior to use, the power source 101 of the device 1 must be fully charged or connected. Once the device 1 is switched on, the electronic circuitry 102 of the device 1 is then configured to pass an AC current through the induction coil 103. The circuitry 102 may be configured to continually pass an AC current through the induction coil 103, or alternatively may be configured to only pass AC current through the induction coil 103 when the refill 2 containing the susceptor 204 is located near the induction coil 103, as will be discussed.

A refill 2 as shown in Figure 1 is connected to or docked with the device 1. To hold the refill 2 in place on the device 1, a fastening means, clip, or cradle may be provided on the device 1, as is shown for example in Figures 4A – 6C. However the refill 2 is connected to the device 1, the main requirement is that the susceptor 204 inside the refill 2 is close enough to be heated by the induction coil 103, and to interact with the optional feedback coil 104, located on the device 1, as will be discussed.

Once the refill 2 is engaged with the device 1, the susceptor 204 of the refill 2, which is positioned within the magnetic field of the induction coil 103, if magnetic, will begin to heat up predominately by magnetic hysteresis heating and possibly to a minor degree also by eddy current heating. If the susceptor is not magnetic, then the susceptor 204 will only heat up by eddy currents and no magnetic hysteresis heating will occur. As the susceptor 204 heats up, due to its proximity with the wick 203, the volatile fluid 202 inside the wick 203 also starts to heat up and vaporise for dispersion to outside of the refill 2. Preferably the susceptor 204 should be in, or at least partially in, the wick 203. This way, the wick 203 thermally insulates the susceptor 204 from the remainder of the fluid in the reservoir 201, meaning the heat emanating from the susceptor 204 is largely contained within the wick 203, and is not transmitted to the fluid reservoir 201 surrounding the wick 203.

To control how much volatile fluid 202 is dispersed at any given time, the electronic circuitry 102 from the device 1, in particular the MCU, can control the amount of current flowing through the induction coil 103, and hence control the amount of heating occurring in the susceptor 204. The current flowing through the induction coil 103 can be varied for example by increasing the duty

- 12 -

cycle of the circuit, or by increasing the maximum current flowing through the induction coil 103. Such control can be either by external human input, for example by an end user via a switch or dial, or preferably by the MCU in response to an output from a feedback coil 104 provided in the electronic circuitry 102, as is discussed below.

5

If a feedback coil 104 is provided, when current is flowing through the induction coil 103, the feedback coil 104 will pick up the magnetic field being emitted from the induction coil 103. When a susceptor 204 contained in a refill 2 is inserted into this magnetic field, the magnetic field will become distorted, depending on the physical properties of the susceptor, and so the signal being
10 picked up from the feedback coil 104 will change. By electrically connecting the MCU to the feedback coil 104, the MCU can be configured to interpret the signal received from the feedback coil 104, and from this interpret what type or shape of susceptor 204 is positioned near the device 1, if any.

15 The feedback coil 104 can also be used as a power control means to prevent the susceptor 204 from getting too hot. As the susceptor heats up during operation, its effect on the magnetic field generated by the induction coil 103 changes. By electrically connecting the MCU to the feedback coil 104, the MCU can be configured to interpret the signal received from the feedback coil 104, and from this interpret the temperature of the susceptor 204. The MCU can then control the
20 amount of current being passed through the induction coil 103.

Another use for the output from the feedback coil 104 by the MCU is for monitoring the form of power being supplied by the electronic circuitry. By sampling the output signal from the feedback coil 104, the MCU can be configured to vary the properties of the electronic circuitry to ensure that
25 the alternating current being passed through the induction coil 103 is matched to the particular susceptor 204 in proximity with the induction coil 103.

If no MCU or feedback coil 104 is present in the electronics of the evaporation device, the device operates at a predetermined power level and operates in either an "on" or "off" state.
30

An example design of both the device 1 and refill 2 is shown in Figures 4A and 4B. The configuration of both the device 1 and refill 2 is largely dependent on the induction coil 103 being able to efficiently heat the susceptor 204, and if a feedback coil 104 is present, allowing this coil to interact with the magnetic fields generated by the induction coil 103. In the case of Figures 4A
35 and 4B, the induction coil 103 is tubular in shape and is located such that once the refill 2 is connected with the device 1, the susceptor 204 fits inside the induction coil 103. Although not shown in Figures 4A and 4B, where a feedback coil 104 is also present, this could be placed in a concentric type arrangement in or around the induction coil 103.

- 13 -

Although only one susceptor 204 is shown in Figures 4A and 4B, it could be that more than one susceptor 204 is used in the wick 203.

- 5 An alternative design to the evaporation device of Figures 4A and 4B is shown in Figures 5A – 5C. These figures show a design which uses a gel matrix wherein the reservoir 201' and fluid transport means 203' are integral with each other and wherein the gel may be supported by a lattice material (not shown) to impart mechanical strength thereto. As fluid in the gel matrix is evaporated adjacent to the susceptor 204, the remainder of the fluid in the reservoir 201' migrates
10 towards the susceptor 204

- Figures 6A – 6C show a further example of the evaporation device. In this embodiment, the refill 2 comprises a wick 203 which lines the inside of the pod shaped refill 2. The wick is saturated with volatile fluid 202, and is evaporated by localised heat from a susceptor 204 also located in the
15 wick 203 on one side of the pod. The refill 2 also comprises a cover 206 which can be perforated.

- The device 1 of the example shown in Figures 6A – 6C comprises tube like perforating elements 105 which are configured to pierce the cover 206 of the refill 2 during operation of the evaporation device. The induction coil 103 on the base element 1 is located to conform to the outer shape of
20 the refill 2.

- To operate the embodiment shown in Figure 6A – 6C, a user places the refill 2 into the device 1 such that the susceptor 204 therein can interact with the induction coil 103 of the device 1. To aid with placing the refill 2 in the correct orientation, an alignment feature (not shown) could be
25 provided on the refill 2 which locates with a corresponding feature on the device 1.

- The user then closes the lid of the device 1 to cause the perforating element 105 to pierce into the cover 206. The induction coil 103 then heats the susceptor 204 of the refill 2 as previously described, causing volatile fluid 202 in the wick 203 near the susceptor 204 to evaporate and flow
30 out through the perforating elements 105. As the volatile fluid 202 which is near the susceptor 204 evaporates, volatile fluid 202 which is located further away from the susceptor 204 is drawn towards it by capillary action as previously described.

- If the volatile fluid 202 in the embodiment of Figures 6A – 6C is in the form of a gel, then the wick
35 203 could be designed in the form of a lattice as described above in relation to Figures 5A – 5C, or designed in any other shape that will support the gel.

- 14 -

As an optional safety feature to the design as shown in Figures 6A – 6C, the perforating elements 105 may be configured to be made inaccessible when the device is not in use.

It will be appreciated that the designs shown in Figures 4A – 6C could be adapted to allow the accommodation of more than one refill 2. For example, extra ports could be provided on the device 1 to allow the connection of additional refills 2. Each port on the device 1 could be provided with its own induction coil 103 such that the fluid 202 contained in each refill 2 could be heated independently of the fluid contained in the other refills 2. Alternatively, all the refills 2 could be selectively heated by a single induction coil 103 located on the device 1, using conventional time switching circuitry. Irrespective of the number of induction coils 103 or number of refills 2 used, the principle of operation would be the same as previously described.

Ideally the material selected should be magnetic and should have a high hysteresis loss so that when it is repeatedly magnetised and demagnetised by an external magnetic field a relatively high proportion of the external field energy is converted into heat. The magnetic properties exhibited by such a magnetic material may be represented by a plot of flux density (B) against magnetic field strength (H) as shown in figure 7. Materials having relatively low hysteresis losses are typified by the solid hysteresis loop which has a small area whilst materials having relatively high hysteresis losses are typified by the dotted hysteresis loop which has a high area. The proportion of the external magnetic field energy that is converted into heat by the susceptor for each magnetic cycle is proportional to the area of the hysteresis loop corresponding to the particular magnetic material. Accordingly magnetic materials having small area hysteresis loops generate less heat when subjected to a given alternating magnetic field and function poorly as susceptor materials. Conversely magnetic materials having large area hysteresis loops generate more heat when subjected to the same alternating magnetic field and function well as susceptor materials. The area of the hysteresis loop of a magnetic material is proportional to its coercivity so that a material having a high coercivity may be particularly suitable for use as a susceptor. Preferably such a material should have a coercivity greater than 50 amperes per meter and more preferably a coercivity in the range of 150 – 1500 ampere per meter.

It is important in the application that the chosen material should not have an excessively high coercivity in order that external alternating magnetic fields may readily bring about the necessary magnetic flux reversals in the material. Such materials are known as magnetically soft materials and are distinguished thereby from the very high coercivity magnetically hard materials which are typically used in permanent magnet applications.

CLAIMS

1. An assembly for evaporating a volatile fluid, the assembly comprising a device and a refill which are detachable from one another;
5 wherein the device comprises a magnetic induction coil;
and wherein the refill comprises a reservoir for the volatile fluid, a volatile fluid transport means to draw the fluid from the reservoir, and at least one susceptor arranged to heat the volatile fluid transport means when said alternating current is passed through the induction coil.
- 10 2. An assembly according to claim 1, wherein the susceptor is provided in direct contact with the volatile fluid transport means.
3. An assembly according to claim 1 or claim 2, wherein susceptor is at least partially embedded within the volatile fluid transport means.
15
4. An assembly according to any preceding claim, wherein the susceptor surrounds a portion of the volatile fluid transport means.
5. An assembly according to any one of claims 1-3, wherein the susceptor is entirely
20 embedded within the volatile fluid transport means.
6. An assembly according to any preceding claim, wherein the susceptor is at least partially located inside the induction coil during the operation of the assembly.
- 25 7. An assembly according to any preceding claim, wherein the refill is provided with a single susceptor.
8. An assembly according to any one of claims 1-6, wherein the refill is provided with more than one susceptor.
30
9. An assembly according to any preceding claim, wherein the device further comprises a control unit to control the operation of the induction coil.
10. An assembly according to claim 9, wherein the device further comprises a feedback coil
35 configured to interact with a magnetic field generated by the induction coil.

11. An assembly according to claim 10, wherein the control unit is configured to process an output from the feedback coil and from this output vary one or more operating parameters of the induction coil.
- 5 12. An assembly according to claim 10 or claim 11, wherein the feedback coil is configured, in use, to change its output when a susceptor is within the magnetic field of the induction coil.
13. An assembly according to any one of claims 10-12, wherein the feedback coil is configured, in use, to change its output when one property of a susceptor is changed from refill to refill, wherein said changing property of the susceptor is one of: the shape; mass; material; or surface area.
- 10 14. An assembly according to claim 13, wherein the control unit is configured to interpret the change in output from the feedback coil to determine what type of refill is within the magnetic field of the induction coil, and from this, automatically vary a property of the induction coil to apply the appropriate heating regime to each particular refill.
- 15 15. An assembly according to claim 14, wherein the assembly is configured such that the feedback coil only has to change its output in response to a change of a single susceptor property from refill to refill, whereby refills for the assembly have three of the following susceptor properties fixed and one of the following susceptor properties variable for detection of this variance by the feedback coil, wherein said susceptor properties are: shape; mass; material and surface area.
- 20 16. An assembly according to any one of claims 11-15, wherein the control unit is configured to interpret the high temperature of the susceptor(s) from the output from the feedback coil changes and based on this output automatically vary a property of the induction coil to cool the susceptor.
- 25 17. An assembly according to any one of claims 11-16, wherein the control unit monitors the output of the feedback coil to alter the duty cycle to ensure the current supplied through the induction coil are optimised to the particular susceptor(s) in proximity with the induction coil.
- 30 18. An assembly according to any one of claims 9-17, wherein the control unit is operable to vary the current being passed through the induction coil by varying at least one of: the maximum amplitude; the frequency; the duty cycle.
- 35 19. An assembly according to any one of claims 9-18, wherein the device is provided with mechanical or electromechanical means that are operable by the control unit to physically move

the refill such that the susceptor is moved relative to the induced magnetic field of the induction coil.

20. An assembly according to any one of claims 9-18, wherein the device is provided with mechanical or electromechanical means that are operable by the control unit to physically move the induction coil within the device housing such that the induced magnetic field is moved relative to the susceptor in the refill.

21. An assembly according to any preceding claim, wherein the alternating current passed through the induction coil is set at a frequency greater than 100 KHz, and more preferably set at a frequency of 150KHz.

22. An assembly according to any preceding claim, wherein the device can accommodate more than one refill, each refill having their own volatile fluid transport means and susceptor.

23. An assembly according to claim 22, wherein the device has a single induction coil configured, in use, to induce a magnetic field surrounding a susceptor in each refill.

24. An assembly according to claim 22, wherein the device has more than one induction coil and each induction coil is associated with a separate refill whereby, in use, the induced magnetic field from one induction coil surrounds the susceptor(s) in only one refill.

25. An assembly according to any preceding claim, wherein the device further comprises an additional susceptor configured to heat an area around the induction coil.

26. An assembly as claimed in any preceding claim, wherein the susceptor(s) is magnetic.

27. An assembly according to claim 26, wherein the magnetic susceptor(s) is made from at least one of the following materials: cast iron (annealed); nickel; nickel-coated steel; cobalt; carbon steel (annealed) 1% C; constructional steel particularly (0.3% C, 1% Ni) and/or (0.4% C, 3% Ni, 1.5%Cr); cobalt-iron alloy (preferably Permendur 24 (24% Co) and/or Permendur 49 (49% Co)); Heusler alloy (61% Cu, 26% Mn, 13% Al); tool steel; powdered iron (preferably set in a resin base or the like); iron filings (preferably set in a resin base or the like).

28. An assembly according to claim 26 or claim 27, wherein the susceptor is made from a material with a stable Curie temperature, preferably less than 150°C.

1/7




Fig. 1




Fig. 2






Fig. 3

4/7



5/7




Fig. 5A




Fig. 5B




Fig. 5C




Fig. 6B




Fig. 6C





Fig. 6A

7/7

*Fig. 7*