

(86) **Date de dépôt PCT/PCT Filing Date:** 2011/04/26
(87) **Date publication PCT/PCT Publication Date:** 2011/11/03
(45) **Date de délivrance/Issue Date:** 2020/03/10
(85) **Entrée phase nationale/National Entry:** 2012/10/26
(86) **N° demande PCT/PCT Application No.:** US 2011/033969
(87) **N° publication PCT/PCT Publication No.:** 2011/137124
(30) **Priorité/Priority:** 2010/04/26 (US61/328,010)

(51) **Cl.Int./Int.Cl. A61M 15/00** (2006.01),
A61M 16/00 (2006.01), **A61M 16/10** (2006.01)


(72) **Inventeurs/Inventors:**
FINE, DAVID H., US;
VASQUEZ, GREGORY, US;
JOHNSON, BRYAN, US;
DENTON, RYAN, US;
GAMERO, LUCAS G., US

(73) **Propriétaire/Owner:**
VERO BIOTECH LLC.

(74) **Agent:** BORDEN LADNER GERVAIS LLP

(54) Titre : ADMINISTRATION DE MONOXYDE D'AZOTE (NO) ULTRA PUR

(54) **Title:** DELIVERY OF ULTRA PURE NITRIC OXIDE (NO)



(57) Abrégé/Abstract:

A system for delivering a therapeutic amount of nitric oxide can include reservoir assembly, a gas supply, and a delivery conduit including a first cartridge wherein the first cartridge can include a surface-activated material saturated with aqueous solution of a reducing agent.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
3 November 2011 (03.11.2011)(10) International Publication Number
WO 2011/137124 A1

(51) International Patent Classification:

A61M 15/00 (2006.01) *A61M 16/00* (2006.01)
A61M 16/10 (2006.01) *A62B 7/00* (2006.01)

(21) International Application Number:

PCT/US2011/033969

(22) International Filing Date:

26 April 2011 (26.04.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/328,010 26 April 2010 (26.04.2010) US

(71) Applicant (for all designated States except US): **GENO LLC** [US/US]; 2941 Oxbow Circle, Cocoa, FL 32926 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **FINE, David, H.** [US/US]; P.O. Box 321610, Cocoa Beach, FL 32932 (US). **VASQUEZ, Gregory** [US/US]; 105 Forest Avenue, PMB 451, Cocoa, FL 32922 (US). **JOHNSON, Bryan** [US/US]; 480 Sail Lane, Apartment # 201, Merritt Island, FL 32953 (US). **DENTON, Ryan** [US/US]; 146 Beverly Street, Titusville, FL 32780 (US). **GAMERO,****Lucas, G.** [AR/US]; 346 Lakepark Trail, Oviedo, FL 32765 (US).(74) Agents: **FOX, Harold, H.** et al.; Steptoe & Johnson LLP, 1330 Connecticut Avenue, NW, Washington, DC 20036 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: DELIVERY OF ULTRA PURE NITRIC OXIDE (NO)




FIGURE 10

(57) Abstract: A system for delivering a therapeutic amount of nitric oxide can include reservoir assembly, a gas supply, and a delivery conduit including a first cartridge wherein the first cartridge can include a surface-activated material saturated with aqueous solution of a reducing agent.

WO 2011/137124 A1

Published:

— *with international search report (Art. 21(3))*

DELIVERY OF ULTRA PURE NITRIC OXIDE (NO)

TECHNICAL FIELD

[0002] This description relates to a systems and methods for the delivery of ultra
5 pure nitric oxide.

BACKGROUND

[0003] Nitric oxide (NO), also known as nitrosyl radical, is a free radical that is an important signalling molecule. For example, NO can cause smooth muscles in blood vessels to relax, thereby resulting in vasodilation and increased blood flow through the
10 blood vessel. These effects can be limited to small biological regions since NO can be highly reactive with a lifetime of a few seconds and can be quickly metabolized in the body.

[0004] Some disorders or physiological conditions can be mediated by inhalation of nitric oxide. The use of low concentrations of inhaled nitric oxide can prevent, reverse,
15 or limit the progression of disorders which can include, but are not limited to, acute pulmonary vasoconstriction, traumatic injury, aspiration or inhalation injury, fat embolism in the lung, acidosis, inflammation of the lung, adult respiratory distress syndrome, acute pulmonary edema, acute mountain sickness, post cardiac surgery acute pulmonary hypertension, persistent pulmonary hypertension of a newborn, perinatal
20 aspiration syndrome, haline membrane disease, acute pulmonary thromboembolism, heparin-protamine reactions, sepsis, asthma and status asthmaticus or hypoxia. Nitric oxide can also be used to treat chronic pulmonary hypertension, bronchopulmonary dysplasia, chronic pulmonary thromboembolism and idiopathic or primary pulmonary hypertension or chronic hypoxia.

[0005] Generally, nitric oxide can be inhaled or otherwise delivered to the
25 individual's lungs. Providing a therapeutic dose of NO could treat a patient suffering from a disorder or physiological condition that can be mediated by inhalation of NO or supplement or minimize the need for traditional treatments in such disorders or physiological conditions. Typically, the NO gas can be supplied in a bottled gaseous

form diluted in nitrogen gas (N_2). Great care should be taken to prevent the presence of even trace amounts of oxygen (O_2) in the tank of NO gas because the NO, in the presence of O_2 , can be oxidized to nitrogen dioxide (NO_2). Unlike NO, the part per million levels of NO_2 gas can be highly toxic if inhaled and can form nitric and nitrous acid in the lungs.

5

SUMMARY

[0006] In one aspect, a system for delivering a therapeutic amount of nitric oxide can include a reservoir, a gas supply and a delivery conduit. A reservoir can be configured to include a nitrogen dioxide source. A delivery conduit can include at least one cartridge. The at least one cartridge can include a surface-activated material and a reducing agent.

10 [0007] In another aspect, a reservoir assembly include a reservoir a restrictor.

[0008] In another aspect, a method of delivering nitric oxide can include releasing nitrogen dioxide from a reservoir into a delivery conduit via a restrictor, passing a gas from a gas supply into the delivery conduit which can allow the gas from the gas supply and the nitrogen dioxide to mix in the delivery conduit, passing the gas and nitrogen
15 dioxide mixture through at least one cartridge, and delivering nitric oxide from an outlet of the delivery conduit.

[0009] In another aspect, a method of manufacturing a reservoir assembly for delivering nitric oxide can include coupling a restrictor to the reservoir, sealing a second end of the restrictor. The method can also include filling a reservoir with a source of
20 nitrogen dioxide. Filling a reservoir can include filling a portion of the reservoir with a source of nitrogen dioxide. The method can further include inserting the restrictor into a metal tube that can be coupled to the reservoir via an adaptor, holding the restrictor place by graphite ferrules, heat sealing the restrictor, and/or testing the restrictor and/or assembly with a helium flow. The testing can be used to check for leaks prior to filling
25 with liquid N_2O_4 .

[0010] In some embodiments, a reservoir can include a nitrogen dioxide source. In some embodiments, the nitrogen dioxide source is dinitrogen tetroxide, more specifically, liquid dinitrogen tetroxide. The amount of liquid N_2O_4 in the reservoir can be less than about 5.0 g, less than about 2.0 g, less than about 1.0 g, less than about 0.50 g, less than
30 0.25 g or less than 0.10 g; the amount of liquid N_2O_4 in the reservoir can be greater than about 0.05 g, greater than about 0.10 g, greater than about 0.20 g, greater than about 0.50 g or greater than about 1.0 g. The amount of liquid N_2O_4 in the reservoir can be less than

about 5 ml, less than about 2 ml, less than about 1 ml, less than about 0.5 ml, less than about 0.25 ml or less than about 0.10 ml; the amount of liquid N₂O₄ in the reservoir can be greater than about 0.001 ml, greater than about 0.01 ml, greater than about 0.05, greater than about 0.10 ml, greater than about 0.25ml, greater than about 0.50 ml or
5 greater than about 1.0 ml.

[0011] In some embodiments, the reservoir can include a restrictor. In some cases, the restrictor can be coupled to the reservoir.

[0012] In some embodiments, a reservoir can also include nitrogen dioxide vapor or nitrogen dioxide gas in a space over the nitrogen dioxide source.

10 [0013] In some embodiments, a reservoir can be less than 6 inches, less than 4 inches, less than 3 inches, less than 2 inches, less than 1 inch, less than 0.5 inch in height. A reservoir can also be less than 4 inches, less than 2 inches, less than 1 inch, less than 0.75 inch or less than 0.5 inch in internal diameter.

[0014] In some embodiments, a restrictor can include an orifice.

15 [0015] In some embodiments, a restrictor can include a first end and a second end. In some embodiments, the first end of the restrictor can be coupled to a reservoir. In some embodiments, the second end can be sealed or closed. In some embodiments, the second end, which was previously sealed or closed, can be opened, unsealed or include a broken seal. In some embodiments, the second end of the restrictor can also be coupled to the
20 delivery conduit. In some embodiments, the delivery conduit can include a device for opening the second end or breaking the seal on the second end.

[0016] In some embodiments, a restrictor can further include a length corresponding to the distance between the first end and the second end. In some cases, the second end of the restrictor is coupled to the delivery conduit such that the delivery conduit traverses in
25 a direction perpendicular to the length of the restrictor.

[0017] In some embodiments, the restrictor can include a tube. In some embodiments, the tube can be a capillary tube, more specifically, a quartz capillary tube. In some embodiments, the length of the restrictor can be at least about 0.1 inch, at least about 0.25 inch or at least about 0.5 inch; the length can be at most about 4 inches, at
30 most about 2 inches, at most about 1 inch, or at most about 0.5 inch. Preferably, the restrictor can have a length of about 0.75 inch. In some embodiments, the internal diameter of the restrictor can be at least about 0.001, at least about 0.005 microns or at least about 0.010; the internal diameter can be at most about 0.100 microns, at most about

0.050 microns, at most about 0.025 microns, or at most about 0.010 microns. Preferably, the restrictor can have a diameter of about 0.010 microns.

[0018] In some embodiments, the gas supply can supply air, oxygen or nitrogen. In some circumstances, the gas supply can be an air supply, more specifically, an air pump.

5 The air pump can be battery powered. The gas supplied by the gas supply can be moist or dry. In some embodiments, the gas supply can be in fluid communication with the delivery conduit.

[0019] In some embodiments, the delivery conduit can have an inlet coupled to the gas source. In some embodiments, the delivery conduit can also include an outlet. In
10 some circumstances, the delivery conduit can include an outlet coupled to the patient interface. A patient interface can include a mouth piece, nasal cannula, face mask, or fully-sealed face mask.

[0020] In some embodiments, a cartridge can include a surface-activated material and a reducing agent. In some cases, the surface-activated material can be saturated with an
15 aqueous solution of a reducing agent. Any appropriate reducing agent that can convert NO_2 or N_2O_4 to NO can be used as determined by a person of skill in the art. For example, the reducing agent can include a hydroquinone, glutathione, and/or one or more reduced metal salts such as Fe(II) , Mo(VI) , NaI , Ti(III) or Cr(III) , thiols, or NO_2^- . The reducing agent can be an antioxidant. The antioxidant can be an aqueous solution of an
20 antioxidant. The antioxidant can be ascorbic acid, alpha tocopherol, or gamma tocopherol. Any appropriate antioxidant can be used depending on the activities and properties as determined by a person of skill in the art. The antioxidant can be used dry or wet.

[0021] In some circumstances, the cartridge can also include an inlet and an outlet.
25 The inlet can be configured to receive a gas flow that can include nitrogen dioxide and can fluidly communicate the gas flow to the outlet through the surface-active material, such that the surface-active material can react with nitrogen dioxide in the gas flow and can convert the nitrogen dioxide to nitric oxide.

[0022] In some embodiments, the delivery conduit further can include a second
30 cartridge. The second cartridge can include a surface-activated material and a reducing agent. In some circumstances, the cartridge can also include an inlet and an outlet. The inlet can be configured to receive a gas flow that can include nitrogen dioxide and can fluidly communicate the gas flow to the outlet through the surface-active material, such

that the surface-active material can react with nitrogen dioxide in the gas flow and can convert the nitrogen dioxide to nitric oxide.

[0023] In some embodiments, the system can include a disposable module and a base unit. In some embodiments, the disposable module can include the reservoir, the
5 restrictor and the first cartridge. In some embodiments, the system can include a base unit, where the base unit can include a gas supply. In some embodiments, the base unit can include batteries, sensors and/or alarm electronics. In some embodiments, the base unit is reusable. In some embodiments, the disposable module can be attached to the base unit for delivery nitric oxide. In some circumstances, the disposable module is
10 configured to be used or attached to the base unit only once.

[0024] In some embodiments, the method can further include comprising attaching a disposable module including a reservoir, a restrictor and a first cartridge to a base unit. The base unit can include the gas supply. The base unit can also include batteries, sensors and/or alarm electronics.

15 [0025] In some embodiments, a system can be portable. In some embodiments, a portable system can include a belt hook, belt, shoulder strap or other device for attaching a portable system to a person.

[0026] In some embodiments, the system can weigh less than 64 ounces, less than 32 ounces or less than 16 ounces. In some embodiments, the system can be less than 2 feet,
20 less than 1.5 feet, less than 1 foot in height; the system can be less than 2 feet, less than 1.5 feet, less than 1 foot, less than 9 inches or less than 6 inches in width; and/or the system can be less than 6 inches, less than 4 inches, less than 3 inches or less than 2 inches in depth.

[0027] In some embodiments, a reservoir assembly can be less than 1 foot, less than 6
25 inches, less than 5 inches, less than 4 inches, less than 3 inches or less than 2 inches in height and/or less than 1 inch, less than 0.75 inch or less than 0.5 inch in diameter.

[0028] In some embodiments, the system can further include a nitric oxide sensor, a nitrogen dioxide sensor, a flow sensor, a pressure sensor, a sensor for atmospheric pressure, and/or a microbial filter.

30 [0029] In some embodiments, a system can further include a heating element. A heating element can include a hot water bath, a heating mantle, heating wire or heating well. A heating element can include a simple flexible circuit board with the wires etched

onto the surface. In some cases, a device including a thermistor can be built into the circuit for measuring and controlling the temperature.

[0030] In some embodiments, the system can operate at a temperature of at least about 25 °C, at least about 30 °C, at least about 35 °C, at least about 40 °C, at least about 45 °C or at least about 50 °C; the system can operate at a temperature of at most about 200 °C, at most about 150 °C, at most about 100 °C, or at most about 75 °C. The optimum temperature range can be about 45 to 75 °C.

[0031] In some embodiments, a method of delivering nitric oxide can include breaking the seal on or opening an end of the restrictor. Breaking the seal on or opening an end of the restrictor can allow nitrogen dioxide to traverse the length of the restrictor and out the previously closed or sealed end of the restrictor.

[0032] In some embodiments, a method of delivering nitric oxide can include heating a reservoir and/or restrictor to a temperature at least about 25 °C, at least about 30 °C, at least about 35 °C, at least about 40 °C, at least about 45 °C or at least about 50 °C; a method of delivering nitric oxide can include heating a reservoir and/or restrictor to a temperature at most about 200 °C, at most about 150 °C, at most about 100 °C, or at most about 75 °C. The optimum temperature range can be about 45 to 75 °C. In some embodiments, releasing nitrogen dioxide from a reservoir into a restrictor and then into a delivery conduit can include heating a reservoir and/or restrictor. In some embodiments, heating a reservoir and/or restrictor can heat nitrogen dioxide in the reservoir, increasing the vapor pressure and releasing the nitrogen dioxide from releasing nitrogen dioxide from a reservoir into a restrictor and then into a delivery conduit.

[0033] In some embodiments, a reservoir assembly can include a heating element, which can reach and maintain a temperature of at least about 25 °C, at least about 30 °C, at least about 35 °C, at least about 40 °C, at least about 45 °C or at least about 50 °C; a reservoir assembly can include a heating element, which can reach and maintain a temperature of at most about 200 °C, at most about 150 °C, at most about 100 °C, or at most about 75 °C. The optimum temperature range can be about 45 to 75 °C. In some embodiments, a method of manufacturing a reservoir assembly can include attaching a heating element, where the heating element can reach and maintain the temperatures discussed above.

BRIEF DESCRIPTION OF THE DRAWINGS

- [0034] FIG. 1 is a diagram of a gas bottle platform.
- [0035] FIG. 2 is a diagram of a cartridge.
- [0036] FIG. 3 includes a diagram of a cartridge and a cut-away diagram of a
 5 cartridge.
- [0037] FIG. 4 is a diagram of a cap of a cartridge.
- [0038] FIG. 5 is a diagram of a system for delivering nitric oxide.
- [0039] FIG. 6 is a diagram of a system for delivering nitric oxide.
- [0040] FIG. 7 is an illustration of a reservoir assembly.
- 10 [0041] FIG. 8 includes a cut-away of a reservoir assembly and a perspective illustration of a reservoir assembly.
- [0042] FIG. 9 is an illustration of a reservoir assembly.
- [0043] FIG. 10 is a picture of a metal tube.
- [0044] FIG. 11 is diagram of a circuit board.
- 15 [0045] FIG. 12 is a diagram of a system including a disposable module.
- [0046] FIG. 13 includes perspective drawings of a system including perspective drawings of a disposable module and a base unit.
- [0047] FIG. 14 is a picture of a system in use.
- [0048] FIG. 15 is a graph of performance data.
- 20 [0049] FIG. 16 is a graph of ppm NO, NO₂ and NO + NO₂ versus time.
- [0050] FIG. 17 is a graph of stability of output versus time.
- [0051] FIG. 18 is a graph of NO and NO₂ output over a period of time.

DETAILED DESCRIPTION

- 25 [0052] When delivering nitric oxide (NO) for therapeutic use to a mammal, it can be important to avoid delivery of nitrogen dioxide (NO₂) to the mammal. Nitrogen dioxide (NO₂) can be formed by the oxidation of nitric oxide (NO) with oxygen (O₂). The rate of formation of nitrogen dioxide (NO₂) can be proportional to the oxygen (O₂) concentration multiplied by the square of the nitric oxide (NO) concentration – that is, (O₂) *
 30 (NO)*(NO) = NO₂. A NO delivery system can convert nitrogen dioxide (NO₂) to nitric oxide (NO).
- [0053] Platforms for delivering nitric oxide currently exist. For example, a platform can be a standalone gas bottle platform, as shown in FIG. 1. A gas bottle platform 100

can include a gas bottle 105, a gas regulator 110 and a GeNO cartridge 115, for example. Using a gas bottle platform, the NO output can be defined by the nitrogen dioxide concentration in the gas bottle and cannot be varied by the user. For example, if the gas bottle contained 80 ppm of NO₂ in air or oxygen, then the output can be 80 ppm of NO₂ in air or oxygen. The gas can be supplied, typically, at a pressure of 2000 psi or greater. The output from the gas cylinder can be delivered to a GeNO cartridge, where one of the O atoms in the NO₂ is stripped out by a reducing agent, for example, ascorbic acid, to generate ultra pure NO. The GeNO cartridge is described in U.S. Patent Application Nos. 12/541,144 and 12/951,811. This platform has been cleared by FDA for use in two clinical trials with human patients. A gas bottle platform can work well, but can be large, heavy and cumbersome because the platform can include a heavy aluminum or steel gas pressure cylinder, a gas regulator and a flow controller.

[0054] Another variation for delivering NO can be to start with a NO₂ gas concentration of up to 2,000 ppm in air or oxygen and dilute it down to 80 ppm of NO₂. This set up can be even more complex in that it can require precision mass flow controllers and meters in order to get a stable mixing ratio.

[0055] As mentioned above, the disadvantage of the gas bottle platform can be that the platform can be large and heavy. The platform can also be inconvenient to use for chronic treatment as an ambulatory platform. Gas bottles can also be cumbersome when used in a confined space such as in an Intensive Care Unit, in a hospital or in a home. In addition, the gas bottles need to be tied down to prevent them from falling over and causing physical injury. Also, the regulator can break off in a fall, and the sudden venting of gas through the opening can cause the heavy bottle to become a projectile, which can penetrate numerous walls and cause injury or death.

[0056] Examples of commercially available platforms are manufactured by Ikaria, two of which are the INOvent and the INOmax DS. Both of these systems use gas bottles of NO diluted in nitrogen (N₂), which is then mixed with oxygen enriched air to provide the inhaled NO gas. Both of these systems are designed to work with a ventilator in an intensive care setting in a hospital. These platforms are not suitable for ambulatory or home use.

[0057] Therefore, there is a need for a nitric oxide delivery platform, which can be used in settings where a large, heavy bottle platform is inconvenient, such as an ambulatory or home setting.

[0058] As one solution, a system can include a permeation tube or permeation cell to provide the source of NO₂. For example, the NO₂ source can be liquid dinitrogen tetroxide (N₂O₄). This approach has been shown to work well. This approach has been described in U.S. Patent Application No. 12/563,662. N₂O₄ can vaporize to produce NO₂, and the process can be reversible. Using a permeation tube, air can be allowed to flow around the permeation tube, where it can mix with the NO₂ that diffuses through the tube, providing a stable mixture of NO₂ in air. The concentration of the NO₂ can be controlled by a number of factors including, for example, the temperature of the tube and the volume of the air flow. However, storing a permeation tube can be a problem. For instance, if NO₂ is in contact with the permeation tube polymer, the storage should be below -11 °C in order to keep the NO₂ frozen, which can prevent loss of NO₂. One solution is to build a separate storage chamber for the permeation tube, which can be connected to the storage tube by a simple valve. This device can be stored at room temperature without loss of NO₂, and it can easily be activated by connecting the reservoir to the permeation tube. The combined storage vessel and permeation tube can work well, but it can have one major disadvantage. Stabilization of a permeation tube can take a long time when the NO₂ is stored in a reservoir and then suddenly opened to the permeation tube. The time to stabilize can be several days. Pre-saturating the permeation tube with NO₂ first can speed up the stabilization, but this may not work well with long term storage of months or years.

[0059] As another solution, a reservoir assembly can be utilized. A reservoir assembly can include a restrictor and a reservoir.

[0060] A reservoir can be any compartment or portion of a compartment suitable for holding N₂O₄, NO₂ or NO, or other compounds which can generate N₂O₄, NO₂ or NO. The reservoir can hold a liquid or a solid, but preferably the reservoir can hold liquid N₂O₄. The reservoir can be made of any material, which does not react with or adsorb N₂O₄, NO₂ or NO, or other compounds which can generate N₂O₄, NO₂ or NO. The material should also be able to tolerate heat within the appropriate range, discussed below, and repeated heating and cooling.

[0061] A reservoir can include a nitrogen dioxide source. A nitrogen dioxide source can include N_2O_4 , NO_2 , or compounds which can generate NO_2 . Preferably, the nitrogen dioxide source can contain liquid N_2O_4 . In the case of liquid N_2O_4 , the amount of liquid N_2O_4 in the reservoir can be less than about 5.0 g, less than about 2.0 g, less than about 1.0 g, less than about 0.50 g, less than 0.25 g or less than 0.10 g; the amount of liquid N_2O_4 in the reservoir can be greater than about 0.05 g, greater than about 0.10 g, greater than about 0.20 g, greater than about 0.50 g or greater than about 1.0 g. The amount of liquid N_2O_4 in the reservoir can be less than about 5 ml, less than about 2 ml, less than about 1 ml, less than about 0.5 ml, less than about 0.25 ml or less than about 0.10 ml; amount of liquid N_2O_4 in the reservoir can be greater than about 0.001 ml, greater than about 0.01 ml, greater than about 0.05, greater than about 0.10 ml, greater than about 0.25ml, greater than about 0.50 ml or greater than about 1.0 ml.

[0062] In one exemplary embodiment, liquid N_2O_4 can be stored in a small reservoir. For a delivery concentration of 80 parts per million in 1 liter of air per minute, for example, the amount of N_2O_4 needed for a 24 hour supply can be approximately 0.24 g, or 0.15 ml. N_2O_4 boils at 21 °C, so the device should be heated to above this temperature in order to have a vapor pressure of NO_2 that is greater than atmospheric pressure. Further description may be found in U.S. Provisional Application Nos. 61/263,332 and 61/300,425.

[0063] A reservoir can also include nitrogen dioxide vapor or gas in a space over the nitrogen dioxide source.

[0064] A reservoir can be any size. The size of the reservoir can depend on how the reservoir will be used. It can also be dependent on the amount of the nitrogen dioxide source, the amount of nitrogen dioxide gas required, or the length of the time over which a flow of nitrogen dioxide would be required. A reservoir can be relatively large, for example, greater than 1 foot, greater than 2 feet, greater than 5 feet, or greater than 8 feet in height (h_3 , FIG.2). A reservoir can also be relatively small, for example, less than 2 feet, less than 1 foot, less than 6 inches, less than 4 inches, less than 3 inches, less than 2 inches, less than 1 inch, less than 0.5 inch in height (h_3 , FIG.2). An assembly can have a size that can accommodate a reservoir and/or additional elements, such as a restrictor. An assembly can be relatively

small, for example, less than 4 inches, less than 2 inches, less than 1 inch, less than 0.75 inch or less than 0.5 inch in internal diameter (d_3 , FIG. 2).

[0065] A restrictor can be any device which can limit the flow of NO_2 from the reservoir. A restrictor can require that there be enough vapour pressure to force the NO_2 vapor out of the reservoir and into the restrictor.

[0066] The reservoir can include the restrictor. For example, the restrictor can be an orifice. The restrictor can be coupled to the reservoir. For example, the restrictor can include a tube, most preferably, a capillary tube. The capillary tube can be a quartz capillary tube. The capillary tube can be a narrow bore capillary tube, which can allow for simple, reproducible and accurate use, as well as a cost effective solution. A convenient commercially available restrictor can be a narrow bore quartz tubing that can be used for gas chromatography (GC).

[0067] A restrictor can include a first end and a second end. In some embodiments, the first end of the restrictor can be coupled to a reservoir and the second end can be sealed or closed. In some embodiments, the second end, which was previously sealed or closed, can be opened, unsealed or include a broken seal. In some embodiments, a restrictor can further include a length corresponding to the distance between the first end and the second end.

[0068] A restrictor can have any dimension, so long as the total pressure drop across the restrictor can be appropriate for the flow of NO_2 that is required. In some embodiments, the length of the restrictor can be relatively long, for example, greater than 4 inches, greater than 6 inches, greater than 1 foot, greater than 2 feet, greater than 5 feet, greater than 10 feet or greater than 20 feet long. In some embodiments, a restrictor can be relatively short, for example, at least about 0.1 inch, at least about 0.25 inch or at least about 0.5 inch; the length can be at most about 4 inches, at most about 2 inches, at most about 1 inch, or at most about 0.5 inch. Preferably, the restrictor can have a length of about 0.75 inch. In some embodiments, the internal diameter of the restrictor can be relatively large, for example, greater than about 0.100 microns, greater than about 1 microns, greater than about 5 microns, greater than about 10 microns, greater than about 50 microns or greater than about 100 microns. In some embodiments, the internal diameter of the restrictor can be relatively small, for example, at least about 0.001, at least about 0.005 microns or at least about 0.010; the internal diameter can be at most about 0.100 microns, at most about 0.050 microns, at most about 0.025 microns, or at most

about 0.010 microns. Preferably, the restrictor can have a diameter of about 0.010 microns.

[0069] The amount of material (e.g. nitrogen dioxide) that is forced out of the reservoir at any temperature can be dependent upon the diameter of the restriction. Thus, the two key design variables can be the temperature of the vessel and the diameter and length of the restriction in the top of the vessel. For example, at about 45 °C a tube of 0.010 microns internal diameter and 0.75 inches long was used to provide 80 ppm of NO₂ in an air stream of 1 l/min.

[0070] The restrictor can be made of other materials known to those of skill in the art.

10 The material should not react with or adsorb N₂O₄, NO₂ or NO, or other compounds which can generate N₂O₄, NO₂ or NO. The material should also be able to tolerate heat within the appropriate range, discussed below, and repeated heating and cooling.

[0071] A restrictor can be sealed. For example, if the restrictor is made of quartz or glass, one end of the restrictor can be heat sealed or melted to close off the opening on that end of the restrictor. The sealed end of the restrictor can be opened by breaking off the end, which can permit a channel in the restrictor to be fully opened. The restrictor can be bevelled or scored to allow for an easier and cleaner break. A restrictor can also be sealed with a metal seal. A metal seal can be melted, punctured, peeled off or otherwise removed to open the sealed end (i.e. break the seal). A restrictor can include a valve, for example, a micromachined valve. Other suitable seals and methods for controlling or preventing flow are known to those of skill in the art. Once the sealed or closed end is opened, nitrogen dioxide can traverse the length of the restrictor and out the previously closed or sealed end.

[0072] A reservoir assembly including a reservoir and a capillary can be less than 1 foot, less than 6 inches, less than 5 inches, less than 4 inches, less than 3 inches or less than 2 inches in height (h_1 , FIG.2). In an exemplary embodiment, the assembly can be approximately 1.6 inches in height. An assembly can also be less than 1 inch, less than 0.75 inch or less than 0.5 inch in diameter (d_1 , FIG. 2). In an exemplary embodiment, the assembly can be approximately 0.4 inch (e.g. 0.43 inch) in diameter.

30 [0073] Referring to FIG. 3, in one embodiment of a reservoir assembly, a restrictor can be a capillary 320, which can be about 1-inch x 10 um internal diameter (TSP010375 Flexible Fused Silica Capillary Tubing Polymicro Technologies). The capillary 320 can be inserted through a metal (303 S.S.) tube 345 made up of two GC nuts 340 and 350

- (1/16" Stainless Steel Nut Valco P/N ZN1-10) connected via their tops to a metal tube 345. Two graphite ferrules 355 (Graphite Ferrules P/N 20227 1/16" X 0.4mm Restek) with their flat ends touching can be placed on one end of the capillary 320, which has the polyamide coating 305 removed below the ferrules 355 (e.g., by burning off the
- 5 polyamide with a flame). The ferrules 355 can hold the capillary 320 securely when the nut 340 is inserted into a separate female end of an adaptor 315, which can be itself inserted into the metal (303 S.S.) reservoir container 310. The adaptor 315 can have a metal sheath 345 on the reservoir end that can cover and protect the area of the capillary without polyamide.
- 10 [0074] The end of the capillary 330 opposite the reservoir adaptor can be flame sealed and scored. The sealed capillary can be tested with a helium flow to assure that the assembly is appropriately sealed and does not leak. The reservoir 310 can be filled with liquid $\text{NO}_2/\text{N}_2\text{O}_4$ by distillation or other means. The capillary 320 is attached to the reservoir by means of a 1/8 inch pipe thread and sealed. The reservoir assembly can be
- 15 heated and checked to assure that there are no NO_2 leaks.
- [0075] The entire liquid reservoir assembly can be heated. Methods for heating the assembly can include: 1) a hot water bath, 2) a heating mantle that straps onto the tubes, insulating the outside of the metal tubing with urethane or another insulator such as paint, and wrapping Kanthal heating wire around the device, and/or 3) using silver paint to paint
- 20 the heating element onto top of the insulating paint.
- [0076] The reservoir assembly 300 can then be attached to the delivery conduit by inserting the sealed end of the capillary 330 with two ferrules 335 (Graphite Ferrules P/N 20227 1/16" X 0.4mm Restek) with their flat ends touching and screwing the exposed GC nut 340 of the reservoir assembly into the delivery conduit.
- 25 [0077] The sealed end of the capillary 330 can be inserted into an off-center hole of the internal delivery seal. When ready to use, the internal delivery seal can be rotated to open the reservoir port to the system flow path, which can break the capillary at its scored end 325, thus opening the reservoir to the system flow path and starting the flow of NO_2 .
- [0078] An advantage of having the capillary tube inside the reservoir and protected by
- 30 the tubing can be that the toxic N_2O_4 can only escape through the narrow bore quartz tube. In order for any material to escape the heater has to be turned on to provide the driving force. The tiny liquid reservoir assembly (FIG. 2), which can measure, for example, about 1.6 inch in height and 0.43 inches in diameter, can replace a large

pressurized gas cylinder, the gas regulator and the gas control valve. The size can be similar to that of a cap for a ball point pen.

[0079] The assembly can be kept the N_2O_4 frozen solid at dry ice temperatures. However, while this is suitable for laboratory use, it may be impractical as a safe medical
5 delivery device for use with a patient.

[0080] FIG. 4 includes an alternative embodiment. The can include a reduced number of parts, but the overall concept can remain the same. This embodiment can be less expensive to produce. The size and shape of the vessel 400 can be such that the liquid 410 can never enter the restrictor 420, e.g. capillary tube. In FIG. 4, the vessel 400 is on
10 its side, and the liquid level 410 can remain below the level where it could enter the restrictor 420. Similarly, the vessel 400 can be inverted and it can still function. The restrictor 420 can be protected by a wider bore splash guard. A baffle (not shown) can also be placed in front of the restrictor 420 so as to eliminate the possibility of a minute droplet entering the restrictor 420.

[0081] In another embodiment, methods that are used to seal carbon dioxide in metal tubes for a wide variety of commercial and consumer applications can be used (FIG. 5). The liquid NO_2 can be sealed inside a steel or aluminum canister, similar to those used for carbon dioxide (see Leland corporation). These devices can have a welded cap made of a thin sheet of steel. The welding can be carried out by resistance heating or other
20 techniques. The advantage of this system can be that the liquid can be sealed inside the container and the containers can be safely shipped. For this application, the volume of the nitrogen dioxide source should be less than 5 ml, less than 2 ml, preferably less than 1 ml. Alternatively, a crimp seal could be used as long as the seal could take the internal pressure of about 100 psi without leaking. The material can be aluminum or stainless
25 steel.

[0082] The loading and cap penetration technique can be identical to what is used for carbon dioxide pellet guns and for the multitude of other uses of these tiny high pressure cylinders.

[0083] In one aspect, a system for delivering nitric oxide can include a reservoir, a gas supply and a delivery conduit. A system can further include a restrictor. A reservoir and a restrictor have been described above. In some embodiments, a system can include a
30 reservoir and a restrictor, which are part of a reservoir assembly.

[0084] A gas supply can be any suitable source of gas, for example air, oxygen or nitrogen. A preferred gas supply is an air supply, for example, an air pump. For the ambulatory platform an air stream can be provided by a small air pump. An air compressor, an external supply of air or oxygen gas from gas bottles can also be used, including oxygen enriched air for a home oxygen generator. The use of air or oxygen, wet or bone dry, may make no difference to performance, as measured by a constant output over time. However, moist air greatly can extend the life of the reducing agent cartridge (e.g. ascorbic acid cartridge) that the NO₂ gas will be passed through to generate the drug, nitric oxide. Nevertheless, the platform can be designed for the worst case, which is bone dry air or oxygen.

[0085] The system can further include a delivery conduit. A delivery conduit can include a NO sensor, a NO₂ sensor, or a temperature sensor. A NO sensor can include a chemiluminescent detector or an electrochemical sensor. A NO₂ sensor can include a chemiluminescent detector or an electrochemical sensor. A temperature sensor can include a thermistor or a thermometer. In some instances, the system can include a pressure sensor or a flow sensor. A delivery conduit can also include other medically relevant devices, for example, a filter for eliminating microorganisms prior to inhalation of NO by a patient. It should also be understood that a delivery conduit can include additional hardware, such as tubing and valves, necessary to fluidly communicate gas (e.g. NO₂, NO, air, oxygen, nitrogen, etc.) from one element of the system to another.

[0086] The delivery conduit can have an inlet, which can be coupled to the gas source. The delivery conduit can also include an outlet, which can be couple to a patient interface. A patient interface can include a mouth piece, nasal cannula, face mask, or fully-sealed face mask.

[0087] If the patient required the co-delivery of oxygen, the air feed can be replaced with oxygen, or a dual lumen cannula can flow both the NO in air and oxygen down parallel lumens to the patient, mixing the NO in air line and the oxygen in the nose.

[0088] It is also well within the capability of the technology to add an oxygen conserver to the NO output, thereby extending the life time of the disposable component.

[0089] The second end of a restrictor can also be coupled to the delivery conduit. The second end of a restrictor can be coupled to the delivery conduit at a location between the inlet and the outlet of the delivery conduit. A restrictor can further include a length corresponding to the distance between the first end and the second end. In some cases,

the second end of the restrictor is coupled to the delivery conduit such that the delivery conduit traverses in a direction perpendicular to the length of the restrictor.

[0090] As the second end of a restrictor can be closed, the delivery conduit can include a device for opening the second end or breaking the seal on the second end.

5 [0091] A system can further include a GeNO cartridge. The cartridge can employ a surface-active material coated with an aqueous solution of a reducing agent, for example an antioxidant, as a simple and effective mechanism for making the conversion. More particularly, NO_2 can be converted to NO by passing the dilute gaseous NO_2 over a surface-active material coated with an aqueous solution of a reducing agent, e.g. an
10 antioxidant. As an example, when the aqueous antioxidant is ascorbic acid (that is, vitamin C), the reaction can be quantitative at ambient temperatures.

[0092] One example of a surface-active material can be silica gel. Another example of a surface-active material that can be used is cotton. The surface-active material may be or may include a substrate capable of retaining a liquid, for example, water. Another type
15 of surface-active material that has a large surface area that is capable of absorbing moisture also may be used.

[0093] FIG. 6 illustrates a cartridge 600 for generating NO by converting NO_2 to NO. The cartridge 600, which may be referred to as a cartridge, a converter, a NO generation cartridge, a GENO cartridge, a GENO cylinder, GENO converter or Nitrosyl™ Primary
20 Cartridge, can include an inlet 605 and an outlet 610. Screen and/or glass wool 615 can be located at the inlet 605 and/or the outlet 610. The remainder of the cartridge 600 can be filled with a surface-active material 620 that is soaked with a saturated solution including a reducing agent to coat the surface-active material. The saturated solution can be, for example, an antioxidant in water. The screen and/or glass wool 615 can also be
25 soaked with the saturated solution before being inserted into the cartridge 600. The antioxidant can be ascorbic acid.

[0094] In a general process for converting NO_2 to NO, a gas flow (e.g. air flow) having NO_2 can be received through the inlet 605. The gas flow can be fluidly communicated to the outlet 610 through the surface-active material 620 coated with the
30 aqueous reducing agent, e.g. antioxidant. As long as the surface-active material 620 remains moist and the reducing agent may not been used up in the conversion, the general process can be effective at converting NO_2 to NO at ambient temperature.

[0095] The inlet 605 also may receive the air flow having NO₂, for example, from source of NO₂. A source of NO₂ can include a pressurized bottle of NO₂, which also may be referred to as a tank of NO₂. The inlet 605 also may receive a gas flow with NO₂ in nitrogen, air, or oxygen. The conversion can occur over a wide concentration range.

5 Experiments have been carried out at concentrations in a gas including from about 2 ppm NO₂ to 100 ppm NO₂, and even to over 1000 ppm NO₂. In one example, a cartridge that was approximately 6 inches long and had a diameter of 1.5-inches was packed with silica gel that had first been soaked in a saturated aqueous solution of ascorbic acid. The moist silica gel was prepared using ascorbic acid (i.e., vitamin C) designated as A.C.S reagent
10 grade 99.1% pure from Aldrich Chemical Company and silica gel from Fischer Scientific International, Inc., designated as S8 32-1, 40 of Grade of 35 to 70 sized mesh. Other sizes of silica gel also can be effective. For example, silica gel having an eighth-inch diameter could also work.

[0096] The silica gel can be moistened with a saturated solution including a reducing
15 agent. For example, a saturated solution of ascorbic acid in water; more specifically, the saturated solution can be a saturated solution that had been prepared by mixing 35% by weight ascorbic acid in water, stirring, and straining the water/ascorbic acid mixture through the silica gel, followed by draining. The conversion of NO₂ to NO can proceed well when the silica gel coated with ascorbic acid is moist. The conversion of NO₂ to NO
20 may not proceed well in an aqueous solution of ascorbic acid alone.

[0097] The cartridge can be filled with the wet silica gel/reducing agent. For example, a cartridge filled with the wet silica gel/ascorbic acid was able to convert 1000 ppm of NO₂ in air to NO at a flow rate of 150 ml per minute, quantitatively, non-stop for over 12 days. A wide variety of flow rates and NO₂ concentrations have been
25 successfully tested, ranging from only a few ml per minute to flow rates of up to 5,000 ml per minute. Any appropriate reducing agent that can convert NO₂ or N₂O₄ to NO can be used as determined by a person of skill in the art. For example, the reducing agent can include a hydroquinone, glutathione, and/or one or more reduced metal salts such as Fe(II), Mo(VI), NaI, Ti(III) or Cr(III), thiols, or NO₂⁻. The reducing agent can be an
30 antioxidant. The antioxidant can be an aqueous solution of an antioxidant. The antioxidant can be ascorbic acid, alpha tocopherol, or gamma tocopherol. Any appropriate antioxidant can be used depending on the activities and properties as determined by a person of skill in the art. The antioxidant can be used dry or wet.

[0098] The antioxidant/surface-active material GENO cartridge may be used for inhalation therapy. In one such example, the GENO cartridge can be used as a NO₂ scrubber for NO inhalation therapy that delivers NO from a pressurized bottle source. The GENO cartridge can be used to remove any NO₂ that chemically forms during inhalation therapy. This GENO cartridge can be used to help ensure that no harmful levels of NO₂ are inadvertently inhaled by the patient.

[0099] Using the system as an inhaled NO drug delivery device, the NO₂ output in air or oxygen can be passed through a GeNO cartridge, which strips out one of the O atoms from the NO₂ to produce ultra pure NO.

10 [00100] Referring to FIG. 7, the cartridges 700 can be blow molded with internal ridges 705 and valleys 710. When packed with the surface active material and reducing agent (e.g. silica gel/ascorbic acid powder), the particles can tend to pack, leaving a small air gap at the top. If the cartridge was allowed to be vibrated on its side, the material could settle. If the tube had a smooth bore, the space above the powder could create a path that bypassed the GeNO converter. By having the ridges 705 and valleys 710, the powder can settle and the vapour cannot have a pathway that would bypass the chemistry reactor. The height of the ridge and its width can be determined by calculation and then confirmed experimentally.

[00101] The cap for the cartridges can be molded from plastic (FIG. 8).

20 [00102] An exemplary embodiment of a system is shown in FIG. 9. Referring to FIG. 9, a system 900 can include a reservoir 905. A reservoir 905 can include a nitrogen dioxide source 910, for example, liquid N₂O₄. Over the nitrogen dioxide source can be nitrogen dioxide vapor 915. As the vapor pressure of the nitrogen dioxide vapor 915 is increased, for example by heating the nitrogen dioxide, the nitrogen dioxide 915 can be forced into a restrictor 920. The restrictor 920 can be coupled to the reservoir at a first end 925. The second end 930 of the restrictor can be closed or sealed for storage. To use the system, the second end 930 can be opened or the seal can be broken, which can allow nitrogen dioxide to traverse the length of the restrictor 920 and out the second end 930. A gas supply 935 can provide gas 950, which can traverse through a delivery conduit 940. 25 An inlet 945 of the delivery conduit 940 can be coupled to the gas supply 935. The second end of the restrictor 930 can also be coupled to the delivery conduit 940. In that way, as gas 950 from the gas supply 935 traverses through the delivery conduit 940 and past the second end of the restrictor 930, the gas 950 from the gas supply 935 and the

nitrogen dioxide vapor 915 from the reservoir will mix, forming a nitrogen dioxide-gas mixture 955. The nitrogen dioxide-gas mixture can then pass through a number of devices including, but not limited to, sensors, cartridges or filters, as discussed below.

[00103] Another exemplary embodiment of a system is shown in FIG. 10. Referring to FIG. 10, a system 1000 can include a reservoir 1005, which can include a nitrogen dioxide source 1010, for example, liquid N_2O_4 . Over the nitrogen dioxide source can be nitrogen dioxide vapor 1015. As the vapor pressure of the nitrogen dioxide vapor 1015 is increased, for example by heating the nitrogen dioxide, the nitrogen dioxide 1015 can be forced into a restrictor 1020. The restrictor 1020 can be coupled to the reservoir 1005 at a first end of the restrictor 1025. The second end 1030 of the restrictor can be closed or sealed for storage. To use the system, the second end 1030 can be opened or the seal can be broken, which can allow nitrogen dioxide to traverse the length of the restrictor 1020 and out the second end 1030. A gas supply 1035 can provide gas 1050, which can traverse through a delivery conduit 1040. An inlet 1045 of the delivery conduit 1040 can be coupled to the gas supply 1035. The second end of the restrictor 1030 can also be coupled to the delivery conduit 1040. In that way, as gas 1050 from the gas supply 1035 traverses through the delivery conduit 1040 and over the second end of the restrictor 1030, the gas 1050 from the gas supply 1035 and the nitrogen dioxide vapor 1015 from the reservoir will mix, forming a nitrogen dioxide-gas mixture 1055. The nitrogen dioxide-gas mixture 1055 can then pass through a first cartridge 1060 included in the delivery conduit. Prior to or following a cartridge 1060, the nitrogen dioxide-gas mixture 1055 can pass through a number of devices which can be included the delivery conduit including, but not limited to, sensors or filters, as discussed in more detail below. The nitrogen dioxide-gas mixture 1055 can also pass through a second cartridge 1060 prior to exiting the delivery conduit. A patient interface can be coupled to an outlet 1065 of the delivery conduit.

[00104] A system can include a heating element. A heating element can be any device that can alter and maintain the temperature of the system, or at least the reservoir and/or the restrictor. The heating element can be a hot water bath, a heating mantle or heating wire. Insulated heating wires can be wrapped directly onto the tube surface. A heated well can also be used. Other suitable examples of a heating element are known to those of skill in the art.

[00105] In an exemplary embodiment, the system or a portion of the system, for example the reservoir and/or restrictor, can be heated by means of a simple flexible circuit board with the wires etched onto the surface (FIG. 11). A device including a thermistor can be built into the circuit for measuring and controlling the temperature.

- 5 [00106] When heating a system or a portion of a system, the lowest temperature that is practical can be about 25 °C. However, it can be difficult to control the temperature precisely when it is close to ambient temperature. For maximum control, the temperature should be set to be above the highest possible ambient temperatures. The upper temperature limit can, in principle, be many hundreds of degrees centigrade. A practical
- 10 limit can be the engineering balance of (a) having the liquid hot enough to develop the pressure that can force the vapor out of the device, and (b) minimizing the amount of energy that may be needed, especially for battery powered devices, minimizing the amount of thermal insulation that may be needed (a size factor) and the complexity of the storage vessel as far as ensuring that it can withstand the pressures that may be developed
- 15 inside the vessel. The temperature can be at least about 25 °C, at least about 30 °C, at least about 35 °C, at least about 40 °C, at least about 45 °C or at least about 50 °C; the temperature can be at most about 200 °C, at most about 150 °C, at most about 100 °C, or at most about 75 °C. The optimum temperature range can be about 45 to 75 °C, which can develop enough vapor pressure to force the NO₂ vapor through the restrictor.
- 20 [00107] The reservoir and/or the restrictor can be heated. The reservoir and the restrictor can be heated to substantially the same temperatures, for example less than 10 °C difference, less than 5 °C difference, 2 °C difference or less than 1 °C difference between the temperature of the reservoir and the temperature of the restrictor. This can avoid condensation of NO₂. Also, the temperature of the system, more specifically, the
- 25 reservoir and/or the restrictor, can be controlled to better than about 1 °C, preferably better than about 0.5 °C, in order to maintain a constant output of NO₂ vapor. The higher the temperature of the vessel, the better the temperature control should be. This need can come about because the vapor pressure can approximately double with a 10 degree rise in temperature. Thus, for a fixed restrictor and fixed air flow, the concentration of NO₂ in
- 30 the output can double from approximately 40 ppm at 45 °C to 80 ppm at 55 °C, to 160 ppm at 65 °C to 320 ppm at 75 °C. At 65 °C, a 0.5 °C variation in temperature can cause a change in output that is more than 4 times greater than at 45 °C.

[00108] In one embodiment, a portion of the system can be reusable and a portion of the system can be disposable. For example, a reusable base unit can include a gas supply (e.g. air pump). A reusable base unit can also include sensors, power supply (e.g. batteries), alarm systems, lights, indicators, and/or electronics (FIG. 12). A disposable unit can include reservoir, the nitrogen dioxide source (e.g. N_2O_4 storage vessel), restrictor and/or at least one GeNO cartridge (e.g. two GeNO cartridges). The disposable unit can further include filters, a heating element, and/or sensors. One purpose of the design can be to make the disposable system as low cost as possible, while ensuring safety. The liquid N_2O_4 source and the at least one GeNO cartridge can be contained in a sealed unit that can be produced in large quantities. A typical patient can use one disposable unit per day, which can depend upon the size of the reservoir, the amount of the nitrogen dioxide source, the size of the cartridges, and the dose required.

[00109] In one embodiment, between the two cartridges, the flow path can pass over an NO sensor (P/N NO-D4 Alphasense, Ltd. United Kingdom), which can verify that the NO levels do not exceed or fall below specified levels. If necessary, the sensor can trigger alarms or shut off the gas supply. One embodiment is shown below in FIG. 13, which shows the base and the disposable, separately and combined.

[00110] Some of the safety features of the disposable/reusable system can include the following: 1) an activated charcoal filter on the air intake prior to the valve which breaks off the quartz tip, where the charcoal filter could be large enough to adsorb all of the NO_2 in the reservoir; 2) a tip enclosed in a sealed Teflon chamber during shipment, which can only be moved by inserting the disposable unit into the base unit, so that even if the glass tip broke the NO_2 would be contained; 3) an interlock so that the disposable unit can only be used once; 4) warnings and alarms, including, but not limited to, warning lights for low battery, low or high NO, wrong flow, etc.; 5) an encased liquid reservoir, where the reservoir can be entirely encased in an activated charcoal sheath which will be of sufficient mass to adsorb all of the NO_2 in the storage vessel; 6) a thermal fuse on the heater element so that the unit can never exceed its set temperature; and 7) sensors for flow, pressure atmospheric pressure, etc.

[00111] FIG. 14 shows the size of an exemplary device, in which a man is shown wearing the device while fishing. The miniaturization can be an important feature. Current commercially available delivery systems for inhaled NO can require a patient to be confined to a bed in a hospital and usually in an Intensive Care Unit. The ability to

supply inhaled NO chronically in a simple fashion represents a breakthrough in treatment with inhaled NO.

[00112] A system can be relatively small. The system can weigh less than 64 ounces, less than 32 ounces or less than 16 ounces. The system can be less than 2 feet, less than 1.5 feet, less than 1 foot in height. The system can be less than 2 feet, less than 1.5 feet, less than 1 foot, less than 9 inches or less than 6 inches in width. The system can be less than 6 inches, less than 4 inches, less than 3 inches or less than 2 inches in depth.

[00113] A method of for delivering nitric oxide can include breaking the seal on a second end or opening a closed second end of a restrictor. The restrictor can have a first end in a reservoir containing a nitrogen dioxide source. The method can also include heating the reservoir and the restrictor, which can also heat the nitrogen dioxide source in the reservoir and nitrogen dioxide gas in the reservoir and/or the restrictor. As the nitrogen dioxide gas is heated, vapor pressure can accumulate within the reservoir, releasing the nitrogen dioxide gas into the restrictor. Once the second end is opened or unsealed, nitrogen dioxide gas that is forced into the restrictor can pass through the second end of the restrictor. The method can further include passing a gas from a gas supply across a second end of a restrictor. Passing gas from a gas supply across the second end of a restrictor can create negative pressure at the second end of the restrictor. The increased vapor pressure in the reservoir and/or the negative pressure at the second end of the restrictor can force NO₂ vapor through the restrictor. This can result in the NO₂ gas mixing with the gas from the gas supply. The NO₂ gas mixed with the gas from the gas supply can then be passed through at least one GeNO converter. Additionally, a method can include monitoring the level of NO with a NO sensor, monitoring the level of NO₂ with a NO₂ sensor, or monitoring the temperature with a temperature sensor.

[00114] In one example, the system is activated by breaking the seal of a sealed restrictor, for example, breaking off the tip of a quartz capillary restrictor tube. NO₂ vapor can be expelled from the reservoir at a constant flow rate, which can be dependent on the availability of liquid in the reservoir and the temperature of the reservoir. The NO₂ vapor can mix with gas, e.g. air, from a small pump and the dilute NO₂ mixture can then be allowed to pass through a first GeNO converter, where the NO₂ can be converted into NO. The converter can be made up of fine silica gel soaked in a reducing agent, e.g. ascorbic acid solution, and then partially dried. The NO in gas stream can be flowed to the second GeNO converter. A second GeNO converter can provides double redundancy.

Each of the two cartridges can have sufficient silica gel-ascorbic acid powder to convert 1.5 times the content of the liquid in the reservoir. Also, each cartridge can be manufactured from a different lot. The NO in gas stream can be passed across an optional NO, an optional NO₂ electrochemical sensor, an optional pressure and/or optional flow sensor. The NO vapor in air can then be delivered to a patient by means of a nasal cannula.

[00115] For home use, patients can use a system that delivers a fixed output per unit time. A patient needing a high dose can be provided with a modified system in which increased output can be achieved either by increasing the temperature of the reservoir, changing the diameter of the restrictor or length of the restrictor.

[00116] In a hospital setting, the nurse may have a need to vary both the flow rate of air and the gas concentration. This can be accomplished by varying the temperature of the reservoir for increase the output of the reservoir. The air flow can be adjusted, either from a compressor or from increasing the power of a small built in air pump. A system with variable flow and variable output can include a monitor and display of the flow rate and the NO concentration.

EXAMPLES

EXAMPLE 1

[00117] The slope of the plot of log (NO) versus 1/T, where T is the absolute temperature, should be a straight line. A typical plot obtained using a nitric oxide delivery system is shown in FIG. 15. The small variation from linearity may due to experimental error due primarily to inadequate temperature control. The flow rate was 1 liter per minute of air.

EXAMPLE 2

[00118] The nitric oxide delivery systems can be operated for many days on end without significant variation or degradation. For example, a typical plot of ppm NO, NO₂ and NO + NO₂ versus time is shown in FIG. 16 for one experiment over a period of about 36 hours. In this experiment the NO₂ to NO conversion cartridge was absent. It shows the output of the reservoir, showing the NO level (green line), the NO₂ level (yellow line) and the NO + NO₂ response (black line) with time in minutes. Without being held to any theory, the initial spike was likely due to the approximately 1% NO impurity that is sometimes added to N₂O₄ to reduce corrosion cracking during its conventional use as a

rocket fuel oxidiser. Because it has a higher vapor pressure, the NO will de-gas from the liquid in the early stages oxidiser.

EXAMPLE 3

[00119] FIG. 17 shows the output when the NO conversion cartridges were included in the system to convert the NO₂. In this experiment, the data was collected for 780 minutes (13 hours). While the data shows some drift, it was well within the $\pm 20\%$ that is required for clinical use.

EXAMPLE 4

[00120] FIG. 18 shows the NO and NO₂ output for a period of 24 hours. The NO₂ concentration after the gas flow was passed through the cartridges was essentially zero.

[00121] The various embodiments described above are provided by way of illustration only and should not be construed to limit the claimed invention. Those skilled in the art will readily recognize various modifications and changes that may be made to the claimed invention without following the example embodiments and applications illustrated and described herein, and without departing from the true spirit and scope of the claimed invention, which is set forth in the following claims.

CLAIMS:

1. A system for delivering a therapeutic amount of nitric oxide, comprising:
 - a reservoir assembly including a reservoir including a restrictor covered by a metal sheath and a heating element, wherein the restrictor includes a first end and a second end, wherein the reservoir includes a nitrogen dioxide source, and wherein the first end of the restrictor is coupled to the reservoir;
 - a permeation tube, wherein the permeation tube is connected to the reservoir assembly outside of the reservoir assembly;
 - a gas supply; and
 - a delivery conduit for delivering a therapeutic amount of nitric oxide including
 - at least one cartridge, wherein the at least one cartridge comprises a surface-activated material and a reducing agent, and
 - a patient interface.
2. The system of claim 1, wherein the restrictor includes an orifice.
3. The system of any one of claims 1, wherein the restrictor includes a tube.
4. The system of claim 3, wherein the tube is a capillary tube.
5. The system of claim 1, wherein the second end of the restrictor is coupled to the delivery conduit.
6. The system of any one of claims 1 to 5, wherein the delivery conduit includes an inlet and an outlet.
7. The system of claim 6, wherein the gas supply is coupled to the inlet of the delivery conduit.
8. The system of claim 6 or 7, wherein the patient interface is coupled to the outlet of the delivery conduit.

9. The system of any one of claims 1 to 8, wherein the gas supply is coupled to the delivery conduit.
10. The system of any one of claims 1 to 9, wherein the nitrogen dioxide source includes liquid dinitrogen tetroxide.
11. The system of any one of claims 1 to 10, wherein the gas supply is an air supply.
12. The system of claim 11, wherein the air supply is an air pump.
13. The system of claim 12, wherein the air pump is battery powered.
14. The system of claim 1, wherein the gas supply is coupled to the inlet of the delivery conduit and wherein a second end of a restrictor is coupled to the delivery conduit.
15. The system of claim 1, wherein the reservoir, the restrictor and the cartridge form a disposable module that is capable of being removed from the system.
16. The system of any one of claims 1 to 15, wherein the system also includes at least one of a nitric oxide sensor, a nitrogen dioxide sensor, a flow sensor, a pressure sensor and a sensor for atmospheric pressure.
17. The system of any one of claims 1 to 16, wherein the system has a weight of less than 32 ounces.
18. The system of any one of claims 1 to 17, wherein the system has a weight of less than 16 ounces.
19. A method of manufacturing a reservoir assembly for delivering nitric oxide, comprising:
filling a reservoir with a source of nitrogen dioxide, wherein the reservoir is less than 6 inches in height and less than 4 inches in diameter; and

forming a restrictor within a metal sheath of the reservoir and a heating element, wherein the restrictor is coupled with the reservoir.

20. The method of claim 19, wherein the restrictor includes a first end and a second end, wherein the first end of the restrictor is coupled the reservoir.

21. The method of claim 20, further includes sealing the second end of the restrictor.

22. A reservoir assembly, comprising
a reservoir, wherein the reservoir is less than 6 inches in height and less than 4 inches in internal diameter and the reservoir includes a restrictor and a heating element, wherein the reservoir includes a nitrogen dioxide source, and wherein the restrictor is coupled with the reservoir.

23. The reservoir assembly of claim 22, wherein the reservoir is less than 4 inches in height and less than 2 inches in internal diameter.

24. The reservoir assembly of claim 23, wherein the reservoir is less than 1 inch in height and less than 1 inch in internal diameter.

25. The reservoir assembly of any one of claims 22 to 24, wherein the restrictor has an internal diameter of less than 0.100 microns.

26. The reservoir assembly of any one of claims 22 to 25, wherein the restrictor has an internal diameter of less than 0.050 microns.

27. The reservoir assembly of any one of claims 22 to 26, wherein the restrictor includes a first end and a second end.

28. The reservoir assembly of claim 27, wherein the first end of the restrictor is coupled to the reservoir.

29. The reservoir assembly of claim 27 or 28, wherein the second end of the restrictor is sealed or closed.
30. The reservoir assembly of any one of claims 22 to 29, wherein the restrictor includes a tube.
31. The reservoir assembly of claim 30, wherein the tube is a capillary tube.

1/18




FIGURE 1

2/18




FIGURE 2

3/18




FIGURE 3

4/18




FIGURE 4

5/18



FIGURE 5

6/18




FIGURE 6

7/18




FIGURE 7

8/18




FIGURE 8

9/18




FIGURE 9

10/18




FIGURE 10

11/18




FIGURE 11

12/18




FIGURE 12

13/18





FIGURE 13

14/18




FIGURE 14


15/18

**FIGURE 15**


16/18

**FIGURE 16**

17/18

**FIGURE 17**

18/18

**FIGURE 18**

