



US009049307B2

(12) **United States Patent**
Tyroler et al.

(10) **Patent No.:** **US 9,049,307 B2**
(45) **Date of Patent:** **Jun. 2, 2015**

(54) **WIRELESS INTERFACE DEVICE ALLOWING A RELIABLE DIGITAL AND AUDIO COMMUNICATION TRANSFER BETWEEN A SECURITY SYSTEM, POTS AND/OR IP NETWORK MODEM DEVICE**

USPC 379/37-49; 455/404.1, 404.2, 456.1, 455/410; 340/506, 541, 628, 632, 540; 348/143, 14.01, 152, 155
See application file for complete search history.

(75) Inventors: **Dan Tyroler**, Great Neck, NY (US); **Robert J. Orlando**, Nesconset, NY (US); **Ronald K. Rothman**, Smithtown, NY (US); **Ray Jordan**, Holtsville, NY (US); **Alfred M. Lizza**, Oyster Bay, NY (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,131,019 A 7/1992 Sheffer et al.
5,237,602 A * 8/1993 Lazik 379/38
(Continued)

(73) Assignee: **HONEYWELL INTERNATIONAL INC.**, Morristown, NJ (US)

OTHER PUBLICATIONS

Tannenbaum, A. S., Computer Networks, 2005, pp. 685-692, 4th Edition, Prentice-Hall.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1706 days.

Primary Examiner — Akelaw Teshale

(74) Attorney, Agent, or Firm — Husch Blackwell LLP

(21) Appl. No.: **12/253,736**

(22) Filed: **Oct. 17, 2008**

(65) **Prior Publication Data**

US 2010/0097210 A1 Apr. 22, 2010

(51) **Int. Cl.**
H04M 11/04 (2006.01)
G01D 21/00 (2006.01)
(Continued)



(57) **ABSTRACT**

A system, method process and apparatus is presented for interfacing digital and audio communications in a security system, comprising, a control panel having one or more first radio receiver/transceivers and one or more remote alarm sensors coupled to the control panel and the control panel receiving one or more digital reports from each one or more remote alarm sensors, a wireless interface device having one or more second radio receiver/transceivers for receiving the digital reports from the control panel unit and for establishing two-way voice communication between the control panel and the wireless interface unit, one or more telephone units coupled to the wireless interface device for communicating with the wireless interface unit and at least one POTS and/or IP network modem device coupled to the wireless interface device, an IP network, wherein, the wireless interface device includes a communication processing unit for transmitting one or more digital reports to a monitoring service via the POTS and/or IP network and for establishing two-way voice communication between the control panel and the monitoring service via a voice channel connection.

(52) **U.S. Cl.**
CPC **H04M 11/04** (2013.01); **G01D 21/00** (2013.01); **G08B 25/10** (2013.01); **H04L 12/2825** (2013.01); **H04L 67/12** (2013.01); **H04W 24/10** (2013.01); **H04W 76/02** (2013.01)

(58) **Field of Classification Search**
CPC G08B 25/008; G08B 13/19669; G08B 25/14; G08B 29/02; G08B 25/002; G08B 29/00; G08B 3/10; G08B 13/122; G08B 17/10; G08B 21/14; G08B 13/19602; H04M 11/04; H04M 11/045; H04M 2242/04; H04W 76/007; H04W 4/22; H04W 12/12; H04W 64/00; H04N 7/147; H04N 7/181; H04N 7/188

29 Claims, 4 Drawing Sheets



(51)	<p>Int. Cl. <i>G08B 25/10</i> (2006.01) <i>H04L 12/28</i> (2006.01) <i>H04L 29/08</i> (2006.01) <i>H04W 24/10</i> (2009.01) <i>H04W 76/02</i> (2009.01)</p>	<p>5,923,731 A * 7/1999 McClure 379/33 6,204,760 B1 * 3/2001 Brunius 340/529 7,106,193 B2 9/2006 Kovach 7,174,176 B1 * 2/2007 Liu 455/462 7,675,402 B2 * 3/2010 Lee et al. 340/5.54 2002/0107036 A1 * 8/2002 Cannon et al. 455/462 2002/0163997 A1 * 11/2002 Bergman et al. 379/37 2003/0013503 A1 * 1/2003 Menard et al. 455/569 2004/0086091 A1 * 5/2004 Naidoo et al. 379/37 2006/0145842 A1 * 7/2006 Stilp 340/539.22 2006/0239250 A1 * 10/2006 Elliot et al. 370/352 2009/0323904 A1 * 12/2009 Shapiro et al. 379/39</p>
(56)	<p style="text-align: center;">References Cited</p> <p style="text-align: center;">U.S. PATENT DOCUMENTS</p> <p>5,278,888 A 1/1994 Myllymaki 5,629,687 A * 5/1997 Sutton et al. 340/6.11</p>	<p>* cited by examiner</p>




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3

**WIRELESS INTERFACE DEVICE ALLOWING
A RELIABLE DIGITAL AND AUDIO
COMMUNICATION TRANSFER BETWEEN A
SECURITY SYSTEM, POTS AND/OR IP
NETWORK MODEM DEVICE**

FIELD OF INVENTION

The present invention relates generally to security systems between a premise security system and a central monitoring service, and in particular to a security system supporting digital and audio communications.

BACKGROUND OF THE INVENTION

Currently, various types of security systems are employed in both residential and business locations where a control panel sends signals containing an alarm or other status reporting information to a central monitoring station. The central monitoring station acts as the link between a home or business and police, fire, and other emergency response authorities. In addition, premise security systems now include the ability to allow two-way voice communication between a control panel and the central monitoring station.

To support these applications, the infrastructure of a conventional security system typically includes a control panel, which includes one of the following possible communication modules to communicate with the central monitoring station: (1) a traditional plain old telephone system (POTS) communication module to access the public switched telephone network (PSTN), (2) a wireless RF communication module to access a digital cellular or digital personal communications service (PCS) network, or (3) an IP communication module to access the Internet. In a conventional security system employing a POTS Dialer module, alarm and/or other status reporting information are reported to the central monitoring station by way of the PSTN network. During the reporting period, two-way voice communication between a control panel and the central monitoring station is possible since the POTS line is in use (a channel which allows transmitting digital status report and handle 2 way voice audio communication). When POTS line are used, physical wires are required between the control panel and a telephone jack thus resulting in an increase in the installation time and costs as well as limiting the placement of the control panel within the premise.

In a conventional security system employing traditional alarm communications protocol alarm and/or status data transfer is not reliable via the current voice over global system mobile communication (GSM) network. This is because GSM providers fail to reliably transfer dual tone multi-frequency (dtmf) oriented digital reports due to latency and timing changes introduced by inferior telecommunications equipment. The only reliable alarm reporting is limited to the digital portion of the GSM's general packet radio services (GPRS) channel, which does not allow traditional analog 2-way voice communication.

In a conventional security system employing a POTS digital dialer communication module, the analog port on the modem of a VOIP communication path is utilized for transmitting digital alarm and/or status reports and two-way voice audio communication. However, some VoIP providers do not allow reliable alarm or other status information reporting and voice communications between the control panel (or keypad) and the central monitoring station. This is because VOIP providers fail to reliably transfer dual tone multi-frequency

(dtmf) oriented digital reports due to latency and timing changes introduced by inferior telecommunications equipment.

Hence, there is a need for an apparatus, system and/or process employed in premise security systems to allow a reliable method to deliver alarm and/or status reports) and also establish 2 way voice communication link between a control panel and the central monitoring station. Also, in some instances it may be desirable to also have an apparatus, system and/or process, which support both digital and two-way voice communications simultaneously. Moreover, it is desirable to achieve this communications goal wirelessly between the control panel and the POTS line, the analog port on the VoIP modem and/or both IP and Analog port, in order to remove the need for running a physical wire between the control panel and these mediums.

SUMMARY OF THE INVENTION

The present invention provides a system for interfacing digital and audio communications in a security system.

Specifically, the present invention provides a system for interfacing digital and audio communications in a security system, comprising a control panel having one or more first radio transceivers and one or more remote alarm sensors coupled to the control panel, the control panel receiving one or more digital reports from each one or more remote alarm sensors, a wireless interface device having one or more second radio transceivers for receiving one or more digital reports from the control panel, one or more telephone devices coupled to the wireless interface device for communicating with a plain old telephone system (POTS), and an IP network modem device coupled to the wireless interface device and an IP network, wherein, the wireless interface device includes a communication processing device for controlling a transmission of one or more digital reports to a monitoring service via the IP network and for establishing a two-way voice communication between the control panel and the monitoring service and for establishing two-way voice communication between the control panel and the wireless interface device.

The communication processing device is locally controlled or remotely via a monitoring service.

The communication processing device is adapted for disconnecting each one or more telephone devices from a voice connection and seizes the voice connection as required either while sending one or more digital reports or while establishing the two-way communication between the control panel and the monitoring service.

One or more first and second radio transceivers provides digital and audio communications via a WiFi, a Bluetooth™ or a Zibee radio standard.

The security system can further comprises an IP router disposed between the IP network modem device and the wireless interface device.

Alternatively, a wireless interface device for communicating digital and audio communications in a security system is provided comprising, one or more radio transceivers for establishing two-way voice communication between the wireless interface device and a control panel, a first port for transmitting one or more digital reports to a monitoring service via an IP network, a second port for receiving and transmitting two-way voice communications, a third port for connection one or more telephones to the wireless interface device, and a communication processor for controlling the transmitting of the one or more digital reports via the IP

network and transmitting and receiving two-way voice communications and for interfacing the control panel and the monitoring service.

Alternatively, a wireless interface device for communicating digital and audio communications in a security system, comprising, one or more radio transceivers for establishing two-way voice communication between the wireless interface device and a control panel, a first port for transmitting one or more digital reports and transmitting two-way voice communications on a plain old telephone system (POTS) phone line, a second port for connection one or more telephones to the wireless interface device, and a communication processor for controlling the transmitting and receiving the digital reports over POTS and transmitting and receiving two-way voice communications and for interfacing the control panel and a monitoring service.

Alternatively, a wireless interface device for communicating digital and audio communications in a security system, comprising, one or more radio transceivers for establishing two-way voice communication between the wireless interface device and a control panel, a first port for transmitting one or more digital reports and transmitting two-way voice communications via an analog port of a broadband modem, a second port for connection of one or more telephones to the wireless interface, and a communication processor for controlling the transmitting and receiving the digital reports over the analog port of the broadband modem and transmitting and receiving two-way voice communications and for interfacing the control panel and a monitoring service.

The present invention also provides a method of interfacing digital and audio communications in a security system, comprising the steps of sending one or more digital reports from one or more remote sensors in the security system to a control panel at a predetermined interval, re-sending wirelessly the received one or more digital reports to a wireless interface device, the wireless interface device coupled to an IP network for forwarding the one or more digital reports to a monitoring service, receiving by the wireless interface device a two-way voice communication request from the monitoring service, and establishing two-way voice communication between the control panel and the monitoring service.

Alternatively, while performing the step of re-sending wirelessly the received one or more digital reports to a wireless interface device, the wireless interface device is not coupled to an IP network modem device and instead coupled directly to a plain old telephone system (POTS) phone line via a rj31x jack.

Alternatively, A system for interfacing digital and audio communications in a security system, comprising, a control panel having one or more first radio transceivers and one or more remote alarm sensors coupled to the control panel, said control panel receiving one or more digital reports from each the one or more remote alarm sensors, a wireless interface device having one or more second radio transceivers for receiving the one or more digital reports from the control panel, one or more telephone devices coupled to the wireless interface device for communicating with a plain old telephone system (POTS), and a plain old telephone system (POTS) phone jack coupled to the wireless interface device and an public switched telephone network (PSTN), wherein, the wireless interface device includes a communication processing device for controlling a transmission of the one or more digital reports to a monitoring service via said PSTN and for establishing a two-way voice communication between the control panel and the monitoring service and for establishing two-way voice communication between the control panel and the wireless interface device.

The monitoring service can locally or remotely controls the communication processing device.

The communication processing device is adapted for disconnecting each said one or more telephone devices from a voice connection and seizes said voice connection as required either while sending said one or more digital reports or while establishing said two-way communication between said control panel and said monitoring service.

An additional object of the present invention is to provide a program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform the above-described method for interfacing digital and audio communications in a security system.

An additional object of the present invention is to provide a wireless means to improve installation speed by removing the necessity for running a physical wire (such as a phone line or cat5 cable) between the control panel and the point of entry of this communication medium, either POTS and/or IP via broadband modem.

The invention is further described in the detailed description that follows, by reference to the noted drawing by way of non-limiting illustrative embodiments of the invention, in which like reference numerals represent similar parts throughout the drawings. As should be understood, however, the invention is not limited to the precise arrangements and instrumentalities shown.

DETAILED DESCRIPTION OF THE DRAWINGS

These and other features, benefits and advantages of the present invention will become apparent by reference to the following text figures, with like reference numbers referring to like structures across the views, wherein:

FIG. 1A depicts a system for interfacing digital and audio communications in a security system according the first embodiment of the present invention.

FIG. 1B depicts a system for interfacing digital and audio communications in a security system according the second embodiment of the present invention.

FIG. 2 depicts a system for interfacing digital and audio communications in a security system according third embodiment of the present invention.

FIG. 3 depicts a system for interfacing digital and audio communications in a security system according the forth embodiment of the present invention.

DISCLOSURE OF THE INVENTION

FIG. 1A shows an exemplary embodiment of the system for interfacing digital and audio communications in a security system of the present invention. In the FIG. 1, a wireless interface device 120 is wirelessly coupled to a control panel 110 and a generic Internet modem 130. Control panel 110 is wired or wirelessly coupled to various types of sensors 155, such as motion, smoke or heat sensors and at least one keypad 150.

As known to those skilled in the art, control panel 110 may additionally include a built-in microphone and speaker (not shown) as well as support circuitry for the purpose of annunciating all human voice discussions (listening and talking) between on-premise persons (typically the homeowner) and the central monitoring operators. This ensures that central monitoring operators can listen to events as they transpire on-premise during the commission of a crime, or other emergency. Additionally the microphone circuitry allows on-premise persons the ability to communicate back to the central station operator. Further, the control panel 110 may

5

support an additional 2 way voice standalone station, either wired or wireless via COM port **114** for this same purpose as discussed above (voice discussions during a 2 way voice session between operator and on-premise persons).

The status of the alarm or security system is maintained in storage (not shown) in the control panel **110**. Periodic status event reports and alarm reports are generated by a processor **113** (microprocessor/controller, or FPGA, or the like) in digital format for example, Full Contact ID or ADEMCO high-speed reporting formats. Other digital alarm reporting formats can be utilized by the present invention as known to those skilled in the art.

Communications between the control panel **110** and the wireless interface device **120** are wireless by means of radio transceivers **112** and **122**. Such emerging radio standards as WiMax™, WiFi, Zibee, Bluetooth™ and the like can be utilized for communications as well as others known in the art. As known to those skilled in the art, radio transceiver **112** can be either an integral part of the control panel **110** (e.g. couple to PCB), or it could be a standalone module which is either mounted on a control panel PCB, or mounted inside a common enclosure with the control panel **110** but a separate PCB. In addition, radio transceiver **112** could be mounted on a PCB outside a control panel enclosure.

Generic Internet modem **130** is a generic Internet modem, which can access the Internet, such as a DSL modem which connects via an IP network port (not shown) and as an rj45 patch or via a fiber optics connection. Alternatively, generic Internet modem **130** can be a cable modem accessible to the Internet via a co-axial cable connection cable, or generic Internet modem **130** can be a WiMax antenna or the like capable accessing the Internet via a hot spot as known to those skilled in the art. As shown in FIG. 1B, an alternative embodiment of the present invention according to a second embodiment **400** includes an optional IP router **195** may be disposed between the generic Internet modem **130** and wireless interface device **120**. In some DSL and cable modems, a plain old telephone service (POTS) port connection **135** can be provided for interfacing the generic Internet modem **130** with a public switched telephone network (PSTN) (not shown). The POTS and PSTN are merely one possible embodiment of the invention. Those skilled in the art could alternatively employ an emerging voice-over IP connection as known to those skilled in the art. Port **134** is provided for interfacing IP communications between generic Internet modem **130** and Port **124** of the wireless interface device **120**. Similarly, Port **135** is provided for interfacing two-way voice communications between generic Internet modem **130** and the wireless interface device **120**, Port **125**.

Referring now to FIG. 2 a system for interfacing digital and audio communications according to the third embodiment of the present invention is shown. In FIG. 2, modem **160** is provided and is an IP based broadband modem or similar device. In this alternative embodiment, the analog output of Port **125** on wireless interface device **120** is connected directly to the analog Port **165** on modem **160**. Moreover, in this alternate configuration the IP Port **164** remains unused for this application and both digital status report (e.g. alarm or trouble reports) and 2 way voice sessions are established via the analog Port **165**. It should be noted that modem **160** is a duplicate of generic Internet modem **130** described above. However, in Modem **160** the IP port **164** is unused and all communications occurs on the analog Port **165**. This alternate configuration eliminates running wires between the control panel **110** and modem **160** and achieves 2-way voice wirelessly.

6

Referring now to FIG. 3 a system for interfacing digital and audio communications according to the fourth embodiment of the present invention is shown. In FIG. 3, POTS device **170** is provided which is an rj31x jack or similar POTS line connection device where the analog output of port **125** on wireless interface device **120** is connected directly to Port **175** on POTS device **170** and to the street via a utility connection **190**. POTS device **170** also connects directly to any on-premise incoming POTS line. Both digital status reports (e.g. alarm or trouble reports) and 2 way voice sessions are established via this medium. This alternate configuration eliminates running wires between the control panel **110** and the POTS device **170**.

Referring back to FIG. 1A the operation of the first embodiment of the present invention will now be described. As shown in FIG. 1A, wireless interface device **120**, Port **126** is provided for interfacing the POTS and a plurality of telephones **140-140n**. A communication controller **127** is provided for controlling the timing and switching between reporting the digital reports generated by processor **113** in the control panel **110** and the establishment of two-way communication between the central monitoring service **180** and control panel **110**. For example, in one instant, a RF signal (originated at control panel **110**) is transmitted by RF radio transceiver **112** to the wireless interface **120** via RF radio transceiver **122**. The communication controller **127** upon receipt of the digital report transmits the report via IP by way of Port **124** of the wireless interface device **120** to Port **134** of the generic Internet modem **130** via a path cable. The digital reports are temporarily storage in memory **128**. The central monitoring service **180** receives the digital report via an IP network such as the Internet from the generic Internet modem **130**.

In the event of an alarm report, the central monitoring service **180** may initiate two-way voice with control panel **110**. That is, the central monitoring service **180** may send a control signal to the communication controller **127** in response to an alarm report via the POTS and/or IP network. Various call back scheme can be employed as known to those skilled in the art such as a generalize call back scheme or a call back scheme triggered by a specific event code reported (e.g. contact ID format). The present invention is not limited to any specific call back scheme.

Next, a control signal sent from the central monitoring service **180** would trace back through the generic Internet modem **130** to the wireless interface device **120** via IP by way of port **134** to port **124** via a path cable. The communication controller **127** will in response to the control signal seize the POTS connection, which will have the effect of disconnecting telephones **140-140n** from the POTS and send an ACK signal back to the central monitoring service **180**. At the same time communication controller **127** will also send a second control signal to processor **113** in the control panel **110** via RF radio transceivers **122** to RF radio transceiver **112**. The second control signal will establish a communication channel between the control panel **110** or a keypad attached to the control panel **110** (e.g. wireless keypad **150**) to allow the transferring of audio communications to port **125** of the wireless interface device to port **135** of the generic Internet modem **130** thereby providing an audio path from the central monitoring station which initiated the requested audio communication (two-way voice communication).

The method of interfacing digital and audio communications in an alarm or security system according to the first embodiment of the present invention comprises the following four steps. First, one or more digital reports are sent from one or more remote sensors **155** to control panel **110** at a prede-

terminated interval. As noted above these digital reports are periodic status event reports and alarm reports generated by a processor **113** in control panel **110** in a digital report format. The second step requires that the communication controller **127** send via IP each digital report received by the wireless interface device **120** from the control panel **110** via an IP network to a central monitoring service **180**.

In the third step, the central monitoring service **180** sends a control signal to wireless interface device **120** to establish two-way voice communication which the communication processor **127** acknowledges so that voice communications may be established between the generic Internet modem **130** and the wireless interface device **120** via analog port **125** on wireless interface device **120**, and analog port **135** on generic interne modem **130** and the control panel **110** via RF radio transceivers. The communication processor **127** is remotely controlled by the central monitoring service **180**.

The present invention provides an apparatus, system and/or process employed in a premise alarm and security systems to supports both digital and audio communications. In particular, digital reports are transmitted via an IP network and two-way voice communications via the audio section of the IP or via POTS allowing a reliable method to deliver status report (e.g. alarm or trouble report etc) and also establishing 2-way voice communication between a control panel **110** and the central monitoring service **180**. Moreover, the present invention eliminates the need for wires between the control panel **110** and an Internet modem **130** while providing reliable status and alarm reporting to a central monitoring service **180**.

While there has been shown and described what is considered to be preferred embodiments of the invention, it will, of course, be understood that various modifications and changes in form or detail could readily be made without departing from the spirit of the invention. It is therefore intended that the scope of the invention not be limited to the exact forms described and illustrated, but should be construed to cover all modifications that may fall within the scope of the appended claims.

As will be readily apparent to those skilled in the art, the method of interfacing digital and audio communications of the invention can be realized in hardware, or as some combination of hardware and software. Any kind of computer/server system(s)—or other apparatus adapted for carrying out the methods described herein—is suited. A typical combination of hardware and software could be a general-purpose computer system with a computer program that, when loaded and executed, carries out methods described herein. Alternatively, a specific use computer, containing specialized hardware for carrying out one or more of the functional tasks of the invention, could be utilized.

Moreover, the present invention or aspects of the invention can also be embodied in a computer program product, which comprises all the respective features enabling the implementation of the methods described herein, and which—when loaded in a computer system—is able to carry out these methods. Computer program, software program, program, or software, in the present context mean any expression, in any language, code or notation, of a set of instructions intended to cause a system having an information processing capability to perform a particular function either directly or after either or both of the following: (a) conversion to another language, code or notation; and/or (b) reproduction in a different material form.

The present invention can also be embodied as a program on a computer-readable recording medium. Examples of the computer-readable recording medium include but are not lim-

ited to Compact Disc Read-Only Memory (CD-ROM), Random-Access Memory (RAM), floppy disks, hard disks, and magneto-optical disks.

What is claimed is:

1. A system for interfacing digital and audio communications in a security system, comprising:
 - a control panel within a premises of a premises owner, the control panel having one or more first radio transceivers and one or more remote alarm sensors coupled directly to said control panel, said control panel receiving one or more digital reports from each said one or more remote alarm sensors;
 - a wireless interface device within the premises, the wireless interface device having one or more second radio transceivers that receive said one or more digital reports directly from said control panel and that establish a two-way voice connection between said control panel and said wireless interface device;
 - one or more telephone devices within the premises, the one or more telephone devices coupled to said wireless interface device that communicate with a plain old telephone system (POTS); and
 - an IP network modem device within the premises, the IP network modem device coupled to said wireless interface device and an IP network,
 wherein, said wireless interface device includes a communication processing device that controls a transmission of said one or more digital reports to a monitoring service via said IP network and that establishes a two-way voice communication between the premises through said control panel and said monitoring service in response to a control signal from said monitoring service regarding an alarm report of any of said one or more digital reports received through the wireless interface device and wherein the wireless interface device establishes two-way voice communication between said control panel and said wireless interface device through the first and second radio transceivers.
2. The system in claim 1, wherein said monitoring service remotely controls said communication processing device.
3. The system in claim 2, wherein said communication processing device is adapted for disconnecting each said one or more telephone devices from a voice connection and seizes said voice connection as required either while sending said one or more digital reports or while establishing said two-way communication between said control panel and said monitoring service.
4. The system in claim 3, wherein said security system further comprises:
 - an IP router disposed between said IP network modem device and said wireless interface device.
5. The system of claim 1, wherein said one or more first and second radio transceivers provides said digital and audio communications via a WiFi, a Bluetooth™ or a Zigbee radio standard.
6. A wireless interface device within a premises of a premises owner for communicating digital and audio communications in a security system of the premises, comprising:
 - one or more radio transceivers that establishes direct two-way voice communication between said wireless interface device within the premises and a control panel within the premises and that transfers one or more digital reports from the control panel to said wireless interface device;
 - a first port that transmits one or more digital reports received from the control panel to a monitoring service via an IP network;

9

a second port that receives and transmits two-way voice communications;
 a third port that connects one or more telephones to said wireless interface device; and

a communication processor that controls the transmitting 5
 of said one or more digital reports via said IP network and transmitting and receiving two-way voice communications and that interfaces said control panel and said monitoring service, wherein the communication processor initiates the transmitting and receiving of the two- 10
 way communications between the premises through said control panel and said monitoring service in response to a control signal from the monitoring service regarding an alarm report of any of the one or more digital reports 15
 received through the wireless

7. The wireless interface device of claim 6 wherein said communication processor is remotely controlled by said monitoring service.

8. The wireless interface device of claim 7, wherein said 20
 communication processor disconnects each said one or more telephones from a voice connection and seizes said voice connection for establishing said two-way communication between said control panel and said monitoring service. inter-
 face device. 25

9. A wireless interface device within a premises of a pre-
 mises owner for communicating digital and audio communi-
 cations in a security system of the premises, comprising:

one or more radio transceivers that establishes direct two-
 way voice communication between said wireless inter-
 face device and a control panel within the premises and
 that transfers one or more digital reports from the control
 panel to the wireless interface device;

a first port that transmits the one or more digital reports 35
 received from the control panel and transmits and receives two-way voice communications on a plain old
 telephone system (POTS) phone connection;

a second port that connects one or more telephones to said
 wireless interface device; and 40

a communication processor that controls the transmitting
 of said one or more digital reports over POTS and trans-
 mitting and receiving two-way voice communications
 and that interfaces said control panel and a monitoring
 service wherein the communication processor initiates 45
 the transmitting and receiving of the two-way commu-
 nications between the premises through said control
 panel and said monitoring service in response to a con-
 trol signal from the monitoring service regarding an
 alarm report of any of the one or more digital reports 50
 received through the wireless interface device.

10. The wireless interface device of claim 9 wherein said
 communication processor is remotely controlled by said
 monitoring service.

11. The wireless interface device of claim 10, wherein said 55
 communication processor disconnects each said one or more
 telephones from a voice connection and seizes said voice
 connection for establishing said two-way communication
 between said control panel and said monitoring service.

12. A wireless interface device within a premises of a 60
 premises owner for communicating digital and audio com-
 munications in a security system of the premises, comprising:
 one or more radio transceivers within the premises that
 establishes direct two-way voice communication
 between said wireless interface device and a control 65
 panel within the premises, the transfers one or more
 digital reports from the control panel and said wireless

10

interface devices and that establishes a two-way voice
 connection between the control panel and the wireless
 interface device;

a first port that transmits the one or more digital reports
 from the control panel and that transmits and receives
 two-way voice communications via an analog port of a
 broadband modem;

a second port that connects one or more telephones to said
 wireless interface; and

a communication processor that controls the transmitting
 said one or more digital reports over the analog port of
 said broadband modem and transmitting and receiving
 two-way voice communications and that interfaces said
 control panel and a monitoring service wherein the com-
 munication processor initiates the transmitting and
 receiving of the two-way communications between the
 premises through said control panel and said monitoring
 service in response to a control signal from the monitor-
 ing service regarding an alarm report of any of the one or
 more digital reports received through the wireless inter-
 face device.

13. The wireless interface device of claim 12 wherein said
 communication processor is remotely controlled by said
 monitoring service.

14. The wireless interface device of claim 13, wherein said
 communication processor disconnects each said one or more
 telephones from a voice connection and seizes said voice
 connection for establishing said two-way communication
 between said control panel and said monitoring service.

15. A method of interfacing digital and audio communica-
 tions in a security system within a premises of a premises
 owner, comprising the steps of:

(1) sending one or more digital reports from one or more
 remote sensors within the premises of said security sys-
 tem to a control panel within the premises at a predeter-
 mined interval;

(2) re-sending wirelessly said received one or more digital
 reports to a wireless interface device within the pre-
 mises, said wireless interface device coupled to an IP
 network for forwarding said one or more digital reports
 to a monitoring service;

(3) receiving by said wireless interface device a two-way
 voice communication request from said monitoring ser-
 vice for two-way communication between the premises
 owner through the control panel and said monitoring
 device; and

(4) establishing two-way voice communication between
 said control panel and said monitoring service through a
 wireless connection between the control panel and wire-
 less interface device wherein the request for the two-way
 communications between said control panel and said
 monitoring service is received in response to an alarm
 report of any of the one or more digital reports received
 through the wireless interface device.

16. The method of claim 15, wherein, while performing the
 step of re-sending wirelessly said received one or more digital
 reports to a wireless interface device, said wireless interface
 device is not coupled to an IP network modem device and
 instead coupled directly to a plain old telephone system
 (POTS) phone line via a rj31x jack.

17. The method of claim 15, wherein said steps of (2)
 through (4) are performed by a communication processor,
 which is remotely controlled by said monitoring service.

18. The method of claim 17, wherein the step (3) further
 comprising the sub-step of (a) disconnecting by said commu-
 nication processor, one or more telephone devices coupled to
 said wireless interface device and seizing a voice connection

11

for establishing said two-way voice communication between said control panel and said monitoring service.

19. The method of claim 15, wherein the step (3) further comprising the sub-step of: (a) disconnecting by said communication processor, one or more telephone devices coupled to said wireless interface device and seizing a voice connection for establishing said two-way voice communication between said control panel and said monitoring service.

20. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform a method for interfacing digital and audio communications in a security system within a premises of a premises owner, comprising:

a process for sending one or more digital reports from one or more remote sensors within the premises of said security system to a control panel within the premises at a predetermined interval;

a process for re-sending wirelessly said received one or more digital reports to a wireless interface device, said wireless interface device coupled to an IP network for forwarding said one or more digital reports to a monitoring service;

a process for receiving by said wireless interface device a two-way voice communication request from said monitoring service; and

a process for establishing two-way voice communication between the premises through said control panel and said monitoring service through the wireless interface and a wireless connection between the control panel and wireless interface device wherein the request for the two-way communications between said control panel and said monitoring service is received in response to an alarm report of any of the one or more digital reports received through the wireless interface device.

21. The program storage device of claim 20, wherein the process of re-sending wirelessly said received one or more digital reports to a wireless interface device, said wireless interface device is not coupled to an IP network modem device and instead coupled directly to a plain old telephone system (POTS) phone line via a rj31x jack.

22. The program storage device of claim 21, wherein said processes are performed by a communication processor, which is remotely controlled by said monitoring service.

23. The method of claim 22, wherein process for re-sending wirelessly said received one or more digital reports to a wireless interface device, further comprising the sub-process of: disconnecting by said communication processor, one or more telephone devices coupled to said wireless interface device and seizing a voice connection for establishing said two-way voice communication between said control panel and said monitoring service.

24. The program storage device of claim 20, wherein said processes are performed by a communication processor, which is remotely controlled by said monitoring service.

12

25. The method of claim 24, wherein the process for re-sending wirelessly said received one or more digital reports to a wireless interface device, further comprising the sub-process of: disconnecting by said communication processor, one or more telephone devices coupled to said wireless interface device and seizing a voice connection for establishing said two-way voice communication between said control panel and said monitoring service.

26. A system for interfacing digital and audio communications in a security system within a premises of a premises owner, comprising:

a control panel having one or more first radio transceivers and one or more remote alarm sensors directly coupled to said control panel, said control panel receiving one or more digital reports from each said one or more remote alarm sensors;

a wireless interface device within the premises having one or more second radio transceivers that directly receives said one or more digital reports from said control panel and that establishes a two-way voice connection between the control panel and the wireless interface device;

one or more telephone devices coupled to said wireless interface device for communicating with a plain old telephone system (POTS); and

a plain old telephone system (POTS) phone jack coupled to said wireless interface device and a public switched telephone network (PSTN), wherein, said wireless interface device includes a communication processing device that controls a transmission of said one or more digital reports to a monitoring service via said PSTN and that establishes a two-way voice communication between the premises through said control panel and said monitoring service in response to a control signal from said monitoring service regarding an alarm report of any of said one or more digital reports received through the wireless interface device and said wireless interface devices establishes two-way voice communication between said control panel and said wireless interface device.

27. The system in claim 26, wherein said monitoring service remotely controls said communication processing device.

28. The system in claim 27, wherein said communication processing device is adapted for disconnecting each said one or more telephone devices from a voice connection and seizes said voice connection as required either while sending said one or more digital reports or while establishing said two-way communication between said control panel and said monitoring service.

29. The system of claim 26, wherein said one or more first and second radio transceivers provides said digital and audio communications via a WiFi, a Bluetooth™ or a Zigbee radio standard.

* * * * *