



(43) International Publication Date
28 June 2012 (28.06.2012)

(10) International Publication Number
WO 2012/085201 A1

- (51) International Patent Classification:
A24B 5/16 (2006.01)
- (21) International Application Number:
PCT/EP2011/073789
- (22) International Filing Date:
22 December 2011 (22.12.2011)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10252214.1 23 December 2010 (23.12.2010) EP
- (71) Applicant (for all designated States except US): **PHILIP MORRIS PRODUCTS S.A.** [CH/CH]; Quai Jeanrenaud 3, CH-2000 Neuchâtel (CH).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DE BORST, Roelof Cornelis** [NL/CH]; Chemin de Floreyres 35, CH-1400 Yverdon-les-Bains (CH). **TRITZ, Poh Yoke** [CH/CH]; Chemin des Sources 44, CH-1400 Yverdon-les-Bains (CH). **HOFFMANN, Harald** [DE/CH]; Bahnhofplatz 4, CH-3066 Stettlen (CH). **KUERSTEINER, Charles** [CH/CH]; Promenade de Flusel 30, CH-1008 Joux-tens-Mezery (CH).
- (74) Agent: **TAYLOR, Gillian**; Reddie & Grose LLP, 16 Theobalds Road, London, Greater London WC1X 8PL (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: TOBACCO CUT FILLER INCLUDING CUT ROLLED STEMS

(57) Abstract: A tobacco cut filler for a smoking article comprises at least 5 % by weight of cut rolled tobacco stems having a mean cut width of 0.1 mm to 0.2 mm and a mean cross-sectional area of between 0.12 and 0.15 square millimetres. The mean thickness of the cut rolled stems is preferably between 0.8 mm and 1.0 mm.



WO 2012/085201 A1

TOBACCO CUT FILLER INCLUDING CUT ROLLED STEMS

The present invention relates to a novel tobacco cut filler comprising cut rolled stems and to a smoking article formed from a tobacco rod of the cut filler according to the invention.

5 Conventionally, cut filler tobacco products for smoking articles are formed predominantly from the lamina portion of the tobacco leaf, which is separated from the stem portion of the leaf during a threshing process. Much of the stem portion that remains after the lamina has been removed and separated is not used. In order to increase the amount of the tobacco material that can be used commercially, it has been previously proposed to add some tobacco stems
10 back into the cut filler together with the lamina. In order to improve the taste and burning characteristics of the tobacco stem for use in the cut filler, the stems are often first subjected to one or more treatment procedures, such as expansion.

For example, in a known process for the treatment of tobacco stems, the stems are first rolled to a thickness of 1 mm before being expanded such that the thickness is increased
15 significantly above 1 mm. After expansion, the tobacco stems are incorporated into a tobacco cut filler.

It would be desirable to provide a tobacco cut filler comprising a proportion of tobacco stems which have been processed in an alternative way in order to more effectively improve the taste and burning characteristics of the tobacco stems. It would be particularly desirable if
20 the inclusion of the tobacco stems could have a positive effect on the cut filler, for example by increasing the filling power of the tobacco cut filler and improving coal drop-off, while minimising the effect on taste.

According to the invention there is provided a tobacco cut filler comprising at least 5% by weight of cut rolled tobacco stems having a mean cut width of about 0.1 mm to about 0.2
25 mm and a mean cross-sectional area of 0.12 to 0.15 square millimetres (mm²). Particularly preferably, the mean cross-sectional area of the cut rolled tobacco stems is around 0.135 square millimetres (mm²).

Preferably, the rolled thickness of the cut rolled tobacco stems in the cut filler is about 0.8 mm to about 1.0 mm. Particularly preferably, the rolled thickness of the cut rolled tobacco
30 stems in the cut filler is around 0.9 mm.

The 'rolled thickness' of the cut rolled stems of cut fillers according to the invention refers to the distance between an upper surface that has been contacted with a rolling apparatus (as described in more detail below) and a lower surface that has been contacted with a rolling apparatus. The rolled thickness therefore corresponds to the dimension of the cut
35 rolled tobacco stems that is reduced in size during the rolling process, which is typically substantially transverse to the direction of movement of the tobacco stems through the rolling

-2-

apparatus. The rolled thickness of an individual tobacco stem particle can be measured using a conventional measuring device under a microscope. The rolled thickness of an individual stem particle is taken at the point along the direction of cutting that yields the largest cross-sectional area.

5 For the purposes of the present invention, the rolled thickness of the cut rolled tobacco stems refers to the stable rolled thickness of the tobacco stems after all of the treatment steps have been carried out. The rolled thickness therefore corresponds to the rolled thickness immediately before the cut filler is incorporated into a smoking article, or when the cut filler is in place within a smoking article. At this stage, the thickness of the stems does not change more
10 than 5% over a period of one week when the cut rolled stems are held at a constant temperature and a constant pressure of 1 atmosphere.

The 'cut width' of the cut rolled stems in cut fillers according to the invention refers to the width of the stem in the direction along which the tobacco stem has been cut. When looking at a stem particle under a microscope, it will generally be possible to observe the
15 direction along which the stem particle has been run through the cutting apparatus. The cut width corresponds to the distance between the two sides of a particle of tobacco stem along this direction of cutting. The cut width of an individual tobacco stem particle can be accurately measured using a conventional measuring device under a microscope. The cut width of an individual stem particle is taken at the point along the direction of cutting that yields the largest
20 cross-sectional area.

The 'cross-sectional area' of the cut rolled stems in cut fillers according to the invention refers to the transverse cross-sectional area, which is the cross-sectional area of the cut rolled stem material, transverse to the direction of cutting. The transverse cross-sectional area of a particle of stem material is taken at the point along the direction of cutting on the stem particle
25 that yields the largest transverse cross-sectional area. The transverse cross-sectional area will be the same as, or can be approximated as, the rolled thickness multiplied by the cut width. Unless otherwise indicated, any references in the present specification to the 'cross-sectional area' of the stem particles refer to the transverse cross-sectional area.

In order to measure the rolled thickness and cut width of the cut rolled stems of cut
30 fillers according to the invention, the tobacco stems must first be separated from the tobacco lamina and other tobacco materials in the cut filler. This can be achieved by visually assessing the cut filler and qualitatively determining which particles of the cut filler are stems and which are lamina or other material. The mean values of cut width and cross-sectional area are determined for the cut rolled stems within the sample of cut filler.

35 According to the invention there is also provided a smoking article comprising a rod of the tobacco cut filler according to the invention. Preferably, smoking articles according to the

invention further comprise a filter in axial alignment with the tobacco rod and connected to the tobacco rod by means of tipping paper. Tobacco cut fillers according to the invention are suitable for use in conjunction with a wide variety of filters, which would be known to the skilled person.

5 It has surprisingly been found that the use of tobacco stem particles having a controlled size and cross-sectional area improves the combustion characteristics of cut filler incorporating the stem particles. It has also surprisingly been found that when using the cut rolled tobacco stems, the impact of the stems on the taste characteristics of the mainstream smoke from the cut filler is limited or in some cases, favourable. The use of cut rolled tobacco stem particles
10 having dimensions within the ranges indicated above also provides improved filling power and an acceptable level of both dust and heavy particles, as discussed further below.

As a result of these positive effects on the properties of the tobacco stems, a significantly greater proportion of tobacco stem particles can be incorporated into the cut filler than has previously been possible. The use of cut rolled stems having the dimensions
15 indicated above in place of the tobacco lamina in cut filler is cost effective, since the stems are typically available at a lower cost than the tobacco lamina. The use of the cut rolled tobacco stems also has a positive environmental impact, since a greater proportion of the tobacco material, including the stem portion, can be used as a component of tobacco cut filler according to the present invention.

20 Tobacco cut fillers according to the invention comprise at least 5 % by weight of the cut rolled tobacco stems, preferably at least 10 % by weight, and more preferably at least 20 % by weight. Tobacco cut fillers according to the invention may comprise up to 100 % by weight of the cut rolled tobacco stems, preferably up to 40 % by weight, more preferably up to 35 % by weight. For example, certain cut fillers according to the invention may contain between 5 %
25 and 95% by weight of the cut rolled tobacco stems of the invention, preferably between 5% and 40% by weight, or more preferably between 10 % and 35 %.

Tobacco cut fillers according to the invention may comprise cut rolled tobacco stems from one or more types of tobacco plant, including but not limited to the stems from Burley tobacco, Oriental tobacco, Virginia tobacco or combinations thereof. The remainder of the cut
30 filler may be made up from tobacco lamina, reconstituted tobacco, expanded tobacco, or any combinations thereof.

Preferably, the tobacco cut filler comprises at least 60 %, and preferably at least 80 % by weight tobacco lamina having a mean cut width between 0.8 mm and 1.1 mm, more preferably about 0.9 mm, and a mean thickness of about 0.2 mm. The tobacco cut filler
35 comprises up to 95 % by weight tobacco lamina with a mean cut width between 0.8 mm and 1.1 mm, more preferably about 0.9 mm, and a mean thickness of about 0.2 mm. The particles

of tobacco lamina in the cut filler are therefore of similar dimensions to the particles of tobacco stem. As such, the tobacco stems are not visually distinct from the tobacco lamina, even at a high inclusion rate. In addition, the blend of tobacco stems and lamina can advantageously be transported and processed effectively without significant settling of the stems. Preferably, the mean cut width of the cut rolled tobacco stems is within about 0.1 mm, more preferably within about 0.05 mm of the mean thickness of the tobacco lamina in the cut filler.

Preferably, the rolling process of the tobacco stems for use in tobacco cut fillers according to the invention ensures that the cellular structure of the stems, in particular the epidermis of the stems, remains substantially intact. This may be achieved by rolling the stems in the stemmery to a final thickness of about 0.7 mm. Alternatively, this could be achieved by rolling the stems at the cigarette factory to a final thickness of about 0.9 mm. The rolling can be performed when the stems are at a relatively high moisture level (as discussed below) to conserve as much of the cellular structure as possible, in particular the epidermis of the cells of the tobacco stems. The preservation of the cellular structure may facilitate subsequent steps in the process, such as expansion of the cut rolled stems. The intact cellular structure of the tobacco stems is observable, for example when the stems are viewed under a microscope.

A further advantage of tobacco cut fillers according to the invention is the increase in the filling power of the cut filler comprising cut rolled tobacco stems having a mean cut width of 0.1 mm to 0.2 mm and a mean cross-sectional area of between 0.12 and 0.15 square millimetres (mm^2), compared to the filling power of cut filler comprising particles of conventionally processed tobacco stem. Preferably, the cut rolled stems used in cut fillers according to the invention have a filling power of at least 6.3 cubic centimetres per gram (cm^3/g) at a reference moisture level of 12.5 % oven volatiles. More preferably, the cut rolled stems used in cut fillers according to the invention have a filling power of at least 6.5 cubic centimetres per gram (cm^3/g) at a reference moisture level of 12.5 % oven volatiles.

The filling power of the tobacco stems depends upon the physical properties, cell structure and epidermis of the stem and may therefore differ according to the origin, stalk position and weather conditions during growth of the tobacco plant. However, the cut rolled tobacco stems used in cut fillers according to the invention will typically have a filling power that is increased by about 0.3 cubic centimetres per gram, or by about 0.5 cubic centimetres per gram (cm^3/g), compared to conventionally processed stems.

The 'filling power' of a tobacco material describes the volume of space taken up by a given weight or mass of the material. The greater the filling power of a tobacco material, the lower the weight of the material required to fill a tobacco rod of standard dimensions. The values of filling power are expressed in terms of corrected cylinder volume (CCV) which is the cylinder volume (CV) of the tobacco material at a reference moisture level of 12.5 % oven

volatiles. The cylinder volume (CV) may be determined using a Borgwaldt densimeter DD60 or DD60A type fitted with a measuring head for cut tobacco and a tobacco cylinder container.

In a suitable method for determining the value of CCV, a sample of the cut filler is placed in the tobacco cylinder container of the Borgwaldt densimeter and subjected to a load of 2 kg for 30 seconds. The height of the sample after the loading time has expired is measured and this is converted to a cylinder volume using the formula:

$$CV = \frac{r^2 \cdot h \cdot \pi}{SW \cdot 10}$$

where r is the cylinder radius (3.00 cm for the densimeter indicated above), h is the height of the sample after the loading time has expired and SW is the weight of the sample. The measured CV is then converted to a corrected value of CCV at the reference moisture level value (ROV) of 12.5 % oven volatiles, using the formula:

$$CCV = (OV - ROV) \cdot f + CV$$

where OV is the actual % oven volatiles of the sample of tobacco stems and f is a correction factor (0.4 for the test indicated).

The moisture content of the tobacco stems is expressed herein as "% oven volatiles", which is determined by measuring the percentage weight loss from the stems upon drying the material in an oven at 103 degrees Centigrade (°C) for 100 minutes. It is assumed that a significant majority of the weight loss from the stems results from the evaporation of moisture.

It is desirable if both the dust level and the level of heavy particles in tobacco cut filler are minimised. Preferably, the cut rolled stems of the cut fillers according to the invention therefore comprise less than 7.5 % by weight of dust particles having a particle size of less than 500 micrometers, more preferably less than 10 % by weight. The proportion of large and heavy particles in the cut rolled stems is advantageously minimised to improve the combustion characteristics of the cut filler. Preferably, the cut rolled stems of the cut fillers according to the invention comprise less than 0.4 % by weight of particles having a particle size greater than 3.35 mm, more preferably less than 0.3 % by weight.

The proportion of the cut rolled stems within these limits can be determined using a known sieve test with screens having sieve openings of 500 micrometers (mesh size 32) and 3.35 mm (mesh size 6). It has been found that both the dust levels and the proportion of large, heavy particles in cut rolled stems according to the invention is relatively low compared to cut rolled stems having larger or smaller particles of tobacco stem.

As illustrated in the comparative example below, in some cases in which the tobacco stems are rolled to a larger thickness and therefore have a greater cross-sectional area than

those used in this invention, the stems have a significantly increased percentage of heavy particles. In addition, in other cases in which the stems are rolled to a lesser thickness and therefore have a lower cross-sectional area than used in this invention, the stems have a significantly increased percentage of dust. In contrast, where the stems are processed to have a cut width between 0.1mm and 0.2mm and a cross-sectional area of between 0.12 and 0.15 square millimetres (mm²), as in the present invention, the cut filler has a limited level of both dust and heavy particles. Particularly, the proportion of heavy particles in the cut rolled stems used in the present invention is decreased by at least 0.2 % by weight compared to conventionally processed stems.

Tobacco cut fillers according to the present invention can be produced using a method comprising the steps of: rolling tobacco stems; cutting the rolled tobacco stems to a mean cut width of 0.1 mm to 0.2 mm; and combining the cut rolled tobacco stems with cut tobacco lamina material to provide a cut filler having at least 5 % by weight of the rolled tobacco stems.

The rolling step is preferably carried out on the green tobacco stems in the stemmery, after the stems have been separated from the tobacco lamina in a suitable threshing process. In this case, the green tobacco stems typically have a high moisture content and are therefore soft and pliable, which in some cases can help minimise damage to the green tobacco stems during rolling. In the stemmery, the stems are preferably rolled to a mean thickness of 0.6 mm to 0.8 mm. During subsequent processing and storage steps, the stems will expand to their final desired thickness of 0.8 mm to 1.0 mm. After rolling, the stems are dried and transferred to the tobacco production plant, where they are cut and added to the tobacco cut filler.

In some cases, the rolling step may alternatively be incorporated as part of the on-line production process for cut filler. In this case, after threshing, the stems will be dried in the stemmery to a moisture content of around 10 % to 11 % oven volatiles and transferred to the tobacco production plant, where the rolling step will be carried out upstream of the apparatus for producing the cut filler. Where the stems are rolled as part of the on-line production process, the stems are preferably rolled to a mean thickness of 0.8 mm to 1.0 mm.

Preferably, in either case, the moisture content of the tobacco stems is around 28 % to 34 % oven volatiles prior to rolling in order to prevent damage to the structure of the stems. If necessary, the tobacco stems are conditioned prior to rolling in order to increase the moisture content to this level. Known processes for conditioning tobacco stems involve contacting the stems with water, steam or a mixture of water and steam. In methods where the rolling step is incorporated on-line and dried stems are received from the stemmery, the conditioning step will typically take longer and may require a soaking step in which the stems are soaked in water for a number of hours prior to rolling. Such a soaking step is typically not required when the green tobacco stems are rolled in the stemmery.

-7-

The tobacco stems may be rolled using a one step rolling process to reduce the thickness of the stems to the desired mean thickness. After rolling, the stems are cut to a cut width of between 0.1 mm and 0.2 mm. The cut rolled stems are then optionally expanded using known stem expansion techniques, and then dried. Where the stems are pre-rolled and
5 dried at the stemmery, it will typically be necessary to condition the stems prior to cutting in order to increase the moisture content of the tobacco stems back to between 28 % and 34 % oven volatiles. This increases the pliability of the tobacco stems in order to limit damage or breakage of the stems during cutting.

Finally, the cut rolled stems are combined with tobacco cut lamina and any additional
10 tobacco materials in order to form cut filler having at least 5 % by weight of the cut rolled tobacco stems.

Cut fillers according to the invention may be incorporated into a variety of smoking articles. For example, the cut filler may be used in the tobacco rod of a combustible smoking article, such as a filter cigarette, cigarillo or cigar. Alternatively, the cut filler may be used to
15 provide the tobacco aerosol generating substrate in a distillation based smoking article, or an electrically heated smoking system. Alternatively, the cut filler may be used as a roll-your-own product, or loose tobacco product for example, for use in a pipe.

Smoking articles comprising cut filler according to the invention may be packaged in containers, for example, containers formed of one or more folded laminar blanks. Suitable
20 containers include but are not limited to hinge lid containers and slide and shell containers.

The invention will be further described by way of the following comparative example:

Comparative Example

In a process for producing cut filler according to the present invention, the stems were
25 first separated from the remainder of the tobacco leaf using a suitable threshing process. At this stage, the green tobacco stems had a moisture content of around 17 % to 20 % oven volatiles. Still within the stemmery, the stems were conditioned by contacting them with a stream of steam and water until the moisture content of the stems reached about 32 % o.v. The moistened stems were then flattened between rollers to a rolled thickness of 0.7 mm.

The rolled stems were dried, packaged and transferred from the stemmery to the
30 tobacco production plant. At the tobacco production plant, the pre-rolled stems were first conditioned in a suitable conditioning device by contacting the stems with a stream of steam and water until the moisture content of the stems returned to about 34 % o.v. During this conditioning step, the rolled stems expanded to a mean thickness of about 0.9mm.

The moistened rolled stems were cut to an average cut width of 0.15 mm to achieve a
35 cross-sectional area of 0.135 square millimetres (mm²). The cut rolled stems were then

expanded and dried before being combined with cut tobacco lamina to form the cut filler. The cut rolled stems and tobacco lamina were blended to form a cut filler having 6 % by weight of the cut rolled stems.

The proportion of dust particles and large, heavy particles in the cut rolled tobacco stems produced in the process described above was determined in a suitable sieve test using screens having openings 500 micrometers and 3.35 mm, respectively. The filling power of the rolled tobacco stems (CCV) was also determined using the method described above. The results are shown in the table below.

Three comparative samples of cut rolled tobacco stems were produced using a similar process to that described above but where the tobacco stems were rolled to 0.9 mm, 0.5 mm or 0.3 mm, respectively. Comparative sample 1 corresponded to a sample of conventionally treated tobacco stems.

The cut width of the tobacco stems remained constant at 0.15 mm and therefore the cross-sectional area of the tobacco stems was in direct proportion to the mean thickness of the stems. The tobacco stems having a mean thickness of 0.9 mm had a greater cross-sectional area than the stems for use in cut fillers according to the present invention, whilst the tobacco stems having a mean thickness of 0.5 mm or 0.3 mm had a smaller cross-sectional area. For each comparative sample, the particle size distribution and the filling power was determined in the same way as for the sample according to the present invention. The results for each sample are shown in the table below. In each case, the values provided correspond to the mean value from 5 substantially identical samples.

	Sample according to the invention	Comparative sample 1	Comparative sample 2	Comparative sample 3
Mean thickness after rolling (mm)	0.7	0.9	0.5	0.3
Mean rolled thickness in cut filler (mm)	0.9	1.1	0.7	0.5
Stem cut width (mm)	0.15	0.15	0.15	0.15
Mean cross- sectional area (mm²)	0.135	0.165	0.105	0.075
Mean CCV (cm³/g)	6.5	6.1	6.2	6.5
% by weight of dust particles (<500 micrometers)	6.5	6.7	11.5	12.9
% by weight of large particles (>3.35 mm)	0.2	0.5	0.1	0.1

It can be seen from the table above that the filling power of the cut rolled tobacco stems is optimised at the 0.7 mm and 0.3 mm rolled thicknesses. However, comparative samples 2 and 3, the cut rolled stems have a significantly higher level of dust particles than in the 0.7 mm sample for use in cut fillers according to the invention.

Whilst the comparative sample 1 was found to have lower dust levels, the level of large and heavy particles was more than double that of the 0.7 mm sample for use in cut fillers according to the invention.

The measured values in the table above therefore illustrate that the 0.7 mm cut rolled stems (corresponding to stems having a final thickness of 0.9 mm) provide a balanced combination of improved filling power and reduced levels of dust particles and large particles.

CLAIMS

1. A tobacco cut filler for a smoking article comprising at least 5% by weight of cut rolled tobacco stems having a mean cut width of 0.1 mm to 0.2 mm and a mean cross-sectional area of 0.12 to 0.15 square millimetres.
2. A tobacco cut filler according to claim 1 comprising at least 10 % by weight of cut rolled tobacco stems.
3. A tobacco cut filler according to claim 1 or 2 comprising at least 20 % by weight of cut rolled stems.
4. A tobacco cut filler according to any preceding claim comprising between 5 % and 40 % by weight of cut rolled stems.
5. A tobacco cut filler according to any preceding claim wherein the cut rolled tobacco stems have a mean thickness of 0.8 mm to 1.0 mm.
6. A tobacco cut filler according to claim 5 wherein the cut rolled tobacco stems have a mean thickness of 0.9 mm.
7. A tobacco cut filler according to any preceding claim wherein the cut rolled tobacco stems have a filling power of at least 6.3 cubic centimetres per gram at a reference moisture value of 12.5 % oven volatiles.
8. A tobacco cut filler according to any preceding claim wherein the cut rolled tobacco stems have less than 7.5 % by weight of particles having a particle size of less than 500 micrometers.
9. A tobacco cut filler according to any preceding claim wherein the cut rolled tobacco stems have less than 0.3 % by weight of particles having a particle size greater than 3.35 mm.
10. A tobacco cut filler according to any preceding claim wherein the cut rolled tobacco stems have a substantially intact epidermal cellular structure.

-11-

11. A tobacco cut filler according to any preceding claim comprising between 5% and 40% cut rolled tobacco stems.
12. A tobacco cut filler according to any preceding claim comprising at least 60% by weight tobacco lamina having a mean cut width of 0.8 mm to 1.1 mm and a mean thickness of about 0.2 mm.
13. A tobacco cut filler according to claim 12 wherein the mean cut width of the cut rolled tobacco stems is within 0.05 mm of the mean thickness of the tobacco lamina.
14. A smoking article comprising a rod of the tobacco cut filler according to any of claims 1 to 13.

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2011/073789

A. CLASSIFICATION OF SUBJECT MATTER

INV. A24B5/16

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A24B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 418 706 A (KIM KI-HWAN [KR] ET AL) 6 December 1983 (1983-12-06) column 1, lines 13-22 column 5, lines 58-60 examples 1,2; tables 1,2	1-14
X	US 4 300 579 A (ULRICH JOERN) 17 November 1981 (1981-11-17) column 4, lines 3-23	1-14
X	US 4 211 243 A (AKAO TAKESHI [JP] ET AL) 8 July 1980 (1980-07-08) column 1, lines 5-26 column 4, lines 13-17 column 4, lines 43-46	1-14
	----- -/-	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 February 2012

Date of mailing of the international search report

05/03/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Kock, Søren

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2011/073789

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2009/076699 A1 (BRITISH AMERICAN TOBACCO AUSTR [AU]; HAMILTON GRAEME CHARLES [MY]; MOR) 25 June 2009 (2009-06-25) page 2, lines 10-16 page 3, lines 5-12 page 4, lines 17-27 page 6, lines 12-14 -----	1-14
A	DE 14 32 585 A1 (MOLINS ORGANISATION LTD) 28 November 1968 (1968-11-28) page 1, line 15 - page 2, line 3 page 9, lines 12-21; claim 1 -----	1-14
A	US 5 826 590 A (METZNER WOLFGANG [DE] ET AL) 27 October 1998 (1998-10-27) column 1, lines 13-29 column 4, lines 13-16 -----	1-14
A	WO 91/12736 A1 (GBE INTERNATIONAL PLC [GB]) 5 September 1991 (1991-09-05) page 10, upper half -----	1-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2011/073789

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4418706	A	06-12-1983	NONE
US 4300579	A	17-11-1981	AU 5701780 A 09-10-1980 BR 8002087 A 25-11-1980 CA 1123699 A1 18-05-1982 DE 2913823 A1 09-10-1980 GB 2048645 A 17-12-1980 US 4300579 A 17-11-1981
US 4211243	A	08-07-1980	JP 1119500 C 28-10-1982 JP 53104797 A 12-09-1978 JP 56001903 B 16-01-1981 US 4211243 A 08-07-1980
WO 2009076699	A1	25-06-2009	AU 2008338293 A1 25-06-2009 EP 2230950 A1 29-09-2010 WO 2009076699 A1 25-06-2009
DE 1432585	A1	28-11-1968	NONE
US 5826590	A	27-10-1998	NONE
WO 9112736	A1	05-09-1991	NONE