



(22) Date de dépôt/Filing Date: 2003/03/25

(41) Mise à la disp. pub./Open to Public Insp.: 2003/10/09

(45) Date de délivrance/Issue Date: 2017/11/07

(62) Demande originale/Original Application: 2 478 860

(30) Priorités/Priorities: 2002/03/26 (US60/367,948);
2002/03/26 (US60/367,950); 2002/03/26 (US60/367,945);
2002/03/26 (US60/367,946); 2002/03/26 (US60/367,975);
2002/03/26 (US60/367,949); 2002/12/23 (US10/329,033)

(51) Cl.Int./Int.Cl. *H04W 80/00* (2009.01),
G10L 19/18 (2013.01), *H04W 88/16* (2009.01)


(72) Inventeurs/Inventors:

CHITRAPU, PRABHAKAR R., US;
MENON, NARAYAN PARAPPIL, US;
OZLUTURK, FATIH M., US;
KIERNAN, BRIAN GREGORY, US;
RAHMAN, SHAMIN AKBAR, US;
CHAO, YI-JU, US;
KAZAKEVICH, LEONID, US;
HUNKELER, TERESA JOANNE, US

(73) Propriétaire/Owner:

(54) Titre : SYSTEME DE TELECOMMUNICATION SANS FIL DE RESEAU DE RADIO LOCAL DOTE D'UNE
PASSERELLE IP DE RESEAU D'ACCES RADIO ET METHODES

(54) Title: RLAN WIRELESS TELECOMMUNICATION SYSTEM WITH RAN IP GATEWAY AND METHODS



(57) Abrégé/Abstract:

A Radio Local Area Network (RLAN) includes a Radio Access Network Internet Protocol (RAN IP) gateway that enables connectivity to the public Internet. The system may serve as a stand-alone system or be incorporated into a UMTS used with conventional Core Network, particularly for tracking and implementing AAA functions in the Core Network.

(73) Propriétaires(suite)/Owners(continued):SIGNAL TRUST FOR WIRELESS INNOVATION, US

(74) Agent: GOWLING WLG (CANADA) LLP

ABSTRACT

A Radio Local Area Network (RLAN) includes a Radio Access Network Internet Protocol (RAN IP) gateway that enables connectivity to the public Internet. The system may serve as a stand-alone system or be incorporated into a UMTS used with conventional Core Network, particularly for tracking and implementing AAA functions in the Core Network.

[0001] RLAN WIRELESS TELECOMMUNICATION
SYSTEM WITH RAN IP GATEWAY AND METHODS

[0002] FIELD OF INVENTION

[0003] The present invention relates to wireless telecommunication systems and in particular to Time Division Duplex - Radio Local Area Network (TDD-RLAN) Code Division Multiple Access (CDMA) systems and connection and communication of such systems with the Internet.

[0004] BACKGROUND

[0005] Wireless telecommunication systems are well known in the art. Wireless systems require an available bandwidth in which to operate. Typically, the permission to use a portion of the available spectrum for wireless communication for a particular geographic region is obtained from an appropriate governmental unit of the physical territory in which the wireless communications are to be conducted. In order to make efficient use of limited spectrum available for operation of a wireless telecommunication system, Code Division Multiple Access (CDMA) systems have been developed which include Time Division Duplex (TDD) modes which provide a very flexible framework for providing concurrent wireless communication services. Supported wireless communication services can be any of a variety of types including voice, fax, and a host of other data communication services.

[0006] In order to provide global connectivity for CDMA systems, standards have been developed and are being implemented. One current standard in widespread use is known as Global System for Mobile Telecommunications (GSM). This was followed by the so-called Second Generation mobile radio system standards (2G) and its revision (2.5G). Each one of these standards sought to improve upon the prior standard with additional features and enhancements. In January 1998, the European Telecommunications Standard Institute – Special Mobile Group (ETSI SMG) agreed on a radio access scheme for Third Generation Radio Systems called Universal Mobile Telecommunications Systems (UMTS). To further implement the UMTS standard, the Third

Generation Partnership Project (3GPP) was formed in December 1998. 3GPP continues to work on a common third generational mobile radio standard.

[0007] A typical UMTS system architecture in accordance with current 3GPP specifications is depicted in Figures 1 and 2. The UMTS network architecture includes a Core Network (CN) interconnected with a UMTS Terrestrial Radio Access Network (UTRAN) via an interface known as IU which is defined in detail in the current publicly available 3GPP specification documents.

[0008] The UTRAN is configured to provide wireless telecommunication services to users through User Equipments (UEs) via a radio interface known as UU. The UTRAN has base stations, known as Node Bs in 3GPP, which collectively provide for the geographic coverage for wireless communications with UEs. In the UTRAN, groups of one or more Node Bs are connected to a Radio Network Controller (RNC) via an interface known as Iub in 3GPP. The UTRAN may have several groups of Node Bs connected to different RNCs, two are shown in the example depicted in Figure 1. Where more than one RNC is provided in a UTRAN, inter-RNC communication is performed via an Iur interface.

[0009] A UE will generally have a Home UMTS Network (HN) with which it is registered and through which billing and other functions are processed. By standardizing the Uu interface, UEs are able to communicate via different UMTS networks that, for example, serve different geographic areas. In such case the other network is generally referred to as a Foreign Network (FN).

[0010] Under current 3GPP specifications, the Core Network of a UE's HN serves to coordinate and process the functions of Authentication, Authorization and Accounting (AAA functions). When a UE travels beyond its Home UMTS Network, the HN's Core Network facilitates the UE's use of a Foreign Network by being able to coordinate the AAA functions so that the FN will permit the UE to conduct communications. To assist in implementing this activity, the Core Network includes a Home Location Register (HLR) which tracks the UEs for which it is the HN and a Visitor Location Register (VLR). A Home Service Server (HSS) is provided in conjunction with the HLR to process the AAA functions.

[0011] Under current 3GPP specifications, the Core Network, but not the UTRAN, is configured with connectivity to external systems such as Public Land Mobile Networks (PLMN), Public Switch Telephone Networks (PSTN), Integrated Services Digital Network (ISDN) and other Real Time (RT) services via an RT service interface. A Core Network will also support Non-Real Time services with the Internet. External connectivity of the Core Network to other systems, enables users using UEs to communicate via their Home UMTS Network, beyond the area served by the HN's UTRAN. Visiting UEs can likewise communicate via a visited UMTS Network, beyond the area served by the visited UMTS's UTRAN.

[0012] Under current 3GPP specifications, the Core Network provides RT service external connectivity via a Gateway Mobile Switching Center (GMSC). The Core Network provides NRT service, known as General Packet Radio Service (GPRS), external connectivity via a Gateway GPRS Support Node (GGSN). In this context, a particular NRT service may actually appear to a user to be a real time communication due to the communication speed and associated buffering of the TDD data packets forming the communication. One example of this is voice communication via the Internet which can appear to the user as a normal telephone call conducted by a switching network, but is actually being conducted using an Internet Protocol (IP) connection which provides Packet data Service.

[0013] A standard interface known as GI is generally used between a CN's GGSN and the Internet. The GI interface can be used with Mobile Internet Protocols, such as Mobile IP v4 or Mobile IP v6 as specified by the Internet Engineering Task Force (IETF).

[0014] Under current 3GPP specifications, to provide support for both RT and NRT services from external sources for radio linked UEs in a 3GPP system, the UTRAN must properly interface with the CN which is the function of the Iu interface. To do this, the Core Network includes a Mobile Switching Centre (MSC) that is coupled to the GMSC and a Serving GPRS Support Node (SGSN) that is coupled to the GGSN. Both are coupled with the HRL and the MSC is usually combined with the Visitor Location Register (VLR).

[0015] The Iu interface is divided between an interface for Circuit Switched communications (Iu-CS) and an interface for packet data via Packet Switched communications (Iu-PS). The MSC is connected to the RNCs of the UTRAN via the Iu-CS interface. The Serving GPRS Support Node (SGSN) is coupled to the UTRAN's RNCs via the Iu-PS interface for Packet Data Services.

[0016] The HLR/HSS is typically interfaced with the CS side of the Core Network, MSC and GMSC via an interface known as Gr which supports AAA functions through a Mobile Application Part (MAP) Protocol. The SGSN and the GGSN of the CN are connected using interfaces known as Gn and Gp.

[0017] Common to 3GPP systems and other systems which utilize TDD-CDMA telecommunications, such as some GSM systems, is the aforementioned division of connectivity between the radio network and the Core Network. In general, the radio network, i.e. the UTRAN in 3GPP, communicates via a wireless interface with UEs and the Core Network communicates with external systems via RT and NRT service connections. Applicants have recognized this standardized type of architecture is most likely the result of the processing of the AAA functions in the Core Network. However, applicants have further recognized that even if the AAA functions are to be maintained in the Core Network, significant advantages and benefits can be obtained by providing direct connectivity from a TDD-CDMA radio network to the Internet.

[0018] In particular, Applicants have recognized that the existing separation of functions of the Iu interface defined in 3GPP for Circuit Switched (CS) communications used with Real Time services (Iu-CS interface) and defined in 3GPP for Packet Switch (PS) service used with Non-Real Time services (Iu-PS interface), enables one to easily provide an IP Gateway in the UTRAN for enabling the UTRAN to direct connectivity to the Internet bypassing use of a Core Network for this function. Moreover, as a result, Applicants have recognized that by permitting direct access to the Internet from the UTRAN, a Radio Local Area Network is defined that can provide significant benefits and advantages for use with or without a Core Network.

[0019] Further detail of a typical 3GPP system is illustrated in Figure 3. The UTRAN segment of a conventional UMTS architecture is split it into two traffic planes known as the C- and U- planes. The C-plane carries control (signaling) traffic, and the U-plane transports user data. The over-the-air segment of the UTRAN involves two interfaces: the Uu interface between UE and Node B, and the Iub interface between the Node B and RNC. As noted above, the back-end interface between the RNC and core network is referred to as the Iu interface, split into the Iu-CS for the circuit-switched connection into the MSC, and the Iu-PS for the packet-switched connection into the SGSN.

[0020] The most significant signaling protocol on the over-the-air segment of the UTRAN is Radio Resource Control (RRC). RRC manages the allocation of connections, radio bearers and physical resources over the air interface. In 3GPP, RRC signaling is carried over the Radio Link Control (RLC) and Medium Access Control (MAC) UMTS protocols between the UE and RNC. Overall, the RNC is responsible for the allocation/de-allocation of radio resources, and for the management of key procedures such as connection management, paging and handover. Over the Iub interface, RRC/RLC/MAC messaging is typically carried on a Transport Layer via Asynchronous Transfer Mode (ATM), using the ATM Adaptation Layer Type 5 (AAL5) protocol over the ATM physical layer with intermediary protocols, such as Service Specific Co-ordination Function (SSCF) and the Service Specific Connection Oriented Protocol SSCOP, being used above AAL5.

[0021] U-plane data (e.g. speech, packet data, circuit-switched data) uses the RLC/MAC layers for reliable transfer over the air interface (between UE and RNC). Over the Iub segment, this data flow (user data/RLC/MAC) occurs over UMTS-specified frame protocols using the ATM Adaptation Layer Type 2 (AAL2) protocol over the ATM physical layer running (AAL2/ATM).

[0022] The Iu interface carries the Radio Access Network Application Part (RANAP) protocol. RANAP triggers various radio resource management and mobility procedures to occur over the UTRAN, and is also responsible for managing the establishment/release of terrestrial bearer connections between the

RNC and SGSN/MSC. RANAP is carried over AAL5/ATM, with intermediary Signaling System 7 (SS7) protocols, such as Signaling Connection Control Part, Message Transfer Part (SCCP/MTP) on top of SSCF and the Service Specific Connection Oriented Protocol (SSCOP), being used above AAL5. Internet Protocol is typically used over AAL5/ATM for the Iu-PS interface so that the intermediate Stream Control Transmission Protocol (SCTP) is then used over IP. Where multiple RNCs exist in a UTRAN which have an Iur interface, IP is also commonly used over ATM and intermediate protocols include SSCP, SCTP and the Message Transfer Part level 3 SCCP adaptation layer of SS7 (M3UA) that have been developed by IETF.

[0023] For the U-Plane, between the UTRAN and the CN, circuit-switched voice/data traffic typically flows over AAL5/ATM, via the Iu-CS interface, between the RNC and MSC. Packet-switched data is carried over the Iu-PS interface between the RNC and SGSN, using the GPRS Tunneling Protocol (GTP) running over the User Data Protocol for the Internet Protocol (UDP/IP) over AAL5/ATM.

[0024] Applicants have recognized that this architecture can be improved upon in connection with providing direct IP connectivity for the UTRAN.

[0025] SUMMARY

[0026] The present invention provides for a Radio Local Area Network (RLAN) which includes a Radio Access Network Internet Protocol (RAN IP) gateway that enables connectivity to the public Internet. The system may serve as a stand-alone system or be incorporated into a UMTS used with conventional Core Network, particularly for tracking and implementing AAA functions in the Core Network.

[0027] The RLAN provides concurrent wireless telecommunication services for a plurality of user equipments (UEs) between UEs and/or the Internet. The RLAN includes at least one base station that has a transceiver configured to conduct code division multiple access (CDMA) wireless

communications preferably time division duplex (TDD) CDMA wireless communications, with UEs in a selected geographic region. The RLAN also has at least one controller that is coupled with a group of base stations, which includes the base station. The controller controls the communications of the group of base stations. A novel Radio Access Network Internet Protocol (RAN IP) Gateway (RIP GW) is coupled with the controller. The RAN IP Gateway has a Gateway General Packet Radio Service (GPRS) Support Node (GGSN) with access router functions for connection with the Internet.

[0028] The RLAN can include a plurality of base stations, each having a transceiver configured with a Uu interface preferably configured to conduct time division duplex (TDD) wideband code division multiple access (W-CDMA) wireless communications with UEs in a selected geographic region. The RLAN can also include a plurality of controllers that are each coupled with a group of base stations.

[0029] Preferably, the RAN IP Gateway has a Serving GPRS Support Node (SGSN) that is coupled with one or more controllers in the RLAN. Preferably, the controllers are Radio Network Controller (RNCs) in accordance with 3GPP specification. Preferably, the RNCs are coupled with the base stations using a stacked, layered protocol connection having a lower transport layer configured to use Internet Protocol (IP). Where the RLAN has multiple RNCs, the RNCs are preferably coupled to each other using a stacked, layered protocol connection having a lower transport layer configured to use Internet Protocol (IP).

[0030] Methods of mobility management using a radio local area network (RLAN) are disclosed for providing concurrent wireless telecommunication services for a plurality of UEs where an associated core network (CN) supports Authentication, Authorization and Accounting (AAA) functions of UEs. A RLAN conducts TDD-CDMA wireless communications with UEs in a RLAN service region. The RLAN has a RAN IP Gateway that has a GPRS connection with the Internet and is configured to communicate AAA function information to the

associated CN.

[0031] In one method, a wireless connection is established between a first UE within the RLAN service region and a second UE outside of the RLAN service region for conducting a communication of user data. AAA functions for said

communication between said first and second UEs are conducted using the Core Network. The GPRS connection with the Internet is used for transporting user data of the communication between the first and second UEs. The method may include continuing the wireless communication between the first and second UEs as the second UE moves from outside to within the RLAN service region, where use of the GPRS connection with the Internet for transporting user data is discontinued. The method can further include continuing the wireless communication between the first and second UEs as either the first or second UE moves from within to outside the RLAN service region by resuming use of the GPRS connection with the Internet for transporting user data.

[0032] In another method, a wireless connection is established between first and second UEs within the RLAN service region for conducting a communication of user data. AAA functions for the communication between the first and second UEs are conducted using the Core Network. The wireless communication between the first and second UEs is continued as either the first or second UE moves from within to outside the RLAN service region by using the GPRS connection with the Internet for transporting user data of the continued communication.

[0033] A further method of mobility management is provided where the associated CN supports AAA functions of home UEs and the GPRS connection of the RAN IP Gateway is configured to tunnel AAA function information through the Internet to the Core Network. A wireless connection is established between a home UE and a second UE for conducting a communication of user data. AAA functions for the communication are conducted using the Core Network by using the GPRS connection with the Internet to tunnel AAA function information through the Internet to the Core Network.

[0034] This method may be used where the wireless connection is established when either the home UE or the second UE is within or outside the RLAN service region. Where one is within and the other is outside of the RLAN service region, the GPRS connection with the Internet is used for transporting user data of the communication between the home and second UEs.

[0035] This method may further include continuing the wireless communication between the home and second UEs as one moves such that both are outside or both are within the RLAN service region, where the use of said General Packet Radio Service (GPRS) connection with the Internet for transporting user data is discontinued. The method may further include continuing the wireless communication between the home and second UEs as either the home or second UE moves so that one is within and the other is outside the RLAN service region by using the GPRS connection with the Internet for transporting user data for the continued communication.

[0036] In one aspect of the invention, the RLAN has as control means one or more U-Plane and C-Plane Servers coupled with base stations. The U-Plane Server(s) are configured to control user data flow of base station communications. The C-Plane Server(s) are configured to control signaling for base stations communication. Preferably, the RAN IP Gateway has a SGSN that is coupled with the U-plane Servers and at least one C-Plane Server. Preferably, the U-Plane Servers and C-Plane Servers are coupled with each other, the base stations, and the RAN IP Gateway using stacked, layered protocol connections having a lower transport layer configured to use Internet Protocol (IP).

[0037] Optionally, a Voice Gateway having a Pulse Code Modulation (PCM) port for external connection may be provided for the RLAN. The Voice Gateway is preferably coupled with a U-plane and a C-Plane Server (or an RNC where RNCs are used) using stacked, layered protocol connections having a lower transport layer configured to use Internet Protocol (IP).

[0038] In another aspect of the invention, the RLAN has one or more Radio Network Controllers (RNCs) coupled with base stations and a RAN IP Gateway to which at least one RNC is coupled via an Iu-PS interface using a stacked, layered protocol connection having a lower transport layer configured to use Internet Protocol (IP). Preferably, the RNCs are coupled the base stations and each other using stacked, layered protocol connections having a lower transport layer configured to use Internet Protocol (IP). Preferably, each base station has a transceiver configured with a Uu interface for conducting time division duplex

(TDD) wideband code division multiple access (W-CDMA) wireless communications with UEs in a selected geographic region and the RAN IP Gateway has a SGSN that is coupled with the RNCs.

[0039] In another aspect of the invention, the RLAN supports voice communications over IP and has a RAN IP Gateway having a GGSN for connection with the Internet that passes compressed voice data. The RLAN is preferably connected to the Internet via an internet service provider (ISP) that has a voice gateway that converts compressed voice data and Pulse Code Modulation (PCM) signaling using a known compression protocol, which may or may not be the type of voice compression data used by UEs conducting wireless communications with the RLAN.

[0040] Where the UEs use one compression protocol and the RLAN is connected with the Internet via an ISP having a voice gateway that converts compressed voice data and PCM signaling using a different compression protocol, the RLAN includes a voice data converter for converting between compressed voice data of the two different compression protocols. Preferably, the RAN IP Gateway includes the voice data converter which is, for example, configured to convert between AMR compressed voice data and G.729 compressed voice data. The RLAN may be configured with U-Plane and C-Plane Servers or RNCs, but preferably all component interfaces within the RLAN use stacked, layered protocol connections having a lower transport layer configured to use Internet Protocol (IP).

[0041] The invention further provides a telecommunication network having one or more radio network for providing concurrent wireless telecommunication services for a plurality of UEs and an associated CN for supporting AAA functions of UEs for which the telecommunication network is a Home Network. One or more of the radio networks is a RLAN having a RAN IP Gateway that has a GGSN configured with a GI interface for connection with the Internet and is configured to communicate AAA function information to the CN. Preferably, the RLANs each have one or more base stations that have a transceiver for conducting TDD-CDMA wireless communications with UEs in a selected

geographic region. Preferably, the RLANs have controllers coupled with the base stations. Preferably, the RLANs' RAN IP Gateways have a SGSN that is coupled with the respective controllers.

[0042] The RLAN may be configured without a direct CN connection where the RAN IP Gateway is configured for communication of AAA function information with the CN by tunneling data through an Internet connection.

Alternatively, the RAN IP Gateway has a coupling with the CN for communication of AAA function information with the CN via a limited connection, such as a Radius/Diameter or MAP supporting connection or a conventional Iu-CS interface, or a full conventional Iu interface.

[0043] Preferably, the RAN IP Gateways have GGSNs configured for connection with the Internet via a GI interface. For mobile support, the GI interface is preferably configured with Mobile IP v4 or Mobile IP v6.

[0043A] According to an embodiment of the present disclosure there is provided a home radio local area network (RLAN) apparatus. The apparatus comprises: a home node B component including a transceiver configured to communicate a third generation partnership project (3GPP) wireless data with at least one user equipment (UE); a controller component in communication with the home node B component; and a radio access network internet protocol (RAN IP) gateway component. The RAN IP gateway is configured to: receive data in a 3GPP wireless format from the at least one UE and output a formatted data as internet protocol (IP) formatted packets, route the IP formatted packets directly through an Internet interface with serving general packet radio service (GPRS) support node (SGSN) functions, and route authentication, authorization and accounting (AAA) information, related to the IP formatted packets routed directly through the Internet interface, to a 3GPP core network through a non-Internet interface.

[0043B] According to another embodiment of the present disclosure there is provided a radio local area network (RLAN) apparatus. The RLAN apparatus comprises: a base station component including a transceiver configured to

communicate a third generation partnership project (3GPP) wireless data with at least one user equipment (UE); a controller component in communication with the base station component; and a radio access network internet protocol (RAN IP) gateway component. The RAN IP gateway component is configured to: convert data, received in a 3GPP wireless format from the at least one UE, to internet protocol (IP) packets, output formatted data as IP formatted packets, route the IP formatted packets directly through an Internet interface with serving general packet radio service (GPRS) support node (SGSN) functions, and route authentication, authorization and accounting (AAA) information, related to the IP formatted packets routed through the Internet interface, to a 3GPP core network through a non-Internet interface.

[0043C] According to another embodiment of the present disclosure there is provided a method for a radio local area network (RLAN) apparatus that includes a base station component having a transceiver configured to communicate a third generation partnership project (3GPP) wireless data with at least one user equipment (UE) and a radio access network internet protocol (RAN IP) gateway component configured with serving general packet radio service (GPRS) support node (SGSN) functions, the RAN IP Gateway having an Internet interface and a non-Internet interface. The method comprises: receiving, from the at least one UE, wireless data in a 3GPP wireless format at the RAN IP gateway; converting data received in a 3GPP wireless format from the at least one UE to internet protocol (IP) packets; providing the IP packets through the Internet interface to bypass a core network; and transmitting authentication, authorization and accounting (AAA) information, related to the IP packets, directly through the non-Internet interface to the core network.

[0043D] According to another embodiment of the present disclosure there is provided a home radio local area network (RLAN) node B comprising: a transceiver configured to operate using internet protocol (IP) over a third generation partnership project (3GPP) wireless data communication channels; an IP network connection configured to route IP packets to a gateway apparatus

such that the gateway apparatus route the IP data directly over the Internet to a cellular core network, wherein the node B includes a processor configured to communicate with the gateway apparatus; and a radio access network internet protocol (RAN IP) gateway component configured with serving general packet radio service (GPRS) support node (SGSN) functions to route the IP packets.

[0043E] According to another embodiment of the present disclosure there is provided a home radio local area network (RLAN) apparatus comprising: a transceiver configured to operate using internet protocol (IP) over a third generation partnership project (3GPP) wireless data communication channels; a node B including a processor configured to communicate with a gateway apparatus configured to route IP data through an Internet interface, and to route authentication, authorization and accounting (AAA) data, related to the IP data, directly through a non-Internet interface in a format that directs the AAA data to a core network; and an IP interface configured to provide the IP data directly over the Internet by communicating with the gateway apparatus.

[0043F] According to another embodiment of the present disclosure there is provided a method implemented in a home radio local area network (RLAN) node B. The method comprises: receiving internet protocol (IP) data transmitted using wireless third generation partnership project (3GPP) data communication channels; communicating the IP data from the node B over an IP network interface to a gateway apparatus; and routing the IP data directly over the Internet via the gateway apparatus.

[0043G] According to another embodiment of the present disclosure there is provided a method comprising: receiving data in a third generation partnership project (3GPP) wireless format from at least one user equipment (UE); routing the data in internet protocol (IP) formatted packets directly through an Internet interface with serving general packet radio service (GPRS) support node (SGSN) functions to bypass a core network; and tunneling authentication, authorization, and accounting (AAA) information directly through the Internet interface to the core network.

[0043H] According to another embodiment of the present disclosure there is provided an apparatus comprising: a radio component configured to: receive data in a third generation partnership project (3GPP) wireless format from at least one user equipment (UE), route the data in internet protocol (IP) formatted packets directly through an Internet interface with serving general packet radio service (GPRS) support node (SGSN) functions to bypass a core network, and tunnel authentication, authorization and accounting (AAA) information directly through the Internet interface to the core network.

[0044] Other objects and advantages of the present invention will be apparent to those skilled in the art from the following detailed description and the drawings.

[0045] BRIEF DESCRIPTION OF THE DRAWING(S)

[0046] Figure 1 is a graphic illustration of a conventional UMTS network in accordance with current 3GPP specification.

[0047] Figure 2 is a block diagram showing various components and interfaces of the network illustrated in Figure 1.

[0048] Figure 3 is a schematic diagram of the conventional network illustrated in Figures 1 and 2 indicating layered stacked protocols of the various component interfaces in both signaling and user data planes.

[0049] Figure 4 is a graphic illustration of a UMTS network including a RLAN with a direct Internet link in accordance with the teachings of the present invention.

[0050] Figure 5 is a block diagram showing various components of the network shown in Figure 4.

[0051] Figure 6 is a block diagram showing a variation of the network where the RLAN has no direct connection with the UMTS Core Network.

[0052] Figure 7 is a schematic illustration of signaling data flow in the UMTS network illustrated in Figure 6.

[0053] Figure 8 is a graphic illustration of a second variation of the UMTS network illustrated in Figure 4 wherein the RLAN has a first type of limited connection with the UMTS Core Network.

[0054] Figure 9 is a graphic illustration of a second variation of the UMTS network illustrated in Figure 4 wherein the RLAN has a second type of limited connection with the UMTS Core Network.

[0055] Figures 10A and 10B illustrate two variations of IP packet data flow for the networks shown in Figures 4, 8 and 9 wherein Mobile IP v4 protocol is implemented by the RLAN.

[0056] Figures 11A and 11B illustrate two variations of IP packet data flow for the networks shown in Figures 4, 8 and 9 wherein Mobile IP v6 protocol is implemented by the RLAN.

[0057] Figure 12 is a schematic illustration of preferred signaling plane and user plane interfaces within a RLAN made in accordance with the teachings of the present invention.

[0058] Figure 13 is a schematic illustration of a RLAN having a single Radio Network Controller in accordance with the teachings of the present invention.

[0059] Figure 14 is a schematic illustration of a RLAN having multiple Radio Network Controllers made in accordance with the teachings of the present invention.

[0060] Figure 15 is an illustrated diagram of an alternate configuration of an RLAN having separate servers for user data and control signals and also an optional voice gateway made in accordance with the teachings of the present invention.

[0061] Figure 16 is a block diagram of components of the RLAN illustrated in Figure 15.

[0062] Figure 17 is a schematic diagram illustrating a preferred protocol stack for the control plane interfaces of a RLAN made in accordance with the teachings of the present invention.

[0063] Figure 18 is a schematic diagram illustrating a preferred protocol stack for the user plane interfaces of a RLAN made in accordance with the teachings of the present invention.

[0064] Figures 19, 20 and 21 are schematic diagrams illustrating three variations of interface protocol stacks in the user plane for supporting voice communication between a UE having a wireless connection with an RLAN and an ISP connected to the RLAN which has a voice gateway.

[0065] Figure 22 is a schematic diagram illustrating a variation of interface protocol stacks in the control plane for supporting voice communication between a UE having a wireless connection with an RLAN and an ISP connected to the RLAN which has a voice gateway.

[0066] TABLE OF ACRONYMS

2G	Second Generation
2.5G	Second Generation Revision
3GPP	Third Generation Partnership Project
AAA functions	Authentication, Authorization and Accounting functions
AAL2	ATM Adaptation Layer Type 2
AAL5	ATM Adaptation Layer Type 5
AMR	A type of voice data compression
ATM	Asynchronous Transfer Mode
CDMA	Code Division Multiple Access
CN	Core Network
CODECs	Coder/Decoders
C-RNSs	Control Radio Network Subsystems
CS	Circuit Switched
ETSI	European Telecommunications Standard Institute
ETSI SMG	ETSI – Special Mobile Group
FA	Forwarding Address
FN	Foreign Network
G.729	A type of voice data compression
GGSN	Gateway GPRS Support Node
GMM	GPRS Mobility Management
GMSC	Gateway Mobile Switching Center

GPRS	General Packet Radio Service
GSM	Global System for Mobile Telecommunications
GTP	GPRS Tunneling Protocol
GW	Gateway
H.323/SIP	H.323 Format for a Session Initiated Protocol
HLR	Home Location Register
HN	Home Network
HSS	Home Service Server
IP	Internet Protocol
ISDN	Integrated Services Digital Network
ISP	Internet Service Provider
Iu-CS	Iu sub Interface for Circuit Switched service
Iu-PS	Iu sub Interface for Packet Switched service
IWU	Inter Working Unit
M3UA	Message Transfer Part Level 3 SCCP SS7 Adaptation Layer
MAC	Medium Access Control
MAP	Mobile Application Part
MSC	Mobile Switching Centre
NRT	Non-Real Time
PCM	Pulse Code Modulation
PLMN	Public Land Mobile Network
PS	Packet Switched
PSTN	Public Switch Telephone Network
RANAP	Radio Access Network Application Part
RAN IP	Radio Access Network Internet Protocol
RIP GW	RAN IP Gateway
RLAN	Radio Local Area Network
RLC	Radio Link Control
RNC	Radio Network Controller
RRC	Radio Resource Control
RT	Real Time
SCCP/MTP	Signaling Connection Control Part, Message Transfer Part
SGSN	Serving GPRS Support Node
SCTP	Stream Control Transmission Protocol
SM	Session Management
SMS	Short Message Service
S-RNS	Serving Radio Network Subsystems
SS7	Signaling System 7
SSCF	Service Specific Coordination Function
SSCOP	Service Specific Connection Oriented Protocol
TDD	Time Division Duplex
UDP/IP	User Data Protocol for the Internet Protocol
UE	User Equipment
UMTS	Universal Mobile Telecommunications System

UTRAN	UMTS Terrestrial Radio Access Network
VLR	Visitor Location Register

[0067] DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

[0068] With reference to Figure 4, there is shown a modified Universal Mobile Terrestrial System (UMTS) network having a Radio Local Area Network (RLAN) with a direct Internet connection. As shown in Figure 5, the RLAN employs base stations to communicate via a wireless radio interface with the various types of User Equipments (UEs). Preferably the base stations are of the type specified in 3GPP as node Bs. A radio controller is coupled to the base stations to control the wireless interface. Preferably the radio controller is a Radio Network Controller (RNC) made in accordance with 3GPP specification. Various combinations of Node Bs and RNCs may be employed as used in a conventional 3GPP UTRAN. Collectively, the geographic ranges of the wireless communications conducted with the base stations of the RLAN defines the RLAN's service coverage area.

[0069] Unlike a conventional UTRAN, the RLAN of the present invention includes a Radio Access Network Internet Protocol (RAN IP) gateway which provides connectivity for the RLAN outside its service coverage area, i.e. the geographic area served by the wireless communication with its base stations. As illustrated in Figures 4 and 5, the RAN IP gateway has a direct Internet connection and may have the standard direct UMTS network connection through an Iu interface with an associated Core Network. Alternatively, as illustrated in Figure 6, the direct interface between an associated Core Network and the RAN IP gateway may be omitted so that the RAN IP Gateway can have only a direct connection with the Internet. In such case, as illustrated in Figure 7, the RLAN of the present invention may still form a part of a UMTS by the tunneling of control and AAA function information to a Core Network which serves as its Home CN.

[0070] Figures 8 and 9 illustrate two separate versions of an RLAN made in accordance with the teachings of the present invention wherein the RAN IP Gateway is configured with a control signal port for establishing a limited direct

connection with its Home UMTS Core Network. In particular, the limited connectivity transports information needed to provide AAA function support for the CN.

[0071] The RAN IP Gateway control signal port may be configured, as illustrated in Figure 8, to provide control signal data using radius/diameter based access in which case the core network includes an Inter Working Unit (IWU) as specified in 3GPP which converts AAA function information into conventional Mobile Application Part (MAP) signaling for connection with the HSS/HLR of the Core Network. Alternatively, as illustrated in Figure 9, the RAN IP Gateway control signal port can be configured as a subset of a standard Gr interface which supports MAP signaling which can be directly used by the HSS/HLR of the CN.

[0072] Preferably, the RAN IP Gateway employs a standard GI interface with the Internet and can be utilized as a stand-alone system without any association with a Core Network of a UMTS. However, in order to support mobility management with roaming and hand-over services available for subscriber UEs of the RLAN, an AAA function connection with a Core Network, such as by way of the various alternatives illustrated in Figures 7, 8 and 9, is desirable. In such case, in addition to a standard GI interface between the RAN IP Gateway of the RLAN and the Internet, a mobile IP protocol is supported. Preferred examples of such mobile IP protocols are the Mobile IP v4 protocol and the Mobile IP v6 protocol as specified by IETF.

[0073] Figure 10A illustrates IP packet data flow for a communication between a first UE having a wireless connection with the RLAN and a second UE outside the wireless service region of the RLAN where Mobile IP v4 is implemented on the GI interface between the RAN IP Gateway and the Internet. In such case, user data from the first UE is sent in IP packet format from the RAN IP Gateway of the RLAN through the Internet to the address provided by the second UE. The second UE communications are directed to the Home Address of the first UE which is maintained at the Core Network since in this example the first UE has the CN as its Home CN. The CN receives the IP data packets from the second UE and then the CN forwards the IP packets to the

current location of the first UE which is maintained in the CN's HLR as the Forwarding Address (FA) of the first UE.

[0074] In this example, since the first UE is "home", the CN tunnels the IP Packets through the Internet to the RAN IP gateway for communication to the first UE. In the case of the first UE traveling outside of the RLAN, its location will be registered with the Core Network and the data packets directed to the address where the first UE is currently located be used by the core network to direct the IP packet data to the current location of the first UE.

[0075] Figure 10B illustrates an alternate approach where Mobile IP v4 is implemented on the GI interface using with reverse path tunneling such that the RLAN directs the IP packets of the first UE's user data to the Home CN where they are relayed to the second UE in a conventional manner.

[0076] When the RLAN has connectivity using a GI interface that implements Mobile IP v6, the IP packet data exchange between the first UE and the second UE will contain binding updates, as illustrated in Figure 11A, which will reflect any redirection of the IP packets needed for hand-over. Figure 11B illustrates an alternative approach using a GI interface implementing mobile IP v6 that includes tunneling between the RLAN and the Home CN. In such case, the CN directly tracks location information of the first UE and the second UE may communicate with the first UE's Home CN in any type of conventional manner.

[0077] With reference to Figure 12, there is shown the construction of preferred interfaces between the components of the RLAN of the present invention. The UE interface between the RLAN via the base station, Node B, is preferably a standard Uu interface for connection with UEs as specified by 3GPP. An Iub interface between each Node B and RNC is preferably implemented both in the control plane and the user data plane as a layered stacked protocol having Internet Protocol (IP) as the transport layer. Similarly at least a subset of an Iu-PS interface is preferably provided between an RNC and the RAN IP Gateway that is a layered stacked protocol having IP as the transport layer.

[0078] In a conventional UMTS where SS7 is implemented over ATM, the MTP3/SSCF/SSCOP layers help SCCP, which is the top layer of the SS7 stack, to plug onto an underlying ATM stack. In the preferred IP approach used in conjunction with the present invention, the M3UA/SCTP stack helps SCCP connect onto IP. Essentially, the M3UA/SCTP stack in the preferred IP-based configuration replaces the MTP3/SSCF/SSCOP layers that are used in the conventional SS7-over-ATM approach. The specific details of these standard protocol stack architecture are defined in the IETF (Internet) standards. The use of IP in lieu of ATS enables cost-savings as well as PICO cells for office and campus departments.

[0079] Where the RLAN has multiple RNCs, the RNCs can be interfaced via an Iur interface having layered stacked protocols for both the signaling plane and user plane using an IP transport layer. Each RNC is connected to one or more Node Bs which in turn serve in plurality of UEs within respective geographic areas that may overlap to enable intra-RLAN service region handover.

[0080] Handover of a UE communication with one Node B within the RLAN to another Node B within the RLAN, intra-RLAN handover, is conducted in the conventional manner specified in 3GPP for intra-UTRAN handover. However, when a UE communicating with a Node B of the RLAN moves outside the RLAN service region, handover is implemented via the RAN IP gateway utilizing IP packet service, preferably, implemented with Mobile IP v4 or Mobile IP v6 as discussed above.

[0081] Figure 13 illustrates the subcomponents of a preferred RLAN in accordance with the present invention. The RNC can be divided into standard Control and Serving Radio Network Subsystems (C-RNSs and S-RNSs) connected by an internal Iur interface. In such a configuration, the S-RNS functions are coupled to a SGSN subcomponent of the RAN IP gateway which supports a subset of the standard SGSN functions, namely, GPRS Mobility Management (GMM), Session Management (SM) and Short Message Service (SMS). The SGSN subcomponent interfaces with a GGSN subcomponent having a subset of a

standard GGSN functions including an access router and gateway functions support for the SGNS subcomponent functions and a GI interface with mobile IP for external connectivity to the Internet. The SGSN subcomponent interface with the GGSN subcomponent is preferably via modified Gn/Gp interface, being a subset of the standard Gn/Gp interface for a CN's SGNS and GGSN.

[0082] Optionally, the RAN IP Gateway has an AAA function communication subcomponent that is also connected to the SGSN subcomponent and provides a port for limited external connectivity to an associated CN. The port supporting either a Gr interface or a Radius/Diameter interface as discussed above in connection with Figures 8 and 9.

[0083] As shown in Figure 14, multiple RNCs of the RLAN can be provided coupled with the SGSN subcomponent by an Iu-PS interface which includes sufficient connectivity to support the functions of the SGSN subcomponent. Where multiple RNCs are provided, they are preferably coupled by a standard Iur interface which utilizes an IP transport layer.

[0084] The use of IP for the transport layer of the various components of the RLAN readily lends itself to implementing the RNC functions in separate computer servers to independently process the user data of communications and the signaling as illustrated in Figure 15. Referring to Figure 16, there is a component diagram where the radio control means is divided between U-plane and C-plane servers. In addition to the basic RLAN components, an optional Voice Gateway is also illustrated in Figures 15 and 16.

[0085] Each Node B of the RLAN has a connection using an IP transport layer with a U-plane server which transports user data. Each Node B of the RLAN also has a separate connection with a C-plane server via a standard Iub signal control interface having an IP transport layer. Both the U-plane server and C-plane server are connected to the IP gateway using layered stacked protocols, preferably having IP as the transport layer.

[0086] For multiple C-plane server configurations, each can be coupled to each other via a standard Iur interface, but only one is required to be directly connected to the RIP GW. This allows the sharing of resources for control signal

processing which is useful when one area of the RLAN becomes much busier in other areas to spread out the signal processing between C-plane servers. A plurality of C-plane and U-plane servers can be connected in a mesh network for sharing both C-plane and U-plane resources via stacked layer protocols preferably having an IP transport layer.

[0087] Where the optional voice gateway having external connectivity via PCM circuit is provided, the U-plane server and C-plane server are coupled to the voice gateway via a stacked layer protocols preferably having an IP transport layer. The C-plane server is then coupled to the U-plane server via a Media gateway control protocol gateway (Megaco) over an IP transport layer. Megaco is a control plane protocol that sets up the bearer connection(s) between a Voice gateway elements, as part of call establishment.

[0088] Referring to Figures 17 and 18, there are shown, respectively, preferred C-plane and U-plane protocol stacks which are implemented between the Node Bs, RNCs (or U- and C-plane servers) and the RAN IP Gateway of the RLAN. In each drawing, the preferred over air protocol stack implemented via the Uu interface with UEs is also shown.

[0089] The RLAN can be configured with voice support over its external IP connection. In such case, the RIP gateway is connected with an Internet Service Provider (ISP) which in turn has a PCM voice gateway. The PCM voice gateway converts voice compression data into a Pulse Code Modulation (PCM) format for external voice communications.

[0090] Vocoders are provided that use Coder/Decoders (CODECs) for compression of voice data. Two common types vocoder formats are the AMR vocoder format and G.729 compression format. Figures 19 and 21 show preferred U-plane protocol stacks which are implemented where the voice gateway of the ISP to which the RLAN is connected uses the same type of voice compression interface as the UE. AMR vocoder format being illustrated in Figure 19; G.729 vocoder format being illustrated in Figure 21. The voice over IP is simply transferred as regular packet data over the IP interface without change.

[0091] Where the UE utilizes a different voice compression protocol than the voice gateway of the ISP, a converter is provided in the RNC or the RAN IP Gateway. Figure 20 shows preferred U-plane protocol stacks, where the UE utilizes an AMR vocoder and the ISP voice gateway utilizes a G.729 vocoder. Preferably, the RAN IP Gateway (RIP GW) includes the AMR/G.729 converter. In the case illustrated in Figure 20, the converter converts AMR compressed data received from the node B to G.729 format compressed voice format for output by the RIP GW. Where the RLAN utilizes separate U-plane and C-plane servers, the compressed voice data is transported by a U-plane server and the converters may be located in either the U-plane servers or the IP gateway.

[0092] With reference from Figures 22, there is shown preferred control plane protocol stack architecture for supporting voice using standard H.323 format for a Session Initiated Protocol (H.323/SIP) over TCP/UDP carry by IP. The control signaling is essentially the same irrespective of the type of voice data compression conducted in the U-Place.

[0093] Although the present invention has been described based on particular configurations, other variations will be apparent to those of ordinary skill in the art and are within the scope of the present invention.

CLAIMS

What is claimed is:

1. A method comprising:

receiving, by an IP gateway, data wirelessly from a user equipment (UE), the data including authentication, authorization, and accounting (AAA) information and Internet Protocol (IP) formatted packets;

passing, by the IP gateway, the IP formatted packets directly to the Internet to bypass a core network that supports real-time services for the UE; and

passing, by the IP gateway, the AAA information to the core network via the Internet for processing by the core network.

2. The method of claim 1, wherein the passing of the AAA information further comprises:

tunneling the AAA information to the core network via the Internet.

3. The method of claim 1, wherein the real-time services include communications over at least one of a Public Land Mobile Network, a Public Switch Telephone Network, and an Integrated Services Digital Network.

4. The method of claim 1, wherein the data is received in a 3rd Generation Partnership Project (3GPP) wireless format.

5. The method of claim 1, wherein the data is received in a time division duplex (TDD) code division multiple access (CDMA) format

6. The method of claim 1, wherein the IP gateway is located remote from the core network.

7. The method of claim 1, wherein the IP gateway is a radio access network IP gateway.

8. The method of claim 1, wherein the core network is part of a Universal Mobile Telecommunications System (UMTS) network;

and wherein the gateway includes an interface for a direct connection to the Internet and an interface for connection with the UMTS.

9. A gateway apparatus comprising:

a first interface; and

a second interface to connect the gateway apparatus to the Internet,

wherein the gateway apparatus:

receives data from a user equipment (UE) via the first interface, wherein the data includes authentication, authorization, and accounting (AAA) information and Internet Protocol (IP) formatted packets,

passes the IP formatted packets through the second interface directly to the Internet while bypassing a core network that supports real-time services for the UE, and

passes AAA information to the core network via the Internet for processing by the core network.

10. The gateway apparatus of claim 9, wherein the gateway apparatus tunnels the AAA information to the core network via the Internet.

11. The gateway apparatus of claim 9, wherein the real-time services include communications over at least one of a Public Land Mobile Network, a Public Switch Telephone Network, and an Integrated Services Digital Network.

12. The gateway apparatus of claim 11, wherein the data is received in a 3rd Generation Partnership Project (3GPP) wireless format.

13. The gateway apparatus of claim 11, wherein the data is received in a time division duplex (TDD) code division multiple access (CDMA) format.

14. The gateway apparatus of claim 9, wherein the gateway apparatus is located remote from the core network.

15. The gateway apparatus of claim 9, wherein the data is received in a 3rd Generation Partnership Project (3GPP) wireless format.

16. The gateway apparatus of claim 9, wherein the core network is part of a Universal Mobile Telecommunications System (UMTS) network.

17. A communications network comprising:

a plurality of transceivers; and

at least one gateway device including:

a first interface that connects the at least one gateway device to a respective one of the transceivers and receives data from a user equipment (UE) via the respective one of the transceivers, wherein the data includes authentication, authorization, and accounting (AAA) information and Internet Protocol (IP) formatted packets; and

a second interface that connects the at least one gateway device to the Internet;

wherein the at least one gateway device:

passes the IP formatted packets through the second interface directly to the Internet while bypassing a core network that supports real-time services for the UE, and

passes the AAA information to the core network via the Internet for processing by the core network.

18. The communications network of claim 17, wherein the at least one gateway device tunnels the AAA information to the core network via the Internet.

19. The communications network of claim 17, wherein the real-time services include communications over at least one of a Public Land Mobile Network, a Public Switch Telephone Network, and an Integrated Services Digital Network.

20. The communications network of claim 19, wherein the data is received in a 3rd Generation Partnership Project (3GPP) wireless format.

21. The communications network of claim 19, wherein the data is received in a time division duplex (TDD) code division multiple access (CDMA) format.

22. The communications network of claim 17, wherein the plurality of transceivers and the at least one gateway device are located remote from the core network.

23. The communications network of claim 17, wherein the core network is part of a Universal Mobile Telecommunications System (UMTS) network.

#1602431




Fig. 1
(Prior Art)




Fig. 2
(Prior Art)




Fig. 3
(Prior Art)






Fig. 4

**Fig. 5**

**Fig. 6**




Fig. 7




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B

Fig. 11A




Fig. 11B

12/22





Fig. 12



--- Signaling
--- Data

Fig. 13




Fig. 14




Fig. 15

16/22




Fig. 16

C - Plane Protocol Stack




Fig. 17

U-Plane Protocol Stack




Fig. 18




Fig. 19

U-Plane Architecture (Voice)




Fig. 20




Fig. 21

C-Plane Architecture (Voice)




Fig. 22

