



US007083620B2

(12) **United States Patent**  
**Jahns et al.**

(10) **Patent No.:** **US 7,083,620 B2**

(45) **Date of Patent:** **Aug. 1, 2006**

(54) **ELECTROSURGICAL HEMOSTAT**

(56) **References Cited**

(75) Inventors: **Scott E. Jahns**, Hudson, WI (US); **David E. Francischelli**, Anoka, MN (US); **Alison A. Lutterman**, Minneapolis, MN (US); **James R. Keogh**, Maplewood, MN (US); **Roderick E. Briscoe**, Rogers, MN (US); **William G. O'Neill**, Maple Grove, MN (US); **Jack Goodman**, Ann Arbor, MI (US); **Tom P. Daigle**, Corcoran, MN (US); **Paul T. Rothstein**, Maple Grove, MN (US); **Adam A. Podbelski**, Minneapolis, MN (US); **Stephen J Roddy**, Maple Grove, MN (US); **David J. S. Kim**, Maple Grove, MN (US); **Mark R. Bilitz**, Minneapolis, MN (US)

(73) Assignee: **Medtronic, Inc.**, Minneapolis, MN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 103 days.

(21) Appl. No.: **10/621,893**

(22) Filed: **Jul. 17, 2003**

(65) **Prior Publication Data**

US 2004/0087940 A1 May 6, 2004

**Related U.S. Application Data**

(60) Provisional application No. 60/422,330, filed on Oct. 30, 2002.

(51) **Int. Cl.**  
**A61B 18/18** (2006.01)  
**A61B 17/28** (2006.01)

(52) **U.S. Cl.** ..... **606/51**; 606/205

(58) **Field of Classification Search** ..... 606/51,  
606/52, 205-207

See application file for complete search history.

**U.S. PATENT DOCUMENTS**

3,736,936 A	6/1973	Basiulis et al.
3,807,403 A	4/1974	Stumpf et al.
3,823,575 A	7/1974	Parel
3,823,718 A	7/1974	Tromovitch
3,827,436 A	8/1974	Stumpf et al.
3,830,239 A	8/1974	Stumpf et al.
3,859,986 A	1/1975	Okada et al.
3,862,627 A	1/1975	Hans, Sr.
3,886,945 A	6/1975	Stumpf et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

WO WO 99/59486 1/1999

**OTHER PUBLICATIONS**

Chitwood, "Will C. Sealy, MD: The Father of Arrhythmia Surgery—The Story of the Fisherman with a Fast Pulse," *Annals of Thoracic Surgery* 58:1228-1239, 1994.

(Continued)


*Primary Examiner*—Michael Peffley

(74) *Attorney, Agent, or Firm*—Tom Berry; Jeffrey J. Hohenshell

(57) **ABSTRACT**

A hemostat-type device for ablative treatment of tissue, particularly for treatment of atrial fibrillation, is constructed with features that provide easy and effective treatment. A swiveling head assembly can allow the jaws to be adjusted in pitch and roll. Malleable jaws can permit curved lesion shapes. A locking detent can secure the jaws in a closed position during the procedure. An illuminated indicator provides confirmation that the device is operating. A fluid delivery system simplifies irrigated ablation procedures.

**58 Claims, 12 Drawing Sheets**



U.S. PATENT DOCUMENTS					
3,907,339 A	9/1975	Stumpf	5,353,783 A	10/1994	Nakao et al.
3,910,277 A	10/1975	Zimmer	5,354,258 A	10/1994	Dory
3,913,581 A	10/1975	Ritson et al.	5,361,752 A	11/1994	Moll et al.
3,924,628 A	12/1975	Droegemueller et al.	5,385,148 A	1/1995	Lesh et al.
4,018,227 A	4/1977	Wallach	5,391,180 A	2/1995	Tovey et al.
4,022,215 A	5/1977	Benson	5,396,887 A	3/1995	Imran
4,061,135 A	12/1977	Widran et al.	5,397,304 A	3/1995	Truckai
4,063,560 A	12/1977	Thomas et al.	5,400,770 A	3/1995	Nakao et al.
4,072,152 A	2/1978	Linehan	5,400,783 A	3/1995	Pomeranz et al.
4,082,096 A	4/1978	Benson	5,403,309 A	4/1995	Coleman et al.
4,128,099 A *	12/1978	Bauer ..... 606/52	5,403,311 A	4/1995	Abele et al.
4,207,897 A	6/1980	Lloyd et al.	5,405,376 A	4/1995	Mulier et al.
4,248,224 A	2/1981	Jones	5,409,483 A	4/1995	Campbell et al.
4,275,734 A	6/1981	Mitchiner	5,423,807 A	6/1995	Milder
4,278,090 A	7/1981	van Gerven	5,423,811 A	6/1995	Imran et al.
4,377,168 A	3/1983	Rzasa et al.	5,427,119 A	6/1995	Swartz et al.
4,485,817 A	12/1984	Swiggett	5,431,649 A	7/1995	Mulier et al.
4,519,389 A	5/1985	Gudkin et al.	5,433,708 A	7/1995	Nichols et al.
4,598,698 A	7/1986	Siegmund	5,435,308 A	7/1995	Gallup et al.
4,601,290 A	7/1986	Efron et al.	5,437,651 A	8/1995	Todd et al.
4,664,110 A	5/1987	Schanzlin	5,443,463 A	8/1995	Stern et al.
4,736,749 A	4/1988	Lundback	5,443,470 A	8/1995	Stern et al.
4,779,611 A	10/1988	Grooters et al.	5,450,843 A	9/1995	Moll et al.
4,802,475 A	2/1989	Weshahy	5,452,582 A	9/1995	Longworth
4,815,470 A	3/1989	Curtis et al.	5,452,733 A	9/1995	Sterman et al.
4,872,346 A	10/1989	Kelly-Fry et al.	5,462,545 A	10/1995	Wang et al.
4,880,015 A	11/1989	Nierman	5,465,717 A	11/1995	Imran et al.
4,916,922 A	4/1990	Mullens	5,469,853 A	11/1995	Law et al.
4,917,095 A	4/1990	Fry et al.	5,472,876 A	12/1995	Fahy
4,936,281 A	6/1990	Stasz	5,478,309 A	12/1995	Sweezer et al.
4,946,460 A	8/1990	Merry et al.	5,478,330 A	12/1995	Imran et al.
4,950,273 A	8/1990	Briggs	5,480,409 A *	1/1996	Riza ..... 606/205
5,013,312 A	5/1991	Parins et al.	5,486,193 A	1/1996	Bourne et al.
5,029,574 A	7/1991	Shimamura et al.	5,487,385 A	1/1996	Avitall
5,044,165 A	9/1991	Linner et al.	5,487,757 A	1/1996	Truckai et al.
5,078,713 A	1/1992	Varney	5,496,312 A	3/1996	Kliceck
5,080,102 A	1/1992	Dory	5,497,774 A	3/1996	Swartz et al.
5,080,660 A	1/1992	Buelina	5,498,248 A	3/1996	Milder
5,100,388 A	3/1992	Behl et al.	5,499,998 A	3/1996	Meade
5,108,390 A	4/1992	Potocky et al.	5,500,012 A	3/1996	Brucker et al.
5,147,355 A	9/1992	Friedman et al.	5,505,730 A	4/1996	Edwards
5,178,133 A	1/1993	Pena	5,514,157 A *	5/1996	Nicholas et al. .... 606/206
5,207,674 A	5/1993	Hamilton	5,516,505 A	5/1996	McDow
5,209,747 A *	5/1993	Knoepfler ..... 606/16	5,520,682 A	5/1996	Baust et al.
5,217,860 A	6/1993	Fahy et al.	5,522,870 A	6/1996	Ben-Zion
5,222,501 A	6/1993	Ideker et al.	5,536,267 A	7/1996	Edwards et al.
5,224,943 A	7/1993	Goddard	5,545,195 A	8/1996	Lennox et al.
5,228,923 A	7/1993	Hed	5,545,200 A	8/1996	West et al.
5,231,995 A	8/1993	Desai	5,549,661 A	8/1996	Kordis et al.
5,232,516 A	8/1993	Hed	5,555,883 A	9/1996	Avitall
5,254,116 A	10/1993	Baust et al.	5,558,671 A	9/1996	Yates
5,263,493 A	11/1993	Avitall	5,560,362 A	10/1996	Sliwa, Jr. et al.
5,269,291 A	12/1993	Carter	5,562,720 A	10/1996	Stern et al.
5,275,595 A	1/1994	Dobak, III	5,569,241 A	10/1996	Edwards
5,277,201 A	1/1994	Stern	5,571,088 A	11/1996	Lennox et al.
5,281,213 A	1/1994	Milder et al.	5,571,215 A	11/1996	Sterman et al.
5,281,215 A	1/1994	Milder	5,573,532 A	11/1996	Chang et al.
5,295,484 A	3/1994	Marcus et al.	5,575,766 A	11/1996	Swartz et al.
5,309,896 A	5/1994	Moll et al.	5,575,788 A	11/1996	Baker et al.
5,316,000 A	5/1994	Chapelon et al.	5,575,810 A	11/1996	Swanson et al.
5,317,878 A	6/1994	Bradshaw et al.	5,578,007 A	11/1996	Imran
5,318,525 A	6/1994	West et al.	5,582,609 A	12/1996	Swanson et al.
5,322,520 A	6/1994	Milder	5,588,432 A	12/1996	Crowley
5,323,781 A	6/1994	Ideker et al.	5,590,657 A	1/1997	Cain et al.
5,324,255 A	6/1994	Passafaro et al.	5,595,183 A	1/1997	Swanson et al.
5,324,284 A	6/1994	Imran	5,607,450 A	3/1997	Zvenyatsky et al.
5,324,286 A	6/1994	Fowler	5,607,462 A	3/1997	Imran
5,330,502 A *	7/1994	Hassler et al. .... 606/205	5,611,813 A	3/1997	Lichtman
5,334,181 A	8/1994	Rubinsky et al.	5,617,854 A	4/1997	Munsif
5,334,193 A	8/1994	Nardella	5,620,459 A	4/1997	Lichtman
5,348,554 A	9/1994	Imran et al.	5,630,837 A	5/1997	Crowley
			5,637,090 A	6/1997	McGee et al.
			5,643,197 A	7/1997	Brucker et al.

5,656,029 A	8/1997	Imran et al.	5,906,587 A	5/1999	Zimmon
5,658,278 A	8/1997	Imran et al.	5,906,606 A	5/1999	Chee et al.
5,671,747 A	9/1997	Connor	5,908,029 A	6/1999	Knudson et al.
5,673,695 A	10/1997	McGee et al.	5,916,213 A	6/1999	Haissaguerre et al.
5,676,662 A	10/1997	Fleischhacker et al.	5,916,214 A	6/1999	Cosio et al.
5,676,692 A	10/1997	Sanghvi et al.	5,921,924 A	7/1999	Avitall
5,676,693 A	10/1997	Lafontaine	5,921,982 A	7/1999	Lesh et al.
5,678,550 A	10/1997	Bassen et al.	5,927,284 A	7/1999	Borst et al.
5,680,860 A	10/1997	Imran	5,928,191 A	7/1999	Houser et al.
5,681,278 A	10/1997	Igo et al.	5,931,810 A	8/1999	Grabek
5,681,308 A	10/1997	Edwards et al.	5,931,848 A	8/1999	Saadat
5,687,723 A	11/1997	Avitall	5,935,126 A	8/1999	Riza
5,687,737 A	11/1997	Branham et al.	5,954,661 A	9/1999	Greenspon et al.
5,688,267 A	11/1997	Panescu et al.	5,971,980 A	10/1999	Sherman
5,690,611 A	11/1997	Swartz et al.	5,971,983 A	10/1999	Lesh
5,697,536 A	12/1997	Eggers et al.	5,993,447 A	11/1999	Blewett et al.
5,697,882 A	12/1997	Eggers et al.	6,007,499 A	12/1999	Martin et al.
5,697,925 A	12/1997	Taylor	6,012,457 A	1/2000	Lesh
5,697,927 A	12/1997	Imran et al.	6,016,811 A	1/2000	Knopp et al.
5,697,928 A	12/1997	Walcott et al.	6,032,077 A	2/2000	Pomeranz
5,713,942 A	2/1998	Stern	6,042,556 A	3/2000	Beach et al.
5,716,389 A	2/1998	Walinsky et al.	6,063,081 A	5/2000	Mulier
5,718,241 A	2/1998	Ben-Haim et al.	6,071,279 A	6/2000	Whayne et al.
5,718,701 A	2/1998	Shai et al.	6,088,894 A	7/2000	Oakley
5,720,775 A	2/1998	Lanard	6,096,037 A	8/2000	Mulier et al.
5,722,402 A	3/1998	Swanson et al.	6,113,592 A	9/2000	Taylor
5,730,074 A	3/1998	Peter	6,117,101 A	9/2000	Diederich et al.
5,730,127 A	3/1998	Avitall	6,120,496 A	9/2000	Whayne et al.
5,730,704 A	3/1998	Avitall	6,132,441 A *	10/2000	Grace ..... 606/147
5,733,280 A	3/1998	Avitall	6,142,944 A	11/2000	Li et al.
5,735,280 A	4/1998	Sherman et al.	6,142,993 A	11/2000	Whayne et al.
5,735,290 A	4/1998	Sterman et al.	6,142,994 A	11/2000	Swanson et al.
5,735,874 A	4/1998	Measamer et al.	6,152,920 A	11/2000	Thompson et al.
5,755,760 A	5/1998	Maguire et al.	6,161,543 A	12/2000	Cox et al.
5,769,846 A	6/1998	Edwards et al.	6,165,174 A	12/2000	Jacobs et al.
5,782,828 A	7/1998	Chen et al.	6,217,528 B1	4/2001	Koblish et al.
5,782,859 A	7/1998	Nicholas et al.	6,217,576 B1	4/2001	Tu et al.
5,785,706 A	7/1998	Bednarek	6,224,592 B1	5/2001	Eggers et al.
5,788,636 A	8/1998	Curley	6,231,518 B1	5/2001	Grabek et al.
5,792,140 A	8/1998	Tu et al.	6,235,024 B1	5/2001	Tu
5,797,959 A	8/1998	Castro et al.	6,237,605 B1	5/2001	Vaska et al.
5,797,960 A	8/1998	Stevens et al.	6,238,347 B1	5/2001	Nix et al.
5,800,428 A	9/1998	Nelson et al.	6,238,393 B1	5/2001	Mulier
5,800,449 A *	9/1998	Wales ..... 606/172	6,245,061 B1	6/2001	Panescu et al.
5,800,482 A	9/1998	Pomeranz et al.	6,245,064 B1	6/2001	Lesh et al.
5,810,802 A	9/1998	Panescu et al.	6,245,065 B1	6/2001	Panescu et al.
5,827,216 A	10/1998	Igo et al.	6,251,092 B1	6/2001	Qin et al.
5,827,323 A	10/1998	Klieman et al.	6,251,128 B1	6/2001	Knopp et al.
5,836,947 A	11/1998	Fleischman et al.	6,270,471 B1	8/2001	Hechel et al.
5,840,030 A	11/1998	Ferek-Petric et al.	6,293,943 B1	9/2001	Panescu et al.
5,844,349 A	12/1998	Oakley et al.	6,296,619 B1	10/2001	Briskin et al.
5,846,187 A	12/1998	Wells et al.	6,302,880 B1	10/2001	Schaer
5,846,191 A	12/1998	Wells et al.	6,311,692 B1	11/2001	Vaska et al.
5,849,028 A	12/1998	Chen	6,312,383 B1	11/2001	Lizzi et al.
5,860,995 A	1/1999	Berkelaar	6,312,435 B1 *	11/2001	Wallace et al. .... 606/130
5,871,523 A	2/1999	Fleischman et al.	6,314,962 B1	11/2001	Vaska et al.
5,871,525 A	2/1999	Edwards et al.	6,314,963 B1	11/2001	Vaska et al.
5,873,845 A	2/1999	Cline et al.	6,325,797 B1	12/2001	Stewart et al.
5,876,399 A	3/1999	Chia et al.	6,328,736 B1	12/2001	Mulier
5,879,295 A	3/1999	Li et al.	6,332,881 B1	12/2001	Carner et al.
5,879,296 A	3/1999	Ockuly et al.	6,358,248 B1	3/2002	Mulier
5,881,732 A	3/1999	Sung et al.	6,361,531 B1	3/2002	Hissong
5,882,346 A	3/1999	Pomeranz et al.	6,364,876 B1	4/2002	Erb et al.
5,885,278 A	3/1999	Fleischman	6,368,275 B1	4/2002	Sliwa et al.
5,893,848 A	4/1999	Negus et al.	6,371,955 B1	4/2002	Fuimaono et al.
5,895,417 A	4/1999	Pomeranz et al.	6,383,151 B1	5/2002	Diederich et al.
5,897,553 A	4/1999	Mulier	6,385,472 B1	5/2002	Hall et al.
5,897,554 A	4/1999	Chia et al.	6,398,792 B1	6/2002	O'Connor
5,899,898 A	5/1999	Arless et al.	6,409,722 B1	6/2002	Hoey
5,899,899 A	5/1999	Arless et al.	6,413,254 B1	7/2002	Hissong et al.
5,902,289 A	5/1999	Swartz et al.	6,419,648 B1	7/2002	Vitek et al.
5,904,711 A	5/1999	Flom et al.	6,425,867 B1	7/2002	Vaezy et al.
5,906,580 A	5/1999	Kline-Schoder et al.	6,430,426 B1	8/2002	Avitall

6,440,130	B1 *	8/2002	Mulier et al. ....	606/49
6,443,952	B1	9/2002	Mulier	
6,447,507	B1	9/2002	Bednarek et al.	
6,461,314	B1	10/2002	Pant et al.	
6,461,956	B1	10/2002	Patterson	
6,464,700	B1	10/2002	Koblish et al.	
6,471,697	B1	10/2002	Lesh	
6,471,698	B1	10/2002	Edwards et al.	
6,474,340	B1	11/2002	Vaska et al.	
6,475,216	B1	11/2002	Mulier	
6,477,396	B1	11/2002	Mest et al.	
6,484,727	B1	11/2002	Vaska et al.	
6,488,680	B1	12/2002	Francischelli	
6,502,575	B1	1/2003	Jacobs et al.	
6,514,250	B1	2/2003	Jahns	
6,527,767	B1	3/2003	Wang et al.	
6,537,248	B1	3/2003	Mulier	
6,537,272	B1	3/2003	Christopherson et al.	
6,558,382	B1	5/2003	Jahns	
6,584,360	B1	6/2003	Francischelli	
6,585,732	B1	7/2003	Mulier	
6,605,084	B1	8/2003	Acker et al.	
6,610,055	B1	8/2003	Swanson et al.	
6,610,060	B1	8/2003	Mulier	
6,613,048	B1	9/2003	Mulier	
6,645,199	B1	11/2003	Jenkins et al.	
6,648,883	B1	11/2003	Francischelli	
6,656,175	B1	12/2003	Francischelli	
6,663,627	B1	12/2003	Francischelli	
6,685,698	B1 *	2/2004	Morley et al. ....	606/1
6,692,450	B1	2/2004	Coleman	
6,692,491	B1	2/2004	Phan	
6,699,240	B1	3/2004	Francischelli	
6,702,811	B1	3/2004	Stewart et al.	
6,706,038	B1	3/2004	Francischelli	
6,706,039	B1	3/2004	Mulier	
6,716,211	B1	4/2004	Mulier	
6,736,810	B1	5/2004	Hoey	
6,755,827	B1	6/2004	Mulier	
6,764,487	B1	7/2004	Mulier	
6,773,433	B1	8/2004	Stewart et al.	
6,776,780	B1	8/2004	Mulier et al.	
6,807,968	B1	10/2004	Francischelli	
6,827,715	B1	12/2004	Francischelli	
6,849,073	B1	2/2005	Hoey	
6,858,028	B1	2/2005	Mulier	
6,887,238	B1	5/2005	Jahns	
6,899,711	B1	5/2005	Stewart et al.	
6,911,019	B1	6/2005	Mulier	
6,916,318	B1	7/2005	Francischelli	
6,936,046	B1	8/2005	Hissong	
6,949,097	B1	9/2005	Stewart et al.	
6,949,098	B1	9/2005	Mulier	
6,960,205	B1	11/2005	Jahns	
6,962,589	B1	11/2005	Mulier	
2003/0045872	A1	3/2003	Jacobs	
2003/0144656	A1	7/2003	Ocel	
2003/0191462	A1	10/2003	Jacobs	
2003/0216724	A1	11/2003	Jahns	
2004/0015106	A1	1/2004	Coleman	
2004/0015219	A1	1/2004	Francischelli	
2004/0044340	A1	3/2004	Francischelli	
2004/0049179	A1	3/2004	Francischelli	
2004/0078069	A1	4/2004	Francischelli	
2004/0082948	A1	4/2004	Stewart et al.	
2004/0087940	A1	5/2004	Jahns	
2004/0092926	A1	5/2004	Hoey	
2004/0138621	A1	7/2004	Jahns	
2004/0138656	A1	7/2004	Francischelli	
2004/0143260	A1	7/2004	Francischelli	
2004/0186465	A1	9/2004	Francischelli	
2004/0215183	A1	10/2004	Hoey	
2004/0220560	A1	11/2004	Briscoe	

2004/0236322	A1	11/2004	Mulier
2004/0267326	A1	12/2004	Ocel
2005/0010095	A1	1/2005	Stewart et al.
2005/0033280	A1	2/2005	Francischelli
2005/0090815	A1	4/2005	Francischelli
2005/0143729	A1	6/2005	Francischelli
2005/0165392	A1	7/2005	Francischelli
2005/0209564	A1	9/2005	Bonner
2005/0267454	A1	12/2005	Hissong
2006/0009756	A1	1/2006	Francischelli
2006/0009759	A1	1/2006	Christian

## OTHER PUBLICATIONS

Gallagher et al., "Cryosurgical Ablation of Accessory Atrioventricular Connections: A Method for Correction of the Pre-excitation Syndrome," *Circulation* 55(3): 471-479, 1977.

Sealy, "Direct Surgical Treatment of Arrhythmias: The Last Frontier in Surgical Cardiology," *Chest* 75(5): 536-537, 1979.

Sealy, "The Evolution of the Surgical Methods for Interruption of Right Free Wall Kent Bundles," *The Annals of Thoracic Surgery* 36(1): 29-36, 1983.

Guiraudon et al., "Surgical Repair of Wolff-Parkinson-White Syndrome: A New Closed-Heart Technique," *The Annals of Thoracic Surgery* 37(1): 67-71, 1984.

Klein et al., "Surgical Correction of the Wolff-Parkinson-White Syndrome in the Closed Heart Using Cryosurgery: A Simplified Approach," *JACC* 3(2): 405-409, 1984.

Randall et al., "Local Epicardial Chemical Ablation of Vagal Input to Sino-Atrial and Atrioventricular Regions of the Canine Heart," *Journal of the Autonomic Nervous System* 11:145-159, 1984.

Guiraudon et al., "Surgical Ablation of Posterior Septal Accessory Pathways in the Wolf-Parkinson-White Syndrome by a Closed Heart Technique," *Journal Thoracic Cardiovascular Surgery* 92:406-413, 1986.

Gallagher et al., "Surgical Treatment of Arrhythmias," *The American Journal of Cardiology* 61:27A-44A, 1988.

Mahomed et al., "Surgical Division of Wolff-Parkinson-White Pathways Utilizing the Closed-Heart Technique: A 2-Year Experience in 47 Patients," *The Annals of Thoracic Surgery* 45(5): 495-504, 1988.

Bredikis and Bredikis; *Surgery of Tachyarrhythmia: Intracardiac Closed Heart Cryoablation: PACE*, vol. 13, pp. 1980-1984.

McCarthy et al., "Combined Treatment of Mitral Regurgitation and Atrial Fibrillation with Valvuloplasty and the Maze Procedure," *The American Journal of Cardiology* 71: 483-486, 1993.

Yamauchi et al., "Use of Intraoperative Mapping to Optimize Surgical Ablation of Atrial Flutter," *The Annals of Thoracic Surgery* 56: 337-342, 1993.

Graffigna et al., "Surgical Treatment of Wolff-Parkinson-White Syndrome: Epicardial Approach Without the Use of Cardiopulmonary Bypass," *Journal of Cardiac Surgery* 8: 108-116, 1993.


Elvan et al., "Radiofrequency Catheter Ablation of the Atria Reduces Inducibility and Duration of Atrial Fibrillation in Dog," *Circulation* 91: 2235-2244, 1995.

Cox et al., "Modification of the Maze Procedure for Atrial Flutter and Atrial Fibrillation. I. Rational and Surgical Results," *The Journal of Thoracic Cardiovascular Surgery* 110: 473-484, 1995.

- Cox, "The Maze III Procedure for Treatment of Atrial Fibrillation," Sabiston DC, ed Atlas of Cardiothoracic Surgery, Philadelphia: WB Saunders: 460-475, 1994.
- Sueda et al., "Simple Left Atrial Procedure for Chronic Atrial Fibrillation Associated with Mitral Valve Disease," The Annals of Thoracic Surgery 62(6): 1796-1800, 1996.
- Tsui et al., "Maze 3 for Atrial Fibrillation: Two Cuts Too Few?" PACE 17: 2163-2166, 1994.
- Kosakai et al., "Cox Maze Procedure for Chronic Atrial Fibrillation Associated with Mitral Valve Disease," The Journal of Thoracic Cardiovascular Surgery 108: 1049-1055, 1994.
- Cox et al., "The Surgical Treatment of Atrial Fibrillation, IV Surgical Technique," *J of Thorac Cardiovasc Surg*, 1991: 101: 584-593.
- Nardella, "Radio Frequency Energy and Impedance Feedback," SPIE vol. 1068, Catheter Based Sensing and Imaging Technology (1989).
- Avitall et. al., "A Thoracoscopic Approach to Ablate Atrial Fibrillation Via Linear Radiofrequency Lesion Generation on the Epicardium of Both Atria," PACE, Apr. 1996;19(Part II):626,#241.
- Sie et al., "Radiofrequency Ablation of Atrial Fibrillation in Patients Undergoing Mitral Valve Surgery. First Experience," Circulation (Nov. 1996) 96:450,I-675,#3946.
- Sie et al., "Radiofrequency Ablation of Atrial Fibrillation in Patients Undergoing Valve Surgery," Circulation (Nov. 1997) 84:I450,#2519.
- Cox, "Evolving Applications of the Maze Procedure for Atrial Fibrillation," Ann Thorac Surg, 1993;55:578-580.
- Cox et al. "Five-Year Experience with the Maze Procedure for Atrial Fibrillation," Ann Thorac Surg, 1993; 56:814-824.
- Avitall et al., "New Monitoring Criteria for Transmural Ablation of Atrial Tissues," Circulation, 1996;94(Supp 1):I-493, #2889.
- Cox et al., "An 8 1/2 Year Clinical Experience with Surgery for Atrial Fibrillation," Annals of Surgery, 1996;224(3):267-275.
- Haissaguerre et al., "Radiofrequency Catheter Ablation for Paroxysmal Atrial Fibrillation in Humans: Elaboration of a procedure based on electrophysiological data," Nonpharmacological Management of Atrial Fibrillation, 1997 pp. 257-279.
- Haissaguerre et al., "Right and Left Atrial Radiofrequency Catheter Therapy of Paroxysmal Atrial Fibrillation," Journal of Cardiovascular Electrophysiology, 1996;7(12):1132-1144.
- Kawaguchi et al., "Risks and Benefits of Combined Maze Procedure for Atrial Fibrillation Associated with Organic Heart Disease," JACC, 1996;28(4):985-990.
- Cox, et al., "Perinodal cryosurgery for atrioventricular node reentry tachycardia in 23 patients," Journal of Thoracic and Cardiovascular Surgery, 99:3, Mar. 1990, pp. 440-450.
- Cox, "Anatomic-Electrophysiologic Basis for the Surgical Treatment of Refractory Ischemic Ventricular Tachycardia," Annals of Surgery, Aug. 1983; 198:2;119-129.
- Sueda et al., "Simple Left Atrial Procedure for Chronic Atrial Fibrillation Associated with Mitral Valve Disease," Ann Thorac Surg, 1996;62:1796-1800.
- Sueda et al., "Efficacy of a Simple Left Atrial Procedure for Chronic Atrial Fibrillation in Mitral Valve Operations," Ann Thorac Surg, 1997;63:1070-1075.
- Cox et al., Surgery for Atrial Fibrillation; Seminars in Thoracic and Cardiovascular Surgery, vol. 1, No. 1 (Jul. 1989) p. 67-73.

\* cited by examiner

FIG. 1








FIG. 2








FIG. 13B

FIG. 13A





FIG. 4

FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B







FIG. 7A

FIG. 7B





**FIG. 9B**



**FIG. 9C**





FIG. 10






FIG. 11B

FIG. 11A




FIG. 12A




FIG. 12B




FIG. 14






FIG. 15A




FIG. 16B





FIG. 15B

FIG. 16A



1

**ELECTROSURGICAL HEMOSTAT****RELATED U.S. APPLICATION DATA**

This application claims priority from U.S. Provisional Patent Application No. 60/422,330 filed Oct. 30, 2002, incorporated herein by reference in its entirety.

**BACKGROUND OF THE INVENTION**

The present invention relates to surgical tools and procedures generally and relates more particularly to the use of electrosurgical ablation to treat atrial fibrillation.

In patients with chronic atrial fibrillation or having atrial tachycardia that is resistant to medical treatment, the Maze III procedure has been employed. This procedure controls propagation of the depolarization wavefronts in the right and left atria by means of surgical incisions through the walls of the right and left atria. The incisions create blind or dead end conduction pathways, which prevent re-entrant atrial tachycardias from occurring. While the Maze procedure is successful in treating atrial fibrillation, the procedure is quite complex and is currently practiced by only a few very skilled cardiac physicians in conjunction with other open-heart procedures. The procedure also is quite traumatic to the heart, as in essence the right and left atria are cut into pieces and sewed back together, to define lines of lesion across which the depolarization wavefronts will not propagate.

It has been suggested that procedures similar to the Maze procedure could be instead performed by means of electrosurgical ablation, for example, by applying radiofrequency (RF) energy to internal or external surfaces of the atria to create lesions across which the depolarization wavefronts will not propagate. Such procedures are disclosed in U.S. Pat. No. 5,895,417, issued to Pomeranz, et al., U.S. Pat. No. 5,575,766, issued to Swartz, et al., U.S. Pat. No. 6,032,077, issued to Pomeranz, U.S. Pat. No. 6,142,944, issued to Swanson, et al., U.S. Pat. No. 5,871,523, issued to Fleischman, et al. and U.S. Pat. No. 6,502,575, issued to Jacobs et al., all incorporated herein by reference in their entireties. Hemostat type, electrosurgical or cryo-ablation devices for use in performing such procedures are described in U.S. Pat. No. 5,733,280 issued to Avitall, U.S. Pat. No. 6,237,605 issued to Vaska, et al, U.S. Pat. No. 6,161,543, issued to Cox, et al., PCT published Application No. WO99/59486, by Wang and in pending U.S. patent application Ser. No. 09/747,609 filed Dec. 22, 2000 by Hooven, et al., all incorporated herein by reference in their entireties. In order for such procedures to be effective it is desirable that the electrosurgically created lesions are continuous along their length and extend completely through the tissue of the heart (i.e. transmural lesions). These goals may be difficult to accomplish employing dry ablation electrodes or electrodes applied only to the interior or exterior surfaces of the heart tissue. Electrosurgical hemostats configured to allow fluid—assisted tissue ablation are generally described in U.S. Pat. No. 6,096,037, issued to Mulier, also incorporated by reference in its entirety.

**SUMMARY OF THE INVENTION**

The present invention provides an ablation hemostat, particularly useful in performing a maze type procedure by applying ablation energy (e.g. RF energy) across the walls of the left and right atria by means of delivery means located on either side of the atrial walls. In a preferred embodiment of the invention, the hemostat is provided with elongated RF

2

electrodes malleable to assume various straight and curved configurations to produce lesions that approximate the incisions that would occur during the Maze III procedure as described in the book '*Cardiac Surgery Operative Technique*' by Donald B. Doty, M. D. at pages 410–419, incorporated herein by reference in its entirety, or to allow creation of lines of lesion corresponding to the incisions that would be provided by other forms of the Maze procedure. The hemostat may be useful in conjunction with other procedures as well.

The hemostat of the present invention is provided with a number of useful features, particularly adapted to ease its use in conjunction with creating elongated lines of lesion. While the disclosed and most preferred embodiments of the invention employ all of the improved features, each of the improved features discussed below is believed valuable in and of itself to improve the performance and ease of use of prior art electrosurgical hemostats.

In order to allow the hemostat to produce straight and curved elongated lesions, the jaws of the hemostat are malleable to allow the physician to set the specific jaw configuration. The jaws are fabricated of a flexible plastic sheath enclosing elongated bendable or malleable backbones and electrodes to achieve this result. The backbones and electrodes may be shaped by the physicians' fingers into a desired curvature and serve to retain the curvature imparted to them until reshaped for creation of a subsequent lesion. The backbones take the form of elongated plates having thicknesses substantially less than their widths to encourage bending of the jaws within a single plane so that the opposed electrodes can more readily be maintained in alignment along their lengths. The backbones are also preferably tapered along their length such that the width of the backbones diminishes as they approach the tips of the jaws, in turn making it easier to provide the jaws with the curvature extending over the entire length of the jaws.

The hemostat includes an elongated handle portion or handle and a jaw assembly mounted at the distal end of the handle. The jaw assembly preferably includes two elongated jaws carrying RF electrodes or other ablation elements, extending along the lengths of the jaws and arranged so that they are located on opposite sides of tissue compressed between the jaws. In preferred embodiments, the electrodes take the form of fluid irrigated RF electrodes, however, other ablation mechanisms such as cyroablation, direct current ablation, microwave ablation, and the like may be substituted for RF ablation electrodes.

The jaw assembly preferably includes a swiveling head assembly adapted to allow the jaws to be rotated relative to the axis of the handle (roll) and allowing the jaws to pivot around an axis perpendicular to the axis of the handle (pitch). Adjustment of the jaws relative to the handle (pitch and roll) is made manually by the physician, and the jaws are retained in their desired orientation relative to the handle by means of detent mechanisms.

The jaws are mounted to one another at a pivot point and are opened and closed by means of a trigger, mounted to the handle, which applies tensile force to a cable or other tension member extending along the handle. The cable, when pulled, pulls the jaws toward one another to compress tissue between them. In the particular embodiments disclosed, the cable is anchored offset from the pivot point to a first one of the jaws. The first jaw is fixed, i.e. retains its location during jaw closure regardless of the pitch and roll adjustment made to the jaw assembly. The second, pivoting jaw, is mounted to the fixed jaw at a pivot point and the cable passes around an internal boss within the pivoting jaw, also offset from the

3

pivot point. Application of tension to the tension member pulls the internal boss in the pivoting jaw toward the cable mounting point in the fixed jaw and thereby causes movement of the jaws toward one another. Tissue placed between the jaws can thus be engaged by the jaws and compressed between the jaws as the jaws close.

The cable enters the jaw assembly along its rotational (roll) axis, so that rotation of the jaw assembly about the roll axis does not alter the operation of the cable. The cable extends around a shoulder internal to the fixed jaw, which shoulder remains essentially in the same location regardless of the pitch adjustment of the jaw assembly, so that pitch adjustment of the jaw assembly does not significantly effect operation of the cable to close the jaws.

In preferred embodiments, the trigger mechanism is provided with a locking detent mechanism which may be engaged or disengaged and which, when engaged, retains the trigger in its position, in turn maintaining compression of the jaws against tissue located there between. The detent mechanism in a preferred embodiment is activated or deactivated by means of a sliding button, mounted to the handle.

In preferred embodiments, irrigation fluid is provided to the electrodes by means of plastic tubing that is provided with in-line flow limiters, controlling the delivery rate of irrigation fluid to the electrodes. This feature allows the use of a simplified fluid pumping mechanism and also provides balanced, even fluid flow to the electrodes. In its preferred embodiment, the trigger, when released, also serves to block fluid flow to the electrodes, preventing irrigation while the hemostat is not in use.

In one embodiment, the RF electrode assembly can take the form of an elongated porous material coupled to the fluid delivery lines and carrying elongated electrode wires on their inner, facing surfaces. The electrode wires may be coupled to the porous material by means of a series of spikes extending from the electrode wires into the porous material. Other alternative electrode designs may of course be substituted, including electrodes comprised of elongated coil electrodes or perforated tubular electrodes with porous material located either inside of or surrounding the electrodes. For example, a perforated tubular electrode can be seated inside a porous polymeric support such the electrode is entirely within the support. In this embodiment, conductive fluid flows through the interior of the electrode, out of perforations in the electrode and through the porous support to facilitate ablation such that the polymeric support, not the electrode, is on the facing surfaces of the jaws to contact the tissue to be ablated.

The hemostat may optionally also include a thermocouple, located along the jaws allowing for temperature controlled feedback of power provided to the RF electrodes and may also preferably includes an indicator LED mounted to the handle, activated to indicate that delivery of RF energy is underway. The hemostat is usable with conventional RF generators. Alternatively, the hemostat may be used in conjunction with an RF generator system, which incorporates a transmurality measurement and automatic shut off of ablation energy.

### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view of an assembled hemostat according to one embodiment of the present invention.

FIG. 2 is an exploded view of the jaw assembly of the hemostat of FIG. 1.

FIG. 3A is a cross-section view through the jaw assembly of the hemostat of FIG. 1.

4

FIG. 3B is a cross-section view through lines 3B—3B of FIG. 3A.

FIG. 4 is an end view in partial cross-section of the proximal end of the knuckle portion of the jaw assembly of the hemostat of FIG. 1.

FIG. 5A is a plan view of an elongated tubular electrode used in the hemostat of FIG. 1.

FIG. 5B is an enlarged cross-section view taken along lines 5B—5B of the electrode illustrated in FIG. 5A.

FIG. 6A is an end view of an electrode support as used in the jaw assembly of the hemostat of FIG. 1.

FIG. 6B is a cross-section view taken along lines 6A—6A of FIG. 6A illustrating the electrode support.

FIG. 7A is an end view of an electrode sheath as included in the jaw assembly of the hemostat of FIG. 1.

FIG. 7B is a cross-section view taken along lines 7B—7B of FIG. 7A illustrating the electrode sheath.

FIG. 8A is a plan view of the right half of the handle employed in the hemostat of FIG. 1.

FIG. 8B is an enlarged plan view of the distal portion of the right handle half illustrated in FIG. 8A.

FIG. 8C is a cross-section view taken along lines 8C—8C through the right handle half of the hemostat of FIG. 1.

FIG. 9A is a plan view of the left half of the handle employed in the hemostat of FIG. 1.

FIG. 9B is an enlarged plan view of the distal portion of the left handle half illustrated in FIG. 9A.

FIG. 9C is a cross-section view taken along lines 9C—9C through the left handle half of the hemostat of FIG. 1.

FIG. 10 is an enlarged view of the trigger portion of a hemostat as in FIG. 1 with the left handle half removed.

FIG. 11A is a perspective view of a trigger lock as employed in the trigger assembly of the hemostat as in FIG. 1.

FIG. 11B is a plan view of the trigger lock of FIG. 11A.

FIG. 12A is a top plan view of a link arm as employed in the trigger assembly of an assembled hemostat as in FIG. 1.

FIG. 12B is a side plan view of the link arm of FIG. 12A.

FIG. 13A is a side plan view from the distal end of the trigger employed in the trigger assembly of the hemostat of FIG. 1.

FIG. 13B is a cross-section view taken along lines 13B—13B through the trigger of FIG. 13A.

FIG. 14 is a cut-away view of the proximal portion of the hemostat of FIG. 1 with the left handle half removed.

FIG. 15A is a sectional view through an alternative embodiment of an upper and lower jaw for use with a hemostat otherwise as in FIG. 1.

FIG. 15B is a cross-sectional view taken along lines 15B—15B of FIG. 15A.

FIG. 16A is a plan view of an electrode extension employed in the alternative embodiment of the upper and lower jaw depicted in FIGS. 15A and 15B.

FIG. 16B is an expanded view of a barb of the electrode extension depicted in FIG. 16A.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In reference to FIG. 1, a preferred embodiment of the hemostat of the present invention generally comprises an elongated handle assembly or handle 10 having a jaw assembly 90 mounted at handle distal end 15, a trigger 20 intermediate the handle proximal and distal ends 95 and 15, and a strain relief 60 located at handle proximal end 95. An elongated cable is coupled to the strain relief 60 and comprises a fluid conduit 70 extending to a proximal fluid fitting

5

75 adapted to be coupled to a source of conductive fluid and a multi-conductor electrical cable 80 extending to a proximal electrical connector 85 adapted to be coupled to an electrosurgical unit. The trigger 20 is employed to move the jaws of the first or lower jaw assembly 40 with respect to the second or upper jaw assembly 30 of the jaw assembly 90 together to compress tissue therebetween to allow for creation of a linear RF ablation by electrically conductive fluid emitted from electrodes and contacting tissue or direct contact of the electrodes located along the upper and lower jaws 35 and 45.

The jaw assembly 90 includes the upper jaw assembly 30, the lower jaw assembly 40, and a swivel assembly 50, discussed in more detail below. The upper jaw and lower jaw assemblies 30 and 40 have opposed upper and lower jaws 35 and 45, respectively, each comprising a fluid assisted elongated electrode assembly. The upper and lower jaw assemblies 30 and 40 support elongated electrodes, discussed in more detail below, each coupled to one of the insulated conductors within conduit 70 extending proximally through the strain relief 60 to electrical connector 85. Each of the jaws 35 and 40 of respective upper and lower jaw assemblies 30 and 40 are also coupled to fluid conduit 80 enabling delivery of saline or other conductive fluid from a source coupled to fitting 75 along the lengths of the opposed jaws 35 and 45.

The swivel assembly 50, provides the physician with the opportunity to position the jaw assembly 90 in a variety of orientations relative to the handle 10, to facilitate placing the 35 and 45 jaws against tissue to form desired lines of lesions, e.g., the heart wall in performance of the above-described Maze procedure. The physician can manually grasp and rotate the swivel assembly 50 and the jaw assembly 90 to provide a roll adjustment R, preferably through an arc of at least 300 degrees, relative to the axis of the distal end 15 of the handle 10 through interaction of components of the handle and swivel assembly described further below. In addition, the physician can grasp the jaw assembly 90 and adjust it in pitch P relative to the swivel assembly 50 through the interaction of components of the jaw assembly 90 and the swivel assembly 50 described further below. Preferably, the available arc of pitch P adjustment extends over at least 90 degrees. Moreover, the upper and lower jaws 35 and 45 are malleable as described further below. The combination of these features and the S-shape handle 10 make the hemostat highly versatile in use.

The trigger 20 is employed to open (separate apart) and close (draw together) the jaws 35 and 45 and to compress tissue between the jaws 35 and 45 prior to application of RF energy to create an elongated lesion. A thumb slide 25 is provided in conjunction with an internal trigger lock, allowing the position of the trigger 20 and the jaws 35, 45 to be locked. After the trigger 20 is drawn toward the handle 10 to close the jaws 35 and 45, the thumb slide 25 is moved distally relative to the handle 10 to cause an internal trigger lock to engage one of a series of ratcheting-lock points that define a set of locking locations for the jaws 35, 45, as described further below. Movement of the thumb slide 25 proximally relative to the handle 10 releases the trigger 20 and the jaw assembly 90, allowing the jaws 35, 45 to return to a fully open position. The interaction of the trigger 20, thumb slide 25 and the associated trigger lock mechanism frees the physician from the need to maintain pressure on the trigger 20 to compress tissue between the jaws 35, 45 during the ablation, simplifying operation of the hemostat.

Referring to FIG. 2, the upper jaw assembly 30 includes a pivotable, relatively rigid, upper jaw mount 300, an

6

elongated backbone 310, an elongated insulated electrode sheath 320, an elongated conductive electrode 330, and an elongated electrode support 340. Upper jaw mount 300 may be fabricated of plastic or other insulated material, and in preferred embodiments may be fabricated of Teflon filled polycarbonate plastic. Backbone 310 is preferably fabricated of malleable stainless steel or other malleable metal and is attached at a proximal end to upper jaw mount 300. An insulated electrode sheath 320 is fitted over spine 310 with its proximal end located adjacent upper jaw mount 300. The elongated conductive electrode 330 comprises a length of malleable conductive metal tubing as shown in FIGS. 5A and 5B is fitted into a lumen of the elongated electrode support 340. The insulated electrode sheath 320 is formed with a channel that receives the sub-assembly of the elongated conductive electrode 330 and electrode support 340 disposed along the jaw 35. Electrode sheath 320 may be fabricated of a flexible, electrically insulating, material, for example, silicone rubber. Elongated electrode support 340 is preferably fabricated of a porous material, such as Porex™ plastic, allowing for conductive fluid infiltration through its sidewall along its length and correspondingly delivery of conductive fluid along the length of jaw 35. The jaw 35 can therefore be bent laterally with respect to the upper jaw mount 300 to form a curve along the length thereof.

The lower jaw assembly 40 also includes a relatively rigid, lower jaw mount 400, an elongated backbone 410, an elongated insulated electrode sheath 420, an elongated conductive electrode 430, and an elongated electrode support 440 that are all formed of the same materials as the corresponding elements of the upper jaw assembly 30. The assembly of the elongated backbone 410, elongated insulated electrode sheath 420, elongated conductive electrode 430, and elongated electrode support 440 is also shown in FIG. 3B.

The jaw 45 can therefore also be bent laterally with respect to the lower jaw mount 400 to form a curve along the length thereof. In use, the physician manually forms a lateral curve in both the upper and lower jaws 35 and 45 to fit the contour of the tissue, e.g., the heart wall.

The lower jaw mount 400 is formed with a pair of spaced apart, parallel, plates or flanges 401 and 403 each bearing a series of notches 402 and 404, respectively, along the edges thereof. When assembled, a proximal portion of the upper jaw mount 300 is fitted between the flanges 401 and 403. A pin 480 extends through aligned holes through the proximal portion of upper jaw mount 300 and the flanges 401 and 403. The ends of pin 480 are fixed to the flanges 401 and 403 allowing the proximal portion of the upper jaw mount 300 to be rotated about the pin 480, thereby allowing jaws 35 and 45 to open and close. The upper and lower jaws 35 and 45 are separated apart a predetermined distance in the fully closed positions although the electrically insulated distal ends of the insulated electrode sheaths 320 and 420 may contact one another. A spring 450 urges the upper and lower jaws 35 and 45 apart from one another, facilitating opening of the jaws 35 and 45 upon release of the trigger 20 after application of RF energy.

As shown in FIGS. 2 and 3A, the swivel assembly 50 includes a swivel 500 that may also be fabricated of Teflon filled polycarbonate plastic to have a tubular proximal swivel portion 506, a pair of parallel plates or flanges 502 and 504 extending distally from swivel proximal portion 506 and an extending detent 501 extending laterally between flanges 502 and 504. The jaw assembly 90 is mounted to the swivel assembly 50 by outwardly and laterally extending bosses 405 on the outer surfaces of flanges 401 and 403 that

are fitted into bores 503 through swivel flanges 502 and 504. The upper jaw mount 300 is mounted to the lower jaw mount 400 by pin 480 as described above, and the lower jaw mount is 400 pivotably mounted relative to the swivel 500. Therefore, the upper and lower jaw assemblies 30 and 40 may be pivoted together relative to the swivel 500, allowing for movement of the jaws 35 and 45 together through the range of pitch P adjustment. The selected pitch P adjustment is maintained by the engagement of the detent 501 into an opposed pair of notches 402 and 404, stabilizing the upper and lower jaws 35 and 45 in a desired orientation relative to the swivel assembly 50. In use, the physician adjusts the relative positions of the jaws 35 and 45 relative to the swivel assembly 50 by simply manually moving the jaw assemblies 30 and 40 in the pitch P direction around the pivot axis defined by bosses 405 within the corresponding bores 505 in swivel flanges 502 and 504. The detent 501 simply rides over the ridges separating adjacent notches 402 and 404.

As noted above, the swivel assembly 50 and the upper and lower jaw assemblies 30 and 40 can be rotated around the axis of the distal end 15 of the handle 10 to a desired roll adjustment R to facilitate positioning the jaws 35 and 45 for creation of elongated lesions. The proximal portion 506 of swivel 500 is rotatably mounted within a collar 550 that is mounted fixedly to the distal end 15 of the handle 10 as shown in FIG. 3A. The collar 550 has a wavy or sinusoidal distally facing surface 551 of collar 550. A washer-shaped insert 510 having a wavy or sinusoidal proximally facing surface 511 is fitted over the elongated proximal portion 506 of swivel 500 and attached to the swivel 500 through notches 514, engaging corresponding bosses 557 and 567 (shown in FIG. 4) formed on swivel 500. A C-clip 524 mounted in a circumferential groove formed in the proximal portion 506 of swivel 500 maintains the proximal portion 506 within the lumen of collar 550. A spring washer 522 and a flat washer 520 are interposed between the C-clip 524 and the proximal end of collar 550. Spring washer 522 urges the wavy or sinusoidal surfaces of collar 550 and insert 510 against one another, whereby a plurality of detent locations are defined that maintain a selected roll R adjustment relative to the distal end 15 of the handle 10. In use, the physician adjusts the roll R of the jaw assembly 90 by simply turning the swivel assembly 50 relative to the handle 10. The detent mechanism maintains the swivel assembly 50 in the selected desired roll R adjustment prior to and during closure of the jaws 35, 45 to compress tissue during application of RF energy.

A cable 390 is also shown in FIGS. 3A and 4 that extends from the trigger 20 and that is employed to open and close the jaws 35 and 45. Cable 390 passes through the internal lumen of proximal swivel portion 502, through cable bore 565, around shoulder 404 of lower jaw mount 400, around boss 303 in upper jaw mount 300 and then upward into bore 408 in lower jaw mount 400. The distal end of the cable 390 is maintained within bore 408 by ball 350. When the cable 390 is pulled proximally by squeezing trigger 25, boss 303 of upper jaw 300 is pulled toward bore 408 in lower jaw 400, thereby pulling upper jaw 35 toward lower jaw 45, allowing for compression of tissue there between. It should be noted that during this operation, the lower jaw mount 400 remains fixed relative to the swivel assembly 50 and only upper jaw mount 300 moves relative to the swivel assembly 50 or the handle 10. Proximal movement of cable 380 does not affect the position of the lower jaw 45 relative to the handle 10, nor does it affect the selected roll R adjustment of swivel 500. Rotation of the jaw assembly 90 and swivel 500 about the roll axis does not affect the operation of the cable 390

because the cable 390 passes through the swivel 500 and enters the jaw assembly 90 along the roll axis. Pitch P adjustment of the jaw assembly 90 does not significantly effect operation of the cable 390 in opening or closing the jaws 35, 45 because shoulder 404 is at the center of rotation of lower jaw mount 400 relative to swivel 500 and remains essentially in the same location regardless of the pitch P adjustment.

FIGS. 3A and 4 also internal electrical wiring and fluid delivery conduits of this embodiment of the invention including, insulated conductors 360 and 460 and fluid conduits 370 and 470 that both terminate at connections with the proximal ends of the upper and lower electrodes 330 and 430, respectively. The fluid conduits 370 and 470 deliver conductive fluid into the lumens of the tubular upper and lower electrodes 330 and 430, respectively. As shown in FIG. 4, the upper insulated conductor 360 and the upper fluid conduit 370 are routed to one side of the cable 390, and the lower insulated conductor 460 and the lower fluid conduit 470 are routed to the other side of the cable 390 while passing through the lumen 534.

The elongated tubular electrodes 330 and 430 are illustrated in FIGS. 5A and 5B. The tubular electrodes 330 and 430 are preferably formed of thin-walled, malleable stainless steel tubing extending between a proximal open end 331, 431 and a distal closed end 333, 433. A series of fluid ports 335, 435 are formed, e.g., by laser drilling, through the sidewall of the tubing from the lumen 339, 439 and extending in a single line, although the fluid ports could be formed in any selected array extending around the circumference of the sidewall of the tubing. The proximal ends 331, 431 are notched in alignment with the series of fluid ports 335, 435 to assist in assembly so that the fluid ports 335, 435 are directed in a particular alignment with the porous electrode support 340, 440.

The porous electrode support 340, 440, depicted in FIGS. 6A and 6B, comprises a length of non-conductive, porous, malleable tubing having a channeled side 343, 443 adapted to fit within an elongated channel 323, 423 of the insulated electrode sheath 320, 420, depicted in FIGS. 7A and 7B. The porous electrode support 340, 440 is conically shaped at the support distal end 347, 447 to fit within a conically shaped terminus 327, 427 of the elongated channel 323, 423 of the insulated electrode sheath 320, 420. During assembly, the elongated tubular electrode 330, 430 is inserted into the elongated lumen 341, 441 of the porous electrode support 340, 440. Preferably, the series of fluid ports 335, 435 are oriented toward the channeled side 343, 443 so that the conductive fluid emitted from the lumen through the series of fluid ports 335, 435 then migrates laterally through the pores of the porous electrode support 340, 440 and around its circumference to thoroughly and uniformly wet the porous electrode support 340, 440 along the upper and lower jaws 35 and 45.

The sub-assembly so formed is fitted into the shaped terminus 327, 427 and the elongated channel 323, 423 of the insulated electrode sheath 320, 420 as also shown in FIGS. 3A and 3B. Adhesive is applied to the contacting surfaces 323, 343 and 423, 443 to maintain the sub-assembly of the elongated tubular electrode 330, 430 inserted into the elongated lumen 341, 441 of the porous electrode support 340, 440 affixed to the insulated electrode sheath 320, 420. The adhesive does not block migration of conductive fluid around the porous electrode support 340, 440. Electrode sheath 320, 420 is also formed having an elongated tapered internal recess 421 441 that receives the malleable backbone 310, 410 as shown in FIGS. 2 and 3. Again, adhesive may

be applied to the contacting surfaces of the backbone 310, 410 and the elongated tapered internal recess 421 441.

The handle 10 is formed of a right handle half 600 depicted in FIGS. 8A–8C and a left handle half 700 depicted in FIGS. 9A–9C. Trigger sections 620 and 720 of the respective right and left handle halves 600 and 700 include downwardly opening recesses 621 and 721 in which trigger 20 is mounted (as shown in FIGS. 1 and 10) to pivot inward to apply tension on cable 390 or outward to release tension on cable 390. Upward openings 627 and 727 in respective right and left handle halves 600 and 700 receive the thumb slide 25. Inwardly extending projections 630 and 730 are also formed in respective right and left handle halves 600 and 700 that function to constrict the fluid conduits 370 and 470 to prevent conductive fluid flow therethrough when the trigger 20 is released as described further below.

A set of circular matching, laterally opposed, sockets 623 and 723 are formed in the interior surfaces of the respective right and left handle halves 600 and 700. The set of sockets 623, 723, receive a pair of pivot bosses 206, 206' of trigger 20 (shown in FIG. 13A) about which the trigger 20 pivots as described further below. A set of matching, laterally opposed, and slightly elongated or oblong, sockets 624 and 724 are formed in the interior surfaces of the respective right and left handle halves 600 and 700. The set of sockets 624, 724 receive and guide a trigger lock 27 (shown in FIGS. 11A and 11B) that interacts with trigger 20 as described further below. The oblong shape of the set of sockets 624, 724 assists in allowing the trigger 20 to ratchet along the trigger lock 27 when trigger is drawn inward to tension the cable 390 during closing of the jaws 35, 45 as described further below.

A further set of matching, laterally opposed, elongated sockets 625 and 725 are also formed in the interior surfaces of the respective right and left handle halves 600 and 700. The set of sockets 625, 725 receive and guide a link arm 26 (shown in FIGS. 12A and 12B) that interacts with trigger 20 as described further below.

As shown in FIGS. 8B and 9B, the distal portions of right and left handle halves 600 and 700 are formed with internal cylindrical recesses or sockets 612 and 712 that receive the laterally extending bosses 552 of collar 550 (FIG. 2). Internal grooves 611 and 711 are also formed within the distal portions of right and left handle halves 600 and 700 in which the c-clip 524, flat washer 520 and spring washer 522 (FIGS. 2 and 3A) are fitted.

As shown in FIGS. 8C and 9C, the right and left handle halves 600 and 700 are also provided with a series of laterally extending, perpendicular internal walls 628 and 728 that include slots and recesses for routing the fluid conduits or tubes 370 and 470, the cable 390 and the insulated wire conductors 360 and 460 that extend through the length of handle 10.

The trigger 20, thumb slide 25, and the associated link arm 26 and trigger lock 27 are shown assembled to the right handle half 600 in FIG. 10 with the trigger 20 in the released position and the thumb slide 25 in the unlocked distal or retracted position. The trigger lock 27 is shown in greater detail in FIGS. 11A–11B, the link arm 26 is shown in greater detail in FIGS. 12A–12B, and the trigger 20 is shown in isolation in FIGS. 13A–13B.

Trigger 20 is provided with laterally extending cylindrical pivot bosses 206, 206' that are mounted into sockets 723 and 623, respectively. When released, trigger 20 extends outward through downwardly opening recesses 621 and 721. When pulled, trigger 20 is pivoted inwardly into the handle recesses 621 and 721 about pivot bosses 206, 206' to apply

tension to the cable 390 that draws the upper and lower jaws 35 and 45 together. Cable 390 is mounted within a lubricious tube 391, extending from the proximal wall 628 to the distal end 15 of the handle 10, to allow the cable 390 to move freely within the handle 10 when trigger 20 is pulled or released.

Trigger 20 is coupled to the proximal end of cable 390 through link arm 26, illustrated in isolation in FIGS. 12A and 12B. Link arm 26 is provided at a distal end with two laterally extending bosses 262 and 262' that are received in circular sockets 204 (one of which is shown in FIG. 13B) formed on the interior walls of the internal chamber 202 of trigger 20 to thereby pivotally mount the distal end of the link arm 26 to the trigger 20. Link arm 26 is formed with a longitudinally extending slot 266, allowing compression of the distal end of the link arm 26 to facilitate positioning of cylindrical bosses 262 and 262' within the corresponding sockets 204 within the trigger 20. As also shown in FIG. 13B, longitudinal slots 215 are provided in the interior 202 to assist insertion of the bosses 262, 262' on link arm 26 into sockets 204 in trigger 20 during assembly. Link arm 26 is provided at its proximal end with two laterally extending, circular bosses 264 and 264' that are received within the elongated slots 625 and 725, respectively, in the respective right and left handle halves 600 and 700. When trigger 20 is released, the circular bosses 264 and 264' are disposed at the distal ends of the opposed elongated slots 625 and 725, respectively. When trigger 20 is pulled inward, the proximal end of the link arm 26 is moved proximally within the opposed slots 625 and 725, applying tension to cable 390.

Cable 390 is coupled to the link arm 26 by means of a swaged retainer 24, mounted within a coil spring 28. Coil spring 28 is fitted within a generally cylindrical chamber 266 formed extending at 90 degrees to the proximal end of link arm 26. Cable 390 passes through an upwardly facing slot 270 in link arm 26 and through the interior of spring 28 to retainer 24. Spring 28 is normally extended within chamber 266 but is compressed to provide protection against over tensioning of the cable 390, if the upper and lower jaws 35 and 45 encounter significant resistance to further movement toward one another. The configuration of the trigger 20, link arm 26 and slots 625 and 725 provide a mechanism whereby, the cable 390 is pulled proximally relatively quickly during initial upward movement of the trigger 20 to facilitate initial rapid closing of the jaws 35 and 45. The cable 390 is pulled relatively more slowly during further upward movement of the trigger 20 to provide increased control to the physician during final compression of the jaws 35 and 45 against the tissue to be ablated.

Trigger 20 is also provided with a distally extending projection 208 terminating with a laterally extending, generally cylindrical, boss 210 shown best in FIG. 13B. As illustrated in FIG. 10, when the trigger 20 is released and in its most downward position (corresponding to the point of maximum jaw opening), the fluid conduits or tubes 370 and 470 are disposed side by side and compressed between cylindrical boss 210 and the inwardly extending projections 630 and 730. This compression of the fluid conduits or tubes 370 and 470 prevents flow of conductive fluid from the fluid source and out of the electrodes 330 and 430 and the electrode mounts 340 and 440 when the hemostat is not in use.

The trigger 20 is also formed with a laterally extending slot 212 having an array of teeth 214 formed along one side of the slot 212. A trigger lock mechanism is provided involving the interaction of the thumb slide 25 with the trigger 20 through a trigger lock 27 that is coupled at one end

11

with the thumb slide 25 and selectively engages the teeth 214 to retain the upper and lower jaws 35 and 45 at a fixed position adjacent tissue to be ablated without requiring the physician to continually apply pressure to trigger 20. Distal or forward movement of the thumb slide 25 causes the trigger lock 27 to engage the teeth 214, and proximal or rearward movement of the thumb slide 25 releases the engagement. The trigger 20 can be operated freely by the physician to open or close the upper and lower jaws 35 and 45 when the thumb slide 25 is in the rearward position. With the thumb slide 25 in the forward position, the trigger 20 can be moved inward ratcheting over the teeth 214 to close the upper and lower jaws 35 and 45, but the trigger 20 will not move outward upon release by the physician.

The trigger lock 27 depicted in isolation in FIGS. 11A and 11B comprises an elongated link arm 275 having rods 272 and 278 laterally extending parallel to one another from opposed ends of the link arm 275. As shown in FIG. 10, the rod 272 is inserted through the slot 202 so that the link arm 275 extends alongside the trigger 20 within the recess 721. The rod 278 extends into a generally centrally located notch 252 of a resilient beam section 250 of the thumb slide 25. Cylindrical pivot bosses 276 and 276' extend laterally on either side of the link arm 275 in alignment with rod 272 and are inserted into sockets 724 and 624, respectively.

The rod 272 inserted through the slot 212 extending through the trigger 20 is formed with a laterally extending ramped tooth 274 that is selectively engagable with one of the ramped teeth 214 formed along the proximal edge of slot 212, when the trigger lock 27 is pivoted forward from the position illustrated in FIG. 10 by distal or forward movement of the thumb slide 25 by the physician. Movement of the trigger 20 inwardly into the handle recess with the trigger lock 27 advanced forward from the position illustrated in FIG. 10 causes the interaction of the tooth 274 on the trigger lock 27 with the teeth 214 to retain the trigger 20 in position when pressure is released. The oblong configuration of sockets 624 and 724 that receive bosses 276' and 276 of the trigger lock 27 allow the trigger lock 27 to move slightly forward during inward movement of the trigger 20 so that the tooth 276 on trigger lock 27 may ratchet along the ramped teeth 214 of trigger 20. Interaction of the teeth 214 with the ramped tooth 274 on the trigger lock 27 prevents outward movement of the trigger 20 as long as the thumb slide 25 remains in the forward position in the slot formed by openings 627 and 727.

Release of the trigger 20 is accomplished by proximal or rearward movement of thumb slide 25, pivoting the ramped tooth 274 out of engagement with a tooth of the teeth 214 along slot 212 which allows the upper and lower jaws 35 and 45 to open unless the physician holds the trigger 20 in position. The trigger 20 is urged outwardly out of the recess in handle 10 by spring 23 upon release of the trigger 20 and rearward movement of the thumb slide 25. When the trigger 20 reaches its full outward position, flow of conductive fluid through fluid conduits 370 and 470 is terminated as the tubing is compressed between the laterally extending boss 210 and the inwardly extending projections 630 and 730, as discussed above.

The thumb slide 25 is provided with a resilient beam section 250, having a generally centrally located notch 252 which engages the laterally extending rod 278 on trigger lock 27, coupling the thumb slide 25 to the trigger lock 27. The thumb slide 25 is preferentially retained at either the proximal, rearward or distal, forward point of its travel, without the necessity of the physician manually maintaining

12

pressure on the thumb slide 25 due to the resilience of the beam 250 and the arcuate path of travel of the rod 278.

FIG. 14 illustrates a proximal portion of the assembled hemostat of FIG. 1 with the left handle half 700 removed to show the multi-conductor cable 80 and fluid conduit 70 extending through the strain relief 60 and their joiner to the wire conductors 360, 460 and the fluid conduits 370, 470.

The distal end of the fluid conduit 80 is coupled through a fitting 802 to proximal end of flexible tubing 804. The distal end of flexible tubing 804 is coupled to the trunk of a Y-connector 806, and the distal legs of the Y connector 806 are coupled to arms of a D-connector 810. The D connector 810 is formed of a flexible plastic, e.g., silicone rubber, providing spaced apart fluid channels that are coupled to the proximal ends of the fluid conduits 370 and 470.

The fitting 804 supports a proximal flow controller or regulator 820 that has a precisely sized orifice that limits conductive fluid flow into the Y-connector 806. The flow regulator 820 establishes a fixed flow rate and pressure within the Y-connector 806 regardless of the pressure of the fluid source that is available in the surgical theatre. The flow rate is established depending upon the upper and lower electrode area and design.

The D connector 810 supports a pair of downstream flow regulators 822 and 824 that have equal, precisely sized orifices that further reduce the fluid flow rate and pressure of the conductive fluid entering the fluid conduits 370 and 470. The downstream flow regulators 822 and 824 ensure that an even flow of conductive fluid is provided from within the Y connector 806 into the fluid conduits 370 and 470. By this mechanism, the hemostat may be operated without the necessity of an associated pressurized fluid source and still provide controlled and even fluid flow to the upper and lower jaws 35 and 45 that contact the tissue to be ablated.

An optional light emitter, e.g., an LED 830, is depicted in FIG. 14 located within the strain relief 60 and coupled through an electrical junction 832 with the insulated wire conductors 360 and 460. The wire conductors 360 and 460 can take the form of a twisted wire cable that extends distally from the electrical junction 832 through the length of the handle to the swivel assembly 50 where they are separated as shown in FIGS. 3A and 4. Separate wire conductors within a cable 834 extend from the electrical junction 832 to the LED 830. In use, the LED 830 is illuminated in response to activation of an associated RF electrosurgical generator, and the LED illumination illuminates the strain relief 60, which is preferably fabricated of a translucent flexible material, such as silicone rubber or the like. The physician will typically hold the handle 10 in orientations that make the strain relief 60 visible, and illumination of the LED 830 indicates to the physician that RF energy is being applied to the electrodes.

The proximal portion of the handle 10 may also optionally carry other electronic components including circuitry containing calibration information, for example calibrating a thermocouple if provided to sense electrode or tissue temperature. Circuitry containing identification information or providing re-use prevention may also be included, however such features are not believed to be essential to or a part of the present invention.

FIGS. 15A and 15B illustrate an alternative embodiment of the electrode described above that can be employed in modified upper and lower jaw assemblies 30A and 40A corresponding generally to upper and lower jaw assemblies 30 and 40. The upper and lower jaw assemblies 30A, 40A have a malleable backbone 310, 410 and a sheath 320, 420 as described above that are attached to the respective upper

13

and lower jaw mounts **300** and **400** as shown in FIGS. **2** and **3**. However, electrode **330A**, **430A** incorporates an exposed elongated electrode extension **350A**, **450A** extending to the outer surface of porous electrode support **340A**, **440A** and along the jaw **35**, **45** that is intended to directly contact the tissue to be ablated. In this embodiment, conductive fluid is delivered as described above into the lumen of the internal tubular electrode **330A**, **430A**, which may be substantially the same as the tubular electrodes **330**, **430**. An elongated electrode surface **352A**, **452A** of the electrode extension **350A**, **450A** and the contacted tissue are irrigated by conductive fluid emitted through the fluid ports of the internal tubular electrode **330A**, **430A** and conducted through the pores of the electrode support **340A**, **440A**.

The electrode extension **350A**, **450A** is depicted prior to assembly with the electrode support **340A**, **440A** and the elongated tubular electrode **330A**, **430A** in FIGS. **16A** and **16B**. As formed, the electrode extension **350A**, **450A** includes an elongated straight portion **352A**, **452A** that is mounted against the exposed to the exterior of the electrode support **340A**, **440A**. A distally extending portion **360A**, **460A** is adapted to be inserted into the lumen of the electrode support **340A**, **440A** to extend alongside the elongated tubular electrode **330A**, **430A** as shown in FIG. **15B**.

A series of barbed projections **354A**, **454A** extend laterally away from the elongated straight portion **352A**, **452A**. The electrode extension **350A**, **450A** is adapted to be bent back at junction **356A**, **456A** to enable insertion of the series of barbed projections **358A**, **458A** into the electrode support **340A**, **440A**. The proximal end **362A**, **462A** is electrically connected to the proximal ends of the tubular electrodes **330A**, **430A** and the distal ends of the wire conductors **360**, **460**.

This alternative exposed electrode embodiment can be formed by modifying the tubular electrode **330**, **430** to have a conductive electrode band extending from the tubular electrode along the surface of the electrode support **340**, **440**. Alternatively, this alternative electrode design can be accomplished without use of the tubular electrode **330**, **430**, whereby conductive fluid is delivered to a lumen of the electrode support **340**, **440** or to a fluid channel between the electrode support **340**, **440** and the sheath **320**, **420**, and the exposed electrode band is supported by the electrode support **340**, **440**.

The embodiments of the electrosurgical hemostat described above contain a number of valuable features and components, all of which contribute to provide a hemostat, which is convenient to use while providing substantial flexibility in use. However, many of the features of the hemostat could be employed in hemostats of other designs. For example, the trigger mechanism and/or the trigger lock mechanism of the above-described hemostat would certainly be of use in conjunction with cable activated hemostats having jaws of alternative designs to that described above. Similarly, the jaw assembly of the present hemostat might well be employed in conjunction with alternative trigger mechanisms. And/or in conjunction with alternative electrode designs, including electrodes which might not include provision for fluid irrigation and/or in the context of the hemostat having jaws that are rigid and not malleable by the physician to assume desired configurations. Further the specific electrode design employed in the hemostat design described above would be of significant use in conjunction with other hemostat types, including hemostats having jaws which are moved toward one another by alternative mechanisms. Similarly, a strain relief of the type described above including an LED indicator is believed to be of value in

14

conjunction with any number of electrosurgical tools, particularly those in which the strain relief is within the physician's field of view, during normal operation of the hemostat. As such, the above description should be taken as exemplary, rather than limiting, with regard to the claims which follow.

We claim:

1. A device for performing a surgical procedure, comprising:

an elongated handle;

a pair of closeable jaws on a distal portion of the handle; means on at least one of the jaws for ablative treatment of tissue;

means for closing the jaws on tissue;

means for adjusting roll and pitch of the pair of jaws relative to the handle, wherein roll is manually adjustable; and

means for retaining a selected roll position such that the jaws can be closed on tissue without changing the selected roll position, wherein the means for retaining the selected roll position includes at least one detent and wherein the means for retaining the selected roll position includes spring means biasing the detent.

2. The device according to claim 1 also comprising means for retaining a selected roll position such that the jaws can be opened from a closed position without changing the selected roll position.

3. A device for performing a surgical procedure, comprising,

an elongated handle;

a pair of closeable jaws on a distal portion of the handle; means on at least one of the jaws for ablative treatment of tissue;

means for closing the jaws on tissue;

means for adjusting roll and pitch of the pair of jaws relative to the handle, wherein pitch is manually adjustable; and

means for retaining a selected pitch position such that the jaws can be closed on tissue without changing the selected pitch position, wherein the means for retaining the selected pitch position includes at least one detent and wherein the means for retaining the selected pitch position includes spring means biasing the detent.

4. The device according to claim 3 also comprising means for retaining a selected pitch position such that the jaws can be opened from a closed position without changing the selected pitch position.

5. The device according to claim 3 wherein the range of adjustment of pitch is at least about 90 degrees.

6. The device according to claim 3 wherein the jaws may be closed on tissue in a pre-selected curved or straight configuration.

7. The device according to claim 6 wherein each of the jaws are manually shapeable.

8. The device according to claim 7 wherein each of the jaws include at least one malleable component.

9. A device for performing a surgical procedure, comprising,

an elongated handle, wherein the handle has a proximal longitudinal axis and a distal longitudinal axis, the distal longitudinal axis laterally offset from the proximal longitudinal axis, and wherein the handle has an "S" shape;

a pair of closeable jaws on a distal portion of the handle; means on at least one of the jaws for ablative treatment of tissue;

means for closing the jaws on tissue; and



## 15

means for adjusting roll and pitch of the pair of jaws relative to the handle.

10. The device according to claim 9 wherein the means for closing the jaws includes a trigger mounted on the handle.

11. The device according to claim 9 wherein the means for closing the jaws includes a lock mounted on the handle that holds the jaws in a selected relative position.

12. The device according to claim 11 wherein the lock is engaged by means of at least one detent.

13. The device according to claim 9 wherein the means for closing the jaws includes a means for limiting the force applied to tissue by the jaws.

14. The device according to claim 13 wherein the means for limiting force includes spring means coupling the trigger and at least one of the jaws.

15. The device according to claim 9 wherein the means for closing the jaws includes a trigger coupled to at least one of the jaws by means providing progressively greater control of jaw movement as the jaws close.

16. The device according to claim 15 wherein the means providing progressively greater control of jaw movement includes a link arm.

17. The device according to claim 9 wherein the means for closing the jaws includes means for closing a first, upper jaw of the pair of jaws while maintaining the second, lower jaw of the pair of jaws in a stationary position.

18. The device according to claim 17 wherein a trigger is operatively coupled to the upper jaw and not the lower jaw.

19. The device according to claim 9 wherein the means for ablative treatment of tissue includes a fluid channel.

20. The device according to claim 9 wherein the means for ablative treatment of tissue includes an electrode.

21. A device for performing a surgical procedure, comprising,

an elongated handle;

a pair of closeable jaws on a distal portion of the handle; means on the jaws for ablative treatment of tissue; and means for closing the jaws on tissue, including a movable trigger; and

means for locking the trigger in a selected position, wherein the means for locking the trigger comprises a slide coupled to a trigger lock, wherein the trigger lock comprises at least one detent, wherein the detent comprises a ramped tooth engagable with a series of ramped teeth on the trigger, and wherein the ramped tooth is rotatable into and out of engagement by movement of the slide.

22. The device according to claim 21 wherein the means for closing the jaws includes at least one tensioning cable.

23. The device according to claim 22 wherein the cable resides within a lubricious tube.

24. The device according to claim 21 wherein the means for closing the jaws on tissue includes at least one spring means biasing the jaws into an open position.

25. The device according to claim 21 wherein the trigger pivots upwardly into the handle.

26. The device according to claim 21 wherein the jaws may be closed on tissue in a pre-selected curved or straight configuration.

27. The device according to claim 21 wherein each of the jaws are manually shapeable.

28. The device according to claim 27 wherein each of the jaws include at least one malleable component.

29. A device for performing a surgical procedure, comprising,

an elongated handle, wherein the handle has a proximal longitudinal axis and a distal longitudinal axis, the

## 16

distal longitudinal axis laterally offset from the proximal longitudinal axis, and wherein the handle has an "S" shape;

a pair of closeable jaws on a distal portion of the handle; means on the jaws for ablative treatment of tissue;

means for closing the jaws on tissue, including a movable trigger; and

means for locking the trigger in a selected position.

30. The device according to claim 29 wherein the means for closing the jaws includes a means coupled to the trigger for limiting the force applied to tissue by the jaws.

31. The device according to claim 30 wherein the means for limiting force includes a spring.

32. The device according to claim 29 wherein the trigger is coupled to at least one of the jaws by means providing progressively greater control of jaw movement as the jaws close.

33. The device according to claim 32 wherein the means providing progressively greater control of jaw movement includes a link arm.

34. The device according to claim 29 wherein the means for closing the jaws includes means for closing a first, upper jaw of the pair of jaws while maintaining the second, lower jaw of the pair of jaws in a stationary position.

35. The device according to claim 34 wherein a trigger is operatively coupled by means of a cable to the upper jaw and the lower jaw.

36. The device according to claim 29 wherein the means for ablative treatment of tissue includes a fluid channel.

37. The device according to claim 29 wherein the means for ablative treatment of tissue includes an electrode.

38. A device for performing a surgical procedure, comprising:

an elongated handle;

a pair of closeable jaws on a distal portion of the handle; means on at least one of the jaws for ablative treatment of tissue;

means for closing the jaws on tissue;

means for manually adjusting roll of the pair of jaws relative to the handle; and

means for retaining a selected roll position such that the jaws can be closed on tissue without changing the selected roll position, wherein the means for retaining the selected roll position includes at least one detent and spring means biasing the detent.

39. The device according to claim 38 wherein the jaws may be closed on tissue in a pre-selected curved or straight configuration.

40. The device according to claim 38 wherein each of the jaws are manually shapeable.

41. The device according to claim 40 wherein each of the jaws include at least one malleable component.

42. The device according to claim 38 wherein the means for ablative treatment of tissue includes an electrode.

43. The device according to claim 38 further comprising means for manually adjusting pitch of the pair of jaws relative to the handle.

44. The device according to claim 38 wherein the handle is an elongated "S" shaped handle having a proximal longitudinal axis and a distal longitudinal axis, the distal longitudinal axis laterally offset from the proximal longitudinal axis.

45. A device for performing a surgical procedure, comprising,

an elongated handle;

a pair of closeable jaws on a distal portion of the handle;

17

means on at least one of the jaws for ablative treatment of tissue;

means for closing the jaws on tissue;

means for manually adjusting pitch of the pair of jaws relative to the handle; and

means for retaining a selected pitch position such that the jaws can be closed on tissue without changing the selected pitch position, wherein the means for retaining the selected pitch position includes at least one detent and spring means biasing the detent.

46. The device according to claim 45 wherein the jaws may be closed on tissue in a pre-selected curved or straight configuration.

47. The device according to claim 45 wherein each of the jaws are manually shapeable.

48. The device according to claim 47 wherein each of the jaws include at least one malleable component.

49. The device according to claim 45 wherein the means for ablative treatment of tissue includes an electrode.

50. The device according to claim 45 further comprising means for manually adjusting roll of the pair of jaws relative to the handle.

51. The device according to claim 45 wherein the handle is an elongated "S" shaped handle having a proximal longitudinal axis and a distal longitudinal axis, the distal longitudinal axis laterally offset from the proximal longitudinal axis.

18

52. A device for performing a surgical procedure, comprising,

an elongated "S" shaped handle having a proximal longitudinal axis and a distal longitudinal axis, the distal longitudinal axis laterally offset from the proximal longitudinal axis;

a pair of jaws on a distal portion of the handle, wherein the roll or pitch of the pair of jaws relative to the handle may be manually adjusted and the pair of jaws may be closed on tissue; and

at least one ablative element on at least one of the jaws for ablative treatment of tissue.

53. The device according to claim 52 wherein roll is manually adjustable.

54. The device according to claim 52 wherein pitch is manually adjustable.

55. The device according to claim 52 wherein the jaws may be closed on tissue in a pre-selected curved or straight configuration.

56. The device according to claim 52 wherein each of the jaws are manually shapeable.

57. The device according to claim 56 wherein each of the jaws include at least one malleable component.

58. The device according to claim 52 wherein the ablative element includes an electrode.

\* \* \* \* \*