



US00D340917S

United States Patent [19]

[11] Patent Number: Des. 340,917

Sakaguchi et al.

[45] Date of Patent: ** Nov. 2, 1993

[54] MEMORANDUM INPUT AND OUTPUT DEVICE

D. 333,298 2/1993 Raslowsky et al. D18/7 X

[75] Inventors: Hiroshi Sakaguchi, Kyoto; Shinsaku Hino, Nara; Makiko Yoshimura, Nara; Koji Nishida, Nara, all of Japan

Primary Examiner—Wallace R. Burke
Assistant Examiner—Freda S. Nunn
Attorney, Agent, or Firm—Nixon & Vanderhye

[73] Assignee: Sharp Kabushiki Kaisha, Osaka, Japan

[57] CLAIM

[**] Term: 14 Years

The ornamental design for a memorandum input and output device, as shown and described.

[21] Appl. No.: 786,428

DESCRIPTION

[22] Filed: Nov. 1, 1991

FIG. 1 is a top plan view of a memorandum input and output device showing our new design in the closed position;

[30] Foreign Application Priority Data

May 29, 1991 [JP] Japan 3-15786

FIG. 2 is a bottom plan view thereof;

[52] U.S. Cl. D14/100; D18/7

FIG. 3 is a front elevational view thereof;

[58] Field of Search D14/100, 106, 115;

FIG. 4 is a rear elevational view thereof;

D18/7; 340/700, 706; 341/22, 23; 235/145 A, 145 R; 364/706-709.09

FIGS. 5 and 6 are right and left side elevational views thereof;

[56] References Cited

U.S. PATENT DOCUMENTS

- D. 308,692 6/1990 Sakaguchi et al. D18/7
- D. 324,513 3/1992 Sakaguchi et al. D18/7 X
- D. 328,089 7/1992 Haneda D18/7 X

FIG. 7 is a left side elevational view thereof with the cover in an open position;

FIG. 8 is a right side elevational view thereof;

FIG. 9 is a front elevational view thereof;

FIG. 10 is a top plan view thereof;

FIG. 11 is a rear elevational view thereof with the cover in the open position; and,

FIG. 12 is a bottom plan view thereof with the cover in an open position.






FIG. 1




FIG. 2




FIG. 3



FIG. 4



FIG. 5




FIG. 6




FIG. 7



FIG. 8

FIG. 9



FIG. 10




FIG. 11



FIG. 12

