



US006439923B1

(12) **United States Patent**
Kirkendall et al.

(10) **Patent No.:** **US 6,439,923 B1**
(45) **Date of Patent:** **Aug. 27, 2002**

(54) **UNIVERSAL WIRING HARNESS FOR AUTOMATIC TRANSMISSION**

(75) Inventors: **W. Scott Kirkendall**, Laurinburg;
Richard J. Dimond, III, West End,
both of NC (US)

(73) Assignee: **Rostra Precision Controls, Inc.**,
Laurinburg, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/448,118**

(22) Filed: **Nov. 24, 1999**

(51) **Int. Cl.**⁷ **H01R 11/00**

(52) **U.S. Cl.** **439/502**

(58) **Field of Search** 439/34, 502, 623,
439/624; 174/72 A

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,819,848 A	*	6/1974	Fry	174/72 A
4,477,801 A	*	10/1984	Robinson, Jr. et al.	340/684
5,168,842 A	*	12/1992	Brooks	123/143
5,501,605 A	*	3/1996	Ozaki et al.	439/34
5,549,344 A	*	8/1996	Nishijima et al.	296/70
5,610,447 A	*	3/1997	Nishikawa et al.	307/38
5,668,415 A	*	9/1997	Nagami	307/9.1
5,829,129 A	*	11/1998	Ito	29/857
6,257,923 B1	*	7/2001	Stone et al.	439/502
6,283,789 B1	*	9/2001	Tsai	439/502

OTHER PUBLICATIONS

THM 4L60-E Internal Wire Harness Identification, ATSG Seminar Information, Slides 23-27, 1997.

* cited by examiner

Primary Examiner—Brian Sircus


Assistant Examiner—Thanh-Tam Le

(74) *Attorney, Agent, or Firm*—MacMillan, Sobanski & Todd, LLC

(57) **ABSTRACT**

A universal wiring harness that is capable of providing electrical connections to the various electrical components contained within a variety of vehicular automatic transmissions includes a plurality of electrical conductors that are supported on a relatively rigid support bracket that is shaped in accordance with the basic structure of the transmission such that the electrical conductors are generally directed toward the locations of the various electrical components. The electrical conductors are preferably covered with an electrical insulator that is formed from polytetrafluoroethylene because it provides enhanced resistance to degradation from chemical exposure, heat, penetration (such as from abrasion or cutting), and color fading. A plurality of terminals and connectors are connected to the ends of the electrical conductors so as to facilitate the connections to the various electrical components of the electronic control system. At least some of the terminals and connectors may be adapted to provide alternative electrical connections with some of the components of the transmission, depending upon the particular structure of the transmission. To prevent dirt and other contaminants from entering into the unused terminal, and further to prevent electrical short circuits from occurring, a closure cap can be provided. If desired, the electrical conductors of the two terminals may be spliced together. The provision of multiple terminals and connectors for a single function allows the wiring harness as a whole to be readily adaptable for use with a variety of different transmission structures. As a result, the number of different wire harness structures that is required to be manufactured or maintained in inventory is greatly reduced.

12 Claims, 2 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4

UNIVERSAL WIRING HARNESS FOR AUTOMATIC TRANSMISSION

BACKGROUND OF THE INVENTION

This invention relates in general to automatic transmissions, such as those that are commonly used in the drive trains systems of many automotive and light truck vehicles. In particular, this invention relates to a universal wiring harness that is capable of providing electrical connections between various devices contained within a variety of different automatic transmission structures.

In most vehicles, a transmission is provided in the drive train between the engine and the driven wheels. As is well known, the transmission includes a housing containing an input shaft, an output shaft, and a plurality of gears that can be selectively connected between the input shaft and the output shaft. By controlling the connection of the gears between the input shaft and the output shaft, various forward and reverse gear ratios can be obtained to provide smooth and efficient operation of the vehicle.

In many automatic transmissions, the connection of the gears between the input shaft and the output shaft is controlled by a hydraulic control system that operates a plurality of mechanical clutches. Typically, the hydraulic control system includes a pump that provides pressurized transmission fluid to operate the clutches so as to connect certain ones of the gears contained within the transmission between the input shaft and the output shaft. This is accomplished by providing one or more fluid valves for each of the clutches. By selectively opening and closing the valves, the pressurized fluid from the pump can be controlled so as to operate the clutches to control which of the gears contained within the transmission are connected between the input shaft and the output shaft.

In many recent model automatic transmissions, the operations of the valves contained are controlled electronically by means of an electronic controller. The electronic controller is connected to a plurality of sensors disposed throughout the transmission. The sensors generate electrical signals that are representative of various operating conditions. In response to such electrical signals, the electronic controller generates electrical signals to a plurality of solenoids. The solenoids are connected to operated the various valves contained within the transmission in response to the electrical signals generated by the electronic controller. Thus, as the solenoids are turned on and off by the electronic controller, the various valves are opened and closed, thereby controlling the operations of the clutches and the transmission as a whole.

In such an electronic control system, a plurality of electrical conductors are usually provided to connect the electronic controller to the various sensors, solenoids, and other electrical devices contained within the transmission. Each of the electrical conductors usually includes a length of insulated wire having terminals connected to the ends thereof. The terminals are usually contained within connectors that are sized and shaped to mate with corresponding connectors provided on the various sensors, solenoids, and other electrical devices contained within the transmission to facilitate the connections thereto. As is well known, a typical automatic transmission contains a number of such electrical devices, each of which requires an individual connection. To simplify the installation process, it is known to combine a plurality of the individual electrical conductors into a single wiring harness. A wiring harness is a group of electrical conductors that have been packaged together to simplify the handling thereof and, as a result, facilitate the installation process. Typically, the lengths of wire are bundled packaged together within a single protective cover from which the various terminals and connectors extend at the ends thereof.

As is well known, a wide variety of automatic transmissions are manufactured and sold with modern vehicles. Because they are associated with vehicles of varying size and expense, the structures of such automatic transmissions also vary widely. In particular, the number, type, and location of the various electrical components contained differ from one automatic transmission to another. Thus, although a traditional wiring harness has been found to facilitate the various electrical connections that are made within a single automatic transmission structure, a wide variety of such wiring harnesses must be provided to accommodate the varying structures of automatic transmissions that are manufactured. Unfortunately, it has been found that the manufacture of a wide variety of wiring harness structures is costly and inefficient. Thus, it would be desirable to provide an improved wiring harness that is capable of providing quickly and easily providing electrical connections among a plurality of electrical various devices contained within a variety of different automatic transmission structures.

SUMMARY OF THE INVENTION

This invention relates to a universal wiring harness that is capable of providing electrical connections to the various electrical components contained within a variety of vehicular automatic transmissions. The wiring harness includes a plurality of electrical conductors that are supported on a relatively rigid support bracket that is shaped in accordance with the basic structure of the transmission such that the electrical conductors are generally directed toward the locations of the various electrical components. The electrical conductors are preferably covered with an electrical insulator that is formed from polytetrafluoroethylene because it provides enhanced resistance to degradation from chemical exposure, heat, penetration (such as from abrasion or cutting), and color fading. A plurality of terminals and connectors are connected to the ends of the electrical conductors so as to facilitate the connections to the various electrical components of the electronic control system. At least some of the terminals and connectors may be adapted to provide alternative electrical connections with some of the components of the transmission, depending upon the particular structure of the transmission. To prevent dirt and other contaminants from entering into the unused terminal, and further to prevent electrical short circuits from occurring, a closure cap can be provided. If desired, the electrical conductors of the two terminal may be spliced together. The provision of multiple terminals and connectors for a single function allows the wiring harness as a whole to be readily adaptable for use with a variety of different transmission structures. As a result, the number of different wire harness structures that is required to be manufactured or maintained in inventory is greatly reduced.

Various objects and advantages of this invention will become apparent to those skilled in the art from the following detailed description of the preferred embodiment, when read in light of the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevational view schematically illustrating a conventional automatic transmission with which a universal wiring harness in accordance with this invention may be used.

FIG. 2 is a block diagram of an electronic control circuit for use with the automatic transmission illustrated in FIG. 1.

FIG. 3 is a perspective view of a universal wiring harness in accordance with this invention for use in the electronic control circuit of FIG. 2.

FIG. 4 is an enlarged elevational view of a portion of the universal wiring harness illustrated in FIG. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, there is schematically illustrated in FIG. 1 an automatic transmission, indicated generally at **10**, that is generally known in the art. The illustrated transmission **10** is intended to be representative of any type of automatic transmission, such as for use in vehicles. The basic structure and operation of the transmission **10** is well known in the art. Thus, only those portions of the transmission **10** that are necessary for an understanding of this invention will be explained and illustrated.

The transmission **10** includes a case or housing **12** having an input end **14** and an output end **16**. As is well known, the housing **12** contains an input shaft (not shown) that extends inwardly through the input end **14** thereof, an output shaft (not shown) that extends outwardly from the output end **16** thereof, and a plurality of gears (not shown) that can be selectively connected between the input shaft and the output shaft. The input shaft is typically rotatably driven by a source of rotational power, such as a vehicle engine, and the input shaft may, for example, be embodied as an output shaft of such a vehicle engine. The output shaft is typically connected through a driveshaft to an axle assembly or other mechanism for rotating the wheels of the vehicle when rotatably driven by the input shaft. By controlling the connection of the gears, various forward and reverse gear ratios can be obtained to provide smooth and efficient operation of the vehicle.

The connection of the gears contained within the transmission **10** between the input shaft and the output shaft is usually controlled by a hydraulic control system that operates a plurality of mechanical clutches. Typically, the hydraulic control system includes a pump that provides pressurized transmission fluid to operate the clutches so as to connect certain ones of the gears contained within the transmission **10** between the input shaft and the output shaft. This is accomplished by providing one or more fluid valves for each of the clutches. By selectively opening and closing the valves, the pressurized fluid from the pump can be controlled so as to operate the clutches to control which of the gears contained within the transmission **10** are connected between the input shaft and the output shaft.

FIG. 2 is a block diagram of an electronic control system, indicated generally at **20**, for use with the automatic transmission **10** illustrated in FIG. 1. The electronic control system **20** includes an electronic controller **21**, which may be embodied as any known electronic computing device, such as a microprocessor, a programmable logic controller, and the like. The electronic controller **21** is connected to a plurality of sensors, switches, or other input devices **22** that are disposed throughout the transmission **10**. The sensors **22** generate electrical signals that are representative of various sensed operating conditions. The electronic controller **21** is also connected to a plurality of solenoids or other output devices **23** that are associated with the valves of the hydraulic control system described above. Operation of the solenoids **23** causes the associated valves to be opened and closed. In a manner that is well known in the art, the electronic controller **21** receives the electrical signals that are generated by the sensors **22**. In response to such signals, the electronic controller generates electrical signals to the solenoids **23**. The solenoids **23** are operated so as to selectively open and close the various valves contained within the transmission **10**. Thus, as the solenoids are turned on and off by the electronic controller, the various valves are opened and closed to control the operation of the transmission **10** in the manner described above.

Referring now to FIG. 3, there is illustrated a universal wiring harness, indicated generally at **30**, in accordance with

this invention. The wiring harness **30** is provided to facilitate the electrical connections between the electronic controller **21**, the sensors **22**, and the solenoids **23** discussed above. To accomplish this, the wiring harness includes a plurality of electrical conductors, several of which are indicated generally at **30a**, that are supported on a relatively rigid support bracket **30b**. The support bracket **30b** is shaped in accordance with the basic structure of the transmission **10** such that the electrical conductors **30a** are generally directed toward the locations of the various electrical components **21**, **22** and **23**.

The electrical conductors **30a** are preferably covered with an electrical insulator that is formed from polytetrafluoroethylene (PTFE). The use of a PTFE covering on the electrical conductors **30a** is desirable because it provides enhanced resistance to degradation from chemical exposure, heat, and penetration, such as from abrasion or cutting. The use of a PTFE covering on the electrical conductors **30a** is also desirable because it resists color fading. It is known to color code the various electrical conductors **30a** to correspond with the various electrical components **21**, **22**, and **23** to which they are attached. Traditionally, the color coding has been accomplished by providing a neutrally colored insulator with a colored coating. However, it has been found that after a period of use, the colored coating can be removed because of chemical reactions or physical wear. When this occurs, the possibility of an erroneous connection is increased. To avoid this, the PTFE covering on the electrical conductors **30a** resists color fading, even after an extended period of use. The support bracket **30b** can be formed from any desired material. Preferably, however, the support bracket **30b** is formed from a non-metallic material that is resistant to heat and corrosion, such as polyamide.

A plurality of connectors **31** through **38** are connected to the ends of the electrical conductors **31a** so as to facilitate the connections to the various electrical components **21**, **22** and **23** of the electronic control system **20**. As is well known, one or more electrical terminals (not shown) are housed within each of the connectors **31** through **38**. The size and shape of each of such connectors **31** through **38** can be selected to correspond with the specific one of the components **21**, **22**, and **23** to which it is to be connected. For example, the connector **31** may be adapted to provide an electrical connection with the electronic controller **21**. The connector **32** may be adapted to provide an electrical connection with an EPC force motor. The connectors **33** and **34** may be adapted to provide electrical connections with respective shift solenoids. The connector **35** may be adapted to provide an electrical connection with a pressure switch assembly or other one of the sensors **22**. The connectors **36** and **37** may be adapted to provide alternative electrical connections with a downshift pulse width modulation controller. The connector **38** may be adapted to provide an electrical connection with a torque converter control pulse width modulation controller. Lastly, one of the electrical conductors **30a** may be hard wired to one of the solenoids **23**.

Referring now to FIG. 4, there is illustrated a portion of the wiring harness **30** illustrated in FIG. 3, including the connectors **36** and **37**. As discussed above, the connectors **36** and **37** may be adapted to provide alternative electrical connections with a downshift pulse width modulation controller. For example, the connector **36** may be sized and shaped to be utilized with a downshift pulse width modulation controller from a first model year or group of model years, while the connector **37** may be sized and shaped to be utilized with a downshift pulse width modulation controller from a second model year or group of model years. Only one of the two connectors **36** and **37** is intended to be used in any given transmission **10**. Thus, depending upon the model year

5

of the transmission 10, either the connector 36 or the connector 37 will be connected to the downshift pulse width modulation controller. For example, if the connector 36 is connected to the downshift pulse width modulation controller, the connector 37 will not be connected to anything. To prevent dirt and other contaminants from entering into the unused connector 37, and further to prevent electrical short circuits from occurring, a closure cap 40 is provided. The closure cap 40 is provided to protectively cover the open end of the unused connector 37 to prevent the entry of dirt, water, and other contaminants therein.

The first connector 36 has first and second electrical conductors 36a and 36b extending therefrom, while the second connector 37 has first and second electrical conductors 37a and 37b extending therefrom. If desired, the first electrical conductors 36a and 37a of the two connectors 36 and 37 may be spliced together to provide a single electrical conductor 36a extending therefrom. Similarly, the second electrical conductors 36b and 37b of the two connectors 36 and 37 may be spliced together to provide a single electrical conductor 36b extending therefrom. In this situation, the connectors 36 and 37 are functionally equivalent to one another, but are adaptable for use with corresponding connectors of differing size and shape. The provision of multiple connectors, such as the connectors 36 and 37, for a single function allows the wire harness 30 as a whole to be readily adaptable for use with a variety of different transmission structures. As a result, the number of different wire harness structures that is required to be manufactured or maintained in inventory is greatly reduced.

In accordance with the provisions of the patent statutes, the principle and mode of operation of this invention have been explained and illustrated in its preferred embodiment. However, it must be understood that this invention may be practiced otherwise than as specifically explained and illustrated without departing from its spirit or scope.

What is claimed is:

1. A wiring harness that is adapted to provide electrical connections between an electronic controller and one of a plurality of different automatic transmissions, wherein each of the different automatic transmissions has a plurality of electrical components provided thereon, said wiring harness comprising:

- a plurality of electrical conductors that are bundled together on a support, each of said electrical conductors including a first end and a second end;
- a first plurality of terminals and connectors that are connected to said first ends of said electrical conductors to facilitate the connection of said electrical conductors to the electronic controller; and
- a second plurality of terminals and connectors that are connected to said second ends of said electrical conductors to facilitate the connection of said electrical conductors to the electrical components of a selected one of the plurality of automatic transmissions, wherein at least one of said electrical conductors has at least two of said terminals and connectors connected to said second end thereof to provide alternative electrical connections with one of the electrical components of the selected one of the plurality of automatic transmissions, wherein only one of said at least two of said terminals and connectors is used at a time.

2. The wiring harness defined in claim 1 wherein said support is a rigid support.

6

3. The wiring harness defined in claim 2 wherein said support is formed from formed from a non-metallic material that is resistant to heat and corrosion.

4. The wiring harness defined in claim 3 wherein said support is formed from polyamide.

5. The wiring harness defined in claim 1 wherein said at least two of said terminals and connectors are spliced to said second end of said electrical conductor.

6. The wiring harness defined in claim 1 further including a closure cap that protectively covers the unused one of said at least two of said terminals and connectors connected to said second end of said electrical conductor.

7. An electronic control system for use with one of a plurality of different automatic transmissions, wherein each of the different automatic transmissions has a plurality of electrical components provided thereon, said electronic control system comprising:

- a plurality of input devices for generating electrical signals that are representative of operating conditions of the automatic transmission;
- a plurality of output devices for controlling the operation of the automatic transmission;
- an electronic controller that is responsive to said electrical signals from said input devices for generating electrical signals to said output devices; and
- a wiring harness that provides electrical connections between said input devices, said electronic controller, and said output devices, said wiring harness including:
 - a plurality of electrical conductors that are bundled together on a support, each of said electrical conductors including a first end and a second end;
 - a first plurality of terminals and connectors that are connected to said first ends of said electrical conductors to facilitate the connection of said electrical conductors to said input devices, said electronic controller, and said output devices; and
 - a second plurality of terminals and connectors that are connected to said second ends of said electrical conductors to facilitate the connection of said electrical conductors to the electrical components of a selected one of the plurality of automatic transmissions, wherein at least one of said electrical conductors has at least two of said terminals and connectors connected to said second end thereof to provide alternative electrical connections with one of the electrical components of the selected one of the plurality of automatic transmissions.

8. The electronic control system defined in claim 7 wherein said support is a rigid support.

9. The electronic control system defined in claim 8 wherein said support is formed from formed from a non-metallic material that is resistant to heat and corrosion.

10. The electronic control system defined in claim 9 wherein said support is formed from polyamide.

11. The electronic control system defined in claim 7 wherein said at least two of said terminals and connectors are spliced to said second end of said electrical conductor.

12. The electronic control system defined in claim 7 further including a closure cap that protectively covers the unused one of said at least two of said terminals and connectors connected to said second end of said electrical conductor.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,439,923 B1
DATED : August 27, 2002
INVENTOR(S) : W. Scott Kirkendall and Richard J. Dimond, III

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 6,

Line 47, after "transmissions" insert -- , wherein only one of said at least two of said terminals and connectors is used at a time. --

Signed and Sealed this

Fourth Day of February, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office