



(12) **United States Patent**
Beardsley et al.

(10) **Patent No.:** **US 9,867,675 B2**
(45) **Date of Patent:** **Jan. 16, 2018**

(54) **SYSTEM AND METHOD FOR PERFORMING SURGICAL PROCEDURES WITH A REUSABLE INSTRUMENT MODULE**

(71) Applicant: **Covidien LP**, Mansfield, MA (US)
(72) Inventors: **John Beardsley**, Wallingford, CT (US);
Matthew Chowaniec, Madison, CT (US); **Russell Pribanic**, Roxbury, CT (US)

(73) Assignee: **COVIDIEN LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/283,489**

(22) Filed: **Oct. 3, 2016**

(65) **Prior Publication Data**
US 2017/0020632 A1 Jan. 26, 2017

Related U.S. Application Data
(63) Continuation of application No. 14/865,843, filed on Sep. 25, 2015, now Pat. No. 9,456,873, which is a (Continued)

(51) **Int. Cl.**
A61B 18/18 (2006.01)
A61B 90/70 (2016.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 90/70** (2016.02); **A61B 17/00** (2013.01); **A61B 17/068** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 5/15188; A61B 2017/2931; A61B 2017/2925; A61B 2017/0046
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,120,845 A 2/1964 Homer
3,528,720 A 9/1970 Treace
(Continued)

FOREIGN PATENT DOCUMENTS

CN 102028509 A 4/2011
DE 3317398 A1 11/1984
(Continued)

OTHER PUBLICATIONS

Chinese Office Action (with English translation) dated Dec. 25, 2015, corresponding to Chinese Application No. 201310012945.0; 16 total pages.


(Continued)

Primary Examiner — Robert N Wieland

(57) **ABSTRACT**

A surgical instrument includes an outer housing shell defining a cavity. The outer housing shell defines an upper outer housing half and a lower outer housing half. The upper outer housing half defines a longitudinal axis. An instrument module is selectively insertable into the cavity of the outer housing shell. The instrument module includes an inner housing shell, at least one motor disposed within the inner housing shell, a control board being in electrical communication with the at least one motor, and an energy source being in electrical communication with the at least one motor and the control board. The instrument module is inserted into the cavity of the outer housing shell in such a manner that the operative axis of the at least one motor is substantially parallel to the longitudinal axis of the upper outer housing half.

20 Claims, 4 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/551,321, filed on Nov. 24, 2014, now Pat. No. 9,155,529, which is a continuation of application No. 13/719,344, filed on Dec. 19, 2012, now Pat. No. 8,894,647.

(60) Provisional application No. 61/586,201, filed on Jan. 13, 2012.

(51) **Int. Cl.**

A61B 17/072 (2006.01)
A61B 17/3201 (2006.01)
A61B 17/068 (2006.01)
A61B 17/32 (2006.01)
A61B 17/00 (2006.01)
A61B 17/29 (2006.01)
A61B 90/00 (2016.01)

(52) **U.S. Cl.**

CPC *A61B 17/07207* (2013.01); *A61B 17/32* (2013.01); *A61B 17/3201* (2013.01); *A61B 2017/00017* (2013.01); *A61B 2017/0046* (2013.01); *A61B 2017/00115* (2013.01); *A61B 2017/00398* (2013.01); *A61B 2017/00734* (2013.01); *A61B 2017/00907* (2013.01); *A61B 2017/2925* (2013.01); *A61B 2090/0813* (2016.02)

6,086,528 A 7/2000 Adair
 6,206,844 B1 3/2001 Reichel et al.
 7,468,041 B2 12/2008 Rhodes et al.
 7,691,622 B2 4/2010 Garland et al.
 8,221,449 B2 7/2012 Gadberry et al.
 8,894,647 B2 11/2014 Beardsley et al.
 9,155,529 B2 10/2015 Beardsley et al.
 9,241,757 B2 1/2016 Beardsley et al.
 9,456,873 B2 10/2016 Beardsley et al.
 2003/0149424 A1 8/2003 Barley et al.
 2003/0205029 A1 11/2003 Chapolini et al.
 2004/0116952 A1 6/2004 Sakurai et al.
 2006/0217729 A1 9/2006 Eskridge et al.
 2006/0226195 A1 10/2006 Scirica et al.
 2008/0077149 A1 3/2008 Hoerle
 2010/0000074 A1 1/2010 Smith et al.
 2010/0057106 A1 3/2010 Sorrentino et al.
 2011/0017801 A1 1/2011 Zemlok et al.
 2011/0112517 A1 5/2011 Peine et al.
 2011/0125138 A1 5/2011 Malinouskas et al.
 2011/0306952 A1 12/2011 Chen et al.
 2012/0116266 A1 5/2012 Houser et al.
 2012/0238829 A1 9/2012 Shelton, IV et al.
 2012/0239010 A1 9/2012 Shelton, IV et al.
 2012/0253116 A1 10/2012 Sniffin et al.
 2012/0253328 A1 10/2012 Cunningham et al.
 2013/0261643 A1 10/2013 Meade et al.
 2014/0207124 A1 7/2014 Aldridge et al.
 2016/0008080 A1 1/2016 Beardsley et al.
 2016/0106401 A1 4/2016 Beardsley et al.
 2016/0113635 A1 4/2016 Beardsley et al.

(56)

References Cited

U.S. PATENT DOCUMENTS



3,734,207 A 5/1973 Fishbein
 3,903,440 A 9/1975 Paule et al.
 3,988,873 A 11/1976 Oliverius
 4,091,880 A 5/1978 Troutner et al.
 4,183,613 A 1/1980 Walchle et al.
 4,441,563 A 4/1984 Walton, II
 4,493,223 A 1/1985 Kishi et al.
 4,886,049 A 12/1989 Darras
 4,919,146 A 4/1990 Rhinehart et al.
 5,105,800 A 4/1992 Takahashi et al.
 5,168,863 A 12/1992 Kurtzer
 5,198,894 A 3/1993 Hicks
 5,230,704 A 7/1993 Moberg et al.
 5,251,613 A 10/1993 Adair
 5,274,500 A 12/1993 Dunn
 5,380,333 A 1/1995 Meloul et al.
 5,386,816 A 2/1995 Inoue et al.
 5,387,217 A 2/1995 Sefcik et al.
 5,499,992 A 3/1996 Meade et al.
 5,569,161 A 10/1996 Ebling et al.
 5,667,068 A 9/1997 Weaver
 5,697,887 A 12/1997 Yabe et al.
 5,746,759 A 5/1998 Meade et al.
 5,752,972 A 5/1998 Hoogeboom
 5,782,821 A 7/1998 Couch
 5,849,023 A 12/1998 Mericle
 5,863,287 A 1/1999 Segawa
 5,868,750 A 2/1999 Schultz
 5,928,255 A 7/1999 Meade et al.
 5,931,849 A 8/1999 Desvignes et al.
 5,971,916 A 10/1999 Koren
 5,986,693 A 11/1999 Adair et al.
 5,997,811 A 12/1999 Esposito
 6,010,477 A 1/2000 Bays
 6,059,806 A 5/2000 Hoerle

FOREIGN PATENT DOCUMENTS

DE 3700487 A1 7/1988
 EP 0238204 A1 9/1987
 EP 0261260 A1 3/1988
 EP 0275392 A1 7/1988
 EP 0804124 B1 11/1997
 JP H09538 1/1997
 JP H109538 A 1/1998
 JP 2000254141 A 9/2000
 JP 2010051805 A 3/2010
 JP 2011078772 A 4/2011
 WO 9806144 A1 2/1998
 WO 0153145 A1 7/2001
 WO 0167970 A1 9/2001
 WO 2014/144780 A1 9/2014

OTHER PUBLICATIONS

European Search Report, dated Mar. 13, 2015, corresponding to European Application No. 13 15 1037.2; 7 pages.
 Chinese First Office Action (with English translation), dated Jan. 26, 2016, corresponding to Chinese Application No. 201310013044.3; 16 total pages.
 Chinese Second Office Action (with English translation), dated Aug. 4, 2016, corresponding to Chinese Application No. 201310012945.0; 18 total pages.
 Japanese Office Action (with English translation), dated Aug. 30, 2016, corresponding to Japanese Application No. 2013-000854; 8 total pages.
 Australian Patent Examination Report No. 1, dated Sep. 20, 2016, corresponding to Australian Application No. 2013200112; 3 pages.
 European Search Report dated Feb. 8, 2017, corresponding to European Application No. 16179552.1; 11 pages.
 European Search Report dated May 11, 2017, corresponding to European Application No. 16206726.8; 14 total pages.
 European Search Report dated Oct. 4, 2017, corresponding to European Application No. 16206726.8; 19 total pages.






Fig. 2




Fig. 3




Fig. 4

SYSTEM AND METHOD FOR PERFORMING SURGICAL PROCEDURES WITH A REUSABLE INSTRUMENT MODULE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 14/865,843, filed Sep. 25, 2015, (now U.S. Pat. No. 9,456,873), which is a continuation of U.S. patent application Ser. No. 14/551,321, filed Nov. 24, 2014, (now U.S. Pat. No. 9,155,529), which is a continuation of U.S. patent application Ser. No. 13/719,344, filed Dec. 19, 2012, (now U.S. Pat. No. 8,894,647), which claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 61/586,201, filed on Jan. 13, 2012, the entire contents of each of which are incorporated by reference herein.

The present application relates to U.S. patent application Ser. No. 13/719,377, titled SYSTEM AND METHOD FOR PERFORMING SURGICAL PROCEDURES WITH A REUSABLE INSTRUMENT MODULE, filed Dec. 19, 2012, the entire contents of which are incorporated by reference herein.

BACKGROUND

Technical Field

The present disclosure relates generally to the field of reusable or reusable surgical instruments. In particular, the disclosure relates to instruments having separable and replaceable components to provide clean, sterile or refurbished surfaces in each instance of use.

Background of Related Art

One type of surgical device is a linear clamping, cutting and stapling device. Such a device may be employed in a surgical procedure to resect a cancerous or anomalous tissue from a gastro-intestinal tract. Conventional linear clamping, cutting and stapling instruments include a pistol grip-styled structure having an elongated shaft and distal portion. The distal portion includes a pair of scissors-styled gripping elements, which clamp the open ends of the colon closed. In this device, one of the two scissors-styled gripping elements, such as the anvil portion, moves or pivots relative to the overall structure, whereas the other gripping element remains fixed relative to the overall structure. The actuation of this scissoring device (the pivoting of the anvil portion) is controlled by a grip trigger maintained in the handle.

In addition to the scissoring device, the distal portion also includes a stapling mechanism. The fixed gripping element of the scissoring mechanism includes a staple cartridge receiving region and a mechanism for driving the staples up through the clamped end of the tissue against the anvil portion, thereby sealing the previously opened end. The scissoring elements may be integrally formed with the shaft or may be detachable such that various scissoring and stapling elements may be interchangeable.

A number of surgical device manufacturers have developed product lines with proprietary drive systems for operating and/or manipulating such surgical device. In many instances, such surgical device further includes a handle assembly, which is reusable, and a disposable end effector or the like that is selectively connected to the handle assembly prior to use and then disconnected from the end effector following use in order to be disposed of or in some instances sterilized for re-use.

Surgical devices that are reusable, or reusable for multiple procedures, reduce the instrumentation costs per procedure. Providing a reusable surgical device, however, presents various challenges. For example, the complexity of a surgical device tends to result in fairly labor intensive cleaning procedures to prepare the surgical device for subsequent use. Improper cleaning may result in dangerous contamination being introduced into the surgical site. Also, some reusable surgical devices have removable and replaceable components to provide clean surfaces for each use. Many of these surgical devices require arduous disassembly and reassembly procedures that require extensive training, and may discourage use of the surgical device.

SUMMARY

According to an embodiment of the present disclosure, a surgical instrument is provided. The surgical instrument includes an outer housing shell defining a cavity, the outer housing shell defining an upper outer housing half and a lower outer housing half, wherein the upper outer housing half defines a longitudinal axis and an instrument module selectively insertable into the cavity of the outer housing shell. The instrument module includes an inner housing shell, at least one motor disposed within the inner housing shell, the at least one motor including a drive shaft defining an operative axis of rotation, a control board disposed within the inner housing and being in electrical communication with the at least one motor and an energy source disposed within the inner housing and being in electrical communication with the at least one motor and the control board. The instrument module is inserted into the cavity of the outer housing shell in such a manner that the operative axis of the at least one motor is substantially parallel to the longitudinal axis of the upper outer housing half.

Additionally, the outer housing shell may be devoid of movable switches.

In an exemplary embodiment, the upper outer housing half and the lower outer housing half combine to form a pistol-grip configuration.

The outer housing shell may be at least partially translucent or at least partially transparent.

In another exemplary embodiment, the upper outer housing half includes at least one speaker for providing feedback information related to tissue parameters and surgical instrument parameters measured during a surgical procedure.

In yet another exemplary embodiment, the upper outer housing half includes at least one viewing window for viewing a display screen disposed therein displaying information related to tissue parameters and surgical instrument parameters measured during a surgical procedure. The display screen includes at least one of numerical indicators and color indicators.

Moreover, the control board electrically communicates with at least one processor for enabling flow of electrosurgical energy between the energy source and the at least one motor.

In yet another exemplary embodiment, the lower outer housing half includes an instrument shell cover hingedly connected thereto, the instrument shell cover configured to swivel into place after the instrument module is inserted into the cavity of the outer housing shell. Alternatively, an instrument shell cover is attached to at least a portion of the lower outer housing half, such that the upper and lower outer housing halves attach to the instrument shell cover to form a secure connection.

3

The outer housing shell may define at least one opening formed in a distal surface thereof for receiving the drive shaft therethrough when the instrument module is fully disposed in the outer housing shell.

A seal may be supported in the opening formed in the distal surface of the outer housing shell, wherein the seal forms a fluid-tight seal between the outer housing shell and the drive shaft.

The instrument module may include a plurality of motors each including a drive shaft extending therefrom. The outer housing shell may define a plurality of openings formed in a distal surface thereof for receiving a respective drive shaft therethrough when the instrument module is fully disposed in the outer housing shell. A seal may be supported in each opening formed in the distal surface of the outer housing shell, wherein each seal forms a fluid-tight seal between the outer housing shell and the respective drive shaft.

In another exemplary embodiment, a method of performing a surgical procedure is presented. The method includes the steps of providing an outer housing shell defining a cavity, the outer housing shell defining an upper outer housing half and a lower outer housing half, wherein the upper outer housing half defines a longitudinal axis and selectively inserting an instrument module into the cavity of the outer housing shell. The instrument module includes an inner housing shell, at least one motor disposed within the inner housing shell, the at least one motor including a drive shaft defining an operative axis of rotation, a control board disposed within the inner housing and being in electrical communication with the at least one motor and an energy source disposed within the inner housing and being in electrical communication with the at least one motor and the control board. The instrument module is inserted into the cavity of the outer housing shell in such a manner that the operative axis of the at least one motor is substantially parallel to the longitudinal axis of the upper outer housing half.

The outer housing shell may be at least partially translucent or at least partially transparent.

The outer housing shell may define at least one opening formed in a distal surface thereof for receiving the drive shaft therethrough when the instrument module is fully disposed in the outer housing shell.

A seal may be supported in the opening formed in the distal surface of the outer housing shell, wherein the seal forms a fluid-tight seal between the outer housing shell and the drive shaft.

The instrument module may include a plurality of motors each including a drive shaft extending therefrom. The outer housing shell may define a plurality of openings formed in a distal surface thereof for receiving a respective drive shaft therethrough when the instrument module is fully disposed in the outer housing shell. A seal may be supported in each opening formed in the distal surface of the outer housing shell, wherein each seal forms a fluid-tight seal between the outer housing shell and the respective drive shaft.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the disclosure and, together with a general description of the disclosure given above, and the detailed description of the embodiment(s) given below, serve to explain the principles of the disclosure, wherein:

4

FIGS. 1A and 1B illustrate perspective views of a reusable surgical instrument module, in accordance with the present disclosure;

FIG. 2 illustrates a reusable surgical instrument module inserted into an outer housing shell having a hinged instrument cover shell, in accordance with an embodiment of the present disclosure;

FIG. 3 illustrates a reusable surgical instrument module inserted into an outer housing shell having a snapable instrument cover shell, in accordance with another embodiment of the present disclosure; and

FIG. 4 is an enlarged, schematic, longitudinal cross-sectional view illustrating the reusable surgical instrument module inserted into the outer housing shell, and showing seals disposed about drive shafts of the reusable surgical instrument module.

DETAILED DESCRIPTION

Embodiments of the presently disclosed apparatus will now be described in detail with reference to the drawings, in which like reference numerals designate identical or corresponding elements in each of the several views. As used herein, the term “distal” refers to that portion of the tool, or component thereof which is further from the user while the term “proximal” refers to that portion of the tool or component thereof which is closer to the user.

Referring to FIGS. 1A and 1B, perspective views of a reusable surgical instrument module **110** are illustrated, in accordance with the present disclosure.

Instrument module **110** defines an upper instrument module half **110A** and a lower instrument module half **110B**, upper instrument module half **110A** defining a longitudinal axis “B.” Instrument module **110** also includes an inner housing shell **111** for incorporating a plurality of components therein, as described below.

Upper instrument module half **110A** includes at least one motor **140**, as well as a display screen **160**. At least one motor **140** is disposed within inner housing shell **111**. A distal end **102** of upper instrument module half **110A** is configured to receive an end effector assembly (not shown). End effector assembly may be at least one of jaw members, a clip applier, vessel sealing devices, circular stapling devices, dissectors, retractors, cutters, graspers, and drills.

Lower instrument module half **110B** includes a battery **120** (or energy source) and at least one control board **130**. Battery **120** and at least one control board **130** are disposed within inner housing shell **111**. Lower instrument module half **110B** is configured to be gripped by a user, such as surgeon, during a surgical procedure. Additionally, upper instrument module half **110A** and lower instrument module half **110B** may combine to form a substantially L-shaped or pistol-grip configuration.

At least one control board **130** is connected, on the one hand, electrically to battery **120**, and, on the other hand, to at least one motor **140**. To this end, electric contacts (not shown) are provided on an upper side of battery **120** for establishing an electric connection with at least one control board **130**. Additionally, at least one control board **130** electrically communicates with at least one processor (not shown) for enabling flow of electrosurgical energy between the energy source (e.g., battery **120**) and each motor **140**.

Each motor **140** is configured to include, for instance, a drive shaft **142**. Drive shaft **142** defines an operative axis of rotation “B.” Each motor **140** is configured to actuate a function or operation of an end effector assembly (not

shown), including but not limited to, articulating, rotating, closing of the jaw members, ejecting fasteners, cutting, and the like.

Instrument module **110** may include a speaker **150** (see FIG. 1B), at a proximal end **104** thereof, for providing feedback information related to tissue parameters and surgical instrument parameters measured during a surgical procedure. Speaker **150** may be used to provide audible feedback. Audible feedback may be used in conjunction with or in lieu of the visual outputs.

Instrument module **110** may include display screen **160** disposed therein displaying information related to tissue parameters and surgical instrument parameters measured during a surgical procedure. Display screen **160** may be configured to provide the surgeon with a variety of suitable output information. Display screen **160** may include at least one of numerical indicators and color indicators.

Instrument module **110** may also include a clamp button **170** and a return button **180**. Clamp button **170** may be configured to actuate an end effector assembly (not shown) connected to distal end **102** of instrument module **110** to a first position. End effector assembly may be a pair of jaw members for clamping tissue in the first position. Return button **180** may be configured to return the jaw members to an open, unclamped position (or second position).

Referring to FIG. 2, a method of inserting a reusable surgical instrument module **110** into an outer housing shell **280** having a hinged instrument cover shell **290**, in accordance with an embodiment of the present disclosure is presented.

Outer housing shell **280** defines a cavity **282** therein. Outer housing shell **280** defines an upper outer housing half **280A** and a lower outer housing half **280B**. Upper outer housing half **280A** defines a longitudinal axis "A" extending therethrough. Outer housing shell **280** also includes instrument shell cover **290** connected to lower outer housing half **280B** via a hinged connection **292**. Instrument shell cover **290** may rotate or pivot in direction "C" after instrument module **110** has been fully inserted into outer housing shell **280**, as described below. In accordance with an embodiment of the present disclosure, outer housing shell **280** may be devoid of movable switches.

In operation or use, instrument module **110** is inserted into cavity **282** of outer housing shell **280** in such a manner that operative axis "B" of at least one motor **140** is substantially parallel to longitudinal axis "A" of upper outer housing half **280A**. Stated differently, instrument module **110** is configured to be inserted into reusable outer housing shell **280**, such that instrument module **110** is inserted and extracted along an axis of operation of at least one motor **140** or along longitudinal axis "B." Upper instrument module half **110A** is configured to underlie or nest upper outer housing half **280A**, whereas lower instrument module half **110B** is configured to underlie or nest lower outer housing half **280B**. Once instrument shell **110** is fully inserted into outer housing shell **280**, instrument shell cover **290** is rotated, in direction "C," in order to create a secure seal with outer housing shell **280**.

Following a surgical procedure, instrument shell cover **290** is opened and instrument module **110** is withdrawn from or removed from cavity **282** of outer housing shell **280** such that outer housing shell **280** and shell cover **290** may be cleaned in accordance with methods and procedures known in the art, for example, sterilizing, autoclaving, steam cleaning, wiping with cleaning products/solvents and the like. Thus, outer housing shell **280** and shell cover **290** may be cleaned or sterilized without compromising instrument mod-

ule **110** inserted therein. Once cleaning or sterilization has been completed, instrument module **110** may be re-introduced into cavity **282** of outer housing shell **280** prior to performing a further surgical procedure.

Referring to FIG. 3, a method of inserting a reusable surgical instrument module **110** into an outer housing shell **380** having a snapable instrument cover shell **390**, in accordance with another embodiment of the present disclosure is illustrated.

Outer housing shell **380** defines a cavity **382** therein. Outer housing shell **380** defines an upper outer housing half **380A** and a lower outer housing half **380B**. Upper outer housing half **380A** defines a longitudinal axis "D" extending therethrough. Lower outer housing half **380B** of outer housing shell **380** may connect or attach to instrument shell cover **390** via, for example, a snapable mechanism including fasteners (not shown). Additionally, a clear viewing window **385** may be constructed so that it overlays a display screen (e.g., as described above with reference to FIGS. 1A and 1B). Viewing window **385** is designed for viewing the display screen disposed therein displaying information related to tissue parameters and surgical instrument parameters measured during a surgical procedure.

In accordance with the present disclosure, it is contemplated that outer housing shell **380** (as well as outer housing shells **180**, **280**) may be fabricated from a translucent or transparent material, such as, for example, a polycarbonate resin thermoplastic. As so constructed, indicia from display screen **160** of instrument module **110** or the like. It is further contemplated that at least a portion of outer housing shell **380** may be translucent or transparent.

In operation or use, instrument module **110** is inserted into cavity **382** of outer housing shell **380** in such a manner that operative axis "E" of at least one motor **140** (or of at least one drive shaft **142**) is substantially parallel to longitudinal axis "D" of upper outer housing half **110A**. Stated differently, instrument module **110** is configured to be inserted into instrument outer housing shell **380**, such that instrument module **110** is inserted and extracted along an axis of operation of at least one motor **140**, or along longitudinal axis "E." Upper instrument module half **110A** is configured to underlie or nest upper outer housing half **380A**, whereas lower instrument module half **110B** is configured to underlie or nest lower outer housing half **380B**. Once instrument shell cover **390** is attached to a portion of lower outer housing half **380B**, instrument module **110** is inserted into outer housing shell **380** such that upper outer housing half **380A** and the remaining portion of the lower outer housing half **380B** lock or secure or seal with instrument shell cover **390** along connection region **395**.

Following a surgical procedure, instrument shell cover **390** is withdrawn or unsnapped from lower outer housing half **380B** (at connection region **395**) and instrument module **110** is withdrawn from or removed from cavity **382** of outer housing shell **380** such that outer housing shell **380** and shell cover **390** may be cleaned in accordance with methods and procedures known in the art. Thus, outer housing shell **380** may be cleaned or sterilized without compromising instrument module **110** inserted therein. Once cleaning or sterilization has been completed, instrument module **110** may be re-introduced into cavity **382** of outer housing shell **380** prior to performing a further surgical procedure.

Turning now to FIG. 4, in accordance with the present disclosure, it is contemplated that outer housing shell **280**, **380** may define a plurality of apertures **150** through which each drive shaft **142** passes. A seal **152** is provided in each aperture **150** and is supported therein so as to remain with

7

outer housing shell **280, 380** during insertion/retraction of instrument module **110** therein/therefrom. Seals **152** may take the form of O-rings or the like, and may be constructed from a resilient, polymeric material, such as, for example, rubber. Seals **152** are configured and dimensioned to establish a fluid-tight seal between outer housing shell **280, 380** and drive shafts **142**. Additionally, seals **152** are configured and dimensioned to permit drive shafts **142** to rotate. In use, when shell covers **290, 390** are closed against respective outer housing shells **280, 380**, a force is exerted against instrument module **110**, substantially along or in direction “B”, to thereby press a distal surface of upper instrument module half **110A** against seals **152** and establish a fluid-tight seal against an outer surface of drive shafts **142**.

While several embodiments of the disclosure have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of presently disclosed embodiments. Thus the scope of the embodiments should be determined by the appended claims and their legal equivalents, rather than by the examples given.

What is claimed is:

1. A method of assembling a surgical instrument, the method comprising:

inserting a proximal end of an instrument module into a proximal portion of an outer housing shell wherein the instrumental module includes at least one of a motor, a control board, or an energy source disposed therein; and

approximating the proximal portion of the outer housing shell and a distal portion of the outer housing shell thereby engaging a mating surface of the proximal portion of the outer housing shell with a corresponding mating surface of the distal portion of the outer housing shell to enclose the instrument module in a cavity cooperatively defined by the proximal and distal portions of the outer housing shell.

2. The method according to claim **1**, wherein inserting the proximal end of the instrument module into the proximal portion of the outer housing shell includes moving the proximal end of the instrument module through an opening defined by a distally-oriented face of the proximal portion of the outer housing shell.

3. The method according to claim **2**, further comprising moving the distal end of the instrument module through an opening defined by a proximally-oriented face of the distal portion of the outer housing shell.

4. The method according to claim **1**, further comprising: decoupling the mating surfaces of the proximal and distal portions of the outer housing shell; and removing the instrument module from the cavity of the outer housing shell.

5. The method according to claim **4**, further comprising inserting the instrument module into the cavity of the outer housing shell subsequent to providing the outer housing shell having at least a sterilized outer surface such that the outer surface of the outer housing shell is sterile following insertion of the instrument module into the outer housing shell.

6. The method according to claim **1**, further comprising forming a fluid-tight seal between the outer housing shell and a drive shaft of the instrument module.

7. A surgical instrument, comprising:
an outer housing shell including:

8

a proximal portion having a face, the face of the proximal portion defining an opening therein and including a mating surface; and

a distal portion having a face, the face of the distal portion defining an opening therein and including a mating surface configured to mate with the mating surface of the proximal portion;

an instrument module configured for receipt in a cavity cooperatively defined by the proximal and distal portions of the outer housing shell, and through at least one of the opening of the proximal portion of the outer housing shell or the opening of the distal portion of the outer housing shell wherein the instrument module includes at least one of a motor, a control board, or an energy source disposed therein.

8. The surgical instrument according to claim **7**, wherein the instrument module includes:

a proximal end configured for receipt within the proximal portion of the outer housing shell; and

a distal end configured for receipt within the distal portion of the outer housing shell.

9. The surgical instrument according to claim **7**, wherein the distal portion of the outer housing shell includes an upper portion and a lower portion extending substantially perpendicularly from the upper portion.

10. The surgical instrument according to claim **7**, wherein the outer housing shell has a first configuration, in which the instrument module is selectively insertable therein, and a second configuration, in which the mating surfaces of the proximal and distal portions of the outer housing shell are engaged to one another.

11. The surgical instrument according to claim **10**, wherein in the first configuration, the face of the proximal portion of the outer housing shell is oriented distally, and the face of the distal portion of the outer housing shell is oriented proximally.

12. The surgical instrument according to claim **7**, wherein the instrument module further includes a drive shaft disposed within the distal end of the instrument module.

13. The surgical instrument according to claim **12**, wherein the outer housing shell includes a seal supported in the distal portion of the outer housing shell, the seal forming a fluid-tight seal between the outer housing shell and the drive shaft.

14. The surgical instrument according to claim **7**, wherein each of the proximal and distal portions of the outer housing shell includes an outer surface and an inner surface, wherein at least the outer surface of each of the proximal and distal portions of the outer housing shell is sterile.

15. A method of assembling a surgical instrument, the method comprising:

providing an outer housing shell including:

a proximal portion having a face, the face of the proximal portion defining an opening therein and including a mating surface; and

a distal portion having a face, the face of the distal portion defining an opening therein and including a mating surface configured to mate with the mating surface of the proximal portion;

providing an instrument module having a proximal end, a distal end, and at least one of a motor, a control board, or an energy source disposed therein;

inserting the proximal end of the instrument module into the proximal portion of the outer housing shell; and

approximating the proximal portion of the outer housing shell and the distal portion of the outer housing shell thereby engaging the mating surface of the proximal

portion of the outer housing shell with the mating surface of the distal portion of the outer housing shell to enclose the instrument module in a cavity cooperatively defined by the proximal and distal portions of the outer housing shell. 5

16. The method according to claim **15**, wherein inserting the proximal end of the instrument module into the proximal portion of the outer housing shell includes moving the proximal end of the instrument module through the opening defined by the face of the proximal portion of the outer housing shell. 10

17. The method according to claim **16**, further comprising moving the distal end of the instrument module through the opening defined by the face of the distal portion of the outer housing shell. 15

18. The method according to claim **15**, further comprising:

decoupling the mating surfaces of the proximal and distal portions of the outer housing shell; and
removing the instrument module from the cavity of the outer housing shell. 20

19. The method according to claim **18**, further comprising inserting the instrument module into the cavity of the outer housing shell subsequent to providing the outer housing shell having at least a sterilized outer surface such that the outer surface of the outer housing shell is sterile following insertion of the instrument module into the outer housing shell. 25

20. The method according to claim **15**, further comprising forming a fluid-tight seal between the outer housing shell and a drive shaft of the instrument module. 30

* * * * *