

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 October 2007 (11.10.2007)

PCT

(10) International Publication Number
WO 2007/113664 A2

(51) International Patent Classification: **Not classified**

(21) International Application Number:
PCT/IB2007/000895

(22) International Filing Date: 4 April 2007 (04.04.2007)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:
BO2006A000244 5 April 2006 (05.04.2006) IT

(71) Applicant (for all designated States except US): **IMA INDUSTRIA MACCHINE AUTOMATICHE S.P.A.**
[IT/IT]; Via Emilia, 428-442, I-40064 Ozzano dell'Emilia (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **TREBBI, Claudio**
[IT/IT]; Via Ugo Morara 104A, I-40059 Medicina (IT).
BISI, Alessandro [IT/IT]; Via F.lli Gnudi 27, I-40050 Argelato (IT).

(74) Agent: **CRUGNOLA, Pietro**; Luppi & Associati S.R.L.,
Via Arienti 15/2A, I-40124 Bologna (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR TRANSFERRING AND MOVING ELEMENTS OF AN AUTOMATIC PACKING MACHINE



(57) Abstract: A system for transferring and moving elements (50, 60) removably associable with a packaging machine (3) comprises at least a transferring unit (5) provided with movement means (20, 21) suitable for receiving and supporting the aforesaid elements (50, 60), the movement means (20, 21) being movable for transferring and/or removing the elements (50, 60) to and/or from the machine (3); a method for transferring and moving elements (50, 60) removably associable with a packaging machine (3) provides supporting and conveying the elements (50, 60) using at least a transferring unit (5) and transferring and/or removing the elements (50, 60) to and/or from the packaging machine (3) using the movement means (20, 21) of the transferring unit (5).

WO 2007/113664 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

System and method for transferring and moving elements of an
automatic packing machine

The present invention relates to a system and a method for transferring and moving elements of an automatic packaging
5 machine.

In particular, the invention relates to a system and a method for performing a plurality of operations automatically or semiautomatically on elements, parts and components of a machine for packaging products, for example drugs, placed
10 inside an aseptic and/or sterile environment, to which the following description will make explicit reference without thereby losing general applicability.

In the pharmaceutical and biotechnological industries there is often a requirement for product packaging processes to use
15 sterile materials and in sterile environments in order to prevent the products suffering particle and bacteriological contamination, i.e. contamination due to the presence in the air of solid suspended particles such as ashes, dust, spores and microorganisms.

For this purpose, the production systems comprise packaging machines or lines inserted inside cleanrooms, which separate an internal processing environment, in fact a sterile processing environment, from a surrounding non-sterile external environment, or environment having a different class
20 of sterility or contamination.

The degree of contamination of an environment is defined by the number of polluting particles present in a unit volume of air. Standard tables define contamination classes for each of which there is defined the maximum permissible number of
30 polluting particles of the indicated dimension per cubic foot (US FED STD 209 Cleanroom standards) or per cubic metre of air (ISO 14644-1 Cleanroom standards).

The contamination class required in the process environment is a function of the product to be packaged. For example, for
35 pharmaceutical products to be administered parenterally or nasally, or ophthalmic products, packaging in a class ISO 5

(ISO 14644-1) or class 100 (US FED STD 209) environment is required.

The separation and insulation between the two environments in some applications also aims to prevent the dispersal into the external environment of products that are potentially toxic and harmful to human health.

The asepsis and/or sterility of the processing environment is ensured by the cleanliness and sterility of each component and element contained inside the cleanroom, and by the presence of a suitable one-way flow of sterile air filtered by suitable absolute (HEPA) filters. The one-way air flow consists of threads of sterile air that move in the same direction almost parallel to one another, at substantially the same speed, in such a way as to create an even air current without turbulence. The air flow descending from top to bottom forms a front of sterile air that drags away any contaminating particles present and prevents them from rising again from the bottom of the chamber.

Inside the cleanroom there is provided the entrance for the operators assigned to performing a plurality of interventions on the packaging machine, such as, for example, adjustments, assembly and dismantling of parts and operating units, interventions that in all cases must not connect the sterile processing environment with non-sterile zones of the machine such as spaces containing mechanisms and movement mechanism.

The objective is to perform operations and interventions on the machine without compromising the sterility of the sterile environment and without contaminating previously sterilised parts and components mounted or to be mounted on the machine, in order to avoid procedures of restoring sterility that are laborious, long and very costly.

For this purpose, in order to avoid the contamination of the sterile environment, and above all of the parts with which they come into contact, the operators wear suitable protective overalls that cover all parts of their body.

In order to sterilize appropriately any object to be

introduced into the cleanroom, there is provided an autoclave, provided with two hatches, which are respectively in communication with the external non-sterile environment and with the internal environment of the cleanroom, in such a way as to prevent a direct connection between said environments.

In this way the operator is able to introduce inside the cleanroom elements to be mounted onto the machine, typically standard components, operating units and devices, for example product batching or container capping devices, to be replaced at the end of production.

These parts are transferred manually by one or more operators from the autoclave to the machine on which they are mounted.

Recently however, the need has arisen to limit the intervention by operators to prevent them interacting directly with parts intended to come into contact with the product to be packaged, such as, for example, batching devices, components for introducing and supplying the product.

In fact, it has been observed that although operators are provided with protective gloves and overalls, they constitute a potential source of particle contamination. The close proximity and the contact of said operators with sterile objects may cause the latter to be contaminated.

This possible and potential contamination may be considered to be unacceptable in certain packaging processes.

From this there arises the need to proceed with further sterilising processes after each operation and/or intervention on parts and components of the machine that are apt to come into contact with the product, with a consequent increase in the cost and time required to set up the operating system.

At the end of production it is generally necessary to dismantle the parts, the components and the operating units of the machine that have come into contact with the product or have a size that is not compatible with the next

production batch. These elements have to be transferred outside the clean room to be cleaned, washed and then sterilised, to make them suitable for subsequent use.

The transfer outside the cleanroom occurs through a communicating chamber provided, similarly to the autoclave, with a first door giving access to the cleanroom and with a second door giving access to the non-sterile external environment. In this way the operators in the cleanroom transfer the elements dismantled from the machine to the chamber from which, after the first door has been closed hermetically, other operators remove them to subject them to washing and sterilising operations.

These manual procedures nevertheless have the drawback of forcing the operators to touch parts and components of the machine on which the packaged product is present in more or less great quantities. Also in the case of pharmaceutical products that are not particularly hazardous and harmful - such as cytotoxic products for which special procedures and containing systems are provided - this direct, prolonged and repeated contact with pharmaceuticals should be avoided as it exposes the operators to the possible absorption of unspecified quantities of product that may harm the health or cause health complaints of varying gravity. This is particularly true in the case of products in the form of fine powders, which can be easily diffused in the air and thus be inhaled and/or absorbed by the operators.

In order to overcome this problem it is currently necessary to limit the operating time of each operator, i.e. the time during which the latter is in contact with parts touched by the product. This is achieved through a frequent turnover of operators, which requires an appropriate number of operators to be made available and prepared for operations inside the cleanroom, with a consequent increase in system running costs.

Alternatively, it is necessary to provide the operators with particular equipment, such as completely airtight overalls

and masks that are able to insulate the operators completely from the surrounding environment. In addition to being very costly, this equipment places significant limitations on movements and performable manual operations.

5 An object of the present invention is to improve known apparatuses and methods for handling and treating elements of a packaging machine operating in a sterile-atmosphere environment.

Another object is to devise a system and a method that enable
10 elements, parts, components and operating units of a packaging machine to be handled and conveyed within a sterile environment atmosphere, without requiring a direct manual intervention by operators.

A further object is to obtain a system and a method that
15 enable parts, components and operating units to be assembled on or dismantled from a packaging machine automatically without a direct manual intervention by operators.

Still another object is to devise a system and a method preventing the operators coming into direct contact with
20 parts of the machine on which there is product to be packaged.

In a first aspect of the invention there is provided a system for transferring and moving elements that are removably associable with a packaging machine comprising at least a
25 transferring unit provided with movement means that is suitable for receiving and supporting said elements, said movement means being movable for transferring to and/or removing said elements from said machine.

Owing to this aspect of the invention it is possible to
30 supply a system that enables elements of a packaging machine such as parts, components, operating units to be transferred and moved, without requiring direct manual intervention by operators. In particular, thanks to the transferring unit it is possible to assemble on the packaging machine or dismantle
35 therefrom a plurality of diverse elements automatically, without the operators coming into direct contact with the

elements. This is particular advantageous if the machine is placed inside a cleanroom. In this case, direct contact of the operator both with sterile elements to be installed on the machine, and with elements soiled with product to be dismantled from the machine at the end of production is in fact not advisable and is sometimes not acceptable.

In the first case the system enables the elements to be maintained at the same level of sterility (contamination class) that they possess exiting from an autoclave.

In the second case the system preserves the operators from contact with the product and prevents possible absorption of unspecified quantities of said product, that may harm the health of or cause health complaints in operators.

In a second aspect of the invention there is provided a method for transferring and moving elements that are removably associable with a packaging machine characterised in that there is provided supporting and conveying said elements by means of at least a transferring unit and transferring to and/or removing from said packaging machine said elements using movement means of said transferring unit. The invention can be better understood and implemented with reference to the attached drawings, which illustrate a preferred embodiment by way of non-limiting example, in which:

- Figure 1 is a schematic plan view of a system for handling and treating elements of a packaging machine according to the invention, showing in particular a packaging machine inside a processing chamber and a transferring unit arranged in different, successive operating positions;
- Figure 2 is a schematic and enlarged side view of a transferring unit of the system of figure 1 in association with carriage means;
- Figure 3 is a schematic lateral view of the transferring unit associated with the packaging machine in Figure 1, in an operating step;
- Figure 4 is a plan view of the transferring unit and of the

packaging machine, showing said transferring unit in a hooking position on said machine, a second hooking position being represented by a broken line;

- Figure 5 is a partial enlarged view of Figure 4, showing a first element partially connected to supporting means of the packaging machine;

- Figure 6 is a partial enlarged view in Figure 1, showing the transferring unit associated with a washing unit in a connecting position, the second connecting position being represented by a broken line.

With reference to Figures 1 to 6, there is generally illustrated a system 1 for transferring and moving elements 50, 60 for an automatic packaging machine 3 operating inside a controlled-atmosphere processing chamber 2.

The elements 50, 60 comprise parts, components, operating units and devices of said machine 3, consisting for example of a batching/capping machine configured for batching a pharmaceutical product inside containers (not shown) and for capping the latter.

According to what has been illustrated in Figure 1, the processing chamber 2 is a cleanroom of the type normally used in pharmaceutical production, i.e. insulated from the external environment by means of airtight walls and doors, and bounding a sterile environment, subject to a flow of vertical one-way sterile air, generated by known air treatment and conditioning means that is not shown.

The chamber 2 is provided with at least a communication chamber 6, a so-called transferring bush, which connects said chamber 2 to a service room 7 that has a non-controlled atmosphere or anyway a contamination class that is less or more approximate than that of the processing chamber 2.

The aforesaid communication chamber 6 is provided with a first access door 66 to the inside of the chamber 2 and with a second access door 67 to the service room 7. Using these two doors prevents a direct connection between the inside of the chamber 2 and the service room 7, in order to maintain

the integrity of the sterile atmosphere inside the chamber 2. The communication chamber 6 is also subject to a one-way sterile air flow to adapt the atmosphere within to that of the chamber 2, during opening of the first door 66.

5 The system 1 further comprises sterilising means 4 comprising one or more autoclaves, of known type, suitable for sterilising elements 50, 60 to be introduced into said processing chamber 2. Similarly to the communication chamber 6, also the autoclave 4 is provided with an internal access
10 hatch 64 and an external access hatch 65, suitable for making the autoclave 4 communicate respectively with the chamber 2 and with the service room 7.

The system 1 further comprises at least a transferring unit 5 that is movable and arranged for conveying a plurality of
15 elements 50, 60 from the service room 7 to the packaging machine 3, through the autoclave 4, and from the packaging machine 3 to the service room 7, through the communication chamber 6.

The transferring unit 5 is, in fact, arranged for being
20 sterilised inside the autoclave 4 together with the elements 50, 60 contained therein. For this purpose, the transferring unit 5 and the elements 50, 60 are made of materials that are suitable for withstanding sterilisation temperatures and pressures.

25 According to what has been illustrated in Figure 2, the transferring unit 5 comprises movement means 20, 21 that is movable and arranged for supporting and moving respective elements 50, 60 to be mounted on or dismantled from the packaging machine 3. In particular the movement means 20, 21
30 is movable between a first operating position D in which it is arranged inside said transferring unit 5 and a second operating position E (figure 3) in which it partially protrudes outside said transferring unit, for example for removing and/or transferring elements 50, 60.

35 The movement means 20, 21 comprises respective grasping means 22, 23 suitable for hooking attaching portions 51, 61 of the

elements 50, 60.

According to what has been illustrated in Figures 2,3 and 4, the movement means 20, 21 is driven manually by the operator by means of respective controls such as cranks or handwheels.

5 Instead of the latter, portable driving means, for example electric screwdrivers can be used. In an embodiment that is not shown, the movement means 20, 21 is driven by motors and/or actuators that are removably mounted on the transferring unit 5, in such a way as to be able to be
10 dismantled during the washing and sterilisation steps in the autoclave. Alternatively, said motor means is suitably configured and insulated for withstanding washing agents and sterilisation pressures and temperatures.

The transferring unit 5 further comprises a supporting frame
15 25 to which said movement means 20, 21 is slidably fixed.

The frame 25 is provided with wheels 26 for enabling the unit 5 to be moved.

In particular, the wheels enable said transferring unit 5 to be easily inserted into and/or extracted from the sterilising
20 means 4 and/or from the communication chamber 6.

Although the atmosphere inside the chamber 4 is sterile and is of a contamination class that is appropriate to the type of process to be conducted, the floor of said chamber 4 can be considered to be of a lower or more approximate
25 contamination class as on it or near it, owing to the one-way vertical air flow, the polluting solid particles that may be present within the chamber are distributed and remain confined.

Thus in order to prevent the transferring unit 5 at the
30 outlet of the autoclave 4 coming into direct contact with the aforesaid floor there is provided carriage means 8 arranged for housing and supporting the transferring unit 5 inside the processing chamber 2.

According to what has been illustrated in Figure 3, the
35 carriage means 8 has a supporting plane 27 that is arranged at the same position or height as the bottom surface of the

autoclave 4 and of the communication chamber 6 to enable the transferring unit 5 to be inserted into and/or withdrawn from the transferring unit 5.

Removal means 19, fixed to the carriage means 8 (figure 2),
5 is provided for hooking and dragging the aforesaid transferring unit 5 onto the carriage means 8 or for pushing it outside the carriage means 8.

The removal means 19 comprises, for example, a telescopic arm or pantograph mechanism, which is able to be lengthened and
10 shortened and is provided with a free end that is suitable for grasping a portion of the supporting frame 25 of the transferring unit 5. The removal means 19 can be driven manually by an operator by means of a crank or handwheel 19a, or using an electric screwdriver.

15 According to what is visible in Figure 2, the carriage means 8 is further provided with containing means 9 suitable for making a covering structure that is able to enclose completely the transferring unit 5. The containing means 9 is substantially box-shaped and comprises two closed side walls,
20 the remaining two opposite walls being provided with respective movable doors 24a, 24b for the entry and exit of the transferring unit 5.

Conditioning means 10 is provided in the upper portion of the containing means 9 to generate a one-way vertical air flow,
25 from top to bottom. The conditioning means 10 comprises one or more fans or blowers 28 able to suck sterile air from the processing chamber and direct it through filtering means 29, for example HEPA absolute filters, onto the transferring unit 5.

30 In order to facilitate moving the carriage means 8, a possibly motor-driven transpallet 39 can be used that is able to lift and move the carriage means 8 and the transferring unit 5.

In an embodiment that is not shown, it is further provided
35 that the carriage means 8 is provided with driving means and with controlling means configured for moving the aforesaid

carriage means 8 independently and automatically, without the assistance of operators, according to set trajectories and paths. The carriage means 8 may comprise, for example, an AGV (Automated Guided Vehicle) unit of known type that is movable
5 along magnetic tracks obtained in the floor of the processing chamber 2 or guided by radio-type navigation systems or GPS. According to what has been illustrated in figure 4, the packaging machine 3 comprises centring means 11, 12 that enables the carriage means 8, i.e. the transferring unit 5,
10 to be placed in one or more hooking positions with respect to the machine 3.

There are, for example, two hooking positions (Figure 4) corresponding to respective specific operating zones of the machine 3, respectively a first operating zone 71 in which
15 there has to be assembled a first element 50, and a second operating zone 72, in which a second element 60 has to be mounted.

The centring means 11, 12 may comprise, for example, one or more pairs of prongs or elongated elements, typically a first
20 pair of prongs 11 and a second pair of prongs 12, each of which is fixed orthogonally to a lower front portion 3a of the machine 3, at the respective operating zone 71, 72.

The prongs of each pair 11, 12 are spaced apart from one another and divergent to the exterior of the machine 3 in
25 such a way as to abut lower side walls of the carriage means 8 and progressively guide and centre the latter, pushed to the machine 3, in a defined respective hooking position G1, G2.

In each hooking position G1, G2 the transferring unit 5 is
30 removably locked on the machine 3 through connecting means 13 configured for engaging in respective attaching means 68, 69 provided in said lower front portion of the machine 3, at the centring means 11, 12. In particular, the machine 3 comprises first attaching means 68, associated with the first pair of
35 prongs 11 and second attaching means 69, associated with the second pair of prongs 12.

The connecting means 13 comprises, for example, a pair of parallel and spaced pins 13a (figure 3) that are rotatably connected to the supporting frame 25 of the transferring unit 5 and provided with external threading. The pins 13a are
5 arranged for being inserted and screwed into in respective threaded seats 68a, 69a (only the seat 68a of which is illustrated in Figure 3) of the respective attaching means 68, 69.

The connecting means 13, i.e. the pins 13a, can be rotated
10 manually by the operator using respective rods 13b controlled by cranks 13c or by portable driving means, for example electric screwdrivers.

It is further provided in an embodiment that is not shown that the connecting means 13 is fixed to the carriage means 8
15 to lock the latter on the machine 3. In this case, the removal means 19 maintains the transferring unit 5 fixed to the carriage means 8.

According to what has been illustrated in Figures 3, 4 and 5, supporting means 30, 36 is provided on the machine 3 to
20 enable respective elements 50, 60 to be mounted and dismantled that are conveyed by the transferring unit 5.

The supporting means 30, 36 comprises respective supporting elements 31, 37 fixed to a horizontal plane and/or to a vertical plane of the machine 3 and is provided with
25 respective hooking means 33, 34 (figure 5) suitable for fixing and supporting the elements 50, 60.

The supporting means 30, 36 further comprises connecting means 32 for connecting to electric, pneumatic, fluid, product supply circuits of the machine, circuits for
30 dispatching and receiving electric or optical signals to/from sensors and coupling means 35 for connection to kinematic and movement mechanisms of the machine.

Specifically, with reference to the packaging machine illustrated in Figures 1 to 6, first supporting means 30 is
35 arranged for receiving and supporting a first element 50, consisting for example in an operating unit for batching a

powder product in containers and consisting of two parts.

The first supporting means 30 comprises a first supporting element 31 fixed to a horizontal plane of the machine 3 and provided with first hooking means 33 suitable for abutting on and locking abutting means 52 of the operating unit 50. The hooking means are, for example, shaped seats 33 suitable for receiving respective locking pins 52. There is provided connecting means 32 for connecting to a pneumatic and product supply circuit of the machine and coupling means 35, consisting of a motor-driven pin connected to the motor of the machine to drive mechanical devices of the operating unit 50.

Second supporting means 36 is on the other hand provided for receiving and supporting a second element 60, consisting for example of a vibrating supply device for caps closing containers. The second supporting means 36 comprises a second supporting element 37 fixed to a horizontal plane of the machine 3 on which the aforesaid device 60 is locked. Second hooking means 34 locks the second element 60 to the second supporting element 37.

The system 1 comprises inside the service room 7 a washing unit 14 (Figures 1 and 6) configured for washing the elements 50, 60 internally and externally.

Typically said elements comprise operating units, parts and components that have come into contact with the product, which, dismantled from the machine at the end of production, need to be cleaned and washed.

The elements are transferred from the packaging machine 3 to the washing unit 14 using the transferring unit 5 according to operating procedures that will be disclosed in detail in the continuation of the description.

According to what has been better illustrated in Figure 1, inside the service room 7 there can be provided further carriage means 8' that is identical to the carriage means 8 operating inside the processing chamber 2 and arranged for receiving the transferring unit 5 at the outlet of the

communication chamber 6.

The transferring unit 5, possibly contained inside said carriage means 8', is moved by an operator and made to abut on the washing unit 14.

5 Similarly to what happens with the packaging machine 3, the transferring unit 5 is positioned with respect to the washing unit 14 in one of different connecting positions, by means of respective centring means 81, 82 provided on said washing unit 14 and substantially identical to the centring means 11,
10 12 of the packaging machine 3 (Figure 6).

In each connecting position the transferring unit 5 is removably locked on the washing unit 14 as the connecting means 13 of said unit 5 is able to engage a respective attaching means 83, 84 provided on a lower front portion of
15 said washing unit 14, at the centring means 81, 82. The attaching means 83, 84 of the washing unit 14 is almost identical to the attaching means 68, 69 of the packaging machine 3.

With particular reference to Figure 6, the connecting
20 positions of the transferring unit to the washing unit 14 may, for example, be two: a first connecting position L1 for transferring the first element 50 to the washing unit 14, and a second connecting position L2 for transferring the second element 60.

25 The washing unit 14 includes a protecting cover 45, provided with one or more doors and defining an internal washing space 49, and resting means 40, 46 that is substantially identical to the supporting means 30, 36 of the packaging machine 3 as it is configured for enable the respective elements 50, 60
30 mounted on the machine 3 to be mounted and dismantled.

The resting means 40, 46 comprises respective supporting elements 41, 47 fixed to a plane of the washing unit 14 and provided with respective hooking means 43, 44 suitable for hooking and supporting the elements 50, 60.

35 Unlike the supporting means 30, 36, the resting means 40, 46 may comprise attachments and connections suitable for

conveying washing fluids inside the elements 50, 60.

With particular reference to Figure 6, the washing unit 14 is arranged for receiving the first element 50, which can be fixed to first resting means 40, and the second element 60, which can, on the other hand, be fixed to the second resting means 46.

The first element 50 is a batching unit that is fixed to first resting means 40 in such a way that supply means 42 of the washing unit 14, consisting of suitable connections, is able to deliver washing fluids into conduits, pipes and internal passages of said operating unit 50 for internal washing and cleaning.

The washing unit 14 is further provided with dispensing means 48, arranged in the internal washing space 49 for externally washing the operating unit 50. The dispensing means 48 comprises, for example, a plurality of sprayers or nozzles 48a distributed in the internal washing space 49 to sprinkle and spray external surfaces of the elements 50, 60.

In an embodiment of the system that is not illustrated, there is provided a further washing unit intended for automatically washing, without the manual intervention of operators, the transferring unit 5, in order to eliminate from the supporting frame 25 and from the movement means 20, 21 possible traces and residue of product that have become detached from the conveyed elements 50, 60.

The operation of the system 1 substantially provides a first sequence of operating steps preparatory to production, i.e. to operation of the packaging machine 3, and a second sequence of steps to be conducted at the end of production.

Initially, the washed and sterilised operating elements 50, 60 have to be mounted and assembled on the packaging machine 3 placed inside the controlled-atmosphere processing chamber 2.

The elements 50, 60 cleaned and washed in the service room 7 are arranged there on a transferring unit 5.

The transferring unit 5 and the elements 50, 60 present

therein are then introduced inside the autoclave 4, where they are sterilised.

At the end of the sterilising step, an operator opens the internal access hatch 64 of the autoclave 4 and arranges the carriage means 8 that is suitable for receiving and containing the transferring unit 5. The operator acts on the removal means 19 that hooks and drags the transferring unit 5 inside the carriage means 8.

The conditioning means 10 of the carriage means 8 is working to direct a one-way vertical air flow, from top to bottom, on the unit 5 and maintain the atmosphere inside the containing means 9 of the carriage means 8 in slightly excess pressure with respect to the chamber 2, in order to prevent the entry of possible contaminating solid particles.

When one of the movable doors 24a, 24b of the containing means 9 is open, the operator acts on the carriage means 8, for example for driving the removal means 19, always being arranged on the side opposite said open door, in such a way that possible polluting particles released thereby do not penetrate inside the containing means.

Before making the carriage means 8 approach the machine 3, the operator opens the door 24a, 24b of the wall facing said machine, whilst corresponding doors 56 of a protective structure 55 of the machine 3 have been opened beforehand (figure 1).

If the first operating element 50 has to be mounted on the machine 3 the operator makes the carriage means 8 approach in such a way that the first centring means 11 precisely positions the carriage means 8 at the first operating zone 71 of the machine 3.

After positioning, the operator drives the connecting means 13 in such a way as to lock the transferring unit 5 on the machine 3 in the first hooking position G1.

It is thus possible to drive the first movement means 20 of the transferring unit 5 to locate the first element 50 on the first supporting means 30. In particular, the first movement

means 20 transfers the first element 50 to the first supporting element 31 of the first supporting means 30, making the locking pins 52 of the operating unit 50 engage the hooking means 33. At the same time, the element 50 is
5 coupled with the connections 32 for connecting to the various supply circuits of the machine and to the mechanical power points 35.

After completing mounting of the first element 50, the transferring unit 5 can be released from the machine 3
10 disengaging the connecting means 13 from the first attaching means 68. At this point the carriage means 8 can be distanced from the machine 3 and, if necessary, moved to the second operating zone 72 of the machine 3 for mounting the second element 60.

15 The transferring unit is then locked by the connecting means 13 onto the machine 3 in the second hooking position G2 and the second movement means 21 is driven to position the second element 60 on the second supporting means 31.

The aforesaid operations are repeated for the plurality of
20 elements present on the transferring unit 5 that have to be mounted on the machine.

When the operations have been completed the packaging machine 3 is ready for production.

The same sequence of steps necessary for mounting the
25 elements 50, 60 on the machine 3 can be used in reverse order to dismantle and load onto the transferring unit 5 the elements 50, 60 to be conveyed outside the processing chamber 2. In this case, the movement elements 20, 21 will hook and extract the elements 50, 60 from the respective supporting
30 means 30, 31.

During movement through the processing chamber 2, the containing means 9 of the carriage means 8 prevents particles and product residue present on the elements 50, 60 from being
35 able to disperse in the chamber 2 and, in particular, come into contact with the operator working on the carriage means 8.

The carriage means 8 is then taken to the communication chamber 6, the first access door 66 of which to the chamber 2 is open, the second passage door 67, to the service room 7, being hermetically sealed.

5 The removal means 19 is driven to push the transferring unit 5 inside the communication chamber 6. The latter, similarly to the autoclave 4, has a bottom surface placed almost at the same level as the supporting plane 27 of the carriage means 8 to enable the transferring unit 5 to be moved.

10 During the various operating steps disclosed above one or more operators move manually the carriage means 8 and drive manually the various operating means 19, 13, 20, 21 of the transferring unit 5 and of the carriage means 8.

The transferring unit 5 and the carriage means 8 can anyway
15 comprise driving means and controlling means that are of known type that is not shown, configured for moving the aforesaid carriage means 8 and driving the various operating means independently and automatically, without requiring the help or the presence of operators inside the processing
20 chamber 2.

Once the transferring unit has been introduced inside the autoclave 4 and the first door 66 has been closed, it is possible to open the second door 67 of the space to enable an operator to remove the transferring unit 5.

25 A tilted ramp will be provided to enable exit from the communication chamber 6 if the floor of the service room 7 is at a different level, for example a lower level than the bottom surface of said space 6.

Alternatively, there can be provided further carriage means
30 8' that is able to remove the transferring unit 5, using the same operating procedures and sequences used to extract said unit 5 from the autoclave 4.

The transferring unit 5 is moved by the operator until it abuts on the washing unit 14 in respect to which it is
35 positioned and locked in sequence in the provided connecting positions L1, L2.

Similarly to what occurs with the carriage means 8 inside the processing chamber 2, the operator interacts with the transferring unit 5 arranging himself at a respective rear side 5A opposite a front access side 5B (figure 1) inside the transferring unit 5. This prevents the operator from coming into contact with residues of product present on the elements 50, 60 conveyed by the transferring unit 5.

In the first connecting position L1, the first movement means 20 of the transferring unit 5 transfers and mounts the first element 50 on the first resting means 40 of the washing unit 14. This mounting further involves connecting conduits, pipes and internal passages present in the first element to the attachments and connections 47 provided in the first resting means 40 for delivering washing fluids.

In the second connecting position L2 the second movement means 21 moves and mounts the second element 60 on the second resting means 46. In this case, as the second element 60 is not provided with conduits and internal passages, the presence on the second resting means 46 of specific connections and attachments for the dispensing of washing fluids is not required.

Obviously, the washing unit 14 can be configured in function of the elements to be washed and thus comprise further resting means suitably arranged for receiving and supporting respective elements, provided or not provided with connections and attachments for the internal washing of said elements.

Once the elements have been assembled on the washing unit 14, the corresponding protecting cover 45 can be closed and the external and internal washing cycle can be started.

The method, duration and features of the internal and external washing are defined in function of the type of package product, the form and structure of the elements, required cleaning requirements, etc.

At the end of washing, the operating elements 50, 60 can be dismantled from the washing unit 14 using the transferring

unit 5 or manually by the operators.

In the first case, the elements 50, 60 have been washed suitably and in compliance with required cleaning requirements and can be conveyed together with the transferring unit 5 inside the autoclave 4 for sterilisation. The transferring unit 5, before removing the elements, has been cleaned and washed beforehand, in such a way as to eliminate traces and residues of product that may be present on the supporting frame 25, on the movement means 20, 21 and on the grasping means 22, 23. The transferring unit 5 can be washed manually by the operators or automatically using a respective and specific washing unit.

If the washing performed by the washing unit 14 is insufficient or if the elements 50, 60 have to be dismantled for modifications, adjustments, or repairs they have to be handled by the operators. Nevertheless, this handling in this step is safe, as most of the product present on the elements 50, 60 was eliminated during automatic cleaning in the washing unit 14.

At the end of these manual operations, the elements 50, 60 can be positioned on the transferring unit 5 and then placed in the autoclave 4 for sterilising.

It should be observed that the system that is the object of the present invention enables elements of a packaging machine to be transferred and moved semiautomatically or automatically without requiring direct manual intervention on said elements by operators.

This is particularly important both during the mounting step to prevent possible contamination of the washed and sterilised elements, and during the dismantling step to prevent the operator coming into contact with the packaged product.

In an embodiment of the system, all the operating procedures can be performed automatically without requiring the presence of operators inside the processing chamber 2.

It is clear that the system 1 may comprise inside the

processing chamber 2 a plurality of packaging machines 3, operating independently on distinct production lines or in series, connected together to form a complete packaging line. Similarly, in the system 1 a plurality of transferring units 5 and of respective carriage means 8 can be used to transfer, mount and dismantle at the same time a plurality of elements and thereby reduce operating time.

CLAIMS

1. System for transferring and moving elements (50, 60) removably associable with a packaging machine (3), characterised in that it comprises at least a transferring unit (5) provided with movement means (20, 21) that are suitable for receiving and supporting said elements (50, 60), said movement means (20, 21) being movable for transferring to and/or removing from said machine (3) said elements (50, 60).
2. System according to claim 1, wherein said transferring unit (5) comprises a supporting frame (25) provided with wheels (26) and suitable for slidably supporting said movement means (20, 21).
3. System according to claim 1 or 2, wherein said movement means (20, 21) comprises respective grasping means (22, 23) arranged for hooking attaching portions (51, 61) of said elements (50, 60).
4. System according to any preceding claim, wherein said movement means (20, 21) is movable between a first operating position (D) wherein it is arranged inside said transferring unit (5) and a second operating position (E) wherein it is extended for removing and/or transferring elements (50, 60).
5. System according to any preceding claim, wherein said movement means (20, 21) is drivable manually by an operator.
6. System according to claim 5, wherein said movement means (20, 21) is driven by actuating means connected to said supporting frame (25).
7. System according to any preceding claim, wherein said transferring unit (5) comprises connecting means (13) arranged for engaging attaching means (68, 69) of said packaging machine (3) to removably lock to the latter said transferring unit (5).
8. System according to any preceding claim, comprising carriage means (8) suitable for supporting and conveying

said transferring unit (5).

9. System according to claim 8, wherein said carriage means (8) comprises containing means (9) arranged for enclosing said transferring unit (5).

5 10. System according to claim 9, wherein said carriage means (8) comprises conditioning means (10) arranged in an upper portion of the containing means (9) and suitable for generating a substantially vertical one-way air flow inside said containing means (9).

10 11. System according to claim 9 or 10, wherein said conditioning means (10) comprises fan means (28) and filtering means (29).

12. System according to any one of claims 8 to 11, wherein said carriage means (8) is movable manually by an operator
15 or by means of a driven carriage (39).

13. System according to any one of claims 8 to 11, wherein said carriage means (8) comprises driving means and controlling means suitable for automatically moving said carriage means (8) along set trajectories and paths.

20 14. System according to any one of claims 8 to 13, wherein said carriage means (8) comprises removal means (19) suitable for hooking and locking said transferring unit (5), said removal means (19) being further movable for introducing and/or ejecting said transferring unit (5)
25 into and/or from said carriage means (8).

15. System according to any one of claims 8 to 14, wherein said carriage means (8) comprises connecting means (13) arranged for engaging in attaching means (68, 69) of said machine (3) to removably lock to the latter said carriage
30 means (8); said supporting means (30, 36) comprising hooking means (33, 34) suitable for abutting on and locking abutting means (52) of said elements (50, 60).

16. System according to any one of claims 8 to 14, wherein said supporting means (30, 36) comprises connecting means
35 (32) for connecting said elements (50, 60) to circuits of the machine (3), for example electric, pneumatic and

supply circuits of a product to be packaged.

17. System according to any preceding claim, comprising a processing chamber (2) suitable for containing said packaging machine (3) and said transferring unit (5); said chamber (2) being insulated and having a controlled, for example sterile atmosphere.
18. System according to claim 17, wherein said chamber (2) comprises means for generating a controlled one-way air flow.
19. System according to any one of claims 17 to 18, comprising a service room (7) adjacent to said processing chamber (2) and connected to the latter through a communication chamber (6); said communication chamber (6) comprising a first access door (66) to said chamber (2) and a second access door (67) to said the service room (7).
20. System according to claim 18 or 19, wherein said communication chamber (6) comprises means for generating a controlled one-way air flow inside said communication chamber (6).
21. System according to any preceding claim, comprising sterilising means (4) configured for housing and containing said transferring unit (5).
22. System according to claim 21, wherein said sterilising means (4) comprises an autoclave provided with an internal access hatch (64) giving access to said processing chamber (2) and an external access hatch (65) giving access to said the service room (7).
23. System according to any preceding claim, wherein said elements (50, 60) and said transferring unit (5) are sterilisable in an autoclave.
24. System according to any preceding claim, comprising at least a washing unit (14) suitable for washing said elements (50, 60) internally and/or externally.
25. System according to claim 24, wherein said washing unit (14) is placed in said service room (7).
26. System according to claim 24 or 25, wherein said washing

unit (14) comprises a protecting cover (45), provided with one or more doors and defining an internal washing space (49).

27. System according to claim 26, wherein said washing unit (14) comprises resting means (40, 46) suitable for supporting said elements (50, 60) during a washing step, said resting means (40, 46) being further configured for receiving said elements (50, 60) from and giving said elements (50, 60) to said movement means (20, 21) of said transferring unit (5).

28. System according to claim 27, wherein said washing unit (14) comprises supply means (42) suitable for being connected to said elements (50) to deliver washing fluids inside the latter.

29. System according to claim 26, wherein said washing unit (14) comprises dispensing means (48), arranged inside said internal washing space (49) for spraying a washing fluid onto said elements (50, 60).

30. System according to claim 29, wherein said dispensing means (48) comprises a plurality of sprayers or nozzles (48a).

31. System according to any preceding claim, wherein said washing unit (14) comprises respective centring means (81, 82) suitable for defining at least a connecting position (L1, L2) of said transferring unit (5) to said washing unit (14).

32. System according to claim 31, wherein said respective centring means (81, 82) of the washing unit (14) comprises at least a pair of elongated elements, spaced from one another and substantially parallel, fixed substantially orthogonally to said washing unit (14).

33. System according to claim 31 or 32, wherein said washing unit (14) comprises attaching means (83, 84) suitable for being engaged by connecting means (13) of the transferring unit (5) for locking the latter on said washing unit (14) in said connecting position (L1, L2).

34. Method for transferring and moving elements (50, 60) removably associable with a packaging machine (3), characterised in that there is provided supporting and conveying said elements (50, 60) using at least a transferring unit (5) and transferring said elements (50, 60) to and/or removing said elements (50, 60) from said packaging machine (3) using movement means (20, 21) for moving said transferring unit (5).

35. Method according to claim 34, wherein said transferring comprises moving said elements (50, 60) from inside the transferring unit (5) and fixing said elements (50, 60) to respective supporting means (30, 36) of said packaging machine (3).

36. Method according to claim 35, wherein said fixing comprises abutting and locking abutting means (52) of said elements (50, 60) on hooking means (33, 34) of said supporting means (30, 36).

37. Method according to claim 35 or 36, wherein said fixing comprises connecting said elements (50, 60) to supply circuits of the machine (3), for example electric, pneumatic and supply circuits of a product to be packaged and to kinematic mechanisms and movement mechanisms of said machine (3).

38. Method according to any one of claims 34 to 37, wherein said transferring comprises releasing said elements (50, 60) fixed to said respective supporting means (30, 36).

39. Method according to claim 38, wherein said releasing comprises unhooking attaching portions (51, 61) of said elements (50, 60) using grasping means (22, 23) of the movement means (20, 21).

40. Method according to any one of claims 34 to 39, wherein said removing comprises detaching said elements (50, 60) from respective supporting means (30, 36) of said packaging machine (3) and moving them inside the transferring unit (5).

41. Method according to claim 40, wherein said detaching

comprises disconnecting said elements (50, 60) from the supply circuits of the machine (3), for example electric, pneumatic and supply circuits supplying a product to be packaged and from the movement mechanisms for moving said machine (3).

42. Method according to claim 40 or 41, wherein said detaching comprises disengaging abutting means (52) of said elements (50, 60) from hooking means (33, 34) of said supporting means (30, 36) and hooking attaching portions (51, 61) of said elements (50, 60), using grasping means (22, 23) of the movement means (20, 21).

43. Method according to any one of claims 34 to 42, wherein before said transferring and/or removing there is provided removably locking said transferring unit (5) to said machine (3).

44. Method according to claim 43, wherein said locking comprises engaging connecting means (13) of said transferring unit (5) to attaching means (68, 69) of said packaging machine (3).

45. Method according to any one of claims 34 to 44, wherein after said transferring and/or removing there is provided releasing said transferring unit (5) from said machine (3).

46. Method according to claim 45, wherein said releasing comprises disengaging connecting means (13) of said transferring unit (5) from attaching means (68, 69) of said packaging machine (3).

47. Method according to any one of claims 34 to 46, comprising manually moving said transferring unit (5).

48. Method according to claim 47, comprising manually interacting with said transferring unit (5) at a side (5A) of the latter opposite an access side (5B) giving access inside said transferring unit (5).


49. Method according to any one of claims 34 to 48, comprising sterilising said transferring unit (5) containing said elements (50, 60) inside sterilising means (4).

50. Method according to claim 49, wherein after said sterilising there is provided the step of introducing said transferring unit (5) into carriage means (8).
51. Method according to claim 50, wherein said conveying said
5 elements (50, 60) using said transferring unit (5) comprises moving said carriage means (8).
52. Method according to claim 50 or 51, comprising generating a one-way air flow inside said carriage means (8).
53. Method according to any preceding claim, comprising moving
10 manually said carriage means (8).
54. Method according to any preceding claim, comprising automatically moving said carriage means (8) along set trajectories and paths using driving means and controlling means of said carriage means (8).
- 15 55. Method according to any preceding claim, wherein said introducing comprises hooking and locking said transferring unit (5) using removal means (19) of said carriage means (8).
56. Method according to claim 55, comprising the phase of
20 manually driving said removal means (19).
57. Method according to any preceding claim, wherein there is provided positioning said packaging machine (3) inside a processing chamber (2)
58. Method according to claim 56, comprising maintaining said
25 chamber (2) insulated with a controlled, for example sterile atmosphere.
59. Method according to any preceding claim, comprising introducing said transferring unit (5), containing said elements (50, 60), in said processing chamber (2) through
30 said sterilising means (4).
60. Method according to any preceding claim, comprising moving said transferring unit (5), containing said elements (50, 60), from said processing chamber (2) to the adjacent service room (7) through a communication chamber (6).
- 35 61. Method according to claim 60, comprising maintaining said communication chamber (6) insulated with a controlled, for

example, sterile atmosphere.


62. System for transferring and moving elements removably associable with a packaging machine, substantially as disclosed and claimed and for the specified purposes.


5 63. Method for transferring and moving elements removably associable with a packaging machine, substantially as disclosed and claimed and for the specified purposes.



2/5

Fig. 2








Fig. 4

