

(19) **DANMARK**



Patent- og
Varemærkestyrelsen

(10) **DK/EP 2866047 T3**

(12) **Oversættelse af
europæisk patentskrift**

-
- (51) Int.Cl.: **G 01 S 13/86 (2006.01)** **G 01 S 7/499 (2006.01)** **G 01 S 17/26 (2020.01)**
G 01 S 17/89 (2020.01)
- (45) Oversættelsen bekendtgjort den: **2021-03-29**
- (80) Dato for Den Europæiske Patentmyndigheds
bekendtgørelse om meddelelse af patentet: **2020-12-23**
- (86) Europæisk ansøgning nr.: **13189856.1**
- (86) Europæisk indleveringsdag: **2013-10-23**
- (87) Den europæiske ansøgnings publiceringsdag: **2015-04-29**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV
MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Ladar Limited, 201 Rogers Office Building , Edwin Wallace Rey Drive, George Hill, Anguilla
Hjelmstad AS, Torggatan 20B, 2000 Lillestrom, Norge**
- (72) Opfinder: **Hjelmstad, Jens, Torvgata 20B, 2000 Lillestrom, Norge**
- (74) Fuldmægtig i Danmark: **GUARDIAN IP CONSULTING I/S, Diplomvej 381, 2800 Lyngby, Danmark**
- (54) Benævnelse: **DETEKTERINGSSYSTEM TIL DETEKTERING AF EN GENSTAND PÅ EN VANDOVERFLADE**
- (56) Fremdragne publikationer:
EP-A2- 1 956 390
DE-B3-102010 007 520
US-A- 4 995 102
US-A- 5 781 147
US-A1- 2011 084 486
US-B1- 6 714 286
**GAVAN G ET AL: "OPTIMIZED LADAR/RADAR SYSTEM FOR DETECTION AND TRACKING", INTERNATIONAL
JOURNAL OF INFRARED AND MILLIMETER WAVES, SPRINGER, DORDRECHT, NL, vol. 13, no. 3, 1 March 1992
(1992-03-01), pages 381-388, XP000259904, ISSN: 0195-9271, DOI: 10.1007/BF01010673**

DESCRIPTION

TECHNICAL FIELD

[0001] The present invention relates to object detection.

BACKGROUND OF THE INVENTION

[0002] Objects on a water surface, i.e. marine objects, can coarsely be detected from a position above the water surface using a radio detection and ranging (radar) device.

[0003] Radio detection and ranging devices are based on transmitting an electromagnetic wave towards the object, and detecting an electromagnetic wave which has been reflected by the object. The electromagnetic wave can be pulsed and/or modulated. Common modulation schemes comprise e.g. a frequency-modulated continuous wave (FMCW) modulation scheme or a frequency-stepped continuous wave (FSCW) modulation scheme.

[0004] The attainable precision and resolution of object detection are mainly influenced by the properties of the applied electromagnetic wave such as the center frequency or the covered frequency bandwidth of the electromagnetic wave. Furthermore, the propagation scenario of the electromagnetic wave, in particular multipath propagation, influences the attainable precision and resolution of object detection.

[0005] Common radio detection and ranging devices for the detection of objects on a water surface operate in the X-band extending from 8.0 GHz to 12.0 GHz. The propagation scenario is non-stationary due to the movement of waves at the water surface and poses significant challenges to object detection. Undesired reflections of the electromagnetic wave at the water surface, also known as clutter, further impede the detection of objects.

[0006] Therefore, the detection of objects on a water surface using a radio detection and ranging device is limited to the detection of large objects exhibiting a high reflectivity of the electromagnetic wave. The detection of small objects is usually not possible due to the non-stationary propagation scenario and difficulties in distinguishing small objects from undesired reflections of the electromagnetic wave at the water surface.

[0007] In US 5,781,147 A, an apparatus and a method for determining a range to a target utilizing both a radar transceiver and a laser transceiver is disclosed. The apparatus can be employed as a docking aid system and can be mounted at a location on a dock to guide a docking of a vessel. The apparatus can further be mounted on board of the vessel. A gating window is used for determining which laser reflection originates from the actual target.

[0008] In US 2011/0084486 A1, an off-shore wind turbine generator comprising a monitoring apparatus for monitoring the surrounding of the wind turbine generator is disclosed. The monitoring apparatus comprises at least one of a radar, a laser radar, and a camera. The radar, the laser radar, and the camera can be mounted at different locations on the wind turbine generator.

[0009] In Gavan et al., "Optimized ladar/radar system for detection and tracking", Int. Journal of Infrared and Millimeter Waves, 13(1992), No. 3, a dual mode LADAR/RADAR system for detection and tracking of cooperative airborne targets is disclosed. At long ranges, a primary mode is activated using the RADAR to detect and track the target. The system switches to a secondary mode using the LADAR to track the target at short ranges.

[0010] In EP 1 956 390 A2, a navigation system for sensor fused navigation is disclosed. The navigation system comprises a plurality of navigation sensors, in particular a vision sensor, a RADAR sensor, and/or a LADAR sensor, which are connected to a processing unit. Each navigation sensor provides data for at least one of a plurality of rigid body states to the processing unit. The navigation system can be used in various vehicles for navigation, including automobiles, aircraft, unmanned air vehicles, space craft, lunar landers, or space probes.

[0011] In DE 10 2010 007 520 B3, a security controller for object detection in industrial environments having a plurality of ports for sensors is disclosed. The sensors can comprise a laser scanner and/or a radar.

[0012] In US 4,995,102 A, a scanning method used by a laser radar for scanning a predetermined scanning region with a laser beam is disclosed, so that the whole of the scanning region is illuminated with the laser beam. The scanning region scanned with the laser beam may be determined on the basis of positional information on a target obtained by a microwave radar.

[0013] In US 6,714,286 B1, an apparatus for dynamically optimizing an acquisition range of a (laser) radar system is disclosed, including modulating a CW radar signal with a PN code that has an adjustable code frequency of modulation and an adjustable chip length.

SUMMARY OF THE INVENTION

[0014] It is therefore the object of the invention to provide an improved concept for detecting an object on a water surface.

[0015] This object is achieved by the features of the independent claims. Further implementation forms are apparent from the dependent claims, the description and the figures.

[0016] The invention is based on the finding that objects on a water surface can be detected

more precisely when coarsely detecting a target water surface area with the object using a radio detection and ranging (radar) device and then more precisely detecting the object within the target water surface area using a laser detection and ranging (ladar) device. The laser detection and ranging device can transmit a laser beam towards the target water surface area, detect a reflected laser beam reflected by the object, and detect the object upon the basis of the reflected laser beam. The usage of a laser beam allows for a high precision and high resolution detection of the object. Thus, even small objects on a water surface can be detected.

[0017] According to an aspect, the invention relates to a detection system for detecting an object on a water surface, the detection system comprising a radio detection and ranging device for coarsely detecting a target water surface area with the object, and a laser detection and ranging device for detecting the object within the target water surface area, wherein the laser detection and ranging device comprises a laser transmitter for transmitting a laser beam towards the target water surface area, a laser detector for detecting a reflected laser beam, the reflected laser beam forming a reflected version of the transmitted laser beam, and a processor for detecting the object within the target water surface area upon the basis of the reflected laser beam.

[0018] The detection system can be mounted on a marine seagoing vessel, e.g. a ship, or a marine stand-still platform, e.g. an oil production platform. The detection system can further be installed at a marine harbor or marine port.

[0019] The object can be a floating obstacle. The object can further be a marine seagoing vessel, e.g. a ship, or a marine stand-still platform, e.g. an oil production platform.

[0020] The water surface can be defined as the surface layer between water and air.

[0021] The radio detection and ranging device can be based on transmitting an electromagnetic wave towards the object, and detecting an electromagnetic wave which has been reflected by the object. The radio detection and ranging device can be a common radio detection and ranging device for marine object detection.

[0022] The target water surface area can coarsely indicate a position of the object. The target water surface area can be defined by an azimuth and/or an elevation with respect to the detection system. The target water surface area can be defined by an azimuth-range cell on the water surface.

[0023] The laser detection and ranging device can be based on transmitting a laser beam towards the object, and detecting a laser beam which has been reflected by the object.

[0024] The transmitted laser beam can be spatially and/or temporally coherent. The transmitted laser beam can be a Gaussian beam. The transmitted laser beam can be polarized, e.g. vertically polarized. The reflected laser beam can be spatially and/or temporally

coherent. The reflected laser beam can be a Gaussian beam. The reflected laser beam can be polarized, e.g. vertically polarized.

[0025] The laser transmitter can be a solid state laser, e.g. a neodymium-doped yttrium aluminum garnet (Nd:YAG) laser. The laser transmitter can further be a dye laser or a gas laser. The laser transmitter can comprise a non-linear optical element, e.g. for frequency doubling. The laser transmitter can operate at an infrared frequency band, an optical frequency band, or an ultraviolet frequency band.

[0026] The laser detector can be a semiconductor-based laser detector or a tube-based laser detector. The laser detector can be configured to convert the detected laser beam into an electrical signal.

[0027] The processor can be programmably arranged to detect the object within the target water surface area upon the basis of the reflected laser beam.

[0028] According to an implementation form, the laser transmitter is configured to transmit a blue-green laser beam in the wavelength range between 400nm and 600nm. Thus, the laser beam can be transmitted efficiently through water and/or fog.

[0029] The wavelength of the blue-green laser beam can be adjusted for enabling a propagation of the blue-green laser beam through water and/or fog with minimum absorption losses.

[0030] According to an implementation form, the laser transmitter is configured to transmit a laser beam having an oval-shaped laser beam cross-section. Thus, azimuth-range cells with equal resolution can be realized within the target water surface area at large ranges.

[0031] The cross-section of the laser beam can be perpendicular with respect to the beam direction. The oval-shaped laser beam cross-section can have an elliptic shape.

[0032] According to an implementation form, the laser transmitter is configured to transmit a modulated laser beam, the modulated laser beam being modulated by a binary pseudo-random coding sequence, in particular by a binary pseudo-random coding sequence which is modulated by a square wave sequence. Thus, a range of the object within the target water surface area can be detected efficiently.

[0033] The binary pseudo-random coding sequence can take values from a binary or 2-ary alphabet, e.g. $\{-1, 1\}$ or $\{0, 1\}$. The binary pseudo-random coding sequence can be generated by a linear feedback shift register. The binary pseudo-random coding sequence can be a maximum length sequence or M-sequence.

[0034] The square wave sequence can take values from a binary or 2-ary alphabet, e.g. $\{-1, 1\}$ or $\{0, 1\}$. The square wave sequence can be periodic. The square wave sequence can be

defined by a duty cycle, e.g. 40%. The rate of the square wave sequence can be lower than the rate of the binary pseudo-random coding sequence.

[0035] By modulating the binary pseudo-random coding sequence by a square wave sequence, a pulsation of the modulated laser beam can be achieved.

[0036] According to an implementation form, the binary pseudo-random coding sequence is a GPS L2 civil moderate length sequence or a GPS L2 civil long length sequence. Thus, the binary pseudo-random coding sequence can be generated efficiently.

[0037] The GPS L2 civil moderate (L2CM) length sequence and the GPS L2 civil long (L2CL) length sequence can e.g. be generated according to the document "Interface Specification IS-GPS-200, Revision G", Global Positioning Systems Directorate, September 5, 2012.

[0038] According to an implementation form, the laser transmitter is configured to transmit a modulated laser beam, the modulated laser beam being modulated by an on-off-keying modulation or an amplitude-shift-keying modulation. Thus, a range of the object within the target water surface area can be detected efficiently.

[0039] The on-off-keying modulation can relate to switching the laser beam on and off upon the basis of a modulating sequence, e.g. the binary pseudo-random coding sequence.

[0040] The amplitude-shift-keying modulation can relate to switching the amplitude or intensity of the laser beam between different values upon the basis of a modulating sequence, e.g. the binary pseudo-random coding sequence.

[0041] According to an implementation form, the laser detector comprises a laser detecting diode or a photo multiplier for detecting the reflected laser beam. Thus, the reflected laser beam can be detected efficiently.

[0042] The laser detecting diode can be a semiconductor photo diode, e.g. an avalanche photo diode. The laser detecting diode can comprise electrical circuitry for converting the detected laser beam into an electrical signal.

[0043] The photo multiplier can be a vacuum photo tube. The photo multiplier can comprise electrical circuitry for converting the detected laser beam into an electrical signal.

[0044] According to an implementation form, the laser detector comprises an optical band-pass filter. Thus, the reflected laser beam can be separated from undesired ambient light components.

[0045] The optical band-pass filter can be configured to pass the reflected laser beam and to attenuate the undesired ambient light components.

[0046] According to an implementation form, the processor is configured to determine a time delay between transmitting the laser beam and detecting the reflected laser beam for determining a range of the object within the target water surface area. Thus, the range of the object within the target water surface area can be determined efficiently.

[0047] The time delay can relate to a round-trip time of the laser beam from the laser transmitter to the object and from the object to the laser detector. The time delay can e.g. be 1 μ s, 2 μ s, 5 μ s or 10 μ s.

[0048] The range of the object can relate to the distance of the object from the laser detection and ranging device. The range of the object can e.g. be determined by multiplying the time delay by the propagation speed of the laser beam and dividing by 2. The range of the object can e.g. be 150m, 300m, 750m or 1.5km.

[0049] According to an implementation form, the processor is configured to determine the time delay by correlating the transmitted laser beam and the detected laser beam in time to obtain a range profile, and by determining a maximum value of the range profile. Thus, the range of the object within the target water surface area can be determined efficiently.

[0050] The correlation of the transmitted laser beam and the detected laser beam in time can relate to determining a cross-correlation function in time between the transmitted laser beam and the detected laser beam. The correlation of the transmitted laser beam and the detected laser beam in time can realize a pulse compression and/or a matched filtering.

[0051] The range profile can indicate the range and reflectivity of objects and/or multipath components. The time delay corresponding to the maximum value of the range profile can indicate the range of the object.

[0052] According to an implementation form, the processor is configured to determine a spectrum of the detected laser beam to determine absorbed or reflected laser beam wavelengths by the object within the target water surface area. Thus, a characterization and/or identification of the object based on spectral properties of the object can be realized. According to an implementation form, the laser detection and ranging device further comprises a motion reference unit for determining a motion of the laser detection and ranging device, wherein a beam direction of the laser beam is stabilized upon the basis of the determined motion of the laser detection and ranging device. Thus, the beam direction of the laser beam can be stabilized efficiently.

[0053] The motion reference unit can be configured to determine a roll, a pitch, and/or a heading of the laser detection and ranging device. The motion of the laser detection and ranging device can be due to a movement of the laser detection and ranging device.

[0054] The beam direction can indicate the direction of propagation of the laser beam. The beam direction can be defined by an azimuth and/or elevation with respect to the laser

detection and ranging device.

[0055] The stabilization can be realized by controlling the beam direction towards a predetermined azimuth, e.g. 5° , and/or a predetermined elevation, e.g. -2° , with respect to the laser detection and ranging device.

[0056] According to an implementation form, the laser detection and ranging device is configured to scan the target water surface area along a horizontal plane for detecting an azimuth of the object within the target water surface area, or a vertical plane for detecting an elevation of the object within the target water surface area. Thus, the object can efficiently be detected within the target water surface area.

[0057] The scanning can be performed by successively directing the laser beam towards different predetermined azimuths and/or elevations within the target water surface area.

[0058] The horizontal plane can be defined by a variable azimuth and a fixed elevation of the beam direction with respect to the laser detection and ranging device. The vertical plane can be defined by a fixed azimuth and a variable elevation of the beam direction with respect to the laser detection and ranging device.

[0059] According to an implementation form, the detection system further comprises a thermal sensor, an infrared sensor, a multi-spectral sensor, a hyper-spectral sensor, a visual band imager, or a camera for detecting the target water surface area with the object. Thus, the target water surface area can be detected efficiently.

[0060] The thermal sensor can be configured to detect the target water surface area upon the basis of heat radiation transmitted from the object. The infrared sensor can be configured to detect the target water surface area upon the basis of infrared radiation transmitted from the object.

[0061] The multi-spectral sensor can be configured to detect the target water surface area upon the basis of radiation transmitted from the object in multiple frequency bands. The hyper-spectral sensor can be configured to detect the target water surface area upon the basis of radiation transmitted from the object over a continuous frequency band.

[0062] The visual band imager can be configured to detect the target water surface area upon the basis of radiation transmitted from the object in a visual frequency band. The camera can be configured to detect the target water surface area upon the basis of a photo or image of the water surface.

[0063] The target water surface area can be detected using a combination of a radio detection and ranging device, a thermal sensor, an infrared sensor, a multi-spectral sensor, a hyper-spectral sensor, a visual band imager, and/or a camera.

[0064] According to an aspect, the invention relates to a detection method for detecting an object on a water surface, the detection method comprising coarsely detecting a target water surface area with the object by a radio detection and ranging device, and detecting the object within the target water surface area by a laser detection and ranging device, wherein detecting the object within the target water surface area by the laser detection and ranging device comprises transmitting a laser beam towards the target water surface area by a laser transmitter, detecting a reflected laser beam by a laser detector, the reflected laser beam forming a reflected version of the transmitted laser beam, and detecting the object within the target water surface area upon the basis of the reflected laser beam by a processor.

[0065] The detection method can be performed by the detection system. Further features of the detection method can directly result from the functionality of the detection system.

[0066] The invention can be implemented in hardware and/or software.

BRIEF DESCRIPTION OF THE DRAWINGS

[0067] Further implementation forms of the invention will be described with respect to the following figures, in which:

Fig. 1

shows a schematic diagram of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 2

shows a schematic diagram of a detection method for detecting an object on a water surface according to an implementation form;

Fig. 3

shows two schematic diagrams of a detection scenario for detecting an object on a water surface according to an implementation form;

Fig. 4

shows a schematic diagram of subsystems of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 5

shows a schematic diagram of a sensor unit of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 6

shows a schematic diagram of a data processor unit of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 7

shows a schematic diagram of a display unit of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 8

shows a schematic diagram of a system console unit of a detection system for detecting

an object on a water surface according to an implementation form;

Fig. 9

shows a schematic diagram of interfaces of a detection system for detecting an object on a water surface according to an implementation form;

Fig. 10

shows a schematic diagram of sensor components of a sensor unit according to an implementation form;

Fig. 11

shows a schematic diagram of processing components of a sensor unit according to an implementation form;

Fig. 12

shows a schematic diagram of a cross-section of a laser beam according to an implementation form;

Fig. 13

shows a schematic diagram of a radar coverage area of a sensor unit according to an implementation form;

Fig. 14

shows a schematic diagram of a ladar coverage area of a sensor unit according to an implementation form;

Fig. 15

shows a schematic diagram of a ladar coverage area of a sensor unit according to an implementation form;

Fig. 16

shows a schematic diagram of a visual band coverage area of a sensor unit according to an implementation form;

Fig. 17

shows a schematic diagram of an infrared coverage area of a sensor unit according to an implementation form;

Fig. 18

shows a schematic diagram of a laser beam refraction for detecting an object under a water surface according to an implementation form;

Fig. 19

shows a schematic diagram of a detection scheme for detecting an object under a water surface according to an implementation form; and

Fig. 20

shows a schematic diagram of a detection scheme for detecting an object under a water surface according to an implementation form.

DETAILED DESCRIPTION OF THE DRAWINGS

[0068] Fig. 1 shows a schematic diagram of a detection system 100 for detecting an object on

a water surface according to an implementation form.

[0069] The detection system 100 comprises a radio detection and ranging device 101 for coarsely detecting a target water surface area with the object, and a laser detection and ranging device 103 for detecting the object within the target water surface area, wherein the laser detection and ranging device 103 comprises a laser transmitter 105 for transmitting a laser beam towards the target water surface area, a laser detector 107 for detecting a reflected laser beam, the reflected laser beam forming a reflected version of the transmitted laser beam, and a processor 109 for detecting the object within the target water surface area upon the basis of the reflected laser beam.

[0070] The detection system 100 can be mounted on a marine seagoing vessel, e.g. a ship, or a marine stand-still platform, e.g. an oil production platform. The detection system 100 can further be installed at a marine harbor or marine port.

[0071] The radio detection and ranging device 101 can be based on transmitting an electromagnetic wave towards the object, and detecting an electromagnetic wave which has been reflected by the object. The radio detection and ranging device 101 can be a common radio detection and ranging device for marine object detection.

[0072] The laser detection and ranging device 103 can be based on transmitting a laser beam towards the object, and detecting a laser beam which has been reflected by the object.

[0073] The transmitted laser beam can be spatially and/or temporally coherent. The transmitted laser beam can be a Gaussian beam. The transmitted laser beam can be polarized, e.g. vertically polarized. The reflected laser beam can be spatially and/or temporally coherent. The reflected laser beam can be a Gaussian beam. The reflected laser beam can be polarized, e.g. vertically polarized.

[0074] The laser transmitter 105 can be a solid state laser, e.g. a neodymium-doped yttrium aluminum garnet (Nd:YAG) laser. The laser transmitter 105 can further be a dye laser or a gas laser. The laser transmitter 105 can comprise a non-linear optical element, e.g. for frequency doubling. The laser transmitter 105 can operate at an infrared frequency band, an optical frequency band, or an ultraviolet frequency band.

[0075] The laser detector 107 can be a semiconductor-based laser detector or a tube-based laser detector. The laser detector 107 can be configured to convert the detected laser beam into an electrical signal.

[0076] The processor 109 can be programmably arranged to detect the object within the target water surface area upon the basis of the reflected laser beam.

[0077] Fig. 2 shows a schematic diagram of a detection method 200 for detecting an object on a water surface according to an implementation form.

[0078] The detection method 200 comprises coarsely detecting 201 a target water surface area with the object by a radio detection and ranging device, and detecting 203 the object within the target water surface area by a laser detection and ranging device.

[0079] Detecting 203 the object within the target water surface area by the laser detection and ranging device comprises transmitting 205 a laser beam towards the target water surface area by a laser transmitter, detecting 207 a reflected laser beam by a laser detector, the reflected laser beam forming a reflected version of the transmitted laser beam, and detecting 209 the object within the target water surface area upon the basis of the reflected laser beam by a processor.

[0080] The detection method 200 can be performed by the detection system. Further features of the detection method 200 can directly result from the functionality of the detection system.

[0081] Fig. 3 shows two schematic diagrams 300A, 300B of a detection scenario for detecting an object 301 on a water surface 303 according to an implementation form.

[0082] The two diagrams 300A, 300B comprise the object 301, the water surface 303, a target water surface area 305, a marine seagoing vessel 307, a transmitted laser beam 309, and a reflected laser beam 311. The detection system 100 is mounted on the marine seagoing vessel 307. The transmitted laser beam 309 is directed from the laser detection and ranging device of the detection system 100 towards the object 301. The reflected laser beam 311 is directed from the object 301 towards the laser detection and ranging device of the detection system 100. The diagram 300A illustrates the detection scenario from a side view. The diagram 300B illustrates the detection scenario from a top view.

[0083] The object 301 can be a floating obstacle. The object 301 can further be a marine seagoing vessel, e.g. a ship, or a marine stand-still platform, e.g. an oil production platform.

[0084] The water surface 303 can be defined as the surface layer between water and air.

[0085] The target water surface area 305 can coarsely indicate a position of the object 301. The target water surface area 305 can be defined by an azimuth and/or an elevation with respect to the detection system 100. The target water surface area 305 can be defined by an azimuth-range cell on the water surface 303.

[0086] The marine seagoing vessel 307 can e.g. be a ship.

[0087] The transmitted laser beam 309 can be spatially and/or temporally coherent. The transmitted laser beam 309 can be a Gaussian beam. The transmitted laser beam 309 can be polarized, e.g. vertically polarized.

[0088] The reflected laser beam 311 can be spatially and/or temporally coherent. The reflected

laser beam 311 can be a Gaussian beam. The reflected laser beam 311 can be polarized, e.g. vertically polarized.

[0089] The object 301 can be detected on the water surface 303 according to the detection method. The detection method comprises coarsely detecting the target water surface area 305 with the object 301 by a radio detection and ranging device, and detecting the object 301 within the target water surface area 305 by a laser detection and ranging device.

[0090] Detecting the object 301 within the target water surface area 305 by the laser detection and ranging device comprises transmitting the laser beam 309 towards the target water surface area 305 by a laser transmitter, detecting the reflected laser beam 311 by a laser detector, the reflected laser beam 311 forming a reflected version of the transmitted laser beam 309, and detecting the object 301 within the target water surface area 305 upon the basis of the reflected laser beam 311 by a processor.

[0091] The laser detection and ranging device of the detection system 100 can be configured to scan the target water surface area 305 along a horizontal plane for detecting an azimuth of the object 301 within the target water surface area 305, or a vertical plane for detecting an elevation of the object 301 within the target water surface area 305.

[0092] Fig. 4 shows a schematic diagram of subsystems of a detection system 100 for detecting an object on a water surface according to an implementation form. The detection system 100 can be used to provide ocean surface layer observations.

[0093] The detection system 100 comprises a sensor unit 401, a sensor unit 403, a data processor unit 405, a display unit 407, a system console unit 409, a radar unit 411, a radar unit 413, a gyro unit 415, a GPS unit 417, an AIS unit 419, and a compass unit 421. The detection system 100 is operated by a system operator 423 and is configured by a system engineer 425.

[0094] The detection system 100 comprises four subsystems: The sensor units 401, 403 as optical instrumentation that enables observations with high resolution at or under the sea surface, the data processor unit 405 as a data processor that processes data from the sensor units and combines the data with data from existing sensors such as radar, the display unit 407 as an operator display that can present the information from the optical instrument and the data processor in an operator-friendly way, and the system console unit 409 as a computer used to configure the detection system.

[0095] The figure gives a schematic overview of the relationship between the subsystems. The subsystems can be connected to ship sensor systems, such as the radar unit 411, the radar unit 413, the gyro unit 415, the GPS unit 417, the AIS unit 419, and the compass unit 421. The data processor unit 405 is connected to the ship sensors as a passive listener. The system console unit 409 and the display unit 407 can use the existing ship communication network to connect to the data processor unit 405.

[0096] The number of sensor units, display units, system console units and radar units can vary. The display unit can use an existing display sharing system on the bridge, so the system can be visible from several consoles on the bridge.

[0097] In an implementation form, only one sensor unit is used, and the data processor unit uses only a single radar unit.

[0098] Fig. 5 shows a schematic diagram of a sensor unit 401, 403 of a detection system for detecting an object on a water surface according to an implementation form.

[0099] The sensor unit 401, 403 comprises a laser unit 501, an auxiliary sensor unit 503, a mechanical scan unit 505, a real-time motion reference unit 507, a real-time control unit 509, a power supply unit 511, and an A/D conversion unit 513.

[0100] The sensor unit 401, 403 comprises a set of sensors that measure the environment of the ship. The following sensors can e.g. be used: a blue-green laser, and/or an optical camera. This instrument can provide the capability to observe objects at or under the sea surface at a resolution better than radar.

[0101] In addition, the sensor unit 401, 403 can have a motion reference unit (MRU) that measures vibrations, attitude and accelerations. The vibration measurements can be used to correct the reported angles at which measurements were taken, and attitude and acceleration are reported to the data processor unit which can use this information to convert sensor unit measurements to a Cartesian Ship-Centered Frame to fuse the sensor unit data with the data from other instruments.

[0102] Fig. 6 shows a schematic diagram of a data processor unit 405 of a detection system for detecting an object on a water surface according to an implementation form. The diagram illustrates the interfaces of the data processor unit 405.

[0103] The data processor unit 405 comprises a data processor core unit 601, an Ethernet network card unit 603, and a serial interface unit 605.

[0104] The Ethernet network card unit 603 is connected to a Fiber / Ethernet switch unit 607. The Fiber / Ethernet switch unit 607 is connected to a sensor unit 401 via a data, monitoring and control signal line 613. The Fiber / Ethernet switch unit 607 is further connected to a sensor unit 403 via a data, monitoring and control signal line 615.

[0105] The Ethernet network card unit 603 is further connected to a radar unit 411 via an observation signal line 617, and to a radar unit 413 via an observation signal line 619.

[0106] The Ethernet network card unit 603 is further connected to a bridge switch unit 609. The bridge switch unit 609 is connected to a display unit 407 and a system console unit 409.

[0107] The serial interface unit 605 is connected to a ship sensor unit 611.

[0108] The data processor unit 405 processes the data of the sensor units 401, 403 and the data of the ship sensors. The data processor unit 405 comprises the following hardware units: a core system where the processing related to the main functionality takes place, an Ethernet switch with ports for fiber optic cables, a radar slave junction box to create a passive connection to the radar and the other ship sensors, a radar digitizer, and a network serial interface to connect to the ship sensors.

[0109] The data processor unit 405 can work autonomously, and can be configured and monitored via a system console unit 409. The data processor unit 405 performs the following processing: read measurements by the ladar and visual band camera of each sensor unit 401, 403 and convert these to a point cloud with position relative to the ship, read measurements by the onboard radar units 411, 413, e.g. a top mast X-band radar and convert these to a point cloud with position relative to the ship, convert measurements of sensor units 401, 403 and ship's radar units 411, 413 to the same reference, perform clustering and tracking to distinguish objects from noise, perform additional analysis and characterization, if possible, on detected objects, and report results to the display unit 407 for display to the end user.

[0110] Fig. 7 shows a schematic diagram of a display unit 407 of a detection system for detecting an object on a water surface according to an implementation form.

[0111] The display unit 407 comprises a visualization unit 701, and an interaction unit 703.

[0112] The visualization unit 701 and the interaction unit 703 are connected to a data processor unit 405. The visualization unit 701 and the interaction unit 703 are further connected to a keyboard-video-mouse switch unit 705.

[0113] The keyboard-video-mouse switch unit 705 is connected to a display unit 707 and a mouse unit 709. The display unit 707 and the mouse unit 709 are operated by a system operator 423.

[0114] The display unit 407 can be the interface between the system and the operator, which can be a captain, a first officer, a pilot or anybody who is interested in the information made available by the system. The bridge can be equipped with a screen sharing system, which comprises several computers and several displays, connected via the keyboard-video-mouse (KVM) switch 705.

[0115] Each of the displays 707 can e.g. select one of four computers to connect with. The display unit 407 can be a computer that is connected to the system so that the output of the system can be viewed on several screens. Additionally, a separate computer, e.g. a laptop, can be used. Integration with an existing bridge system such as a conning station or an ECDIS can be realized.

[0116] One or more displays, with optional mouse input, can be connected to the display unit 407 via the keyboard-video-mouse (KVM) switch unit 705.

[0117] Fig. 8 shows a schematic diagram of a system console unit 409 of a detection system for detecting an object on a water surface according to an implementation form.

[0118] The system console unit 409 comprises a keyboard-mouse-touch unit 801, a command generator unit 803, a network card unit 805, a display control unit 807, and a display unit 809.

[0119] The network card unit 805 is connected to a sensor unit 401, a sensor unit 403, and a data processor unit 405. The keyboard-mouse-touch unit 801 and the display unit 809 are operated by a system engineer 425.

[0120] The system console unit 409 can be used to control the sensor units 401, 403 and the data processor unit 405. It provides a technical view of the inner functionality of the sensor units 401, 403 and it can be used to change modes and settings of each. This functionality can be integrated with the operator display unit 407.

[0121] The system console unit 409 can be used to incidentally configure the system. Once this is done, operating the instrument can happen via the display unit 407. The target user of the system console unit 409 can be an engineer, not a navigation officer or captain.

[0122] The system console unit 409 can be used to control both the data processor unit 405 as well as the sensor units 401, 403. The communication to the sensor units 401, 403 can be routed via the data processor unit 405.

[0123] Fig. 9 shows a schematic diagram of interfaces 903, 905, 907, 909, 911, 913, 915, 917 of a detection system for detecting an object on a water surface according to an implementation form. The diagram comprises a sensor unit 401, 403, a data processor unit 405, a display unit 407, a system console unit 409, a ship sensor unit 611, and a ship structure 901.

[0124] The interface 903 connects the sensor unit 401, 403 to the ship structure 901. This interface illustrates the way that the sensor unit 401, 403 is mounted on the ship. The interface 903 comprises electrical power cables, e.g. 230 VAC, 60 Hz, and a network fiber optic cable to the network. The fiber optic cable can be of multimode type, e.g. core/cladding diameter of 62.5/125µm, terminated with connector type SC on the sensor unit 401, 403 end and LC on the data processor unit 405 end.

[0125] The interface 905 connects the sensor unit 401, 403 to the data processor unit 405. The sensor units 401, 403 can connect to the data processor unit 405 via a LAN network. The sensor units 401, 403 can provide data via the LAN using a specific protocol for the data and commands. Time synchronization can be done using the Network Time Protocol (NTP). The data rate of the link between sensor unit 401, 403 and the data processor unit 405 can be 1

Gbps. The LAN can be implemented as a fiber-optic network and separated from the existing ship network. The sensor unit 401, 403 provides the following information for each shot: power-delay profiles in CPICF, a pointing direction of the laser at the time of firing, a time of measurement in microseconds since some epoch, and at regular intervals a current best estimate of parameters describing yaw/pitch/roll and surge/sway/heave.

[0126] The interface 907 connects the data processor unit 405 to the ship sensor unit 611. Two types of data of radar signals can be available: the navigational messages and the analog video signal. The navigational messages of the radar and other ship sensors, e.g. time information, position, and heading, can be made available by a navigation device using a network serial interface. This device can provide one or more serial lines, e.g. at a maximum data rate of 38.4 kbps each, that contain NMEA-0183 messages. The analog video signal can be provided via a navigation device slave junction box. A scan streamer can read the radar video and data signals, and converts these into digital messages made available to the data processor unit 405 via an Ethernet port. There can e.g. be three radar systems of which the system can receive information: a bow radar, a mast radar, and/or a stern radar. However, only one radar can be used. This radar can have adequate properties regarding field of view, resolution, and height. The radar can be a top X-band radar e.g. with 1cm resolution and 360° view.

[0127] The interface 909 connects the data processor unit 405 to the ship structure 901. The data processor unit 405 can be a server system. The form factor can vary. The data processor unit 405 can e.g. be a wall-mountable system. Furthermore, an Ethernet switch can be mounted. A fiber optic cable from the sensor unit 401, 403 can be available, e.g. using connector type LC. Furthermore, electrical power, e.g. 24 VDC or 100 to 240 VAC, can be available. Also, a network cable for the network connection on which the display unit 407 and the system console unit 409 are connected, can be available. Also, the signals from the navigation device slave junction box for the radar video signal and the serial lines from the navigation device network serial interface can be available.

[0128] The interface 911 connects the data processor unit 405 to the display unit 407. The data processor unit 405 can connect to the operator display unit 407 via a network cable. The protocol between the data processor unit 405 and the display unit 407 can be a specific protocol with open NMEA-0183 or NMEA-2000 sentences. In addition, there can be HTTP traffic for instrument control.

[0129] The interface 913 connects the display unit 407 to the ship structure 901. The operator display unit 407 can be a laptop. A network cable can be used to facilitate a connection from the data processor unit 405 to the operator display unit 407.

[0130] The interface 915 connects the system console unit 409 to the data processor unit 405. There are different possible realizations for the operator console: the operator console can e.g. be a separate laptop, or the operator console can be a special mode of the operator display unit 407, where a full computer keyboard can be available for the user. The operator console

does not need to be in use all the operational time. A surface for the computer keyboard can be available in range of the keyboard connector, or can be available for a laptop with network connection. Therefore, the data processor unit 405 can be reached. The system console unit 409 can be integrated with the display unit 407. The display unit 407 can also comprise a web browser that can be used to perform maintenance tasks and diagnostics.

[0131] The interface 917 connects the system console unit 409 to the sensor unit 401, 403. The system console unit 409 or operator console can be used to control the sensor units 401, 403 and the data processor unit 405. This can involve sending commands to the sensor units 401, 403 to change modes or settings and retrieving housekeeping data. The protocol between the system console unit 409 or operator console and the sensor units 401, 403 can be based on a specific protocol. The communication between the system console unit 409 or operator console and the sensor units 401, 403 can be routed via the data processor unit 405, because it can be the data processor unit 405 to which the sensor units 401, 403 are connected, e.g. using a fiber-optic network.

[0132] The following coordinate frames can be used: an uncompensated polar instrument-centered frame (UPICF) wherein coordinates are round trip time and uncorrected laser pointing angles, e.g. azimuth and elevation, with respect to the fixed instrument, a compensated polar instrument-centered frame (CPICF) wherein coordinates are range and laser pointing angles, e.g. azimuth and elevation, with respect to the fixed instrument and corrected for vibrations measured by the sensor unit 401, 403, a Cartesian ship-centered frame (CSCF) wherein coordinates are Cartesian with the origin in the center of the ship, and wherein X can be forward, Y can be in starboard direction and Z can be positive downward, an earth-centered inertial frame (ECIF) wherein coordinates are Cartesian with the origin at the center of the earth, and/or a latitude longitude altitude (LLA) frame wherein coordinates are latitude and longitude in fractional degrees, e.g. according to WGS84, and altitude is with respect to the local geoid.

[0133] A conversion between coordinate frames can be performed. In order to process the information from the sensor unit 401, 403, which can be provided as a power-delay profile measured in a particular direction with respect to the sensor unit 401, 403, it can be converted to the Cartesian ship-centered frame (CSCF), so that it can be compared with radar measurements which can also be converted to this frame.

[0134] The conversion from UPICF to CPICF can take place on the sensor unit 401, 403. The following steps can be involved: convert from mirror angle to angle with respect to the sensor unit 401, 403 wherein instrument geometrical parameters can be input, correct for vibrations wherein measurements from a motion reference unit (MRU) can be input, convert round trip time into range with respect to a reference point in the sensor unit 401, 403 wherein instrument calibration parameters can be input. The sensor unit measurements can be sent to the data processor unit 405 in CPICF.

[0135] A conversion from CPICF to CSCF can be performed. The data processor unit 405 can

receive sensor unit and radar measurements in CPICF, with the origin at some reference point in each of the instruments. These measurements can first be converted to a common Cartesian ship-centered frame (CSCF) so that the results can be combined. This can be done using the following steps: shift the reference point from the sensor unit / radar center to the ship center wherein instrument locations with respect to the ship center can be input, convert attitude relative to the instrument to attitude with respect to the ship horizontal wherein instrument orientation can be input, convert attitude with respect to the ship to attitude with respect to the local horizon wherein roll, pitch and yaw angles of the ship from an MRU and/or a ship gyro can be input, convert from polar coordinates azimuth, elevation and range to Cartesian coordinates with the ship as origin, e.g. with X is forward, Y is starboard direction, Z is downward, and shift to the average ship center by correcting for heave, surge and sway wherein heave, surge and sway movement of the ship from an MRU and/or ship GPS can be input.

[0136] A conversion from CSCF to ECI can be performed. To convert from CSCF to ECI, the ship position obtained from a GPS can be used.

[0137] A conversion from ECI to LLA can be performed. Some NMEA sentences can present locations in latitude/longitude/altitude (LLA) coordinates. Using e.g. a WGS84 coordinate system definition, the LLA coordinates can be converted to ECI and the other way around.

[0138] Fig. ²10 shows a schematic diagram of sensor components of a sensor unit 401, 403 according to an implementation form.

[0139] The sensor unit 401, 403 comprises a ladar unit 1001, a visual mirror 1003, a visual window 1005, an IR / BIL unit 1007, an IR mirror 1009, an IR window 1011, a mirror drive unit 1013, a cam unit 1015, a cam unit 1017, and a control, IMU and power unit 1019.

[0140] The sensor unit 401, 403 can comprise the following set of sensors in the sensor pod.

[0141] Firstly, a CCD visual band imager can be included in the sensor unit 401, 403. This can be placed in a circular structure to provide omnidirectional visibility from the sensor.

[0142] Secondly, a ladar unit can be included in the sensor unit 401, 403. The ladar unit can comprise a laser transmitter and beam shaping optics, receiving optics and multiple detection channels. Separate systems can provide high sensitivity, long range window and matrix detection of the scene. A mirror or prism based precision pointing system can control the beam.

[0143] Thirdly, an infrared active and passive imager can be included in the sensor unit 401, 403. This unit can provide high magnification, long range target detection and imaging. The unit can use an active near IR waveform to provide long range all-weather classification and a medium wave IR waveform for long range passive detection. This part of the system can be seen as an adjunct sensor to the ladar.

[0144] The unit can also comprise a processing and interface unit that can provide local system control and high throughput local sensor processing. An onboard motion reference unit (IMU) can provide location and attitude data. The motion sensor data can be used to provide correction data or to dynamically stabilize the pointing of the sensor.

[0145] The mechanical design of the system can be implemented to provide a robust and nonintrusive design, with the ability to withstand any environmental condition.

[0146] The mechanical system and the optical apertures comprise a self-supporting vertical cylinder with two optical apertures, one cylindrical aperture for the visible band, e.g. 400-800nm, and one separate cylindrical aperture for the infrared band, e.g. 1200nm-6000nm. The optical apertures can have the following specifications: the external surface can be water and contamination resistant having an optical quality surface, the internal surface can be non-reflective coated having an optical quality surface, and the mechanical strength can resist environments and bird strikes.

[0147] The ladar system can operate in the blue-green part of the spectrum and can provide data for surface and subsurface imaging. Key specifications can be: a wavelength in the region 480nm - 600nm, a solid state laser technology, a pulse energy of 1 - 10mJ per pulse, a pulse length of 3ns nominal, controllable 1ns - 100ns, and a pulse repetition frequency of nominally 10kHz, in the region 5kHz - 50kHz. A first detector can be characterized by a high sensitivity time series recording, a sampling speed of min. 300MHz, and a dynamic range of min. 90dB. A second detector can comprise a very high sensitivity photomultiplier and can provide a single range cell. A third detector can comprise a monochrome high resolution imager. A fourth detector can optionally be hyper-spectral or a line array.

[0148] The visual band imager can provide a continuous coverage around the ship. Key specifications can be: a CMOS imager having a resolution of 1920 x 1080 or better, an orthonormal lens providing a horizontal coverage of 109 degrees, and a specific data output.

[0149] The infrared imager can be optional. Key specifications can be: a scanning area of 360 degrees azimuth, +20 degrees to -45 degrees elevation, two simultaneous modes with active 1500nm and passive 5000nm infrared, at 1500nm with a sector of observation of 1.5 x 1.5 degrees, at 5000nm with a sector of observation of 15 x 15 degrees, and a specific data output.

[0150] The scanning mirror system can provide a capability for continuous scanning and target tracking. Key specifications can be: a mirror dimension to support 15cm beam envelope, scan modes comprising step azimuth with swing vertical, step vertical with swing azimuth, and slew to position, a specific scan velocity, a scan accuracy of e.g. 1mrad, and IMU reference modes comprising a free scan with IMU tagging, and an IMU slewed scan.

[0151] The navigation and inertial reference can measure the movement of the platform in

order to compensate for the ship movement. It can cover the following directions: pitch, roll, and heave.

[0152] The heading can also be relevant in the system, but the change of heading can be considered to be so slow that the ship compass can be used. Since the sensor update rate is min. 1 Sec., the most critical parameter can be considered to be the dynamic pitch, roll and heave measurement.

[0153] Key specifications can be: a heave range of $\pm 2\text{M}$, a heave accuracy of $\pm 0.2\text{M}$ with 1sec. repeatability, a pitch range of $\pm 5^\circ$, a pitch accuracy of $\pm 0.025^\circ$ with 1sec. repeatability, a pitch angular rate of $\pm 1^\circ/\text{sec}$, a roll range of $\pm 5^\circ$, a roll accuracy of $\pm 0.025^\circ$ with 1sec. repeatability, and a roll angular rate of $\pm 0.5^\circ/\text{sec}$.

[0154] Fig. 11 shows a schematic diagram of processing components of a sensor unit according to an implementation form.

[0155] The processing components comprise an FPGA unit 1101, a RAM unit 1103, an A/D conversion unit 1105, an A/D conversion unit 1107, a CPU unit 1109, a RAM unit 1111, a FLASH unit 1113, an Ethernet unit 1115, an IMU unit 1117, a scan controller unit 1119, a step motor drive unit 1121, a step motor drive unit 1123, a piezo drive unit 1125, and a piezo drive unit 1127.

[0156] The ladar processing system can handle sensor near processing such as ping averaging, digital filtering, and/or vibration correction. In addition, the processing system can control the scan motion of the mirror system.

[0157] Fig. 12 shows a schematic diagram of a cross-section of a laser beam according to an implementation form.

[0158] The diagram comprises a cross-section of an ideal circular laser beam 1201, a cross-section of a divergent circular laser beam 1203 at range, and a cross-section of an asymmetrically divergent oval laser beam 1205 at range.

[0159] The laser generation unit can be based on a Q switched Nd:YAG laser emitting 532nm wavelength light. This approximate wavelength is desirable as light in this region of the spectrum, i.e. blue-green in color, can pass through water with little attenuation, allowing an illumination of objects below the water surface. The wavelength of the system can also be altered from 532nm to 488nm. This small shift towards blue light can allow the system to more easily penetrate water.

[0160] The sensor unit optics can provide a balance of system output power, detector performance, and eye safety. The method by which both eye safety and detection performance are obtained is through the use of large beam spreading and light collecting optics, respectively. To increase the amount of light power which can be emitted while remaining eye

safe, a collimator can be used to spread the beam and thus lower the energy density and therefore the risk of eye damage.

[0161] Similarly, detection performance can be improved by gathering a larger surface area of returned light energy, and focusing this onto the detector surface. Also, a dividing baffle can be employed that can physically isolate transmit and receive optical paths to maximize detector performance. While the use of a coded detection waveform can also reduce a crosstalk hazard, a careful optical path design can be advantageous to the system performance.

[0162] While common laser systems can be calibrated by use of a visible light camera in the optical path of the laser, and since the laser in the sensor unit can be capable of low power continuous wave emission, the calibration can be carried out by observing the beam intersect point remotely, allowing an elimination of the weight of a prism and a camera from a mobile portion of the optics assembly.

[0163] While it can be possible to increase both the output beam diameter and input detector aperture, both of these parameters can be based on larger optical assemblies, which in turn limit the speed with which the optics may be scanned. The sensor unit can have fixed output optics, or can be designed to scan up to 1000 spatial points per second.

[0164] While the use of a collimated beam at this power level with a 50mm divergence can remain below the maximum permissible exposure limits (MPEs), e.g. specified in IEC 60825-1 ed. 2.0, it can be desirable to also provide a provision for accidental viewing of the beam with aiding optics such as binoculars. To this end, the beam can be imparted with an asymmetric divergence. This can both improve the eye safety of the system while also providing a nearly circular beam footprint when this shape is projected onto the water surface at range.

[0165] The sensor unit can e.g. emit 130mJ of energy in a 15ns pulse over a surface area of 3.1×10^{-5} square meters. The sensor unit can also spread its energy over a much larger surface area as well as a much longer duration. By emitting e.g. 200mW of 50% duty cycle light over 1ms on a surface area of 2.0×10^{-3} square meters, the system can have a short term energy density, i.e. energy per unit surface area, of 2.8×10^8 lower over 15ns, while also imparting 77% of the energy of the sensor unit system over a 1ms period. Due to a pulse repetition rate (PRF) limit of e.g. 30 Hz, it can be advantageous to employ very high power individual pulses, while a modulated diode of the sensor unit can permit to use many lower power and much less hazardous pulses, while also performing more measurements per second.

[0166] The sensor unit can use a time gated ranging concept to detect targets at differing ranges. The sensor unit can also use advanced signal processing to allow a simultaneous measurement of multiple range hypotheses, as well as to allow operation at a lower power level by making multiple less intense illuminations of the same target.

[0167] A code modulation and a ranging peak detection scheme can be applied. For this purpose, sampling and triggering components of the system can be used. The triggering

process can be performed by a modulator, a laser, a photodiode, and a digitizer combination.

[0168] A pseudo-random sequence of ± 1 can be used to modulate the laser. A high autocorrelation suppression characteristic of the modulating or spreading waveform can be desirable. An improvement in SNR can indicate a high achievable cross-correlation suppression of the system. A noise floor raised by the signal itself can indicate an autocorrelation suppression. A correlation peak can show multiple environmental reflections. An artificially increased level of noise floor can be due to a high SNR signal with finite cross-correlation suppression.

[0169] The detection of the laser return waveform can be accomplished by an avalanche photodiode (APD), specially designed to be sensitive to the blue-green laser light used by the transmitting laser, as well as to have a wide bandwidth, e.g. 530 MHz nominal. The wide sensor bandwidth can allow the high bandwidth diode laser to produce a sharp correlation or detection peak, which in turn can allow for a precision of up to 30cm in the determination of range to target.

[0170] To augment the situational awareness provided by the sensor unit, the system can be fitted with multiple visible band cameras. These can serve the dual purpose of providing a potential for a human readable overlay to detected objects, as well as potentially augmenting detection of threats during daylight conditions. An infrared system, such as a burst illumination system, can further be employed for surface target detection.

[0171] The laser beam can be modulated using a general spread spectrum modulation for laser range finding. The modulation can be characterized by the following general characteristics. The laser beam modulation can be based on an advanced time coded modulation scheme for optimum range resolution and target detection clutter suppression. The modulation scheme can achieve a maximum range performance by having a very high duty cycle and a very high processing gain. The modulation scheme can be structured to give a maximum suppression of external disturbance, e.g. light disturbance. The modulation can also be structured to cancel any close up effects.

[0172] The laser beam can be implemented as follows. The laser beam can be stabilized to operate with a very narrow bandwidth. The laser beam can be modulated with a very high rate, e.g. 25MHz up to more than 200MHz. The modulation can be an on off modulation, optionally an amplitude shift modulation can be used for enhanced mean power. A minimum side-lobe spreading code can be used. The spreading code can be long enough to provide a unique code for the total range swath, e.g. more than 10000 chips. The spreading code can be superimposed a low rate, e.g. typically 10kHz, square wave modulation wherein a duty cycle can be less than 50%, e.g. typically 40%. This modulation can be matched filtered in the receiver with a resulting range sensitivity curve adjusted to provide a desired range sensitivity profile.

[0173] Additionally, the following features can be used. A highly concentrated laser beam to

give positive SNR ratio to allow for efficient integration can be utilized. A very high precision stabilization can be utilized to allow for dual mode ranging through range and elevation measurement. Very asymmetrical laser beams can be utilized for optimum target detection at a slant angle. Specific angle and/or scan patterns for target detection, e.g. a carpet mode, a range only mode, a sector mode, etc. can be used.

[0174] Fig. 13 shows a schematic diagram of a radar coverage area 1323 of a sensor unit according to an implementation form.

[0175] The diagram further comprises a horizon line 1301, an elevation line 1303, an elevation line 1305, an elevation line 1307, an elevation line 1309, an elevation line 1311, a front direction line 1313, an aft direction line 1315, a further aft direction line 1317, a starboard direction line 1319, and a port direction line 1321.

[0176] The elevation line 1303 can relate to an elevation of -0.9 degrees and/or a range of 2km. The elevation line 1305 can relate to an elevation of -1.7 degrees and/or a range of 1km. The elevation line 1307 can relate to an elevation of -3.4 degrees and/or a range of 500m. The elevation line 1309 can relate to an elevation of -16 degrees and/or a range of 100m. The elevation line 1311 can relate to an elevation of -45 degrees and/or a range of 30m.

[0177] The front direction line 1313, the aft direction line 1315, the further aft direction line 1317, the starboard direction line 1319, and the port direction line 1321 can indicate an azimuth. The interface to the onboard navigation radar or radars can provide a general situation awareness and detection of surface targets. The navigation radar can be able to detect targets in a 360 degrees sector, and with a range coverage from about 300m to a limit depending on the radar height, target size and environmental condition, e.g. to a 20-30km range.

[0178] An extractor can be part of a central data fusion system, and data from this extractor can be used to provide a data general situation awareness picture, and to cue the sensor unit for target confirmation and specific target investigation.

[0179] Fig. 14 shows a schematic diagram of a ladar coverage area 1401, 1403 of a sensor unit according to an implementation form. The ladar coverage area 1401 can relate to the front. The ladar coverage area 1403 can relate to the aft.

[0180] The diagram further comprises a horizon line 1301, an elevation line 1303, an elevation line 1305, an elevation line 1307, an elevation line 1309, an elevation line 1311, a front direction line 1313, an aft direction line 1315, a further aft direction line 1317, a starboard direction line 1319, and a port direction line 1321.

[0181] The elevation line 1303 can relate to an elevation of -0.9 degrees and/or a range of 2km. The elevation line 1305 can relate to an elevation of -1.7 degrees and/or a range of 1km. The elevation line 1307 can relate to an elevation of -3.4 degrees and/or a range of 500m. The

elevation line 1309 can relate to an elevation of -16 degrees and/or a range of 100m. The elevation line 1311 can relate to an elevation of -45 degrees and/or a range of 30m.

[0182] The front direction line 1313, the aft direction line 1315, the further aft direction line 1317, the starboard direction line 1319, and the port direction line 1321 can indicate an azimuth.

[0183] The ladar system can have the capability to scan a predetermined sector or predetermined sectors for detecting surface and/or subsurface targets. During normal forward moving operation of the ship or vessel, a forward looking mode can be utilized to scan for targets in the forward path of the ship.

[0184] The forward looking mode can scan within a narrow sector, e.g. 20 degrees, from a short range looking down in front of the ship to a maximum range determined by the environmental conditions and settings of the operator. Under optimal conditions and when looking for very shallow targets, a forward looking range of up to 2km can be used.

[0185] When two sensor units are used on the ship, a separate front and aft looking sector may be employed or activated.

[0186] Fig. 15 shows a schematic diagram of a ladar coverage area 1501, 1503, 1505 of a sensor unit according to an implementation form. The ladar coverage area 1501, the ladar coverage area 1503, and the ladar coverage area 1505 can realize an omnidirectional coverage around a ship.

[0187] The diagram further comprises a horizon line 1301, an elevation line 1303, an elevation line 1305, an elevation line 1307, an elevation line 1309, an elevation line 1311, a front direction line 1313, an aft direction line 1315, a further aft direction line 1317, a starboard direction line 1319, and a port direction line 1321.

[0188] The elevation line 1303 can relate to an elevation of -0.9 degrees and/or a range of 2km. The elevation line 1305 can relate to an elevation of -1.7 degrees and/or a range of 1km. The elevation line 1307 can relate to an elevation of -3.4 degrees and/or a range of 500m. The elevation line 1309 can relate to an elevation of -16 degrees and/or a range of 100m. The elevation line 1311 can relate to an elevation of -45 degrees and/or a range of 30m.

[0189] The front direction line 1313, the aft direction line 1315, the further aft direction line 1317, the starboard direction line 1319, and the port direction line 1321 can indicate an azimuth.

[0190] In port or when having emphasis on ship security, a round-scanning mode of the system can be activated. This can scan the active laser beam in a perimeter mode around the vessel. The range at which this scan can be performed can be determined by a target depth detection setting. For deepest laser penetration, the perimeter can be set as close to the

vessel as possible. This can also be determined by an installation location.

[0191] Fig. 16 shows a schematic diagram of a visual band coverage area 1601, 1603, 1605, 1607, 1609 of a sensor unit according to an implementation form. The visual band coverage area 1601, the visual band coverage area 1603, the visual band coverage area 1605, the visual band coverage area 1607, and the visual band coverage area 1609 can be realized by sector cameras.

[0192] The diagram further comprises a horizon line 1301, an elevation line 1303, an elevation line 1305, an elevation line 1307, an elevation line 1309, an elevation line 1311, a front direction line 1313, an aft direction line 1315, a further aft direction line 1317, a starboard direction line 1319, and a port direction line 1321.

[0193] The elevation line 1303 can relate to an elevation of -0.9 degrees and/or a range of 2km. The elevation line 1305 can relate to an elevation of -1.7 degrees and/or a range of 1km. The elevation line 1307 can relate to an elevation of -3.4 degrees and/or a range of 500m. The elevation line 1309 can relate to an elevation of -16 degrees and/or a range of 100m. The elevation line 1311 can relate to an elevation of -45 degrees and/or a range of 30m.

[0194] The front direction line 1313, the aft direction line 1315, the further aft direction line 1317, the starboard direction line 1319, and the port direction line 1321 can indicate an azimuth.

[0195] A complete omnidirectional visual depiction of the ship's or vessel's surroundings can be provided from a set of sector antennas. A stack of e.g. 4 cameras with distortion free optics can be used. They can provide a continuous coverage from short range determined by visibility from the installation locations to the horizon and also including a view above the horizon for reference.

[0196] The cameras can provide very low light visibility, and can also have enhanced near-infrared sensitivity to image targets in near no-light situations.

[0197] Fig. 17 shows a schematic diagram of an infrared coverage area 1701, 1703 of a sensor unit according to an implementation form. The infrared coverage area 1701 and the infrared coverage area 1703 can illustrate a scan area and/or an engagement element.

[0198] The diagram further comprises a horizon line 1301, an elevation line 1303, an elevation line 1305, an elevation line 1307, an elevation line 1309, an elevation line 1311, a front direction line 1313, an aft direction line 1315, a further aft direction line 1317, a starboard direction line 1319, and a port direction line 1321.

[0199] The elevation line 1303 can relate to an elevation of -0.9 degrees and/or a range of 2km. The elevation line 1305 can relate to an elevation of -1.7 degrees and/or a range of 1km. The elevation line 1307 can relate to an elevation of -3.4 degrees and/or a range of 500m. The

elevation line 1309 can relate to an elevation of -16 degrees and/or a range of 100m. The elevation line 1311 can relate to an elevation of -45 degrees and/or a range of 30m.

[0200] The front direction line 1313, the aft direction line 1315, the further aft direction line 1317, the starboard direction line 1319, and the port direction line 1321 can indicate an azimuth.

[0201] A combined active/passive infrared imager can have a large magnification imaging sector that can be scanned and positioned over a total azimuth and elevation scan area. This sensor can be employed or activated based on requests from an operator or automatically from the system to confirm detection from other sensors.

[0202] This sensor can also be able to provide very long range, e.g. larger than 2km, up to 15km, classification of targets by providing detailed images and live video for manual inspection or automatic classification. The sensor can also provide a capability to detect submerged targets.

[0203] Fig. 18 shows a schematic diagram of a laser beam refraction for detecting an object 301 under a water surface 303 according to an implementation form. The transmitted laser beam 309 and the reflected laser beam 311 can be refracted on the water surface 303.

[0204] At oblique angles, the laser beam 309, 311 can enter the water with a steeper angle than the incidence angle according to Snell's law of refraction.

[0205] It can be shown that $n_W \cdot \sin(\theta_W) = n_{Air} \cdot \sin(\theta_{Air})$. Assuming $n_W = 1.33$, $n_{Air} = 1.008$, and a grazing incidence angle $\theta_{Air} = 90^\circ$, a critical angle $\theta_{Critical} = \theta_W = 49.3^\circ$ can be obtained.

[0206] This means that even at long ranges when viewed from a ship, a look down into the water is possible.

[0207] Fig. 19 shows a schematic diagram of a detection scheme for detecting an object 301 under a water surface 303 according to an implementation form.

[0208] The diagram further comprises a detection system 100 mounted on a marine seagoing vessel 307. The transmitted laser beam 309 and the reflected laser beam 311 are refracted on the water surface 303.

[0209] The object position is denoted as (x, y). The distance from the detection system 100 to the water surface 303 is denoted as R1. The distance from the water surface 303 to the object 301 is denoted as R2. The angle α is measured between the water surface 303 and the laser beam 309, 311.

[0210] By measuring $R = R1 + R2$ and α , absolute values for x and y can be obtained.

[0211] The following sea corollaries can be considered. Firstly, reflection and refraction amplitude can be polarization dependent. The VV, i.e. vertical-vertical, polarization can be desirable. Secondly, for a rough sea surface, the surface may not be flat with angles from horizontal up to 10 degrees. The sea surface can comprise gravity waves and/or capillary waves.

[0212] Fig. 20 shows a schematic diagram of a detection scheme for detecting an object 301 under a water surface 303 according to an implementation form.

[0213] The diagram further comprises a detection system 100 mounted on a marine seagoing vessel 307. The transmitted laser beam 309 and the reflected laser beam 311 are refracted on the water surface 303.

[0214] The laser beam can follow a path from the detection system 100 to the object 301 and the same path back.

[0215] The reflection calculations can be based on the following. The sensor can be mounted 30 meters above sea level. The distance to the object or target can be 1km. The laser beam angle of incidence to the water surface 303 at the object 301 or target can be $\arctan(30/1000) = 1.7^\circ$.

[0216] The reflection from the air/water interface and the transmission into water can be calculated by the expressions for Fresnel reflections. At a very low angle of incidence to the air/water interface, the reflection can be very high and the transmission into water can be very low.

[0217] The transmission into water can amount to 21.5% for the vertical polarization and 12.5% for the horizontal. Thus, if a maximization of the coupling of laser light into the water is desired, the laser can be vertically polarized. Then, 21.5% of the laser light can go into the water.

[0218] This light can hit an underwater part of the object 301 or target and can be reflected back. This reflected laser light can once more have to travel through the air/water interface. If it is assumed that the target is a perfect Lambertian reflector, the reflected laser light can be unpolarized. That means that it can be 50%-50% vertically and horizontally polarized.

[0219] The reflection loss, and thereby the transmission from water into the air can then be the average of the vertical and horizontal polarization. That is $T=17\%$. The total transmission into and out of the water can then be $21.5\% \times 17\% = 3.6\%$, e.g. for vertical polarized input laser light, similarly for horizontal input laser light $12.5\% \times 17\% = 2.1\%$. The reflection coefficient of the target can further reduce this.

[0220] It can be assumed that the object 301 or target can have the same surface color above and below the water line. Therefore the reflection coefficient from the above water and from

the below water can be the same. The below water fraction of the beam can be very much reduced because it can have to travel through the air/water interface twice.

[0221] An additional point can be the transmission losses in water. If it is assumed that the laser beam has 1meter in diameter, the lower part of the beam can have to travel 25meters through water before hitting the object 301 or target, and then 25meters back before hitting the water/air interface again. Values for the attenuation of laser light in water can e.g. be between 0,0001 and 0,01 cm^{-1} . If 0.001 cm^{-1} is assumed, the transmission can become 0.7% through 50meters. This illustrates that the upper part of the laser beam can be a major contributor to the reflection from the object 301 or target.

[0222] A further point can be that when 21.5% of the laser beam is coupled into the water, 78.5% can be reflected from the air/water interface. A part of this laser light can hit the above water part of the object 301 or target and can be reflected back towards the sensor. This can increase the contribution to the signal from the above water part of the object 301.

[0223] In these calculations, no waves are assumed. This can be an idealized situation. However, it can illustrate the point that the reflection from the above water part of the object 301 or target can be stronger than the reflections from the underwater part.

[0224] According to an implementation form, the invention relates to a sensor and sensor exploitation system that has a number of application areas related to the maritime environment. These can include vessel safety and security, offshore energy projects, coastal and river applications. A feature of the invention can relate to fully utilize the electromagnetic radiation in a narrow part of the visible range that e.g. permits the transmission of light through a significant body of water, e.g. 5-50m by means of an active imaging process.

[0225] This feature can further be enhanced by having a complement of adjunct sensors that can be tailored to the application, e.g. for ship security. An active ladar can be complemented with passive optical imagers for long range operation and visual characterization and dedicated radar extraction method for complementary object detection of targets on the surface. The invention can therefore include a dedicated data fusion process to provide 3D and time domain fusion of the signals and the appropriate interface and presentation tools.

[0226] The invention can relate to range gated active illumination optical target detection and imaging systems. This can imply that the invention relates to a system that utilizes active illumination in the form of coded laser emissions, e.g. in the form of a modulated solid state laser, and provides detection by having a very high speed data acquisition system and signal processing implementation to generate range profiles. Also mechanical scanning systems can be included to allow for area scanning and to generate 3D data. Furthermore precision position registration can be included via a satellite positioning and inertial measurement to allow for operation of the sensor in moving or oscillating environments. Additionally, the usage of passive optical sensors in the visible and infrared wavelength bands can be included, also the use of microwave radars and the use of data fusion schemes.

[0227] The invention can relate to security and safety for maritime vessels and platforms which can imply that the operators desire to have knowledge of objects in the seas around the vessel. This can include in particular objects that are not seen from the surface and which may be at a depth that could harm the vessel.

[0228] The invention can relate to the implementation of a sensor that can combine the capabilities of a radar to detect objects over a considerable distance and the capabilities of an active optical system using wavelengths that can penetrate the ocean surface to see deeply submerged targets. This combination of capabilities has not existed before, and the invention can present a solution for this challenge.

[0229] According to an implementation form, the invention relates to a system for detecting, tracking and classifying objects on or under the sea surface in the vicinity of maritime vessels and maritime platforms utilizing active laser illumination sensors in the conjunction with active radar sensors and passive electro-optical sensors for the purpose of providing situation awareness and the detection of specific objects of interest or threat to the vessel as defined by a dedicated central processing system, comprising the design and operation of the active laser illumination sensor using an electromagnetic wavelength that can significantly penetrate the water surface while illuminating the water surface at a very oblique angle thus obtaining near surface and submerged target detection at significant range using the inherent properties of the air/water interface to by refractive and scattering processes to accept the incoming near horizontal illumination and causing bundles of light at nearer vertical angles to propagate into the water column, and upon reflection from objects to be reradiated in the upwards direction and be again refracted and scattered into the near horizontal direction and being received and processed by a receiving apparatus and therewith also being combined with additional data from passive optical systems which give data from the same surface and in particular providing additional detection and classification of surface and near surface objects and also being combined with data from an active radar sensor that can give detection and verification of surface objects only although thereby enhancing the capabilities of the system in certain forms of inclement weather and at large ranges. The overall combined implementation can provide an area coverage limited by a sector up to a full 360 degree coverage and from a range adjacent to the vessel or platform and up to a distance range limited by the physical capabilities of the system and giving detection from the surface and to a depth limited by physical characteristics thus providing a full 3D coverage of the surrounding water surface and near surface area from the platform or the vessel.

[0230] According to an implementation form, the invention relates to a system where the active laser illumination system utilizes a coded waveform to allow for high average power and maximum detection range.

[0231] According to an implementation form, the invention relates to a system where the active laser illumination system utilizes a code which is concurrent and using code waveform technologies derived from communication and satellite positioning systems.

[0232] According to an implementation form, the invention relates to a system where the active laser illumination system utilizes a coded waveform with a high switching frequency to allow for range discrimination and filtering of unwanted echoes.

[0233] According to an implementation form, the invention relates to a system where the active laser illumination system utilizes an interrupted waveform superimposed on the coded waveform to allow filtering and cancellation of echoes close to the laser sensor unit.

[0234] According to an implementation form, the invention relates to a system where the active laser illumination is selected to be on or near an optimum wavelength of 488nm to give maximum penetration depth.

[0235] According to an implementation form, the invention relates to a system where maximum penetration is achieved to more than 5m and up to 30m providing physical conditions allow.

[0236] According to an implementation form, the invention relates to a system where the laser energy is concentrated into a narrow beam which extends to an angular coverage not significantly exceeding the dimensions of the typical objects being detected.

[0237] According to an implementation form, the invention relates to a system where the laser energy is concentrated into a narrow beam which is shaped in an oval form that allows for range-azimuth equal resolution cells when illuminating a sea patch at large distance.

[0238] According to an implementation form, the invention relates to a system wherein the optical receiver system comprises an optical receiving apparatus with a beam which is nearly as narrow as the transmitted beam to only register light from the active laser thereby suppressing ambient light.

[0239] According to an implementation form, the invention relates to a system wherein the receiving system has a very narrow band filter to suppress ambient light thus causing limitation to the detection range at wavelengths that can otherwise influence the detector.

[0240] According to an implementation form, the invention relates to a system wherein the receiving system utilizes concurrent pulse compression to provide range profiles in real time to the data processor.

[0241] According to an implementation form, the invention relates to a system wherein the combined receiving and transmitting optics perform a scanning operation in the vertical plane thereby mapping a specific sector in range and in depth.

[0242] According to an implementation form, the invention relates to a system wherein the combined receiving and transmitting optics perform a scanning operation in the vertical plane thereby mapping a specific sector in range and in depth.

[0243] According to an implementation form, the invention relates to a system wherein the combined receiving and transmitting optics perform a scanning operation in the horizontal plane thereby mapping a specific sector in azimuth and in depth.

[0244] According to an implementation form, the invention relates to a system wherein the combined receiving and transmitting optics perform a scanning operation in the horizontal plane as well as in the vertical plane thereby mapping a specific sector in azimuth, range and in depth thereby constituting a 3D system.

[0245] According to an implementation form, the invention relates to a system wherein the subsystem further comprises at least one out of a thermal sensor, a laser, an infrared sensor and a hyper-/multi-spectral sensor.

[0246] According to an implementation form, the invention relates to a system wherein the active laser system is supplemented with a coaxial to the laser system passive imaging visual band imager for additional data capture of surface and near surface objects.

[0247] According to an implementation form, the invention relates to a system wherein the active laser system is supplemented with a coaxial to the laser system passive near infrared, medium infrared or long wave infrared imager for additional data capture of surface and near surface objects under conditions of sunlight, dim light and very low light operation.

[0248] According to an implementation form, the invention relates to a system wherein the active laser system is supplemented with a set of cameras with panoramic view for additional data capture of surface and near surface objects under conditions of sunlight, dim light and very low light operation.

[0249] According to an implementation form, the laser detection and ranging device uses a narrow scanning beam, is designed for eye-safety, uses a slant incidence, uses a non-pulsed waveform, employs specific scanning patterns, applies an ambient light removal, and/or uses precision pointing.

[0250] According to an implementation form, the laser detection and ranging device can discriminate between range along the sea surface and depth under the water. It can apply precision pointing, employ a narrow laser beam, provide a high range resolution, and/or measure range as well as elevation precisely.

[0251] According to an implementation form, the laser detection and ranging device uses polarization for sunlight suppression and/or uses dual polarization for enhanced detection.

[0252] The research leading to these results has received funding from the European Community's Seventh Framework Programme FP7/2007-2013 under grant agreement n°286220.

REFERENCE LIST**[0253]**

- 100
 - Detection system
- 101
 - Radio detection and ranging device
- 103
 - Laser detection and ranging device
- 105
 - Laser transmitter
- 107
 - Laser detector
- 109
 - Processor
- 200
 - Detection method
- 201
 - Coarsely detecting a target water surface area
- 203
 - Detecting the object within the target water surface area
- 205
 - Transmitting a laser beam towards the target water surface area
- 207
 - Detecting a reflected laser beam
- 209
 - Detecting the object within the target water surface area
- 300A
 - Diagram
- 300B
 - Diagram
- 301
 - Object
- 303
 - Water surface
- 305
 - Target water surface area
- 307
 - Marine seagoing vessel
- 309

	Transmitted laser beam
311	Reflected laser beam
401	Sensor unit
403	Sensor unit
405	Data processor unit
407	Display unit
409	System console unit
411	Radar unit
413	Radar unit
415	Gyro unit
417	GPS unit
419	AIS unit
421	Compass unit
423	System operator
425	System engineer
501	Laser unit
503	Auxiliary sensor unit
505	Mechanical scan unit
507	Real-time motion reference unit
509	Real-time control unit
511	Power supply unit
513	A/D conversion unit

601	Data processor core unit
603	Ethernet network card unit
605	Serial interface unit
607	Fiber / Ethernet switch unit
609	Bridge switch unit
611	Ship sensor unit
613	Data, monitoring and control signal line
615	Data, monitoring and control signal line
617	Observation signal line
619	Observation signal line
701	Visualization unit
703	Interaction unit
705	Keyboard-video-mouse switch unit
707	Display unit
709	Mouse unit
801	Keyboard-mouse-touch unit
803	Command generator unit
805	Network card unit
807	Display control unit
809	Display unit
901	

	Ship structure
903	
	Interface
905	
	Interface
907	
	Interface
909	
	Interface
911	
	Interface
913	
	Interface
915	
	Interface
917	
	Interface
1001	
	Ladar unit
1003	
	Visual mirror
1005	
	Visual window
1007	
	IR / BIL unit
1009	
	IR mirror
1011	
	IR window
1013	
	Mirror drive unit
1015	
	Cam unit
1017	
	Cam unit
1019	
	Control, IMU and power unit
1101	
	FPGA unit
1103	
	RAM unit
1105	
	A/D conversion unit

1107	A/D conversion unit
1109	CPU unit
1111	RAM unit
1113	FLASH unit
1115	Ethernet unit
1117	IMU unit
1119	Scan controller unit
1121	Step motor drive unit
1123	Step motor drive unit
1125	Piezo drive unit
1127	Piezo drive unit
1201	Ideal circular laser beam
1203	Divergent circular laser beam
1205	Divergent oval laser beam
1301	Horizon line
1303	Elevation line
1305	Elevation line
1307	Elevation line
1309	Elevation line
1311	Elevation line
1313	Front direction line
1315	

- Aft direction line
- 1317
- Further aft direction line
- 1319
- Starboard direction line
- 1321
- Port direction line
- 1323
- Radar coverage area
- 1401
- Ladar coverage area
- 1403
- Ladar coverage area
- 1501
- Ladar coverage area
- 1503
- Ladar coverage area
- 1505
- Ladar coverage area
- 1601
- Visual band coverage area
- 1603
- Visual band coverage area
- 1605
- Visual band coverage area
- 1607
- Visual band coverage area
- 1609
- Visual band coverage area
- 1701
- Infrared coverage area
- 1703
- Infrared coverage area

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in

compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US5781147A [0007]
- US20110084486A1 [0008]
- EP1956390A2 [0010]
- DE102010007520B3 [0011]
- US4995102A [0012]
- US6714286B1 [0013]

Non-patent literature cited in the description

- **GAVAN et al.**Optimized ladar/radar system for detection and trackingInt. Journal of Infrared and Millimeter Waves, 1992, vol. 13, 3 [0009]
- Interface Specification IS-GPS-200, Revision GGlobal Positioning Systems Directorate, 2012, [0037]

DETEKTERINGSSYSTEM TIL DETEKTERING AF EN GENSTAND PÅ EN VANDOVERFLADE

PATENTKRAV

1. Detekteringssystem (100) til detektering af en genstand (301) på en vandoverflade (303), hvilket detekteringssystem (100) omfatter:

en radiodetekterings- og radioafstandsmåleindretning (101) til grovdetektering af et målvandoverfladeområde (305) med genstanden (301); og

en laserdetekterings- og laserafstandsmåleindretning (103) til detektering af genstanden (301) inden for målvandoverfladeområdet (305),

10 hvor laserdetekterings- og laserafstandsmåleindretningen (103) omfatter en lasersender (105) til afsendelse af en moduleret laserstråle (309) med et ovalt laserstråletværsnit hen imod målvandoverfladeområdet (305), idet den modulerede laserstråle (309) er moduleret af en binær pseudotilfældig kodningssekvens, der er moduleret af en firkantbølgesekvens, hvor hastigheden for firkantbølgesekvensen er
15 lavere end hastigheden for den binære pseudotilfældige kodningssekvens, hvor lasersenderen (105) er konfigureret til at overføre den modulerede laserstråle (309) med det ovale laserstråletværsnit, en laserdetektor (107) til detektering af en reflekteret laserstråle (311), idet den reflekterede laserstråle (311) danner en reflekteret version af den sendte modulerede laserstråle (309), og en processor
20 (109) til detektering af genstanden (301) inden for målvandoverfladeområdet (305) på grundlag af den reflekterede laserstråle (311),

hvor laserdetekterings- og laserafstandsmåleindretningen (103) er konfigureret til at scanne målvandoverfladeområdet (305) langs et horisontalt plan til detektering af en azimuth for genstanden (301) inden for
25 målvandoverfladeområdet (305) i forhold til detekteringssystemet (100) og et vertikalt plan til detektering af en elevation for genstanden (301) inden for målvandoverfladeområdet (305) i forhold til detekteringssystemet (100).

2. Detekteringssystem (100) ifølge krav 1, hvor lasersenderen (105) er konfigureret til at sende en blågrøn laserstråle i bølgelængdeområdet mellem
30 400 nm og 600 nm.

3. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor den binære pseudotilfældige kodningssekvens er en civil GPS L2-sekvens med moderat længde eller en civil GPS L2-sekvens med stor længde.
4. Detekteringssystem (100) ifølge et hvilket som helst af de foregående
5 krav, hvor lasersenderen (105) er konfigureret til at sende en moduleret laserstråle, idet den modulerede laserstråle er moduleret med en on-off-keying-modulering eller en amplitude-shift-keying-modulering.
5. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor laserdetektoren (107) omfatter en laserdetekteringsdiode eller en
10 fotomultiplikator til detektering af den reflekterede laserstråle (311).
6. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor laserdetektoren (107) omfatter et optisk båndpasfilter.
7. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor processoren (109) er konfigureret til at bestemme en tidsforsinkelse mellem
15 afsendelse af laserstrålen (309) og detektering af den reflekterede laserstråle (311) til bestemmelse af en afstand for genstanden (301) inden for målvandoverfladeområdet.
8. Detekteringssystem (100) ifølge krav 7, hvor processoren (109) er konfigureret til at bestemme tidsforsinkelsen ved tidsmæssig korrelering af den sendte laserstråle (309) og den detekterede laserstråle (311) til opnåelse af en
20 afstandsprofil og ved bestemmelse af en maksimumsværdi for afstandsprofilen.
9. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor processoren (109) er konfigureret til at bestemme et spektrum af den detekterede laserstråle (311) til bestemmelse af laserstrålebølgelængder, der absorberes eller reflekteres af genstanden (301) inden for
25 målvandoverfladeområdet (305).
10. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, hvor laserdetekterings- og laserafstandsmålingsindretningen (103) endvidere omfatter en bevægelsesreferenceenhed til bestemmelse af en bevægelse af laserdetekterings- og laserafstandsmålingsindretningen (103), og hvor en

stråleretning af laserstrålen (309) stabiliseres på grundlag af den bestemte bevægelse af laserdetekterings- og laserafstandsmålingsindretningen (103).

11. Detekteringssystem (100) ifølge et hvilket som helst af de foregående krav, der endvidere omfatter en termisk sensor, en infrarød sensor, en flerspektral
5 sensor, en hyperspektral sensor, en billedgenerator for det visuelle bånd eller et kamera til detektering af målvandoverfladeområdet (305) med genstanden (301).

12. Detekteringsfremgangsmåde (200) til detektering af en genstand (301) på en vandoverflade (303) under anvendelse af et detekteringssystem (100), hvilken detekteringsfremgangsmåde (200) omfatter:

10 grovdetektering (201) af et målvandoverfladeområde (305) med genstanden (301) ved hjælp af en radiodetekterings- og radioafstandsmåleindretning (101);

detektering (203) af genstanden (301) inden for målvandoverfladeområdet (305) ved hjælp af en laserdetekterings- og laserafstandsmåleindretning (103),

hvor detektering (203) af genstanden (301) inden for
15 målvandoverfladeområdet (305) ved hjælp af laserdetekterings- og laserafstandsmåleindretningen (103) omfatter afsendelse (205) af en moduleret laserstråle (309) med et ovalt laserstråletværsnit hen imod målvandoverfladeområdet (305) med en lasersender (105), idet den modulerede laserstråle (309) er moduleret af en binær pseudotilfældig kodningssekvens, der er
20 moduleret af en firkantbølgesekvens, hvor hastigheden for firkantbølgesekvensen er lavere end hastigheden for den binære pseudotilfældige kodningssekvens, hvor lasersenderen (105) er konfigureret til at sende den modulerede laserstråle (309) med det ovale laserstråletværsnit, detektering (207) af en reflekteret laserstråle (311) med en laserdetektor (107), idet den reflekterede laserstråle (311) danner en
25 reflekteret version af den sendte modulerede laserstråle (309), og detektering (209) af genstanden (301) inden for målvandoverfladeområdet (305) på grundlag af den reflekterede laserstråle (311) ved hjælp af en processor (109);

scanning af målvandoverfladeområdet (305) langs et horisontalt plan til detektering af en azimuth for genstanden (301) inden for

målvandoverfladeområdet (305) i forhold til detekteringssystemet (100) ved hjælp af laserdetekterings- og laserafstandsmåleindretningen (103); og

scanning af målvandoverfladeområdet (305) langs et vertikalt plan til detektering af en elevation for genstanden (301) inden for

- 5 målvandoverfladeområdet (305) i forhold til detekteringssystemet (100) ved hjælp af laserdetekterings- og laserafstandsmåleindretningen (103).

DRAWINGS




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20