

**(12) STANDARD PATENT**  
**(19) AUSTRALIAN PATENT OFFICE**

(11) Application No. **AU 2010358879 B2**

(54) Title  
**Solar concentrator with support system and solar tracking**

(51) International Patent Classification(s)  
**F24J 2/54** (2006.01)                      **F24J 2/08** (2006.01)

(21) Application No: **2010358879**                      (22) Date of Filing: **2010.08.09**

(87) WIPO No: **WO12/020146**

(43) Publication Date: **2012.02.16**

(44) Accepted Journal Date: **2016.11.17**

(71) Applicant(s)  
**Compania Valenciana de Energias Renovables, S.A.**

(72) Inventor(s)  
**Peris Domingo, Gonzalo Bernabe;Ehlis Pirretas, Sergio;Mulet Mas, Jordi;Rosell Urrutia, Joan Ignasi;Chemisana Villegas, Daniel**

(74) Agent / Attorney  
**A.P.T. Patent and Trade Mark Attorneys, PO BOX 222, MITCHAM, SA, 5062**

(56) Related Art  
**GB 1590841 A**  
**US 2008/0295825 A1**

(12) SOLICITUD INTERNACIONAL PUBLICADA EN VIRTUD DEL TRATADO DE COOPERACIÓN EN MATERIA DE PATENTES (PCT)

(19) Organización Mundial de la Propiedad  
Intelectual

Oficina internacional



(10) Número de Publicación Internacional

**WO 2012/020146 A1**

(43) Fecha de publicación internacional  
16 de febrero de 2012 (16.02.2012)


PCT

- (51) Clasificación Internacional de Patentes:  
*F24J 2/54* (2006.01) *F24J 2/08* (2006.01)
- (21) Número de la solicitud internacional:  
PCT/ES2010/070543
- (22) Fecha de presentación internacional:  
9 de agosto de 2010 (09.08.2010)
- (25) Idioma de presentación: español
- (26) Idioma de publicación: español
- (71) Solicitante (para todos los Estados designados salvo US): **COMPANÍA VALENCIANA DE ENERGÍAS RENOVABLES, S.A.** [ES/ES]; C/ Universidad 4 3º, 11ª, E-46003 Valencia (ES).
- (72) Inventores; e
- (75) Inventores/Solicitantes (para US solamente): **PERIS DOMINGO, Gonzalo Bernabé** [ES/ES]; C/ Universidad 4 3º, 11ª, E-46003 Valencia (ES). **EHLIS PIRRETAS, Sergio** [ES/ES]; Avda. Diagonal, 676, E-08034 Barcelona (ES). **MULET MAS, Jordi** [ES/ES]; C. Nou, nº 24., E-080849 Sant Climent de Llobregat (Barcelona) (ES). **ROSELL URRUTIA, Joan Ignasi** [ES/ES]; C/ Antoni Sole nº 9, E-25001 Lleida (ES). **CHEMISANA VILLEGAS, Daniel** [ES/ES]; Avda. Valencia nº 43, E-25001 Lleida (ES).
- (74) Mandatario: **CARPINTERO LOPEZ, Mario**; Herrero & Asociados, S.L., C/ Alcalá, 35, E-28014 Madrid (ES).
- (81) Estados designados (a menos que se indique otra cosa, para toda clase de protección nacional admisible): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Estados designados (a menos que se indique otra cosa, para toda clase de protección regional admisible): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), euroasiática (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europea (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continúa en la página siguiente]

(54) Title: SOLAR CONCENTRATOR WITH SUPPORT SYSTEM AND SOLAR TRACKING

(54) Título : CONCENTRADOR SOLAR CON SISTEMA DE SOPORTE Y SEGUIMIENTO SOLAR



**FIG. 3**

(57) Abstract: The invention discloses a solar concentrator comprising one or more lenses and one or more collectors and at least two joint structures (2) for the solar collector and the lens and at least two fastening structures (1) enabling rotation about a longitudinal axis. The joint structure can be rotated or moved, enabling movement of the lens (3) and the collector (4) in opposing directions and variation of the relative distance thereof, which addresses the problem of varying the focal length for each individual angle of incidence of the radiation.

(57) Resumen: La invención propone un concentrador solar que comprende una o varias lentes y uno o varios captadores y al menos dos estructuras de unión (2) del captador solar y la lente y al menos dos estructuras de sujeción (1) que permiten una rotación

[Continúa en la página siguiente]

WO 2012/020146 A1

**Publicada:**

— *con informe de búsqueda internacional (Art. 21(3))*

## **SOLAR CONCENTRATOR WITH SUPPORTING AND SOLAR TRACKING SYSTEM**

### Field of the Invention

5           The present invention is applied to systems for solar collection by refraction. More specifically, it relates to a system capable of tracking the rays of the sun both depending on the hours of the day and on the season of the year.

### Background of the Invention

10           There are many types of systems for collecting solar energy as well as for concentrating the rays linearly for heating a fluid to a high temperature, which is generally used to produce electricity.

15           A type of concentrator existing today is the one which uses linear Fresnel lenses for concentrating the rays of the sun on the fluid. The system is basically formed by the lens, a collector which receives the concentrated radiation and the supporting structure and mechanisms. A frequent problem in the existing systems is that if it only tracks the rays of the sun on an axis in an east-west trajectory as the day advances, or north-south for different seasons of the year, this involves a loss of efficiency of the system as it loses  
20           concentration in the collection line. This is due to the use of linear concentrating lenses, because the focal point of maximum concentration varies depending on the angle of incidence of the radiation, affecting the efficiency of the installation.

25           This technical problem has only been solved up until now by means of systems for movement on two axes perpendicular to one another which allow tracking the sun in all its positions, whereby the angle of incidence of the rays of the sun on the lens is always perpendicular with respect to both axes, maintaining the point of maximum concentration invariable, i.e., the focal distance between lens and collector is constant. To achieve high temperature  
30           jumps, collectors must be connected in series, and the manner of maximizing efficiency is by placing said collectors forming very long straight lines, and this is not allowed by the two-axes system described above.

35           Patent WO2007/087343 describes a system which allows movement in both the east-west axis and in the north-south axis to optimize the use of the energy for any angle of incidence. However, the system is based on spheres which rotate about two axes and concentrate the rays individually,

which prevents optimizing the efficiency in linear concentrators.

#### Object of the Invention

5 The object of the invention is to solve the technical problems set forth in the previous section. To that end, it proposes a solar concentrator provided with at least one linear concentrating lens, and at least one collector, and provided with a supporting and tracking system, wherein the system comprises at least two fastening structures adapted for rotating about a first longitudinal axis, and at least two attachment structures for attaching the solar collector or collectors and the lens or lenses, fixed at two points to each 10 fastening structure, and capable of rotating with respect to a second transverse axis passing through these two points and perpendicular to the first, such that the plane defined by the attachment structure is inclined with respect to the plane of the fastening structure, and wherein the attachment structure is adapted such that it allows the displacement of the lens or lenses and the collector or collectors in opposite directions and the variation of their 15 relative distance.

Particular embodiments are defined in the dependent claims.

As a result of the system of the invention, it is therefore possible to vary the distance between lens and collector, such that the latter is at the 20 point of maximum solar concentration.

#### Brief Description of the Drawings

For the purpose of aiding to better understand the features of the invention according to a preferred practical embodiment thereof, a set of drawings is attached to the following description in which the following has 25 been depicted with an illustrative character:

Figure 1 is a schematic depiction of the principle of the invention.

Figure 2 shows a first embodiment of the invention.

Figure 3 shows a second embodiment of the invention.

Figure 4 is a front and cross-sectional view of the Fresnel lens and the 30 collector when the rays of the sun strike perpendicular to the system.

Figure 5 is a front and cross-sectional view when the rays strike obliquely.

Figure 6 shows several systems mounted contiguously for their installation in a thermal solar facility.

35 Figure 7 shows several alternative embodiments of the attachment structure.

Figure 8 shows an alternative form of the attachment and fastening structures.

Figures 9A, 9B and 9C are other particular embodiments adapted for the use of several lenses and collectors in parallel.

5 Detailed Description of the Invention

Figures 2-3 show systems according to the invention, comprising at least two attachment structures (2) for attaching the solar collector (4) and the lens (3) and at least two fastening structures (1). The longitudinal axis of the assembly is defined as that which is parallel to the lens and to its longest edges. The fastening structure allows the rotation about the longitudinal axis. 10

Figure 2 shows a first embodiment in which the fastening structure (1) and the collector (4) are solidary/integral, the longitudinal axis coincides with the axis of the collector and the attachment structure is provided with a counterweight (8). 15

Figure 3 shows the system of the invention in the configuration with the attachment structure in a circumferential arc shape. In this particular embodiment, the counterweight is not necessary because the axis of rotation of the fastening structure is located above the collector. In order to achieve the rotation of the fastening structure a rack system could be used (without the invention being limited thereto). The transverse axis is defined as that which passes through the two anchoring points between the fastening structure and the attachment structure. The attachment structure can rotate with respect to two points of the fastening structure for any position of the latter, such that the plane defined by the attachment structure is inclined with respect to the plane of the fastening structure, allowing the longitudinal displacement of the lens and the collector in the opposite direction, further varying their relative distance. 20 25

The lens-collector attachment structure preferably has a circumferential arc shape which is concentric to the fastening structure and fixed thereto with the possibility of rotation about the transverse axis, located approximately at the center of gravity between lens and collector, such that the rotation is balanced. This structure can also have a V shape with straight sections which attach the edges of the lens with the collector, a square shape or a U shape (Figure 7). 30

The lens will preferably a Fresnel type lens due to its lower weight and cost. It has further been found that the curved type Fresnel lens offers better 35

features. The lens can alternatively be a spherical type lens. The lens can incorporate a frame about its edges to provide it with rigidity and to facilitate the connection with the attachment structure.

5 A feature of linear concentrating lenses is, as mentioned, that if the angle of incidence is not normal to the surface, the focal distance (see Figures 4 and 5, ref.  $f_1$  and  $f_2$ ) measured perpendicular to the surface of the lens varies. Therefore, if the radiation reaching the lens is to be used to its maximum potential, there is no other choice but to vary the distance between lens and collector so that the latter is located at all times in the area of maximum concentration of the rays. This is achieved as a result of the rotation of the attachment structure with respect to the fastening structure by means of articulations which allow a displacement of up to 75 degrees (friction bearings, for example), and as a result of the fact that the collector and the lens are connected to the attachment structure also by means of articulations (5) which allow the position of both elements to remain parallel.

10 When the angle of incidence of the rays on the lens is not perpendicular with respect to the longitudinal axis, a displacement of the solar spot (area where the radiation is concentrated) towards an end (Figures 1 and 5) in the longitudinal direction also occurs. As a result of the invention, this effect is compensated with the displacement of the lens with respect to the collector, thereby achieving that the entire solar spot is projected by the lens and strikes the collector.

15 As mentioned, the lens and the collector are attached by means of a structure articulated both in the attachment with the lens or its frame and in the attachment with the collector. The distance between the articulations is fixed and said articulations will allow a longitudinal displacement of the collector and the lens to occur when the attachment structure rotates. Said rotation likewise causes a variation of the distance between lens and collector.

20 The combination of movements of the two structures allows the lens an infinity of positions with east/west or north/south inclination, and positions of the lens closer to or farther away from the axis of rotation of the attachment structure. By means of the rotation of the fastening structure on the longitudinal axis, the angle of incidence of the rays of the sun is always perpendicular to the transverse axis. By means of the rotation of the attachment structure on the transverse axis, the distance between lens and

collector is located at the point of maximum concentration of the rays of the sun.

The lens will thus always move in the direction opposite the collector, varying its relative longitudinal position and its distance in the normal direction, but never its relative transverse position.

An alternative embodiment is shown in Figure 8, in which both the attachment structure (2) and the fastening structure (1) have a V shape. The fastening structure (1) can rotate about a longitudinal axis, which in this case passes through its vertex. The rotation of the attachment structure and the relative movement of the lens and the collector occur similarly to the previous examples. To assure the stability of the system, the latter is provided with telescopic supports (6) which, upon varying in length, make the fastening structure be inclined towards one side or the other about the longitudinal axis. These telescopic systems can be hydraulic or electric, or function by means of a rack or "worm screw" system.

In other particular embodiments, which can be seen in Figures 9A, 9B and 9C, the attachment structure would have a saw or boat shape, such that it can house several collectors and several lenses in parallel. This system has the advantage that the proportions are flatter, i.e., the height of the assembly is less with respect to the width, gaining in stability. For this embodiment, two different types of fastening structure are contemplated: the first one (Figure 9A) is the one previously described (Figure 3) and the second one (Figure 9B and 9C) is in a boat shape, i.e., formed by a horizontal section in the base or rest position to place the collectors and two vertical or inclined sections at the ends. Said structure therefore has two vertices (9). For the case of Figure 9B, the longitudinal axis is located between the vertex of one side and the axis of symmetry when the assembly rotates towards that side or between the vertex of the other side and the axis of symmetry when the assembly rotates towards that other side. The base structure of this latter embodiment is a platform or pedestal, preferably made of reinforced concrete. The system of Figure 9C is a particular case of the 9B in which the longitudinal axis always remains fixed in the axis of symmetry.

The operation of the rotation of the fastening structure for the cases described in Figures 9B and 9C will preferably be done by means of telescopic supports which, upon varying in length, make the fastening structure be inclined towards one side or another about a longitudinal axis.

These telescopic systems can be hydraulic or electric and function by means of a rack or "worm screw" system. Another type of operation is by means of a motor with a fixed reducer acting on the axis of rotation.

5 Examples of materials for the different elements of the supporting system are: steel for the fastening and attachment structures, and they can also be made of aluminum or thermoplastic and reinforced steel and metal for the base structure.

#### Preferred Embodiment

10 In a preferred embodiment, the collection systems can be mounted continuously in the north-south direction to form modules. Each module is defined as an assembly of systems which share operation (Figure 6).

15 The east-west movement for the preferred embodiment of the fastening structure occurs about an imaginary axis parallel to the lens (longitudinal axis) and located approximately at the center of gravity of the assembly, such that it is a balanced rotation.

20 A loop will be formed by an assembly of modules attached in series to achieve a determined temperature jump. The system is formed by a Fresnel lens which can be formed by several parts, a collector and two base structure, fastening structure and attachment structure assemblies. Upon attaching several successive systems, every two systems share a base, fastening and attachment structures assembly (Figure 6).

25 The attachment between the base structure (7) and the fastening structure can mainly be of two types: a circular guide by means of rollers which allow the displacement between structure and guide, always keeping the axis of the circle of the structure (longitudinal axis) in the same position, and with rollers or stops which do not allow other movement or the separation of the structure with respect to the guide, or a horizontal flat guide, the fastening structure being displaced like a wheel on the surface.

30 In both cases the base (7) is preferably formed of pieces of concrete fixed to the ground by means of sole plates. Said pieces would have a parallelepiped shape with a recess in the form of a circular sector in the upper face for the first case explained above, and a parallelepiped shape with continuous faces in the second case.

35 The pieces of concrete would be completed with the necessary guides and elements which only allow the rotational movement, preventing lateral displacements and uplifting.

CLAIMS

2010358879 22 Oct 2016

1.- Solar concentrator provided with at least one linear concentrating lens (3), and at least one collector (4), and a supporting and tracking system, wherein the system comprises at least two holding structures (1) adapted for rotating about a longitudinal axis, characterized in that it further comprises at least two attachment structures (2) for attaching the at least one solar collector (4) and the at least one lens (3), each one of the at least two attachment structures (2) being rotatably fixed at two points (5) to one of the at least two holding structure (1) and capable of rotating with respect to a transverse axis passing through these two points and perpendicular to the longitudinal axis, such that, when the at least two attachment structures (2) rotate around the traverse axis, the at least one lens (3) and the at least one collector (4) move in opposite and parallel directions thereby causing a variation of the distance between the at least one lens (3) and the at least one solar collector (4).

2.- Solar concentrator according to claim 1, wherein each one of the at least two attachment structures (2) has articulations in the points (5) of attachment with the at least one collector (4), the at least one lens (3) and the at least two holding structures (1).

3.- Solar concentrator according to claim 2, wherein a frame is incorporated to provide support to the at least one lens (3) and attach them to the attachment structure (2) through the joints.

4.- Solar concentrator according to claim 1, provided with a single collector and a single lens, and wherein the holding structure (1) and the collector (4) are integral, the longitudinal axis coincides with the axis of the collector and the attachment structure is provided with a counterweight (8).

5.- Solar concentrator according to any of claims 1-3, wherein the attachment structure (2) and the holding structure (1) have a circumferential arc shape and the longitudinal axis is parallel to the axis of the collector (4).

5 6.- Solar concentrator according to any of claims 1-3, wherein the attachment structure (2) has a rectangular, V or U shape, the holding structure (1) has a circumferential arc shape and the longitudinal axis is parallel to the axis of the collector (4).



10 7.- Solar concentrator according to any of claims 1-3, wherein the holding structure (1) and the attachment structure (2) have a V shape and the longitudinal axis passes through the vertex of the holding structure (1).

15 8.- Solar concentrator according to any of claims 1-3, comprising at least two lenses and two collectors, and wherein the attachment structure has a boat or saw shape.


20 9.- Solar concentrator according to claim 8, wherein the holding structure (1) has a boat shape, and wherein the longitudinal axis is between a vertex (9) and the axis of symmetry of the concentrator.

25 10.- Solar concentrator according to claim 8, wherein the holding structure (1) has a boat shape, and wherein the longitudinal axis of rotation coincides with the axis of symmetry of the concentrator.


30 11.- Solar concentrator according to any of the previous claims, wherein the at least one lens (3) is a linear Fresnel or spherical-type lens.



**FIG. 1**




**FIG. 2**




**FIG. 3**

*RAYS OF THE SUN*




*RAYS OF THE SUN*




4/11


**FIG. 4**




**FIG. 5**




**FIG. 6**





**FIG. 7**





**FIG. 8**



**FIG. 9A**



**FIG. 9B**



**FIG. 9C**