




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : H04Q 7/38</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/30395 (43) International Publication Date: 25 May 2000 (25.05.00)</p>
<p>(21) International Application Number: PCT/US99/26503 (22) International Filing Date: 11 November 1999 (11.11.99) (30) Priority Data: 09/191,334 13 November 1998 (13.11.98) US (71) Applicant: ERICSSON, INC. [US/US]; 740 East Campbell Road, Richardson, TX 75081 (US). (72) Inventor: AMIRIJOO, Shahrokh; 3560 Alma Road #2326, Richardson, TX 75080 (US). (74) Agent: NAVARRO, Arthur, I.; Navarro IP Law Group, P.C., 801 East Campbell Road, #655, Richardson, TX 75081 (US).</p>	<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: METHOD AND SYSTEM FOR DYNAMICALLY AND PERIODICALLY UPDATING MOBILE STATION LOCATION DATA IN A TELECOMMUNICATIONS NETWORK

(57) Abstract

A method and system in a telecommunications network for dynamically updating data indicative of the availability of mobile stations within the telecommunications network. Periodically, a total number of mobile location updates and a total number of failed pagings occurring with the telecommunications network during a prior time interval are ascertained. Thereafter, a ratio of the total number of mobile location updates to the total number of failed pagings is determined, in response to ascertaining the total number of mobile location updates and the total number of successful paging occurring within the prior time interval. A threshold value is designated such that the threshold value is determinative of whether or not to release to the telecommunications network, data indicative of the availability of mobile stations within the telecommunications network. At a particular time, the data is automatically released, in response to ascertaining whether the ratio falls within an appropriate range of the threshold value. The use of the threshold value to assist in determining whether or not to release the data to the telecommunications network at a particular time, promotes the dynamic release of the data to the telecommunications network without the necessity of manual intervention.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**METHOD AND SYSTEM FOR DYNAMICALLY AND PERIODICALLY
UPDATING MOBILE STATION LOCATION DATA IN A
TELECOMMUNICATIONS NETWORK**

5

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

10 The present invention is related to an improved telecommunications network. In particular, the present invention relates to wireless telecommunications networks. More particularly, the present invention relates to cellular telephone networks. Still more particularly, the present invention relates to techniques for periodically notifying a
15 telecommunications network of the availability of mobile stations within the telecommunications network.

2. Description of Related Art

20 Present-day mobile telephony has spurred rapid technological advances in both wireless and non-wireless areas. The telecommunications industry is a rapidly growing industry, with advances, improvements, and technological breakthroughs occurring on an almost daily basis. Many mobile telecommunications systems, among them the European GSM-system, have
25 already passed through several basic development phases and system designers are now concentrating on further improvements to the systems, including system refinements and the introduction of optional services.

30 Most wireless telecommunication systems currently in use are implemented as cellular telephone networks. Cellular telephone networks typically are composed of a group of base stations connected to a centrally

located switch. This centrally located switch is commonly referred to as a Mobile Switching Center (MSC). Base stations are usually spaced apart from each other by distances of between one-half and twenty kilometers. Each base station is assigned a number of two-way voice and control channels. The voice channels transmit voice signals to and from proximately located mobile stations, and transmit control information to and from these mobile stations, usually for the purpose of establishing a voice communications link.

A typical cellular telephone network also includes a group of interconnected mobile switching centers, which operate in association with a gateway mobile switching center through which the cellular telephone network interconnects with a conventional public switched telephone network (PSTN). In addition, at least one home location register (HLR) operates within the cellular telephone network. The HLR stores network subscriber information, including the identified location of current mobile stations within the network.

In response to an incoming call dialed to a mobile station, a signal is sent to the home location register requesting routing information through the network to the called mobile station. The home location register "looks up" the current location of the mobile station and contacts the currently serving mobile switching center to pre-route the call and retrieve a temporary location directory number, which is utilized to route the call through the cellular telephone network for delivery to the mobile station. The serving mobile switching center retrieves from a visitor location register (VLR), the identification of the cell within which the called mobile station is currently located. The mobile switching center then instructs the base station associated with that particular cell to page the mobile station. Responding to the page, the mobile station requests assignment of a channel, and the network routes the call through the serving mobile switching center and over the assigned channel.

Periodic updating, a well-known telecommunications technique, is a technique utilized in GSM-type telecommunications networks to periodically notify the network of the availability of the mobile stations within the telecommunications network. Periodic updating may be accomplished utilizing location updating or routing area update procedures. Timers located at mobile stations within the network control the timing of such procedures. In a GSM-type telecommunications network, such timers may be located at an MSC. In a General Packet Radio Service (GPRS) telecommunications system, the timer may be located at a Serving GPRS Support Node (SGSN). A GPRS telecommunications system is a standardized switched data service for GSM based systems and networks.

Regardless of the type of telecommunications network utilized, such timers must currently be set manually. Correct timer settings are very important from a network-load point of view. A wrong setting may result in a serious overload in the network, particularly following a long network shutdown. The timers present at the mobile stations may additionally expire at an inopportune moment, causing a network overload and massive access requests for location updates. A setting that its too short may result in excessive signaling due to the generation of unnecessary location updates. A longer setting may result in inaccurate location identification for the mobile stations, which in turn promotes excess paging. An excess number of pagings may also contribute to an increase in the network load. Such excess pagings are usually very unsuccessful. The timer settings themselves will vary according to the type of network utilized, the type of cells planned, coverage area, and so forth.

From the foregoing, it can be appreciated that a need exists for a reliable method and system for automatic evaluation and implementation of timer settings in telecommunication networks. Such a method and system, if implemented, would serve to promote accurate and efficient periodic Location

Update and Periodic Routing Area timers in GSM and GPRS systems, which would in turn create less havoc and frustration in telecommunication networks, as is the case with current time configurations.

5

SUMMARY OF THE INVENTION

It is therefore one object of the present invention to provide an improved telecommunications network.

10

It is another object of the present invention to provide an improved cellular telephone network.

15

It is still another object of the present invention to provide a method and system for periodically notifying a telecommunications network of the availability of mobile stations within the telecommunications network.

20

It is yet another object of the present invention to provide a method and system for automatically notifying a telecommunications network of the availability of mobile stations within the telecommunications network.

25

The above and other objects are achieved as is now described. A method and system in a telecommunications network for dynamically updating data indicative of the availability of mobile stations within the telecommunications network is disclosed. Periodically, a total number of mobile location updates and a total number of failed pagings occurring with the telecommunications network during a prior time interval are ascertained. Thereafter, a ratio of the total number of mobile location updates to the total number of failed pagings is determined, in response to ascertaining the total number of mobile location updates and the total number of successful paging occurring with the prior time interval.

30

A threshold value is designated such that the threshold value is determinative of whether or not to release to the telecommunications network data indicative of the availability of mobile stations within the telecommunications network. At a particular time, the data is automatically released, in response to ascertaining whether the ratio falls within an appropriate range of the threshold value. The use of the threshold value to assist in determining whether or not to release the data to the telecommunications network at a particular time, promotes the dynamic release of the data to the telecommunications network without the necessity of manual intervention.

If the ratio is found to be greater than a specified upper limit of the threshold value, the particular time is decreased. If, however, the ratio is found to be less than a specified lower limit of the threshold value, the particular time is increased. The threshold value itself is dependent upon the total number of mobile switching centers present within the telecommunications network.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of this invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objects, and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

25

FIG. 1 depicts a block diagram illustrative of a telecommunications network in which a preferred embodiment of the present invention may be implemented;

30

FIG. 2 illustrates a block diagram illustrative of a GPRS

telecommunications network, in accordance with a preferred embodiment of the present invention;

FIG. 3 depicts a high-level logic flow diagram illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention;

FIG. 4 illustrates a detailed logic flow diagram illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention; and

FIG. 5 depicts a detailed mathematical logic flow diagram illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention.

15

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Reference is now made to **FIG. 1**, wherein a block diagram illustrates a telecommunications network **10** in which a preferred embodiment of the present invention may be implemented. Telecommunications network **10** depicted in **FIG. 1** is divided into a Switching System (SS) **22** and a Base Station System (BSS) **40**. Each of these systems contains a number of functional units, which process information and carry out operations of a functional telecommunications network. The functional units themselves may be implemented utilizing various telecommunications hardware devices.

25

Switching System (SS) **22** is composed of a Visitor Location Register (VLR) **30**, a Home Location Register (HLR) **28**, and Authentication Center (AUC) **24**, an Equipment Identity Register (EIR) **26**, and a Mobile Switching Center (MSC) **27**. Base Station System (BSS) **40** is composed of a Base

30

Station Controller (BSC) **46** and a Base Transceiver Station (BTS) **44**. An Operations and Maintenance Center (OMC) **48** is connected to equipment present within Switching System (SS) **22** and to BSC **46**. The dashed lines in **FIG. 1** represent information transmission, while solid lines represent both call connections and information transmission.

Telecommunications network **10** illustrated in **FIG. 1** may be realized as a network of neighboring radio cells, which together provide complete coverage for a service area. The service area is the geographic area served by a given telecommunications supplier, and is the area in which the supplier stands ready to provide its service. The service area of New York Telephone, for example, is most (but not all) of New York State. Each cell contains a base station transceiver (BTS) operating on a set of radio channels. These channels differ from the channels utilized by neighboring cells in order to avoid interference.

Each base station controller (BSC) controls a group of base station transceivers. The base station controller controls well-known telecommunication functions, such as "Handover" and power control. A number of base station controllers (e.g., BSC **46**) are served by a mobile switching center (MSC) **27**, which controls calls to and from a Public Switched Telephone Network (PSTN) **18**. MSC **27** also controls calls to and from an Integrated Services Digital Network (ISDN) **12**, a Public Land Mobile Network (PLMN) **20**, a Circuit Switched Public Data Network (CSPDN) **16**, and also, various private networks such as, for example, a Packet Switched Public Data Network (PSPDN) **14**.

Each unit is actively involved in carrying speech connections between Mobile Station (MS) **42** and, for example, a subscriber in a fixed network, such as PSTN **18**. Because of the extreme difficulties involved in completing an MS terminated telephone call, a number of databases located within the

telecommunications network keep track of Mobile Station (MS) **42**. The most important of these databases is Home Location Register (HLR) **28**. When a user subscribes to a telecommunications network, such as the telecommunications network depicted in **FIG. 1**, the user is registered within Home Location Register (HLR) **28**. Home Location Register (HLR) **28** contains subscriber information, such as supplementary services and authentication parameters.

Data describing the location of the MS, such as the area (i.e., the MSC area) in which the MS presently resides, is contained with the Home Location Register (HLR) **28**. The MSC area represents that portion of the telecommunications network covered by a single MSC. In order to route a call to a mobile subscriber within a telecommunications network, such as the telecommunications network depicted in **FIG. 1**, the path through the network links to the MSC in the MSC area where the subscriber is currently located. Data describing the location of the MS is thus actively altered as the MS moved from cell to cell within the telecommunications network. MS **42** sends location information, via MSC **27** and Visitor Location Register (VLR) **30**, to an associated HLR, which permits MS **42** to receive calls. The Authentication Center (AUC) **24** is connected to Home Location Register (HLR) **28**, and provides Home Location Register (HLR) **28** with authentication parameters and ciphering keys utilized for security purposes.

Visitor Location Register (VLR) **30** is a database that contains information regarding all mobile stations currently located in the MSC area. When MS **42** roams in the new MSC area, the VLR connected to the MSC in that particular area requests data about the MS from Home Location Register (HLR) **28**. Simultaneously, Home Location Register (HLR) **28** is provided with the location of the MSC area in which MS **42** resides. If it is later desired to make a call from MS **42**, Visitor Location Register (VLR) **30** will have at its disposal, all the

information necessary for call set-up, without being forced to interrogate Home Location Register (HLR) **28** each time a call is made. Visitor Location Register (VLR) **30** thus functions as a distributed HLR. Visitor Location Register (VLR) **30** also contains precise information about the location of the MS in the MSC area.

If an individual subscriber within the fixed network PSTN **18** desires to make a call to a GSM subscriber, an exchange within PSTN **18** connects the call to an MSC equipped with a function commonly known as a "gateway" function. In the telecommunications arts, an MSC having a "gateway" function is commonly referred to as a Gateway MSC (GMSC). The MSC in telecommunications network **10** of **FIG. 1** may be implemented as a Gateway MSC. Most MSC's within GSM telecommunications networks function as a Gateway MSC's. The GMSC must find the location of the searched MS, which can be accomplished by interrogating the HLR where the MS is registered. The HLR then replies with the address of the current MSC area. Thereafter, the GMSC can re-route the call to the correct MSC. When the call reaches that MSC, the VLR will have additional information regarding the precise location of the MS. The call can then be switched through to completion.

The telecommunications network depicted in **FIG. 1** may be implemented as a GSM-type network. Those skilled in the art can appreciate that although the present invention is described and illustrated in the context of a GSM network standard, the present invention may also be implemented in accordance with other standards and networks, including those utilized throughout North and South America. The GSM network standard, as discussed herein, is merely presented for illustrative purposes only and is not a limiting feature of the present invention.

FIG. 2 illustrates a block diagram illustrative of a GPRS

telecommunications network **11**, in accordance with a preferred embodiment of the present invention. Those skilled in the art will appreciate that the method and system described herein may be implemented within the context of a GPRS telecommunications network. Thus, the GPRS telecommunications network depicted in **FIG. 2** adds the GPRS the packet switching functionality to the GSM telecommunications network illustrated in **FIG. 1**. Data packets sent through GPRS telecommunications network **11** may be transmitted at transmission rates of up to **115 kbits/s**. The GPRS architecture utilizes existing GSM nodes and adds new nodes for handling packet switching, point to multi-point service handling, and interworking of existing packet data networks.

GPRS telecommunications network **11** includes a Base Transceiver Station (BTS) **13**, which is linked to a Base Station Controller (BSC) **15**. Base Transceiver Station (BTS) **13** is analogous to Base Transceiver Station (BTS) **44** of **FIG. 1**. Base Station Controller (BSC) **15** is analogous to a Base Station Controller (BSC) **46** of **FIG. 1**. GPRS telecommunications network **11** also is composed of a Backbone Network **31** linked to a first Serving GPRS Support Node (SGSN) **21**, a first Gateway GPRS Support Node (GGSN) **25**, a second Gateway GPRS Support Node (GGSN) **25**, a second Gateway GPRS Support Node **33**, and a Point-to-Multipoint Service Center (PTM-SC) **35**.

GPRS telecommunications network **11** further includes a Mobile Switching Center/Visitor Location Register (MSC/VLR) **19**, which functions as an interface between an MSC and SGSN. MSC/VLR **19** coordinates signaling for mobile stations that have both circuit-switched and packed-switched capabilities. In addition, GPRS telecommunications network **11** includes a Home Location Register (HLR) **23**, which is analogous to Home Location Register (HLR) **28** of **FIG. 1**. Home Location Register (HLR) **23** contains subscription data and routing information. Home Location Register (HLR) **23** is also maps each subscriber to one or more Gateway GPRS support nodes.

Home Location Register (HLR) **23** is accessible from Gateway GPRS Support Node (SGSN) **21**.

5 Wireless devices, such as a Notebook & GPRS Mobile unit **39** may be utilized in association with GPRS telecommunications network **11**. Portable computers, such as "lap-tops," "palm-tops," and so forth that run standard operating systems may be utilized in accordance with a preferred embodiment of the present invention. Other wireless devices that are suitable for GPRS services include so-called "smart phones," "card phones," and standard mobile
10 phones. In addition, an External Internet protocol (IP) Network **29** may be linked to telecommunications network **11** via Gateway GPRS Support Node (GGSN) **25**. An External X.25 Network may also be linked to telecommunications network **11** via Gateway GPRS Support Node **33**. The GGSN provides the interface towards external IP packet networks and X.25 networks, both well-
15 known networks utilized in the telecommunication arts.

FIG. 3 illustrates a high-level logic flow diagram **60** illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention. It can be
20 appreciated by those skilled in the art that **FIG. 3**, **FIG. 4**, and **FIG. 5**, as illustrated and described herein, present a self-consistent sequence of steps leading to a desired result. The steps are those requiring the physical manipulation of physical quantities. Usually, although not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored,
25 transferred, combined, compared, and otherwise manipulated.

It has proven convenient at times by those skilled in the art, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. It should be borne in mind, however, that all of these and similar
30 terms are to be associated with the appropriate physical quantities and are

merely convenient labels applied to these quantities.

5 Further, the manipulations performed are often referred to in terms, such as "designating," "delivering" or "conveying", which are commonly associated with mental operations performed by a human operator. No such capability of a human operator is necessary or desirable in most cases of the operations described herein, which form part of the present invention. As indicated herein, these operations are primarily machine operations. Useful machines for performing operations of a preferred embodiment of the present invention include data-processing systems, such as general-purpose digital computer or other similar devices. In all cases the distinction between the method of operations in operating a computer and the method of computation itself should be borne in mind.

15 The present invention relates to method steps for processing electrical or other (e.g. mechanical, chemical) physical signals to generate other desired physical signals, and can be implemented via a computer or microcomputer. However, it is necessary to maintain within a computer memory of a mobile telephone subscriber unit, instructions implementing these method steps. Such instructions can be maintained within a computer memory location of a wireless telephone base station or at a central broadcasting center from which such base stations receive instructions. Implementation of the method described herein is left to the discretion of a particular wireless telephone system designer, whether cellular-based or otherwise.

25 It can be appreciated by those skilled in the art that the methods described herein can be implemented as a program product (e.g., a control program residing in a computer memory) containing instruction that when executed on a CPU, carry out the operations depicted in the logic flow diagrams of FIG. 3, FIG. 4, and FIG.. 5. While the present invention is described in the

30

context of a fully functional computer system, those skilled in the art will further appreciate that the present invention is capable of being distributed as a program product in a variety of forms, and that the present invention is capable of being distributed as a program product in a variety of forms, and that the present invention applies equally, regardless of the particular type of signal-bearing media utilized to actually carry out the distribution. Examples of signal-bearing media include recordable-type media, such as floppy disks, hard-disk drives and CD ROM's, and transmission-type media, such as digital and analog communication links.

Preferred implementations of the invention can include implementations to execute the method or methods described herein as a program product residing in a memory of microcomputer. Alternatively, a preferred embodiment of the present invention can include a program product residing in a microcomputer memory located at an MSC (e.g., MSC 27 of FIG. 1 herein). The MSC controls system operations in cellular telephone networks, thereby managing calls, tracking billing information, and locating cellular subscribers. The program product thus includes sets of instructions for executing the method and system described herein. Until required by a microcomputer, the set of instructions may be stored in a computer-program product in another computer memory. For example, the set of instructions may be stored as a computer-program product in a disk drive attached to a microcomputer (which may include a removable memory such as an optical disk or floppy disk for eventual use in the disk drive).

The computer-program product can also be stored at another computer and transmitted, when desired, to a user's workstation by an internal or external network. Those skilled in the art will appreciate that the physical storage of the sets of instructions physically change the medium upon which it is stored so that the medium carries computer-readable information. The change may be

electrical, magnetic, chemical, or some other physical change. While it is convenient to describe the invention in terms of instructions, symbols, characters, or the like, the reader should remember that all of these and similar terms should be associated with the appropriate physical elements.

5

Thus, as depicted at block **62**, the process for implementing the present invention is initiated. As indicated at block **64**, the total number of location updates and unsuccessful pagings that occurred in a telecommunications network (e.g., such as the telecommunications network depicted in **FIG. 1**) during a previous time period are determined. This time period will likely have occurred immediately prior to the processing of the operation depicted at block **64**. However, the time period may have occurred earlier. The choice of which time period to analyze is left up to the designer of a telecommunications network in which the present invention is implemented.

15

Thereafter, as indicated at block **68**, the ratio of the total number of location updates to the total number of unsuccessful pagings is determined. A threshold value is designated, as illustrated at block **70**. This threshold value can later be utilized to compare to the ratio value determined earlier (i.e., see block **68**). As illustrated thereafter at block **72**, a test is performed to determine if the ratio falls within a desired range of the threshold value.

20

If it is determined, as depicted at block **72**, that the ratio does not lie within a desired range of the threshold value, then as illustrated at block **74**, the time for releasing data describing the availability of mobile stations within the telecommunications network is altered. Thereafter, as indicated at block **76**, the data is released to the telecommunications network at the altered time. The process then terminates, as illustrated at block **78**. If, however, it is determined according to the operation depicted at block **72**, that the ratio does fall within the desired range of the threshold value, the data is simply released to the

25

30

telecommunications network at the unaltered or originally set time, as illustrated at block **73**. The process thereafter terminates, as illustrated at block **78**.

FIG. 4 depicts a detailed logic flow diagram **80** illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention. Thus, as depicted at block **82**, a detailed process for implementing the present invention is initiated. As indicated by block **84**, the total number of location updates and unsuccessful pagings that occurred in a telecommunications network (e.g., such as the telecommunications network depicted in **FIG. 1**) during a previous time period are determined. This time period will likely have occurred immediately prior to the processing of the operation depicted at block **84**. However, the time period may have occurred even earlier. Again, the choice of which time period to analyze and utilize as a parameter in accordance with a preferred embodiment of the present invention may be left to the discretion of the network designer.

Thereafter, as indicated at block **86**, the ratio of the total number of location updates to the total number of unsuccessful pagings is determined. A threshold value is designated, as illustrated at block **88**, which can later be utilized to compare to the ratio value determined earlier, as described at block **86**. This threshold value, although depicted at block **88** following processing of the operation depicted at block **86**, may be designated prior to the processing of any of the previous steps. However, for illustrative purposes only, the threshold value is determined, as indicated at block **88**. The threshold value is a specified limit dependent upon processing time, and/or radio or terrestrial resources required to perform paging and location updates within various GSM nodes (e.g., MSC and associated interfaces) operating in the telecommunications network.

As illustrated thereafter at block **90**, a time parameter to release data

relating to the availability of mobile stations within the telecommunications network is determined. At this particular time, this data will be released to the telecommunications network. Then, as indicated at block **98**, a test is performed to determine if the ratio determined earlier is greater than an upper limit of the threshold value. If the ratio is greater than an upper limit of the threshold value, then as described at block **100**, the time designated earlier (i.e., see block **90**) is decreased by a specified period. Thereafter, the data is released to the telecommunications network at this altered time, as depicted at block **104**. The telecommunications network will then have at its disposal, data relating to the availability of mobile stations within the network.

If, however, the ratio is not greater than an upper limit of the threshold value, an additional test is performed, as illustrated at block **92**, to determine if the ratio is less than a lower limit of the threshold value. If the ratio is less than a lower limit of the threshold value, then as indicated at block **102**, the time designated earlier, as described at block **90**, is increased by a specified period. The data is then released, as depicted at block **104**, at the newly altered time. The process then terminates, as depicted at block **106**. If the ratio is not greater than a lower limit of the threshold value, the time remains unchanged, as illustrated at block **94**, and the data is released to the telecommunications network at the time determined originally, as described at block **90**. The process then terminates, as indicated at block **106**.

FIG. 5 depicts a detailed mathematical logic flow diagram **120** illustrating process steps for implementing the method and system of the present invention, in accordance with a preferred embodiment of the present invention. As indicated at block **122**, the process is initiated. As illustrated at block **124**, the number of location updates and unsuccessful pagings having occurred in a prior time period are determined. The total number of location updates occurring in the prior time period is represented by the value N_{LU} .

The total number of unsuccessful pagings occurring in the prior time period is represented by the value N_{UP} . The ratio of the total number of location updates to the total number of unsuccessful pagings is represented by the value N_{LU}/N_{UP} , as depicted at block **126**. Thereafter, as illustrated at block **128**, a specified value (i.e., a threshold value) is designated. This specified value is represented by the variable $C_{UP/LU}$. Ideally, the ratio should be kept as close as possible to the specified value. Thereafter, as indicated at block **130**, the time at which the data (i.e., data indicative of the availability of mobile stations within the telecommunications network) will release to the telecommunications network is designated.

This time the parameter is represented by the variable $T_{LU,init}$. Blocks **122** to **130** can be described as operations in which measures are performed and paging location update statistics are collected. Thereafter, as depicted at block **132** a test is performed to determine if the ratio N_{LU}/N_{UP} is greater than an upper limit of $C_{UP/LU}$. If it is determined that N_{LU}/N_{UP} is greater than the upper limit of $C_{UP/LU}$, then the designated time (i.e., see block **130**) at which data is to be released to the telecommunications network is decreased by a specified time period, represented by the variable T_{dec} . Mathematically, the operation illustrated at block **142**, which is analogous to the operation illustrated at block **100** of **FIG. 4**, can be described by the following mathematical formula:

$$T_{LU,n} = T_{LU,init} - T_{dec}$$

If it is determined that N_{LU}/N_{UP} is not greater than the upper limit of $C_{UP/LU}$, then a test is performed to determine if N_{LU}/N_{UP} is less than a lower limit of $C_{UP/LU}$. If it is determined that N_{LU}/N_{UP} is less than a lower limit of $C_{UP/LU}$, then as indicated at block **140**, the designated time is increased by a specified time period parameter. Mathematically, the operation illustrated at block **140**, which is analogous to the operation depicted at block **102** of **FIG. 4**, can be described

by the following mathematical formula:

$$T_{LU,n} = T_{LU,init} + T_{dec}$$

5 If it is determined that N_{LU}/N_{UP} is not less than the lower limit of $C_{UP/LU}$, then as depicted at block **136**, the time remains unchanged. As illustrated at block **138**, the data is then released to the telecommunications network at the originally designated time (i.e., see block **130**). The process then terminates, as described at block **146**.

10

The embodiments and examples set forth herein are presented in order to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. However, those skilled in the art will recognize that the foregoing description and examples have
15 been presented for the purpose of illustration and example only. The description as set forth is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims.

20

WHAT IS CLAIMED IS:

1. A method in a telecommunications network for dynamically updating data indicative of the availability of mobile stations within said telecommunications network, said method comprising the steps of:

periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval;

determining a ratio of said total number of mobile location updates to said total number of failed pagings, in response to ascertaining said total number of mobile location updates and said total number of successful paging occurring within said prior time interval;

designating a threshold value determinative of whether to release to said telecommunications network, data indicative of the availability of mobile stations within said telecommunications network; and

automatically releasing said data to said telecommunications network at a particular time, in response to ascertaining whether said ratio falls within an appropriate range of said threshold value, thereby promoting the dynamic release of said data to said telecommunications network.

2. The method of claim 1 further comprising the step of:

decreasing said particular time, if said ratio is greater than a specified upper limit of said threshold value.

3. The method of claim 2 further comprising the step of:

increasing said particular time, if said ratio is less than a specified lower limit of said threshold value.

4. The method of claim 3 wherein the step of designating a threshold value
5 determinative of whether to release to said telecommunications network, data
indicative of the availability of mobile stations within said telecommunications
network, further comprises the step of:

10 designating a threshold value determinative of whether to release to said
telecommunications network, data indicative of the availability of mobile stations
within said telecommunications network, wherein said threshold value is
dependent upon a total number of mobile switching centers present within said
telecommunications network.

15 5. The method of claim 4 wherein the step of periodically ascertaining a total
number of mobile location updates and a total number of failed pagings
occurring within said telecommunications network during a prior time interval,
further comprises the step of:

20 periodically ascertaining a total number of mobile location updates and
a total number of failed pagings occurring within said telecommunications
network during a prior time interval, wherein said total number of mobile location
updates comprises a total number of mobile switching center updates occurring
within said telecommunications network during said prior time interval.

25 6. The method of claim 5 wherein the step of periodically ascertaining a total
number of mobile location updates and a total number of failed pagings
occurring within said telecommunications network during a prior time interval,
further comprises the step of:

30

periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, wherein said telecommunications network comprises a wireless telecommunications network.

5

7. The method of claim 6 wherein the step of periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, further comprises the step of:

10

periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, wherein said telecommunications network comprises a cellular telephone network.

15

8. The method of claim 6 wherein the step of periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, further comprises the step of:

20

automatically periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval.

25

9. A system in a telecommunications network for dynamically updating data indicative of the availability of mobile stations within said telecommunications network, said system comprising:

30

means for periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said

telecommunications network during a prior time interval;

means for determining a ratio of said total number of mobile location updates to said total number of failed pagings, in response to ascertaining said
5 total number of mobile location updates and said total number of successful paging occurring within said prior time interval;

means for designating a threshold value determinative of whether to release to said telecommunications network, data indicative of the availability of
10 mobile stations within said telecommunications network; and

means for automatically releasing said data to said telecommunications network at a particular time, in response to ascertaining whether said ratio falls within an appropriate range of said threshold value, thereby promoting the
15 dynamic release of said data to said telecommunications network.

10. The system of claim 9 further comprising:

means for decreasing said particular time, if said ratio is greater than a
20 specified upper limit of said threshold value.

11. The system of claim 10 further comprising:

means for increasing said particular time, if said ratio is less than a
25 specified lower limit of said threshold value.

12. The system of claim 11 wherein said threshold value is dependent upon a total number of mobile switching centers present within said telecommunications network.

30

13. The system of claim 12 wherein said total number of mobile location updates comprises a total number of mobile switching center updates occurring within said telecommunications network during said prior time interval.

5 14. The system of claim 13 wherein said telecommunications network comprises a wireless telecommunications network.

15. The system of claim 14 wherein said telecommunications network comprises a cellular telephone network.

10

16. The system of claim 15 wherein said means for periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, further comprises:

15

means for automatically periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval.

20 17. A program product residing in computer memory in a computer for dynamically updating data indicative of the availability of mobile stations within a telecommunications network, said program product comprising:

25 instruction means residing in a computer for periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval;

30 instruction means residing in a computer for determining a ratio of said total number of mobile location updates to said total number of failed pagings, in response to ascertaining said total number of mobile location updates and

said total number of successful paging occurring within said prior time interval;

instruction means residing in a computer for designating a threshold value determinative of whether to release said telecommunications network, data
5 indicative of the availability of mobile stations within said telecommunications network; and

instruction means residing in a computer for automatically releasing said data to said telecommunications network at a particular time, in response to
10 ascertaining whether said ratio falls within an appropriate range of said threshold value, thereby promoting the dynamic release of said data to said telecommunications network.

18. The program product of claim 17 further comprising:

15

instruction means residing in a computer for decreasing said particular time, if said ratio is greater than a specified upper limit of said threshold value.

19. The program product of claim 18 further comprising:

20

instruction means residing in a computer for increasing said particular time, if said ratio is less than a specified lower limit of said threshold value.

20. The program product of claim 19 wherein said threshold value is
25 dependent upon a total number of mobile switching centers present within said telecommunications network.

21. The program product of claim 20 wherein said total number of mobile
30 location updates comprises a total number of mobile switching center updates occurring within said telecommunications network during said prior time interval.

22. The program product of claim 21 wherein said telecommunications network comprises a wireless telecommunications network.

5 23. The program product of claim 22 wherein said telecommunications network comprises a cellular telecommunications network.

10 24. The program product of claim 23 wherein said instruction means residing in a computer for periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval, further comprises:

15 instruction means residing in a computer for automatically periodically ascertaining a total number of mobile location updates and a total number of failed pagings occurring within said telecommunications network during a prior time interval.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/26503

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 972 355 A (MULLINS JEFFERY L) 20 November 1990 (1990-11-20) column 1, line 13 - line 52 column 2, line 54 -column 3, line 16 figure 1	1-24
A	AKYILDIZ I F ET AL: "DYNAMIC MOBILE USER LOCATION UPDATE FOR WIRELESS PCS NETWORKS" WIRELESS NETWORKS,US,ACM, vol. 1, no. 2, 1 July 1995 (1995-07-01), pages 187-196, XP000524642 ISSN: 1022-0038 paragraph '0001! - paragraph '0003! -/--	1-24

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

17 March 2000

Date of mailing of the international search report

28/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Rabe, M

1

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/26503

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 851 702 A (NIPPON ELECTRIC CO) 1 July 1998 (1998-07-01) abstract column 1, line 16 -column 2, line 6 column 6, line 31 -column 7, line 48 ---	1-24
A	WO 98 37721 A (NOKIA TELECOMMUNICATIONS OY ;SOEDERBACKA LAURI (FI); EINOLA HEIKKI) 27 August 1998 (1998-08-27) abstract page 2, line 27 -page 3, line 19 page 8, line 24 -page 10, line 11 figure 1 -----	1-24

INTERNATIONAL SEARCH REPORT

Information on patent family members

Inter. nal Application No
PCT/US 99/26503

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4972355	A	20-11-1990	AU 627079 B AU 6427390 A CA 2041636 A,C CN 1050804 A,B DE 69015611 D DE 69015611 T EP 0446327 A WO 9105413 A	13-08-1992 28-04-1991 03-04-1991 17-04-1991 09-02-1995 27-07-1995 18-09-1991 18-04-1991

EP 0851702	A	01-07-1998	JP 2853688 B JP 10191434 A US 6018573 A	03-02-1999 21-07-1998 25-01-2000

WO 9837721	A	27-08-1998	FI 970705 A FI 980351 A AU 6216398 A EP 0962113 A ZA 9801325 A	20-08-1998 20-08-1998 09-09-1998 08-12-1998 08-09-1998
