



(86) **Date de dépôt PCT/PCT Filing Date:** 2011/09/15  
 (87) **Date publication PCT/PCT Publication Date:** 2012/03/22  
 (45) **Date de délivrance/Issue Date:** 2019/01/15  
 (85) **Entrée phase nationale/National Entry:** 2013/03/11  
 (86) **N° demande PCT/PCT Application No.:** NO 2011/000254  
 (87) **N° publication PCT/PCT Publication No.:** 2012/036562  
 (30) **Priorité/Priority:** 2010/09/15 (NO20101289)


(51) **Cl.Int./Int.Cl. A63C 9/086** (2012.01),  
**A63C 9/08** (2012.01), **A63C 9/20** (2012.01)

(72) **Inventeurs/Inventors:**  
WOLLO, EVEN, NO;  
HOLM, THOMAS, NO;  
SVENDSEN, OYVAR, NO;  
PETTERSEN, AKSEL, NO

(73) **Propriétaire/Owner:**  
ROTTEFELLA AS, NO

(74) **Agent:** BORDEN LADNER GERVAIS LLP

(54) **Titre : FIXATION DE SKI DE RANDONNEE OU DE SKI DE FOND**  
 (54) **Title: TOURING OR CROSS-COUNTRY SKI BINDING**



(57) **Abrégé/Abstract:**

The present invention relates to a ski binding that requires fewer parts, that is easier to assemble, and that has a reliable release mechanism compared with conventional bindings. Such ski binding comprises: an engagement section (2.1), that pivotally

**(57) Abrégé(suite)/Abstract(continued):**

engages a ski shoe engagement pin (21), including stationary (4) and movable (5) engagement parts; the movable part (5) being a slider in sliding engagement with the stationary engagement part (4); an activation element (6) for moving the movable part (5) between locking and releasing positions of the engagement pin; and a downwards pointing button (6.2) arranged on the activation element (6) to directly engage an opening (5.3) in the movable engagement part, whereby when a downwards force is applied to the activation element (6) at a position behind the fulcrum pins (6.1), the movable part (5) slides forward into the releasing position.

## ABSTRACT

The present invention relates to a ski binding that requires fewer parts, that is easier to assemble, and that has a reliable release mechanism compared with conventional bindings. Such ski binding comprises: an engagement section (2.1), that pivotally engages a ski shoe engagement pin (21), including stationary (4) and movable (5) engagement parts; the movable part (5) being a slider in sliding engagement with the stationary engagement part (4); an activation element (6) for moving the movable part (5) between locking and releasing positions of the engagement pin; and a downwards pointing button (6.2) arranged on the activation element (6) to directly engage an opening (5.3) in the movable engagement part, whereby when a downwards force is applied to the activation element (6) at a position behind the fulcrum pins (6.1), the movable part (5) slides forward into the releasing position.

## Touring or cross-country ski binding

The present invention relates to an improved ski binding for touring or cross-country skiing and a method of assembling the same.

5

As is well known by any manufacturer of ski bindings, as well as most users of ski bindings, a ski binding should comprise of as few functional parts as possible to functionally flawless in use when exposed to repetitive stress, snow, ice and water entering and freezing within the binding.

10

Moreover, less functional parts allows easier assembly and lower production cost of the binding. To further reduce production cost while simultaneously offering a high quality binding to a customer at acceptable sale price, is it advantageously to allow most or all of the assembly of the parts of the binding to be performed in a fully automatic process.

15

The fewer manual operations required, the less expensive the binding becomes.

Currently there exists a very large amount of ski bindings on the market, and a substantial number of these bindings is based on the well-known NNN norm, i.e. for use with ski shoes that has a transversal engagement pin mounted underneath the front of the sole of the ski shoe, the binding engaging the engagement pin at either end of the engagement pin or parts of the engagement pin. Several of these ski bindings is constructed in a way that requires several manual and/or complicated automated operations to able to assemble the different parts of the binding. In particular, in an automated assembly operation it is disadvantageous to allow operations performed from different directions, i.e. some operation in a vertical direction, some in a horizontal direction as well as at an angle relative to these directions. Also, rotating an constructional part or element could complicate or add further complexity or cost of the required equipment. Operations in several directions to assemble parts could therefore include joining certain parts either manual or in different position prior to the in-line part assembly.

30

Thus, an object of the present invention is to provide a ski binding that comprises construction parts or elements that are easy to assemble; that has a simple, yet reliable release mechanism with improved release-element functionality; that provides an improved shoe fixing member; and offers an easy method to assemble the parts.

35

The following non-exclusive list over references to prior art is listed to illustrate some of the disadvantages of the prior art that the present intentions aims at solving. US 5,338,053; EP 1,848,516 B1 and WO 04/050197A1 all relate to a ski binding that requires more constructional parts that envisaged and offered by the present invention, and that further requires that the constructional parts are mounted from different directions.

To illustrate prior art release mechanisms having a release button and a shoe fixing element it is referred to EP 1,848,516 B1; US 5,092,620; US 6,957,827; US 4,997,199; US 4,915,405; US 4,616,843 and US 6,412,808. Another reference to prior art relating to a snowboard binding is US 6,290,250. These prior art references either include an element that transfers the force between a locking button and a locking slider, or an additional locking element that secures the shoe in the binding and wherein such an locking element in turn is operated by the locking slider by activation of the locking element.

US 5,092,620; US 6,957,827; US 6,623,027; US 4,616,843 and WO 04/050197 A1 relates to the aspect regarding a locking slider of a ski binding.

In one aspect, the present invention provides touring or cross-country binding comprising:

an engagement section (2.1) for pivotal engagement of a ski shoe engagement pin (21), the engagement section including a stationary engagement part (4) and a movable engagement part (5); the stationary engagement part (4) comprising a base (4.1) and a pair of protruding elements (4.2), wherein a distal part of the protruding elements (4.2) are provided with a recess (4.3) adapted to receive the ski shoe engagement pin; and

the movable engagement part (5) is a slider in sliding engagement with the stationary engagement part (4);

an activation element (6) adapted to move the movable engagement part (5) between a locking position and a releasing position of the engagement pin; and

a downwards pointing button (6.2) arranged on the activation element (6) to directly engage an opening (5.3) in the movable engagement part, whereby the movable engagement part (5) slides forward to the releasing position by a downwards force on the activation element (6) at a position behind the fulcrum pins (6.1) of the activation element, wherein the stationary engagement part (4) is positioned below the movable engagement part (5) and rests on a first housing section (7), whereby a front area of the movable engagement part (5) slides on top of the bottom of the first housing section (7), and a rear area of the movable engagement part (5) slides on the stationary engagement part (4).

In a further aspect, the present invention provides a method for assembling functional parts of a touring or cross country ski binding to provide a binding for releasable engagement with an engagement means of a ski shoe, comprising the steps of:

- a) providing a first housing section (7);
- b) positioning, by a downwards vertical motion, one end of a spring (8) against an abutment (7.5) of a first housing section (7), whereby the spring extends in longitudinal direction of the first housing section (7);
- c) positioning, by downwards vertical motion, a stationary (4) and a movable (5) engagement part on a bottom (7.1) of the first housing section (7), whereby the movable engagement part (5) is arranged in sliding engagement with guides (7.4) of the first housing section and in abutment with a second end of the spring (8);
- d) positioning by a downwards vertical motion, an activation element (6) on the first housing section (7), whereby a downwards pointing button (6.2) of the activation element (6) is arranged in abutment with an opening (5.3) in front of the movable engagement part (5); and
- e) connecting by a downwards vertical motion, a second housing section (9) on the first housing section (7) by means of an interlocking snap connection.

An aspect of the present invention relates to a touring or cross-country binding comprising:

- 5           - an engagement section 2.1 for pivotal engagement of a ski shoe engagement pin 21, the engagement section including a stationary engagement part 4 and a movable engagement part 5; the stationary engagement part 4 comprising a base 4.1 and a pair of protruding elements 4.2, wherein the distal part of the protruding elements 4.2 are provided with a recess 4.3 adapted to receive the ski shoe engagement pin; and the movable engagement part 5 is a slider in sliding engagement with the stationary engagement part 4;
- 10          - an activation element 6 adapted to move the movable engagement part 5 between a locking position and a releasing position of the engagement pin; and
- 15          - a downwards pointing button 6.2 arranged on the activation element 6 to directly engage an opening 5.3 in the movable engagement part, whereby the movable engagement part 5 is sliding forward to the releasing position by a downwards

force on the activation element 6 at a position behind the fulcrum pins 6.1 of the activation element.

Further, the present invention relates to a ski binding as disclosed above having  
5 alternative features, wherein:

- wherein at least one locking element 5.1 is arranged on the movable engagement part  
5 in the locking position co-operating with the recesses 4.3 to provide a means for  
locking the engagement pin 21; and the at least one locking element 5.1 in the releasing  
10 position is displaced from the recesses 4.3 in the lengthwise direction of the binding.

- wherein a spring 8 is arranged between an abutment 7.5 at the bottom 7.1 of a first  
housing section 7 and an abutment 5.4 on the movable engagement part 5 to provide  
spring loading of the movable engagement part 5 and the activation element 6.

15 - wherein the stationary engagement part 4 is positioned below the movable engagement  
part 5 and rests on a first housing section 7, whereby the movable engagement part 5 at  
its front area is sliding on top of the bottom of the first housing section 7, and at its rear  
area is sliding on the stationary engagement part 4.

20 - wherein the stationary engagement part 4 is positioned above the movable engagement  
part 5, and the stationary engagement part 4 have feet or other fastening means  
engaging the bottom of a first housing section 7, whereby the movable engagement part  
5 on its underside is sliding on the bottom of the first housing section 7 and on the upper  
25 surface on the rear area is in sliding connection with an underside of the stationary  
engagement part 4.

- wherein a second housing section 9 is provided, the second housing section adapted to  
interlocking snap connection with the first housing section 7.

30 - wherein the front area of the second housing section 9 is provided with two recesses  
9.1 constituting a pivotal engagement with the upper part of the fulcrum pins 6.1.

- wherein the second housing section 9 is provided with an opening 9.2 to accommodate  
35 the pair of protruding elements 4.2 and the at least one locking element 5.1.

-wherein wherein a first housing section 7 is adapted to releasable and adjustable snap fastening on a base element 1.1, the base element 1.1 being fixed to, or integrated with a ski 1.

5 -wherein at least one resilient element 10;11 is fastenable to the second housing section 9, where at least one resilient element is fastened, respectively in front of 10, or behind 11 the engagement section 2.1 for pivotal engagement of the ski shoe.

- wherein the front resilient element 10 is fastenable to the second housing section 9 from underneath the second housing section 9.

10 - wherein the back resilient element 11 is fastenable to the second housing section 9 from above the second housing section 9.

- wherein the first housing section 7, the spring 8, the stationary engagement part 4, the movable engagement part 5, the activation element 6, and the second housing section 9 all are assembled by successive vertical directed mounting steps.

15 Further the invention relates to a method for assembling functional parts of a touring- or cross country ski binding to provide a binding for releasable engagement with an engagement means of a ski shoe, comprising the steps of:

- a) providing a first housing section 7;
- b) positioning, by a downwards vertical motion, one end of a spring 8 against an abutment 7.5 of the first housing section 7, whereby the spring extends in longitudinal  
20 direction of the first housing section 7;
- c) positioning, by downwards vertical motions, the stationary 4 and movable 5 engagement parts on a bottom 7.1 of the first housing section 7, whereby the movable engagement part 5 is arranged in sliding engagement with guides 7.4 of the first housing section and in abutment with the second end of the spring 8;
- 25 d) positioning, by a downwards vertical motion, an activation element 6 on the first housing section 7, whereby a downwards pointing button 6.2 of the activation element 6 is arranged in abutment with an opening 5.3 in front of the movable engagement part 5; and
- e) connecting by a downwards vertical motion, a second housing section 9 on the first  
30 housing section 7 by means of an interlocking snap connection.

## 5

The method can further comprise one or more steps:

- wherein step d) further comprises: positioning fulcrum pins 6.1 of the activation element 6 in bearing surfaces 7.3 on a pair of side elements 7.2 extending from the first housing section 7.

5 -wherein step c) comprises positioning the stationary engagement part 4 prior to positioning the movable engagement part 5.

-wherein step c) comprises position the movable engagement part 5 prior to positioning the stationary engagement part 4.

10 -wherein a resilient element 10 is positioned by a downwards vertical motion on top of the stationary and movable engagements parts 4,5 prior to performing step e).

- wherein a resilient element 10 is positioned in an opening 9.2 of the second housing section 9 prior to performing step e).

15 The invention will no be described in further detail by way of exemplary illustrations herein below. However, it is envisaged that the shape and constructive design of one or more of the parts to be assembled may be modified shape wise without influencing the function and the assembly steps of the binding.

20 Fig. 1 illustrates a complete ski binding mounted on a ski by a binding attachment base-element according to the present invention;

Fig. 2 illustrates a front and back section of the ski binding of Fig. 1;

Fig. 3 is an exploded view of the ski binding sections of Fig. 2;

Figs. 4a and 4b are top views of the ski binding sections of Fig. 2;

Figs. 5a and 5b are side views of the ski binding sections of Fig. 2;

25 Figs. 6a and 6b are bottom views of the ski binding sections of Fig. 2;

Fig. 7 illustrates the cross section VII-VII of Fig. 4a;

Figs. 8 and 9 are front and back views of the ski binding section of Figs. 4a, 5a and 6a;

Fig. 10 is a perspective view of the top and a first side of the release- and locking mechanism in the front section of the ski binding according to the present invention;

30 Fig. 11 is a perspective view of the top and the second side of the release- and locking mechanism of Fig. 10 according to the present invention, and illustrates the locking slide in a released, non-locking position;

Fig. 12 is a perspective view of the top and the second side of the release- and locking mechanism as illustrated in Fig.10 according to the present invention, and illustrates the locking slide in a locking position.

Figs. 13 and 14 illustrates one operational aspect of the release- and locking mechanism part of the of the front section of the ski binding according to the present invention.

Figs. 15 and 16 illustrates the cross sections XV-XV and XVI-XVI of Fig. 4a, and illustrates a second operational aspect of the release- and locking mechanism of the front section of the ski binding according to the present invention;

Figs. 17 and 18 represents a modification of the embodiment as illustrated in Figs. 3, 7 and 10 – 16;

Fig. 19 is a perspective view of the top and front of the locking mechanism part of Fig.10 according to the present invention and illustrates the locking slider in a locked position;

Fig. 20 is a perspective view of the top and backside of the locking mechanism part of Fig. 10 according to the present invention and illustrates the locking slider in a locking position;

Fig. 21 illustrates a complete ski binding mounted on a ski binding attachment base-element according to the present invention, where the sole of a ski shoe is in a lifted position and locked to the binding.

Figure 1 illustrates a ski binding 2,3 fixed to the upper surface of a ski 1, where the ski binding comprises a front element having an engagement section 2.1 for pivotal engagement of a ski shoe engagement pin 21, and a rear binding element 3 for engagement with a slit in the underside of the heel of the ski shoe. The front and rear elements of the ski binding also appears from figure 2. The ski has on its upper surface a ski binding fastening base element 1.1, e.g. a so called NIS-plate<sup>TM</sup>, to which the front and rear binding elements 2,3 can be releasable fastened by snap fastening. Also, by utilizing such an element 1.1 adjustable positioning of the elements 2,3 along the ski becomes possible to adjust to the ski shoe size and the substantially vertical load on the ski. The base element 1.1 can be fastened to or integrated with a ski 1. Alternatively, could the elements 2,3 be fastened to the ski by use of regular screws or other fastening means could be used.

Now with reference to figure 3 showing an exploded view of the ski binding. The engagement section 2.1 of the binding includes a first stationary engagement part 4 and a movable engagement part 5. A spring-loaded activation element 6 is also provided to move the movable engagement part 5 between a locking position and a release position

## 7

of the ski shoe. Further, a first housing section 7 exists having a bottom 7.1 and a pair of side elements 7.2 extending from the bottom 7.1 and providing bearing surfaces 7.3 for the fulcrum pins 6.1 of the activation element 6.

5 The stationary engagement part 4 includes a base 4.1 and a pair of protruding elements 4.2, which at top have recesses 4.3 to provide the engagement section 2.1, as shown in more detail in figure 10-20.

The movable engagement part 5 is a slider in sliding engagement with the stationary  
10 engagement part 4 and in sliding engagement with slider guides 7.4 of the first housing section 7. The movable engagement part 5 includes at a rear area thereof a pair of protruding locking elements 5.1, e.g. hook shaped elements, extending from a base 5.2 of the movable engagement part 5. Each locking element 5.1 in locking position for the movable engagement part 5 is positioned sideways in relation to adjacent recess 4.3 on  
15 the stationary engagement section 4 to provide in co-operation with said recess 4.3 a means for locking the engagement pin 21, see figure 11, 13, 15, 17 and 20. Each locking element 5.1 in ski shoe releasing position of the movable engagement part 5 is positioned forward in relation to the adjacent recess 4.3 of the stationary engagement part 4, that is, displaced from the recess 4.3 in the lengthwise direction of the binding,  
20 see figures 12, 14, 16 and 18.

Activation element 6 includes a button 6.2 extending downwards to directly engage an forward positioned opening 5.3 in the slider, whereby the slider 5 is slided forward to a releasing position by a downwards pushing operation on the activation element 6 at a  
25 position behind its fulcrum pins 6.1. A lower edge 6.4 of each sidewall of the activation element, at a position below the fulcrum pins 6.1, is curved. The curved lower edge 6.4 sits on a neighboring surface of the base 5.2 of the slider shaped movable engagement part 5 to reduce the stress on the fulcrum pins 6.1.

30 A spring 8 is positioned between an abutment 7.5 at the bottom 7.1 of the first housing section 7 and an abutment 5.4 on the slider shaped movable engagement part 5 to provide spring loading of the movable engagement part 5 and the activation element 6.

35 As illustrated in figure 3 and 10-16, the stationary engagement part 4 is positioned under the slider shaped movable engagement part 5 and rests on the bottom 7.1 of the first housing section, whereby the movable engagement part 5 at its front area is sliding

on top of the bottom 7.1 of the first housing section 7 and at its rear area slides on top of the stationary engagement section 4.

In the alternative illustrated in figure 17 and 18, the stationary engagement part 4 is positioned above the slider shaped movable engagement section 5, and the stationary engagement section 4 has feet or other types of fastening means (not clearly shown) resting on the bottom 7.1 of the first housing section 7, whereby the movable engagement part 5 on its underside is sliding on the bottom 7.1 of the first housing section 7 and with its upper surface of its rear area sliding connects with a underside surface of the stationary engagement part 4.

The element 6 acts as a release mechanism, and due to the button 6.2 co-operating with opening 5.3 of the movable engagement part 5, and the part 5 is spring-loaded by the spring 8, element 6 is also spring-loaded. It should be noted that the outside of engagement pocket 7.5 constitute one of the guides 7.4 for part 5.

An important aspect of the present invention is that element 6 is arranged to directly exert a force on the movable engagement section 5, that in reality constitutes a ski shoe fastening element.

By activation of the release element 6 by exertion of a release force, e.g. by utilizing the pointed end of a ski pole; on position 6.2, is a substantial stress applied the fulcrum pins 6.1 from the bearing surfaces 7.3 on the side elements 7.2 provided a remedy is provided to reduce such stress. To avoid breakage in the release mechanism, i.e. fulcrum pins 6.1, as a result of substantial vertical release force, represents the provision of the curved bottom edge 6.4 to ride the adjacent surface of the base 5.2 of the slider shaped movable engagement part 5, that the vertically directed stress component exerted on the fulcrum pins is substantially reduced, and the smaller stress component working in the vertical direction on the fulcrum pins, will have an acceptable value. Hence, the stress exerted on the fulcrum pins will be within fully acceptable limits. The risk of malfunction is with that removed. It should also be envisaged that when element 6 via its button 6.2 displaces the movable engagement part 5 in a forwards direction, the curved bottom edge 6.4 by frictional contact with the base 5.2 of the part 5 assist the operation of the button 6.2.

Figure 21 illustrates the sole of a ski shoe or ski boot wherein the front area of the sole comprises an engagement pin 21 attached to the ski binding 2, whereby the engagement pin is lies in the engagement section 2.1 and is locked by locking element 5.1.

As indicated in the exploded view of figure 3 is a second housing part 9 provided, the second housing section 9 being adapted to snap connection from above on the first housing section 7. The second housing section 9 has at a front area thereof a pair of recesses 9.1 for pivotal engagement with an upper part of the fulcrum pins 6.1. The second housing section 9, at the position of the protruding elements 4.2, 5.1 of the stationary and movable engagement parts 4, 5, an opening 9.2. The second housing section 9 effects that the fulcrum pins 6.1 of the element 6 is limited in upwards movement, and also effects that the stationary and movable engagement element 5, 6 is limited in upwards movement.

At least one resilient elements 10, 11 is fastenable to the second housing section 9, where at least one resilient element is fastenable in front of or behind the engagement section 2.1 for pivotal engagement of the ski shoe. The front resilient elements 10 is preferably fastenable to the second housing section 9 from underneath the second housing section 9, by utilizing pins on the underside of the element 10 to engage holes in flanges of element 10.

The behind, or rear, resilient element 11 is fastenable to the second housing section from above by snap connection. The resilient elements 10, 11 is present to provide backwards and forwards biasing, respectively, of the rotation of the ski shoe. In addition the resilient element 10, 11 aids to keep snow from entering the inner part of the ski binding.

The elements 12, 13 in figure 3 is only plates of decorative and cover purposes and have no further functionality.

As is understood from viewing figure 3, the first housing section 7, the stationary engagement part 4, the movable engagement part 5, the spring 8, the activation element 6, and the second housing section 9, all capable of being assembled by successive vertical directed mounting steps. To further explain the method steps of assembly of the functional parts of the touring- and cross-country ski binding, according to the present invention, comprises the following steps:

- a) providing the first housing section 7;
- b) downwards vertical moving one end of a spring 8 against an abutment 7.5 of the first housing section 7, whereby the spring extends in longitudinal direction of the first housing section 7;

- c) positioning, by downwards vertical motions, the stationary 4 and movable 5 engagement parts on the bottom 7.1 of the first housing section 7, whereby the movable engagement part 5 is arranged in sliding engagement with guides 7.4 of the first housing section and in abutment with the second end of the spring 8;
- 5 d) positioning, by a downwards vertical motion, the activation element 6 on the first housing section 7, whereby the downwards pointing button 6.2 of the activation element 6 is arranged in abutment with the opening 5.3 in front of the movable engagement part 5; and
- e) connecting by a downwards vertical motion, the second housing section 9 on the first  
10 housing section 7 by means of an interlocking snap connection.

An important aspect of the method disclosed above is the fact that the ski binding can be assembled for one side only, and mainly in the same inserting direction. As such, the ski binding of the present invention can also be assembled by following steps:

- 15 a) providing and turning the second housing section 7 upside down;
- b) positioning, by a downwards vertical motion, the activation element 6 on the second housing section 9, thereby positioning the fulcrum pins 6.1 of the activation element into the recesses 9.1 of the second housing section, and the downwards (that is, as long as the second housing section is upside down, actually pointing upwards) pointing  
20 button 6.2 of the activation element 6 is arranged in abutment with the opening 5.3 in front of the movable engagement part 5;
- c) positioning, by downwards vertical motions, the stationary 4 and movable 5 engagement parts on the underside of the second housing section, whereby the pair of protruding elements 4.2 and the at least one locking element 5.1 is accommodated in the  
25 opening 9.2 of the second housing section 9;
- d) downwards vertical moving one end of a spring 8 against the abutment 5.4 of the movable engagement part 5, whereby the springs in longitudinal direction of the second housing section 9;
- e) connecting by a downwards vertical motion, the first housing section 7 on the second  
30 housing section 9 by means of an interlocking snap connection, whereby the movable engagement part 5 is arranged in sliding engagement with guides 7.4 of the first housing section and in abutment with the second end of the spring 8.

Step c) of either of the above disclosed methods comprises positioning the stationary  
35 engagement part 4 prior to providing the movable engagement part 5, as illustrated in figures 3 and 10-16.

In an alternative, as also explained above with reference to the figures 17 and 18, can step c) comprise positioning the movable engagement part 5 prior to positioning the stationary engagement part 4.

- 5 As disclosed above, according to the first method the resilient element 10 is inserted from below in front of the engagement section 2.1 in the opening 9.2 of the second housing section 9 prior to performing step e), and the element can have holes adapted for tight fitting on pins on underneath the second housing section 9.
- 10 It is envisaged that if the ski binding is assembled manually, then no tools are required to perform the operations. If the operations is automated by use of robots, then no sophisticated tools are required. Figures 4a-9 are merely attached to illustrate how the invention can be utilized industrially, with additional guidance from the exploded view of figure 3, and the detail of the release- and ski boot fastening mechanism illustrated in
- 15 figures 10-21.

**CLAIMS:**

1. Touring or cross-country binding comprising:
  - an engagement section (2.1) for pivotal engagement of a ski shoe engagement pin (21), the engagement section including a stationary engagement part (4) and a movable engagement part (5); the stationary engagement part (4) comprising a base (4.1) and a pair of protruding elements (4.2), wherein a distal part of the protruding elements (4.2) are provided with a recess (4.3) adapted to receive the ski shoe engagement pin; and the movable engagement part (5) is a slider in sliding engagement with the stationary engagement part (4);
  - an activation element (6) adapted to move the movable engagement part (5) between a locking position and a releasing position of the engagement pin; and
  - a downwards pointing button (6.2) arranged on the activation element (6) to directly engage an opening (5.3) in the movable engagement part, whereby the movable engagement part (5) slides forward to the releasing position by a downwards force on the activation element (6) at a position behind the fulcrum pins (6.1) of the activation element,
  - wherein the stationary engagement part (4) is positioned below the movable engagement part (5) and rests on a first housing section (7), whereby a front area of the movable engagement part (5) slides on top of the bottom of the first housing section (7), and a rear area of the movable engagement part (5) slides on the stationary engagement part (4).
2. The binding according to claim 1, wherein the binding further comprises at least one locking element (5.1) arranged on the movable engagement part (5) in the locking position cooperates with the recesses (4.3) to provide a means for locking the engagement pin (21); and the at least one locking element (5.1) in the releasing position is displaced from the recesses (4.3) in the lengthwise direction of the binding.
3. The binding according to claim 1, wherein the binding further comprises a spring (8) arranged between an abutment (7.5) at the bottom (7.1) of a first housing section (7) and an

abutment (5.4) on the movable engagement part (5) to provide spring loading of the movable engagement part (5) and the activation element (6).

4. The binding according to claim 1 or 2, wherein a second housing section (9) is provided, the second housing section adapted for interlocking snap connection with the first housing section (7).

5. The binding according to claim 3, wherein a second housing section (9) is provided, the second housing section adapted for interlocking snap connection with the first housing section (7).

6. The binding according claim 4 or 5, wherein a front area of the second housing section (9) is provided with two recesses (9.1) constituting a pivotal engagement with the upper part of the fulcrum pins (6.1).

7. The binding according to claim 4 or 5, wherein the second housing section (9) is provided with an opening (9.2) to accommodate the pair of protruding elements (4.2) and the at least one locking element (5.1).

8. The binding according to claim 1, wherein the first housing section (7) is adapted for releasable and adjustable snap fastening on a base element (1.1), the base element (1.1) being fixed to, or integrated with a ski (1).

9. The binding according to claim 4 or 5, wherein at least one resilient element (10;11) is fastenable to the second housing section (9), where at least one resilient element is fastened, respectively in front of (10), or behind (11) the engagement section (2.1) for pivotal engagement of the ski shoe.

10. The binding according to claim 9, wherein the at least one resilient element (10) is fastened in front of (10) the engagement section (2.1), and is fastenable to the second housing section (9) from underneath the second housing section.

11. The binding according to claim 9, wherein the at least one resilient element (11) is fastened behind (11) the engagement section (2.1), and is fastenable to the second housing section (9) from above the second housing section (9).

12. The binding according to claim 5, wherein the first housing section (7), the spring (8), the stationary engagement part (4), the movable engagement part (5), the activation element (6), and the second housing section (9) all are assembled by successive vertical directed mounting steps.

13. A method for assembling functional parts of a touring or cross country ski binding to provide a binding for releasable engagement with an engagement means of a ski shoe, comprising the steps of:

a) providing a first housing section (7);

b) positioning, by a downwards vertical motion, one end of a spring (8) against an abutment (7.5) of a first housing section (7), whereby the spring extends in longitudinal direction of the first housing section (7);

c) positioning, by downwards vertical motion, a stationary (4) and a movable (5) engagement part on a bottom (7.1) of the first housing section (7), whereby the movable engagement part (5) is arranged in sliding engagement with guides (7.4) of the first housing section and in abutment with a second end of the spring (8);

d) positioning by a downwards vertical motion, an activation element (6) on the first housing section (7), whereby a downwards pointing button (6.2) of the activation element (6) is arranged in abutment with an opening (5.3) in front of the movable engagement part (5);

and

e) connecting by a downwards vertical motion, a second housing section (9) on the first housing section (7) by means of an interlocking snap connection.


14. The method according to claim 13, wherein step d) further comprises positioning fulcrum pins (6.1) of the activation element (6) in bearing surfaces (7.3) on a pair of said elements (7,2) extending from the first housing section (7).

15. The method according to claim 13 or 14, wherein step c) comprises positioning the stationary engagement part (4) prior to positioning the movable engagement part (5).

16. The method according to claim 13, 14, or 15, wherein step e) comprises positioning the movable engagement part (5) prior to positioning the stationary engagement part (4).

17. The method according to claim 13, 14, or 15, wherein a resilient element (10) is positioned by a downwards vertical motion on top of the stationary and movable engagements parts (4,5) prior to performing step e).

18. The method according to claim 13, 14, or 15, wherein a resilient element (10) is positioned in an opening (9.2) of the second housing section (9) prior to performing step e).








Fig. 2



3/13

Fig. 3







Fig. 5a




Fig. 5b




Fig. 6a




Fig. 6b




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19





Fig. 20



13/13

Fig. 21

