



(19) **United States**

(12) **Patent Application Publication**  
**Anderton et al.**

(10) **Pub. No.: US 2010/0301134 A1**

(43) **Pub. Date: Dec. 2, 2010**

(54) **MOBILE FLUID DISTRIBUTION SYSTEM AND METHOD**

**Publication Classification**

(75) Inventors: **Peter W. Anderton**, Peoria, IL (US); **Gary A. Ellertson**, Pleasant Prairie, WI (US)

(51) **Int. Cl.**  
**E01H 3/02** (2006.01)  
**B05B 1/14** (2006.01)  
**B05B 1/30** (2006.01)

Correspondence Address:  
**Caterpillar Inc.**  
**Intellectual Property Dept.**  
**AH 9510, 100 N.E. Adams Street**  
**PEORIA, IL 61629-9510 (US)**

(52) **U.S. Cl. .... 239/172; 239/557; 239/562; 239/569**

(73) Assignee: **Caterpillar Inc.**, Peoria, IL (US)

(57) **ABSTRACT**

(21) Appl. No.: **12/643,833**

A fluid distribution system and method for mobile applications. The system includes a power source, a pump driven by the power source, and a motor driven by the pump. The system also includes a spray head with a fluid inlet passage, a fluid outlet passage, a fluid piston disposed in a chamber for controlled access between the inlet and outlet passages and defining a variable orifice, and a hydraulic cylinder controllably engaged to the orifice. The fluid piston and the hydraulic cylinder are aligned with a common longitudinal axis, and the inlet passage is offset from the axis in a direction opposed to the location of the outlet passage.

(22) Filed: **Dec. 21, 2009**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 12/472,415, filed on May 27, 2009.

100




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6







FIG. 7




# FIG. 8









**FIG. 9**




**FIG. 9A**



**FIG. 9B**



**FIG. 10A**



**FIG. 10B**




FIG. 11

**MOBILE FLUID DISTRIBUTION SYSTEM AND METHOD**

[0001] This application is a continuation-in-part of U.S. patent application Ser. No. 12/472,415, entitled “MOBILE FLUID DISTRIBUTION SYSTEM AND METHOD”, filed May 27, 2009.

**TECHNICAL FIELD**

[0002] This disclosure relates generally to a system and method for fluid distribution and, more particularly, to a system and method for controlled distribution of a fluid in a mobile environment.

**BACKGROUND**

[0003] Fluid distribution systems, in particular mobile fluid distribution systems, are used in a variety of applications. For example, at mining and construction sites, it is common to use mobile fluid distribution systems to spray water over routes and work areas to minimize the creation of dust during operations. A specific example might include a water truck that sprays water over roads at a mine site.

[0004] Other applications of mobile fluid distribution systems may include spraying of pesticides and herbicides, e.g., for agricultural use, disbursement of saline solutions on roads for snow and ice control, fire suppression, and the like.

[0005] For various reasons, such as cost and consistent fluid application, it is desired to maintain control of the amount and pattern of fluids being distributed, in particular with regard to maintaining a uniform and consistent application of fluid per unit of area. For example, when spraying water on mine roads, it may be desired to uniformly distribute the water over the road surface to avoid applying excess water in specific locations.

[0006] Typical fluid distribution systems spray fluids at flows that are directly proportional to engine speeds of the mobile machines. Operators attempt to keep the fluid flow relatively constant by maintaining constant engine speeds, at least to the extent possible. These efforts typically require operating mobile machines at reduced transmission gear ratios to maintain desired engine speeds. However, these efforts cannot be maintained, for example, when ascending or descending steep inclines, conditions which generally require changing engine speeds. The spray head’s spray pattern changes as the flow changes, making it difficult for an operator to distribute the desired fluid per unit of area without causing spray overlap, often significant in nature, from multiple spray heads that causes poor traction conditions.

[0007] Efforts have been made to maintain fluid flow in proportion to machine speed, i.e., ground speed, rather than engine speed. Although this has resulted in improved fluid distribution per unit area, it is still difficult to maintain precise control during various operating maneuvers, such as starting and stopping, and as operating conditions vary. Furthermore, many of these systems still distribute fluids in proportion to fluid flow, which adds to the difficulty of consistent application per unit of area.

[0008] One example of an attempt to achieve uniform fluid application is described in U.S. Pat. No. 5,964,410 to Brown et al. (the Brown patent). Brown employs spray heads with variable orifices to attempt maintenance of constant velocities and exit flow trajectories. The spray heads are pressure con-

trolled, however, relying on pressure of the fluid being sprayed to overcome a spring force to open the spray nozzle. Furthermore, the components that are used to control the nozzle are located in the main fluid flow chamber, and thus are susceptible to corrosion and contamination by particles and debris in the fluid. As a result, the system would still have difficulty achieving consistent application of the fluid per unit of area during various operating conditions.

[0009] The present disclosure is directed to overcoming one or more of the problems as set forth above.

**SUMMARY**

[0010] In one aspect of the present disclosure a fluid distribution system is disclosed. The system includes a power source, a pump driven by the power source, and a motor driven by the pump. The system also includes a spray head with a fluid inlet passage, a fluid outlet passage, a fluid piston disposed in a chamber for controlled access between the inlet and outlet passages and defining a variable orifice, and a hydraulic cylinder controllably engaged to the orifice. The fluid piston and the hydraulic cylinder are aligned with a common longitudinal axis, and the inlet passage is offset from the axis in a direction opposed to the location of the outlet passage.

[0011] In another aspect of the present disclosure a method for distributing a fluid is disclosed. The method includes determining a ground speed of a mobile machine, determining a flow of fluid being delivered to a spray head having a variable orifice, comparing the determined flow to a desired fluid flow, controlling a motor to maintain the desired fluid flow, and controlling the variable orifice as a function of the ground speed and independent of fluid flow to maintain a desired spray pattern to provide a consistent and uniform distribution of fluid.

[0012] In yet another aspect of the present disclosure a spray head for a fluid distribution system is disclosed. The spray head includes a fluid inlet passage, a fluid outlet passage, a fluid piston disposed in a chamber for controlled access between the inlet and outlet passages and defining a variable orifice, and a hydraulic cylinder controllably engaged to the orifice. The fluid piston and the hydraulic cylinder are aligned with a common longitudinal axis, and the inlet passage is offset from the axis in a direction opposed to the location of the outlet passage.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0013] FIG. 1 is a diagrammatic illustration of a mobile machine suited for use with the present disclosure;

[0014] FIGS. 2A and 2B are diagrammatic views of a spray head suited for use with the present disclosure;

[0015] FIG. 3 is a cut-away view of the spray head of FIGS. 2A and 2B;

[0016] FIG. 4 is a representative block diagram of a fluid distribution system;

[0017] FIGS. 5A and 5B are representative diagrams of a hydraulic system suited for use with the fluid distribution system of FIG. 4;

[0018] FIG. 6 is a flow diagram depicting a method of the present disclosure;

[0019] FIG. 7 is a flow diagram depicting another method of the present disclosure; and

[0020] FIG. 8 is a diagrammatic representation of an operator control suited for use with the present disclosure.

[0021] FIGS. 9A and 9B are perspective illustrations of a spray head of the present disclosure

[0022] FIGS. 10A and 10B are cross-sectional illustrations of the spray head of FIGS. 9A and 9B.

[0023] FIG. 11 is an expanded view of the spray head of FIGS. 9A and 9B.

#### DETAILED DESCRIPTION

[0024] Referring to the drawings, a mobile fluid distribution system 100 and method for distributing fluids is shown.

[0025] Referring to FIG. 1 in particular, a mobile machine 102 suited for use for distributing fluids is depicted. The mobile machine 102 of FIG. 1 is shown as a truck, i.e., typical for use in off-highway applications, converted for use to distribute fluids. However, other types of mobile machines may be employed, for example, articulated trucks, on-highway trucks, tractor-scrapers, tractors in combination with trailers, and the like.

[0026] Although not labeled as such in FIG. 1, the mobile machine 102 is fitted with a fluid tank (element 430 in FIG. 4), and is shown with a variety of piping, hoses, pumps and valves for fluid distribution purposes. In particular, the mobile machine 102 in FIG. 1 is shown as an off-highway truck configured as a water truck for spraying water at a work site that typically generates much dust during work operations. The present disclosure, however, may also apply to other types of mobile machines set up to distribute water or other types of fluids in a wide variety of applications. For example, a tractor pulling a trailer may be used to distribute chemicals in agricultural settings, an on-highway truck may be configured to spray a saline solution on roads, runways, or parking lots to melt snow and ice, and other varieties of applications and setups may be used.

[0027] FIGS. 2A and 2B illustrate views of a spray head 200 that may be used with the present disclosure. As shown more clearly and in more detail in FIG. 3, the spray head 200 may be assembled in relation to a longitudinal axis 312 for reference purposes. For example, the spray head 200 includes a fluid inlet passage 302 and a fluid outlet passage 304. The outlet passage 304 may be located at a position offset from the longitudinal axis 312. The inlet passage 302 may be located at a position offset from the longitudinal axis 312 and in a direction opposed to the location of the outlet passage 304. The location of the inlet passage 302 relative to the location of the outlet passage 304, i.e., on opposite sides of the longitudinal axis 312, may contribute to providing a laminar flow of fluid from the spray head 200. Such laminar flow may result in a flat spray pattern having droplets of a minimal size large enough to achieve reduced atomization of the fluid. In a water truck example, this may contribute to optimal fluid control from the spray head 200 to a desired surface during mobile spraying.

[0028] A fluid piston 306 disposed in a chamber 307 of the spray head 200 defines a variable orifice 308 and may provide controlled access between the inlet passage 302 and the outlet passage 304. Movement of the fluid piston may be controlled via any suitable means known in the art, such as, e.g., with a single or double acting hydraulic cylinder or an electric motor ballscrew. Specifically, as shown in FIG. 3, a hydraulic cylinder 310 is controllably engaged to the orifice 308. The hydraulic cylinder 310 includes a hydraulic piston 316 connected to a rod 322, which in turn is connected to the fluid piston 306. In operation, as the hydraulic piston 316 is controlled to move, i.e., linear with the longitudinal axis 312, the

rod 322 moves and the fluid piston 306 subsequently moves, which results in a change in size of the orifice 308.

[0029] In the embodiment shown in FIG. 3, the hydraulic cylinder 310 is a double acting hydraulic cylinder 310. That is, the hydraulic cylinder 310 is hydraulically controlled to move in either direction. In more detail, the hydraulic piston 316 includes a head end 318 and a rod end 320. The hydraulic cylinder 310 includes a first hydraulic port 324 positioned to allow hydraulic fluid in the hydraulic cylinder 310 at the rod end 320, and a second hydraulic port 326 positioned to allow hydraulic fluid in the hydraulic cylinder 310 at the head end 318. Detailed operation of hydraulic circuits that may be used to control the spray heads 200 is described below.

[0030] The hydraulic cylinder 310 may include a spring 328 disposed in the head end 318. The spring 328 may provide additional force to hold the orifice 308 in a closed position, for example when the hydraulic circuits are shut down. The spring 328 may also be used to supplement the force applied to the head end 318 of the hydraulic cylinder 310. For example, the spring 328 may be selected having a desired compression rate (e.g., force per unit of compression). The total forces applied to the head end 318 may be from a combination of hydraulic fluid supplied to the second hydraulic port 326 and the force of the spring 328, and the total forces applied to the rod end 320 may be from a combination of hydraulic fluid supplied to the first hydraulic port 324 and pressure from fluid entering the inlet passage 302. If the fluid pressure entering the inlet passage 302 is kept fairly constant, then control of the degree of opening of the orifice 308 may be attained by varying the hydraulic fluid to the first hydraulic port 324.

[0031] It is noted that the spray head 200 may be configured for control of the fluid piston 306 by use of other configurations. For example, the hydraulic cylinder 310 may be configured without the second hydraulic port 326 and the associated hydraulic components, thus relying on hydraulic pressure on the rod end 320 and spring pressure on the head end 318.

[0032] It is further noted that the spray head 200 may be configured for control by other than a hydraulic piston 316. For example, the hydraulic cylinder 310, hydraulic piston, 316, and all associated hydraulic circuits and components could be replaced by electrical or mechanical actuators. As specific examples, the fluid piston 306 may be controlled by an electrical actuator such as a solenoid (not shown), or may be controlled by a mechanical actuator which may include any of a variety of cams, screws, levers, fulcrums, and the like (also not shown).

[0033] The hydraulic cylinder 310 may be fluidically isolated from the chamber 307, thus isolating the fluid that passes through the orifice 308 from the hydraulic fluid in the hydraulic cylinder 310. This design offers the advantage of keeping particles and contaminants away from the components in the hydraulic cylinder 310, for example when water from retaining ponds is used for dust suppression applications.

[0034] The spray head 200 may include one or more fluid deflectors 314 connected to the spray head 200 and configured to control a fluid distribution pattern from the outlet passage 304. For example, two fluid deflectors 314 are shown in FIG. 3 (and may be viewed in FIGS. 2A and 2B, although not labeled as such). The fluid deflectors 314 may be configured to control the fluid distribution pattern, for example in a laminar flow, from the outlet passage 304 in furtherance of the

laminar flow control that may be provided by the above-described specific locations of the inlet and outlet passages **302,304** relative to the longitudinal axis **312**.

[0035] A seal plate **330**, attached to the fluid piston **306**, may be used to further deflect fluid to attain a desired spray pattern, for example by designing the seal plate **330** with a desired shape and physical configuration.

[0036] Referring to FIG. 4, a block diagram of a representative portion of a fluid distribution system **100** is shown. For exemplary purposes, FIG. 4 is described as applied to a mobile machine **102**, i.e., an off-highway truck, set up for use as a water truck at a mining or construction site, although the fluid distribution system **100** shown in FIG. 4 could be used in other applications as noted above.

[0037] A power source **402** to supply power for the fluid distribution system **100** may also be used to supply motive power for the mobile machine **102**. For example, the power source **402** may include a prime mover **404** for the mobile machine **102**. The prime mover **404** may include an engine **406** drivably connected to the mobile machine **102** and a transmission **408** driven by the engine **406**. The engine **406** and transmission **408** may be chosen from among many types and configurations that are well known in the art. It is also well known to use the power supplied by prime movers **404** for other purposes in addition to providing motive power. For example, an off-highway truck, prior to being configured for water distribution applications, may have been designed to use power from the prime mover **404** for applications such as raising and lowering a truck bed.

[0038] A pump **410**, driven by the power source **402**, is in turn configured to drive a motor **412**. The pump **410** may be driven by the engine **406** or the transmission **408** by means that are known in the art, and may be a hydraulic pump **410** as is also known in the art. The pump **410** may be configured to drive the motor **412** by well known hydraulic means. A hydraulic tank **428** may be used to supply and recover hydraulic fluid to and from the pump **410** and motor **412**.

[0039] In the embodiment shown in FIG. 4, the pump **410** may be a fixed displacement type and the motor **412** may be variable displacement. For example, an off-highway truck configured for use as a water truck may have an existing fixed displacement pump **410** already in place for other purposes. Adding a variable displacement motor **412** may offer advantages in control of the fluid distribution system **100**, for example by enabling control of fluid pressure to maintain the fluid at a constant desired pressure regardless of engine speed or ground speed. A fixed displacement pump **410** may still be used for applications other than fluid distribution without being affected by changes in fluid distribution parameters. For example, the pump **410** may drive the motor **412** and also drive a system for cooling brake components (not shown). The brake cooling system would not be affected by load changes from the fluid distribution system **100**. In alternative embodiments, the pump **410** and motor **412** may be other combinations of fixed and variable displacement devices, for example a variable displacement pump and a fixed displacement motor.

[0040] The motor **412** is fluidly connected to one or more spray heads **200**, e.g., three spray heads as shown in FIG. 4. More specifically, the motor **412** may provide hydraulic power to a fluid pump **426**, which in turn delivers fluid by way of fluid lines **432** to the inlet passages **302** and through the

orifices **308** of the spray heads **200**. The fluid pump may obtain fluid from a fluid tank **430**, for example a water tank mounted on a water truck.

[0041] Although the three spray heads **200** in FIG. 4 are shown connected by common fluid lines **432** to the fluid pump **426**, each spray head **200** may be independently controllable. In addition, each spray head **200** may include an orifice **308** that is continuously variable from a fully closed position to a fully open position, as distinguished from an orifice that is capable of only being open or closed.

[0042] A ground speed sensor **414**, located on the mobile machine **102**, may be configured to sense a ground speed as the machine moves. The ground speed sensor **414** may be located to sense ground speed based on operation of the transmission **408**, rotational movement of a ground engaging member (not shown) such as a wheel, or by some other method known in the art.

[0043] A fluid pressure sensor **416** may be located to sense pressure of fluid in fluid lines **432**, or alternatively fluid pressure exiting fluid pump **426**.

[0044] An engine speed sensor **418** may be located to sense the speed of the engine **406**.

[0045] A transmission state sensor **420** may be located to sense the state, e.g., forward, neutral, or reverse, of the transmission **408**. The transmission state sensor **420** may alternatively sense direction of motion of the mobile machine **102** to determine transmission state.

[0046] Any of the above sensors may be configured to directly sense a desired parameter, may sense one or more secondary parameters and derive a value for the desired parameter, or may determine a value for the desired parameter by some other indirect means. Operation of the above sensors for their intended purposes are well known in the art and will not be described further.

[0047] A controller **422** may receive sensed or derived signals from the ground speed sensor **414**, the fluid pressure sensor **416**, the engine speed sensor **418**, and the transmission state sensor **420**. The controller **422** may also be controllably connected to one or more of the motor **412** and the spray heads **200**. For example, and as described in more detail below, the controller **422** may use information received from the ground speed sensor **414** and the fluid pressure sensor **416** to determine a desired fluid pressure to maintain, and responsively control the variable displacement of the motor **412** to maintain a constant fluid pressure. The controller **422** may also use information received from the engine speed sensor **418** for further control of the variable displacement motor **412**. The controller **422** may also use the above received information to control the variable orifices **308** of the spray heads **200** to control a flow rate of the fluid being delivered to and sprayed from the spray heads **200**. In one specific example, the controller **422** may determine from the transmission state sensor **420** if the mobile machine **102** is moving in reverse, and responsively shut off the fluid distribution system **100** during this condition.

[0048] An operator control device **424**, located in a cab compartment (not shown) of the mobile machine **102**, may provide an operator with a variety of control and display functions for the fluid distribution system **100**. The operator control **424** may be of any desired configuration and may be custom designed for specific mobile machines and applications.

[0049] Referring to FIG. 8, the operator control **424** may include a display **802**. The display **802** may be used to provide

visual indication of a wide variety of information including, but not limited to, a current operating mode of the fluid distribution system **100**, various sensed and determined parameters (such as engine and ground speeds, fluid pressures, and the like) fluid levels in the fluid tank **430**, and any other information desired to be provided. The display **802** may include visual display of information and may also include audible alerts such as low levels of fluid in the fluid tank **430**, and the like.

[0050] Various operating modes may be selected from the operator control **424** through the use of a wide variety of operator input devices (not shown) which may include, but are not limited to, switches, dials, levers, joysticks, buttons, and the like. FIG. **8** lists a sampling of available modes in no particular order. The list is not meant to be all-inclusive and additional modes may be made available as desired.

[0051] Pre-programmed spray modes may allow an operator to select from among a variety of spray modes based on the intended application. It may also be a feature that additional modes may be programmed for later use.

[0052] Manual mode may allow an operator to set up desired parameters, for example selecting a desired pressure, flow rate, number of active spray heads, spray pattern, and the like.

[0053] Intermittent mode may allow an operator to select a pulsing spray pattern that may be adjusted as a function of time or spray distance.

[0054] Fire fighting mode may allow the fluid to be diverted to a spray cannon (not shown), hose reel (not shown), and/or to any combination of spray heads **200**.

[0055] Tank fill mode may enable pumps and valves needed to pump fluid into the fluid tank **430**. Tank fill mode may be set up to be automatic, semi-automatic, or manual. Alternatively to pumping fluid into the fluid tank **430**, tank fill mode may provide for filling of the fluid tank **430** by gravity or external pumping means.

[0056] Cleanout mode may be used to open each orifice **308** to a maximum open position to flush debris from the spray heads **200**. This feature may be particularly useful, for example, when a water truck obtains water from a pond or stream, thus introducing sediment, debris and particles into the fluid tank **430**.

[0057] Oncoming traffic cutout mode may be used to quickly and easily shut off specific spray heads **200** that otherwise would undesirably direct spray onto objects, such as other vehicles passing the mobile machine **102**. This feature may be needed for a short duration only, and thus may be controlled by use of a momentary contact switch or trigger.

[0058] Referring to FIGS. **5A** and **5B**, various embodiments of a hydraulic system **500** suited to control a portion of the fluid distribution system **100** is shown. The hydraulic system **500** is representative only and is not meant to be limiting in scope and application. For illustrative purposes only, four spray heads **200** are shown.

[0059] Each hydraulic cylinder **310** may be double acting, i.e., each hydraulic piston **316** is controlled at both a head end **318** and a rod end **320**. A head end valve **502**, hydraulically connected to the second hydraulic port **326**, is controlled to apply pressure to the head end **318**, thus driving the orifice **308** toward a closed position. A rod end valve **504**, hydraulically connected to the first hydraulic port **324**, is controlled to apply pressure to the rod end **320**, thus driving the orifice **308** toward an open position.

[0060] FIG. **5A** depicts one head end valve **502** controlling all spray heads **200** simultaneously, and one rod end valve **504** controlling each spray head **200** individually. In this configuration, the single head end valve **502** applies pressure to all spray heads **200** toward a closed position, and each rod end valve **504** is independently controlled to apply pressure to a corresponding spray head **200** toward an open position. Other configurations may be used, however, without deviating from the scope of the present disclosure. For example, as depicted in FIG. **5B**, multiple head end valves **502** may be used to control a corresponding number of spray heads **200** individually.

[0061] A hydraulic supply **506** and a hydraulic tank **508** supply hydraulic fluid to and from the head end and rod end valves **502,504**. Although the hydraulic supply **506** and hydraulic tank **508** are shown as separate units for each valve (for ease of illustration), it is contemplated that one hydraulic supply **506** provides pressurized hydraulic fluid to all of the valves **502,504**, and one hydraulic tank **508** provides a return to tank path for all of the valves **502,504**. The hydraulic supply **506** may be a dedicated supply, e.g., a pilot supply, located on the mobile machine **102**, or may be part of a larger hydraulic system which may include the pump **410**. In like manner, the hydraulic tank **508** may be a separate tank or may be associated with the hydraulic tank **428**.

[0062] With reference to FIGS. **9A** and **9B**, another embodiment of the present disclosure is displayed. As seen in these figures, both a first fluid deflector **901** and a second fluid deflector **902** are integrated as cast-in contoured aspects of spray head **200** components as opposed to having right angled tabs that serve as the connection joint, as shown in FIGS. **2A** and **2B**. As shown, first fluid deflector **901** and second fluid deflector **902** are joined to spray head body **903** at positions likely to minimize the stress on the deflectors **901,902** themselves. FIGS. **9A** and **9B** further show how o-ring **904** and clamp ring **905**, which comprise multiple pieces, are oriented to form a fluid-tight interface between the component delivering fluid to spray head **200** and spray head **200** itself.

[0063] FIGS. **10A** and **10B** show further distinguishing aspects of this embodiment when compared to FIG. **3**. In particular, FIG. **10A** shows spray head **200** with piston **1001** in the open position, such that fluid entering spray head **200** at inlet passage **302** is permitted to exit spray head **200** at outlet passage **304**, while FIG. **10B** shows spray head **200** with piston **1001** in the closed position.

[0064] Seal **1002** is joined to piston **1001** and acts to prevent fluid from entering hydraulic cylinder **310** and prevent fluid from entering spray head **200** via inlet passage **302** when piston **1001** is in the closed position, as shown in FIG. **10B**. Seal **1002** may be made of any suitable material, such as a polymer, that is able to prevent fluid movement into hydraulic cylinder **310**, withstand the wear of fluid engaging the surface of seal **1002** throughout operation of spray head **200**, and form a reliable fluid-tight interface between inlet passage **302** and seal **1002**.

[0065] Internal diverter **1003** may also be joined to piston **1001** and seal **1002** using any acceptable joining means, such as, e.g., the screw shown in FIGS. **10A** and **10B**. Unexpectedly, it was discovered that the presence of internal diverter **1003** may introduce turbulence in the fluid flowing through spray head **200**, and that the induced turbulence allows the fluid flow to be more accurately controlled and be more predictable. In existing spray heads without an internal diverter, spray flow has been shown to be heavily concen-



trated in the middle of the spray width by as much as five times the concentration as the amount distributed at the periphery of the spray width. As indicated, the presence of the internal diverter **1003** reduces the variance in the concentration of the spray across the spray width. Internal diverter **1003** may be made of any suitable material such as, in one example, a polymer. Internal diverter **1003** may be of any suitable shape, such as, e.g., the wedge shape shown in FIGS. **10** and **11**. However, it is probable that the beneficial impact of internal diverter **1003** is due at least in part to the amount of area of inlet passage **302** that is obstructed by the presence of internal diverter **1003**. That is, it may be beneficial to have the surface area of the internal diverter **1003** surface facing inlet passage **302**, shown as **1103** in FIG. **11**, be in a ratio to the total area of the orifice of inlet passage **302** of between about 2:3 and about 1:10. For example, this ratio is between about 1:2 and about 1:5, such as between about 1:3 and about 1:4. [0066] Notably, spray head **200** depicted in FIGS. **9-11** does not include one or more o-ring seals between piston **1001** and spray head body **903**. It was discovered that the absence of such o-ring seals permitted some fluid to flow behind piston **1001** and into chamber **307**. The presence of fluid in chamber **307** was found to be advantageous because it allows for greater control over the rate at which piston **1001** is raised and lowered, thereby permitting greater control over the fluid rate and pressure as fluid exits outlet passage **304**. This is, in part, how spring **328** may be compressed at a constant rate as opposed to forcing piston **1001** into being in the open or closed position. This blow-by gap between piston **1001** and spray head body **903** around the circumference of the piston is at least about 0.25 mm, such as at least about 0.5 mm or at least about 0.75 mm. In one example, the blow-by gap between piston **1001** and spray head body **903** is between about 0.75 mm and about 1.5 mm, such as about 1.0 mm. One advantage of the blow-by gap is that fluid is not trapped in chamber **307**. Rather, the fluid drains out of chamber **307**, thereby reducing the likelihood of corrosion or freezing damage. Moreover, unexpectedly, the changes to the design of spray head **200** originating from the absence of an o-ring lead to an increased spray width, at some pressures by as much as at least about 8 ft. Whereas the previous maximum spray width was between about 20 ft to about 30 ft, the maximum spray width attainable with spray head **200** is between about 30 ft and about 40 ft.

[0067] FIG. **11** shows spray head **200** assembly in an exploded view, depicting how hydraulic cylinder **310** is connected to spray head body **903** with nut **1101**. Further, FIG. **11** shows the portion of piston **1001** referred to as dam **1102**, which acts as an initial fluid deflector that reduces aeration of the fluid and helps yield a flatter fluid spray dispersion.

[0068] Spray head **200** configuration advantageously allows for constant fluid delivery pattern at an adjustable delivery rate.

#### INDUSTRIAL APPLICABILITY

[0069] An example of application of the present disclosure can be described with reference to the flow diagrams of FIGS. **6** and **7**.

[0070] Referring to FIG. **6**, in a first control block **602**, a ground speed of the mobile machine **102** is determined. The ground speed may be sensed directly, for example by a ground speed sensor **414**, or may be determined by other means known in the art.

[0071] In a second control block **604**, a fluid pressure of the fluid lines **432** is determined. The fluid pressure may be sensed directly, for example by a fluid pressure sensor **416**, or may be determined by other means known in the art. The fluid pressure may be determined from the fluid lines **432** directly,

or may be determined at some other location associated with the fluid lines **432**, such as the spray head **200**, the fluid pump **426**, the pump **410**, the motor **412**, or some other location. The fluid pressure may also be determined at multiple locations.

[0072] In a third control block **606**, the determined fluid pressure is compared to a desired fluid pressure. The desired fluid pressure may be set based on a pre-programmed spray mode, a manually input desired fluid pressure, by some other operating mode of the fluid distribution system **100**, or by some other determined or input parameter.

[0073] In a fourth control block **608**, the motor **412** is controlled to maintain the determined fluid pressure at the desired fluid pressure. The motor **412** may be a variable displacement motor **412**, which may be controlled by varying the displacement of the motor **412**, as is well known in the art. Alternatively, the pump **410** may be a variable displacement pump **410** that may be controlled for the same purpose. Other types of controllable pumps and motors, such as electric and such, may also be used to control the fluid pressure. As an alternative to controllable pumps and/or motors, other means known in the art, such as variable orifices, valves, and the like, may be used to maintain the fluid pressure as well. In yet another configuration, the motor **412** is a variable displacement motor and the pump **410** is variable displacement pump. Such a configuration allows for a wide range of fluid pressure through the spray head **200**, such as below about 10 psi to more than about 110 psi, although fluid pressure is more typically within the range of between about 50 psi to about 80 psi at idle.

[0074] In a fifth control block **610**, each variable orifice **308** is controlled to maintain a desired distribution of fluid. In a fluid distribution system **100** having multiple spray heads **200**, and thus a corresponding multiple of orifices **308**, each variable orifice **308** may be controlled independent of each other variable orifice **308**, and all orifices **308** may be controlled independent of fluid pressure. The variable orifices **308** may be controlled to maintain a desired fluid distribution, for example a desired fluid distribution per unit of area. Control of the variable orifices **308** may be accomplished by controllably opening and closing each orifice in a manner described above with reference to FIG. **3**. Opening and closing an orifice **308** is a variable process, thus providing a continuously variable number of orifice positions for optimal control of the distribution of fluid.

[0075] Referring to FIG. **7**, a flow chart depicting another method of the present disclosure is shown.

[0076] In a first control block **702**, a condition associated with a location for fluid distribution is determined. Although a number of conditions may be determined, for illustrative purposes an exemplary condition of a level of dryness associated with the location is described. The level of dryness may be determined, for example in a water truck application, by an operator's observations of a relative dryness of the roads and surfaces to be sprayed. Alternatively, other more automated means for determining a level of dryness may be used.

[0077] In a second control block **704**, a desired fluid pressure as a function of the determined condition is determined. The desired fluid pressure may be a modification of the desired fluid pressure associated with the method described with reference to FIG. **6**.

[0078] In a third control block **706**, the motor **412** is controlled to maintain the desired fluid pressure, in the same manner as described above with reference to FIG. **6**.

[0079] In a fourth control block **708**, the variable orifice **308** is controlled as a function of both the ground speed and the determined condition to maintain the desired distribution of fluid.

[0080] The present disclosure provides a mobile fluid distribution system 100 and method which offers many advantages, among which includes providing control of fluid distribution over a desired area, in particular control of an amount of fluid distributed over a desired unit of area under varying conditions. Maintaining a constant fluid pressure while varying the flow rate through individual spray heads 200 provides more precise control of fluid distribution and the capability for a number of specialized flow control modes.

[0081] Other aspects can be obtained from a study of the drawings, the specification, and the appended claims.

What is claimed is:

- 1. A spray head for a fluid distribution system comprising:
  - a fluid inlet passage;
  - a fluid outlet passage;
  - a piston disposed in a chamber of a spray head body for controlled access between the inlet and outlet passages and defining a variable orifice;
  - an internal diverter joined to the piston and is within the variable orifice, wherein the internal diverter is disposed in the inlet passage when the variable orifice is closed; and
  - a double acting hydraulic cylinder controllably engaged to the orifice.
- 2. The spray head of claim 1, wherein the piston is oriented within the chamber such that there is a blow-by gap between the piston and the spray head body around the circumference of the piston of at least about 0.25 mm.
- 3. The spray head of claim 1, wherein the piston is oriented within the chamber such that there is a blow-by gap between the piston and the spray head body around the circumference of the piston of between about 0.75 mm and about 1.5 mm.
- 4. The spray head of claim 1, wherein the internal diverter has a surface facing the inlet passage and the ratio of the area of said internal diverter surface to the area of the inlet passage is 2:3 and about 1:10.
- 5. The spray head of claim 1, wherein the internal diverter has a surface facing the inlet passage and the ratio of the area of said internal diverter surface to the area of the inlet passage is 1:3 and about 1:4.
- 6. The spray head of claim 1, the spray head further including a fluid deflector connected to the spray head and configured to control a fluid distribution pattern from the outlet passage
- 7. The spray head of claim 6, wherein the fluid deflector is configured to control a fluid distribution pattern in a laminar flow from the outlet passage.
- 8. The spray head of claim 7, the spray head further including a second fluid deflector.
- 9. The spray head of claim 1, wherein the hydraulic cylinder includes:
  - a hydraulic piston having a head end and a rod end;
  - a rod connecting the hydraulic piston to the fluid piston;
  - a first hydraulic port positioned to allow hydraulic fluid in the hydraulic cylinder at the rod end; and
  - a second hydraulic port positioned to allow hydraulic fluid in the hydraulic cylinder at the head end.
- 10. The spray head of claim 9, wherein the hydraulic cylinder further includes a spring disposed in the hydraulic cylinder at the head end.
- 11. The spray head of claim 1, wherein the hydraulic cylinder is fluidly isolated from the chamber.

- 12. A fluid distribution system, comprising:
  - a power source;
  - a pump driven by the power source;
  - a motor driven by the pump; and
  - a spray head configured to receive fluid from a fluid source associated with the motor, the spray head including:
    - a fluid inlet passage;
    - a fluid outlet passage;
    - a piston disposed in a chamber of a spray head body for controlled access between the inlet and outlet passages and defining a variable orifice;
    - an internal diverter joined to the piston and is within the variable orifice, wherein the internal diverter is disposed in the inlet passage when the variable orifice is closed; and
    - a double acting hydraulic cylinder controllably engaged to the orifice.
- 13. The fluid distribution system of claim 12, wherein the motor is a variable displacement motor.
- 14. The fluid distribution system of claim 13 further comprising:
  - a ground speed sensor;
  - a fluid pressure sensor; and
  - a controller receivably connected to the ground speed sensor and the fluid pressure sensor, and controllably connected to the variable displacement motor and the spray head.
- 15. The fluid distribution system of claim 14, wherein the spray head includes a plurality of independently controllable spray heads.
- 16. The fluid distribution system of claim 12, wherein the variable orifice is a continuously variable orifice.
- 17. The fluid distribution system of claim 12, wherein the power source includes a prime mover for a mobile machine.
- 18. The fluid distribution system of claim 17, wherein the prime mover includes an engine drivingly connected to the mobile machine and a transmission driven by the engine.
- 19. The fluid distribution system of claim 18, wherein the pump is a hydraulic pump driven by one of the engine and the transmission.
- 20. A spray head for a fluid distribution system comprising:
  - a fluid inlet passage;
  - a fluid outlet passage;
  - a piston disposed in a chamber of a spray head body for controlled access between the inlet and outlet passages and defining a variable orifice, wherein the piston is oriented within the chamber such that there is a blow-by gap between the piston and the spray head body around the circumference of the piston of at least about 0.25 mm;
  - an internal diverter joined to the piston and is within the variable orifice, wherein the internal diverter is disposed in the inlet passage when the variable orifice is closed, and wherein the internal diverter has a surface facing the inlet passage and the ratio of the area of said internal diverter surface to the area of the inlet passage is 2:3 and about 1:10; and
  - a double acting hydraulic cylinder controllably engaged to the orifice.

\* \* \* \* \*