

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 December 2005 (08.12.2005)

PCT

(10) International Publication Number
WO 2005/115118 A2


- (51) International Patent Classification: Not classified
(21) International Application Number: PCT/US2005/018442
(22) International Filing Date: 25 May 2005 (25.05.2005)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data: 60/574,429 25 May 2004 (25.05.2004) US
(71) Applicant (for all designated States except US): CHEST-NUT MEDICAL TECHNOLOGIES, INC. [US/US]; 173 Jefferson Drive, Menlo Park, CA 94025-1114 (US).
(72) Inventors; and
(75) Inventors/Applicants (for US only): BEREZ, Aaron, Lee [US/US]; 1485 Laurel Street, Menlo Park, CA 94025 (US). TRAN, Quang, Quoc [US/US]; 11 Channel Drive, Redwood City, CA 94065 (US).
(74) Agent: HANLON, Brian, E.; Banner & Witcoff, LTD, 11th Floor, 1001 G Street, N.W., Washington, D.C. 20001-4597 (US).
(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: FLEXIBLE VASCULAR OCCLUDING DEVICE



WO 2005/115118 A2

(57) Abstract: A vascular occluding device for modifying blood flow in a vessel, while maintaining blood flow to the surrounding tissue. The occluding device includes a flexible, easily compressible and bendable occluding device that is particularly suited for treating aneurysms in the brain. The neurovascular occluding device can be deployed using a micro-catheter. The occluding device can be formed braiding wires in a helical fashion and can have varying lattice densities along the length of the occluding device. The occluding device could also have different lattice densities for surfaces on the same radial plane.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

FLEXIBLE VASCULAR OCCLUDING DEVICE

Related Application

- [01] Benefit of the May 25, 2004 filing date of U.S. Provisional Application Serial No. 60/574,429, entitled "Flexible Vascular Prosthesis" is hereby claimed. This application is expressly incorporated herein by reference.

Field of the Invention

- [02] The invention relates generally to an implantable device that could be used in the vasculature to treat common vascular malformations. More particularly, it relates to a flexible, biocompatible device that can be introduced into the vasculature of a patient to embolize and occlude aneurysms, particularly cerebral aneurysms.

Background of the Invention

- [03] Walls of the vasculature, particularly arterial walls, may develop pathological dilatation called an aneurysm. Aneurysms are commonly observed as a ballooning-out of the wall of an artery. This is a result of the vessel wall being weakened by disease, injury or a congenital abnormality. Aneurysms have thin, weak walls and have a tendency to rupture and are often caused or made worse by high blood pressure. Aneurysms could be found in different parts of the body; the most common being abdominal aortic aneurysms (AAA) and the brain or cerebral aneurysms. The mere presence of an aneurysm is not always life-threatening, but they can have serious health consequences such as a stroke if one should rupture in the brain. Additionally, as is known, a ruptured aneurysm can also result in death.
- [04] The most common type of cerebral aneurysm is called a saccular aneurysm, which is commonly found at the bifurcation of a vessel. The locus of bifurcation, the bottom of the V in the Y, could be weakened by hemodynamic forces of the blood flow. On a histological level, aneurysms are caused by damage to cells in the arterial wall. Damage is believed to be caused by shear stresses due to blood flow. Shear stress generates heat that breaks down the cells. Such hemodynamic

stresses at the vessel wall, possibly in conjunction with intrinsic abnormalities of the vessel wall, have been considered to be the underlying cause for the origin, growth and rupture of these saccular aneurysms of the cerebral arteries (Lieber and Gounis, The Physics of Endoluminal stenting in the Treatment of Cerebrovascular Aneurysms, Neurol Res 2002: 24: S32-S42). In histological studies, damaged intimal cells are elongated compared to round healthy cells. Shear stress can vary greatly at different phases of the cardiac cycle, locations in the arterial wall and among different individuals as a function of geometry of the artery and the viscosity, density and velocity of the blood. Once an aneurysm is formed, fluctuations in blood flow within the aneurysm are of critical importance because they can induce vibrations of the aneurysm wall that contribute to progression and eventual rupture. For a more detailed description of the above concepts see, for example, Steiger, Pathophysiology of Development and Rupture of Cerebral Aneurysms, Acta Neurochir Suppl 1990: 48: 1-57; Fergusson, Physical Factors in the Initiation, Growth and Rupture of Human Intracranial Saccular Aneurysms, J Neurosurg 1972: 37: 666-677.

- [05] Aneurysms are generally treated by excluding the weakened part of the vessel from the arterial circulation. For treating a cerebral aneurysm, such reinforcement is done in many ways: (i) surgical clipping, where a metal clip is secured around the base of the aneurysm; (ii) packing the aneurysm with microcoils, which are small, flexible wire coils; (iii) using embolic materials to "fill" an aneurysm; (iv) using detachable balloons or coils to occlude the parent vessel that supplies the aneurysm; and (v) endovascular stenting. For a general discussion and review of these different methods see Qureshi, Endovascular Treatment of Cerebrovascular Diseases and Intracranial Neoplasms, Lancet. 2004 Mar 6;363 (9411):804-13; Brilstra et al. Treatment of Intracranial Aneurysms by Embolization with Coils: A Systematic Review, Stroke 1999; 30: 470-476.
- [06] As minimally invasive interventional techniques gain more prominence, micro-catheter based approaches for treating neurovascular aneurysms are becoming more prevalent. Micro-catheters, whether flow-directed or wire-directed, are used

for dispensing embolic materials, microcoils or other structures (e.g., stents) for embolization of the aneurysm. A microcoil can be passed through a microcatheter and deployed in an aneurysm using mechanical or chemical detachment mechanisms, or be deployed into the parent vessel to permanently occlude it and thus block flow into the aneurysm. Alternatively, a stent could be tracked through the neurovasculature to the desired location. Article by Pereira, History of Endovascular Aneurysms Occlusion in Management of Cerebral Aneurysms; Eds: Le Roux et al., 2004, pp: 11-26 provides an excellent background on the history of aneurysm detection and treatment alternatives.

- [07] As noted in many of the articles mentioned above, and based on the origin, formation and rupture of the cerebral aneurysm, it is obvious that the goal of aneurysmal therapy is to reduce the risk of rupture of the aneurysm and thus the consequences of sub-arachnoid hemorrhage. It should also be noted that while preventing blood from flowing into the aneurysm is highly desirable, so that the weakened wall of the aneurysm doesn't rupture, it may also be vital that blood flow to the surrounding structures is not limited by the method used to obstruct blood flow to the aneurysm. Conventional stents developed for treating other vascular abnormalities in the body are ill suited for embolizing cerebral aneurysms. This could lead to all the usual complications when high oxygen consumers, such as brain tissue, are deprived of the needed blood flow.
- [08] There are many shortcomings with the existing approaches for treating neurovascular aneurysms. The vessels of the neurovasculature are the most tortuous in the body; certainly more tortuous than the vessels of the coronary circulation. Hence, it is a challenge for the surgeon to navigate the neurovasculature using stiff coronary stents that are sometimes used in the neurovasculature for treating aneurysms. The bending force of a prosthesis indicates the maneuverability of the prosthesis through the vasculature; a lower bending force would imply that the prosthesis is more easily navigated through the vasculature compared to one with a higher bending force. Bending force for a typical coronary stent is 0.05 lb-in (force to bend 0.5 inches cantilever to 90

degree). Hence, it will be useful to have neural prosthesis that is more flexible than existing stents.

- [09] Existing stent structures, whether used in coronary vessels or in the neurovasculature (microcoils) are usually straight, often laser cut from a straight tubing or braiding with stiff metallic materials. However, most of the blood vessels are curved. Hence, current stent structures and microcoils impart significant stress on the vessel walls as they try to straighten a curved vessel wall. For a weakened vessel wall, particularly where there is a propensity for an aneurysm formation, this could have disastrous consequences.
- [10] As noted earlier, the hemodynamic stress placed on the blood vessels, particularly at the point of bifurcation, leads to weakening of the vessel walls. The most significant source of such stress is the sudden change in direction of the blood flow. Hence, if one were to minimize the sudden change in direction of blood flow, particularly at the location of vessel weakness, it would be beneficial.
- [11] Existing approaches to occluding aneurysms could lead to another set of problems. Methods that merely occlude the aneurysm by packing or filling it with embolic material (coils or liquid polymers) do not address the fundamental flow abnormalities that contribute to the formation of aneurysm.
- [12] Currently, many different stent structures and stent deployment methods exist. A stent structure could be expanded after being placed intraluminally on a balloon catheter. Alternatively, self-expanding stems could be inserted in a compressed state and expanded upon deployment. All the stents need to have the radial rigidity to maintain patency of the lumen and simultaneously have the longitudinal flexibility to facilitate navigating the tortuous path of the vasculature. For balloon expandable stents, the stent is mounted on a balloon at the distal end of a catheter, the catheter is advanced to the desired location and the balloon is inflated to expand the stent into a permanent expanded condition. The balloon is then deflated and the catheter withdrawn leaving the expanded stent to maintain vessel patency. Because of the potentially lethal consequences of dissecting or

rupturing an intracerebral vessel, the use of balloon expandable stents in the brain is fraught with problems. Proper deployment of a balloon expandable stent requires slight over expanding of the balloon mounted stent to embed the stent in the vessel wall and the margin of error is small. Balloon expandable stents are also poorly suited to adapt to the natural tapering of cerebral vessels which taper proximally to distally. If a stent is placed from a parent vessel into a smaller branch vessel the change in diameter between the vessels makes it difficult to safely deploy a balloon expandable stent. A self-expanding stent, where the compressed or collapsed stent is held by an outer restraining sheath over the compressed stent to maintain the compressed state until deployment. At the time of deployment, the restraining outer sheath is retracted to uncover the compressed stent, which then expands to keep the vessel open. Additionally, the catheters employed for delivering such prosthesis are micro-catheters with outer diameter of 0.65 mm to 1.3 mm compared to the larger catheters that are used for delivering the large coronary stents to the coronaries.

- [13] Various stent structures and solutions have been suggested for treating cerebral aneurysms. US Patent No. 6,669,719 (Wallace et al.) describes a stent and a stent catheter for intra-cranial use. A rolled sheet stent is releasably mounted on the distal tip of a catheter. Upon the rolled sheet being positioned at the aneurysm, the stent is released. This results in immediate and complete isolation of an aneurysm and surrounding side branches of the circulatory system and redirecting blood flow away from the aneurysm. A significant drawback of such a system is that the surrounding side branches, along with the target aneurysm, are deprived of the needed blood flow after the stent has been deployed.
- [14] US Patent No. 6,605,110 (Harrison) describes a self-expanding stent for delivery through a tortuous anatomy or for conforming the stent to a curved vessel. This patent describes a stent structure with radially expandable cylindrical elements arranged in parallel to each other and interspersed between these elements and connecting two adjacent cylindrical elements are struts that are bendable. While

this structure could provide the necessary flexibility and bendability of the stent for certain applications, it is expensive and complex to manufacture.

- [15] US Patent No. 6,572,646 (Boylan) discloses a stent made up of a super-elastic alloy, such as Ni-Ti alloy (Nitinol), with a low temperature phase that induces a first shape to the stent and a high temperature phase that induces a second shape to the stent with a bend along the length. US Patent No. 6,689,162 (Thompson) discloses a braided prosthesis that uses strands of metal, for providing strength, and compliant textile strands. The objective of Thompson is to have a prosthesis that combines the structural strength and resiliency of a self-expanding stent and the low permeability of a graft. US Patent No. 6,656,218 (Denardo et al.) describes an intravascular flow modifier that allows microcoil introduction even after placing the modifier.

Summary of the Invention

- [16] An aspect of the present invention provides a highly flexible implantable occluding device that can easily navigate the tortuous vessels of the neurovasculature. Additionally, occluding device can easily conform to the shape of the tortuous vessels of the vasculature. Furthermore, the occluding device can direct the blood flow within a vessel away from an aneurysm; additionally such an occluding device allows adequate blood flow to be provided to adjacent structures such that those structures, whether they are branch vessels or oxygen demanding tissues, are not deprived of the necessary blood flow.
- [17] The occluding device is also capable of altering blood flow to the aneurysm, yet maintaining the desired blood flow to the surrounding tissue and within the vessel. In this instance, some blood is still allowed to reach the aneurysm, but not enough to create a laminar flow within the aneurysm that would cause injury to its thinned walls. Instead, the flow would be intermittent, thereby providing sufficient time for blood clotting or filler material curing within the aneurysm.

- [18] The occluding device is flexible enough to closely approximate the native vasculature and conform to the natural tortuous path of the native blood vessels. One of the significant attributes of the occluding device according to the present invention is its ability to flex and bend, thereby assuming the shape of a vasculature within the brain. These characteristics are for a neurovascular occluding device than compared to a coronary stent, as the vasculature in the brain is smaller and more tortuous.
- [19] In general terms, aspects of the present invention relate to methods and devices for treating aneurysms. In particular, a method of treating an aneurysm with a neck comprises deploying a vascular occluding device in the lumen of a vessel at the location of the aneurysm, whereby the blood flow is redirected away from the neck of the aneurysm. The induced stagnation of the blood in the lumen of the aneurysm would create embolization in the aneurysm. The occluding device spans the width of the stem of the aneurysm such that it obstructs or minimizes the blood flow to the aneurysm. The occluding device is very flexible in both its material and its arrangement. As a result, the occluding device can be easily navigated through the tortuous blood vessels, particularly those in the brain. Because the occluding device is flexible, very little force is required to deflect the occluding device to navigate through the vessels of the neurovasculature, which is of significance to the operating surgeon.
- [20] A significant feature of the occluding device, apart from its flexibility, is that the occluding device may have an asymmetrical braid pattern with a higher concentration of braid strands or a different size of braid strands on the surface facing the neck of the aneurysm compared to the surface radially opposite to it. In one embodiment, the surface facing the aneurysm is almost impermeable and the diametrically opposed surface is highly permeable. Such a construction would direct blood flow away from the aneurysm, but maintain blood flow to the side branches of the main vessel in which the occluding device is deployed.

- [21] In another embodiment, the occluding device has an asymmetrical braid count along the longitudinal axis of the occluding device. This provides the occluding device with a natural tendency to curve, and hence conform to the curved blood vessel. This reduces the stress exerted by the occluding device on the vessel wall and thereby minimizing the chances of aneurysm rupture. Additionally, because the occluding device is naturally curved, this eliminates the need for the tip of the micro-catheter to be curved. Now, when the curved occluding device is loaded on to the tip of the micro-catheter, the tip takes the curved shape of the occluding device. The occluding device could be pre-mounted inside the micro-catheter and can be delivered using a plunger, which will push the occluding device out of the micro-catheter when desired. The occluding device could be placed inside the micro-catheter in a compressed state. Upon exiting the micro-catheter, it could expand to the size of the available lumen and maintain patency of the lumen and allow blood flow through the lumen. The occluding device could have a lattice structure and the size of the openings in the lattice could vary along the length of the occluding device. The size of the lattice openings can be controlled by the braid count used to construct the lattice.
- [22] According to aspects of the invention, the occluding device can be used to remodel an aneurysm within the vessel by, for example, neck reconstruction or balloon remodeling. The occluding device can be used to form a barrier that retains occlusion material such as a well known coil or viscous fluids, such as "ONYX" by Microtherapeutics, within the aneurysm so that introduced material will not escape from within the aneurysm due to the lattice density of the occluding device in the area of the aneurysm.
- [23] In another aspect of this invention, a device for occluding an aneurysm is disclosed. The device is a tubular with a plurality of perforations distributed on the wall of the member. The device is placed at the base of the aneurysm covering the neck of the aneurysm such that the normal flow to the body of the aneurysm is disrupted and thereby generating thrombus and ultimately occlusion of the aneurysm.

- [24] In yet another aspect of this invention, the device is a braided tubular member. The braided strands are ribbons with rectangular cross section, wires with a circular cross section or polymeric strands.
- [25] In another embodiment, a device with a braided structure is made in order to conform to a curved vessel in the body, where the density of the braid provides enough rigidity and radial strength. Additionally, the device can be compressed using a force less than 10 grams. This enables the device to be compliant with the artery as the arterial wall is pulsating. Also, the device is capable of bending upon applying a force of less than 5 gram/cm.
- [26] Other aspects of the invention include methods corresponding to the devices and systems described herein.

Brief Description of the Drawings

- [27] The invention has other advantages and features which will be more readily apparent from the following detailed description of the invention and the appended claims, when taken in conjunction with the accompanying drawings, in which:
- [28] FIG. 1 is an illustration of an aneurysm, branch vessels and blood flow to the aneurysm.
- [29] FIGS. 2A and 2B illustrate one embodiment of an occluding device to treat aneurysms.
- [30] FIG. 3 is an illustration of the embodiment shown in FIG. 2 in a compressed state inside a micro-catheter.
- [31] FIG. 4A is another embodiment of an occluding device for treating aneurysms.
- [32] FIGS. 4B and 4C illustrate cross sections of portions of ribbons that can be used to form the occluding device of FIG. 4A.

- [33] FIG. 5 shows the occluding device in a compressed state inside a micro-catheter being advanced out of the micro-catheter using a plunger.
- [34] FIG. 6 shows the compressed occluding device shown in FIG. 5 deployed outside the micro-catheter and is in an expanded state.
- [35] FIG. 7 shows the deployed occluding device inside the lumen of a vessel spanning the neck of the aneurysm, a bifurcation and branch vessels.
- [36] FIG. 8 is a schematic showing the occluding device located in the lumen of a vessel and the change in the direction of the blood flow.
- [37] FIG. 9 shows the effect of a bending force on a conventional stent compared to the occluding device of the present invention.
- [38] FIG. 10 demonstrates the flexibility of the current invention, compared to a traditional stent, by the extent of the deformation for an applied force.
- [39] FIG. 11 shows the non-uniform density of the braid that provides the desired curved occluding device.
- [40] FIG. 12 illustrates the difference in lattice density or porosity due to the non-uniform density of the braiding of the occluding device.
- [41] FIG. 13 shows the varying lattice density occluding device covering the neck of an aneurysm.
- [42] FIGS. 14 and 15 show an embodiment of the vascular occluding device where the lattice density is asymmetrical about the longitudinal axis near the aneurysm neck.
- [43] FIG. 16 illustrates a bifurcated occluding device according to an embodiment of the present invention in which two occluding devices of lesser densities are combined to form a single bifurcated device.

Detailed Description Of The Preferred Embodiments

- [44] The devices shown in the accompanying drawings are intended for treating aneurysms. They are generally deployed, using micro-catheters, at the location of a cerebral aneurysm that is intended to be treated. One such system is disclosed in copending U.S. Patent Application titled “System and Method for Delivering and Deploying an Occluding Device Within a Vessel”, (Atty. Docket Number 006258.00008) filed on May 25, 2005, which is incorporated herein by reference in its entirety. The embodiments of the endovascular occluding device according to aspects of the present invention is useful for treating cerebral aneurysms that are commonly treated using surgical clips, microcoils or other embolic devices.
- [45] FIG. 1 illustrates a typical cerebral aneurysm 10 in the brain. A neck 11 of the aneurysm 10 can typically define an opening of between about 2 to 25 mm. As is understood, the neck 11 connects the vessel 13 to the lumen 12 of the aneurysm 10. As can be seen in FIG. 1, the blood flow 1 within the vessel 13 is channeled through the lumen 12 and into the aneurysm. In response to the constant blood flow into the aneurysm, the wall 14 of lumen 12 continues to distend and presents a significant risk of rupturing. When the blood within the aneurysm 10 causes pressure against the wall 14 that exceeds the wall strength, the aneurysm ruptures. The present invention could prevent such ruptures. Also shown in FIG. 1 are the bifurcation 15 and the side branches 16.
- [46] FIG. 2 illustrates one embodiment of an vascular occluding device 20 in accordance with an aspect of the present invention. In the illustrated embodiment, the occluding device 20 has a substantially tubular structure 22 defined by an outer surface 21, an inner surface 24 and a thin wall that extends between the surfaces 21, 24. A plurality of openings 23 extend between the surfaces 21, 24 and allow for fluid flow from the interior of the occluding device 20 to the wall of the vessel. Occluding device 20 is radially compressible and longitudinally adjustable.

- [47] FIG. 3 shows a micro-catheter 25 and the occluding device 20 inside the micro-catheter 25 in a compressed state prior to being released within the vasculature of the patient.
- [48] FIG. 4 illustrates another embodiment of the occluding device 30 having two or more strands of material(s) 31, 32 wound in a helical fashion. The braiding of such material in this fashion results in a lattice structure 33. As can be understood, the dimension of the lattice 33 and the formed interstices 34 is determined, at least in part, by the thickness of the strand materials, the number of strands and the number of helices per unit length of the occluding device 30.
- [49] The occluding device 30 is radially compressible and radially expandable without the need for supplemental radially expanding force, such as an inflatable balloon. The occluding device 30 is constructed by winding the two strands (31, 32) in opposite directions. In an embodiment, the strands 31, 32 are in the shape of rectangular ribbon (See Figure 4C). The ribbons can be formed of known flexible materials including shape memory materials, such as Nitinol, platinum and stainless steel.
- [50] The ribbon used as the braiding material for the strands 31, 32 can include a rectangular cross section 35 (Figure 4C). As shown in Figures 4C and 7, the surface 36 that engages an inner surface of the vessel has a longer dimension (width) when compared to the wall 38 that extends between the surfaces 36, 37 (thickness). A ribbon with rectangular cross section has a higher recovery (expansive) force for the same wall thickness when compared to a wire with a circular (round) cross section. Additionally, a flat ribbon allows for more compact compression of the occluding device 20 and causes less trauma to the vascular wall when deployed because it distributes the radial expansion forces over a greater surface area. Similarly, flat ribbons form a more flexible device for a given lattice density because their surface area (width) is greater for a given thickness in comparison to round wire devices.

- [51] While the illustrated embodiment discloses a ribbon having a rectangular cross section in which the length is greater than its thickness, the ribbon for an alternative embodiment of the disclosed occluding devices may include a square cross section. In another alternative embodiment, a first portion of the ribbon may include a first form of rectangular cross section and a second portion 39 of the ribbon (Figure 4B) may include a round, elliptical, oval or alternative form of rectangular cross section. For example, end sections of the ribbons may have substantially circular or oval cross section and the middle section of the ribbons could have a rectangular cross section.
- [52] In an alternative embodiment, the occluding device 30 can be formed by winding more than two strands of ribbon. In an embodiment, the occluding device 30 could include as many as sixteen strands of ribbon. By using standard techniques employed in making radially expanding stents, one can create an occluding device 30 with interstices 34 that are larger than the thickness of the ribbon or diameter of the wire. The ribbons can have different widths. In such an embodiment, the different ribbon(s) can have different width(s) to provide structure support to the occluding device 30 and the vessel wall. The ribbons according to the disclosed embodiments can also be formed of different materials. For example, one or more of the ribbons can be formed of a biocompatible metal material, such as those disclosed herein, and one or more of the ribbons can be formed of a biocompatible polymer.
- [53] FIG. 5 shows the intravascular occluding device 30 in a radially compressed state located inside the micro-catheter 25. In one embodiment, the occluding device 30 could be physically attached to the catheter tip. This could be accomplished by constraining the occluding device 30 in the distal segment of the micro-catheter. The micro-catheter 25 is slowly advanced over a guidewire (not shown) by a plunger 50 and when the tip of the micro-catheter 25 reaches the aneurysm, the occluding device is released from the tip. The occluding device 30 expands to the size of the vessel and the surface of the occluding device 30 is now apposed to the vessel wall 15 as shown in FIG. 6. Instruments and methods for delivering and

deploying the occluding device 30 are disclosed in the above-referenced copending application.

- [54] With reference to FIG. 7, the occluding device 30 is deployed inside the lumen of a cerebral vessel 13 with an aneurysm 10. During its deployment, the proximal end 43 of the occluding device 30 is securely positioned against the lumen wall of the vessel 13 before the bifurcation 15 and the distal end 45 of the occluding device 30 is securely positioned against the lumen wall of the vessel 13 beyond the neck 11 of aneurysm 10. After the occluding device 30 is properly positioned at the desired location within the vessel 13 (for example, see FIG. 7), flow inside the lumen of aneurysm 10 is significantly minimized while the axial flow within the vessel 13 is not significantly compromised, in part due to the minimal thickness of the walls 38.
- [55] The flow into the aneurysm 10 will be controlled by the lattice density of the ribbons and the resulting surface coverage. Areas having greater lattice densities will have reduced radial (lateral) flow. Conversely, areas of lesser lattice densities will allow significant radial flow through the occluding device 30. As discussed below, the occluding device 30 can have longitudinally extending (lateral) areas of different densities. In each of these areas, their circumferential densities can be constant or vary. This provides different levels of flow through adjacent lateral areas. The location within a vessel of the areas with greater densities can be identified radiographically so that the relative position of the occluding device 30 to the aneurysm 10 and any vascular branches 15, 16 can be determined. The occluding device 30 can also include radiopaque markers.
- [56] The reduction of blood flow within the aneurysm 10 results in a reduction in force against the wall 14 and a corresponding reduction in the risk of vascular rupturing. When the force and volume of blood entering the aneurysm 10 is reduced by the occluding device, the laminar flow into the aneurysm 10 is stopped and the blood within the aneurysm begins to stagnate. Stagnation of blood, as opposed to continuous flow through the lumen 12 of the aneurysm 10, results in

thrombosis in the aneurysm 10. This also protects the aneurysm from rupturing. Additionally, due to the density of the portion of the occluding device 30 at the bifurcation 15, the openings (interstices) 34 in the occluding device 30 allow blood flow to continue to the bifurcation 15 and the side branches 16 of the vessel. If the bifurcation 15 is downstream of the aneurysm, as shown in FIG. 8, the presence of the occluding device 30 still channels the blood away from the aneurysm 10 and into the bifurcation 15.

- [57] The occluding devices described herein have the flexibility necessary to conform to the curvature of the vasculature. This is in contrast to coronary stents that cause the vasculature to conform essentially to their shape. The ability to conform to the shape of the vasculature is more significant for neurovascular occluding devices than coronary stents, as the vasculature in the brain is smaller and more tortuous. Tables 1 and 2 demonstrate these characteristics of the claimed neurovascular occluding device. To demonstrate that the disclosed occluding devices exhibit very desirable bending characteristics, the following experiment was performed. The occluding device made by the inventors was set on a support surface 90 as shown in FIG. 9. About 0.5 inches of the occluding device 30 was left unsupported. Then, a measured amount of force was applied to the unsupported tip until the occluding device was deflected by 90 degrees from the starting point. A similar length of a commercially available coronary stent was subjected to the same bending moment. The results are shown in Table 1. Similar to the reduced compressive force, the occluding device of the present invention required an order of magnitude lower bending moment (0.005 lb-in compared to 0.05 lb-in for a coronary stent).

Table 1: Bending Force Required to Bend a 0.5 " Cantilever Made by the Occlusion Device

Coronary stent	commercially available stent	0.05 lb-in
----------------	------------------------------	------------

Neurovascular Occluding Device (30)	0.005 lb-in
-------------------------------------	-------------

[58] The occluding devices according to the present invention also provides enhanced compressibility (i.e., for a given force how much compression could be achieved or to achieve a desired compression how much force should be exerted) compared to coronary stents. An intravascular device that is not highly compressible is going to exert more force on the vessel wall compared to a highly compressible device. This is of significant clinical impact in the cerebral vasculature as it is detrimental to have an intravascular device that has low compressibility.

Table 2: Compressive Force Required to Compress the Occluding device to 50% of the Original Diameter (see FIG. 10)

Coronary stem (commercially available)	0.2lb
Neurovascular Occluding device (30)	0.021b

[59] FIGS. 11-13 show an embodiment of the occluding device 60 in which the lattice structure 63 of the occluding device 60 is non-uniform across the length of the occluding device 60. In the mid-section 65 of the occluding device 60, which is the section likely to be deployed at the neck of the aneurysm, the lattice density 63a is intentionally increased to a value significantly higher than the lattice density elsewhere in the occluding device 60. For example, as seen in FIG. 11, lattice density 63A is significantly higher than the lattice density 63 in adjacent section 64. At one extreme, the lattice density (porosity provided by the interstices) could be zero, i.e., the occluding device 60 is completely impermeable. In another embodiment, the lattice density 63A in mid-section 65

could be about 50%, while the lattice density in the other sections 64 of the occluding device is about 25%. FIG. 12 shows such the occluding device 60 in a curved configuration and FIG. 13 shows this occluding device 60 deployed in the lumen of a vessel. FIG. 13 also illustrates the part of the occluding device 60 with increased lattice density 63A positioned along the neck of aneurysm 10. As with any of the disclosed occluding devices, the lattice density of at least one portion of occluding device 60 can be between about 20% and about 80%. The lattice density of these embodiments could be between about 25% and about 50%.

- [60] Another embodiment of the occluding device 300 is shown in FIGS. 14 and 15. In this embodiment, the occluding device 300 is deployed in lumen of a vessel with an aneurysm. The occluding device 300 includes a surface 310 that faces the lumen of the aneurysm. This surface 310 has a significantly higher lattice density (smaller and/or fewer interstices) compared to the diametrically opposite surface 320. Due to the higher lattice density of surface 310, less blood flows into the lumen of the aneurysm. However, there is no negative impact on the blood flow to the side branches as the lattice density of the surface 320 facing the side branches is not reduced.
- [61] Any of the occluding devices disclosed herein can be used with a second occluding device to create a bifurcated occluding device 400 as shown in Figure 16. This device could be created *in vivo*. In forming the occluding device 400, a portion of a first occluding device 410 having a low density can be combined with a portion of a second occluding device 410 that also has a low density. The occluding devices 410, 420 can be any of those discussed herein. After these portions of the two occluding devices 410, 420 are combined in an interwoven fashion to form an interwoven region 425, the remaining portions 414, 424 can branch off in different directions, thereby extending along two branches of the bifurcation. Areas outside of the interwoven region 425 can have greater lattice density for treating an aneurysm or lesser lattice density for allowing flow to branches 15, 16 of the vessel.

- [62] The density of the lattice for each of the disclosed occluding devices can be about 20% to about 80% of the surface area of its occluding device. In an embodiment, the lattice density can be about 20% to about 50% of the surface area of its occluding device. In yet another embodiment, the lattice density can be about 20% to about 30% of the surface area of its occluding device.
- [63] A typical occluding device having sixteen strand braids with 0.005 inch wide ribbon, 30 picks per inch (PPI) (number of crosses/points of contact per inch), and 0.09 inch outer diameter has approximately 30% of lattice density (surface covered by the ribbon). In the embodiments disclosed herein, the ribbon can be about 0.001 inch thick with a width of between about 0.002 inch to about 0.005 inch. In an embodiment, the ribbon has a thickness of about 0.004 inch. For a 16-strands ribbon that is about 0.001 inch thick and about 0.004 inch wide, the coverage for 50 PPI, 40 PPI, and 30 PPI will have 40%, 32% and 24% approximate surface coverage, respectively. For a 16-strands ribbon that is about 0.001 inch thick and about 0.005 inch wide, the coverage for 50 PPI, 40 PPI, and 30 PPI will be about 50%, 40% and 30% approximate surface coverage, respectively.
- [64] In choosing a size for the ribbon, one must consider that, when the ribbons are bundled up, will they traverse through a micro-catheter. For example, sixteen strands of a 0.006 inch wide ribbon may not pass through a micro-catheter having an internal diameter of 0.027 inch or less. However, as the width of ribbons become smaller, the recovery strength may decrease proportionally.
- [65] While other strand geometry may be used, these other geometries, such as round, will limit the device due to their thickness dimension. For example, a round wire with a 0.002 inch diameter will occupy up to 0.008 inch in cross sectional space within the vessel. This space can impact and disrupt the blood flow through the vessel. The flow in the vessel can be disrupted with this change in diameter.
- [66] Although the detailed description contains many specifics, these should not be construed as limiting the scope of the invention but merely as illustrating different

examples and aspects of the invention. It should be appreciated that the scope of the invention includes other embodiments not discussed in detail above. Various other modifications, changes and variations which will be apparent to those skilled in the art may be made in the arrangement, operation and details of the method and apparatus of the present invention disclosed herein without departing from the spirit and scope of the invention as defined in the appended claims. Therefore, the scope of the invention should be determined by the appended claims and their legal equivalents. Furthermore, no element, component or method step is intended to be dedicated to the public regardless of whether the element, component or method step is explicitly recited in the claims.

- [67] In the claims, reference to an element in the singular is not intended to mean "one and only one" unless explicitly stated, but rather is meant to mean "one or more." In addition, it is not necessary for a device or method to address every problem that is solvable by different embodiments of the invention in order to be encompassed by the claims.

What is Claimed:

1. A device for positioning within a blood vessel for embolization of an aneurysm, said device including a plurality of woven ribbons, each said ribbon comprising an inner surface, an outer surface for positioning adjacent an inner wall of a vessel, said outer surface forming a portion of an outer circumference of said device between first and second ends of said device, and a plurality openings extending between said inner and outer surfaces, said outer surface of said device comprising between about 20 to about 50 percent of the total circumferential area of said device.
2. The device of claim 1 wherein said openings occupy between about 50 to about 80 percent of the total circumferential area of said device.
3. The device of claim 1 wherein said ribbons form a lattice structure along the length of said device.
4. The device of claim 3 wherein the density of the lattice structure is between about 25 to about 50 picks per inch.
5. The device of claim 1 wherein said device has a length, a first portion with a lattice density that restricts fluid flow there through in a direction at an angle to said length and a second portion having a lattice density that permits greater fluid flow there through relative to said first portion in said direction.
6. The device of claim 1 wherein said ribbon has a substantially rectangular cross section.

7. The device of claim 1 wherein said ribbon is woven such that it forms a lattice structure having areas of different lattice densities for positioning in predetermined locations within the vessel.
8. The device of claim 7 wherein said lattice density is greater in a first circumferentially extending area relative to the lattice density of a second circumferentially extending area that is axially spaced from said first area.
9. The device of claim 1 wherein said device is bifurcated such that a first end of the device includes a first axial opening and a second end of said device includes at least two axial openings.
10. The device of claim 9 wherein said bifurcated device is formed in vivo by weaving together portions of at least two of said devices.
11. The device of claim 1 comprising a length that can be adjusted during deployment such that the deployed length of the occluding device can be adjusted after the occluding device is loaded within a delivery catheter.
12. The device of claim 1 comprising regions for positioning proximate a branch or feeder portion of the vessel, said regions having a lesser lattice density relative to a region intended to be positioned proximate an aneurysm.
13. A braided device for occluding a portion of a vessel comprising an elongated flexible member having an asymmetrical braided pattern in which a first portion of the braided pattern allows a first amount of radial blood flow to pass there through and a second portion of the braided pattern allows a second amount of radial blood flow there through, said first amount being greater than said second amount.

14. The device of claim 13 wherein said braided pattern has a lattice density of about 20% to about 50% of a surface area of said device.
15. The device of claim 13 wherein said braid pattern is formed of interwoven ribbons having at least a first portion including a substantially rectangular cross section.
16. The device of claim 15 wherein said braided pattern forms a lattice structure along the length of said device having a lattice density between about 25 to about 50 picks per inch.
17. The device of claim 16 wherein said first and second portions include different lattice densities.
18. The device of claim 13 wherein said first portion includes a first circumferentially extending area, and said second portion includes a second circumferentially extending area that is axially spaced from said first area.
19. The device of claim 13 wherein said first portion includes a first axially extending area, and said second portion includes a second axially extending area that is circumferentially spaced from said first area.
20. The device of claim 13 wherein said device is bifurcated such that a first end of the device includes a first axial opening and a second end of said device includes at least two axial openings.
21. The device of claim 20 wherein said bifurcated device is formed *in vivo* by weaving together portions of at least two of said devices.
22. The device of claim 13 comprising a length that can be adjusted during deployment such that the deployed length of the occluding device can be adjusted after the occluding device is loaded within a delivery catheter.

23. The device of claim 13 comprising regions for positioning proximate a branch or feeder portion of the vessel, said regions having a lesser lattice density relative to a region intended to be positioned proximate an aneurysm.


FIG. 1

FIG. 2A




FIG. 2B




FIG. 3

F.I.G. 4B

39

Fig. 4 A







FIG. 5FIG. 6






Fig. 9




Fig. 10

Compression force









FIG. 11














FIG. 16