



US009208078B2

(12) **United States Patent**
Luukkainen et al.

(10) **Patent No.:** **US 9,208,078 B2**
(45) **Date of Patent:** **Dec. 8, 2015**

(54) **APPARATUS AND METHOD TO SHARE
HOST SYSTEM RAM WITH MASS STORAGE
MEMORY RAM**

USPC 711/103
See application file for complete search history.

(71) Applicant: **MEMORY TECHNOLOGIES LLC,**
Las Vegas, NV (US)

(56) **References Cited**

(72) Inventors: **Olli Luukkainen,** Salo (FI); **Kimmo J.**
Myly, Ylojarvi (FI); **Jani Hyvonen,**
Tampere (FI)

U.S. PATENT DOCUMENTS

5,586,291 A 12/1996 Lasker et al.
5,701,516 A 12/1997 Cheng et al.
5,802,069 A 9/1998 Coulson

(Continued)

(73) Assignee: **Memory Technologies LLC,** Las Vegas,
NV (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

CN 101329654 12/2008
CN 101937318 1/2011

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **14/520,030**

PCT Search Report mailed Feb. 25, 2015 for PCT application No.
PCT/US2014/069616, 10 pages.

(22) Filed: **Oct. 21, 2014**

(Continued)

(65) **Prior Publication Data**

US 2015/0039819 A1 Feb. 5, 2015

Primary Examiner — Yong Choe

(74) *Attorney, Agent, or Firm* — Lee & Hayes, PLLC

Related U.S. Application Data

(63) Continuation of application No. 12/455,763, filed on
Jun. 4, 2009, now Pat. No. 8,874,824.

(51) **Int. Cl.**
G06F 12/02 (2006.01)


(52) **U.S. Cl.**
CPC **G06F 12/0246** (2013.01); **G06F 12/0223**
(2013.01); **G06F 2212/171** (2013.01); **G06F**
2212/7202 (2013.01); **G06F 2212/7203**
(2013.01); **G06F 2212/7207** (2013.01)

(58) **Field of Classification Search**
CPC G06F 12/0223; G06F 12/0246; G06F
2212/171; G06F 2212/7202; G06F 2212/7203;
G06F 2212/7207

(57) **ABSTRACT**

A method includes, in one non-limiting embodiment, sending a request from a mass memory storage device to a host device, the request being one to allocate memory in the host device; writing data from the mass memory storage device to allocated memory of the host device; and subsequently reading the data from the allocated memory to the mass memory storage device. The memory may be embodied as flash memory, and the data may be related to a file system stored in the flash memory. The method enables the mass memory storage device to extend its internal volatile RAM to include RAM of the host device, enabling the internal RAM to be powered off while preserving data and context stored in the internal RAM.

27 Claims, 7 Drawing Sheets



(56)

References Cited**U.S. PATENT DOCUMENTS**

5,809,340 A 9/1998 Bertone et al.
 5,924,097 A 7/1999 Hill et al.
 6,067,300 A 5/2000 Baumert et al.
 6,115,785 A 9/2000 Estakhri et al.
 6,480,936 B1 11/2002 Ban et al.
 6,513,094 B1 1/2003 Magro
 6,522,586 B2 2/2003 Wong
 6,665,747 B1 12/2003 Nazari
 6,785,764 B1 8/2004 Roohparvar
 6,842,829 B1 1/2005 Nichols et al.
 7,136,963 B2 11/2006 Ogawa et al.
 7,181,574 B1 2/2007 Lele
 7,321,958 B2 1/2008 Hofstee et al.
 7,480,749 B1 1/2009 Danilak
 7,571,295 B2 8/2009 Sakarda et al.
 7,697,311 B2 4/2010 Fukuda et al.
 7,809,962 B2 10/2010 Chang et al.
 8,190,803 B2 5/2012 Hobson et al.
 8,218,137 B2 7/2012 Noh et al.
 8,321,713 B2 11/2012 Nobunaga
 2002/0087817 A1 7/2002 Tomaiuolo et al.
 2002/0093913 A1 7/2002 Brown et al.
 2002/0108014 A1 8/2002 Lasser
 2003/0028737 A1 2/2003 Kaiya et al.
 2003/0137860 A1 7/2003 Khatri et al.
 2004/0010671 A1 1/2004 Sampsa et al.
 2004/0049692 A1 3/2004 Okamoto
 2004/0203670 A1 10/2004 King et al.
 2004/0221124 A1 11/2004 Beckert et al.
 2005/0010738 A1 1/2005 Stockdale et al.
 2005/0071570 A1 3/2005 Takasugl et al.
 2005/0097280 A1 5/2005 Hofstee et al.
 2005/0204113 A1 9/2005 Harper et al.
 2006/0041888 A1 2/2006 Radulescu et al.
 2006/0069899 A1 3/2006 Schoinas et al.
 2006/0075147 A1 4/2006 Schoinas et al.
 2006/0075395 A1 4/2006 Lee et al.
 2006/0174056 A1 8/2006 Lambert et al.
 2006/0179212 A1 8/2006 Kim et al.
 2006/0184758 A1 8/2006 Satori et al.
 2006/0280077 A1 12/2006 Suwa
 2007/0088867 A1 4/2007 Cho et al.
 2007/0207854 A1 9/2007 Wolf et al.
 2007/0234006 A1 10/2007 Radulescu et al.
 2007/0283078 A1 12/2007 Li et al.
 2008/0080688 A1 4/2008 Burgan et al.
 2008/0104291 A1 5/2008 Hinchey
 2008/0127131 A1 5/2008 Gao et al.
 2008/0162792 A1 7/2008 Wu et al.
 2008/0183954 A1 7/2008 Lee et al.
 2008/0228984 A1 9/2008 Yu et al.
 2008/0244173 A1 10/2008 Takai
 2008/0281944 A1 11/2008 Vorne et al.
 2008/0282030 A1 11/2008 Kalwitz et al.
 2008/0320211 A1 12/2008 Kinoshita
 2009/0106503 A1 4/2009 Lee et al.
 2009/0157950 A1 6/2009 Selinger
 2009/0164705 A1 6/2009 Gorobets
 2009/0182940 A1 7/2009 Matsuda et al.
 2009/0182962 A1 7/2009 Khmelniitsky et al.
 2009/0198871 A1 8/2009 Tzeng
 2009/0198872 A1 8/2009 Tzeng
 2009/0210615 A1 8/2009 Struk et al.
 2009/0216937 A1 8/2009 Yasufuku
 2009/0222629 A1 9/2009 Yano et al.
 2009/0307377 A1 12/2009 Anderson et al.
 2009/0313420 A1 12/2009 Wiesz et al.
 2009/0327584 A1 12/2009 Tetrack et al.
 2010/0005281 A1 1/2010 Buchmann et al.
 2010/0030961 A9 2/2010 Ma et al.
 2010/0037012 A1 2/2010 Yano et al.
 2010/0100648 A1 4/2010 Madukkarumukumana et al.
 2010/0106886 A1 4/2010 Marcu et al.
 2010/0106901 A1 4/2010 Higeta et al.
 2010/0115193 A1 5/2010 Manus et al.

2010/0161882 A1 6/2010 Stern et al.
 2010/0169558 A1 7/2010 Honda et al.
 2010/0169604 A1 7/2010 Trika et al.
 2010/0172180 A1 7/2010 Paley et al.
 2010/0250836 A1 9/2010 Sokolov et al.
 2010/0268928 A1 10/2010 Wang et al.
 2010/0293420 A1 11/2010 Kapil et al.
 2010/0312947 A1 12/2010 Luukkainen et al.
 2011/0082967 A1 4/2011 Deshkar et al.
 2011/0087804 A1 4/2011 Okaue et al.
 2011/0099326 A1 4/2011 Jung et al.
 2011/0208914 A1 8/2011 Winokur et al.
 2011/0264860 A1 10/2011 Hooker et al.
 2011/0296088 A1 12/2011 Duzly et al.
 2012/0079171 A1 3/2012 Ju et al.
 2012/0102268 A1 4/2012 Smith et al.
 2012/0131263 A1 5/2012 Yeh
 2012/0131269 A1 5/2012 Fisher et al.
 2012/0210326 A1 8/2012 Torr et al.
 2013/0007348 A1 1/2013 Fai et al.
 2013/0138840 A1 5/2013 Kegel et al.
 2013/0145055 A1 6/2013 Kegel et al.
 2013/0332691 A1 12/2013 Hyvonen et al.
 2013/0339635 A1 12/2013 Amit et al.
 2013/0346668 A1 12/2013 Floman et al.

FOREIGN PATENT DOCUMENTS

EP 0481716 4/1992
 JP 59135563 8/1984
 KR 20060082040 A 7/2006

OTHER PUBLICATIONS

U.S. Appl. No. 13/358,806, filed Jan. 26, 2012, Mylly, et al., "Apparatus and Method to Provide Cache Move with Non-Volatile Mass Memory System," 45 pages.
 Chinese Office Action mailed Dec. 19, 2013 for Chinese patent application No. 200980106241.1, a counterpart foreign application of U.S. Pat. No. 8,307,180, 3 pages.
 Chinese Office Action mailed Apr. 9, 2013 for Chinese patent application No. 200980106241.1, a counterpart foreign application of U.S. Pat. No. 8,307,180, 4 pages.
 European Search Report for Application No. 09715221.9, dated Oct. 25, 2011, 30 pages.
 JEDEC Standard, "Embedded MultiMediaCard (eMMC) Product Standard, High Capacity," JESD84-A42, Jun. 2007, 29 pages.
 JEDEC Standard, "Embedded MultiMediaCard (eMMC) eMMC/ Card Product Standard, high Capacity, Including Reliable Write, Boot, and Sleep Modes," (MMCA, 4.3), JSEDD84-A43, Nov. 2007, 166 pages.
 JEDEC Standard, "Embedded MultiMediaCard (eMMC) Mechanical Standard," JESD84-C43, Jun. 2007, 13 pages.
 Translated Japanese Office Action mailed Jan. 16, 2013 for Japanese patent application No. 2010548134, a counterpart foreign application of U.S. Pat. No. 8,307,180, 6 pages.
 Translated Japanese Office Action mailed Nov. 25, 2013 for Japanese patent application No. 2013-103695, a counterpart foreign application of U.S. Pat. No. 8,307,180, 8 pages.
 Japanese Office Action mailed Aug. 27, 2013 for Japanese patent application No. 2010548134, a counterpart foreign application of U.S. Pat. No. 8,307,180, 4 pages.
 Japanese Search Report for Application No. 2010-548134, mailed on May 10, 2012, 11 pages.
 Translated Korean Office Action mailed Mar. 3, 2014 for Korean patent application No. 2013-7002338, a counterpart foreign application of U.S. Pat. No. 8,307,180, 5 pages.
 Office Action for Korean Patent Application No. 10-2010-7021534, mailed on Sep. 30, 2011, 3 pages.
 Lin et al., "A NAND Flash Memory Controller for SDIMM Flash Memory Card," IEEE 2007, pp. 933-935.
 Numonyz, "How to boot an embedded system from an eMMCTM equipped with a Microsoft FAT file system." Application note AN2539, Nov. 2008, pp. 1-25.

(56)

References Cited

OTHER PUBLICATIONS

Office Action for U.S. Appl. No. 13/451,951, mailed on Jan. 7, 2014, Kimmo J. Mylly, "Managing Operational State Data in Memory Module", 24 pages.

Office Action for U.S. Appl. No. 13/951,169, mailed on Oct. 8, 2013, Jani Hyvonen, "Extended Utilization Area for a Memory Device", 9 pages.

Final Office Action for U.S. Appl. No. 13/451,951, mailed on Dec. 4, 2014, Kimmo J. Mylly, "Managing Operational State Data of a Memory Module Using Host Memory in Association with State Change", 24 pages.

Final Office Action for U.S. Appl. No. 13/951,169, mailed on Mar. 27, 2014, Jani Hyvonen, "Extended Utilization Area for a Memory Device", 10 pages.

PCT Search Report and Written Opinion mailed Sep. 5, 2013 for PCT application No. PCT/US13/37298, 9 pages.

International Search Report for PCT Application No. PCT/FI2009/050083 dated Jun. 3, 2009, pages.

Apostolakis, et al., "Software-Based Self Testing of Symmetric Shared-Memory Multiprocessors", IEEE Transactions on Computers, vol. 58, No. 12, Dec. 2009, 13 pages.

"Embedded MultiMediaCard (eMMC) Mechanical Standard", JESD84-C43, JEDEC Standard, JEDEC Solid State Technology Association, Jun. 2007, 13 pages.

"How to Boot an Embedded System for an eMMC Equipped with a Microsoft FAT File System", AN2539 Numonyx Application Note, Nov. 2008, 25 pages.

Translated Japanese Office Action mailed Jan. 7, 2015 for Japanese patent application No. 2013-103695, a counterpart foreign application of U.S. Pat. No. 8,307,180, 8 pages.

Li, et al., "A Method for Improving Concurrent Write Performance by Dynamic Mapping Virtual Storage System Combined with Cache Management", 2011 IEEE 7th International Conference of Parallel Distributed System, Dec. 7-8, 2011, 10 pages.

Final Office Action for U.S. Appl. No. 13/527,745, mailed on Jan. 16, 2015, Matti Floman, "Virtual Memory Module", 22 pages.

Office Action for U.S. Appl. No. 13/358,806, mailed on Nov. 27, 2013, Kimmo J. Mylly, "Apparatus and Method to Provide Cache Move With Non-Volatile Mass Memory System", 26 pages.

Office Action for U.S. Appl. No. 13/596,480, mailed on Mar. 13, 2014, Kimmo J. Mylly, "Dynamic Central Cache Memory", 15 pages.

Office action for U.S. Appl. No. 13/527,745, mailed on Jun. 23, 2014, Floman et al., "Virtual Memory Module", 13 pages.

Final Office Action for U.S. Appl. No. 13/358,806, mailed on Sep. 10, 2014, Kimmo J. Mylly, "Apparatus and Method to Provide Cache Move With Non-Volatile Mass Memory System", 27 pages.

PCT Search Report and Written Opinion mailed Mar. 6, 2014 for PCT application No. PCT/US13/56980, 11 pages.

PCT Search Report and Written Opinion mailed Apr. 16, 2014 for PCT application No. PCT/US13/49434, 8 pages.

Tanenbaum, "Structured Computer Organization", Prentice-Hall, Inc, 1984, 5 pages.

Office Action for U.S. Appl. No. 13/358,806, mailed on Apr. 30, 2015, Kimmo J. Mylly, "Apparatus and Method to Provide Cache Move With Non-Volatile Mass Memory System", 42 pages.

Office Action for U.S. Appl. No. 13/451,951 mailed on Jun. 18, 2015, Kimmo J. Mylly, "Managing Operational State Data of a Memory Module Using Host Memory in Association with State Change", 33 pages.

Office Action for U.S. Appl. No. 14/732,507, mailed on Jul. 1, 2015, Jani Hyvonen, "Extended Utilization Area for a Memory Device", 11 pages.

Translation of the Chinese Office Action mailed Jul. 17, 2015 for Chinese patent application No. 201310136995.X, a counterpart foreign application of U.S. Appl. No. 13/451,951, 28 pages.

The Extended European Search Report mailed Aug. 31, 2015 for European patent application No. 13741595.6, a counterpart foreign application of U.S. Appl. No. 13/358,806, 8 pages.




FIG. 1A




FIG.1B




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG. 7

1

APPARATUS AND METHOD TO SHARE HOST SYSTEM RAM WITH MASS STORAGE MEMORY RAM

RELATED APPLICATION

This Application is a continuation of and claims priority to U.S. patent application Ser. No. 12/455,763, entitled "Apparatus and Method to Share Host System RAM with Mass Storage Memory RAM," filed Jun. 4, 2009, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The exemplary and non-limiting embodiments of this invention relate generally to memory storage systems, methods, devices and computer programs and, more specifically, relate to mass memory devices, such as those containing non-volatile flash memory.

BACKGROUND

This section is intended to provide a background or context to the invention that is recited in the claims. The description herein may include concepts that could be pursued, but are not necessarily ones that have been previously conceived, implemented or described. Therefore, unless otherwise indicated herein, what is described in this section is not prior art to the description and claims in this application and is not admitted to be prior art by inclusion in this section.

The following abbreviations that may be found in the specification and/or the drawing figures are defined as follows:

CPU central processing unit
eMMC embedded multimedia card
exFAT extended file allocation table
LBA logical block address
MMC multimedia card
RAM random access memory
SCSI small computer system interface
SD secure digital
SW software
UFS universal flash storage

Various types of flash-based mass storage memories currently exist. A basic premise of mass storage memory is to hide the flash technology complexity from the host system. A technology such as eMMC is one example.

FIG. 1A reproduces FIG. 2 from JEDEC Standard, Embedded MultiMediaCard (eMMC) Product Standard, High Capacity, JESD84-A42, June 2007, JEDEC Solid State Technology Association, and shows a functional block diagram of an eMMC. The JEDEC eMMC includes, in addition to the flash memory itself, an intelligent on-board controller that manages the MMC communication protocol. The controller also handles block-management functions such as logical block allocation and wear leveling. The interface includes a clock (CLK) input. Also included is a command (CMD), which is a bidirectional command channel used for device initialization and command transfers. Commands are sent from a bus master to the device, and responses are sent from the device to the host. Also included is a bidirectional data bus (DAT[7:0]). The DAT signals operate in push-pull mode. By default, after power-up or RESET, only DAT0 is used for data transfer. The memory controller can configure a wider data bus for data transfer using either DAT[3:0] (4-bit mode) or DAT[7:0] (8-bit mode).

2

One non-limiting example of a flash memory controller construction is described in "A NAND Flash Memory Controller for SD/MMC Flash Memory Card", Chuan-Sheng Lin and Lan-Rong Dung, IEEE Transactions of Magnetics, Vol. 43, No. 2, February 2007, pp. 933-935 (hereafter referred to as Lin et al.) FIG. 1B reproduces FIG. 1 of Lin et al., and shows an overall block diagram of the NAND flash controller architecture for a SD/MMC card. The particular controller illustrated happens to use a w-bit parallel Bose-Chaudhuri-Hocquengham (BCH) error-correction code (ECC) designed to correct random bit errors of the flash memory, in conjunction with a code-banking mechanism. Of particular interest herein are the various RAM memories (e.g., buffer RAM, bank RAM, common RAM) that form part of the controller architecture.

Reference may also be made to U.S. Patent Application Publication 2008/0228984, Sep. 18, 2008, "Single-Chip Multi-Media Card/Secure Digital (MMC/SD) Controller Reading Power-On Boot Code from Integrated Flash Memory for User Storage", I-Kang Yu et al. This publication describes another example of a flash controller where a Multi-Media Card/Secure Digital (MMC/SD) single-chip flash device contains a MMC/SD flash microcontroller and flash mass storage blocks containing flash memory arrays that are block-addressable rather than randomly-addressable. MMC/SD transactions from a host MMC/SD bus are read by a bus transceiver on the MMC/SD flash microcontroller. Various routines that execute on a CPU in the MMC/SD flash microcontroller are activated in response to commands in the MMC/SD transactions. A flash-memory controller in the MMC/SD flash microcontroller transfers data from the bus transceiver to the flash mass storage blocks for storage. Rather than booting from an internal ROM coupled to the CPU, a boot loader is transferred by direct memory access (DMA) from the first page of the flash mass storage block to an internal RAM. The flash memory is automatically read from the first page at power-on. The CPU then executes the boot loader from the internal RAM to load the control program. This approach is said to enable the microcontroller ROM to be eliminated or minimized.

Also of potential interest is an application note AN2539 "How to boot an embedded system from an eMMC™ equipped with a Microsoft FAT file system", Numonyx B. V., November 2008. This application note in Appendix A provides an overview of eMMC, and in Appendix B provides an overview of FAT.

SUMMARY

In a first aspect thereof the exemplary embodiments of this invention provide a method that comprises, in response to an allocation of read/write memory in a host device for use by a mass memory storage device, writing data from the mass memory storage device to the allocated read/write memory of the host device; and subsequently reading the data from the allocated memory to the mass memory storage device.

In another aspect thereof the exemplary embodiments of this invention provide an apparatus that comprises a controller; a volatile memory that is readable and writable by the controller; a non-volatile memory that is readable and writable by the controller; and an interface for connecting the apparatus to a host device. The controller is configurable to respond to an allocation of read/write memory in the host device to write data to the allocated memory of the host device, and to subsequently read the data from the allocated memory.

In another aspect thereof the exemplary embodiments of this invention provide a method that comprises allocating read/write memory in a host device for use by a mass memory storage device; receiving data from the mass memory storage device and writing the received data into the allocated read/write memory of the host device; and subsequently sending the data from the allocated memory to the mass memory storage device.

In a still further aspect thereof the exemplary embodiments of this invention provide an apparatus that comprises a controller; a memory that is readable and writable by the controller; and an interface for connecting the apparatus to a mass storage memory device. The controller is configurable to allocate a portion of the memory for use by the mass storage memory device. The controller is further configurable to receive data from the mass storage memory device and to store the received data in the allocated portion of the memory, and to subsequently send the data from the allocated portion of the memory to the mass storage memory device.

BRIEF DESCRIPTION OF THE DRAWINGS

In the attached Drawing Figures:

FIG. 1A reproduces FIG. 2 from JEDEC Standard, Embedded MultiMediaCard (eMMC) Product Standard, High Capacity, JESD84-A42, June 2007, JEDEC Solid State Technology Association, and shows a functional block diagram of an eMMC.

FIG. 1B reproduces FIG. 1 of Lin et al., and shows an example of an overall block diagram of a NAND flash controller architecture for a SD/MMC card.

FIG. 2 is a simplified block diagram of a host device connected with a mass storage memory device, and is helpful in describing the exemplary embodiments of this invention.

FIG. 3 is a signal/message flow diagram that describes an exemplary embodiment of this invention for the mass storage memory device of FIG. 2 to allocate, use and de-allocate RAM of the host device.

FIG. 4 is a signal/message flow diagram that describes another exemplary embodiment of this invention, where the mass storage memory device of FIG. 2 has a built-in file system.

FIG. 5 shows a block diagram of one exemplary embodiment of the host device when embodied as a wireless communication device.

FIG. 6 is a logic flow diagram that illustrates the operation of a method, and a result of execution of computer program instructions embodied on a computer readable memory, in accordance with the exemplary embodiments of this invention.

FIG. 7 is a logic flow diagram that illustrates the operation of a method, and a result of execution of computer program instructions embodied on a computer readable memory, further in accordance with the exemplary embodiments of this invention.

DETAILED DESCRIPTION

At present, most mass storage memories provide LBA-based access, e.g., eMMC and different types of external memory cards such as SD. However, it may also be the case that the entire file system (FS) SW is embedded in the mass storage memory device.

When a mass storage memory is used in a high volume consumer device, such as a mobile wireless communication

device, one important consideration is cost, and one factor affecting the cost is the amount of RAM in the mass storage memory device itself.

Another important consideration is performance. The overall performance depends on many factors. For example, for lengthy (time consuming) operations (in particular if the mass storage memory device contains an entire file system SW) there would be an advantage to include a substantial amount of RAM in the mass storage memory device. However, this can have a negative impact on the cost.

It may be the case that system context (metadata) would be stored in the flash memory of the mass storage memory device. However, this approach has several associated disadvantages. For example, repeatedly writing the system context (metadata) to the mass storage memory device raises wearing issues that can impact the usable life of the mass storage memory device. Also, writing data to the flash memory can be a relatively slow process.

Another important consideration is the power efficiency. To provide good power efficiency the mass storage memories are preferably shutdown (powered-off) when not needed (meaning also that the internal RAM of the device is preferably shutdown as well). However, and assuming that the RAM is volatile in nature, then whatever data is stored in the RAM is lost when the power is removed from the RAM. To then perform re-initialization after power-up all needed information (e.g., logical-to-physical mapping information and/or file system structures) need to be restored. A full re-initialization of a LBA mass storage memory may require a substantial (and user-noticeable) amount of time (e.g., up to one second with an SD card), and entire file system initialization (if the file system is resident in the mass storage memory) may take even longer. Therefore, it is desirable to retain internal device context over the power-off/power-on cycle.

Before further describing the exemplary embodiments of this invention, reference is made to FIG. 2 which shows is a simplified block diagram of a host system or device 10 connected with a mass storage memory 20 via a mass storage memory bus (MSMB) 18. The MSMB 18 may be compatible with any suitable mass memory interface standard such as MMC or UFS, as two non-limiting examples. The MSMB 18 may include signal lines such as those shown in FIG. 1A for an eMMC embodiment. The host device 10 includes at least one controller, such as a CPU 12 that operates in accordance with stored program instructions. The program instructions may be stored in a RAM 14 or in another memory or memories. The CPU 12 is connected with the RAM 14 and a MSMB interface (I/F) 16 via at least one internal bus 17. The MSMB interface 16 may include a memory controller (MC), or may be coupled with a MC unit associated with the CPU 12. The host device 10 may be a computer, a cellular phone, a digital camera, a gaming device or a PDA, as several non-limiting examples. Note that the RAM 14 may be any read/write memory or memory device, such as semiconductor memory or a disk-based memory.

The mass storage memory 20 includes a microcontroller or, more simply, a controller 22 that is connected via at least one internal bus 27 with a volatile RAM 24, a non-volatile mass memory 26 (e.g., a multi-gigabyte flash memory mass storage) and a MSMB interface (I/F) 28. The controller 22 operates in accordance with stored program instructions. The program instructions may be stored in the RAM 24 or in a ROM or in the mass memory 26. The mass storage memory 20 may be embodied as an MMC, eMMC or a SD device, as non-limiting examples, and may be external to (plugged into) the host device 10 or installed within the host device 10. Note that the mass memory 26 may, in some embodiments, store a

5

file system (FS) 26A. In this case then the RAM 24 may store FS-related metadata 24A, such as one or more data structures comprised of bit maps, file allocation table data and/or other FS-associated information.

The exemplary embodiments of this invention provide a technique to share the RAM 14 of the host device 10 with the mass storage memory device 20. It may be assumed that the host device 10 (e.g., a mobile computer, a cellular phone, a digital camera, a gaming device, a PDA, etc.) has the capability to allocate and de-allocate the RAM 14. As will be discussed in further detail below, the allocation of the RAM 14 may be performed dynamically or it may be performed statically. The allocation of a portion of the RAM may be performed in response to a request received at the host device 10, or at the initiative of the host device 10.

In the exemplary embodiments of this invention the RAM 14 allocation is provided for the mass storage memory 20 (connected via the MSMB 18 to the host CPU 12), if the mass storage memory 20 has a need to extend its own RAM 24 space and/or if the mass storage memory 20 has a need for non-volatile RAM (the contents of which are not lost when the mass storage memory 20 is powered-off). It is also within the scope of the exemplary embodiments of this invention for the mass storage memory 20 to read and/or write (R/W) allocated RAM 14 in the host device 10. The allocation/de-allocation and R/W access methods may be implemented by extensions to a command set used to communicate with the mass storage memory 20 via an applicable mass storage memory protocol.

In accordance with certain exemplary embodiments of this invention the mass storage memory device 20 is provided with a mechanism to interrupt/send a message to host device 10 to initiate an allocation of space in the RAM 14. The interrupt/message is sent over the MSMB 18, and may be considered as an extension to current command sets. Referring to FIG. 3, an allocate memory command is sent during operation 3-1. If the allocation request succeeds (indicated during operation 3-2) the controller 22 is enabled to extend its own RAM 24 with the RAM 14 of the host device 10. The mass storage memory device 20 may store, for example, large tables into the RAM 14 using a RAM WRITE command (a newly specified command), or it may fetch data from the host device RAM 14 using a RAM READ command (another newly specified command). The read or write operation is shown as interleaved operations 3-3, 3-4, 3-5, 3-6, . . . , 3-(N-1), 3-N. When the mass storage memory device 20 completes the operation with the RAM 14 it may free the host device RAM 14 using another newly specified command that requests that the host 10 RAM memory be de-allocated (operation 3-(N+1)).

FIG. 4 illustrates a further exemplary embodiment that utilizes the host system RAM 14 for the mass storage memory 26 having a built-in file system, such as the FS 26A shown in FIG. 2. First the host system 10 sends a SHUTDOWN command to the mass storage memory device 20 (operation 4-1). Next the mass storage memory device 20 allocates RAM 14 from the host 10 and then loads (stores using a RAM WRITE command) all vital 'static' file system-related data (meta-data 24A) into host RAM 14 (operation 4-2). 'Static' data in this context may be, for example, various bitmaps, such as an allocation bitmap in the exFAT or ext3 file systems. This data may be processed (e.g., at least one of sorted, arranged and filtered) by the CPU 12 (controller) of the host device, and may include data from a large number of sectors in the mass storage memory 26. Mass memory storage device 20 may then send a shutdown OK indication (operation 4-3). The host 10 can remove power from the mass memory storage device

6

20, and the device 20 may be physically removed from the MSMB 18. Re-initialization (operations 4-4, 4-5, 4-6) of the mass storage memory device 20 is performed when host device 10 needs to get/put certain data from or into the mass storage memory device 20. Re-initialization of the mass storage memory 26 (and the file system 26A) may be sped up by using the sorted/arranged/filtered read data from the RAM 14. When the re-initialization operation is completed the mass storage memory device 20 may de-allocate the used RAM 14 in the host device 10, or the RAM 14 may not be de-allocated thereby reserving the RAM space for future use by the mass storage memory device 20.

It should be noted that in other exemplary embodiments of this invention the allocation of host RAM 14 may occur differently. For example, the host device 10 may allocate RAM 14 dynamically and pass a 'pointer' to the allocated RAM to the mass storage memory device 20. It is then up to the controller 22 of the mass storage memory device 20 how to utilize the allocated host RAM 14. Note that in this embodiment an explicit allocation request from the mass storage memory device 20 may not be sent to the host device 10. Instead, the host device 10 may on its own initiative allocate a portion of the RAM 14, such as when it first detects the presence of the mass memory storage device 20. Of course, subsequent signaling between the mass storage memory device 20 and the host device 10 may be used to change the size of the allocated RAM 14 if the initial allocation is not sufficient for the needs of the controller 22. As another example of RAM 14 allocation, a portion of the RAM 14 may be allocated by the host 10 in a static manner, and the mass storage memory device 20 then simply uses the same portion of the RAM 14 each time it needs to extend the RAM 24. In this case the mass storage memory device 20 may already have knowledge of the location/size of the allocated RAM 14, and a pointer is not needed to be sent from the host device 10.

Note that while it may typically be the case that the mass storage memory device 20 will receive an allocation of host memory to store contents of the volatile RAM 24, in general the allocation may be for storing data for any read/write memory contained within the mass storage memory device 20.

FIG. 5 illustrates one non-limiting embodiment of the host device 10 used with the mass storage memory device 20, referred to in FIG. 5 simply as a memory card. In this exemplary embodiment the host device is embodied as a user equipment (UE), shown in both plan view (left) and sectional view (right). In FIG. 5 the UE 10 has a graphical display interface 120 and a user interface 122 illustrated as a keypad but understood as also encompassing touch screen technology at the graphical display interface 120 and voice recognition technology received at the microphone 124. A power actuator 126 controls the device being turned on and off by the user. The exemplary UE 10 may have a camera 128 which is shown as being forward facing (e.g., for video calls) but may alternatively or additionally be rearward facing (e.g., for capturing images and video for local storage). The camera 128 is controlled by a shutter actuator 30 and optionally by a zoom actuator which may alternatively function as a volume adjustment for the speaker(s) 34 when the camera 128 is not in an active mode.

Within the sectional view of FIG. 5 are seen multiple transmit/receive antennas 36 that are typically used for cellular communication. The antennas 36 may be multi-band for use with other radios in the UE. The operable ground plane for the antennas 36 is shown by shading as spanning the entire space enclosed by the UE housing though in some embodiments the ground plane may be limited to a smaller area, such

7

as disposed on a printed wiring board on which the power chip **38** is formed. The power chip **38** controls power amplification on the channels being transmitted and/or across the antennas that transmit simultaneously where spatial diversity is used, and amplifies the received signals. The power chip **38** outputs the amplified received signal to a radio frequency (RF) chip **40** which demodulates and downconverts the signal for baseband processing. A baseband (BB) chip **42** detects the signal which is then converted to a bit stream and finally decoded. Similar processing occurs in reverse for signals generated in the host device **10** and transmitted from it.

Signals going to and from the camera **128** may pass through an image/video processor **44** that encodes and decodes the various image frames. A separate audio processor **46** may also be present controlling signals to and from the speakers **34** and the microphone **124**. The graphical display interface **120** is refreshed from a frame memory **48** as controlled by a user interface chip **50** which may process signals to and from the display interface **20** and/or additionally process user inputs from the keypad **22** and elsewhere.

Certain embodiments of the UE **10** may also include one or more secondary radios such as a wireless local area network radio WLAN **37** and a Bluetooth radio **39**, which may incorporate an antenna on the chip or be coupled to an antenna off the chip. Throughout the apparatus are various memories such as random access memory RAM **43**, read only memory ROM **45**, and in some embodiments removable memory such as the illustrated memory card **20** on which various programs **10C** may be stored. All of these components within the UE **10** are normally powered by a portable power supply such as a battery **49**.

The processors **38**, **40**, **42**, **44**, **46**, **50**, if embodied as separate entities in a UE **10**, may operate in a slave relationship to the main processor (CPU) **12**, which may then be in a master relationship to them. Certain embodiments may be disposed across various chips and memories as shown, or disposed within another processor that combines some of the functions described above for FIG. **5**. Any or all of these various processors of FIG. **5** access one or more of the various memories, which may be on chip with the processor or separate from the chip with the processor. Note that the various integrated circuits (e.g., chips **38**, **40**, **42**, etc.) that were described above may be combined into a fewer number than described and, in a most compact case, may all be embodied physically within a single chip.

In this exemplary embodiment the CPU **12** of the UE **10** (the host device) operates with the memory card **20** (the mass storage memory device) as described above with respect to FIGS. **3** and **4** so that the RAM **24** of the memory card **20** may be extended to use the RAM **14** of the UE **10**.

There are a number of technical effects that may be realized by the use of the exemplary embodiments of the invention. For example, there is provided a cost efficient way to extend RAM in the mass storage memory device **20**. Further by example, the mass storage memory device **20** may be powered off, while retaining mass storage memory device information on the RAM **14** of the host system.

Based on the foregoing it should be apparent that the exemplary embodiments of this invention provide a method, apparatus and computer program(s) to extend the RAM of a mass storage memory device to include the RAM of an attached host device.

FIG. **6** is a logic flow diagram that illustrates the operation of a method, and a result of execution of computer program instructions, in accordance with the exemplary embodiments of this invention. In accordance with these exemplary embodiments a method performs, at Block **6A**, in response to

8

an allocation of read/write memory in a host device for use by a mass memory storage device, writing data from the mass memory storage device to the allocated read/write memory of the host device. At Block **6B** there is an operation of subsequently reading the data from the allocated memory to the mass memory storage device.

FIG. **7** is a logic flow diagram that illustrates the operation of a method, and a result of execution of computer program instructions, in accordance with the exemplary embodiments of this invention. In accordance with these exemplary embodiments a method performs, at Block **7A**, an operation of allocating read/write memory in a host device for use by a mass memory storage device. At Block **7B** there is an operation of receiving data from the mass memory storage device and writing the received data into the allocated read/write memory of the host device. At Block **7C** there is an operation of subsequently sending the data from the allocated memory to the mass memory storage device.

The various blocks shown in FIGS. **6** and **7** may be viewed as method steps, and/or as operations that result from operation of computer program code, and/or as a plurality of coupled logic circuit elements constructed to carry out the associated function(s).

In general, the various exemplary embodiments may be implemented in hardware or special purpose circuits, software, logic or any combination thereof. For example, some aspects may be implemented in hardware, while other aspects may be implemented in firmware or software which may be executed by a controller, microprocessor or other computing device, although the invention is not limited thereto. While various aspects of the exemplary embodiments of this invention may be illustrated and described as block diagrams, flow charts, or using some other pictorial representation, it is well understood that these blocks, apparatus, systems, techniques or methods described herein may be implemented in, as non-limiting examples, hardware, software, firmware, special purpose circuits or logic, general purpose hardware or controller or other computing devices, or some combination thereof.

It should thus be appreciated that at least some aspects of the exemplary embodiments of the inventions may be practiced in various components such as integrated circuit chips and modules, and that the exemplary embodiments of this invention may be realized in an apparatus that is embodied as an integrated circuit. The integrated circuit, or circuits, may comprise circuitry (as well as possibly firmware) for embodying at least one or more of a data processor or data processors, a digital signal processor or processors, baseband circuitry and radio frequency circuitry that are configurable so as to operate in accordance with the exemplary embodiments of this invention.

Various modifications and adaptations to the foregoing exemplary embodiments of this invention may become apparent to those skilled in the relevant arts in view of the foregoing description, when read in conjunction with the accompanying drawings. However, any and all modifications will still fall within the scope of the non-limiting and exemplary embodiments of this invention.

It should be noted that the terms "connected," "coupled," or any variant thereof, mean any connection or coupling, either direct or indirect, between two or more elements, and may encompass the presence of one or more intermediate elements between two elements that are "connected" or "coupled" together. The coupling or connection between the elements can be physical, logical, or a combination thereof. As employed herein two elements may be considered to be "connected" or "coupled" together by the use of one or more wires, cables and/or printed electrical connections, as well as

by the use of electromagnetic energy, such as electromagnetic energy having wavelengths in the radio frequency region, the microwave region and the optical (both visible and invisible) region, as several non-limiting and non-exhaustive examples.

Furthermore, some of the features of the various non-limiting and exemplary embodiments of this invention may be used to advantage without the corresponding use of other features. As such, the foregoing description should be considered as merely illustrative of the principles, teachings and exemplary embodiments of this invention, and not in limitation thereof.

What is claimed is:

1. A memory storage device, comprising:
 - a controller;
 - a random access memory that is readable and writable by the controller;
 - a non-volatile memory that is readable and writable by the controller; and
 - an interface for connecting the memory storage device to a host device;
 the controller operable to:
 - in response to receiving, from the host device, allocation information associated with read/write memory in the host device that is allocated for use by the memory storage device, create an extended random access memory that includes the read/write memory in the host device;
 - write data to the extended random access memory; and
 - read the data from the extended random access memory.
2. The memory storage device of claim 1, wherein the data comprises meta-data associated with a file system stored in the non-volatile memory of the memory storage device.
3. The memory storage device of claim 1, the controller further operable to:
 - remove power to the random access memory of the memory storage device after writing the data to the extended random access memory.
4. The memory storage device of claim 1, the controller further operable to:
 - send an allocate request to the host device to allocate the read/write memory in the host device.
5. The memory storage device of claim 1, the controller further operable to:
 - send a de-allocate request to the host device to de-allocate the the read/write memory in the host device.
6. The memory storage device of claim 1, wherein the non-volatile memory comprises flash memory.
7. The memory storage device of claim 1, wherein a logical-to-physical mapping table is stored in the extended random access memory.
8. A method comprising:
 - receiving, at a memory storage device, allocation information associated with read/write memory in a host device that is allocated for use by the memory storage device;
 - creating an extended random access memory that includes the read/write memory in the host device;
 - writing data to the extended random access memory; and
 - reading the data from the extended random access memory.
9. The method of claim 8, wherein the data comprises meta-data associated with a file system stored in a non-volatile memory of the memory storage device.
10. The method of claim 8, further comprising:
 - removing power to a random access memory of the memory storage device after writing the data to the extended random access memory.

11. The method of claim 8, further comprising:
 - sending an allocate request to the host device to allocate the read/write memory in the host device.
12. The method of claim 8, further comprising:
 - sending a de-allocate request to the host device to de-allocate the read/write memory in the host device.
13. The method of claim 8, wherein the memory storage device comprises flash memory.
14. The method of claim 8, wherein a logical-to-physical mapping table is stored in the extended random access memory.
15. A host device comprising:
 - an interface to connect the host device to a memory storage device that comprises non-volatile memory;
 - a host read/write memory;
 - a host controller that is operable to:
 - send allocation information associated with a portion of the host read/write memory that is allocated for inclusion in an extended random access memory for use by the memory storage device;
 - receive at least a first command to write data to the extended random access memory; and
 - receive at least a second command to read the data from the extended random access memory.
16. The host device of claim 15, wherein the data comprises meta-data associated with a file system stored in the non-volatile memory of the memory storage device.
17. The host device of claim 15, further comprising:
 - a host processor to process the data before sending the data from the host read/write memory to the memory storage device.
18. The host device of claim 17, wherein processing the data comprises at least one of sorting the data, arranging the data, or filtering the data.
19. The host device of claim 15, wherein the host controller is further operable to:
 - send a shutdown command to the memory storage device; and
 - remove power from the memory storage device after receiving the data.
20. The host device of claim 15, wherein the non-volatile memory comprises flash memory.
21. The host device of claim 15, wherein a logical-to-physical mapping table is stored in the extended random access memory.
22. The host device of claim 15, further comprising:
 - a host processor operable to allocate at least the portion of the host read/write memory that is included in the extended random access memory.
23. The host device of claim 15, wherein the host controller is further operable to:
 - write the data to at least the portion of the host read/write memory that is included in the extended random access memory; and
 - read the data from at least the portion of the host read/write memory that is included in the extended random access memory.
24. The host device of claim 15, wherein the host controller is further operable to:
 - send the allocation information based at least on detecting presence of the memory storage device.
25. A memory storage device, comprising:
 - a random access memory that is readable and writable;
 - a non-volatile memory that is readable and writable;
 - an interface for connecting the memory storage device to a host device;

means for receiving, at the memory storage device, allocation information associated with read/write memory in the host device that is allocated for use by the memory storage device;

means for creating an extended random access memory 5
that includes the read/write memory in the host device;

means for writing data to the extended random access memory; and

means for reading the data from the extended random access memory. 10

26. The memory storage device of claim **25**, wherein the data comprises meta-data associated with a file system stored in the non-volatile memory of the memory storage device.

27. The memory storage device of claim **25**, further comprising: 15

means for removing power to the random access memory of the memory storage device after writing the data to the extended random access memory.

* * * * *