



(11)

EP 3 329 722 B1

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:  
**03.06.2020 Bulletin 2020/23**

(51) Int Cl.:  
**H04W 48/08 (2009.01)**      **H04W 74/00 (2009.01)**

(21) Application number: **16760579.9**

(86) International application number:  
**PCT/US2016/044806**

(22) Date of filing: **29.07.2016**

(87) International publication number:  
**WO 2017/023785 (09.02.2017 Gazette 2017/06)**

## (54) TECHNIQUES FOR JOINT TRANSMISSION IN UNLICENSED SPECTRUM

VERFAHREN FÜR GEMEINSAME ÜBERTRAGUNG IN EINEM UNLIZENSIERTEN SPEKTRUM  
TECHNIQUES POUR UNE TRANSMISSION CONJOINTE DANS UN SPECTRE NON AUTORISÉ

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**

(30) Priority: **31.07.2015 US 201562199846 P  
28.07.2016 US 201615222731**

(43) Date of publication of application:  
**06.06.2018 Bulletin 2018/23**

(73) Proprietor: **Qualcomm Incorporated  
San Diego, CA 92121-1714 (US)**

(72) Inventors:  

- **ZHANG, Xiaoxia  
San Diego, California 92121-1714 (US)**
- **YERRAMALLI, Srinivas  
San Diego, California 92121-1714 (US)**
- **LUO, Tao  
San Diego, California 92121-1714 (US)**

(74) Representative: **Wegner, Hans  
Bardehle Pagenberg Partnerschaft mbB  
Patentanwälte, Rechtsanwälte  
Prinzregentenplatz 7  
81675 München (DE)**

(56) References cited:  

<b>EP-A1- 2 213 125</b>	<b>WO-A1-2009/053941</b>
<b>WO-A1-2014/074919</b>	<b>US-A1- 2008 181 156</b>
<b>US-A1- 2013 142 095</b>	<b>US-A1- 2014 153 471</b>

- **ETRI: "Design of variable-length preamble for modified LBE and fine frequency/time", 3GPP DRAFT; R1-150647\_DETAILED VARIABLE LENGTH PREAMBLE DESIGN, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE , vol. RAN WG1, no. Athens, Greece; 20150209 - 20150213 8 February 2015 (2015-02-08), XP050933849, Retrieved from the Internet:  
URL:[http://www.3gpp.org/ftp/Meetings\\_3GPP\\_SYNC/RAN1/Docs/](http://www.3gpp.org/ftp/Meetings_3GPP_SYNC/RAN1/Docs/) [retrieved on 2015-02-08]**

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

### BACKGROUND

**[0001]** Aspects of this disclosure relate generally to telecommunications, and more particularly to techniques for joint transmission in unlicensed spectrum.

**[0002]** Long Term Evolution networks are expanding operation in unlicensed radio frequency (RF) bands for data offload. For example, using carrier aggregation features, LTE networks can operate at higher data rates while using both licensed and unlicensed RF bands. A wireless communication network may be deployed to provide various types of services (e.g., voice, data, multimedia services, etc.) to users within a coverage area of the network. In some implementations, one or more access points (e.g., corresponding to different cells) provide wireless connectivity for access terminals (e.g., cell phones) that are operating within the coverage of the access point(s). In some implementations, peer devices provide wireless connectivity for communicating with one another.

**[0003]** Moreover, as LTE networks expand operation in unlicensed RF bands in order to focus on higher capacity and provide higher bitrates, a number of other requirements need to be fulfilled. For example, the LTE networks need to provide increased peak data rates, higher spectral efficiency, increased number of simultaneously active subscribers, and improved performance at cell edges. In order to improve performance at cell edges, Coordinated Multi-Point operation (CoMP) was introduced. In CoMP, a number of transmit points provide coordinated transmission in the downlink, and a number of receive points provide coordinated reception in the uplink. In the case of downlink, data is available for transmission from two transmitting network entities or transmit points (e.g., two access points or base stations, also referred to as cells or nodes). When two or more network entities transmit on the same frequency and in the same subframe the transmission may be referred to as a "joint transmission." A joint transmission can be broadly described as a simultaneous or concurrent transmission of data to a user equipment or UE (also referred to as a wireless device, wireless terminal device, wireless terminal, or mobile device) from multiple cooperating access points.

**[0004]** Similarly, multicast-broadcast single-frequency network (MBSFN) was introduced to further improve the efficiency of the enhanced Multimedia Broadcast Multicast Service (eMBMS) service, which can deliver services such as mobile TV using the LTE infrastructure. A network device may transmit the same data (identical data) to multiple UEs simultaneously. Furthermore, network devices configured in MBSFN mode may also engage in joint transmission on the downlink. For example, multiple network entities may transmit the identical data simultaneously so that device UE may receive the same data from multiple access points.

**[0005]** As such, and given the growing use of the unlicensed spectrum, techniques are needed to provide efficient and improved identification of the type of downlink transmissions from one or more network entities.

**[0006]** Document US 2013/0142095 discloses a system and method for traffic signalling in wireless or sensor networks. The system and method use information or bits in a Signal Field (SIG) of Physical Layer (PHY) preamble in a packet to provide traffic control information. A method implemented by a network component comprises indicating a traffic direction and a traffic type for traffic control in a SIG in a frame and transmitting the frame including the SIG. Another method comprises receiving in a frame a SIG for traffic control that indicates a transmission type and decoding the SIG field to determine whether to process remaining information in the frame if the frame comprises data payload or a Media Access Control (MAC) header.

**[0007]** Another example can be found in patent document WO2014/074919.

### SUMMARY

**[0008]** The invention is defined in the independent claims. The following presents a simplified summary of one or more aspects in order to provide a basic understanding of such aspects. This summary is not an extensive overview of all contemplated aspects, and is intended to neither identify key or critical elements of all aspects nor delineate the scope of any or all aspects. Its sole purpose is to present some concepts of one or more aspects in a simplified form as a prelude to the more detailed description that is presented later.

**[0009]** In accordance with an aspect, a present method for identifying joint transmissions in unlicensed spectrum is provided. The described aspects include receiving, at a user equipment (UE), a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. The described aspects further include determining whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble.

**[0010]** In another aspect, a present apparatus for identifying joint transmissions in unlicensed spectrum may include memory configured to store instructions, and one or more processors communicatively coupled with the memory, wherein the one or more processors and the memory are configured to receive, at a UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. The described aspects further determine whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble.

**[0011]** In another aspect, a present computer-readable medium may store computer executable code for identifying joint transmissions in unlicensed spectrum. The described aspects include code for receiving, at UE, a frame from one or more network entities over a contention-

based medium, wherein the frame includes a preamble. The described aspects further include code for determining whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble.

**[0012]** In another aspect, a present apparatus for identifying joint transmissions in unlicensed spectrum may include means for receiving, at UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. The described aspects further include means for determining whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble.

**[0013]** In accordance with another aspect, a present method for identifying joint transmissions in unlicensed spectrum is provided. The described aspects include determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. The described aspects further include transmitting the frame with a preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0014]** In another aspect, a present apparatus for identifying joint transmissions in unlicensed spectrum may include memory configured to store instructions, and one or more processors communicatively coupled with the memory, wherein the one or more processors and the memory are configured to determine, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. The described aspects further include transmit the frame with a preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0015]** In another aspect, a present computer-readable medium may store computer executable code for identifying joint transmissions in unlicensed spectrum. The described aspects include code for determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. The described aspects further include code for transmitting the frame with a preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0016]** In another aspect, a present apparatus for identifying joint transmissions in unlicensed spectrum may include means for determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. The described aspects further include means for transmitting the frame with a preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0017]** Various aspects and features of the disclosure are described in further detail below with reference to various examples thereof as shown in the accompanying

drawings. While the present disclosure is described below with reference to various examples, it should be understood that the present disclosure is not limited thereto. Those of ordinary skill in the art having access to the teachings herein will recognize additional implementations, modifications, and examples, as well as other fields of use, which are within the scope of the present disclosure as described herein, and with respect to which the present disclosure may be of significant utility.

## BRIEF DESCRIPTION OF THE DRAWINGS

**[0018]** The features, nature, and advantages of the present disclosure will become more apparent from the detailed description set forth below when taken in conjunction with the drawings in which like reference characters identify correspondingly throughout, where dashed lines may indicate optional components or actions, and wherein:

FIG. 1 shows a block diagram conceptually illustrating an example of a telecommunications system, in accordance with aspects described herein.

FIG. 2 is a diagram illustrating an example of an access network.

FIG. 3 is a diagram illustrating an example of an evolved Node B and user equipment in an access network.

FIGs. 4A and 4B are simplified block diagrams of several sample aspects of a communication system in accordance with various aspects of the present disclosure.

FIG. 5 is a diagram illustrating example frame structures for preamble transmission on a contention-based medium in accordance with various aspects of the present disclosure.

FIG. 6 is a flow diagram illustrating an example method of identifying joint transmissions in unlicensed spectrum during wireless communication in accordance with various aspects of the present disclosure.

FIG. 7 is another flow diagram illustrating an example method of identifying joint transmissions in unlicensed spectrum during wireless communication in accordance with various aspects of the present disclosure.

FIG. 8 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus including a frame identifying component in accordance with various aspects of the present disclosure.

FIG. 9 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system including a frame identifying component in accordance with various aspects of the present disclosure.

FIG. 10 is a conceptual data flow diagram illustrating the data flow between different means/components in an exemplary apparatus including a frame identi-

fying component in accordance with various aspects of the present disclosure.

FIG. 11 is a diagram illustrating an example of a hardware implementation for an apparatus employing a processing system including a frame identifying component in accordance with various aspects of the present disclosure.

## DETAILED DESCRIPTION

**[0019]** The detailed description set forth below in connection with the appended drawings is intended as a description of various configurations and is not intended to represent the only configurations in which the concepts described herein may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of various concepts. However, it will be apparent to those skilled in the art that these concepts may be practiced without these specific details. In some instances, well known components are shown in block diagram form in order to avoid obscuring such concepts. In an aspect, the term "component" as used herein may be one of the parts that make up a system, may be hardware or software, and may be divided into other components.

**[0020]** The present aspects generally relate to identifying joint transmissions in unlicensed spectrum during wireless communication. In particular, for example, preambles (e.g., channel usage beacon signals (CUBS) or a cell-specific reference signal (CRS), and/or physical frame format indicator channel (PFFICH) or a common PDCCH indicating the current frame format) may be used to indicate the start of a data transmission, and as such, a UE may be configured to search for preambles from a network entity acting as the serving cell. In an aspect, preamble detection is less power consuming than monitoring grants. Preambles may be configured in a manner in which the tone mapping is a function of public land mobile network (PLMN) identification (ID), and the sequence generation is a function of both PLMN ID and cell ID. Preambles with cell specific identifiers may be suitable for cell specific transmission (e.g., unicast transmissions), but they may not be able to exploit the gain with joint transmissions such as CoMP and/or MBSFN. Even if multiple cells transmit the same data, their corresponding preambles may suffer from other cell interference and therefore cannot benefit from joint transmission gains. For unicast transmissions (e.g., cell specific transmission) the UE may readily search for the preamble transmitted by the serving cell since the cell ID specific sequence of the serving cell is made previously available to the UE through cell acquisition. However, a UE may not be able to search for preambles corresponding to joint transmissions because the preambles are scrambled with additional identifiers and each frame in which the preambles are transmitted are dedicated with a specific transmission type (e.g., unicast, CoMP, or MBSFN). Therefore, in certain aspects, a UE operating in uni-

cast mode may be unable to search for preambles corresponding to joint transmissions.

**[0021]** Accordingly, in some aspects, the present methods and apparatuses may provide an efficient solution, as compared to current solutions, by identifying joint transmissions in unlicensed spectrum during wireless communication. In other words, in the present aspects, a UE may determine whether a transmission corresponds to a unicast transmission or a joint transmission. As such, the present aspects provide one or more mechanisms for receiving, at a UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble, and determining whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble (e.g., based on the preamble scrambling). Moreover, the present aspects also provide one or more mechanisms for determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission, and transmitting the frame with a preamble to a UE over a contention-based medium, where the preamble (e.g., the preamble scrambling and/or tone mapping) is based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0022]** Aspects of the disclosure are provided in the following description and related drawings directed to specific disclosed aspects. Alternate aspects may be devised without departing from the scope of the disclosure. Additionally, well-known aspects of the disclosure may not be described in detail or may be omitted so as not to obscure more relevant details. Further, many aspects are described in terms of sequences of actions to be performed by, for example, elements of a computing device. It will be recognized that various actions described herein can be performed by specific circuits (e.g., application specific integrated circuits (ASICs)), by program instructions being executed by one or more processors, or by a combination of both. Additionally, these sequence of actions described herein can be considered to be embodied entirely within any form of computer readable storage medium having stored therein a corresponding set of computer instructions that upon execution would cause an associated processor to perform the functionality described herein. Thus, the various aspects of the disclosure may be embodied in a number of different forms, all of which have been contemplated to be within the scope of the claimed subject matter. In addition, for each of the aspects described herein, the corresponding form of any such aspects may be described herein as, for example, "logic configured to" perform the described action.

**[0023]** Referring first to FIG. 1, a diagram illustrates an example of a wireless communications system 100, in accordance with aspects described herein. The wireless communications system 100 includes a plurality of base stations (e.g., eNBs, WLAN access points, or other access points) 105, a number of user equipment (UEs) 115, and a core network 137. One or more UEs 115 may in-

clude a frame identifying component 130 (see e.g., FIG. 4A) configured to identify joint transmissions in unlicensed spectrum. Similarly, one or more base stations 105 may include a frame identifying component 140 (see e.g., FIG. 4B) configured to identify joint transmissions in unlicensed spectrum. In an aspect, the frame identifying components 130/140 may search for preambles corresponding to joint transmissions even when a UE, such as UEs 115 are operating in unicast mode. The preambles are scrambled with additional identifiers and each frame in which the preambles are transmitted in are dedicated with a specific transmission type (e.g., unicast, CoMP, or MBSFN).

**[0024]** Accordingly, for example, the UEs 115 may communicate with one another (e.g., with or without the assistance of a base station 105 to schedule resources) using a direct message-based communication. Some of the base stations 105 may communicate with the UEs 115 under the control of a base station controller (not shown), which may be part of the core network 137 or the certain base stations 105 (e.g., eNBs) in various examples. Base stations 105 may communicate control information and/or user data with the core network 137 through backhaul links 126. In examples, the base stations 105 may communicate, either directly or indirectly, with each other over backhaul links 127, which may be wired or wireless communication links. The wireless communications system 100 may support operation on multiple carriers (waveform signals of different frequencies). Multi-carrier transmitters can transmit modulated signals simultaneously on the multiple carriers. For example, each of communication links 125 may be a multi-carrier signal modulated according to the various radio technologies described above. Each modulated signal may be sent on a different carrier and may carry control information (e.g., reference signals, control channels, etc.), overhead information, data, etc.

**[0025]** The base stations 105 may wirelessly communicate with the UEs 115 via one or more base station antennas. Each of the base stations 105 sites may provide communication coverage for a respective coverage area 110. In some examples, base stations 105 may be referred to as a base transceiver station, a radio base station, a radio transceiver, a basic service set (BSS), an extended service set (ESS), a NodeB, eNodeB, Home NodeB, a Home eNodeB, or some other suitable terminology. The coverage area 110 for a base station may be divided into sectors making up only a portion of the coverage area (not shown). The wireless communications system 100 may include base stations 105 of different types (e.g., macro, micro, and/or pico base stations). The base stations 105 may also utilize different radio technologies, such as cellular and/or WLAN radio access technologies (RAT). The base stations 105 may be associated with the same or different access networks or operator deployments. The coverage areas of different base stations 105, including the coverage areas of the same or different types of base stations 105, utilizing the

same or different radio technologies, and/or belonging to the same or different access networks, may overlap.

**[0026]** In LTE/LTE-Advanced (LTE-A), for example, the terms evolved Node B (eNodeB or eNB) may be generally used to describe the base stations 105. The wireless communications system 100 may be a Heterogeneous LTE/LTE-A network in which different types of access points provide coverage for various geographical regions. For example, each base station 105 may provide communication coverage for a macro cell, a pico cell, a femto cell, and/or other types of cell. Small cells such as pico cells, femto cells, and/or other types of cells may include low power nodes or LPNs. A macro cell generally covers a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by UEs 115 with service subscriptions with the network provider. A small cell would generally cover a relatively smaller geographic area and may allow unrestricted access by UEs 115 with service subscriptions with the network provider, for example, and in addition to unrestricted access, may also provide restricted access by UEs 115 having an association with the small cell (e.g., UEs in a closed subscriber group (CSG), UEs for users in the home, and the like). An eNB for a macro cell may be referred to as a macro eNB. An eNB for a small cell may be referred to as a small cell eNB. An eNB may support one or multiple (e.g., two, three, four, and the like) cells.

**[0027]** The core network 137 may communicate with the eNBs or other base stations 105 via a backhaul links 126 (e.g., S1 interface, etc.). The base stations 105 may also communicate with one another, e.g., directly or indirectly via backhaul links 127 (e.g., X2 interface, etc.) and/or via backhaul links 126 (e.g., through core network 137). The wireless communications system 100 may support synchronous or asynchronous operation. For synchronous operation, the base stations 105 may have similar frame timing, and transmissions from different base stations 105 may be approximately aligned in time. For asynchronous operation, the base stations 105 may have different frame timing, and transmissions from different base stations 105 may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

**[0028]** The UEs 115 are dispersed throughout the wireless communications system 100, and each UE 115 may be stationary or mobile. A UE 115 may also be referred to by those skilled in the art as a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology. A UE 115 may be a cellular phone, a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a tablet computer, a laptop computer, a cordless phone, a wearable item such as a watch or glasses, a wireless

local loop (WLL) station, a vehicle-based UE, or the like. A UE 115 may be able to communicate with macro eNodeBs, small cell eNodeBs, relays, and the like. A UE 115 may also be able to communicate over different access networks, such as cellular or other WWAN access networks, or WLAN access networks.

**[0029]** The communication links 125 shown in wireless communications system 100 may include uplink (UL) transmissions from a UE 115 to a base station 105, and/or downlink (DL) transmissions, from a base station 105 to a UE 115. The downlink transmissions may also be called forward link transmissions while the uplink transmissions may also be called reverse link transmissions. The UEs 115 may be configured to collaboratively communicate with multiple base stations 105 through, for example, Multiple Input Multiple Output (MIMO), carrier aggregation (CA), Coordinated Multi-Point (CoMP), multiple connectivity, or other schemes. MIMO techniques use multiple antennas on the base stations 105 and/or multiple antennas on the UEs 115 to transmit multiple data streams.

**[0030]** FIG. 2 is a diagram illustrating an example of an access network 200 in an LTE network architecture or similar cellular network architecture. In this example, the access network 200 is divided into a number of cellular regions (cells) 202. One or more lower power class base stations 208 may have cellular regions 210 that overlap with one or more of the cells 202. The lower power class base stations 208 may be a femto cell (e.g., home eNB (HeNB)), pico cell, micro cell, or remote radio head (RRH). The macro base stations 204 are each assigned to a respective cell 202 and are configured to provide an access point to the core network 137 for all the UEs 206 in the cells 202.

**[0031]** In an aspect, one or more UEs 206 may include a frame identifying component 130 (see e.g., FIG. 4A) configured to identify joint transmissions in unlicensed spectrum. Similarly, one or more base stations 204/208 may include a frame identifying component 140 (see e.g., FIG. 4B) configured to identify joint transmissions in unlicensed spectrum. There is no centralized controller in this example of an access network 200, but a centralized controller may be used in alternative configurations. The base stations 204 are responsible for all radio related functions including radio bearer control, admission control, mobility control, scheduling, security, and connectivity to one or more components of core network 137.

**[0032]** The modulation and multiple access scheme employed by the access network 200 may vary depending on the particular telecommunications standard being deployed. In LTE applications, OFDM may be used on the DL and SC-FDMA may be used on the UL to support both frequency division duplexing (FDD) and time division duplexing (TDD). As those skilled in the art will readily appreciate from the detailed description to follow, the various concepts presented herein are well suited for LTE applications. However, these concepts may be readily extended to other telecommunication standards employ-

ing other modulation and multiple access techniques. By way of example, these concepts may be extended to Evolution-Data Optimized (EV-DO) or Ultra Mobile Broadband (UMB). EV-DO and UMB are air interface standards promulgated by the 3rd Generation Partnership Project 2 (3GPP2) as part of the CDMA2000 family of standards and employs CDMA to provide broadband Internet access to mobile stations. These concepts may also be extended to Universal Terrestrial Radio Access (UTRA) employing Wideband-CDMA (W-CDMA) and other variants of CDMA, such as TD-SCDMA; Global System for Mobile Communications (GSM) employing TDMA; and Evolved UTRA (E-UTRA), IEEE 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, and Flash-OFDM employing OFDMA. UTRA, E-UTRA, UMTS, LTE and GSM are described in documents from the 3GPP organization. CDMA2000 and UMB are described in documents from the 3GPP2 organization. The actual wireless communication standard and the multiple access technology employed will depend on the specific application and the overall design constraints imposed on the system.

**[0033]** The base stations 204 may have multiple antennas supporting MIMO technology. The use of MIMO technology enables the base stations 204 to exploit the spatial domain to support spatial multiplexing, beamforming, and transmit diversity. Spatial multiplexing may be used to transmit different streams of data simultaneously on the same frequency. The data streams may be transmitted to a single UE 206 to increase the data rate or to multiple UEs 206 to increase the overall system capacity. This is achieved by spatially precoding each data stream (i.e., applying a scaling of an amplitude and a phase) and then transmitting each spatially precoded stream through multiple transmit antennas on the DL. The spatially precoded data streams arrive at the UE(s) 206 with different spatial signatures, which enables each of the UE(s) 206 to recover the one or more data streams destined for that UE 206. On the UL, each UE 206 transmits a spatially precoded data stream, which enables the base stations 204 to identify the source of each spatially precoded data stream.

**[0034]** Spatial multiplexing is generally used when channel conditions are good. When channel conditions are less favorable, beamforming may be used to focus the transmission energy in one or more directions. This may be achieved by spatially precoding the data for transmission through multiple antennas. To achieve good coverage at the edges of the cell, a single stream beamforming transmission may be used in combination with transmit diversity.

**[0035]** In the detailed description that follows, various aspects of an access network will be described with reference to a MIMO system supporting OFDM on the DL. OFDM is a spread-spectrum technique that modulates data over a number of subcarriers within an OFDM symbol. The subcarriers are spaced apart at precise frequencies. The spacing provides "orthogonality" that enables a receiver to recover the data from the subcarriers. In the

time domain, a guard interval (e.g., cyclic prefix) may be added to each OFDM symbol to combat inter-OFDM-symbol interference. The UL may use SC-FDMA in the form of a DFT-spread OFDM signal to compensate for high peak-to-average power ratio (PAPR).

**[0036]** FIG. 3 is a block diagram of a base station 310 in communication with a UE 350 in an access network. In the DL, upper layer packets from the core network are provided to a controller/processor 375. The controller/processor 375 implements the functionality of the L2 layer. In the DL, the controller/processor 375 provides header compression, ciphering, packet segmentation and reordering, multiplexing between logical and transport channels, and radio resource allocations to the UE 350 based on various priority metrics. The controller/processor 375 is also responsible for HARQ operations, retransmission of lost packets, and signaling to the UE 350.

**[0037]** The transmit (TX) processor 316 implements various signal processing functions for the L1 layer (i.e., physical layer). The signal processing functions includes coding and interleaving to facilitate forward error correction (FEC) at the UE 350 and mapping to signal constellations based on various modulation schemes (e.g., binary phase-shift keying (BPSK), quadrature phase-shift keying (QPSK), M-phase-shift keying (M-PSK), M-quadrature amplitude modulation (M-QAM)). The coded and modulated symbols are then split into parallel streams. Each stream is then mapped to an OFDM subcarrier, multiplexed with a reference signal (e.g., pilot) in the time and/or frequency domain, and then combined together using an Inverse Fast Fourier Transform (IFFT) to produce a physical channel carrying a time domain OFDM symbol stream. The OFDM stream is spatially precoded to produce multiple spatial streams. Channel estimates from a channel estimator 374 may be used to determine the coding and modulation scheme, as well as for spatial processing. The channel estimate may be derived from a reference signal and/or channel condition feedback transmitted by the UE 350. Each spatial stream is then provided to a different antenna 320 via a separate transmitter 318TX. Each transmitter 318TX modulates an RF carrier with a respective spatial stream for transmission. In addition, base station 310 may include a frame identifying component 140 (see e.g., FIG. 4B) configured to identify joint transmissions in unlicensed spectrum. Though frame identifying component 140 is shown as coupled to controller/processor 375, it is to be appreciated that frame identifying component 140 can also be coupled to other processors (e.g., RX processor 370, TX processor 316, etc.) and/or implemented by the one or more processors 316, 370, 375 to perform actions described herein. Furthermore, for example, frame identifying component 140 may be implemented by any one or more of the processors including, but not limited to, processors 316, 370, and/or 375. Similarly, frame identifying component 130 may be implemented by any one or more of the processors including, but not limited to,

processors 356, 359, and/or 368.

**[0038]** At the UE 350, each receiver 354RX receives a signal through its respective antenna 352. Each receiver 354RX recovers information modulated onto an RF carrier and provides the information to the receive (RX) processor 356. The RX processor 356 implements various signal processing functions of the L1 layer. The RX processor 356 performs spatial processing on the information to recover any spatial streams destined for the UE 350. If multiple spatial streams are destined for the UE 350, they may be combined by the RX processor 356 into a single OFDM symbol stream. The RX processor 356 then converts the OFDM symbol stream from the time-domain to the frequency domain using a Fast Fourier Transform (FFT). The frequency domain signal comprises a separate OFDM symbol stream for each subcarrier of the OFDM signal. The symbols on each subcarrier, and the reference signal, is recovered and demodulated by determining the most likely signal constellation points transmitted by the base station 310. These soft decisions may be based on channel estimates computed by the channel estimator 358. The soft decisions are then decoded and deinterleaved to recover the data and control signals that were originally transmitted by the base station 310 on the physical channel. The data and control signals are then provided to the controller/processor 359.

**[0039]** The controller/processor 359 implements the L2 layer. The controller/processor can be associated with a memory 360 that stores program codes and data. The memory 360 may be referred to as a computer-readable medium. In the UL, the controller/processor 359 provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing to recover upper layer packets from the core network. The upper layer packets are then provided to a data sink 362, which represents all the protocol layers above the L2 layer. Various control signals may also be provided to the data sink 362 for L3 processing. The controller/processor 359 is also responsible for error detection using an acknowledgement (ACK) and/or negative acknowledgement (NACK) protocol to support HARQ operations. In addition, UE 350 may include a frame identifying component 130 (see e.g., FIG. 4A) configured to identify joint transmissions in unlicensed spectrum. Though frame identifying component 130 is shown as coupled to controller/processor 359, it is to be appreciated that communicating component 461 can also be coupled to other processors (e.g., RX processor 356, TX processor 368, etc.) and/or implemented by the one or more processors 356, 359, 368 to perform actions described herein.

**[0040]** In the UL, a data source 367 is used to provide upper layer packets to the controller/processor 359. The data source 367 represents all protocol layers above the L2 layer. Similar to the functionality described in connection with the DL transmission by the base station 310, the controller/processor 359 implements the L2 layer for

the user plane and the control plane by providing header compression, ciphering, packet segmentation and reordering, and multiplexing between logical and transport channels based on radio resource allocations by the base station 310. The controller/processor 359 is also responsible for HARQ operations, retransmission of lost packets, and signaling to the base station 310.

**[0041]** Channel estimates derived by a channel estimator 358 from a reference signal or feedback transmitted by the base station 310 may be used by the TX processor 368 to select the appropriate coding and modulation schemes, and to facilitate spatial processing. The spatial streams generated by the TX processor 368 are provided to different antenna 352 via separate transmitters 354TX. Each transmitter 354TX modulates an RF carrier with a respective spatial stream for transmission.

**[0042]** The UL transmission is processed at the base station 310 in a manner similar to that described in connection with the receiver function at the UE 350. Each receiver 318RX receives a signal through its respective antenna 320. Each receiver 318RX recovers information modulated onto an RF carrier and provides the information to a RX processor 370. The RX processor 370 may implement the L1 layer.

**[0043]** The controller/processor 375 implements the L2 layer. The controller/processor 375 can be associated with a memory 376 that stores program codes and data. The memory 376 may be referred to as a computer-readable medium. In the UL, the controller/processor 375 provides demultiplexing between transport and logical channels, packet reassembly, deciphering, header decompression, control signal processing to recover upper layer packets from the UE 350. Upper layer packets from the controller/processor 375 may be provided to the core network. The controller/processor 375 is also responsible for error detection using an ACK and/or NACK protocol to support HARQ operations.

**[0044]** Referring to FIGs. 4A4A and 4B4B, in an aspect, a wireless communication system 400 includes at least one UE 115, similar to UE 115 (FIG. 1), UE 206 (FIG. 2), and/or UE 350 (FIG. 3), in communication coverage of at least network entities 105-a and 105-b. The UE 115 may communicate with network via network entity 105-b and/or network entity 105-a. In an example, UE 115 may transmit and/or receive wireless communication to and/or from network entities 105-a, 105-b via one or more communication channels 125-a, 125-b, which may include an uplink communication channel (or simply uplink channel) and a downlink communication channel (or simply downlink channel), such as but not limited to an uplink data channel and/or downlink data channel. Such wireless communications may include, but are not limited to, data, audio and/or video information.

**[0045]** Referring to FIG. 4A, in accordance with the present disclosure, UE 115 may include a memory 44, one or more processors 20 and a transceiver 60. The memory, one or more processors 20 and the transceiver

60 may communicate internally via a bus 11. In some examples, the memory 44 and the one or more processors 20 may be part of the same hardware component (e.g., may be part of a same board, module, or integrated circuit). Alternatively, the memory 44 and the one or more processors 20 may be separate components that may act in conjunction with one another. In some aspects, the bus 11 may be a communication system that transfers data between multiple components and subcomponents of the UE 115. In some examples, the one or more processors 20 may include any one or combination of modem processor, baseband processor, digital signal processor and/or transmit processor. Additionally or alternatively, the one or more processors 20 may include a frame identifying component 130 for carrying out one or more methods or procedures described herein. The frame identifying component 130 may comprise hardware, firmware, and/or software and may be configured to execute code or perform instructions stored in a memory (e.g., a computer-readable storage medium).

**[0046]** In some examples, the UE 115 may include the memory 44, such as for storing data used herein and/or local versions of applications or communication with frame identifying component 130 and/or one or more of its subcomponents being executed by the one or more processors 20. Memory 44 can include any type of computer-readable medium usable by a computer or processor 20, such as random access memory (RAM), read only memory (ROM), tapes, magnetic discs, optical discs, volatile memory, non-volatile memory, and any combination thereof. In an aspect, for example, memory 44 may be a computer-readable storage medium (e.g., a non-transitory medium) that stores one or more computer-executable codes defining frame identifying component 130 and/or one or more of its subcomponents, and/or data associated therewith, when UE 115 is operating processor 20 to execute frame identifying component 130 and/or one or more of its subcomponents. In some examples, the UE 115 may further include a transceiver 60 for transmitting and/or receiving one or more data and control signals to/from the network via network entity 105-a and/or 105-b. The transceiver 60 may comprise hardware, firmware, and/or software and may be configured to execute code or perform instructions stored in a memory (e.g., a computer-readable storage medium). The transceiver 60 may include a 1<sup>st</sup> RAT radio 160 comprising a modem 165, and a 2<sup>nd</sup> RAT radio 170 (e.g., LTE radio) comprising a modem 175. The 1<sup>st</sup> RAT radio 160 and 2<sup>nd</sup> RAT radio 170 may utilize one or more antennas 64 for transmitting signals to and receiving signals from the network entity 105-a and/or 105-b. In an example, 1<sup>st</sup> RAT radio 160 may be associated with a wireless local area network (WLAN) and 2<sup>nd</sup> RAT radio 170 may be associated with a wireless wide area network (WWAN) over unlicensed spectrum.

**[0047]** When the UE 115 (or any other devices in the system 400) uses a first RAT to communicate on a given resource, this communication may be subjected to inter-

ference from nearby devices that use a second RAT to communicate on that resource. For example, communication by the UE 115 via LTE using second RAT radio 170 on a particular unlicensed RF band may be subject to interference from Wi-Fi devices operating on that band. For convenience, LTE on an unlicensed RF band may be referred to herein as LTE/LTE Advanced in unlicensed spectrum, or simply LTE in the surrounding context.

**[0048]** When network entity 105-b (and/or network entity 105-a) sends downlink transmissions to UE 115, assigned resources on the downlink frequency band are utilized. For example, the network entity 105-b operating in an unlicensed RF band may be assigned an interface of RBs in which downlink data transmissions may be sent. In order to avoid collisions with other access points in a contention based downlink channel, the network entity 105-b may send a preamble. For convenience, LTE on an unlicensed RF band may be referred to herein as LTE/LTE Advanced in unlicensed spectrum, or simply LTE in the surrounding context. Moreover, LTE operating over an unlicensed spectrum may refer to the use or modification of LTE to operate in a contention-based communication system that uses a shared medium.

**[0049]** In some systems, LTE in unlicensed spectrum may be employed in a standalone configuration, with all carriers operating exclusively in an unlicensed portion of the wireless spectrum (e.g., LTE Standalone). In other systems, LTE in unlicensed spectrum may be employed in a manner that is supplemental to licensed band operation by providing one or more unlicensed carriers operating in the unlicensed portion of the wireless spectrum in conjunction with an anchor licensed carrier operating in the licensed portion of the wireless spectrum (e.g., LTE Supplemental DownLink (SDL)). In either case, carrier aggregation may be employed to manage the different component carriers, with one carrier serving as the Primary Cell (PCell) for the corresponding UE (e.g., an anchor licensed carrier in LTE SDL or a designated one of the unlicensed carriers in LTE Standalone) and the remaining carriers serving as respective Secondary Cells (SCells). In this way, the PCell may provide an FDD paired downlink and uplink (licensed or unlicensed), and each SCell may provide additional downlink capacity as desired.

**[0050]** In general, LTE utilizes orthogonal frequency division multiplexing (OFDM) on the downlink and single-carrier frequency division multiplexing (SC-FDM) on the uplink. OFDM and SC-FDM partition the system bandwidth into multiple (K) orthogonal subcarriers, which are also commonly referred to as tones, bins, etc. Each subcarrier may be modulated with data. In general, modulation symbols are sent in the frequency domain with OFDM and in the time domain with SC-FDM. The spacing between adjacent subcarriers may be fixed, and the total number of subcarriers (K) may be dependent on the system bandwidth. For example, K may be equal to 128, 256, 512, 1024 or 2048 for system bandwidth of 1.25, 2.5, 5, 10 or 20 megahertz (MHz), respectively. The sys-

tem bandwidth may also be partitioned into subbands. For example, a subband may cover 1.08 MHz, and there may be 1, 2, 4, 8 or 16 subbands for system bandwidth of 1.25, 2.5, 5, 10 or 20 MHz, respectively.

**[0051]** LTE may also use carrier aggregation. UEs (e.g., LTE-Advanced enabled UEs) may use spectrum of up to 20 MHz bandwidths allocated in a carrier aggregation of up to a total of 100 MHz (5 component carriers) used for transmission and reception. For the LTE-Advanced enabled wireless communication systems, two types of carrier aggregation (CA) methods have been proposed, continuous CA and non-continuous CA. Continuous CA occurs when multiple available component carriers are adjacent to each other. On the other hand, non-continuous CA occurs when multiple non-adjacent available component carriers are separated along the frequency band. Both non-continuous and continuous CA may aggregate multiple component carriers to serve a single unit of LTE-Advanced UEs.

**[0052]** In a blended radio environment such as system 400, different RATs may make use of different channels at different times. Because different RATs are sharing the spectrum and operating partly independently of others, access to one channel may not imply access to another channel. Accordingly, a device capable of transmitting using multiple channels may need to determine whether each channel is available before transmitting. In order to increase bandwidth and throughput, it may be beneficial in some situations to wait for an additional channel to become available rather than transmitting using currently available channel(s).

**[0053]** Similarly, with regard to FIG. 4B, network entity 105-b may include a memory 45, one or more processors 21 and a transceiver 61. Memory 45, one or more processors 21 and a transceiver 61 may operate in the same and/or similar manner to memory 44, one or more processors 20 and a transceiver 60 of UE 115 described in FIG. 4A. Furthermore, memory 45, one or more processors 21 and a transceiver 61 may operate the same and/or similar components including, but not limited to a 1<sup>st</sup> RAT radio 161 with modem 166, a 2<sup>nd</sup> RAT radio 171 with modem 176, and antennas 65. Moreover, memory 45, one or more processors 21 and the transceiver 61 may communicate internally via a bus 12.

**[0054]** Referring back to FIG. 4A, as noted above, UE 115 may include the frame identifying component 130 for identifying joint transmissions in unlicensed spectrum from either or both network entity 105-a and/or 105-b. Identifying joint transmissions may involve identifying or distinguishing between unicast transmissions and joint transmissions, as well as identifying the type of joint transmission (e.g., CoMP or MBSFN transmission). Frame identifying component 130 may include hardware or means for identifying joint transmissions in unlicensed spectrum. Frame identifying component 130 may include a frame 131 which may include a preamble 132, and a determining component 133. The frame identifying component 130 and/or a receiver (not shown) may be con-

figured to receive a frame 131 from one or more access points (e.g., network entities 105-a and/or 105-b) over a contention-based spectrum, and the frame 131 includes a preamble 132. The determining component 133 may determine whether the frame 131 corresponds to a unicast transmission 134 or a joint transmission 135 based on the preamble 132, and if the frame is a joint transmission 135, which type of joint transmission is associated with the frame 131. For example, determining component 133 may determine whether the frame corresponds to a unicast transmission 134 or a joint transmission 135 based on the identifiers used to scramble preamble 132 and/or to obtain tone mapping for preamble 132. In an aspect, an UE 115 configured in unicast mode may execute descrambling component 136 to descramble preambles using the cell identifier (ID) and/or extract tone mapping for preambles using the cell ID. Further, UE 115 configured in CoMP mode may execute descrambling component 136 to descramble and/or extract tone mapping for preambles using the cell identifier and a virtual cell identifier. Additionally, UE 115 configured in MBSFN mode may execute descrambling component 136 to de-scramble and/or extract tone mapping for preambles using the cell identifier and an MBSFN area identifier. As a result, a UE, such as UE 115, that is configured for unicast mode may reduce power consumption by search for preambles instead of monitoring for grants since it does not decode joint transmissions. Specifically, the UE 115 may search for preambles scrambled with a cell identifier which is less power consuming than monitoring for grants.

**[0055]** Furthermore, UE 115 may search for preambles scrambled with either virtual cell identifiers or MBSFN identifiers and trigger a sleep mode if the preambles are found. For example, if UE 115 is in CoMP mode but detects a preamble 132 with a MBSFN identifier, UE 115 may assume the frame is dedicated for MBSFN transmissions, and triggers sleep mode until the next frame is received. Similarly, if UE 115 is only monitoring MBSFN transmissions but is not configured in CoMP mode, and detects a preamble 132 with a virtual cell identifier that is not configured for MBSFN transmission, then UE 115 may trigger a sleep mode until the next frame is received. Therefore, UE 115 searches not only its own preamble 132 but also searches for preamble with other possible identifiers to determine what transmission type the frame will be dedicated to. UE 115 may receive the one or more identifiers (e.g., cell identifier, virtual cell identifier, and/or MBSFN identifier) via one or more system information blocks (SIBs) from a network entity or via the RRC configuration message, such as network entity 105-b. Moreover, the network entity 105-b and UE 115 may perform time division multiplexed (TDM) operations among the unicast transmission and joint transmission (e.g., CoMP or MBSFN) on the frame 131 (see e.g., FIG. 2).

**[0056]** Referring to FIG. 4B, network entity 105-b may include a frame identifying component 140 for identifying whether a frame to be transmitted corresponds to joint transmissions. Frame identifying component 140 may in-

clude hardware or means for identifying the transmission type for a frame (e.g., frame 142) to be transmitted over the unlicensed or shared spectrum (e.g., by accessing a contention-based medium). Frame identifying component 140 may include a determining component 141. The determining component 141 may include hardware or means for determining whether a frame 142 corresponds to a unicast transmission 144 or a joint transmission 145. In an aspect, scrambling component 146 may configure the preamble 143 with a cell identifier for a unicast transmission 144, a virtual cell identifier for a joint transmission 145 such as CoMP, or a MBSFN identifier for a joint transmission 145 such as MBSFN. Furthermore, frame identifying component 140 may include a transceiver 60 configured to transmit the frame 142 with a preamble 143 to UE 115 over a contention-based spectrum based on determining whether the frame 142 corresponds to the unicast transmission 144 or the joint transmission 145. Moreover, frame identifying component 140 may configure network entity 105-b to transmit one or more SIBs comprising one or more identifiers to any UEs served by the network entity 105-b. For example, network entity 105-b may signal virtual cell identifiers for unicast mode UEs so that unicast mode UEs may be configured to search for both preambles with cell identifiers and virtual cell identifiers in order to determine what transmission type a receive frame corresponds to.

**[0057]** Additionally, as used herein, the one or more wireless nodes, including, but not limited to, network entities 105-a and 105-a of wireless communication system 400, may include one or more of any type of network component, such as a network entity, including a base station or node B, a relay, a peer-to-peer device, an authentication, authorization and accounting (AAA) server, a mobile switching center (MSC), a radio network controller (RNC), etc. In a further aspect, the one or more wireless serving nodes of wireless communication system 400 may include one or more small cell base stations, such as, but not limited to a femtocell, picocell, microcell, or any other base station having a relatively small transmit power or relatively small coverage area as compared to a macro base station.

**[0058]** Referring to FIG. 5, is a diagram 500 illustrating an example downlink transmission by one or more network entities or nodes (e.g., network entity 105-a or network entity 105-b) engaged in joint transmission over an unlicensed or shared spectrum. In an aspect, diagram 500 illustrates a scenario where a first frame, a second frame, a third frame, and a fourth frame that are part of a sequence of frames are transmitted on an unlicensed or shared spectrum from a network entity (e.g., network entity 105-b of FIG. 4A) to a UE (e.g., UE 115 of FIG. 4A). For example, UE 115 may receive the first frame and execute frame identifying component 130 to determine whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble. In this example, the first frame is identified with a CoMP preamble, so UE 115 determines that the first frame cor-

responds to a joint transmission. As such, a UE, such as UE 115, that is operating in unicast mode may trigger sleep mode for the remainder of the frame (and until the next frame is received) in order to save power since it does not process joint transmission data. Once UE 115 receives the second frame it may return to active mode and again determine whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble. In this example, the second frame is identified with a unicast preamble, so UE 115 determines that the second frame corresponds to a unicast transmission. As such, the UE 115 will decode the remaining data received on the second frame. For the third and fourth frames, UE 115 will again determine whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble. In this example, third and fourth frames are identified with a MBSFN preamble, so UE 115 determines that the third and fourth frames correspond to a joint transmission. As such, UE 115 may trigger sleep mode for the remainder of each frame (and until the next frame is received) in order to save power.

**[0059]** Referring to FIG. 6, an example of one or more operations and/or an example of architectural layout and components and subcomponents (FIG. 4A) of an aspect of frame identifying component 130 (FIG. 4A) according to the present apparatus and methods are described with reference to one or more methods and one or more components that may perform the actions of these methods. Although the operations described below are presented in a particular order and/or as being performed by an example component, it should be understood that the ordering of the actions and the components performing the actions may be varied, depending on the implementation. Also, although the frame identifying component 130 is illustrated as having a number of subcomponents, it should be understood that one or more of the illustrated subcomponent may be separate from, but in communication with, the frame identifying component 130 and/or each other. Moreover, it should be understood that the following actions or components described with respect to the frame identifying component 130 and/or its sub-components may be performed by a specially-programmed processor, a processor executing specially-programmed software or computer-readable media, or by any other combination of a hardware component and/or a software component specially configured for performing the described actions or components.

**[0060]** In an aspect, at block 610, method 600 includes receiving, at a UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. In an aspect, for example, UE 115, may execute frame identifying component 130 (FIG. 4A) and/or a transceiver 60 to receive a frame 131 from one or more network entities (network entity 105-a and/or 105-b) over a contention-based medium, wherein the frame 131 includes a preamble 132. Further, the preamble may comprise a channel usage beacon signal (CUBS) or a cell-specific reference signal (CRS). The

preamble may also comprise a physical frame format indicator channel (PFFICH) or a common PDCCH indicating the current frame format. In a further aspect, processing system 1114 (FIG. 11), processor 1104, and/or memory 1106 may execute reception component 1004, or

5 may perform at least some of the functions of reception component 1004, to receive a frame 131 from one or more network entities over a contention-based medium.

**[0061]** In an aspect, at block 620, method 600 optionally includes identifying a scrambling of the preamble. In an aspect, for example, UE 115, may execute frame identifying component 130 (FIG. 4A) and/or descrambling component 136 to identify a scrambling of the preamble 132. For example, the preamble 132 may be scrambled by identifier associated with a specific transmission type such as a cell identifier, virtual cell identifier, or MBSFN identifier. In a further aspect, processing system 1114 (FIG. 11), processor 1104, and/or memory 1106 may execute frame identifying component 1020, or may perform 10 at least some of the functions of frame identifying component 1020, to identify a scrambling of the preamble 132.

**[0062]** In an aspect, at block 630, method 600 includes determining whether the frame corresponds to a unicast 15 transmission or a joint transmission based on the preamble. In an aspect, for example, UE 115, may execute frame identifying component 130 (FIG. 4A) and/or determining component 133 to determine whether the frame 131 corresponds to a unicast transmission 134 or a joint 20 transmission 135 based on the preamble 132. For example, frame identifying component 130 and/or determining component 133 may determine whether the frame 131 corresponds to the unicast transmission 134 or joint transmission 135 based on the scrambling of the preamble 132. In an aspect, frame identifying component 130 and/or determining component 133 may determine that the frame 131 corresponds to the unicast transmission 134 in response to identifying that the preamble 132 is 25 scrambled by a cell identifier. As such, method 600 may proceed to block 640. Moreover, frame identifying component 130 and/or determining component 133 may determine that the frame 131 corresponds to a joint transmission 135 associated with a CoMP transmission in response to identifying that the preamble 132 is scrambled by a cell identifier. As such, method 600 may proceed to block 650. Similarly, frame identifying component 130 and/or determining component 133 may determine that the frame 131 corresponds to a joint transmission 30 35 40 45 50 55 60 65 70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190 195 200 205 210 215 220 225 230 235 240 245 250 255 260 265 270 275 280 285 290 295 300 305 310 315 320 325 330 335 340 345 350 355 360 365 370 375 380 385 390 395 400 405 410 415 420 425 430 435 440 445 450 455 460 465 470 475 480 485 490 495 500 505 510 515 520 525 530 535 540 545 550 555 560 565 570 575 580 585 590 595 600 605 610 615 620 625 630 635 640 645 650 655 660 665 670 675 680 685 690 695 700 705 710 715 720 725 730 735 740 745 750 755 760 765 770 775 780 785 790 795 800 805 810 815 820 825 830 835 840 845 850 855 860 865 870 875 880 885 890 895 900 905 910 915 920 925 930 935 940 945 950 955 960 965 970 975 980 985 990 995 1000 1005 1010 1015 1020 1025 1030 1035 1040 1045 1050 1055 1060 1065 1070 1075 1080 1085 1090 1095 1100 1105 1110 1115 1120 1125 1130 1135 1140 1145 1150 1155 1160 1165 1170 1175 1180 1185 1190 1195 1200 1205 1210 1215 1220 1225 1230 1235 1240 1245 1250 1255 1260 1265 1270 1275 1280 1285 1290 1295 1300 1305 1310 1315 1320 1325 1330 1335 1340 1345 1350 1355 1360 1365 1370 1375 1380 1385 1390 1395 1400 1405 1410 1415 1420 1425 1430 1435 1440 1445 1450 1455 1460 1465 1470 1475 1480 1485 1490 1495 1500 1505 1510 1515 1520 1525 1530 1535 1540 1545 1550 1555 1560 1565 1570 1575 1580 1585 1590 1595 1600 1605 1610 1615 1620 1625 1630 1635 1640 1645 1650 1655 1660 1665 1670 1675 1680 1685 1690 1695 1700 1705 1710 1715 1720 1725 1730 1735 1740 1745 1750 1755 1760 1765 1770 1775 1780 1785 1790 1795 1800 1805 1810 1815 1820 1825 1830 1835 1840 1845 1850 1855 1860 1865 1870 1875 1880 1885 1890 1895 1900 1905 1910 1915 1920 1925 1930 1935 1940 1945 1950 1955 1960 1965 1970 1975 1980 1985 1990 1995 2000 2005 2010 2015 2020 2025 2030 2035 2040 2045 2050 2055 2060 2065 2070 2075 2080 2085 2090 2095 2100 2105 2110 2115 2120 2125 2130 2135 2140 2145 2150 2155 2160 2165 2170 2175 2180 2185 2190 2195 2200 2205 2210 2215 2220 2225 2230 2235 2240 2245 2250 2255 2260 2265 2270 2275 2280 2285 2290 2295 2300 2305 2310 2315 2320 2325 2330 2335 2340 2345 2350 2355 2360 2365 2370 2375 2380 2385 2390 2395 2400 2405 2410 2415 2420 2425 2430 2435 2440 2445 2450 2455 2460 2465 2470 2475 2480 2485 2490 2495 2500 2505 2510 2515 2520 2525 2530 2535 2540 2545 2550 2555 2560 2565 2570 2575 2580 2585 2590 2595 2600 2605 2610 2615 2620 2625 2630 2635 2640 2645 2650 2655 2660 2665 2670 2675 2680 2685 2690 2695 2700 2705 2710 2715 2720 2725 2730 2735 2740 2745 2750 2755 2760 2765 2770 2775 2780 2785 2790 2795 2800 2805 2810 2815 2820 2825 2830 2835 2840 2845 2850 2855 2860 2865 2870 2875 2880 2885 2890 2895 2900 2905 2910 2915 2920 2925 2930 2935 2940 2945 2950 2955 2960 2965 2970 2975 2980 2985 2990 2995 3000 3005 3010 3015 3020 3025 3030 3035 3040 3045 3050 3055 3060 3065 3070 3075 3080 3085 3090 3095 3100 3105 3110 3115 3120 3125 3130 3135 3140 3145 3150 3155 3160 3165 3170 3175 3180 3185 3190 3195 3200 3205 3210 3215 3220 3225 3230 3235 3240 3245 3250 3255 3260 3265 3270 3275 3280 3285 3290 3295 3300 3305 3310 3315 3320 3325 3330 3335 3340 3345 3350 3355 3360 3365 3370 3375 3380 3385 3390 3395 3400 3405 3410 3415 3420 3425 3430 3435 3440 3445 3450 3455 3460 3465 3470 3475 3480 3485 3490 3495 3500 3505 3510 3515 3520 3525 3530 3535 3540 3545 3550 3555 3560 3565 3570 3575 3580 3585 3590 3595 3600 3605 3610 3615 3620 3625 3630 3635 3640 3645 3650 3655 3660 3665 3670 3675 3680 3685 3690 3695 3700 3705 3710 3715 3720 3725 3730 3735 3740 3745 3750 3755 3760 3765 3770 3775 3780 3785 3790 3795 3800 3805 3810 3815 3820 3825 3830 3835 3840 3845 3850 3855 3860 3865 3870 3875 3880 3885 3890 3895 3900 3905 3910 3915 3920 3925 3930 3935 3940 3945 3950 3955 3960 3965 3970 3975 3980 3985 3990 3995 4000 4005 4010 4015 4020 4025 4030 4035 4040 4045 4050 4055 4060 4065 4070 4075 4080 4085 4090 4095 4100 4105 4110 4115 4120 4125 4130 4135 4140 4145 4150 4155 4160 4165 4170 4175 4180 4185 4190 4195 4200 4205 4210 4215 4220 4225 4230 4235 4240 4245 4250 4255 4260 4265 4270 4275 4280 4285 4290 4295 4300 4305 4310 4315 4320 4325 4330 4335 4340 4345 4350 4355 4360 4365 4370 4375 4380 4385 4390 4395 4400 4405 4410 4415 4420 4425 4430 4435 4440 4445 4450 4455 4460 4465 4470 4475 4480 4485 4490 4495 4500 4505 4510 4515 4520 4525 4530 4535 4540 4545 4550 4555 4560 4565 4570 4575 4580 4585 4590 4595 4600 4605 4610 4615 4620 4625 4630 4635 4640 4645 4650 4655 4660 4665 4670 4675 4680 4685 4690 4695 4700 4705 4710 4715 4720 4725 4730 4735 4740 4745 4750 4755 4760 4765 4770 4775 4780 4785 4790 4795 4800 4805 4810 4815 4820 4825 4830 4835 4840 4845 4850 4855 4860 4865 4870 4875 4880 4885 4890 4895 4900 4905 4910 4915 4920 4925 4930 4935 4940 4945 4950 4955 4960 4965 4970 4975 4980 4985 4990 4995 5000 5005 5010 5015 5020 5025 5030 5035 5040 5045 5050 5055 5060 5065 5070 5075 5080 5085 5090 5095 5100 5105 5110 5115 5120 5125 5130 5135 5140 5145 5150 5155 5160 5165 5170 5175 5180 5185 5190 5195 5200 5205 5210 5215 5220 5225 5230 5235 5240 5245 5250 5255 5260 5265 5270 5275 5280 5285 5290 5295 5300 5305 5310 5315 5320 5325 5330 5335 5340 5345 5350 5355 5360 5365 5370 5375 5380 5385 5390 5395 5400 5405 5410 5415 5420 5425 5430 5435 5440 5445 5450 5455 5460 5465 5470 5475 5480 5485 5490 5495 5500 5505 5510 5515 5520 5525 5530 5535 5540 5545 5550 5555 5560 5565 5570 5575 5580 5585 5590 5595 5600 5605 5610 5615 5620 5625 5630 5635 5640 5645 5650 5655 5660 5665 5670 5675 5680 5685 5690 5695 5700 5705 5710 5715 5720 5725 5730 5735 5740 5745 5750 5755 5760 5765 5770 5775 5780 5785 5790 5795 5800 5805 5810 5815 5820 5825 5830 5835 5840 5845 5850 5855 5860 5865 5870 5875 5880 5885 5890 5895 5900 5905 5910 5915 5920 5925 5930 5935 5940 5945 5950 5955 5960 5965 5970 5975 5980 5985 5990 5995 6000 6005 6010 6015 6020 6025 6030 6035 6040 6045 6050 6055 6060 6065 6070 6075 6080 6085 6090 6095 6100 6105 6110 6115 6120 6125 6130 6135 6140 6145 6150 6155 6160 6165 6170 6175 6180 6185 6190 6195 6200 6205 6210 6215 6220 6225 6230 6235 6240 6245 6250 6255 6260 6265 6270 6275 6280 6285 6290 6295 6300 6305 6310 6315 6320 6325 6330 6335 6340 6345 6350 6355 6360 6365 6370 6375 6380 6385 6390 6395 6400 6405 6410 6415 6420 6425 6430 6435 6440 6445 6450 6455 6460 6465 6470 6475 6480 6485 6490 6495 6500 6505 6510 6515 6520 6525 6530 6535 6540 6545 6550 6555 6560 6565 6570 6575 6580 6585 6590 6595 6600 6605 6610 6615 6620 6625 6630 6635 6640 6645 6650 6655 6660 6665 6670 6675 6680 6685 6690 6695 6700 6705 6710 6715 6720 6725 6730 6735 6740 6745 6750 6755 6760 6765 6770 6775 6780 6785 6790 6795 6800 6805 6810 6815 6820 6825 6830 6835 6840 6845 6850 6855 6860 6865 6870 6875 6880 6885 6890 6895 6900 6905 6910 6915 6920 6925 6930 6935 6940 6945 6950 6955 6960 6965 6970 6975 6980 6985 6990 6995 7000 7005 7010 7015 7020 7025 7030 7035 7040 7045 7050 7055 7060 7065 7070 7075 7080 7085 7090 7095 7100 7105 7110 7115 7120 7125 7130 7135 7140 7145 7150 7155 7160 7165 7170 7175 7180 7185 7190 7195 7200 7205 7210 7215 7220 7225 7230 7235 7240 7245 7250 7255 7260 7265 7270 7275 7280 7285 7290 7295 7300 7305 7310 7315 7320 7325 7330 7335 7340 7345 7350 7355 7360 7365 7370 7375 7380 7385 7390 7395 7400 7405 7410 7415 7420 7425 7430 7435 7440 7445 7450 7455 7460 7465 7470 7475 7480 7485 7490 7495 7500 7505 7510 7515 7520 7525 7530 7535 7540 7545 7550 7555 7560 7565 7570 7575 7580 7585 7590 7595 7600 7605 7610 7615 7620 7625 7630 7635 7640 7645 7650 7655 7660 7665 7670 7675 7680 7685 7690 7695 7700 7705 7710 7715 7720 7725 7730 7735 7740 7745 7750 7755 7760 7765 7770 7775 7780 7785 7790 7795 7800 7805 7810 7815 7820 7825 7830 7835 7840 7845 7850 7855 7860 7865 7870 7875 7880 7885 7890 7895 7900 7905 7910 7915 7920 7925 7930 7935 7940 7945 7950 7955 7960 7965 7970 7975 7980 7985 7990 7995 8000 8005 8010 8015 8020 8025 8030 8035 8040 8045 8050 8055 8060 8065 8070 8075 8080 8085 8090 8095 8100 8105 8110 8115 8120 8125 8130 8135 8140 8145 8150 8155 8160 8165 8170 8175 8180 8185 8190 8195 8200 8205 8210 8215 8220 8225 8230 8235 8240 8245 8250 8255 8260 8265 8270 8275 8280 8285 8290 8295 8300 8305 8310 8315 8320 8325 8330 8335 8340 8345 8350 8355 8360 8365 8370 8375 8380 8385 8390 8395 8400 8405 8410 8415 8420 8425 8430 8435 8440 8445 8450 8455 8460 8465 8470 8475 8480 8485 8490 8495 8500 8505 8510 8515 8520 8525 8530 8535 8540 8545 8550 8555 8560 8565 8570 8575 8580 8585 8590 8595 8600 8605 8610 8615 8620 8625 8630 8635 8640 8645 8650 8655 8660 8665 8670 8675 8680 8685 8690 8695 8700 8705 8710 8715 8720 8725 8730 8735 8740 8745 8750 8755 8760 8765 8770 8775 8780 8785 8790 8795 8800 8805 8810 8815 8820 8825 8830 8835 8840 8845 8850 8855 8860 8865 8870 8875 8880 8885 8890 8895 8900 8905 8910 8915 8920 8925 8930 8935 8940 8945 8950 8955 8960 8965 8970 8975 8980 8985 8990 8995 9000 9005 9010 9015 9020 9025 9030 9035 9040 9045 9050 9055 9060 9065 9070 9075 9080 9085 9090 9095 9100 9105 9110 9115 9120 9125 9130 9135 9140 9145 9150 9155 9160 9165 9170 9175 9180 9185 9190 9195 9200 9205 9210 9215 9220 9225 9230 9235 9240 9245 9250 9255 9260 9265 9270 9275 9280 9285 9290 9295 9300 9305 9310 9315 9320 9325 9330 9335 9340 9345 9350 9355 9360 9365 9370 9375 9380 9385 9390 9395 9400 9405 9410 9415 9420 9425 9430 9435 9440 9445 9450 9455 9460 9465 9470 9475 9480 9485 9490 9495 9500 9505 9510 9515 9520 9525 9530 9535 9540 9545 9550 9555 9560 9565 9570 9575 9580 9585 9590 9595 9600 9605 9610 9615 9620 9625 9630 9635 9640 9645 9650 9655 9660 9665 9670 9675 9680 9685 9690 9695 9700 9705 9710 9715 9720 9725 9730 9735 9740 9745 9750

identifier and a MBSFN identifier in response to identifying that the scheduling frame corresponds to the joint transmission 135 where joint PFFICH transmission across nodes further implies transmitting same PFFICH contents across nodes participating in joint transmission. In a further aspect, processing system 1114 (FIG. 11), processor 1104, and/or memory 1106 may execute frame identifying component 1020, or may perform at least some of the functions of frame identifying component 1020, to determine whether the frame 131 corresponds to a unicast transmission 134 or a joint transmission 135 based on the preamble 132.

**[0063]** Referring to FIG. 7, an example of one or more operations and/or an example of architectural layout and components and subcomponents (FIG. 4B) of an aspect of frame identifying component 140 (FIG. 4B) according to the present apparatus and methods are described with reference to one or more methods and one or more components that may perform the actions of these methods. Although the operations described below are presented in a particular order and/or as being performed by an example component, it should be understood that the ordering of the actions and the components performing the actions may be varied, depending on the implementation. Also, although the frame identifying component 140 is illustrated as having a number of subcomponents, it should be understood that one or more of the illustrated subcomponent may be separate from, but in communication with, the frame identifying component 140 and/or each other. Moreover, it should be understood that the following actions or components described with respect to the frame identifying component 140 and/or its sub-components may be performed by a specially-programmed processor, a processor executing specially-programmed software or computer-readable media, or by any other combination of a hardware component and/or a software component specially configured for performing the described actions or components.

**[0064]** In an aspect, at block 710, method 700 includes determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. In an aspect, for example, network entity 105-b, may execute frame identifying component 140 (FIG. 4B) and/or determining component 141 to determine whether a frame 142 corresponds to a unicast transmission 144 or a joint transmission 145. For example, if the frame 142 corresponds to a joint transmission 145, it may correspond to a CoMP or MBSFN transmission. In a further aspect, processing system 914 (FIG. 9), processor 904, and/or memory 906 may execute frame identifying component 820, or may perform at least some of the functions of frame identifying component 820, to determine whether a frame 142 corresponds to a unicast transmission 144 or a joint transmission 145.

**[0065]** In an aspect, at block 720, method 700 optionally includes configuring the preamble of the frame based on determining whether the frame corresponds to the unicast transmission or the joint transmission. In an as-

pect, for example, network entity 105-b, may execute frame identifying component 140 (FIG. 4B) and/or determining component 141 to configure the preamble 143 of the frame 142 based on determining whether the frame 142 corresponds to the unicast transmission 144 or the joint transmission 145. For example, frame identifying component 140 and/or determining component 141 may configure the preamble 143 with a cell identifier if the frame 142 is determined to correspond to a unicast transmission 144. Moreover, frame identifying component 140 and/or determining component 141 may configure the preamble 143 with a virtual cell identifier if the frame 142 is determined to correspond to a joint transmission 145 such as CoMP. Similarly, frame identifying component 140 and/or determining component 141 may configure the preamble 143 with a MBSFN identifier if the frame 142 is determined to correspond to a joint transmission 145 such as MBSFN. In a further aspect, processing system 914 (FIG. 9), processor 904, and/or memory 906 may execute frame identifying component 820, or may perform at least some of the functions of frame identifying component 820, to configure the preamble 143 of the frame 142 based on determining whether the frame 142 corresponds to the unicast transmission 144 or the joint transmission 145.

**[0066]** In an aspect, at block 730, method 700 includes transmitting the frame with the preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission. In an aspect, for example, network entity 105-b, may execute frame identifying component 140 (FIG. 4B) and/or a transceiver 61 to transmit the frame 142 with the preamble 143 to a UE (e.g., UE 115) over a contention-based medium, the preamble 143 being based on determining whether the frame 142 corresponds to the unicast transmission 144 or the joint transmission 145. In a further aspect, processing system 914 (FIG. 9), processor 904, and/or memory 906 may execute transmission component 812, or may perform at least some of the functions of transmission component 812, to transmit the frame 142 with the preamble 143 to a UE (e.g., UE 115) over a contention-based medium

**[0067]** **FIG. 8** is a conceptual data flow diagram 800 illustrating the data flow between different means/components in an exemplary apparatus 802 that includes frame identifying component 820, which may be the same as or similar to frame identifying component 140. The apparatus 802 may be a base station, which may include base station 105 of FIGs. 1 and 4B. The apparatus 802 includes frame identifying component 820 that, in an aspect, determines, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. The apparatus 802 further includes a transmission component 812 that transmits the frame with a preamble to a UE, such as UE 115, over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast trans-

mission or the joint transmission. Further, apparatus 802 includes reception component 804 that receives one or more signals from at least one of the one or more UEs.

**[0068]** The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. 8. As such, each block in the aforementioned flowcharts of FIG. 8 may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to perform the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

**[0069]** FIG. 9 is a diagram 900 illustrating an example of a hardware implementation for an apparatus 802' employing a processing system 914 that includes frame identifying component 820 (FIG. 8), which may be the same as or similar to frame identifying component 140 (FIG. 4B). The processing system 914 may be implemented with a bus architecture, represented generally by the bus 924. The bus 924 may include any number of interconnecting buses and bridges depending on the specific application of the processing system 914 and the overall design constraints. The bus 924 links together various circuits including one or more processors and/or hardware components, represented by the processor 904, which may be the same as or similar to processor(s) 375 (FIG. 3) and/or 21 (FIG. 4B), the components 804, 812, and 820, and the computer-readable medium / memory 906, which may be the same as or similar to memory 376 (FIG. 3) and/or 45 (FIG. 4B). The bus 924 may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

**[0070]** The processing system 914 may be coupled to a transceiver 910. The transceiver 910 is coupled to one or more antennas 920. The transceiver 910 provides a means for communicating with various other apparatus over a transmission medium. The transceiver 910 receives a signal from the one or more antennas 920, extracts information from the received signal, and provides the extracted information to the processing system 914, specifically the reception component 804. In addition, the transceiver 910 receives information from the processing system 914, specifically the transmission component 812, and based on the received information, generates a signal to be applied to the one or more antennas 920. The processing system 914 includes a processor 904 coupled to a computer-readable medium / memory 906. The processor 904 is responsible for general processing, including the execution of software stored on the computer-readable medium / memory 906. The software, when executed by the processor 904, causes the processing system 914 to perform the various functions described *supra* for any particular apparatus. The com-

puter-readable medium / memory 906 may also be used for storing data that is manipulated by the processor 904 when executing software. The processing system 914 further includes at least one of the components 804, 812, and 820. The components may be software components running in the processor 904, resident/stored in the computer readable medium / memory 906, one or more hardware components coupled to the processor 904, or some combination thereof.

**[0071]** In one configuration, the apparatus 902/802' for wireless communication includes means for identifying joint transmissions in unlicensed spectrum. The apparatus includes means for determining, at a network entity, whether a frame corresponds to a unicast transmission or a joint transmission. Further, in another configuration, the apparatus 902/802' for wireless communication includes means for transmitting the frame with a preamble to a UE over a contention-based medium, the preamble being based on determining whether the frame corresponds to the unicast transmission or the joint transmission.

**[0072]** The aforementioned means may be one or more of the aforementioned components of the apparatus 902 and/or the processing system 914 of the apparatus 802' configured to perform the functions recited by the aforementioned means. As described *supra*, the processing system 914 may include the TX Processor 316, the RX Processor 370, and the controller/processor 375. As such, in one configuration, the aforementioned means may be the TX Processor 316, the RX Processor 370, and the controller/processor 375 configured to perform the functions recited by the aforementioned means.

**[0073]** FIG. 10 is a conceptual data flow diagram 1000 illustrating the data flow between different means/components in an exemplary apparatus 1002 that includes frame identifying component 1020, which may be the same as or similar to frame identifying component 130. The apparatus 1002 may be a UE, which may include UE 115 of FIGs. 1 and 4A. The apparatus 1002 includes reception component 1004 that, in an aspect, receives, at a UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. The apparatus 1002 includes frame identifying component 1020 that determines whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble. In an aspect, the apparatus 1002 further includes transmission component 1012 that transmits one or more signals to at least one of the one or more base stations.

**[0074]** The apparatus may include additional components that perform each of the blocks of the algorithm in the aforementioned flowcharts of FIG. 10. As such, each block in the aforementioned flowcharts of FIG. 10 may be performed by a component and the apparatus may include one or more of those components. The components may be one or more hardware components specifically configured to carry out the stated processes/algorithm, implemented by a processor configured to per-

form the stated processes/algorithm, stored within a computer-readable medium for implementation by a processor, or some combination thereof.

**[0075]** FIG. 11 is a diagram 1100 illustrating an example of a hardware implementation for an apparatus 1002' employing a processing system 1114 that includes frame identifying component 1020 (FIG. 10), which may be the same as or similar to frame identifying component 130 (FIG. 4A). The processing system 1114 may be implemented with a bus architecture, represented generally by the bus 1124. The bus 1124 may include any number of interconnecting buses and bridges depending on the specific application of the processing system 1114 and the overall design constraints. The bus 1124 links together various circuits including one or more processors and/or hardware components, represented by the processor 1104, which may be the same as or similar to processor(s) 20 (FIG. 4A), the components 1004, 1010, and 1012, and the computer-readable medium / memory 1106, which may be the same as or similar to memory 44 (FIG. 4A). The bus 1124 may also link various other circuits such as timing sources, peripherals, voltage regulators, and power management circuits, which are well known in the art, and therefore, will not be described any further.

**[0076]** The processing system 1114 may be coupled to a transceiver 1110. The transceiver 1110 is coupled to one or more antennas 1120. The transceiver 1110 provides a means for communicating with various other apparatus over a transmission medium. The transceiver 1110 receives a signal from the one or more antennas 1120, extracts information from the received signal, and provides the extracted information to the processing system 1114, specifically the reception component 1004. In addition, the transceiver 1110 receives information from the processing system 1114, specifically the transmission component 1112, and based on the received information, generates a signal to be applied to the one or more antennas 1120. The processing system 1114 includes a processor 1104 coupled to a computer-readable medium / memory 1106. The processor 1104 is responsible for general processing, including the execution of software stored on the computer-readable medium / memory 1106. The software, when executed by the processor 1104, causes the processing system 1114 to perform the various functions described *supra* for any particular apparatus. The computer-readable medium / memory 1106 may also be used for storing data that is manipulated by the processor 1104 when executing software. The processing system 1114 further includes at least one of the components 1004, 1010, and 1012. The components may be software components running in the processor 1104, resident/stored in the computer readable medium / memory 1106, one or more hardware components coupled to the processor 1104, or some combination thereof.

**[0077]** In one configuration, the apparatus 1102/1002' for wireless communication includes means for receiv-

ing, at a UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble. The apparatus includes means for determining whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble

**[0078]** The aforementioned means may be one or more of the aforementioned components of the apparatus 1102 and/or the processing system 1114 of the apparatus 1002' configured to perform the functions recited by the aforementioned means. As described *supra*, the processing system 1114 may include the TX Processor 368, the RX Processor 356, and the controller/processor 359. As such, in one configuration, the aforementioned means may be the TX Processor 368, the RX Processor 356, and the controller/processor 359 configured to perform the functions recited by the aforementioned means.

**[0079]** It is understood that the specific order or hierarchy of steps in the processes disclosed is an illustration of exemplary approaches. Based upon design preferences, it is understood that the specific order or hierarchy of steps in the processes may be rearranged. Further, some steps may be combined or omitted. The accompanying method claims present elements of the various steps in a sample order, and are not meant to be limited to the specific order or hierarchy presented.

**[0080]** In some aspects, an apparatus or any component of an apparatus may be configured to (or operable to or adapted to) provide functionality as taught herein. This may be achieved, for example: by manufacturing (e.g., fabricating) the apparatus or component so that it will provide the functionality; by programming the apparatus or component so that it will provide the functionality; or through the use of some other suitable implementation technique. As one example, an integrated circuit may be fabricated to provide the requisite functionality. As another example, an integrated circuit may be fabricated to support the requisite functionality and then configured (e.g., via programming) to provide the requisite functionality. As yet another example, a processor circuit may execute code to provide the requisite functionality.

**[0081]** It should be understood that any reference to an element herein using a designation such as "first," "second," and so forth does not generally limit the quantity or order of those elements. Rather, these designations may be used herein as a convenient method of distinguishing between two or more elements or instances of an element. Thus, a reference to first and second elements does not mean that only two elements may be employed there or that the first element must precede the second element in some manner. Also, unless stated otherwise a set of elements may comprise one or more elements. In addition, terminology of the form "at least one of A, B, or C" or "one or more of A, B, or C" or "at least one of the group consisting of A, B, and C" used in the description or the claims means "A or B or C or any combination of these elements." For example, this terminology may include A, or B, or C, or A and B, or A and

C, or A and B and C, or 2A, or 2C, and so on.

**[0082]** Those of skill in the art will appreciate that information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

**[0083]** Further, those of skill in the art will appreciate that the various illustrative logical blocks, modules, circuits, and algorithm steps described in connection with the aspects disclosed herein may be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, circuits, and steps have been described above generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. Skilled artisans may implement the described functionality in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the present disclosure.

**[0084]** The methods, sequences and/or algorithms described in connection with the aspects disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor.

**[0085]** Accordingly, an aspect of the disclosure can include a computer readable medium embodying a method for dynamic bandwidth management for transmissions in unlicensed spectrum. Accordingly, the disclosure is not limited to the illustrated examples.

**[0086]** While the foregoing disclosure shows illustrative aspects, it should be noted that various changes and modifications could be made herein without departing from the scope of the disclosure as defined by the appended claims. The functions, steps and/or actions of the method claims in accordance with the aspects of the disclosure described herein need not be performed in any particular order. Furthermore, although certain aspects may be described or claimed in the singular, the plural is contemplated unless limitation to the singular is explicitly stated.

## Claims

1. A method (600) of communication, comprising:
  - 5 receiving (610), at a user equipment, UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble;
  - 10 determining (630) whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble; and
  - 15 triggering the UE to a sleep mode for a remainder of the frame in response to determining that the frame corresponds to the joint transmission and the UE being in a unicast mode, wherein the UE remains in the sleep mode until a next frame is received.
2. The method of claim 1, further comprising identifying a scrambling of the preamble, wherein determining whether the frame corresponds to the unicast transmission or the joint transmission is based on the scrambling of the preamble.
- 25 3. The method of claim 2, wherein determining whether the frame corresponds to the unicast transmission or the joint transmission comprises determining that the frame corresponds to the unicast transmission in response to identifying that the preamble is scrambled by a cell identifier.
4. The method of claim 2, wherein determining whether the frame corresponds to the unicast transmission or the joint transmission comprises determining that the frame corresponds to a joint transmission associated with a coordinated multi point, CoMP, transmission in response to identifying that the preamble is scrambled by a virtual cell identifier.
- 40 5. The method of claim 2, wherein determining whether the frame corresponds to the unicast transmission or the joint transmission comprises determining that the frame corresponds to a joint transmission associated with a multicast-broadcast single-frequency network, MBSFN, transmission in response to identifying that the preamble is scrambled by an MBSFN area identifier.
- 45 6. The method of claim 2, further comprising identifying a tone location of the preamble based on at least one or more of a cell identifier, a virtual cell identifier and a multicast-broadcast single-frequency network, MBSFN, area identifier.
- 50 7. The method of claim 1, wherein the preamble comprises a channel usage beacon signal, CUBS, or a cell-specific reference signal, CRS.

8. The method of claim 7, wherein the preamble further comprises a physical frame format indicator channel, PFFICH, or a common PDCCH indicating the current frame format. 5
9. The method of claim 8, further comprising performing tone mapping of the PFFICH or a common PDCCH indicating the current frame format using a virtual cell identifier and a multicast-broadcast single-frequency network, MBSFN, area identifier in response to identifying that a scheduling frame corresponds to the joint transmission. 10
10. The method of claim 9, further comprising performing the joint transmission of the PFFICH or a common PDCCH indicating the current frame format across the one or more network entities participating in the joint transmission. 15
11. The method of claim 1, wherein the contention-based medium is associated with an unlicensed or shared spectrum. 20
12. An apparatus for communication, comprising:  
 means for receiving (610), at a user equipment, UE, a frame from one or more network entities over a contention-based medium, wherein the frame includes a preamble; 30  
 means for determining (630) whether the frame corresponds to a unicast transmission or a joint transmission based on the preamble; and  
 means for triggering the UE to a sleep mode for a remainder of the frame in response to determining that the frame corresponds to the joint transmission and the UE being in a unicast mode, wherein the UE remains in the sleep mode until a next frame is received. 35
13. The apparatus of claim 12, further comprising means for performing the steps of any of claims 2 to 11. 40
14. A computer program comprising executable instructions for causing at least one computer to perform a method according to one of the claims 1 to 11 when executed. 45
- ob der Rahmen einer Unicast-Übertragung oder einer gemeinsamen Übertragung entspricht; und  
 Auslösen, dass das UE in einem Schlafmodus für einen Rest des Rahmens übergeht als Antwort auf das Ermitteln, dass der Rahmen der gemeinsamen Übertragung entspricht und die UE in einem Unicast-Modus ist, wobei die UE in einem Schlafmodus verbleibt bis ein nächster Rahmen empfangen wird. 50
2. Verfahren nach Anspruch 1, ferner umfassend identifizieren eines Scramblings der Präambel, wobei bestimmen ob der Rahmen der Unicast-Übertragung oder der gemeinsamen Übertragung entspricht auf dem Scrambling der Präambel basiert. 55
3. Verfahren nach Anspruch 2, wobei bestimmen ob der Rahmen der Unicast-Übertragung oder der gemeinsamen Übertragung entspricht umfasst bestimmen das der Rahmen der Unicast-Übertragung entspricht, in Antwort auf identifizieren, dass die Präambel durch eine Zell-Kennung gescrambelt wird.
4. Verfahren nach Anspruch 2, wobei bestimmen ob der Rahmen der Unicast-Übertragung oder der gemeinsamen Übertragung entspricht umfasst bestimmen das der Rahmen einer gemeinsamen Übertragung entspricht, die mit einer koordinierten Multi-Punkt-, CoMP-, Übertragung verknüpft ist, in Antwort auf identifizieren, dass die Präambel durch eine virtuelle Zell-Kennung gescrambelt ist. 60
5. Verfahren nach Anspruch 2, wobei bestimmen ob der Rahmen der Unicast-Übertragung oder der gemeinsamen Übertragung entspricht umfasst bestimmen das der Rahmen einer gemeinsamen Übertragung entspricht, die mit einer Multicast-Broadcast-Einzelfrequenz-Netzwerk-, MBSFN-, Übertragung verknüpft ist, in Antwort auf identifizieren, dass die Präambel durch eine MBSFN-Gebiets-Kennung gescrambelt ist. 65
6. Verfahren nach Anspruch 2, ferner umfassend identifizieren einer Tonlage der Präambel, basierend zu mindest auf eine oder auf mehrere von einer Zell-Kennung, einer virtuellen Zellkennung und einer Multicast-Broadcast-Einzelfrequenz-Netzwerk-, MBSFN-, Gebietskennung. 70
7. Verfahren nach Anspruch 1, wobei die Präambel einen Kanalnutzungs-Bakensignal, CUBS, oder ein zellspezifisches Referenzsignal, CRS, umfasst. 75
8. Verfahren nach Anspruch 7, wobei die Präambel ferner einen physikalischen Rahmen-Formatindikator-Kanal, PFFICH, oder eine allgemeinen PDCCH der das aktuelle Rahmenformat anzeigt, umfasst. 80

## Patentansprüche

### 1. Verfahren (600) zur Kommunikation, umfassend:

Empfangen (610) an einer Benutzervorrichtung, UE, eines Rahmens von einer oder mehreren Netzwerk-Einheiten über ein konkurrenzbasiertes Medium, wobei der Rahmen eine Präambel beinhaltet;  
 Bestimmen (630), basierend auf der Präambel,

9. Verfahren nach Anspruch 8, ferner umfassend durchführen von Ton-Abbildung des PFFICH oder eines allgemeinen PDCCH, der das aktuelle Rahmenformat anzeigt unter Verwendung einer virtuellen Zell-Kennung und einer Multicast-Broadcast-Einzelfrequenz-Netzwerk-, MBSFN, Gebietskennung, in Antwort auf identifizieren, dass ein geplanter Rahmen der gemeinsamen Übertragung entspricht. 5
10. Verfahren nach Anspruch 9, ferner umfassend durchführen der gemeinsamen Übertragung des PF-FICH oder eines allgemeinen PDCCH, der das aktuelle Rahmenformat, über die einen oder mehreren Netzwerk-Einheiten, anzeigt, die an der gemeinsamen Übertragung teilnehmen. 10
11. Verfahren nach Anspruch 1, wobei das konkurrenz-basierte Medium mit einem unlizenzierten oder geteilten Spektrum verknüpft ist. 15
12. Vorrichtung zur Kommunikation, umfassend:
- Mittel zum Empfangen (610) an einer Benutze-vorrichtung, UE, eines Rahmens von einer oder mehreren Netzwerk-Einheiten über ein konkurrenzbasiertes Medium, wobei der Rahmen eine Präambel beinhaltet; 20
- Mittel zum Bestimmen (630), basierend auf der Präambel, ob der Rahmen einer Unicast-Übertragung oder einer gemeinsamen Übertragung entspricht; und 25
- Mittel zum Auslösen, dass das UE einem Schlaf-modus für einen Rest des Rahmens übergeht als Antwort auf ermitteln das der Rahmen der gemeinsamen Übertragung entspricht und die UE in einem Unicast-Modus ist, wobei die UE in einem Schlafmodus verbleibt bis ein nächster Rahmen empfangen wird. 30
13. Vorrichtung nach Anspruch 12, ferner umfassend Mittel zum Durchführen der Schritte nach einem der Ansprüche 2 bis 11. 40
14. Computerprogramm umfassend ausführbare Anwei-sungen, die zumindest einen Computer veranlassen ein Verfahren gemäß einem der Ansprüche 1 bis 11 durchzuführen, wenn diese ausgeführt werden. 45
- Revendications** 50
1. Un procédé (600) de communication, comprenant :
- la réception (610), au niveau d'un équipement utilisateur, UE, d'une trame à partir d'une ou de plusieurs entités de réseau sur un support basé sur la contention, dans lequel la trame inclut un préambule ; 55
- la détermination (630) si la trame correspond à une transmission unicast ou à une transmission conjointe sur la base du préambule ; et le basculement de l'UE vers un mode veille pendant un reste de la trame en réponse à la détermi-nation que la trame correspond à la transmission conjointe et l'UE étant dans un mode unicast, dans lequel l'UE reste dans le mode veille jusqu'à ce qu'une trame suivante soit reçue.
2. Le procédé selon la revendication 1, comprenant en outre l'identification d'un brouillage du préambule, dans lequel la détermination si la trame correspond à une transmission unicast ou à la transmission con-jointe est basée sur le brouillage du préambule. 60
3. Le procédé selon la revendication 2, dans lequel la détermination si la trame correspond à la transmission unicast ou à la transmission conjointe comprend la détermination que la trame correspond à la transmission unicast en réponse à l'identification que le préambule est brouillé par un identifiant de cellule. 65
4. Le procédé selon la revendication 2, dans lequel la détermination si la trame correspond à la transmission unicast ou à la transmission conjointe comprend la détermination que la trame correspond à une transmission conjointe associée à une transmission multipoint coordonnée, CoMP, en réponse à l'iden-tification que le préambule est brouillé par un iden-tifiant de cellule virtuelle. 70
5. Le procédé selon la revendication 2, dans lequel la détermination si la trame correspond à la transmission unicast ou à la transmission conjointe comprend la détermination que la trame correspond à une transmission conjointe associée à une transmission de réseau monofréquence multicast-broadcast, MBSFN, en réponse à l'identification que le préambule est brouillé par un identifiant de zone MBSFN. 75
6. Le procédé selon la revendication 2, comprenant en outre l'identification d'une position de tonalité du préambule sur la base d'au moins un ou plusieurs d'un identifiant de cellule, d'un identifiant de cellule virtuelle et d'un identifiant de zone de réseau monofréquence multicast-broadcast, MBSFN. 80
7. Le procédé selon la revendication 1, dans lequel le préambule comprend un signal de balise d'utilisation de canal, CUBS, ou un signal de référence spécifique à la cellule, CRS. 85
8. Le procédé selon la revendication 7, dans lequel le préambule comprend en outre un canal indicateur de format de trame physique, PFFICH, ou un PDCCH commun indiquant le format de trame cour-ant. 90

9. Le procédé selon la revendication 8, comprenant en outre la réalisation d'un mappage de tonalité du PF-FICH ou d'un PDCCH commun indiquant le format de trame courant au moyen d'un identifiant de cellule virtuelle et d'un identifiant de zone de réseau monofréquence multicast-broadcast, MBSFN, en réponse à l'identification qu'une trame de planification correspond à la transmission conjointe. 5

10. Le Procédé selon la revendication 9, comprenant en outre la réalisation de la transmission conjointe du PFFICH ou d'un PDCCH commun indiquant le format de trame courant sur les une ou plusieurs entités de réseau participant à la transmission conjointe. 10

11. Le procédé selon la revendication 1, dans lequel le support basé sur la contention est associé à un spectre non autorisé ou partagé. 15

12. Un appareil de communication, comprenant : 20

des moyens pour recevoir (610), au niveau d'un équipement utilisateur, UE, une trame à partir d'une ou de plusieurs entités de réseau sur un support basé sur la contention, dans lequel la trame inclut un préambule ; 25

des moyens pour déterminer (630) si la trame correspond à une transmission unicast ou à une transmission conjointe sur la base du préambule ; et 30

des moyens pour faire basculer l'UE vers un mode de veille pendant un reste de la trame en réponse à la détermination que la trame correspond à la transmission conjointe et l'UE étant dans un mode unicast, dans lequel l'UE reste dans le mode veille jusqu'à ce qu'une trame suivante soit reçue. 35

13. L'appareil selon la revendication 12, comprenant en outre des moyens pour réaliser les étapes selon l'une quelconque des revendications 2 à 11. 40

14. Un programme informatique comprenant des instructions exécutables pour amener au moins un ordinateur à réaliser un procédé selon l'une des revendications 1 à 11 lorsqu'il est exécuté. 45




FIG.




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6






FIG. 7



**FIG. 8**

**FIG. 9**




FIG. 10




FIG. 11

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- US 20130142095 A [0006]
- WO 2014074919 A [0007]