



(22) Date de dépôt/Filing Date: 2010/01/28

(41) Mise à la disp. pub./Open to Public Insp.: 2010/08/27

(45) Date de délivrance/Issue Date: 2014/08/19

(30) Priorité/Priority: 2009/02/27 (EPEP09154049)

(51) Cl.Int./Int.Cl. *H04W 88/02* (2009.01),
H04R 1/22 (2006.01)


(72) Inventeurs/Inventors:
WELKER, MICHAEL, CA;
HANSON, DANIEL, CA

(73) Propriétaire/Owner:
BLACKBERRY LIMITED, CA

(74) Agent: MCCARTHY TETRAULT LLP

(54) Titre : ENCEINTE DE HAUT-PARLEUR D'UN DISPOSITIF SANS FIL

(54) Title: ENCLOSURE FOR A SPEAKER OF A WIRELESS DEVICE



(57) Abrégé/Abstract:

An enclosure for a magnetic speaker of a wireless device is provided. The wireless device has a display mounted in a case and a transparent cover mounted over at least the display. The enclosure comprises: an upper surface of the display at least partially spaced from a lower surface of the transparent cover to form at least a portion of an enclosed back-volume formed within the case for the magnetic speaker, the magnetic speaker being mounted proximate to the enclosed back-volume, and at least one of the transparent cover and the case having an opening formed therein for emitting sound from the magnetic speaker.

ABSTRACT

An enclosure for a magnetic speaker of a wireless device is provided. The wireless device has a display mounted in a case and a transparent cover mounted over at least the display. The enclosure comprises: an upper surface of the display at least partially spaced from a lower surface of the transparent cover to form at least a portion of an enclosed back-volume formed within the case for the magnetic speaker, the magnetic speaker being mounted proximate to the enclosed back-volume, and at least one of the transparent cover and the case having an opening formed therein for emitting sound from the magnetic speaker.

ENCLOSURE FOR A SPEAKER OF A WIRELESS DEVICE**FIELD OF THE APPLICATION**

[0001] This application relates to the field of wireless
5 devices, and more specifically, to an enclosure for a speaker
of a wireless device.

BACKGROUND

[0002] Current wireless mobile communication devices include
10 microprocessors, memory, soundcards, speakers, headphones, and
run one or more software applications in addition to providing
for voice communications. Examples of software applications
used in these wireless devices include micro-browsers, address
books, email clients, instant messaging ("IM") clients, and
15 wavetable instruments. Additionally, wireless devices have
access to a plurality of services via the Internet. A wireless
device may, for example, be used to browse web sites on the
Internet, to transmit and receive graphics, and to execute
streaming audio and/or video applications. Such wireless
20 devices may operate on a cellular network, on a wireless local
area network ("WLAN"), or on both of these types of networks.

[0003] One problem with current wireless devices pertains to
speaker performance. Speakers in wireless devices require a
back-volume to perform properly. The back-volume is a space,
25 cavity, or volume typically located behind the speaker which
is sized to allow unrestricted movement of the speaker's
cone. If an adequate back-volume is not provided, the
frequency response and efficiency of the speakers may be
adversely affected by back pressure restricting movement of
30 the speaker's cone. In general, providing a speaker with a
back-volume by placing the speaker in an enclosure results in
improved low frequency response and higher volume or loudness.
Cavities associated with the wireless device's internal

antenna or internal printed circuit boards may be used as a back-volume for the wireless device's speaker. However, using such cavities typically requires a complicated sealing geometry. In addition, such cavities may not be large enough
5 to provide an adequate back-volume for the wireless device's speaker. As such, these cavities may have to be increased in volume by increasing the thickness of the wireless device thus increasing the overall size of the wireless device, which is not desirable.

10 **[0004]** A need therefore exists for an improved enclosure for a speaker of a wireless device. Accordingly, a solution that addresses, at least in part, the above and other shortcomings is desired.

15 **BRIEF DESCRIPTION OF THE DRAWINGS**

[0005] Features and advantages of the embodiments of the present application will become apparent from the following detailed description, taken in combination with the appended drawings, in which:

20 **[0006]** FIG. 1 is a front view illustrating a wireless device in accordance with an embodiment of the application;

[0007] FIG. 2 is a block diagram illustrating the wireless device of FIG. 1;

25 **[0008]** FIG. 3 is a block diagram illustrating a memory of the wireless device of FIG. 1;

[0009] FIG. 4 is a simplified longitudinal section view illustrating an enclosure for a speaker of the wireless device of FIG. 1;

30 **[0010]** FIG. 5 is a simplified longitudinal section view illustrating an enclosure for a speaker of a wireless device in accordance with an alternate embodiment;

[0011] FIG. 6 is a simplified longitudinal section view illustrating an enclosure for a speaker of a wireless device in accordance with an alternate embodiment;

[0012] FIG. 7 is a simplified longitudinal section view illustrating an enclosure for a speaker of a wireless device in accordance with an alternate embodiment; and,

[0013] FIG. 8 is a simplified longitudinal section view illustrating an enclosure for a speaker of a wireless device in accordance with an alternate embodiment.

[0014] It will be noted that throughout the appended drawings, like features are identified by like reference numerals.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0015] In the following description, details are set forth to provide an understanding of the application. In some instances, certain software, circuits, structures and techniques have not been described or shown in detail in order not to obscure the application.

[0016] FIG. 1 is a front view illustrating a wireless device **100** in accordance with an embodiment of the application. The wireless device **100** includes a case **150**, a display (e.g., a liquid crystal display ("LCD")) **122**, a graphical user interface ("GUI") **180** displayed on the display **122**, a transparent cover (e.g., a lens) **105** mounted over the display **122** for protection thereof, a speaker **134**, a keyboard (or keypad) **132**, a thumbwheel (or trackwheel) **110**, various select buttons **120**, and various inputs/outputs (e.g., power connector jack, data interface ports, headphones jack, etc.) **160**. Internally, the wireless device **100** typically includes one or more circuit boards (not shown in FIG. 1), a CPU **138**, memory **124**, **126**, **200**, a battery **156**, an antenna (not shown in FIG. 1), etc., which are operatively coupled to the various

inputs/outputs **160**, the keyboard **132**, the display **122**, the speaker **134**, etc., as will be described below.

[0017] FIG. 2 is a block diagram illustrating the wireless device **100** of FIG. 1. The wireless device **100** may operate over
5 a wireless network **220**. The wireless network **220** may include antenna, base stations, access points, transceivers, supporting radio equipment, etc., as known to those of ordinary skill in the art, for supporting wireless communications between the wireless device **100** and other
10 devices (not shown).

[0018] The wireless device **100** may be a two-way communication device having at least voice and advanced data communication capabilities, including the capability to communicate with other devices. Depending on the functionality provided by the
15 device **100**, it may be referred to as a data messaging device, a two-way pager, a cellular telephone with data messaging capabilities, a wireless Internet appliance, a data communication device (with or without telephony capabilities), a Wi-Fi device, a WLAN device, a dual-mode (i.e., Wi-Fi and
20 cellular) device, or a portable audio device. The device **100** may communicate with any one of a plurality of transceiver stations (not shown) within its geographic coverage area.

[0019] The wireless device **100** has a communication subsystem **111**, which includes a RF receiver, a RF transmitter, and
25 associated components, such as one or more antenna elements (e.g., embedded or internal), local oscillators ("LOs"), and a processing module such as a digital signal processor ("DSP") (all not shown).

[0020] The device **100** may be capable of cellular network access and hence the device **100** may have a subscriber identity module
30 (or "SIM" card) **162** for inserting into a SIM interface ("IF") **164** in order to operate on the cellular network (e.g., a global system for mobile communication ("GSM") network).

[0021] The device **100** may be a battery-powered device and so it may also include a battery IF **154** for receiving one or more rechargeable batteries **156**. The battery (or batteries) **156** provides electrical power to most if not all electrical circuitry in the device **100**, and the battery IF **154** provides for a mechanical and electrical connection for it. The battery IF **154** is coupled to a regulator (not shown) which provides regulated power to the circuitry of the device **100**.

[0022] The wireless device **100** includes a microprocessor **138** which controls overall operation of the device **100**. Communication functions, including at least data and voice communications, are performed through the communication subsystem **111**. The microprocessor **138** also interacts with additional device subsystems such as the display **122**, a flash memory **124** or other persistent store, a random access memory ("RAM") **126**, auxiliary input/output ("I/O") subsystems **128**, a serial port (e.g., a universal serial bus ("USB") port) **131**, the keyboard **132**, the clickable thumbwheel **110**, the speaker **134**, a microphone **136**, a short-range communications subsystem **141**, and other device subsystems **142**.

[0023] The microprocessor **138**, in addition to its operating system functions, preferably enables execution of software applications on the device **100**. A predetermined set of applications which control basic device operations, including at least data and voice communication applications, will normally be installed on the device **100** during its manufacture. A preferred application that may be loaded onto the device **100** may be a personal information manager ("PIM") application having the ability to organize and manage data items relating to the user such as, but not limited to, instant messaging ("IM"), email, calendar events, voice mails, appointments, and task items. Naturally, one or more memory

stores are available on the device **100** and SIM **162** to facilitate storage of PIM data items and other information.

[0024] In a data communication mode, a received signal such as a text message, an email message, or web page download will be processed by the communication subsystem **111** and input to the microprocessor **138**. The microprocessor **138** will preferably further process the signal for output to the display **122** and/or to the auxiliary I/O device **128**. A user of the wireless device **100** may also compose data items, such as email messages, for example, using the keyboard **132** in conjunction with the display **122**, and possibly the auxiliary I/O device **128**. The keyboard **132** is preferably a complete alphanumeric keyboard and/or a telephone-type keypad. These composed items may be transmitted over a communication network **220** through the communication subsystem **111** or the short range communication subsystem **141**.

[0025] For voice communications, the overall operation of the wireless device **100** is substantially similar, except that the received signals would be output to the speaker **134** and signals for transmission would be generated by the microphone **136**. Alternative voice or audio I/O subsystems, such as a voice message recording subsystem, may also be implemented on the device **100**. Although voice or audio signal output is preferably accomplished primarily through the speaker **134**, the display **122** may also be used to provide, for example, an indication of the identity of a calling party, duration of a voice call, or other voice call related information.

[0026] FIG. 3 is a block diagram illustrating a memory **200** of the wireless device **100** of FIG. 1. The microprocessor **138** is coupled to the memory **200**. The memory **200** has various hardware and software components for storing information (e.g., instructions, data, database tables, test parameters, etc.) for enabling operation of the device **100** and may include flash

memory **124**, RAM **126**, ROM (not shown), disk drives (not shown), etc. In general, the memory **200** may include a variety of storage devices typically arranged in a hierarchy of storage as understood to those skilled in the art.

5 **[0027]** According to one embodiment, the wireless device **100** may be a multi-tasking wireless communications device configured for sending and receiving data items and for making and receiving voice calls. In addition, the microprocessor **138** of the wireless device **100** is typically coupled to one or more
10 devices or subsystems (e.g., **110**, **120**, **132**) for receiving user commands or queries and for displaying the results of these commands or queries to the user on the display **122**. To provide a user-friendly environment to control the operation of the device **100**, operating system ("O/S") software modules **202**
15 resident on the device **100** provide a basic set of operations for supporting various applications typically operable through the GUI **180** and supporting GUI software modules **204**. For example, the O/S **202** provides basic input/output system features to obtain input from the auxiliary I/O **128**, the
20 keyboard **132**, the clickable thumbwheel **110**, and the like, and for facilitating output to the user through the display **122**, the speaker **134**, etc. Though not shown, one or more applications for managing communications or for providing personal digital assistant like functions may also be
25 included. According to one embodiment, the wireless device **100** is provided with hardware and/or software modules **206** for facilitating and implementing various additional functions. According to one embodiment, a user may interact with the wireless device **100** and its various software modules **202**, **204**,
30 **206**, using the GUI **180**.

[0028] The present application provides an enclosure for the speaker **134** that allows the wireless device **100** to maintain its thickness while using a cavity that is not used for

anything else in the wireless device **100**. In addition, there is no need for separate sealing of this cavity as dust sealing of this cavity is already provided.

[0029] FIG. 4 is a simplified longitudinal section view illustrating an enclosure **400** for a speaker **134** of the wireless device **100** of FIG. 1. The enclosure **400** provides a back-volume **410** or cavity for the speaker **134** of the wireless device **100**. According to one embodiment, the enclosure **400** is formed by the lower surface of the transparent cover **105**, also called a lens, the upper surface of the display **122**, and sealing material **420** that forms or completes the walls of the enclosure **400**. The lens **105** is spaced apart from the display **122** by the sealing material **420** to form the back-volume **410** therebetween. Portions of the enclosure **400** may be formed by various supports **430** for the display **122** and/or speaker **132** (e.g., printed circuit boards, spacers, baffles, etc.) and by various portions of the case **150** depending on the geometry of the display **122**, transparent cover **105**, speaker **134**, and case **150**. For example, depending on the geometry of the components used, the speaker **134** may form or complete a wall of the enclosure **400**.

[0030] According to one embodiment, the sealing material **420** may include dust sealing material that is typically used to seal the perimeter of the display **122** and transparent cover **105** to prevent dust from entering therebetween. In addition, the sealing material **420** may include acoustic sealing material to improve the performance of the back-volume **410**. Of course, the material chosen for the sealing material **420** may include both appropriate dust sealing and acoustic sealing properties. According to one embodiment, the sealing material **420** may be silicon or a thermoplastic elastomer ("TPE").

[0031] The speaker **134** is mounted proximate to the back-volume **410**, and may become part of the enclosure **400**. In FIGS. 1 and

4, the speaker **134** is shown as being mounted behind the transparent cover **105** for projecting sound through an appropriate opening or openings **440** in the transparent cover **105**. However, according to another embodiment, the speaker **134**
5 may be mounted in the case **150** proximate to the back-volume **410** (see FIGS. 7-9).

[0032] According to one embodiment, the speaker **134** is a magnetic type loudspeaker (i.e., having a magnet, cone, frame, etc.). According to one embodiment, the wireless device **100**
10 has two or more speakers **134**.

[0033] FIG. 5 is a simplified longitudinal section view illustrating an enclosure **400** for a speaker **134** of a wireless device **100** in accordance with an alternate embodiment. In FIG. 5, the transparent cover **105** is L-shaped having one end
15 proximate to one end of the display **122**. In this embodiment, the sealing material **420** does not necessarily form a significant portion of the enclosure **400**.

[0034] FIG. 6 is a simplified longitudinal section view illustrating an enclosure **400** for a speaker **134** of a wireless device **100** in accordance with an alternate embodiment. In FIG. 6, the transparent cover **105** is tapered at one end proximate
20 to one end of the display **122**. In this embodiment, the sealing material **420** does not necessarily form a significant portion of the enclosure **400**.

[0035] FIG. 7 is a simplified longitudinal section view illustrating an enclosure **400** for a speaker **134** of a wireless device **100** in accordance with an alternate embodiment. In FIG. 7, the transparent cover **105** is L-shaped having one end
25 proximate to one end of the display **122**. In this embodiment, the sealing material **420** does not necessarily form a significant portion of the enclosure **400**. In this embodiment, the speaker **134** is mounted on the back of the case **150** to
30 which the back-volume **410** extends.

[0036] FIG. 8 is a simplified longitudinal section view illustrating an enclosure 400 for a speaker 134 of a wireless device 100 in accordance with an alternate embodiment. In FIG. 8, the support 430 is C-shaped having one end proximate to the case 150. In this embodiment, the sealing material 430 between the transparent cover 105 and the support 430 forms a portion of the enclosure 400 but the sealing material 430 between the support 430 and the case 150 does not necessarily form a significant portion of the enclosure 400. In this embodiment, an opening or openings 440 for the speaker 134 is provided in the case 150 rather than in the transparent cover 105.

[0037] The above embodiments may provide one or more advantages. First, no additional volume within the wireless device 100 is required. Second, the thickness or overall size of the wireless device 100 does not have to be increased to accommodate the back-volume 410. Third, no additional sealing parts are necessary, thus reducing costs. Fourth, the enclosure 400 provides a back-volume 410 that is large enough to provide good speaker performance.

[0038] The embodiments of the application described above are intended to be exemplary only. Those skilled in this art will understand that various modifications of detail may be made to these embodiments.

CLAIMS:

1. A system for enclosing a magnetic speaker and a display of a wireless device, the system located in a case of the wireless device and comprising:

a support for mounting the display, the support forming a part of an enclosed back-volume for the magnetic speaker and forming a first opening above the display; and

a transparent cover mounted in the first opening to complete a wall of an enclosure for the system, the transparent cover having a lower surface forming at least a portion of the enclosed back-volume and a second opening through its outer surface to receive the magnetic speaker.

2. The system of claim 1 wherein the magnetic speaker is mounted to the transparent cover in the second opening.

3. The system of claim 1 or claim 2 wherein a portion of the case defines the enclosed back-volume.

4. The system of any one of claims 1 to 3 wherein the support is a portion of the case.

5. The system of any one of claims 1 to 4 wherein the support is a printed circuit board.

6. The system of any one of claims 1 to 5 wherein a portion of sealing material defines the enclosed back-volume.

7. The system of claim 6 wherein the portion of sealing material is located proximate the lower surface of the transparent cover.

8. The system of claim 7 wherein the sealing material is at least one of dust sealing and acoustic sealing material.

9. The system of any one of claims 1 to 8 wherein the magnetic speaker is mounted under the transparent cover and emits sound through the second opening.

10. The system of any one of claims 1 to 9 wherein:
the support is a printed circuit board (PCB); and
the display is mounted to the PCB.

11. A system for housing a magnetic speaker and a display for a wireless device, the system comprising:

a case for enclosing the magnetic speaker and the display, the case having a first opening located above the display;

a support for mounting the display within the case, the support forming part of an enclosed back-volume for the magnetic speaker; and

a transparent cover mounted over display in the first opening of the case, the transparent cover having a lower surface forming at least a portion of the enclosed back-volume and a second opening through its outer surface to receive the magnetic speaker.

12. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 11 wherein:

the magnetic speaker is mounted adjacent to the transparent cover in the opening to complete a wall of the case; and

a portion of the case defines the enclosed back-volume.

13. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 11 or claim 12 wherein:

the support is a printed circuit board (PCB).

14. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 13 wherein:

the display is mounted to the PCB.

15. The system for housing a magnetic speaker and a display for a wireless device as claimed in any one of claims 11 to claim 14 wherein:

the transparent cover is L-shaped having a top section that extends inwardly to the interior of the case; and

a top section of the display is adjacent to the case forming another part of the enclosed back volume.

16. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 15 further comprising:

sealing material located proximate the lower surface of the transparent cover, sealing a part of the transparent cover to the display.

17. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 15 wherein:

the display is mounted on the PCB to extend past a top edge of the PCB.

18. The system for housing a magnetic speaker and a display for a wireless device as claimed in any one of claims 11 to 14 wherein:

the transparent cover is tapered having a top section that extends inwardly to the interior of the case; and

a top section of the display is adjacent to the case forming another part of the enclosed back volume.

19. The system for housing a magnetic speaker and a display for a wireless device as claimed in claim 18 further comprising:

sealing material located proximate the lower surface of the transparent cover, sealing a part of the transparent cover to the display.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

