



US009752738B2

(12) **United States Patent**
Baxter et al.

(10) **Patent No.:** **US 9,752,738 B2**
(45) **Date of Patent:** **Sep. 5, 2017**

(54) **LED BASED SEARCHLIGHT/SKY LIGHT**

(2013.01); *F21V 21/30* (2013.01); *F21V 29/70* (2015.01); *F21W 2131/107* (2013.01); *F21Y 2105/10* (2016.08); *F21Y 2113/13* (2016.08); *F21Y 2115/10* (2016.08)

(75) Inventors: **Kevin C. Baxter**, Glendale, CA (US);
Fred H. Holmes, Cleveland, OK (US)

(73) Assignee: **Sportsbeams Lighting, Inc.**, Plano, TX (US)

(58) **Field of Classification Search**

CPC *F21L 4/02*; *F21V 29/22*; *F21V 7/0008*; *F21V 29/402*; *F21S 8/003*
USPC 362/184, 373, 294, 249.01, 35; 340/815.45
See application file for complete search history.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/441,831**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(22) Filed: **Apr. 6, 2012**

5,895,128 A 4/1999 Kishimoto et al.
6,623,144 B2* 9/2003 Bornhorst 362/318
(Continued)

(65) **Prior Publication Data**

US 2013/0094193 A1 Apr. 18, 2013

OTHER PUBLICATIONS

Related U.S. Application Data

http://en.wikipedia.org/wiki/Searchlight.*

(60) Provisional application No. 61/472,532, filed on Apr. 6, 2011.

Primary Examiner — Tracie Y Green

(51) **Int. Cl.**

(74) *Attorney, Agent, or Firm* — Gable Gotwals; Scott R. Zingerman

F21L 4/02 (2006.01)
F21V 7/00 (2006.01)
F21V 29/00 (2015.01)
F21V 29/56 (2015.01)
F21S 8/00 (2006.01)
F21V 7/06 (2006.01)
F21V 7/22 (2006.01)
F21V 21/30 (2006.01)
F21W 131/107 (2006.01)
F21V 29/70 (2015.01)
F21Y 105/10 (2016.01)

(57) **ABSTRACT**


LED based searchlight/sky light including, in a basic embodiment, a housing; an LED array supported in/by the housing, a heat sink in communication with the LED array, and a reflector supported in the housing such that the LED array is supported by the housing a distance sufficient above the reflector to allow the light emitted by the LED array to be reflected by the reflector. The reflector is preferably a parabolic reflector such that the light emitted by the LED array is reflected by the parabolic reflector in an intense collimated beam. The LED array may be supported above the parabolic reflector a distance equal to the focal length of the parabolic reflector. A power supply may also be included to regulate the electrical current applied to the LED array.

(Continued)

(52) **U.S. Cl.**

CPC *F21L 4/02* (2013.01); *F21S 8/003* (2013.01); *F21V 7/00* (2013.01); *F21V 7/0008* (2013.01); *F21V 7/06* (2013.01); *F21V 29/402* (2013.01); *F21V 29/56* (2015.01); *F21V 7/22*

18 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
F21Y 115/10 (2016.01)
F21Y 113/13 (2016.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,749,310	B2	6/2004	Pohlert et al.	
6,824,283	B2	11/2004	Pohlert et al.	
6,948,823	B2	9/2005	Pohlert et al.	
7,140,742	B2	11/2006	Pohlert et al.	
7,163,302	B2	1/2007	Pohlert et al.	
7,178,937	B2*	2/2007	McDermott	362/187
7,314,291	B2*	1/2008	Tain	F21K 9/00 257/99
7,318,652	B2	1/2008	Pohlert et al.	
7,331,681	B2	2/2008	Pohlert et al.	
7,429,117	B2	9/2008	Pohlert et al.	
7,510,290	B2	3/2009	Pohlert et al.	
7,604,361	B2	10/2009	Pohlert et al.	
7,798,667	B2*	9/2010	Klipstein	362/109
7,874,701	B2	1/2011	Pohlert et al.	
7,902,761	B2*	3/2011	Ang et al.	315/194
7,972,022	B2	7/2011	Pohlert et al.	
8,025,417	B2	9/2011	Pohlert et al.	
8,506,125	B2	8/2013	Pohlert et al.	
8,540,383	B2	9/2013	Pohlert et al.	
8,702,255	B2	4/2014	Baxter et al.	
8,882,283	B2	11/2014	Baxter et al.	
2005/0128752	A1*	6/2005	Ewington et al.	362/294
2007/0253188	A1*	11/2007	Klipstein et al.	362/105
2008/0175008	A1*	7/2008	Hu	F21K 9/00 362/373
2009/0059594	A1*	3/2009	Lin	362/294
2010/0204841	A1*	8/2010	Chemel et al.	700/282

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4

LED BASED SEARCHLIGHT/SKY LIGHT**CROSS REFERENCE TO RELATED APPLICATION**

This application claims the benefit of U.S. Provisional Patent Application Ser. No. 61/472,532, filed on Apr. 6, 2011, and incorporates said provisional Application Ser. No. 61/472,532 by reference into this document as if fully set out at this point.

FIELD OF THE INVENTION

This invention relates to searchlights, also known as sky lights commonly used in the advertising industry.

BACKGROUND OF THE INVENTION

Searchlights, also commonly called sky lights, have historically been based on carbon arc or more recently xenon short arc bulbs as the light source. A dense amount of light in a very small area is considered a point source and this coupled with a parabolic mirror allow searchlights to provide an intense projected beam of light. To the present, carbon arcs and xenon short arc lamps have been considered the best existing point sources of light. However, these light sources require large amounts of power, emit large amounts of infrared (IR) and ultraviolet (UV), have a short bulb life, and are not completely stable in their operation. These fixtures use deep parabolic mirrors that reflect the emitted light into a highly collimated beam that under ideal atmospheric conditions appear as tight beams which can be seen for miles.

Several, and usually four, of these fixtures are mounted on a platform which spins and the light's vertical direction is simultaneously tipped up and down. This type of movement projects moving, dancing, sweeping beams of light through the sky, attracting the attention of the public, and drawing them to the source of the beams, in essence an advertising method.

These moving platforms of light require substantial amounts of electricity in order to operate as each light fixture uses between 2,000 and 4,000 watts of electricity. When a group of 4 lights are used and the motors and power supplies are included, the power draw can easily exceed 100 amps and most business either don't have that much excess power or it is not available at the location that the lights must be positioned, such as on a roof. This large power demand requires a generator to also be provided, along with the fuel and an operator, to keep it all fueled and running. It can be a very expensive proposition. A need exists for a searchlight which requires substantially less electricity such that a generator and dedicated operator are not necessary.

There are additional issues such as the bulbs themselves. When they burn out, the service technician must wear protective gear to shield themselves during the re-bulbing process from flying quartz glass as the bulbs, especially when hot, have enormous pressures inside. The bulbs have a life from 200-1000 hours but rarely longer and they can be very expensive depending on their size. The technician usually wears leather wrist covers, a leather chest protector and a face shield over safety goggles whenever he handles one. The bulbs also sometimes explode when being used, destroying not just themselves but a very expensive reflector and the cover glass. Quartz glass shards are nearly invisible when impaled into the human body and consequently are very hard to find often requiring them to be removed by

surgeons in a hospital setting. The cover glass in current designs is safety glass and also has UV absorbing properties to protect the public and operator from excessive UV exposure.

The bulb's life decreases and the risk of explosion increases if a careless technician were to accidentally touch one with a bare finger wherein the finger oil reacts on the glass when the bulb heats up. The bulbs must also be blasted by a powerful amount of moving cool air and that air exhausted in order to keep the bulbs from melting or exploding. They can do either or both if the fan fails or isn't run long enough after the bulb is turned off such as when a generator unexpectedly fails. These bulbs also suffer from an instable arc which appears as flicker though this is usually just the arc jumping around and not being stable, but the unwanted effect from the defocusing act of this jumping appears to the observer as going on and off rapidly.

The parabolic reflectors used in present searchlights/sky lights are highly reflective mirrors plated onto a nickel metal shape. The process of making these types of mirrors is a long and arduous process using large quantities of nickel, electricity, and vacuum chambers for depositing the nickel to form the highly reflective mirror like surface. This process is well known in the art but the simple fact is that these mirrors are very expensive and their finish is very delicate and easy to damage, even by simple mishandling such as touching them with bare fingers. In the case of searchlights, the reflectors are more complicated in some aspects as they have to be very deep because the light emitted from the xenon bulbs is omni-directional. That is to say that the light comes out at nearly 360 degrees, on all axes, and that light must all then be directed in a single direction with the aid of the reflector.

The reflectors also have to be able to reflect heat and not just the light out of the fixture in the light beam using such technology as in a cold mirror which is mostly made by using specially and expensively applied layers of reflector material in the vacuum chamber process or a traditional hot mirror where the mirror and the nickel absorb a great deal of the heat so it is not transmitted in the light beam. Xenon beams have been known to burn people by the projected IR waves and to start many fires because their beams are so intense. The hot mirrors also have to be cooled by powerful fans in order to remove the intense heat from the fixture.

These reflectors are generally sized by two parameters, total wattage and arc size. The greater the power of the light, the more surface area of mirror is required because a mirror can only absorb or reflect so much IR before it heats up to the point where the surface materials degrade. There is also the issue of point source size vs. focal length. A large source requires a much longer focal length, and the reflector then would require a much larger outside diameter. This increased size exponentially increases the cost of the mold, nickel, and fabrication costs in general so it is best to minimize the point source size to minimize the reflector size requirements. Deep reflectors also cost much more than shallow reflectors but yet they capture a larger angle of emitted light than the shallow versions, a trade-off situation.

The primary function of these searchlights/sky lights is to attract attention and occasionally operators are asked to add colored filters to increase the attention further. The hot light from these arc sources generally fade the filter material in a matter of hours or worse yet melt them beyond usability.

What is needed is new point source light that does not have the requirements of high power usage, short life, does

not emit UV, IR, risk explosions, require safety clothing, sensitive handling, powerful cooling fans, deep reflectors, or high cost.

SUMMARY OF THE INVENTION

The device of the present disclosure uses at least one high flux LED and preferably a plurality of high flux LEDs arranged in an array such that the light emitted is directed toward a reflector. The array could be of any suitable geometry and includes a suitable number of LEDs to the power requirements. The array of LEDs is positioned with respect to the reflector so as to focus the individual beams of light emitted from the individual LED's into a single intense column of light suitable for projection by a searchlight/sky light application. These LEDs can be clustered in a tight group. It is preferred to employ a cluster of high flux LEDs to at least double the amount of light as a xenon bulb consuming the same power. LEDs emit no UV and an extremely small amount of IR.

The LED based searchlight/sky light of the present disclosure includes, in a basic embodiment, a housing; an LED array supported in/by the housing, a heat sink in communication with the LED array, and a reflector supported in the housing such that the LED array is supported by the housing a distance sufficient above the reflector to allow the light emitted by the LED array to be reflected by the reflector. The reflector is preferably a parabolic reflector such that the light emitted by the LED array is reflected by the parabolic reflector in a collimated beam. In other words, the LED array is preferably supported above the parabolic reflector by a distance equal to the focal length of the parabolic reflector.

It is contemplated that the device of the present disclosure may use a heatsink on this highly concentrated array of high density LEDs. It is further contemplated that this heatsink would have to be actively cooled by forced air, heat pipes, or liquid cooled, with liquid cooling being the preferred method. This may best be accomplished by a liquid which is a water/glycol mixture circulated through a jacket or manifold and then to a radiator or other such heat exchange apparatus that would in turn be fan cooled. The liquid mixture used for cooling may be moved (circulated) by a small pump. A radiator could be either in the fixture head itself or somewhat removed nearby for heat exchange.

The expensive parabolic mirror of present designs would ideally be replaced with a reflector made of relatively inexpensive plastic with an applied mirror finish so as to reduce costs, weight, and would be much easier to replace and recycle than the present nickel/aluminum versions. The LED arrays would preferably have integral lenses so that they would project light in a 120 degree cone, not omnidirectionally, allowing a much shallower reflector with little waste of light. The safety glass which was previously quite fragile could be replaced with a sheet of polycarbonate, sometimes called bullet proof glass or other suitable material.

The fixtures of the present disclosure could be mounted on moving arms and in groups to provide lighting effects similar to those used with present short arc lamps but without all of the hazards and negatives referenced above with regard to existing constructions. The LEDs could be driven with constant current to protect them from over current situations or brightness changes caused by the LED's forward voltage changing due to LED temperature changes, a physical reality. This inventive power process would also protect the LED arrays from voltage spikes when powered from unstable generators or AC power.

The lights of the present disclosure could be able to be controlled manually or remotely by such methods as DMX-512, an industry standard, or by wireless, or by a connection through the Internet. Internet based controls would allow feedback regarding the internal conditions of the light which the other methods might or might not need to provide. The LEDs are preferably white but in alternate embodiments are replaced with red, green, or blue (RGB). These bright RGB colors could provide the color effects but will not fade as filters do with traditional light sources.

The light of the present disclosure might also use light shaping diffusion (LSD) which is a holographic type film that can change the shape of the light to best conform to the shape of an object such as a building and not allow significant light spill into the sky. This feature would allow the inventive light to best conform to "dark skies" initiatives. This LSD would be unique to the industry because most architectural lighting is simply too hot and would melt the LSD when applied during use. The tight group (array) of clustered high flux LEDs could also be arranged into an elongated pattern rather than a circular shape to allow the shape of the light emitted from the present system to be elongated in such a way as to best match the shape of a desired object, such as a building's outline, without using LSD.

Other aspects and advantages of the invention will be apparent from the following description and the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top cutaway view of the LED based searchlight/sky light of the present disclosure.

FIG. 2 is an isometric view of the LED based searchlight/sky light of the present disclosure moveably mounted to a base.

FIG. 3 is a top view of the LED based searchlight/sky light of the present disclosure.

FIG. 4 is a bottom view of the LED based searchlight/sky light of the present disclosure.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

With reference to the figures, the LED based searchlight/sky light of the present disclosure **100** includes, in a basic preferred embodiment, a frame/housing **116** and an LED array **102** supported in/or by frame/housing **116**. LED array **102** is preferably in thermal communication with a heatsink **104** so as to dissipate heat generated by the operation of LED array **102**. In a preferred arrangement, LED array **102** is secured to heatsink **104** such that heatsink **104** is supported in and/or by frame/housing **116** by a plurality of support arms **106**. A reflector **122** is also supported in and/or by frame/housing **116**. In a preferred arrangement, reflector **122** is a parabolic reflector **122** and LED array **102** is positioned above reflector **102** a distance sufficient such that light emitted from LED array **102** is directed toward reflector **122** and reflected by reflector **122** in an intense collimated beam of light. This intense collimated beam can be projected outwardly from searchlight/sky light **100** so as to attract attention of an observer a distance away for purposes such as advertising.

In an alternate embodiment, frame/housing **116** could be sealed by the installation of a piece of glass **118** which allows the collimated beam **128** to pass therethrough. Glass **118** is secured into frame/housing **116** by glass mount **120**.

It is understood that glass **118** could be glass, plastic, polymer or other material suitable for this purpose. It is generally desirable to employ a light, strong, impact resistant material. In a preferred embodiment, glass **120** is constructed of polycarbonate, a light, extremely strong material, however, it is understood that glass **118** could be constructed of any suitable material.

The LED based searchlight/sky light **100** of the present disclosure employs at least one high flux LED and preferably a plurality of high flux LEDs arranged in an array. Suitable high flux LEDs may be obtained from LEDengine in Santa Clara, Calif., which can provide up to 90 watts of LED light. In a preferred arrangement the combined output of the LED array **102** is at least approximately 350 watts and most preferably approximately 1,000 watts of LED light.

The LEDs can be clustered in an array **102** which could be in any suitable geometry. For example, without limitation, these LEDs can be clustered in a tight circular group of 12 mounted to a circuit board to form array **102** for a fixture that would provide approximately 1,000 watts of LED light. This example arrangement and light output equates to at least double the amount of light emitted than if a xenon bulb were employed while consuming the same power. In addition, LEDs emit no UV radiation and an extremely small amount of IR radiation. The LEDs comprising LED array **102** are preferably white but can, in an alternate embodiments, be replaced with red, green, or blue (RGB) LEDs. These bright RGB colors could be employed to provide a desired color effect in the projected beam of light without having to employ filters as with traditional light sources. However, it is understood, that colored filters could alternately be applied over glass **118** to also produce a colored effect.

Frame/housing **116** could include a frame structure which supports an outer solid, preferably opaque housing. Alternatively, frame/housing **116** could be constructed such that the outer, preferably opaque housing supports an internal frame structure. In yet another preferred embodiment, the outer, preferably opaque housing could be constructed strong enough such that itself serves as the frame without frame structure.

Heatsink **104**, in an effort to assist in the dissipation of heat generated by LED array **102** is preferably secured to and supported from heatsink **104**. In the preferred arrangement heatsink **104** is actively cooled through the use of a cooling mixture which is preferably a mixture of water and ethylene glycol. To accomplish this, heatsink **104** is essentially a manifold through which the cooling mixture is circulated. A pair of coolant hoses **108** and **114** are employed to circulate coolant to and from heatsink **104**. Coolant may be circulated from heatsink **104** through coolant line **108** to a heat exchanger **110**. Heat exchanger **110** could be any suitable structure, known in the art and may operate similar to a radiator or automotive heater core such that coolant which is heated as a result of circulation through heatsink/manifold **104** enters heat exchanger **110** and passes there-through. Heat exchanger **110** may include fins for additional dissipation of heat through contact with surrounding air. For additional cooling, a suitable fan **109** such as a simple 12 volt muffin fan, for example, may be employed to move air across heatsink **110** to enhance the heat exchange capabilities. Once the coolant passes through heat exchanger **110** it is sufficiently cooled so as to be circulated back through coolant hose **114** into manifold/heatsink **104**. Such circulation of coolant through heatsink **104** is continuous while searchlight/sky light **100** is in operation. A pump **112** may be

employed to circulate coolant through this system. Pump **112** could be any suitable pump such as a 12 volt fluid pump known in the art.

In an alternate embodiment (not shown), heat tubes could be employed which extend from manifold/heatsink **104** to the outside of housing **116** which may then be in contact with a finned heat exchanger. In such an embodiment (not shown) the heat tubes would be oriented to allow for the convection of the coolant contained therein without the requirement of a powered pump to circulate the coolant.

Reflector **122** is mounted in and supported by frame/housing **116** such that its reflective surface is directed toward LED array **102**. As stated, in a preferred arrangement, reflector **122** is a parabolic reflector which receives and reflects light photons emitted from LED array **102**. Since LEDs are known to conduct heat as opposed to radiating heat, as is the case with carbonarc or xenon shortarc bulbs, reflector **122** of LED based searchlight/sky light **100** will not be subject to an intense radiation of heat. As a result, reflector **122** in the present disclosure can be constructed of lightweight, relatively inexpensive materials to which a reflective/mirror finish is applied. Any suitable mirror finish capable of receiving and reflecting light photons emitted from LED array **102** may be suitable.

LED array **102** is secured to heatsink **104**. Heatsink **104** is supported within frame/housing **116** by supports **106** such that LED array **102** secured thereto is positioned above reflector **122**. The LEDs in LED array **102** would preferably be constructed to include integral lenses so that they would each emit light in a 120° cone as shown in FIG. 1 as **126**. LED array **102** is positioned above reflector **122** such that light photons emitted from the LEDs would impact parabolic reflector **122** such that they are reflected in an collimated orientation depicted in FIG. 1 as **128**. As a result, in a preferred arrangement, LED array **102** is positioned above reflector **122** a distance sufficient such that light photons emitted from LED array **102** are reflected by reflector **122** to form an intense collimated beam. In a particularly preferred embodiment, LED array **102** is positioned above reflector **122** at the focal length of parabolic reflector **122**.

LED array **102** and heatsink/manifold **104** may be sized and constructed so as to preferably not interfere with (block) the beam of collimated light reflected from parabolic reflector **122** past LED array **102** and heatsink/manifold **104** so as to exit housing **116** as shown in FIG. 1 as **128**. By way of example only, and without limitation, it is contemplated that a housing **116** sized so as to receive a parabolic reflector having approximately a 3' diameter may be constructed with an LED array **102** positioned at its focal length wherein LED array **102** and heatsink **104** are sized approximately 2¼" by 2¼" with a thickness of approximately ½". As a result, an LED array **102** secured to a heatsink/manifold **104** of such an exemplary size and construction positioned above such a sized parabolic reflector **122** would cause very little obstruction of light projected from searchlight/sky light **100**. However, it is understood that this is just an example and many different sizes are contemplated without departing from the scope of the present disclosure.

Power supply **124** produces roughly 48 volts at approximately 21 amps and is preferably a switch mode power supply operating to produce a substantially constant current to LED array **102**. A dimmer operatively selects the level at which the constant current is supplied. Thus at full brightness, power supply **124** outputs approximately 21 amps, at half brightness 10.5 amps, etc. Power supply **124** also preferably accepts DMX-512 to set the output current. Alternatively, power supply **124** could output 48 volts at 21

amps and use variable duty cycle to control the brightness. Internet based controls could be employed to allow feedback regarding the internal conditions of the searchlight/sky light 100. Such feedback could be helpful to an operator at a remote location.

Light shaping diffusion (LSD), a holographic-type film can be applied over glass 118 of housing 116 in order to shape the light as desired. For example, the light emitted could be shaped to conform to an object such as a building. As a result, unwanted light spillage into the sky around the building could be avoided.

With specific reference to FIG. 2, searchlight/sky light 100 is depicted as mounted to a base 134. Searchlight/sky light 100 could be mounted to base 134 using a known method such as a yoke 130 supported on a pin 132. In such an embodiment, pin 132 will allow yoke 130 to rotate in relation to base 134 in one axis and searchlight/sky light may be rotated within yoke 130 in relation to base 134 in another axis. As a result, searchlight/sky light 100 may be embodied so as to be moveable, either manually or remotely, with respect to base 134. In the event of remote operation, electric motors would be employed in a known manner so as to effectuate rotation of light 100 or yoke 130 with respect to base 134. Remote operation can be accomplished by such methods as DMX-512, wirelessly, or by an internet connection.

In alternate embodiments, a plurality of searchlights/sky lights 100 could be positioned adjacent each other. In such an embodiment the plurality of lights 100 could be operated, either manually or remotely, to produce a desired visual effect

With specific reference to FIG. 4, a bottom or rear panel 200 (depending on the orientation of light 100) is depicted. Rear panel 200 may include a vent 202 to allow the evacuation of air heated by its passage through heat exchanger 110 (FIG. 1). Rear panel 200 may also include a connector for electrical current such as a known IEC power connector 204 and may also include a power switch 206. A manual dimmer knob 208 may also be located on rear panel 200. Rear panel 200 may further include connectors such as DMX connectors 210 to provide for the remote control of searchlight/sky light 100.

A list of elements is depicted in the Figures, wherein:

- 100 LED based searchlight/sky light fixture assembly
- 102 LED array
- 104 water cooled heatsink
- 106 support arms
- 108 water line from heatsink
- 110 radiator
- 112 pump
- 114 water line to heatsink
- 116 fixture housing/frame
- 118 glass
- 120 glass mount
- 122 parabolic reflector
- 124 power supply
- 126 path of photon emitted by LED array
- 128 path of photon reflected by parabolic mirror reflector
- 130 yoke
- 132 pivot pin
- 134 base
- 200 rear panel
- 202 vent
- 204 electrical current connector
- 206 power switch
- 208 dimmer knob

210 DMX connectors

Thus, the present invention is well adapted to carry out the objects and attain the ends and advantages mentioned above as well as those inherent therein. While presently preferred embodiments have been described for purposes of this disclosure, numerous changes and modifications will be apparent to those skilled in the art. Such changes and modifications are encompassed within the spirit of this invention as defined by the appended claims.

What is claimed is:

1. A searchlight, comprising:
 - a frame;
 - a 350 watt array of light emitting diodes or more capable of emitting light upon application of electrical current;
 - said array of light emitting diodes being mounted to a heat sink;
 - said heat sink being liquid cooled and in conductive thermal communication with said array of light emitting diodes;
 - a heat exchanger in fluid communication with said heat sink;
 - a pump for circulating liquid coolant continuously between said heat sink and said heat exchanger in a closed system;
 - at least a 350 watt power supply configured for providing electrical current to said array of light emitting diodes and regulating said electrical current applied to said array of light emitting diodes;
 - a reflector supported by said frame such that said array of light emitting diodes is positioned above said reflector such that said light emitted from said array of light emitting diodes is directed toward said reflector and is reflected by said reflector to produce an intense projected beam of light directed back toward and beyond said array of light emitting diodes;
 - said array of light emitting diodes, said heat sink, and said heat exchanger being positioned so as not to block said intense projected beam of light reflected by said reflector.
2. The searchlight of claim 1 wherein said reflector is a parabolic reflector.
3. The searchlight of claim 1 wherein said heatsink includes a manifold containing said liquid coolant therein in fluid communication with said heat exchanger.
4. The searchlight of claim 1 wherein said power supply is capable of selectively dimming said at least one LED.
5. The searchlight of claim 1 wherein said at least a 350 watt power supply is a switch mode power supply.
6. The searchlight of claim 1 further comprising a fan for moving air across said heat exchanger.
7. The searchlight/skylight of claim 1 wherein said heat exchanger is physically removed from said heat sink.
8. A searchlight/sky light for the projection of an intense beam of light into the night sky, comprising:
 - a housing having an interior;
 - a 350 watt LED array or more capable of emitting light upon application of electric current;
 - a liquid cooled heat sink in conductive thermal communication with said LED array;
 - a heat exchanger in fluid communication with said heat sink;
 - a pump for circulating liquid continuously between said heat sink and said heat exchanger supported in said housing;
 - a parabolic reflector supported in said housing;
 - said LED array being positioned above and not in conductive thermal communication with said parabolic

9

reflector at the focal length of said parabolic reflector and directed toward said parabolic reflector such that an intense projected beam of light is produced; said heat exchanger being positioned in said housing between said parabolic reflector and the interior of said housing.

9. The searchlight/sky light of claim 8 wherein said LED array is positioned in said housing such that light emitted from said LED array directed toward said parabolic reflector is reflected in a collimated beam.

10. The searchlight/sky light of claim 8 further including a remotely controllable power supply for regulating the electric current applied to said LED array.

11. The searchlight/sky light of claim 10 wherein said LED array is dimmable by controlling said power supply to vary the electric current applied to said LED array.

12. The searchlight/sky light of claim 8 wherein said heat sink includes a manifold containing a liquid coolant and is in fluid communication with said at least one heat exchanger.

10

13. The searchlight/sky light of claim 12 further comprising a fan configured for moving air across said heat exchanger.

14. The searchlight/sky light of claim 8 wherein said LED array is comprised of high flux LEDs.

15. The searchlight/sky light of claim 9 wherein said housing is mounted to a base such that said housing is movable with respect to said base in order to vary the direction of said collimated beam.

16. The searchlight/sky light of claim 15 wherein the movement of said housing with respect to said base is controlled remotely.

17. The searchlight/skylight of claim 8 further comprising a polycarbonate cover secured to said housing.

18. The searchlight/skylight of claim 10 wherein said power supply is a switch mode power supply.

* * * * *