

(19)



(11)

EP 1 678 366 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
11.03.2009 Bulletin 2009/11

(51) Int Cl.:
D06F 58/20 ^(2006.01) **C11D 1/66** ^(2006.01)

(21) Application number: **04796488.7**

(86) International application number:
PCT/US2004/035566

(22) Date of filing: **27.10.2004**

(87) International publication number:
WO 2005/045120 (19.05.2005 Gazette 2005/20)

(54) **FABRIC ARTICLE TREATING SYSTEM AND METHOD**

TEXTILERZEUGNISBEHANDLUNGSSYSTEM UND -VERFAHREN

SYSTEME ET PROCEDE DE TRAITEMENT D'ARTICLES TEXTILES

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PL PT RO SE SI SK TR**

(30) Priority: **29.10.2003 US 697734**
29.10.2003 US 697735
29.10.2003 US 697736
29.10.2003 US 697685
21.01.2004 US 762152
05.05.2004 US 839549
06.05.2004 US 568771 P

(43) Date of publication of application:
12.07.2006 Bulletin 2006/28

(73) Proprietor: **THE PROCTER & GAMBLE COMPANY**
Cincinnati, Ohio 45202 (US)

(72) Inventors:
• **ZHANG, Shulin, Larry**
West Chester, OH 45069 (US)
• **DEGUZMAN TRAJANO, Trace, Wendell**
Mason, OH 45040 (US)

- **OFOSU-ASANTE, Kofi**
Cincinnati, OH 45224 (US)
- **HEATHERLY, Joseph, Dean**
Morrow, OH 45152 (US)
- **BARNABAS, Freddy, Arthur**
West Chester, OH 45069 (US)
- **CHILDERS, Jamie, Marie**
Loveland, OH 45140 (US)
- **BEDE, Cynthia, Maria**
Cincinnati, OH 45227 (US)
- **DUVAL, Dean, Larry**
Lebanon, OH 45036 (US)

(74) Representative: **Goodier, Claire-Louise et al**
NV Procter & Gamble Services SA,
Temselaan 100
1853 Strombeek-Bever (BE)

(56) References cited:
WO-A-03/087461 **US-A- 4 022 938**
US-A- 4 207 683

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 1 678 366 B1

Description

FIELD OF INVENTION

[0001] The present invention relates to systems and methods useful for treating a fabric article with a composition comprising polyol-based fabric care materials and a dispersing medium. The dispersing medium is a liquid at room temperature and has a flash point of greater than about 65°C. Specifically, the composition may be dispensed to treat fabric articles in an appliance during the fabric article drying process.

BACKGROUND OF THE INVENTION

[0002] Fabric article treating methods and/or apparatuses have been evolving over the past 20 years. For example, technologies relating to fabric treatment compositions and/or dispensing devices suitable for use in a tumble dryer are disclosed in U.S. Patent 4,207,683; U.S. Patent Publications 2003/0200674A1; 2003/0213145A1; and PCT Publication WO 03/087286A1.

[0003] There exists a continuing need to develop a fabric article treating methods and/or systems, especially for in-home fabric article treating applications in the drying cycle that improves and/or enhances the deposition of fabric article actives onto fabric articles being treated. There also exists a continuing need to develop fabric treatment compositions having characteristics (such as viscosity-temperature profile, flash point, odor) suitable for use in those fabric article treating method and/or systems. Moreover there exists a continuing need to develop fabric treatment compositions that are comfortable against the skin and that does not yellow with repeated use.

SUMMARY OF THE INVENTION

[0004] One aspect of the present invention relates to a fabric article treating system comprising:

- (a) a fabric article drying appliance; and
- (b) a fabric article treating device removably attached to said drying appliance, said treating device comprising a source for containing a fabric treatment composition and means for dispensing said composition in said drying appliance, in the form of droplets having an average particle size of from 0.1 to 1000 microns said means is in liquid communication with said source;

wherein said composition comprises a polyol-based fabric care material and a dispersing medium.

[0005] In another aspect of the invention, methods for treating a fabric article with a composition comprising polyol-based fabric care materials in a fabric article drying appliance are also provided.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The accompanying drawings incorporated in and forming a part of the specification illustrate several aspects of the present invention, and together with the description and claims serve to explain the principles of the invention. In the drawings:

FIG. 1 is a perspective view of an embodiment for a stand-alone fabric article treating apparatus that is constructed according to the principles of the present invention.

FIG. 2 is a perspective view from the opposite angle of the fabric article treating apparatus of FIG. 1.

FIG. 3 is an elevational view from one end in partial cross-section of the fabric article treating apparatus of FIG. 1, illustrating the internal housing and external housing, as joined together by a flat cable.

FIG. 4 is an elevational view from one side in partial cross-section of the internal housing portion of the fabric article treating apparatus of FIG. 1.

FIG. 5 is a block diagram of some of the electrical and mechanical components utilized in the fabric article treating apparatus of FIG. 1.

FIG. 6 is a diagrammatic view in partial cross-section of the fabric article treating apparatus of FIG. 1, as it is mounted to the door of a clothes dryer apparatus.

FIG. 7 is a perspective view of a fabric article drying appliance that has a nozzle which sprays a benefit composition into the drum portion of the dryer, as constructed according to the principles of the present invention.

FIG. 8 is a perspective view of another embodiment of a stand-alone unit for dispensing a benefit composition constructed according to the principles of the present invention.

FIG. 9 is a perspective view from an opposite angle of the unit of Fig. 8. FIG. 10 is an exploded view of the unit

illustrated in FIGS. 8 and 9.

FIG. 10 is an exploded view of the unit illustrated in FIGS. 8 and 9.

FIG. 11 is an exploded view of the fluid container, the first and second fitments and the first and second mounting shelves.

FIG. 12 is a block diagram of at least a portion of the electrical and mechanical components utilized in the unit of FIGS. 8 - 10.

DETAILED DESCRIPTION OF THE INVENTION

Definitions

[0007] As used herein, "fabric article" means an article composed of fabrics and/or fibers. Such articles include, but are not limited to, clothing, towels and other bath linens, bed linens, table cloths, carpets, curtains, upholstery coverings, sleeping bags, tents, shoes, and car interior (such as car seat covers, car floor mats).

[0008] As used herein, "during a drying cycle" means while the dryer is operating.

[0009] As used herein, "fabric care material" means a material or combination of materials that can deliver one or more of the following benefits to a fabric article; softening, crispness, water and/or stain repellency, refreshing, antistatic, anti-shrinkage, anti-microbial, durable press, wrinkle resistance, odor resistance, abrasion resistance, anti-felting, anti-pilling, appearance enhancement, and mixtures thereof.

[0010] As used herein, "fabric treatment composition" means a composition that comprises one or more fabric care materials, or one or more perfume materials, or combinations thereof. Suitable forms of treatment compositions include, but are not limited to, fluidic substances, such as liquids or gases, and solid compounds, such particles or powders.

[0011] As used herein, the terms "treatment composition", "fabric treatment composition" and "benefit composition" are synonymous.

[0012] As used herein, the articles "a" and "an", when used in a claim, are understood to mean one or more of the material that is claimed or described.

[0013] Unless otherwise noted, all component or composition levels are in reference to the active level of that component or composition, and are exclusive of impurities, for example, residual solvents or by-products, which may be present in commercially available sources.

[0014] Unless otherwise indicated, all percentages and ratios are calculated based on weight of the total composition.

Treating System And Delivery Method

[0015] In one aspect of Applicants' invention, a fabric treatment composition that is applied by processes including, but not limited to, spraying, to a fabric article, wherein the treatment composition comprises one or more polyol-based fabric care materials.

[0016] In another aspect of Applicants' invention, the treatment composition that is applied by processes including, but not limited to, spraying, to a fabric article can be a composition comprising a polyol-based fabric care material, a dispersing medium, and optionally, one or more adjunct materials, such as fabric care materials or other adjuncts.

[0017] In a further aspect of Applicants' invention, the treatment composition is applied to a fabric article by a treating system that is configured to deliver, such as spraying, or otherwise release the treatment composition into a receiving volume, which could be the drum (or other chamber) of a clothes drying appliance, within which a fabric article is treated.

[0018] The treating system would typically comprise: a drying appliance comprising a drum in which the fabric article is deposited and treated; a housing or enclosure, such as a reservoir, that contains a source of the fabric treatment composition, or is in communication with an external source of the fabric treatment composition; a dispensing device that provides the means for releasing or dispensing the fabric treatment composition, such as a nozzle; a controller, such as an electronic control device with a processing circuit, and input and output circuits; one or more sensors, such as a temperature sensor or a vapor and/or gas sensor; one or more input devices, such as a start switch and/or a keypad; one or more indicating devices, such as color lights or LED's; and optionally, a charging system, if the fabric treatment composition is to be electrostatically charged before (or while) being delivered. Details of the electrostatically charged spraying apparatus and method are disclosed in U.S. Patent Publication No. 2004/0025368A1 filed April 17, 2003.

[0019] Reference will now be made in detail to suitable non-limiting embodiments of the treating system for delivering a fabric treatment, an example of which is illustrated in the accompanying drawings, wherein like numerals indicate the same elements throughout the views. Other treating systems suitable for use herein are disclosed in U.S. Patent 4,207,683; U.S. Patent Publications Nos. 2003/0200674A1; 2003/0213145A1; 2004/0025368A1; and U.S. Patent Application Serial Nos. 10/697,685 and 10/697,736.

[0020] FIGS. 1-4 illustrate one embodiment of an exemplary fabric article treating system for use in the present invention, while FIG. 5 depicts one embodiment of a suitable controller, and other electrical and electronic devices for

use in the present invention.

[0021] Referring now to the embodiment of FIG. 1, a "stand-alone" controller and dispenser unit (i.e., as a self-contained device), generally designated by the reference numeral 10, is illustrated as having two major enclosures (or housings) 20 and 50. In this embodiment, the enclosure 20 acts as an "inner housing" which is located in the interior of a fabric article drying appliance (e.g., a clothes dryer), while the enclosure 50 acts as an "outer housing" that is located in the exterior of the fabric article drying appliance. The enclosure 50 may be mounted on the exterior surface of the fabric article drying appliance door, however, it may instead be mounted on any exterior surface, non-limiting examples of which include: the side walls, the top walls, the outer surface of a top-opening lid, and the like, including a wall or other household structure that is separate from the fabric article drying appliance. Furthermore, the enclosure 20 may be mounted on any interior surface of the fabric article drying appliance, examples of which include, but are not limited to: the interior surface of the door, the drum of the fabric article drying appliance, the back wall, the inner surface of a top-opening lid, and the like.

[0022] Enclosure 50 may be permanently mounted to the exterior surface, or preferably releasably attached to the exterior surface. Likewise, enclosure 20 may be permanently mounted to the interior surface, or releasably attached to the interior surface. One configuration for such an attachment is illustrated in FIG. 6, in which the door of the drying appliance is generally designated by the reference numeral 15.

[0023] When mounted on the interior surface of the door, for example, the enclosure 20 may be constructed so as to have the appearance of being "permanently" mounted, such that it seems to be "built into" the door of a dryer unit (or other type of fabric article drying appliance), without it actually being truly constructed as part of the fabric article drying appliance. On the other hand, enclosure 20 perhaps may be more loosely mounted near the door, or along side the interior surface of the door, much like one of the embodiments 10 as depicted in FIGS. 1-4 that "hangs" along a vertical door of the appliance. It will be understood that the term "door," as used herein, represents a movable closure structure that allows a person to access an interior volume of the dryer apparatus, and can be of virtually any physical form that will enable such access. The door "closure structure" could be a lid on the upper surface of the dryer apparatus, or a hatch of some sort, or the like.

[0024] It should be noted that the treating apparatus 10 may be grounded by way of being in contact with a grounded part of the fabric article drying appliance such as by a spring, patch, magnet, screw, or other attaching means, and/or by arc corona discharge, or by way of dissipating residual charge. Non-limiting examples of suitable methods for dissipating charge are disclosed in U.S. Patent Publication No. 2004/0025368.

[0025] In FIG. 1, a discharge nozzle 24 and a "door sensor" 22 are visible on the inner housing 20, which also includes a benefit composition-holding reservoir 26 within an interior volume of the inner housing 20. The reservoir 26 may be used to hold a benefit composition. The discharge nozzle 24 can act as a fluid atomizing nozzle, using either a pressurized spray or, along with an optional high voltage power supply (not shown in FIG. 1) it can act as an electrostatic nozzle. One suitable example of a fluid atomizing nozzle is a pressure swirl atomizing nozzle. Non-limiting examples of suitable nozzles include the Cosmos 13 NBU nozzle manufactured by Precision Valve Corporation of Marietta, Georgia, the WX12 and WD32 nozzles manufactured by Saint-Gobain Calmar USA, Inc. of City of Industry, California, and Seaquist Model No. DU-3813 manufactured by Seaquist Dispensing of Cary, Illinois. The nozzle may be permanently attached or releasably attached to the treating device. One non-limiting example of a releasably attached nozzle is a nozzle which is threaded such that it can easily be removed from or placed in the treating device. The nozzle may be disposable.

[0026] A spray nozzle or a fluid atomizing nozzle typically provides an average droplet size that is less than about 1000 microns, typically from about 100 to about 1000 microns, or from about 120 to about 500 microns, or from about 150 to about 300 microns. This average droplet size is measured by a Malvern particle analyzer. When a spray nozzle is covered with a fine grid or a membrane to produce a finer mist of droplets with an average particle size of less than 100 microns.

[0027] Nebulizers, atomizers and like devices are well known to those skilled in the art. A suitable device for use herein is a nebulizer that has at least one ultrasonic sonotrode, or ultrasonic vibrating cell. Typical of such nebulizer is commercially available under the tradename Acu Mist® from Sono Tek Corporation, Milton, New York. Still other examples of such devices are available from Omron Health Care, GmbH, Germany; and from Flaem Nuove, S.P.A, Italy. Likewise, aerosol delivery systems, which are well known to the art, can be used to deliver the detergent and/or finishing compositions. The benefit composition can comprise a fluidic substance, such as a liquid or a gaseous compound, or it can comprise a solid compound in the form of particles, such as a powder, or solid particles in solution with a liquid.

[0028] Reservoir 26 can be of essentially any size and shape, and could take the form, for example, of a pouch or a cartridge; or perhaps the reservoir could be connected to a source of dispersing medium (for example, a household water line for situations in which the benefit composition comprises potable water) such that the benefit composition in the reservoir can be diluted to the desired viscosity and/or surface tension.

[0029] The inner housing 20 and outer housing 50 are typically in electrical communication. In the embodiment of FIG. 1, a flat cable 40 (also sometimes referred to as a "ribbon cable") is run between the two housings 20 and 50, and travels along the inner surface of the fabric article drying appliance door 15 (see FIG. 6, for example), over the top of the door

15, and down the exterior surface of the door 15.

[0030] FIG. 2 shows the same fabric article treating apparatus 10 from an opposite angle, in which the outer housing 50 is provided with an ON-OFF switch at 56. The flat cable 40 is again visible in FIG. 2, and along the surface of the inner housing 20 visible in FIG. 2, a door mounting strap 21 is visible. An end of the mounting strap is also visible in FIG. 1. Certainly other arrangements for attaching the inner housing 20 to a dryer door 15 (or other interior surface) are available without departing from the principles of the present invention.

[0031] Referring now to FIG. 3, the fabric article treating apparatus 10 is illustrated such that the reservoir 26 can be seen as an interior volume of the inner housing 20. In the outer housing 50, a set of batteries 52 can be seen, as well as a printed circuit board with electronic components at 54. The electronic components of one embodiment will be discussed below in greater detail. It will be understood that any type of electrical power source could be used in the present invention, including standard household line voltage, or even solar power. Batteries may be utilized if it is desired to make the apparatus 10 easily portable, however, any appropriate power adapter can be provided to convert an AC power source to the appropriate DC voltage(s) used in the electronic components on the PC board 54, or to convert a DC power source (including a battery or solar panel) to the appropriate DC voltage(s) used in the electronic components on the PC board 54.

[0032] Referring now to FIG. 4, some of the other hardware devices are illustrated with respect to the inner housing 20. In the embodiment of FIG. 4, the discharge nozzle 24 acts as an electrostatic nozzle, and thereby is coupled with a high voltage power supply 28, by use of an electrical conductor not shown in this view. A quick disconnect switch 34 is included for safety purposes, so that the high voltage power supply 28 can be quickly shut down if necessary. A pump 30 and a corresponding electric motor 32 are visible in FIG. 4. Some type of pumping apparatus is used regardless as to whether the discharge nozzle 24 is producing a pressurized spray only, or an electrostatic spray that utilizes a high voltage power supply 28.

[0033] FIG. 5 provides a block diagram of some of the electrical and mechanical components that are included in a fabric article treating apparatus 10, as constructed according to one embodiment of the present invention. In this example embodiment, the high voltage power supply 28 is provided in the inner housing 20, which will be used to electrically charge the fluid that will be dispensed through the discharge nozzle 24, thus making this an electrostatic nozzle system. The inner housing 20 utilizes a general body or enclosure to contain the devices needed within the drying appliance, and it will be understood that such components will generally be subjected to relatively high temperatures during the treatment cycle of the drying appliance. Consequently, the more sensitive electronic components will generally (but not always) be mounted in a different location, such as in the outer housing 50.

[0034] The flat cable 40 will bring certain command signals and electrical power into the inner housing 20, and will also receive electrical signals from sensors mounted in the inner housing 20 and communicate those sensor signals back to the outer housing 50. A power supply control signal follows a wire 70 through the quick disconnect switch 34 to the high voltage power supply 28. This signal can comprise a constant DC voltage, a constant AC voltage, a variable DC voltage, a variable AC voltage, or some type of pulse voltage, depending on the type of control methodology selected by the designer of the fabric article treating apparatus 10.

[0035] In one embodiment, the signal at 70 is a variable DC voltage, and as this voltage increases, the output of the high voltage power supply 28 will also increase in voltage magnitude, along a conductor 39 (e.g., a wire) that is attached to an electrode 38 that carries the high voltage to the nozzle 24, or into the reservoir 26. The voltage impressed onto the electrode 38 will then be transferred into the benefit composition. A constant output voltage DC high voltage power supply could optionally be used instead of the variable output voltage power supply 28 of the exemplary embodiment.

[0036] Once the benefit composition is charged within the reservoir 26 it will travel through a tube or channel 42 to the inlet of the pump 30, after which the composition will be pressurized and travel through the outlet of the pump along another tube (or channel) 44 to the discharge nozzle 24. For use in the present invention, the actual details of the type of tubing used, the type of pump 30, and the type of electric motor 32 that drives the pump, can be readily configured for almost any type of pressure and flow requirements. The electrical voltage and current requirements of the electric motor 32 to provide the desired pressure and flow on the outlet of the pump 30 can also be readily configured for use in the present invention. Virtually any type of pump and electric motor combination can be utilized in some form or another to create a useful device that falls within the teachings of the present invention, or a stand-alone pump can be used (i.e., without an associated electric motor), as discussed below.

[0037] It should be noted that some types of pumps do not require separate input and output lines or tubes to be connected thereto, such as peristaltic pumps, in which the pump acts upon a continuous tube that extends through an inlet opening and continues through a discharge opening of the pump. This arrangement is particularly beneficial for use with electrostatically charged fluids or particles that are being pumped toward the discharge nozzle 24, because the tubing can electrically insulate the pump from the charged benefit composition. It should also be noted that an alternative pumping device could be used, if desired, such as a spring-actuated pumping mechanism. A non-limiting example of a suitable peristaltic pump is the Model 10/30 peristaltic pump, which may be obtained from Thomas Industries of Louisville, Kentucky.

[0038] The types of control signals used to control the electric motor 32 can vary according to the design requirements of the apparatus 10, and such signals will travel along an electrical conductor 72 to control motor 32, via the flat cable 40. If the motor 32 is a DC variable-speed motor, then a variable "steady" DC voltage can be applied, in which the greater the voltage magnitude, the greater the rotational speed of the motor. In one embodiment, the electrical signal traveling along conductor 72 can be a pulse-width modulated (PWM) signal, that is controlled by a microprocessor or a micro-controller. Of course, such a pulse-width modulated signal can also be controlled by discrete logic, including analog electronic components.

[0039] The fabric article treating apparatus 10 can be enhanced by use of certain sensors, examples of which include but are not limited to a door (or lid) sensor 22, a motion sensor 36, a humidity sensor 46, and/or a temperature sensor 48. An analog output temperature sensor can be used to provide an analog signal along the electrical conductor 86 that leads back to the controller in the outer housing 50.

[0040] The major components of the exterior housing 50 typically comprise the electronics 54 and the power source 52. For example, if power source 52 comprises four D-cell batteries connected in series, a +6 volt DC voltage will be provided to a set of DC power supplies generally designated by the reference numeral 58. It will be presumed that more than one DC power supply voltage will be required by the control circuit in the outer housing 50. One of the DC power supply voltages provides energy for the high voltage power supply 28, via the electrical conductor 70 that runs through the flat cable 40. Another output voltage is provided to a microcontroller 60, which in an exemplary embodiment requires a +3.3 volt DC power supply. In an exemplary embodiment, a digital-to-analog converter (DAC) 62 is used, and the device provided by Analog Devices of Norwood, Massachusetts (Part No. AD 5301), requires a +5 volt DC power supply. All of these power supplies are provided by the "set" of DC power supplies 58.

[0041] Part of the external housing 50 includes inputs to the microcontroller 60. One important element that could be used as a user interface to the microcontroller 60 would be a keypad 66, such as a set of bubble or membrane switches that have the numbers 0-9, as well as an "ENTER" key. Other keys could be included as part of keypad 66, including a "CANCEL" key, or perhaps a decimal point key.

[0042] FIG. 6 diagrammatically shows the general location of some of the components of one of the stand-alone embodiments of the fabric article treating apparatus 10 of the present invention. As discussed above, the electronics 54 and the batteries 52 are located within the outer housing 50, which is electrically connected to a flat cable 40 that carries power supply and input/output signals between the outer housing 50 and the inner housing 20.

[0043] Contained within the inner housing 20 are the reservoir 26, pump 30, electric motor 32, optional high voltage power supply 28, discharge nozzle 24, and various sensors that may or may not be included for a particular version of the treating apparatus 10. The electrical conductor 39 is depicted, which carries the high voltage to the nozzle 24, and this is one configuration that could be alternatively used instead of carrying the high voltage to the reservoir 26. The tubing 42 to the inlet of the pump is illustrated, as well as the tubing 44 from the outlet of the pump that provides the benefit composition to the nozzle 24. It should be noted that the high voltage power supply 28 is strictly optional within the teachings of the present invention; if spray droplets/particles emitted from the nozzle 24 are not to be electrostatically charged, then there is no need for a high voltage power supply within the inner housing 20.

[0044] FIG. 7 illustrates an alternative embodiment for use with the present invention, which depicts a fabric article drying appliance generally designated by the reference numeral 110. In this mode of the present invention, the controller depicted in the stand-alone embodiment of the earlier figures is now integrated into the electronic control system of the drying appliance 110. A door 15 is illustrated in FIG. 7, which is the normal point of access by a human user to the interior drum volume of the drying appliance 110. A nozzle 24 is used to direct a benefit composition into the drum area, in which the drum is generally designated by the reference numeral 114. A supply pipe 44 brings the benefit composition to the nozzle 24, through a control valve 120, that can have an ON/OFF push button 56, if desired.

[0045] In FIGS. 10-14, where like reference numerals indicate like elements, a benefit composition dispensing apparatus 1100 constructed in accordance with a third embodiment of the present invention is illustrated. The apparatus 1100 comprises two enclosures or housings 1120 and 1150. Enclosure 1120 defines an "inner housing" located in an interior of a fabric enhancement apparatus such as a fabric article drying appliance, e.g., a clothes dryer (not shown in FIGS. 10-14), while the enclosure 1150 defines an "outer housing" located outside of the fabric article drying appliance. The fabric enhancement apparatus may also comprise a laundry apparatus or a laundry and drying apparatus. The enclosure 1150 may be mounted on an exterior surface of the fabric enhancement apparatus door (not shown), such as by pressure sensitive, thermally stable adhesive foam strips (not shown). Alternatively, the enclosure 1150 may be mounted on any other exterior surface of the fabric enhancement apparatus, non-limiting examples of which include: side walls, top walls, an outer surface of a top-opening lid, and the like. The enclosure 1150 may also be mounted on a wall or other household structure that is separate from the fabric enhancement apparatus. Furthermore, the enclosure 1120 may be mounted, such as by pressure sensitive, thermally stable adhesive foam strips (not shown), on any interior surface of the fabric enhancement apparatus, examples of which include, but are not limited to: the interior surface of the door, a drum of the apparatus, the back wall, the inner surface of a top-opening lid, and the like.

[0046] As illustrated in FIGS. 8 and 9, the inner housing enclosure 1120 comprises a main body 1121 comprising an

integral front/side main section 1122 and a back plate section 1123 secured to the main section 1122 via screws, adhesive, snap-fit elements or the like. The sections 1122 and 1123 are preferably molded from a polymeric material. Housed within the main body 1121 are the following elements: a discharge nozzle 24; a door sensor 22 for sensing ambient light when the door of the fabric enhancement apparatus is open such that the sensor 22 is exposed to ambient light; a motion sensor 36 (contained within the main body 1121 and not visible from outside the main body 1121); a humidity sensor 46; and a temperature sensor 48. In this embodiment, the nozzle 24 is not combined with a high voltage power supply. The nozzle 24 functions as a fluid atomizing nozzle so as to generate a pressurized spray.

[0047] The enclosure 1150 comprises a main body 1151 having a back wall 1151a, a first inner compartment 1151b, see Fig. 8, for storing varying lengths of unused cable 1140, to be described below, and a second compartment 1151c, see Fig. 9, for storing a fluid pump 1130, a motor 1132 for driving the pump 1130, batteries 52, a tube 1142 (to be discussed below) and a portion of a tube 1144 (to be discussed below). The enclosure 1150 further comprises a cassette door 11 S2 pivotably coupled to the main body 1151 such as by pins 1152a (only one of which is illustrated in Fig. 10), a printed circuit board 1160a and a face plate 1162. The printed circuit board 1160a is housed between the main body 1151 and the face plate 1162. The face plate 1162 is coupled to the main body 1151 via screws, adhesive, snap-fit elements, or like coupling elements. The pivotable door 1152 comprises a pocket 1152b for receiving a fluid reservoir defined by a removable container 1170 filled with a benefit composition, which composition may comprise any one of the benefit compositions discussed in this document or the documents noted herein. The container 1170 may be formed from a polymeric material, paper, foil, a combination of these materials or a like material. The door 1152 is releasably held in a closed position within the main body 1151 via first and second flex arms 1153, which are coupled to the main body 1151.

[0048] Extending through corresponding openings in the face plate 1162 are an ON-OFF switch 1266c, a "refluff" key or switch 266d, and a dial 266a, which may comprise a potentiometer, which a user rotates to dial in a desired one of a strong, regular or light setting corresponding to a strong, regular or light benefit level to be provided by a benefit composition during the drying process.

[0049] The cable 1140 is coupled to and extends between the enclosures 1120 and 1150. The cable 1140 may run along the inner surface of the fabric enhancement apparatus door, over the top of the door, and down the exterior surface of the door. Any unused length of the cable 1140 can be manually inserted into the first compartment 1151b for storage.

[0050] The cable 1140 carries benefit composition from the fluid pump 1130 in the outer enclosure 1150 to the nozzle 24 in the inner enclosure 1120, see FIG. 14, and electrical signals from the sensors 36, 22, 46 and 48 mounted in the inner enclosure 1120 to a microcontroller 1160 mounted to the printed circuit board 1160a in the outer enclosure 1150.

[0051] A first fitment 1172 is mounted to the main body 1151 via first and second mounting shelves 1155a and 1155b, see FIGS. 10 and 11, and is coupled to the tube or channel 1142 (not shown in FIG. 11), which, in turn, is coupled to the pump 1130. The first and second shelves 1155a and 1155b are positioned on opposing sides of a flange 1172a of the first fitment 1172 and are snap fit, adhesively secured or bolted together so as to encompass the flange 1172a. The assembly comprising the shelves 1155a and 1155b and fitment 1172 is mounted to the main body 1151 such that the shelves 1155a and 1155b are received within a slot 1151d defined in the main body 1151. The fitment 1172 is inserted into a second fitment 1170a forming part of the fluid container 1170 when the door 1152 is pivoted to its closed position and functions to pierce or otherwise penetrate the container 1170 so as to provide a pathway for the benefit composition to travel from the container 1170 to the tube 1142. From the tube 1142, the benefit composition travels to the inlet of the pump 1130, after which the composition is pressurized and carried via the tube or channel 1144, which extends through the cable 1140, to the discharge nozzle 24, where the benefit composition is discharged. In the illustrated embodiment, the pump 1130 and the motor 1132 comprises a single assembly, namely, a piezoelectric pump, one of which is commercially available from Par Technologies, LLC, under the product designation LPD-30S.

[0052] The types of control signals used to control the electric motor 1132 can vary according to the design requirements of the apparatus 1100, and such signals will travel to the motor 1132 via an electrical conductor 1172. In the illustrated embodiment, the electrical signal traveling along conductor 1172 comprises a pulse-width modulated (PWM) signal controlled by the microcontroller 1160. Of course, such a pulse-width modulated signal can also be generated by any appropriate controller or processor, or appropriate discrete logic.

[0053] As noted above, the enclosure 1150 comprises a second compartment 1151c for storing batteries 52, which may comprise two AA batteries.

[0054] A suitable microcontroller 1160 is a microprocessor manufactured by Atmel Corporation and sold under the product designation Atmega48-16A1. Alternatively, the microcontroller 1160 may comprise a microprocessor manufactured by Atmel Corporation and sold under the product designation Atmega48-16AJ. Of course, other microcontrollers, microprocessors, controllers, or processors made by different manufacturers, or discrete digital logic could alternatively be used.

[0055] The microcontroller 1160 includes on-board memory and input and output lines for analog and digital signals. The microcontroller 1160 also has a serial port that can be interfaced to an optional programmer interface using an RS-232 communications link. As noted above, the ON-OFF switch 1266c, and the refluff key 266d are coupled to the

microcontroller 1160, see FIG. 12. As also noted above, the motion sensor 36, door sensor 22, humidity sensor 46 and temperature sensor 48 generate signals to the microcontroller 1160. As further noted above, the microcontroller 60 generates a pulse-width modulated (PWM) signal to the pump motor 1132 via the conductor 1172. An audio indicator 1300 is further coupled to the microcontroller 1160 and functions to indicate that a drying cycle has been completed, clothes have been treated with the benefit composition, an error occurred during the benefit composition dosing cycle or the benefit composition dispensing apparatus is out of fluid. The audio indicator 1300 is mounted to the printed circuit board 1160, see FIG. 10.

[0056] Further coupled to the microcontroller 1160 are first, second, third, fourth and fifth light emitting diodes 1400a-1400e, see FIGS. 9 - 11. The diodes are coupled to the face plate 1162 so as to be visible to an operator when actuated, see FIG. 9. The first diode 1400a is actuated by the microcontroller 1160 when the apparatus 1100 is activated via the ON-OFF switch 1266c. The second diode 1400b is actuated by the microcontroller 1160 when the pump 1130 is pumping benefit composition to the nozzle 24. The third diode 1400c is actuated by the microcontroller 1160 when the refluff key 266d has been activated. The fourth diode 1400d is actuated by the microcontroller 1160 when the spraying operation has been completed for the corresponding fabric enhancement operation cycle. The fifth diode 1400e is actuated by the microcontroller 1160 to generate a warning signal when the container is out of fluid; or the fabric enhancement cycle has been interrupted, which latter event may be detected via the door sensor 22 sensing light or the motion sensor 36 sensing no motion. The microcontroller 1160 may sense that the container 1170 is out of fluid by sensing a change in the current drawn by the pump motor 1132.

[0057] It is further contemplated that a benefit composition dispensing apparatus constructed in accordance with the present invention may comprise a "single-housing" stand-alone unit similar to the one disclosed in patent application U.S. Serial No. 10/762,152, entitled "Volatile Material Delivery Method." In such an embodiment, the apparatus comprises a single housing in which all electrical, electronic and mechanical components are housed. For example, such a single-housing stand-alone unit may comprise the components illustrated in Fig. 5 or the components illustrated in Fig. 12 of this application, which components are all housed within a single housing. The single housing is adapted to be positioned within an apparatus for effecting a fabric enhancement operation.

[0058] In most conventional dryers, whether for home use or commercial use, the heating element will be a binary device, such that it is always ON at full power or is completely OFF at zero power. A more expensive dryer apparatus could use a proportional controller to control an electrical heating element, for example, although the typical result of proportional control would nevertheless exhibit undershoots and overshoots about the setpoint temperature. The principles of the present invention could be used in such a proportional controller.

[0059] Assuming for this example that the heating element is a binary device, then while it is energized, the temperature will tend to continually increase within the drying chamber. Once the heating element is turned off, then the temperature will begin to decrease (although there could be some overshoot). During a single drying cycle, the heating element may be turned on and off several times, in which case a temperature versus time graph would have the appearance of a sawtooth waveform, in which an increasing slope (assuming temperature is the Y-axis and time is the X-axis) would occur when the heating element is turned on, and a decreasing slope when the heating element is turned off. During this sawtooth waveform interval, the overall temperature versus time chart will have the appearance of a plateau, in which the chart exhibits a relatively long increasing slope during the beginning of the drying cycle, then it reaches the plateau region (exhibiting the sawtooth waveform), and at the end of the drying cycle the slope will continually decrease on the "far" side of the plateau.

[0060] If the fabric treatment composition contains a volatile material (such as certain perfumes), then it normally would be better to not release such volatile materials into the drying chamber until the temperature of that drying chamber is below a certain level, which might not occur until after the heating cycle has been completed. One way to detect this is to know when the heating element is actually energized or not, and an integral control device that is mated into the dryer's heating element controller would have knowledge of that status for the heating element, and thus could easily prevent any dispensing or application of the fabric treatment composition until after the heating element had been de-energized at the end of a heating cycle (as opposed to during the plateau region of the heating cycle, when the heating element could turn off, but also could later turn back on).

[0061] Assuming, however, that the heating element control status is not known to the fabric treatment composition dispensing controller, which would be the case if the dispensing apparatus was a self-contained unit that is not in communication with the dryer's controller, then another means of determining the end of the heating cycle would be required. One way of determining the end of a heating cycle (or "heating event") would be to determine the maximum and minimum temperatures that occur during the sawtooth waveform portion of the heating cycle, also referred to above as the "plateau region." If, for example, the internal temperature of the dryer's chamber will rise to a maximum temperature T_{MAX} , and then fall to a momentary "minimum" temperature that is about 10-15°C lower than T_{MAX} , then the controller for the dispensing apparatus could determine when to begin applying the fabric treatment composition, which is after the dryer's internal temperature falls below maximum temperature T_{MAX} , less the 10-15°C "minimum" temperature. These sawtooth minimum and maximum temperature values can be considered a single differential temperature value,

and that type of differential temperature will be referred to herein by a variable " T_{DIFF} ". Some extra tolerance could be built in to the T_{DIFF} value, so that, for example, if most home dryers rise and fall by approximately 1S, C during the plateau region of the drying cycle, then the value for T_{DIFF} could be set to 20° C.

[0062] One optional aspect of the present invention is to provide the fabric treatment composition at two different time intervals during the drying cycle such as described in commonly assigned co-pending application U.S. Serial No. 10/762,152, filed January 21, 2004.

Fabric Treatment Composition

[0063] One aspect of Applicants' invention is a fabric treatment composition that can comprise a polyol-based fabric care material, a dispersing medium, and optionally, one or more adjunct materials.

[0064] In one embodiment, the fabric treatment composition comprises a polyol-based fabric care material, such as sucrose esters; a dispersing medium, such as water, alcohols, diols; and optionally, one or more adjunct materials (such as fabric care agents and adjunct materials) selected from the group consisting of softening agents, perfumes, wetting agents, emulsifiers, emulsion stabilizing agents, viscosity modifiers, pH buffers, antibacterial agents, antioxidants, radical scavengers, chelants, antifoaming agents, and mixtures thereof.

[0065] In another embodiment, the fabric treatment composition comprises from about 0.1 % to about 95% by weight of the treatment composition of a polyol-based fabric care material and from about 1% to about 99% by weight of the treatment composition of a dispersing medium.

[0066] In another embodiment, the fabric treatment composition comprises a polyol-based fabric care material and a dispersing medium having the weight ratio ranging from about 1:1000 to about 90:1, or from about 1:40 to about 1:4.

[0067] In another embodiment, the fabric treatment composition comprises from about 0.1% to about 95% by weight of the treatment composition of a polyol-based fabric care material, from about 1% to about 99% by weight of the treatment composition of a dispersing medium, and the balance of one or more adjunct materials.

[0068] In another aspect of the invention, the treatment composition that is applied to the fabric article comprises a polyol-based fabric care material that has a boiling point of less than or equal to 250°C at 1 atmosphere. Suitable polyol-based fabric care materials and sources for obtaining such materials are described herein below.

[0069] In another aspect of the invention, the treatment composition that is applied to the fabric article comprises a dispersing medium that has a flash point, as measured according to American Society for Testing and Materials (ASTM) method D93-02a, of at least about 65°C, or at least about 75°C, or at least about 95°C, or from about 65°C to about 400°C, or from about 80°C to about 300°C, or from about 90°C to about 232°C.

[0070] In another aspect of the invention, the treatment composition suitable for use in the treatment system of the present invention has a viscosity of from about 1 to about 200 cps (0.001 1 to 0.20 Pa·s), or from about 5 to about 150 cps (0.002 to 0.15 Pa·s), or from about 10 to about 100 cps (0.01 to 0.1 Pa·s), as measured by a Brookfield viscometer model # LVDVII+ at 20°C. The spindle used for these measurements is LV1 with the appropriate rotational speed to measure compositions of different viscosities, e.g., 30 rpm to measure compositions with viscosities between about 500 cps (0.5 Pa·s) and about 1000 cps (1 Pa·s); 60 rpm to measure compositions with viscosities less than about 500 cps (0.5 Pa·s).

[0071] In another aspect of the invention, the treatment composition suitable for use in the treatment system of the present invention has a static surface tension of from about 3 to about 70 dynes/cm, or from about 5 to about 50 dynes/cm, or from about 10 to about 40 dynes/cm, at room temperature, as measured by a Kruss K12 Processor Tensiometer using the Wilhemy test method at room temperature.

Polyol-Based Fabric Care Materials

[0072] "Polyol", as used herein, means any aliphatic or aromatic compound containing at least two free hydroxyl groups. In practicing the processes disclosed herein, the selection of a suitable polyol is simply a matter of choice. For example, suitable polyols may have a backbone chain selected from the following classes: saturated or unsaturated, linear or branched or cyclic (including heterocyclic), aliphatic or aromatic (including mononuclear or polynuclear aromatics). Exemplary polyols include carbohydrates (such as saccharides), glycols (such as glycerin), and derivatives thereof (such as sugar alcohols). Monosaccharides suitable for use herein include, but are not limited to, mannose, galactose, arabinose, xylose, ribose, apiose, rhamnose, psicose, fructose, sorbose, tagitose, ribulose, xylulose, glucose, and erythrulose. Oligosaccharides suitable for use herein include, but are not limited to, maltose, kojibiose, nigerose, cellobiose, lactose, melibiose, gentiobiose, turanose, rutinose, trehalose, sucrose and raffinose. Polysaccharides suitable for use herein include, but are not limited to, amylose, glycogen, cellulose, chitin, inulin, agarose, xylans, mannan and galactans. The sugar alcohols suitable for use herein include, but are not limited to, sorbitol, erythritol, arabitol, xylitol, threitol, pentaerythritol, mannitol and galactitol.


[0073] Also suitable for use herein are other classes of polyol-based materials include sugar ethers, alkoxylated

polyols, such as polyethoxy glycerol, pentaerythritol and other polyols containing amines such as glucosamine.

[0074] These polyol-based materials have the ability to modify a fabric surface to provide fabric care benefits. The derivatization or functionalization of the polyol is designed to be effective for different fabric care applications. Examples of functionalization approaches may include, but not limited to, esterification, etherification, alkylation, amidation, amination and other linking chemistries.

[0075] Typical fabric care benefits may include, but are not limited to: enhancement of fabric feel such as softness, hand and comfort; reduce or resist wrinkling; ease of ironing; enhancement of fabric color; abrasion resistance; fabric shape retention (elasticity, non-shrinkage, non-elongation); static reduction; lint reduction; faster drying; whitening; stain repellency.

[0076] Polyol-based materials suitable for use herein may have the following general formula:



wherein $P(OH)_w$ is a polyol as defined above;

R^1 , R^2 , R^3 and R^4 are moieties independently selected from C1-C22 alkyl or C1-C30 alkoxy, linear or branched, cyclic or acyclic, saturated or unsaturated, substituted or unsubstituted;

L is a linkage which is an atom selected from O; S; N; P;

X is a heteroatom-containing functional group, wherein the heteroatom is independently selected from O, N, S, P, Si and F;


w is an integer selected from 2 to 20;

x, y, z, u and v are integers independently selected from 0 to w;

s is the sum of x, y, z, u and v, and should be equal to or smaller than w; or

$s = x + y + z + u + v \leq w$.

[0077] In one embodiment, the polyol-based fabric care material is a sucrose derivatized by esterification and has the following formula



wherein $P(OH)_8$ is sucrose;

x is an integer selected from 1 to 8, or from 2 to 8, or from 3 to 8, or from 4 to 8; and

R^1 are independently selected from C1-C22 alkyl or C1-C30 alkoxy, linear or branched, cyclic or acyclic, saturated or unsaturated, substituted or unsubstituted.

[0078] In one embodiment, some of the R^1 moieties may comprise linear alkyl or alkoxy moieties comprising varying chain length. For example, R^1 may comprise a mixture of linear alkyl or alkoxy moieties wherein greater than about 20% of the linear chains are C 18, or greater than about 50% of the linear chains are C18, or greater than about 80% of the linear chains are C18.

[0079] In another embodiment, some of the R^1 moieties may comprise a mixture of saturate and unsaturated alkyl or alkoxy moieties; the degree of unsaturation can be measured by "Iodine Value" (hereinafter referred as "IV", as measured by the standard AOCS method). The IV of the polyol-based fabric care material suitable for use herein ranges from about 1 to about 150, or from about 2 to about 100, or from about 5 to about 85. The R^1 moieties may be hydrogenated to reduce the degree of unsaturation.

[0080] In a further embodiment, some of the R^1 moieties may comprise unsaturated alkyl or alkoxy moieties, wherein the unsaturated moieties may comprise a mixture of "cis" and "trans" forms about the unsaturated sites. The "cis" / "trans" ratios may range from about 1:1 to about 50:1, or from about 2:1 to about 40:1, or from about 3:1 to about 30:1, or from about 4:1 to about 20:1.

[0081] The polyol-based fabric care materials are present in the treatment composition of the present invention at levels from about 0.1% to about 95%, or from about 1% to about 50%, or from about 2% to about 30%, by weight of the composition.

Dispersing Medium

[0082] The fabric treatment composition of the present invention also comprises a dispersing medium. Suitable dispersing medium include, but are not limited to, water, water soluble solvents selected from the group consisting of C4 to C10 glycol ethers, C2 to C7 glycols, polyethers, such as glycerin, and mixtures thereof.

[0083] The treatment composition may comprise, based on weight percent of the treatment composition, from about 1 wt% to about 99 wt%, from about 10 wt% to about 95 wt%, or from about 30 wt% to about 90 wt% of the dispersing medium. Typically, water comprises greater than about 40 wt%, or greater than about 60 wt%, or greater than about 80%, or greater than about 90 wt% of the treatment composition; the balance of the dispersing medium comprises water soluble solvents.

[0084] When fabric treatment composition comprises water, the pH of said composition may be in the range of from about 2 to about 10, from about 3 to about 9, from about 4 to about 8, or from about 5.5 to about 7.5. Commonly known pH buffers, such as those disclosed below in the "Adjunct materials", can be used to adjust and/or control the pH of the composition.

Adjunct Materials

[0085] The treatment composition may also comprise optional adjunct materials. Adjunct materials include, but are not limited to, wetting agents, emulsifiers, emulsion stabilizing agents, viscosity modifiers, pH buffers, antibacterial agents, antioxidants, radical scavengers, chelants, antifoaming agents, fabric care agents such as softening agents, perfumes, and mixtures thereof.

[0086] When present, each adjunct material is present, based on total composition weight, at one of the following levels, at least about 0.5 wt %, at least about 2 wt %, from about 4 wt % to about 90 wt %, from about 4 wt % to about 50 wt %, or from about 4 wt % to about 10 wt %.


[0087] The composition of the present invention may optionally comprise one or more fabric care materials. These fabric care material provides one or more fabric benefits including, but not limited to, softness, odor, anti-soil re-deposition, stain or water repellency, color or whiteness enhancement, enhanced absorbency, anti-static, anti-bacterial, or fabric abrasion resistance. Some representative, but nonlimiting examples of fabric care materials, such as softening agents, are described below.

[0088] Exemplary softening agents include, but are not limited to, diester quaternary ammonium compounds (DEQA); polyquaternary ammonium compounds; triethanolamine esterified with carboxylic acid and quaternized (so called "esterquat"); amino esterquats; cationic diesters; betaine esters; betaines; silicone or silicone emulsions comprising amine-silicones, cationic silicones, quat/silicone mixtures; functionalized PDMS; amine oxides; and mixtures thereof.

[0089] Nonlimiting examples of quaternary ammonium type softeners may be selected from the group consisting of: N,N-dimethyl-N,N-di(tallowyloxyethyl) ammonium methylsulfate, N-methyl-N-hydroxyethyl-N,N-di(canoyloxyethyl) ammonium methylsulfate, N,N-ditallow N,N-dimethyl ammonium chloride, N,N-ditallowylethanol N,N-dimethyl ammonium chloride, and mixtures thereof.

[0090] Additional examples of non-silicone fabric softening agents and deposition aids are described in EP 902 009; WO 99/58492; US 4,137,180; WO 97/08284; WO 00/70004; WO 00/70005; WO 01/46361; WO 01/46363; WO 99/64661; WO 99/64660; JP 11-350349; JP11-081134; and JP 11-043863. Additional examples of silicone fabric softening agents and deposition aids are described in US 4,448,810; US 4,800,026; US 4,891,166; US 5,593,611; EP 459 821; EP 530 974; WO 92/01773; WO 97/32917; WO 00/71806; WO 00/71807; WO 01/07546; WO 01/23394; JP 2000-64180; JP 2000-144199; JP 2000-178583; and JP 2000-192075.


[0091] Some of the softening agents are described in details below. Suitable protonatable amines include, protonatable amines having Formula I below:



Formula I

wherein the index m = 0, 1, 2 or 3; the index n=1, 2, 3 or 4, preferably n is 2 or 3, more preferably n is 2, each R is independently selected from C₁-C₂₂ alkyl, C₁-C₂₂ hydroxyalkyl or a benzyl group; each R¹ is independently selected from C₁₁-C₂₂ linear alkyl, C₁₁-C₂₂ branched alkyl, C₁₁-C₂₂ linear alkenyl, or C₁₁-C₂₂ branched alkenyl; and each Q may comprise a carbonyl, carboxyl, or amide moiety.


[0092] Suitable alkylated quaternary ammonium compounds (quats), include mono-alkyl quats, di-alkyl, tri-alkyl quats and tetra-alkyl quats and certain cationic surfactants. Suitable mono-alkyl quats, di-alkyl, tri-alkyl quats and tetra-alkyl quats typically have Formula II below:



Formula II

wherein the index $m = 0, 1, 2, 3$ or 4 ; the index $n = 1, 2, 3$ or 4 , preferably n is 2 or 3 , more preferably n is 2 , each R is independently selected from C_1 - C_{22} alkyl, C_1 - C_{22} hydroxyalkyl, or a benzyl group; each R^1 is independently selected from C_{11} - C_{22} linear alkyl, C_{11} - C_{22} branched alkyl, C_{11} - C_{22} linear alkenyl, or C_{11} - C_{22} branched alkenyl; X^- is a water soluble anionic species such as chloride, bromide or methyl sulfate, and Q may comprise a carbonyl, carboxyl, or amide moiety.


[0093] Suitable cationic surfactants include quaternary ammonium surfactants selected from the group consisting of mono C_6 - C_{16} , preferably C_6 - C_{10} N-alkyl or alkenyl ammonium surfactants, wherein the remaining N positions are substituted by methyl, hydroxyethyl or hydroxypropyl groups. Another preferred cationic surfactant is C_6 - C_{18} alkyl or alkenyl ester of a quaternary ammonium alcohol, such as quaternary choline esters. More preferably, the cationic surfactants have Formula III below:



Formula III

wherein R^1 is a C_8 - C_{18} hydrocarbyl, preferably C_{8-14} alkyl, more preferably C_8 , C_{10} or C_{12} alkyl, and X^- is a water soluble anionic species such as chloride, bromide or methyl sulfate.

[0094] Suitable cationic silicones include silicones functionalized by amine derived compounds and cationic silicone polymers. Suitable silicones functionalized by amine derived compounds include amino silicones having Formula IV below:



wherein m , a , b , and c are independently selected from integers between 0 and 6000 ; $p = 2 + b + c$; R^1 , R^2 , R^3 , R^4 , R^5 , R^6 , R^7 , R^8 , L , K are various side chains attached to the silicone or nitrogen atoms within the molecule. In Formula IV above, R^1 , R^2 , R^3 , R^4 are independently selected from:

- 1.) C_1 - C_{22} linear or branched, substituted or unsubstituted hydrocarbyl moiety; or
- 2.) $-\text{O}-\text{R}^{11}$, $-\text{O}-\text{R}^{12}$, $-\text{O}-\text{R}^{13}$ and $-\text{O}-\text{R}^{14}$, wherein R^{11} , R^{12} , R^{13} , and R^{14} are independently selected from H , or C_1 - C_{22} linear or branched, substituted or unsubstituted hydrocarbyl moiety.

In Formula IV above, L and K are independently selected from C_1 - C_{22} linear or branched, substituted or unsubstituted hydrocarbyl moieties. Preferably L and K are independently selected from C_1 - C_{12} linear or branched, substituted or unsubstituted hydrocarbyl moieties. More preferably L and K are independently selected from C_1 - C_4 linear or branched, substituted or unsubstituted hydrocarbyl moieties. Most preferably L and K are independently selected from methylene, ethylene, propylene, 2-methylpropylene, butylene, octadecylene or 3-(2,2',6,6'-tetramethyl-4-oxy-piperidyl)propyl. In Formula IV above, R^5 , R^6 , R^7 and R^8 are independently selected from H , or C_1 - C_{22} linear or branched, substituted or unsubstituted hydrocarbyl moieties. As used in Formula IV above, " $\text{SiO}_{n/2}$ " means the ratio of oxygen atoms to silicon atoms, i.e., $\text{SiO}_{1/2}$ means one oxygen atom is shared between two silicon atoms.

[0095] Suitable cationic silicone polymers include cationic silicone polymers having Formula V below:




wherein [CAP] is a backbone termination or truncation unit; m is an integer from 1 to 50 and each Z unit has Formula VI below:



wherein for Formula VI:

x is 0 or 1;


W is a siloxane unit having Formula VII below:



Formula VII

wherein for Formula VII each R¹ unit is a C₁-C₂₂ linear or branched, substituted or unsubstituted hydrocarbyl moiety;

wherein for Formula VI above R has Formula VIII below:




wherein for Formula VIII above:

y is 0 or 1;

L is a suitable carbon containing linking unit, suitable linking units include, but are not limited to, alkylene moieties, acrylate moieties, and amide containing moieties;

each B is a unit comprising at least one secondary, tertiary, or quaternary amino moiety;

R² is a coupling unit having the Formula IX below:



Formula IX

wherein for Formula IX above:

each R³ is independently selected from a C₂-C₁₂ linear or branched alkylene moiety, preferably each R³ is independently ethylene, 1,3-propylene, or 1,2-propylene;


each R⁴ is independently selected from hydrogen, or a C₁-C₂₂ linear or branched, substituted or unsubstituted hydrocarbyl moiety, preferably each R⁴ is independently selected from hydrogen, a C₁-C₂₂ linear or branched alkyl moiety;

a C₁-C₂₂ cycloalkyl moiety; a C₁-C₂₂ linear or branched fluoroalkyl moiety; a C₂-C₂₂ linear or branched alkenyl moiety; a C₆-C₂₂ aryl moiety; or a C₇-C₂₂ alkylenearyl moiety; most preferably each R⁴ is hydrogen, or a C₁-C₁₀ linear or branched alkyl moiety; and

z is an integer from 0 to 50;


[0096] Other suitable fabric materials may be polymeric materials such as polyacrylates, polyvinylalcohols, polyethyleneglycols, and derivatives or copolymers of the aforementioned materials.

[0097] Non-limiting examples of suitable silicone copolyols are silicone copolyols having Formula X below:



Formula X

wherein for Formula X above, a + b is an integer from 1 to about 50, preferably a + b is an integer from about 3 to about 30, more preferably a + b is an integer from about 10 to about 25; and at least one R¹ is a poly(ethyleneoxy/propyleneoxy) copolymer group having Formula XI below and the remaining R¹ moieties are independently selected from the group consisting of methyl and the poly(ethyleneoxide/propyleneoxide) copolymer group having Formula XI below:



Formula XI

wherein for Formula XI above, n is 3 or 4, preferably n is 3; c is an integer from 1 to about 100, preferably c is an integer from about 6 to about 100; d is an integer from 1 to about 14, and preferably d is an integer from 1 to about 3; the total of c+d is an integer, of from about 5 to about 150, preferably the total of c+d is an integer from about 9 to about 100; and each R² is independently selected from the group consisting of hydrogen, an alkyl moiety comprising up to 4 carbon atoms, or an acetyl group.

[0098] Nonlimiting examples of emulsifiers include amine oxides, alkyl polyglucosides, cetyltrimethyl ammonium chloride, alkyl, sulfates, alkyl sulfonates, alkyl ethoxylates, alkyl ethoxy sulfates, and mixtures thereof.

[0099] Nonlimiting examples of emulsion stabilizing agent is selected from the group consisting of ethoxylated terephthalate, arabinogalactan, ethoxylated polyethylene imines, and mixtures thereof.

[0100] Nonlimiting examples of viscosity modifiers include salts, such as CaCl₂, MgCl₂, NaCl, guar gum, polysaccharides, and mixtures thereof. Other salts containing and other alkali or alkaline earth metal cations and halide anions, and the like, are also suitable.

[0101] Nonlimiting examples of pH buffers include citric acid, lactic acid, succinic acid, phosphoric acid, sodium bicarbonate, and mixtures thereof.

[0102] The antibacterial agents include didecyl dimethyl ammonium chloride, which is available under the tradename Uniquat® (from Lonza), 1,2-benzisothiazolin-3-one, which is available under the tradename Proxel® (from Zeneca Inc.), dimethylol-5,5-dimethylhydantoin, which is available under the tradename Dantoguard® (from Lonza) and 5-Chloro-2-methyl-4-isothiazolin-3-one / 2-methyl-4-isothiazolin-3-one, which is available under the tradename Kathon® (from Rohm and Haas).

[0103] The antioxidants include, but are not limited to tocopherol acetates, quinines, polyphenols, and mixtures thereof.

[0104] The radical scavengers include, but are not limited to propyl gallate, polyimines, trimethoxy benzoic acid and mixtures thereof.

[0105] The chelants include, but are not limited to diethylene triamine pentaacetic acid, ethylene diamine teraacetic acid, diethylene triamine pentamethylethylene phosphonic acid, citric acid and mixtures thereof.

[0106] The antifoaming agent include, but are not limited to silicone oils, ethoxylated surfactants, Tetronics® (available from BASF), and mixtures thereof.

[0107] Other examples of ethoxylated surfactant include, but are not limited to, carboxylated alcohol ethoxylates; ethoxylated quaternary ammonium surfactants; and ethoxylated alkyl amines. Nonlimiting examples of ethoxylated surfactants are provided:

a) C₉-C₁₈ alkyl ethoxylates, such as Neodol® nonionic surfactants from Shell;

b) C₆-C₁₂ alkyl phenol alkoxyates wherein the alkoxyate units are a mixture of ethyleneoxy and propyleneoxy units;

c) C₁₂-C₁₈ alcohol and C₆-C₁₂ alkyl phenol condensates with ethylene oxide/propylene oxide block polymers such as Pluronic® from BASF;

d) C₁₄-C₂₂ mid-chain branched alcohols, BA, as discussed in US 6,150,322;

e) C₁₄-C₂₂ mid-chain branched alkyl alkoxyates, BAE_x, wherein x 1-30, as discussed in US 6,153,577, US 6,020,303 and US 6,093,856;

f) ether capped poly(oxyalkylated) alcohol surfactants as discussed in US 6,482,994, WO 01/42408, and WO 01/42408; and

g) fatty acid (C₁₂-18) sorbitan esters, Span®, and their ethoxylated (EO₅₋₁₀₀) derivatives, polysorbates; such as Span®20, Tween® 20, Tween® 60, Tween® 80 (commercially available from Uniqema).

[0108] Other examples of ethoxylated surfactant include carboxylated alcohol ethoxylates; ethoxylated quaternary ammonium surfactants; and ethoxylated alkyl amines.

[0109] Suitable nonionic materials include certain surfactants produced by the condensation of alkylene oxide groups with an organic hydrophobic moiety, said moiety can be aliphatic or alkyl aromatic in nature; silicone copolyols; and mixtures thereof. Examples of suitable nonionic surfactants include, but are not limited to alkyl phenol ethoxylates, polyethylene glycol/polypropylene glycol block copolymers, fatty alcohol and fatty acid ethoxylates, long chain tertiary

amine oxides, alkyl polysaccharide, polyethylene glycol (PEG) glyceryl fatty esters and mixtures thereof.

[0110] The perfume materials may be obtained from one or more of the following perfume material suppliers Firmenich (Geneva, Switzerland), Givaudan (Argenteuil, France), IFF (Hazlet, NJ), Quest (Mount Olive, NJ), Bedoukian (Danbury, CT), Sigma Aldrich (St. Louis, MO), Millennium Specialty Chemicals (Olympia Fields, IL), Polarone International (Jersey City, NJ), Fragrance Resources (Keyport, NJ), and Aroma & Flavor Specialties (Danbury, CT).

[0111] Suitable particulate materials include inorganic or organic particulates such as polymeric particles, clays, talcs, zeolites and mixtures thereof. Suitable polymeric particles typically have an average particle size less than about 10 microns, preferably less than 5 microns, more preferably less than about 1 micron. Such particles may comprise polyethylene, polystyrene, polypropylene and mixtures thereof. Suitable clay materials include phyllosilicate clays with a 2:1 layer structure, such as smectite clays for example pyrophyllite, montmorillonite, hectorite, saponite and vermiculite, and micas. Particularly suitable clay materials include smectite clays described in U.S. Pat. No. 4,062,647. Other disclosures of suitable clay materials for fabric softening purposes include European patent specification EP 26528-A1, U.S. Pat. No. 3,959,155 and U.S. Pat. No. 3,936,537.

[0112] Other suitable adjunct materials include, but are not limited to, preservatives such as benzyl alcohol, methyl paraben, propyl paraben and imidazolidinyl urea; suspending agents such as magnesium/aluminum silicate; sequestering agents such as disodium ethylenediamine tetraacetate; and certain synthetic or naturally-derived oils and/or fats, such as certain triglycerides, mineral oils, and mixtures thereof. Specific examples of oils or fats suitable for use herein as adjunct materials include but are not limited to; triglycerides from beef tallow, palm oil, cottonseed oil, canola oil, and soybean oil, all with varying levels of hydrogenation; paraffin oils, and mixtures thereof.

[0113] Additional adjunct materials further include, but are not limited to, wrinkle releasing/prevention agent, anti-static agent, crystal modifier, soil release/prevention agent, colorant, brightener, odor reducer/eliminator, deodorizer/refreshing agent, stain repellent, color enhancer, perfume release and/or delivery agent, shape retention agent, fiber rebuild agent, fiber repair agent, and mixtures thereof.

[0114] Additional examples of suitable adjuncts and levels of use are found in U.S. Pat. 6,653,275.

[0115] Suitable adjunct materials are commercially available from Mazer Chemicals (Gurnee, Illinois, USA), Clariant Corporation, (Glattbrugg, Switzerland), Rhodia Incorporated (Cranbury, New Jersey, USA), Scher Chemicals, Inc. (Clifton, New Jersey, USA), Dow Coming Corporation (Midland, Michigan, USA) and General Electric Company (Fairfield, Connecticut, USA), Witco Corporation (Middlebury, Connecticut, USA), Degussa-Huls (Marl, Germany), BASF (Mount Olive, New Jersey, USA), Sigma-Aldrich (St. Louis, Missouri, USA), 20 Microns Ltd. (Baroda, India), and Twin Rivers Technologies (Quincy, Massachusetts, USA).

Processes of Making Fabric Treatment Compositions

[0116] The fabric treatment compositions of the present invention can be formulated into any suitable form and prepared by any process chosen by the formulator, non-limiting examples of which are described in U.S. Pat. 6,653,275.

EXAMPLES

[0117] The following compositions are examples of fabric treatment compositions useful in the present invention:

Component	A	B	C	D	E	F
Sucrose fatty esters (7 ester groups)	2	2	2	0	3	8
Sucrose fatty esters (4 ester groups)	0	0	0	2	3	0
DTDMAC ^a	6	0	0	6	1	0
DTDMAMS ^b	0	6	0	0	0	0
DEEHMAMS ^c	0	0	6	0	0	0
CTMAC ^d	0	0	0	0	1	2
Lactic acid	0.1	0.1	0.1	0.1	0.1	0
Propel® ^e	0.1	0.1	0.1	0.1	0.1	0.1
Dantoguard® ^f	0.15	0.15	0.15	0.1	0.15	0.15
Phenoxyethanol	0.1	0.1	0.1	0.1	0.1	0.1
Propylene glycol, n-butyl ether	2	2	2	1	1	0

(continued)

Component	A	B	C	D	E	F
1,2 Propanediol	4	4	4	0	2	0
CaCl ₂	0.1	0.1	0	0.05	0.1	0.05
Na ₂ SO ₄	0	0	0.1	0	0	0
TMBA ^g	0.05	0.05	0.05	0.05	0.05	0.1
DTPA ^h	0.05	0.05	0.05	0.05	0.05	0.1
Water	Bal.	Bal.	Bal.	Bal.	Bal.	Bal.
TOTAL	100	100	100	100	100	100
a. DTDMAC = Di-Tallow Di-methyl Ammonium Chloride b. DTDAMS = Di-Tallow Di-methyl Ammonium Methyl Sulfateb. c. DEEHMAMS = Di-(Tallow oxyethyl) Hydroxy Ethyl Methyl Ammonium Methyl Sulfate d. CTMAC = Cetyl Trimethyl Ammonium Chloride e. Proxel® = 1,2-Benzisothiazolin-3-one f. Dantoguard® = Dimethylol-5,5-Dimethylhydantoin g. TMBA = Trimethoxy Benzoic Acid h. DTPA = Sodium Diethylene Triamine Pentaacetate						

[0118] It should be understood that every maximum numerical limitation given throughout this specification includes every lower numerical limitation, as if such lower numerical limitations were expressly written herein. Every minimum numerical limitation given throughout this specification will include every higher numerical limitation, as if such higher numerical limitations were expressly written herein. Every numerical range given throughout this specification will include every narrower numerical range that falls within such broader numerical range, as if such narrower numerical ranges were all expressly written herein.


Claims

1. A fabric article treating system comprising:

- (a) a fabric article drying appliance; and
- (b) a fabric article treating device removably attached to said drying appliance, said treating device comprising a source for containing a fabric treatment composition and means for dispensing said composition in said drying appliance in the form of droplets, having an average particle size of from 0.1 to 1000 microns, said means is in liquid communication with said source, preferably wherein said means for dispensing comprises a nozzle;

wherein said composition comprises a polyol-based fabric care material and a dispersing medium, preferably wherein the dispersing medium is water or a water soluble solvent selected from the group consisting of C4 to C10 glycol ethers, C2 to C7 glycols, polyethers, and mixtures thereof, preferably wherein the dispersing medium is liquid at room temperature, and preferably wherein the dispersing medium has a flash point of at least 65°C.

2. The system of claim 1 wherein the polyol-based fabric care material has the following formula:




wherein $P(OH)_w$ is a polyol,

R^1 , R^2 , R^3 and R^4 are moieties independently selected from C1-C22 alkyl or C1-C30 alkoxy, linear or branched, cyclic or acyclic, saturated or unsaturated, substituted or unsubstituted;
 L is a linkage, which is an atom selected from O; S; N; P;
 X is a heteroatom-containing functional group, wherein the heteroatom is independently selected from O, N, S, P, Si and F;

w is an integer selected from 2 to 20;

x, y, z, u and v are integers independently selected from 0 to w;

s is the sum of $x + y + z + u + v$ and $s \leq w$, preferably wherein the polyol-based fabric care material is a sucrose ester having the formula:



wherein $P(OH)_8$ is sucrose;

x is an integer selected from 1 to 8;

R^1 is independently selected from C1-C22 alkyl or C1-C30 alkoxy, linear or branched, cyclic or acyclic, saturated or unsaturated, substituted or unsubstituted.

3. The system of claims 1 - 2 wherein the composition further comprising one or more adjunct material selected from the group consisting of:

(a) a wetting agent, preferably wherein the wetting agent is selected from the group consisting of silicone copolyols, dioctyl sulfosuccinate, acetylene surfactants and mixtures thereof;

(b) an emulsifier, preferably wherein the emulsifier is selected from the group consisting of amine oxide, alkyl polyglucoside, cetyltrimethyl ammonium chloride, alkyl sulfates, alkyl sulfonates, alkyl ethoxylates, alkyl ethoxy sulfates, and mixtures thereof;

(c) an emulsion stabilizing agent, preferably wherein the emulsion stabilizing agent is selected from the group consisting of ethoxylated terephthalate, arabinogalactan, ethoxylated polyethylene imines, and mixtures thereof;

(d) a viscosity modifier, preferably wherein the viscosity modifier is selected from the group consisting of $CaCl_2$, $MgCl_2$, NaCl, guar gum, polysaccharides, and mixtures thereof;

(e) a pH buffer, preferably wherein the pH buffer is selected from the group consisting of citric acid, lactic acid, succinic acid, phosphoric acid, sodium bicarbonate, and mixtures thereof;

(f) an antibacterial agent, preferably wherein the antibacterial agent is selected from the group consisting of didecyl dimethyl ammonium chloride, 1,2-benzisothiazolin-3-one, 1,3-bis (hydroxymethyl)-5,5-dimethyl hydantoin, 5-chloro-2 methyl-4 isothiazolin-3-one, and mixtures thereof;

(g) an antioxidant, preferably wherein the antioxidant is selected from the group consisting of tocopherol acetates, quinines, polyphenols, and mixtures thereof;

(h) a radical scavenger, preferably wherein the radical scavenger is selected from the group consisting of propyl gallate, trimethoxybenzoic acid (TMBA), polyimines, and mixtures thereof;

(i) a chelant, preferably wherein the chelant is selected from the group consisting of diethylene triamine pentacetic acid, ethylene diamine tetra acetic acid, diethylene triamine pentamethylene phosphonic acid, and mixtures thereof;

(j) an antifoaming agent, preferably wherein the antifoaming agent is selected from the group consisting of silicone oils, ethoxylated surfactants, ethylene diamine polyglycol ether, ethylene oxide/propylene oxide block copolymer, and mixtures thereof;

(k) a softening agent, preferably wherein the softening agent is a dialkyl quaternary ammonium compound selected from the group consisting of N,N-ditallow N,N-dimethyl ammonium chloride and N, N-di-tallowylethanol ester N,N-dimethylammonium chloride, and mixtures thereof;

(l) a perfume; and

(m) mixtures thereof.

4. The system according to any preceding claim wherein the composition comprises from 0.1% to 95% by weight of the composition of the polyol-based fabric care material; from 1% to 99% by weight of the composition of the dispersing medium; and the balance one or more adjunct materials.

5. The system according to any preceding claim wherein the composition further comprises an adjunct selected from the group consisting of wrinkle releasing/prevention agent, anti-static agent, crystal modifier, soil release/prevention agent, colorant, brightener, odor reducer/eliminator, deodorizer/refreshing agent, stain repellent, color enhancer, perfume release and/or delivery agent, shape retention agent, fiber rebuild agent, fiber repair agent, and mixtures thereof.

6. The system according to any preceding claim wherein said composition has a viscosity of 1 to 200 cps at room

temperature.


7. The system according to any preceding claim wherein said composition has a static surface tension of 3 to 70 dynes/cm at room temperature.

8. A method for applying a fabric treatment composition to a fabric article in a fabric article drying appliance, said method comprising the steps of:

- (a) providing a drying appliance comprising a treatment chamber and a fabric article treating device;
- (b) providing a fabric treatment composition comprising a polyol-based fabric care material and a dispersing medium, preferably wherein the dispersing medium is liquid at room temperature and has a flash point of greater than 65°C;
- (c) placing a fabric article in said treatment chamber,
- (d) dispensing said composition into said treatment chamber such that said dispensed composition contacts said fabric article, wherein said composition is dispensed in the form of droplets having an average particle size in the range of from 0.1 to 1000 microns;

wherein the fabric treating device is removably attached to said drying appliance and is configured to dispense said composition into said chamber.

9. The method according to claim 8 wherein the dispersing medium is water or a water soluble solvent selected from the group consisting of C4 to C7 glycol ethers, C2 to C7 glycols, polyethers, and mixtures thereof; and the polyol-based fabric care material has the following formula:



wherein $P(OH)_w$ is a polyol;

- R^1 , R^2 , R^3 and R^4 are moieties independently selected from C1-C22 alkyl or C1-C30 alkoxy, linear or branched, cyclic or acyclic, saturated or unsaturated, substituted or unsubstituted;
- L is a linkage selected from O; S; N; P;
- X is a heteroatom-containing functional group, wherein the heteroatom is independently selected from O, N, S, P, Si and F;
- w is an integer selected from 2 to 20;
- x, y, z, u and v are integers independently selected from 0 to w;
- s is the sum of x + y + z + u + v and $s \leq w$.

10. The method according to claims 8 or 9 wherein said composition has a viscosity of 1 to 200 cps at room temperature.


Patentansprüche

1. Textilartikelbehandlungssystem, das Folgendes umfasst:

- (a) eine Textilartikel Trocknungsvorrichtung; und
- (b) eine Textilartikelbehandlungsvorrichtung, die an der Trocknungsvorrichtung abnehmbar befestigt ist, wobei die Behandlungsvorrichtung eine Quelle zum Enthalten einer Textilbehandlungszusammensetzung und ein Mittel für die Abgabe der Zusammensetzung in die Trocknungsvorrichtung in Form von Tröpfchen umfasst, wobei diese eine durchschnittliche Teilchengröße von 0,1 bis 1000 Mikrometern aufweisen, wobei das Mittel in Flüssigkeitsaustausch mit der Quelle steht, wobei das Mittel für die Abgabe vorzugsweise eine Düse umfasst;

wobei die Zusammensetzung ein Textilpflegematerial auf Polyolbasis und ein Dispergiermittel umfasst, wobei das Dispergiermittel vorzugsweise Wasser oder ein wasserlösliches Lösungsmittel, ausgewählt aus der Gruppe, bestehend aus C4- bis C10-Glykolethern, C2- bis C7-Glycolen, Polyethern und Mischungen davon ist, wobei das Dispergiermittel vorzugsweise bei Raumtemperatur flüssig ist und wobei das Dispergiermittel vorzugsweise einen Flammpunkt von mindestens 65 °C aufweist.

2. System nach Anspruch 1, wobei das Textilpflegematerial auf Polyolbasis folgende Formel aufweist:



wobei $P(OH)_w$ ein Polyol ist,

R^1 , R^2 , R^3 und R^4 Einheiten sind, die unabhängig voneinander ausgewählt sind aus C1-C22-Alkyl oder C1-C30-Alkoxy, linear oder verzweigt, zyklisch oder azyklisch, gesättigt oder ungesättigt, substituiert oder nicht-substituiert;


L eine Bindung ist, die ein Atom, ausgewählt aus O; S; N; P, ist;

X eine heteroatomhaltige funktionelle Gruppe ist, wobei das Heteroatom unabhängig aus O, N, S, P, Si und F ausgewählt ist;

w eine ganze Zahl ist, die aus 2 bis 20 ausgewählt ist;

x, y, z, u und v ganze Zahlen sind, die unabhängig voneinander aus 0 bis w ausgewählt sind;

s die Summe von $x + y + z + u + v$ und $s \leq w$ ist, wobei das Textilepflegematerial auf Polyolbasis vorzugsweise ein Saccharoseester mit folgender Formel ist:



wobei $P(OH)_8$ Saccharose ist;

x eine ganze Zahl ist, die aus 1 bis 8 ausgewählt ist;

R^1 unabhängig ausgewählt ist aus C1-C22-Alkyl oder C1-C30-Alkoxy, linear oder verzweigt, zyklisch oder azyklisch, gesättigt oder ungesättigt, substituiert oder nichtsubstituiert.

3. System nach Ansprüchen 1 - 2, wobei die Zusammensetzung ferner ein oder mehrere Zusatzmaterialien umfasst, ausgewählt aus der Gruppe, bestehend aus:

(a) einem Benetzungsmittel, wobei das Benetzungsmittel vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Silikoncopolyolen, Dioctylsulfosuccinat, Acetylentensiden und Mischungen davon;

(b) einem Emulgator, wobei der Emulgator vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Aminoxid, Alkylpolyglucosid, Cetyltrimethylammoniumchlorid, Alkylsulfaten, Alkylsulfonaten, Alkylethoxylaten, Alkylethoxysulfaten und Mischungen davon;

(c) einem Emulsionstabilisierungsmittel, wobei das Emulsionstabilisierungsmittel vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus ethoxyliertem Terephthalat, Arabinogalactan, ethoxylierten Polyethylenimininen und Mischungen davon;

(d) einem Viskositätsregler, wobei der Viskositätsregler vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus CaCl₂, MgCl₂, NaCl, Guargummi, Polysacchariden und Mischungen davon;

(e) einem pH-Puffer, wobei der pH-Puffer vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Citronensäure, Milchsäure, Bernsteinsäure, Phosphorsäure, Natriumbicarbonat und Mischungen davon;

(f) einem antibakteriellen Mittel, wobei das antibakterielle Mittel vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Didecyldimethylammoniumchlorid, 1,2-Benzisothiazolin-3-on, 1,3-Bis (hydroxymethyl)-5,5-dimethylhydantoin, 5-Chlor-2-methyl-4-isothiazolin-3-on und Mischungen davon;

(g) einem Antioxidationsmittel, wobei das Antioxidationsmittel vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Tocopherolacetaten, Chininen, Polyphenolen und Mischungen davon;

(h) einem Radikalfänger, wobei der Radikalfänger vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Propylgallant, Trimethoxybenzoesäure (TMBA), Polyimininen und Mischungen davon;

(i) einem Komplexbildner, wobei der Komplexbildner ausgewählt ist aus der Gruppe, bestehend aus Diethylen-triaminpentaessigsäure, Ethylendiamintetraessigsäure, Diethylentriaminpentamethylenphosphonsäure und Mischungen davon;

(j) einem Schaumverhinderer, wobei der Schaumverhinderer vorzugsweise ausgewählt ist aus der Gruppe, bestehend aus Silikonölen, ethoxylierten Tensiden, Ethylendiaminpolyglycoether, Ethylenoxid-/Propylenoxid-Blockcopolymer und Mischungen davon;

(k) einem Weichmacher, wobei der Weichmacher vorzugsweise eine quartäre Dialkylammoniumverbindung ist, ausgewählt aus der Gruppe, bestehend aus N,N-Dialg-N,N-dimethylammoniumchlorid und N,N-Dialgethanolester-N,N-dimethylammoniumchlorid und Mischungen davon;

(l) einem Duftstoff; und

(m) Mischungen davon.

4. System nach einem der vorstehenden Ansprüche, wobei die Zusammensetzung von 0,1 Gew.-% bis 95 Gew.-% der Zusammensetzung das Textilpflegematerial auf Polyolbasis; von 1 Gew.-% bis 99 Gew.-% der Zusammensetzung das Dispergiermittel; und zu übrigen Teilen ein oder mehrere Zusatzmaterialien umfasst.

5. System nach einem der vorstehenden Ansprüche, wobei die Zusammensetzung ferner einen Zusatzstoff, ausgewählt aus der Gruppe, bestehend aus Faltenlöse-/verhinderungsmittel, antistatischem Mittel, Kristallmodifikator, Schmutzabweise-/verhinderungsmittel, Farbstoff, Aufheller, Geruch verringerndem/beseitigendem Mittel, deodorisierendem/auffrischendem Mittel, Fleckenabweisemittel, Farbverstärker, Duftstoff freisetzendem und/oder abgebendem Mittel, Mittel zur Formbewahrung, Fasererneuerungsmittel, Faserreparaturmittel und Mischungen davon, umfasst.

6. System nach einem der vorstehenden Ansprüche, wobei die Zusammensetzung eine Viskosität von 0,001 Pa.s (1 cP) bis 0,2 Pa.s (200 cP) bei Raumtemperatur aufweist.


7. System nach einem der vorstehenden Ansprüche, wobei die Zusammensetzung eine statische Oberflächenspannung von 3 bis 70 Dyn/cm bei Raumtemperatur aufweist.

8. Verfahren für das Auftragen einer Textilbehandlungszusammensetzung auf einen Textilartikel in einer Textilartikel-trocknungsvorrichtung, wobei das Verfahren folgende Schritte umfasst:

- (a) Bereitstellen einer Trocknungsvorrichtung, die eine Behandlungskammer und eine Textilartikelbehandlungs-vorrichtung umfasst;
- (b) Bereitstellen einer Textilbehandlungszusammensetzung, die ein Textilpflegematerial auf Polyolbasis und ein Dispergiermittel umfasst, wobei das Dispergiermittel bei Raumtemperatur vorzugsweise flüssig ist und einen Flammpunkt von über 65 °C aufweist;
- (c) Geben eines Textilartikels in die Behandlungskammer;
- (d) Abgabe der Zusammensetzung in die Behandlungskammer, so dass die abgegebene Zusammensetzung mit dem Textilartikel in Kontakt kommt, wobei die Zusammensetzung in Form von Tröpfchen mit einer durchschnittlichen Teilchengröße im Bereich von 0,1 bis 1000 Mikrometern abgegeben wird;

wobei die Textilbehandlungsvorrichtung an der Trocknungsvorrichtung abnehmbar befestigt ist und so ausgelegt ist, dass die Zusammensetzung in die Kammer abgegeben wird.

9. Verfahren nach Anspruch 8, wobei das Dispergiermittel Wasser oder ein wasserlösliches Lösungsmittel, ausgewählt aus der Gruppe, bestehend aus C4-bis C7-Glycolethern, C2- bis C7-Glycolen, Polyethern und Mischungen davon, ist; und das Textilpflegematerial auf Polyolbasis folgende Formel aufweist:



wobei $P(OH)_w$ ein Polyol ist;

R^1 , R^2 , R^3 und R^4 Einheiten sind, die unabhängig voneinander ausgewählt sind aus C1-C22-Alkyl oder C1-C30-Alkoxy, linear oder verzweigt, zyklisch oder azyklisch, gesättigt oder ungesättigt, substituiert oder nicht-substituiert;

L eine Bindung ist, die aus O; S; N; P ausgewählt ist;

X eine heteroatomhaltige funktionelle Gruppe ist, wobei das Heteroatom unabhängig aus O, N, S, P, Si und F ausgewählt ist;

w eine ganze Zahl ist, die aus 2 bis 20 ausgewählt ist;

x, y, z, u und v ganze Zahlen sind, die unabhängig voneinander aus 0 bis w ausgewählt sind;

s die Summe von $x + y + z + u + v$ und $s \leq w$ ist.

10. Verfahren nach einem der Ansprüche 8 oder 9, wobei die Zusammensetzung eine Viskosität von 0,001 Pa.s (1 cP) bis 0,2 Pa.s (200 cP) bei Raumtemperatur aufweist.

Revendications


1. Système de traitement d'article textile comprenant :

(a) un appareillage de séchage d'article textile ; et

(b) un dispositif de traitement d'article textile fixé de façon amovible audit appareillage de séchage, ledit dispositif de traitement comprenant une source pour contenir une composition de traitement des tissus et un moyen pour distribuer ladite composition dans ledit appareillage de séchage sous la forme de gouttelettes, ayant une taille moyenne des particules allant de 0,1 à 1000 microns, ledit moyen est en communication du point de vue des liquides avec ladite source, de préférence dans lequel ledit moyen pour distribuer comprend une buse ;

dans lequel ladite composition comprend un matériau pour le soin des tissus à base de polyol et un milieu de dispersion, de préférence dans lequel le milieu de dispersion est de l'eau ou un solvant hydrosoluble choisi dans le groupe constitué d'éthers de glycol en C4 à C10, glycols en C2 à C7, polyéthers, et leurs mélanges, de préférence dans lequel le milieu de dispersion est liquide à la température ambiante, et de préférence dans lequel le milieu de dispersion a un point d'éclair d'au moins 65 °C.

2. Système selon la revendication 1, dans lequel le matériau pour le soin des tissus à base de polyol est de formule suivante :



dans laquelle $P(OH)_w$ est un polyol ;

R^1 , R^2 , R^3 et R^4 sont des fragments indépendamment choisis parmi un alkyle en C1 à C22 ou un alcoxy en C1 à C30, linéaire ou ramifié, cyclique ou acyclique, saturé ou insaturé, substitué ou non substitué ;


L est une liaison, qui est un atome choisi parmi O ; S ; N ; P ;

X est un groupe fonctionnel contenant un hétéroatome, dans lequel l'hétéroatome est indépendamment choisi parmi O, N, S, P, Si et F ;

w est un nombre entier choisi parmi 2 à 20 ;

x, y, z, u et v sont des nombres entiers indépendamment choisis parmi 0 à w ;

s est la somme de $x + y + z + u + v$ et $s \leq w$, de préférence dans lequel le matériau pour le soin des tissus à base de polyol est un saccharose ester de formule :



dans laquelle $P(OH)_8$ est du saccharose ;

x est un nombre entier choisi parmi 1 à 8 ;

R^1 est indépendamment choisi parmi un alkyle en C1 à C22 ou un alcoxy en C1 à C30, linéaire ou ramifié, cyclique ou acyclique, saturé ou insaturé, substitué ou non substitué.

3. Système selon les revendications 1 à 2, dans lequel la composition comprend en outre un ou plusieurs matériaux additifs choisis dans le groupe constitué de :

(a) un agent mouillant, de préférence dans lequel l'agent mouillant est choisi dans le groupe constitué de copolyols de silicone, sulfosuccinate de dioctyle, des agents tensioactifs d'acétylène et leurs mélanges ;

(b) un émulsifiant, de préférence dans lequel l'émulsifiant est choisi dans le groupe constitué d'oxyde d'amine, alkyl polyglucoside, chlorure de cétyltriméthyl ammonium, alkyl sulfates, alkyl sulfonates, éthoxylates d'alkyle, éthoxy-sulfates d'alkyle, et leurs mélanges ;

(c) un agent stabilisant d'émulsion, de préférence dans lequel l'agent stabilisant d'émulsion est choisi dans le groupe constitué de téréphtalate éthoxylé, arabinogalactane, polyéthylène imines éthoxylées, et leurs mélanges ;

(d) un agent modifiant la viscosité, de préférence dans lequel l'agent modifiant la viscosité est choisi dans le groupe constitué de $CaCl_2$, $MgCl_2$, NaCl, gomme guar, polysaccharides, et leurs mélanges ;

(e) un tampon de pH, de préférence dans lequel le tampon de pH est choisi dans le groupe constitué d'acide citrique, acide lactique, acide succinique, acide phosphorique, bicarbonate de sodium, et leurs mélanges ;

(f) un agent antibactérien, de préférence dans lequel l'agent antibactérien est choisi dans le groupe constitué de chlorure de didécyl diméthyl ammonium, 1,2-benzisothiazolin-3-one, 1,3-bis (hydroxyméthyl)-5,5-diméthyl hydantoïne, 5-chloro-2 méthyl-4 isothiazolin-3-one, et leurs mélanges ;

(g) un antioxydant, de préférence dans lequel l'antioxydant est choisi dans le groupe constitué d'acétates de

tocophérol, quinine, polyphénols, et leurs mélanges ;

(h) un agent anti-radicaux libres, de préférence dans lequel l'agent anti-radicaux libres est choisi dans le groupe constitué de gallate de propyle, acide triméthoxybenzoïque (TMBA), poly-imines, et leurs mélanges ;

(i) un agent chélatant, de préférence dans lequel l'agent chélatant est choisi dans le groupe constitué d'acide diéthylène triamine pentacétique, d'acide éthylène diamine tétra-acétique, d'acide diéthylène triamine penta-méthylène phosphonique, et leurs mélanges ;

(j) un agent antimousse, de préférence dans lequel l'agent antimousse est choisi dans le groupe constitué d'huiles de silicone, agents tensioactifs éthoxylés, éthylène diamine polyglycol éther, copolymère séquencé oxyde d'éthylène/oxyde de propylène, et leurs mélanges ;

(k) un agent adoucissant, de préférence dans lequel l'agent adoucissant est un composé de dialkyl ammonium quaternaire choisi dans le groupe constitué de chlorure de N,N-disulf N,N-diméthyl ammonium et chlorure de N, N-di-sulf-oyl-éthanolester N,N-diméthylammonium, et leurs mélanges ;

(l) un parfum ; et

(m) leurs mélanges.

4. Système selon l'une quelconque des revendications précédentes, dans lequel la composition comprend de 0,1 % à 95 % en poids de la composition du matériau pour le soin des tissus à base de polyol ; de 1 % à 99 % en poids de la composition du milieu de dispersion ; et le complément un ou plusieurs matériaux additifs.

5. Système selon l'une quelconque des revendications précédentes, dans lequel la composition comprend en outre un additif choisi dans le groupe constitué d'agent de libération/prévention des plis, agent antistatique, agent modifiant de cristal, agent antissalissure/prévention des salissures, colorant, azurant, réducteur/supprimeur d'odeur, agent désodorisant/rafraîchissant, repellant des taches, amplificateur de couleur, agent de libération et/ou d'apport de parfum, agent de rétention de forme, agent de reconstruction des fibres, agent de réparation des fibres, et leurs mélanges.

6. Système selon l'une quelconque des revendications précédentes, dans lequel ladite composition a une viscosité de 0,001 Pa.s (1 cP) à 0,2 Pa.s (200 cP) à la température ambiante.

7. Système selon l'une quelconque des revendications précédentes, dans lequel ladite composition a une tension superficielle statique de 3 à 70 dynes/cm à la température ambiante.

8. Procédé pour appliquer une composition de traitement des tissus à un article textile dans un appareillage de séchage d'article textile, ledit procédé comprenant les étapes consistant à :

(a) fournir un appareillage de séchage comprenant une chambre de traitement et un dispositif de traitement d'article textile ;


(b) fournir une composition de traitement des tissus comprenant un matériau pour le soin des tissus à base de polyol et un milieu de dispersion, de préférence dans lequel le milieu de dispersion est liquide à la température ambiante et a un point d'éclair supérieur à 65 °C ;

(c) placer un article textile dans ladite chambre de traitement ;

(d) distribuer ladite composition dans ladite chambre de traitement de telle sorte que ladite composition distribuée vient en contact avec ledit article textile, dans lequel ladite composition est distribuée sous la forme de gouttelettes ayant une taille moyenne des particules dans l'intervalle allant de 0,1 à 1000 microns ;

dans lequel le dispositif de traitement de tissu est fixé de façon amovible audit appareillage de séchage et est configuré pour distribuer ladite composition dans ladite chambre.

9. Procédé selon la revendication 8, dans lequel le milieu de dispersion est de l'eau ou un solvant hydrosoluble choisi dans le groupe constitué d'éthers de glycol en C4 à C7, de glycols en C2 à C7, de polyéthers, et leurs mélanges ; et le matériau pour le soin des tissus à base de polyol est de formule suivante :



dans laquelle $P(OH)_w$ est un polyol ;

R^1 , R^2 , R^3 et R^4 sont des fragments indépendamment choisis parmi un alkyle en C1 à C22 ou un alcoxy en C1 à C30, linéaire ou ramifié, cyclique ou acyclique, saturé ou insaturé, substitué ou non substitué ;

EP 1 678 366 B1

L est une liaison choisie parmi O ; S ; N ; P ;

X est un groupe fonctionnel contenant un hétéroatome, dans lequel l'hétéroatome est indépendamment choisi parmi O, N, S, P, Si et F ;

w est un nombre entier choisi parmi 2 à 20 ;

x, y, z, u et v sont des nombres entiers indépendamment choisis parmi 0 à w ;

s est la somme de $x + y + z + u + v$ et $s \leq w$.

10. Procédé selon la revendication 8 ou 9, dans lequel ladite composition a une viscosité de 0,001 Pa.s (1 cP) à 0,2 Pa.s (200 cP) à la température ambiante




Fig. 1




Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9





Fig. 10






Fig. 12

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 4207683 A [0002] [0019]
- US 20030200674 A1 [0002] [0019]
- US 20030213145 A1 [0002] [0019]
- WO 03087286 A1 [0002]
- US 20040025368 A1 [0018] [0019]
- US 697685 A [0019]
- US 10697736 A [0019]
- US 20040025368 A [0024]
- US 10762152 B [0057] [0062]
- EP 902009 A [0090]
- WO 9958492 A [0090]
- US 4137180 A [0090]
- WO 9708284 A [0090]
- WO 0070004 A [0090]
- WO 0070005 A [0090]
- WO 0146361 A [0090]
- WO 0146363 A [0090]
- WO 9964661 A [0090]
- WO 9964660 A [0090]
- JP 11350349 A [0090]
- JP 11081134 A [0090]
- JP 11043863 A [0090]
- US 4448810 A [0090]
- US 4800026 A [0090]
- US 4891166 A [0090]
- US 5593611 A [0090]
- EP 459821 A [0090]
- EP 530974 A [0090]
- WO 9201773 A [0090]
- WO 9732917 A [0090]
- WO 0071806 A [0090]
- WO 0071807 A [0090]
- WO 0107546 A [0090]
- WO 0123394 A [0090]
- JP 2000064180 A [0090]
- JP 2000144199 A [0090]
- JP 2000178583 A [0090]
- JP 2000192075 A [0090]
- US 6150322 A [0107]
- US 6153577 A [0107]
- US 6020303 A [0107]
- US 6093856 A [0107]
- US 6482994 B [0107]
- WO 0142408 A [0107] [0107]
- US 4062647 A [0111]
- EP 26528 A1 [0111]
- US 3959155 A [0111]
- US 3936537 A [0111]
- US 6653275 B [0114] [0116]