

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 February 2007 (08.02.2007)

PCT

(10) International Publication Number
WO 2007/016407 A1

(51) International Patent Classification:

G01B 11/24 (2006.01) **A01B 69/00** (2006.01)

(21) International Application Number:

PCT/US2006/029558

(22) International Filing Date: 31 July 2006 (31.07.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/704,412 1 August 2005 (01.08.2005) US

(71) Applicant (for all designated States except US): **PIO-NEER HI-BRED INTERNATIONAL, INC.** [US/US]; 7100 N.W. 62ND AVENUE, P.O. Box 1014, Johnston, IA 50131-1014 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SPICER, Mark, W.** [US/US]; 718 Nw Stratford Court, Ankeny, IA 50023 (US). **RUCKELSHAUSEN, Arno** [DE/DE]; Schelverstr. 27, 49080 Osnabrück (DE). **DZINAJ, Timur, M.** [DE/DE]; Clemensstr. 12, 49090 Osnabrück (DE). **LINZ, Andreas** [DE/DE]; Johann-sebastian-bach-str. 4, 49076 Osnabrück (DE).

(74) Agents: **PICHE, Jason, O.** et al.; ALSTON & BIRD LLP, Bank of America Plaza, 101 South Tryon Street, Suite 4000, Charlotte, NC 28280-4000 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: SENSOR SYSTEM, METHOD, AND COMPUTER PROGRAM PRODUCT FOR PLANT PHENOTYPE MEASUREMENT IN AGRICULTURAL ENVIRONMENTS



(57) Abstract: A sensor system, method, and computer program product for determining physical characteristics of individual plants within a row located in an agricultural environment is provided. Embodiments of the present invention include, but are not limited to, a sensor assembly including a plurality of emitters and a corresponding plurality of receivers disposed substantially opposite one another such that the receivers may receive a plurality of signals emitted by said emitters to generate a binary profile image of each plant within a row of plants positioned along a row axis. Embodiments of the present invention also include supplementary sensors for determining other plant characteristics including leaf pattern and plant location along the row axis. The method and computer program product embodiments of the present invention may also differentiate selected plants of interest from invasive or weed species using the outputs of the sensor device of the present invention.

WO 2007/016407 A1



-
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

SENSOR SYSTEM, METHOD, AND COMPUTER PROGRAM PRODUCT
FOR PLANT PHENOTYPE MEASUREMENT IN AGRICULTURAL
ENVIRONMENTS

FIELD OF THE INVENTION

The present invention relates generally to sensor devices adapted to detect and measure plant characteristics and dimensions in an agricultural environment. More particularly the sensor device, method, and computer program product of the present invention allows for the real-time measurement of plant characteristics including, but not limited to: plant profile, leaf size, leaf configuration, height, stem configuration, spectral signature, and other characteristics that may be used to identify a plant of interest and/or indicate the viability or physiological state of a particular plant of interest. Embodiments of the present invention may also allow for the accurate identification of selected plant varieties of interest in an agricultural environment such that weeds, soil, dust, and/or invasive plant species may be accurately differentiated from the selected plants of interest.

BACKGROUND OF THE INVENTION

Farmers and agricultural researchers have, for many years, developed various tools, devices, and methods for identifying and controlling native weeds, invasive plant species, and/or other plants that may interfere or hinder the growth or harvest of a crop (such as maize) in an agricultural plot. There has also been interest in accurately measuring and tracking the expression of genetics as physical traits (or phenotypes) of plants that have been bred for uniformity, yield, increased biomass, and other quantifiable physical traits. The accurate measurement and/or identification of plant phenotypes in an agricultural environment is crucial for providing the foundation for new agricultural methods such as, for example, automated weed control, the tracking of genotype expression *in vivo* and other automated agricultural techniques.

Furthermore, some research has been directed towards controlling weeds using automated physical means without the use of chemicals and/or herbicidal agents. However, such automated physical means for controlling weeds require the accurate identification and classification of crop plants and of weed plants that should be

targeted by the weed control activity. Some sensor systems have been proposed for imaging useful plant species using spectral cameras either alone or in combination with geometric signatures obtained from alternate camera devices. Other proposed systems utilize high-resolution 3-D cameras to image plants in the field. However, these solutions are not practical due to the lack of market availability for high-resolution and reliable camera systems that may stand up to the rigors of use in a working agricultural environment. Industrial light curtains have been developed and used extensively in industrial environments, providing arrays of emitters for emitting light beams towards corresponding receiver elements that surround industrial equipment that may be hazardous while running. In use, these systems automatically shut off power to the industrial equipment for safety when the light beams are broken by an intervening object. While such light curtains are durable and might be suited for collecting lateral plant profile and height information, they have not yet been successfully utilized in conjunction with a computer device for generating imagery and complex plant characteristic data sets for identifying and classifying crop plants such as maize. Furthermore, light curtain technology has not been successfully integrated with spectral imaging technology to form a durable and reliable sensor assembly with a computer device capable of providing a plant characteristic data set having sufficient detail and accuracy for identifying plants of interest and differentiating such plants of interest from native weeds or other plants. Furthermore, plant characteristic data from redundant data sources (such as multiple light curtains and supplementary cameras, distance sensors, location sensors) has not been collected in a working agricultural environment and integrated to allow for the automated detection, identification, and cataloging of plants of interest, such as maize plants being cultivated in a field.

Thus in order to facilitate an economical, reliable, and accurate system for automating the collection of phenotypic plant data for research purposes and/or for crop vs. weed differentiation, there is a need in the art for a sensor system, method, and computer program product that allows for the collection of plant characteristic (phenotypic) data from a number of sensors and/or measurement devices and a system that effectively integrates such data into a comprehensive plant characteristic data set. Furthermore, there exists a need for a sensor assembly that is reliably operable in a variety of agricultural environments that may be obscured by dust, moisture, bright

sunlight, subject to extreme temperatures. Furthermore, there exists a need in the art for a sensor assembly with a high-throughput capability that is capable of scanning a large number of plants as the assembly is advanced along a row of plants being cultivated in an agricultural environment. There further exists a need for a system and/or method for scanning plants that may be cultivated in a greenhouse and/or laboratory operation in pots, trays, or other containers that may be conveyed to and from scanning sensors fixed in a static position.

SUMMARY OF THE INVENTION

The embodiments of the present invention satisfy the needs listed above and provide other advantages as described below. Embodiments of the present invention may include a system for measuring physical characteristics of plants within a row or planted in some linear fashion, wherein each plant in the row defines a stem axis extending substantially vertically from the row axis in an agricultural environment. In some embodiments, the system comprises a sensor assembly including a plurality of emitters and a plurality of receivers disposed substantially opposite and parallel to the emitters for receiving a plurality of signals such that the receivers and corresponding emitters may be positioned on opposite sides of the row, and a computer device in communication with said sensor assembly for controlling the emission and/or reception of signals by the emitters and/or receivers, respectively. Furthermore, according to some embodiments, the emitters emit signals such that a portion of a plant in the row obscures at least a portion of a plurality of signals and the computer device receives a plant profile data set generated by the receivers. The emitters may, in some embodiments, passively emit signals or, in other embodiments, be controlled by the computer device to emit the signals. The plant profile data set may comprise a plurality of positive data points corresponding to an uninterrupted, received signal and a plurality of negative data points corresponding to the portion of the plurality of signals obscured and/or broken by the plant. Furthermore, according to some system embodiments, the computer device generates a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from the receivers such that the plant characteristic data set may be used to: measure the physical characteristics of the plants within the row; count a number of a plurality of

plants within the row; and/or determine a density and/or frequency of a particular plant of interest within a given cultivation area or row.

According to some embodiments, the sensor assembly of the present invention further comprises at least one of: an industrial light curtain, a plurality of photodiodes
5 substantially aligned with a corresponding plurality of optical sensors, and combinations thereof. Furthermore, the system of the present invention may further comprise a wheeled carriage or other carrier device for advancing the sensor assembly along the row, such that the computer device may further control the emitters to repeatedly emit the signals at a selected rate to generate a two-dimensional profile of
10 the plant by compiling plant profile data generated by said receivers at a plurality of longitudinal points along the row axis. In addition, various system embodiments of the present invention may comprise other components for generating physical plant data that may be added to the plant characteristic data set by the computer device. For example, system embodiments of the present invention may further comprise
15 components including, but not limited to: distance sensors for locating plant stem location and plant height; multi-spectral sensors or imaging systems such as a multi-spectral device, spectrograph, and/or spectrometer for capturing multi-spectral plant images; a shaft encoder operably engaged with a carriage wheel axle for transmitting plant position and sensor position data within a row location to the computer device;
20 and a global positioning system device for determining a geographical position of the plant.

According to some embodiments of the system of the present invention, the system further comprises a memory device in communication with the computer device for storing the plant characteristic data set of a known plant of interest. Thus,
25 in some system embodiments, the computer device may further identify and count the plant by comparing the generated plant characteristic data set with the stored plant characteristic data set of the known plant of interest.

The embodiments of the present invention also provide a method and computer program product for measuring physical characteristics of and/or counting
30 each plant positioned within a row, defining, in some cases, a row axis wherein each plant in the row defining a stem axis extending substantially vertically from the row axis in an agricultural environment. According to some embodiments, the method first comprises providing a sensor assembly including a plurality of emitters and a

corresponding plurality of receivers disposed substantially opposite the emitters for receiving a plurality of signals emitted thereby and a computer device in communication with said profile sensor assembly. The method and/or computer program product embodiments of the present invention may also comprise positioning the sensor assembly relative to the row of plants such that the receivers and emitters are positioned on opposite sides of the row, emitting the plurality of signals from such that a portion of a plant in the row obscures at least a portion of the signals, and receiving a portion of the plurality of signals at the receivers such that the receivers generate a plant profile data set comprising a plurality of positive data points corresponding to a received signal and a plurality of negative data points corresponding to the signals obscured by the portion of the plant. Finally, the method and/or computer program product embodiments of the present invention may also comprise generating a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from the receivers such that the plant characteristic data set may be used to measure the physical characteristics of the plants.

Some method and computer program product embodiments of the present invention further comprise advancing the sensor assembly along the row axis, wherein the emitting step further comprises repeatedly emitting the signals at a selected rate, and wherein the generating step further comprises generating a two-dimensional profile of the plant by compiling the plant profile data set generated by said receivers at a plurality of longitudinal points along the row axis. The method and/or computer program product may also further comprise, in some embodiments, generating a binary image based on the plant characteristic data set, displaying the binary image to a user via a user interface, and adding the binary image to the plant characteristic data set.

The method and computer program product embodiments of the present invention may also comprise collecting a variety of plant characteristic data types to be added to the plant characteristic data set that may be stored in a memory device and used to characterize and/or count a selected plant of interest such that the computer device may thereafter use the stored plant characteristic data to identify a plant being cultivated in the agricultural environment. For example, some method and/or computer program product embodiments further comprise: locating a position

of the stem axis relative to the sensor assembly using a distance sensor; capturing a multi-spectral image of the plants to differentiate the plant from a plurality of surrounding materials; transmitting a location data set from a shaft encoder (operably engaged with a wheeled carriage for advancing the sensor assembly) to determine a distance along the row of plants; and/or determining the position of the plant using a global positioning system.

Thus the various embodiments of the device, method, and computer program product of the present invention provide many advantages that may include, but are not limited to: providing sensor assembly for compiling a plant characteristic data set that may operate quickly and effectively to generate plant characteristic data in working agricultural environments, providing an agricultural sensor array comprising a plurality of relatively low-cost and durable sensors and/or imaging devices, and allowing for the storage of plant characteristic data sets that may be used to identify, count, classify, and locate plants of interest within a working agricultural environment. Some embodiments of the system, method, and computer program product of the present invention provide the added advantage of allowing selected plant types to be quickly compared with stored plant profile data for real-time identification and accurately locating plants within a commercial or research agricultural plot such that plants having selected phenotypes may be accurately mapped.

These advantages, and others that will be evident to those skilled in the art, are provided in the system, method, and computer program product of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1 shows a perspective view of the system according to one embodiment of the present invention wherein the sensor assembly is positioned about a row of plants;

FIG. 2 shows a top view of the sensor assembly positioned relative to a row of plants according to one embodiment of the system of the present invention;

FIG. 3 shows a top view of a sensor assembly according to one embodiment of the present invention including multiple emitter and receiver arrays, distance sensors, a multi-spectral device, and additional sensor types for measuring plant characteristics;

5 **FIG. 4** shows an exemplary image of a plant profile that may be generated according to some embodiments of the sensor assembly of the present invention;

FIG. 5 shows an exemplary image of a top view of a plant (and associated spectrographs) that may be generated by a spectral camera positioned generally above a plant according to some embodiments of the sensor assembly of the present
10 invention;

FIG. 6A shows an exemplary camera image generated by the camera component of the multi-spectral device of the system of the present invention;

FIG. 6B shows an example of a camera image generated by the multi-spectral device of a system the present invention wherein the image has been optimized using
15 spectrographic data;

FIG. 6C shows an example of a spectrographic data plot for plant matter surrounded by a soil substrate as generated by the spectrograph component of a multi-spectral device included in some embodiments of the system of the present invention;

FIG. 7A shows an exemplary plant profile and top view profile of a typical
20 maize plant;

FIG. 7B shows an exemplary plant profile and top view profile of a typical weed plant;

FIG. 8 shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set using a sensor
25 assembly positioned about a row of plants;

FIG. 9 shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set and generating a binary image of a plant using the plant characteristic data set;

FIG. 10 shows a flow chart of one embodiment of the method of the present invention further comprising advancing a sensor assembly along a row of plants to
30 generate and display a two-dimensional plant profile to a user;

FIG. 11 shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set comprising a location of a position of a stem axis of a plant;

5 **FIG. 12** shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set comprising a multi-spectral image of a plant;

FIG. 13 shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set comprising a row location of a plant as transmitted by a shaft encoder device operably engaged with the
10 sensor assembly;

FIG. 14 shows a flow chart of one embodiment of the method of the present invention comprising generating a plant characteristic data set comprising a GPS coordinate set corresponding to a plant location;

FIG. 15 shows a flow chart of one embodiment of the method of the present
15 invention comprising generating a plant characteristic data set for a plant of interest and storing the plant characteristic data set in a memory device; and

FIG. 16 shows a flow chart of one embodiment of the method of the present invention further comprising identifying a plant by comparing a generated plant characteristic data set to a stored plant characteristic data set corresponding to a
20 selected plant of interest.

DETAILED DESCRIPTION OF THE INVENTION

The present inventions now will be described more fully hereinafter with reference to the accompanying drawings, in which some, but not all embodiments of
25 the invention are shown. Indeed, these inventions may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements. Like numbers refer to like elements throughout.

While the embodiments of the present invention are described below in the
30 context of an agricultural environment for growing maize plants in rows defining row axes, it should be understood that the embodiments of the present invention may also be used to measure the physical characteristics of various other types of plants, which may be cultivated in a variety of configurations and environments. For example, in

some embodiments, the sensor assembly **100** of the present invention may be statically positioned in a greenhouse and/or laboratory such that potted and/or container-cultivated plants may be conveyed to a position relative to the sensor assembly **100** such that the plants **10** may be scanned and/or measured using the
5 embodiments of the present invention. In addition, one skilled in the art will appreciate that the methods and computer program products of the present invention may also be used to characterize, identify, catalog, and measure phenotypic traits of a variety of different plants that may include a variety of crops, weeds, native plants, invasive plant species, and or other objects present in an agricultural environment that
10 may have a measurable profile when exposed to the sensor assembly of the present invention.

FIG. **1** shows a perspective view of a sensor assembly **100** that may be provided as part of a system for measuring physical characteristics of plants **10** within a row of generally defining a row axis **20**, wherein each plant **10** in the row defines a
15 stem axis **30** extending substantially vertically from the row axis **20** in an agricultural environment, such as, for example, a field, greenhouse, research plot, and/or other cultivation environment. According to one embodiment, the system comprises a sensor assembly **100** including a plurality of emitters **110a** arranged in an emitter array **110** and a plurality of receivers **110b** arranged in a receiver array **120** and
20 disposed substantially opposite and parallel to the emitter array **110**. The receiver array **120** may thus be positioned and configured to receive a plurality of signals emitted by the emitters **110a**. As shown in FIG. **1**, the sensor assembly **100** may be positioned relative to the row axis **20** such that the receiver array **120** and the emitter array **110** may be aligned and positioned on opposite sides of the row of plants **10**.
25 While FIG. **1** generally shows the emitter array **110** and the complementary receiver array **120** extending substantially parallel to the stem axis **30**, the sensor assembly **100** may also be positioned at various angular positions relative to either the stem axis **30** or the row axis **20** such that the emitter and receiver arrays **110**, **120** may be used to capture data related to various portions of the plants **10** or other features of the
30 agricultural environment, including topography, large debris, or other features that may be measured and/or used to block the signals emitted by the emitter array **110**.

The sensor assembly **100** may comprise, in some embodiments, an industrial light curtain apparatus, such as for example the Konturflex LUMiflex K-5-320 by

Leuze Electronic. Such light curtain devices may be configured to emit optic signals from the emitter array **110** that may be received by a complementary receiver array **120** that is aligned therewith such that individual emitters **110a** are accurately aligned with complementary individual receivers **120a** disposed within the receiver array **120**.

5 According to other embodiments, the sensor array **100** may also comprise a plurality of photodiodes serving as individual emitters **110a** within the emitter array **110**. In such embodiments, the receivers **120a** may comprise individual photosensors configured to detect signals emitted by complementary photodiodes. In addition, according to some embodiments, such as that shown generally in FIG. 3 (showing a
10 top view of the sensor assembly **100**), the sensor assembly **100** may comprise several complementary pairs of emitter arrays **110** and receiver arrays **120** arranged at various angles relative to the row axis **20** such that the sensor assembly **100** may generate an image of the profile of the individual plants **10** in the row that takes into account the statistical orientation of the single plant **10**. In some embodiments, multiple
15 complementary emitter arrays **110** and receiver arrays **120** may also be interleaved, so that for a given left and right side of the sensor assembly **100**, the left side would comprise, in an alternating pattern, an emitter array **110**, receiver array **120**, emitter array **110**, etc., and the right side would thus comprise complementary receiver array **120**, emitter array **110**, receiver array **120**, etc.

20 In some embodiments, multiple array pairs **110, 120** may be used for purposes including, but not limited to: capturing a different angle/view of the plant; capturing redundant images of a plant **10** in order to clarify the images generated in a dusty and/or otherwise obscured environment; and/or providing different sensing capabilities based on wavelength or resolution of particular array pairs **110, 120**. In
25 some embodiments, two different array pairs having different emitter **110a** and receiver **120a** quantity and spacing. For example, one array pair **110, 120** may comprise a "high resolution" sensor defining 50 beams with 5 millimeters of vertical separation between beams and a second array pair **110, 120** may provide lower resolution with 10 millimeters of vertical separation between beams. Each array pair
30 **110, 120** may prove advantageous based on the plant characteristics being measured. In some cases the low-resolution array pair is preferred since there is less generated noise. In addition, one or more supplementary array pairs **110, 120** may be used with

beams of higher intensity or of a different wavelength to provide additional filtering of noise or inconsequential plant sections.

As described in further detail below, the computer device **120** of the present invention may then receive data sets from the various receiver arrays **120** and
5 generate a comprehensive profile image of the plant **10** that may include data from several receiver arrays **120** that may be disposed in several positions within the sensor assembly **100** as shown generally in FIG. 3.

As shown in FIG. 1, the system embodiments of the present invention may also comprise a computer device **200** in communication with the sensor assembly **100**
10 for controlling the emission and reception of signals by the emitters **110a** and the receivers **120a**. The computer device **200** may be configured to be capable of controlling the emitters **110a** to emit a plurality of signals such that a portion of a plant **10** (such as a leaf, stalk, stem, flower, and/or other plant structure) in the row obscures at least a portion of the plurality of signals. According to some
15 embodiments, the emitters **110a** may be passive emitters (*i.e.*, always “on” and/or always emitting a signal”) such that the computer device **200** may be capable of reading, at a given time, the state of the signals (or beams formed thereby) that are broken by an obstruction (such as a plant **10**, or portion thereof). Furthermore, the computer device **200** may also be capable of receiving a profile data set generated by
20 the receivers **120a** in response to the reception (or lack thereof) of the plurality of signals. The profile data set received from the receivers **120a** may comprise a plurality of positive data points corresponding to a received signal and a plurality of negative data points corresponding to the portion of the plurality of signals obscured by the plant **10** (and correspondingly not received by the receivers **120a**). For
25 example, , in one embodiment, the combinations of “broken beams” (or obstructed light signals) may be read as a binary output from the receiver array **120**, wherein a binary “1” is a continuous, or received signal, and a binary “0” is a broken beam or obscured signal. In some embodiments, the binary definitions of broken and continuous beams and/or signals may also be reversed. In addition, in response to the
30 data set received from the receivers **120a**, the computer device **200** may generate a plant characteristic data set that comprising at least the plant profile data set (which may comprise, for example, a binary string (*i.e.*, 0010100101)) which may be integrated with data received from a plurality of other sensors such that the computer

device may be capable of generating a plant characteristic data set comprising both plant profile data and a variety of other data types related to the physical attributes of one or more plants, as described below.

Furthermore, as shown in FIG. 2, some embodiments of the system of the present invention may further comprise a wheeled carriage (including, for example, a pair of wheels **101** disposed on an axle) operably engaged with the sensor assembly **100** for advancing the sensor assembly **100** along the row axis **20**. In such embodiments, the computer device **120** may further control the emitters **110a** to repeatedly emit the signals at a selected rate that may correspond to the speed at which the wheeled carriage is advanced along the row axis **20**. The sensor assembly **100** may also be advanced along the row axis by other mechanisms or processes, including via a carrier assembly onboard a piece of agricultural machinery such as a combine, tractor, planter, irrigation rig, or other mechanism. For example, in some embodiments, the sensor assembly **100** may be carried by a “fork” attachment at the front or rear of a tractor or other piece of agricultural equipment. In addition, the sensor assembly may also be carried by hand by an individual operator through a research plot and placed over a plant of interest in order to measure a single “slice” of the plant **10** profile at one particular position along the row axis **20**. According to some alternate embodiments, the sensor assembly **100** may be placed over an individual plant **10** and rotated the stem axis **30** to generate a 360 degree profile of the plant **10**. In such embodiments, a shaft encoder may also be disposed about a bearing shaft carrying the rotatable sensor assembly **100** such that the radial position of the emitter arrays **110** and receiver arrays **120** may be accurately determined and/or added to the plant characteristic data set. As described in further detail below, the sensor array **100** of the present invention may also comprise a global positioning system (GPS) device for precisely locating the sensor assembly **100**. Thus, such hand-carried sensor assembly **100** embodiments may be used to log the location of a particular plant **10** as well as the height of the plant **10** in order to evaluate, track, and/or determine the height of plants **10** in particular locations within the agricultural environment. In other embodiments, the sensor assembly **100** of the present invention may be suspended from a ceiling-mounted track system (in greenhouse applications, for example) and/or from a conveyor system disposed adjacent to the row axis **20** (such as a track or conveyor belt).

According to some system embodiments, the computer device **120** may trigger the emitters **110a** to emit the signals at a predetermined rate such that the corresponding receivers **120a** receive the signals and the computer device further generates a two-dimensional profile of the plant by compiling the data generated by said receivers at a plurality of longitudinal points along the row axis. For example, as shown in FIG. 4, the sensor assembly **100** (including complementary emitter **110** and receiver arrays **120**) may be advanced along the row axis **20**) such that the computer device **200** may generate a two-dimensional profile (displayed via the user interface **210**) of the plant **10** by compiling data sets received from the receiver array **120** and data related to the speed of the advancement of the sensor assembly **100** along the row axis **20**. In other embodiments, (as shown generally in the top view of a system in FIG. 2) a shaft encoder **150** (or other transducer device for measuring rotational movement or velocity) may be operably engaged with an axle of a wheel **101** for conveying the sensor array, such that the shaft encoder **150** may transmit a location data set (indicating a linear position along the row axis **20**, for example) to the computer device **200**. Using the encoder information, and wheel **101** diameter data that may be stored in a memory device **220** within or in communication with the computer device **200**, the computer device **200** may determine a distance along the row axis **20**. The computer device **200** may, in turn, add the location data set generated by the shaft encoder to the plant characteristic data set generated by the receivers **120** to generate a two-dimensional plant **10** profile that may be displayed to a user of the system via a user interface **210**, such as a display, in communication with the computer device **200**.

According to some system embodiments, the shaft encoder **150** may be used as a trigger device to control the computer device **200** to read data from the receiver array **120** at specified distance interval (such as every millimeter traveled by the sensor assembly **100**). The plant profile data set (such as a binary stream of "1's" and "0's") is cached into the memory device **220** to build a binary profile image of the plant **10**. Subsequently, the computer device **200** may apply an algorithm to analyze the binary image. For example, according to some system and method embodiments of the present invention, the binary image may be used to identify a plant of interest and distinguish it from another plant type and/or other debris or obstructions that may be present in an agricultural environment.

An example of a plant **10** profile that may be generated using the plant profile data is shown generally in FIG. 4 wherein the plant profile is shown from the point of view of the receiver array **120** (that may be positioned parallel to the row axis **20**).

According to some system embodiments, the computer device **200** generates a binary image (such as that shown generally in FIG. 4) based on the plant characteristic data set and displays the binary image to a user via the user interface **210**. The computer device **200** may also comprise a memory device **220** in communication therewith such that the computer device may add the generated binary image to the plant characteristic data set and store the integrated plant characteristic data set for later use in comparison or identification processes.

In other system embodiments of the present invention, the sensor assembly **100** may also comprise a variety of other sensors, transducers, and/or other measurement or imaging devices that may also be in communication with the computer device **200** for measuring and/or classifying a variety of characteristics that may be exhibited by a plant **10**. Such characteristics may include, but are not limited to: plant height; two-dimensional plant profile (as discussed above); precise geographical location of the plant **10**, top-view plant profile; spectral signature of the plant; location of the plant **10** relative to the sensor assembly **100** and/or row axis **20**; longitudinal position of the plant **10** along the row axis **20** (as described generally above with respect to the shaft encoder **150**); and/or other plant characteristics that may be indicative, in some cases, of plant genotype and plant viability.

Furthermore, the sensor assembly **100** (in cooperation with the computer device **200** may be further configured to utilize the plant characteristic data to generate and/or store a count of a plurality of plants so as to compile population data for a certain number of plants. Thus, using such embodiments, researchers may obtain data as to the relative population of crop plants versus weeds or invasive species in a particular stand and/or row of plants (using plant count data and plant characteristic data corresponding to each counted plant). Thus, in such embodiments, a density and/or plant population per a selected physical unit (i.e. per acre, per row, per research plot) may be computed using count data obtained by the sensor assembly **100** and stored by the computer device **200**. According to such embodiments, the selected "area" or other physical unit used to calculate population density of a particular plant may have a previously-developed start and end point (stored in the

computer device **200**, for example) wherein the start and end points are provided by a GPS device and/or other locator devices that may be included as part of the sensor assembly **100**, as described further herein. Such embodiments may then allow then a computer program product or routine (housed, for example, in the computer device **200**) to sum the number of plants discretely identified, by the sensor assembly **100**, for example, between the starting point to the ending point of a particular physical unit or area. Other embodiments may utilize pre-programmed logic to segment plant characteristic data sets received from the sensor assembly **100** by, for example, research plot, row number, and/or other physical unit. For example, the system may be able to infer that an observed gap in plants (as indicated by the sensor assembly's **100** lack of detected plant matter) is a space between plots and that therefore it should reset the count for a new physical unit. More particularly, such logic steps may include the following logic "rules" stored in a memory device in communication with and/or part of the computer device **200**: (1) all research plots have at least X plants per plot; (2) alleys are at least 24"; and (3) if X number of plants have been counted and a 24" gap is observed then a new plot is starting and the count should be reset. Such logic-based embodiments may, for example, reduce the dependence of the system on GPS positioning data and/or be utilized as a redundant "check" on GPS data stored as part of the plant characteristic data set.

Such measurable plant **10** characteristics may also be used by the computer device **200** of the present invention to identify plants of interest and/or plants exhibiting selected phenotypic responses by comparing measured plant characteristics to characteristics stored within a memory device **220** in communication with the computer device **200** of the present invention. As described in further detail below, various data types may be produced by the variety of additional sensors that may be received by the computer device **200** and thereafter added to the plant characteristic data set for storage and/or use in identification, cataloging, and/or measurement processes.

Some embodiments of the present system, as shown, for example, in FIGS. **2** and **3**, may further comprise a plurality of distance sensors **140a**, **140b**, **140c** wherein at least one of the distance sensors **140c** is positioned on a side of the sensor assembly **100** with the emitter array **110** and opposite the receiver array **120**. The distance sensor **140c** may be disposed on a lower portion of the sensor assembly and

positioned so as to be capable of emitting a triangulating signal that reaches the stem axis **30** of the plant **10** such that the distance sensor **140c** may accurately determine the distance between the sensor's **140c** position on the sensor assembly **100** and the position of the stem axis **30** of the plant. Furthermore, in some system embodiments, an additional distance sensor **140b** may also be provided and disposed on a side of the sensor assembly **100** opposite the distance sensor **140c** so as to be capable of providing a second distance measurement between the second distance sensor **140c** and the stem axis **30**. Thus, the combination of distance sensors **140c**, **140b** may be used to accurately determine the position of the stem axis relative to the emitter array **110** side of the sensor assembly **100** and the receiver array **120** side of the sensor assembly.

According to other embodiments, a third distance sensor **140a** may also be disposed on the sensor assembly **100** to determine a height of the plant **10** by determining a distance between a top portion **102** of the sensor assembly **100** and the topmost point of the plant **10**. For example, as shown generally in FIG. 2, the distance sensor **140a** may be positioned to emit a laser triangulation signal down from the top portion **102** of the sensor assembly **100** to determine the height of a plant **10** over which the sensor assembly **100** may be advanced.

Furthermore, according to various system embodiments of the present invention, the computer device **200** may be in communication with the distance sensors **140a**, **140b**, **140c** for locating a position of the stem axis **30** and a top-most portion of the plant **10** relative to the sensor assembly **100**. For example, while the distance sensors may be configured to measure a distance between their positions on the sensor assembly **100**, the computer device **200** (and/or a memory device **220** in communication therewith) may be capable of storing dimensional specifications of the sensor assembly **100** (such as the width and/or height of the sensor assembly **100**) such that the computer device **200** may be capable of using the dimensional specifications and the distance data returned by one or more triangulations sensors **140a-140c** to determine the position of the stem axis **30** of a plant **10**, the height of a particular plant **10**, and/or the diameter of a plant **10** stem (using, for example, two opposing distance sensors **140b**, **140c**).

The distance sensors may comprise various types of sensors for measuring distance including, but not limited to: triangulation sensors, optical encoders, laser

diode arrays suitable for measuring distance; position sensitive devices (PSD's); CMOS devices; and/or charge coupled devices (CCD's). Additional distance sensors may also be added to the sensor assembly **100** according to other system embodiments, for providing supplemental distance measurements between the
5 location of the distance sensor on the sensor assembly and the location of a particular plant part.

The system of the present invention may also comprise (as shown generally in the top views of FIGS. **2** and **3**) a multi-spectral device **130** (such as a camera **130** and/or hyper-spectral device) operably engaged with a top portion **102** (such as a
10 cross-rail) of the sensor assembly **100** for capturing a multi-spectral image of the plant **10** from a position above the plant **10** so as to differentiate the plant from a plurality of surrounding materials (such as soil, dust, weeds, foreign objects, and/or other vegetation that may be present in the cultivation environment. The multi-spectral device **130** may be positioned at a center point between the emitter array **110** and
15 receiver array **120** (see FIG. **2**, for example) such that the camera **130** may be capable of capturing an image of the plant **10** from a central perspective along the row axis **20**. In other embodiments, the multi-spectral device **130** may also be "side" mounted to capture side profile images of the plant **10**. For example, the multi-spectral camera **130** may be positioned on one or both of the emitter **110** and receiver **120** sides of the
20 sensor assembly **100** for capturing a multi-spectral image of the side profile of the plant **10**.

The multi-spectral device **130** may comprise, for example, an imaging spectrograph alone and/or in combination with an industrial monochrome camera such that the spectral camera **130** may take advantage of the differing reflectivity and
25 spectral signatures of soil, weeds, and/or the plant **10** of interest in order to generate an accurate depiction of the plant's **10** leaf shape and leaf geometry. In some embodiments, however, the multi-spectral device **130** comprises only a spectrograph capable of generating a line-scan to build a composite image in, for example, the green region of the spectrum. By isolating the green region, background noise and
30 dirt may be eliminated from the spectrograph and pattern matching (comparing, for example, a stored leaf pattern of a plant of interest to the generated spectrograph) may be used based on the composite image. According to some embodiments, an imaging spectrograph such as the ImSpector (produced by Specim) is used in conjunction with

an industrial camera to generate a multi-spectral overhead image of a plant **10**. As discussed above, imaging spectrographs such as the ImSpector may be used along and/or in conjunction with a camera to generate an image of the plant **10**. In other embodiments, CMOS cameras and/or additional digital camera technologies can also
5 be used to generate a base image (see FIG. **6A**, for example) for the spectral camera **130**. The computer device **200** of the present invention may then receive the camera image and enhance the differences between plant material and surrounding soil material (using differences in spectral signature) as detected by the imaging spectrograph in order to generate a multi-spectral image of the plant as shown
10 generally in FIG. **6B**. FIG. **6A** generally shows an unenhanced camera image. Furthermore, FIG. **6B** shows an enhanced multi-spectral image generated by the multi-spectral device **130** differentiating plant leaf material from surrounding soil material. FIG. **6C** shows a spectrograph indicating the relative spectral signatures of the plant and soil materials in the image. The input from the spectrograph component
15 of the multi-spectral device **130** may thus allow the camera to effectively generate images of plant material even in working agricultural environments that may be obscured by dust, moisture, fog, and/or other foreign materials that have a spectral signature that is significantly different from that of plant material.

According to some embodiments, the data compiled by the imaging
20 spectrograph may also be used to generate quantitative plant data that may be indicative of plant phenotype, including, for example, chlorophyll content, photosynthesis and PAR (photosynthetically active radiation), nitrogen utilization, leaf thickness, leaf count, and other plant data. The imaging spectrograph may also be used to analyze plant **10** phenotypic properties in the infrared, ultraviolet, and/or
25 other non-visible spectra. For example, water absorption levels may be detected by the multi-spectral device **130** when scanning in the near infra-red spectrum.

An exemplary multi-spectral image produced by a multi-spectral device **130** from a top view is shown generally in FIG. **5**. According to some system embodiments of the present invention, such a multi-spectral image may be displayed
30 to a user via the user interface **210** in communication with the computer device **200** of the system of the present invention. In addition, in some embodiments, the spectral image and data embodied therein may be received by the computer device **200** and added to the plant characteristic data set for a particular plant. Thus, the multi-

spectral device image of the plant **10** may be linked with the plant profile data set (obtained from the sensor array **100**) in the plant characteristic data set so as to provide a more complete set of plant characteristics that may be stored in a memory device **220** and/or compared with a stored plant characteristic data set of a known
5 plant of interest in order to identify the known plant of interest in real-time or near-real-time applications.

According to other system embodiments of the present invention, the system may further comprise one or more devices configured to be capable of generating location data for a particular plant **10** such that the computer device **200** may add such
10 location data to the plant characteristic data set and generate a map and/or catalog of plant **10** locations within a given agricultural plot, research plot, greenhouse zone, row number, and/or other division of cultivation area. For example, in some embodiments wherein the sensor assembly **100** of the present invention is advanced along the row axis **20** on a carriage comprising wheels **101** (as shown generally in the
15 top view of FIG. 1), the wheeled carriage may comprise at least one axle (for carrying the wheels **101**) and a shaft encoder **150** operably engaged with said axle for transmitting a location data set to the computer device **200** to determine a distance along the row axis **20**. The computer device **200** may also further add the location data set generated by the shaft encoder **150** to the plant characteristic data set such
20 that the plant characteristics may be linked to a location along the row axis **20** for mapping of particular phenotypes or for the accurate tagging of weeds for later automated weeding processes.

According to other system embodiments of the present invention, the system may further comprise a global positioning system (GPS) device **160** (as shown in FIG.
25 **2**) in communication with the computer device **200** for determining the position of the plant **10** using a global positioning system. As shown in FIG. 2, the GPS device may be co-located and/or located near a sensor for detecting plant height (such as the distance sensor **140a**) such that the position of the plant may be plotted via GPS coordinates with accuracy up to a few inches (depending upon the GPS device used).
30 Furthermore, the computer device **200** may further add the position of the plant **10** (as determined by the GPS device) to the plant characteristic data set such that the plant characteristics may be linked to a location along the row axis **20** for mapping of

particular phenotypes or for the accurate marking of weeds for subsequent automatic weeding.

As shown in FIG. 1 and described above, system embodiments of the present invention may also comprise a memory device **220** in communication with the computer device **200** for storing the plant characteristic data set of a known plant of interest and/or a count of a plurality of plants of interest. For example, the computer device **200** of the present invention may be used to set the sensor assembly **100** to a “learn” mode wherein a user of the system may advance the sensor assembly **100** over a known plant of interest, such as an early-stage maize plant (as shown, for example, in profile from the top and side (parallel to the row axis **20**) in FIG. 7A). Thus, the computer device **200** and the various sensors of the sensor assembly **100** may be used to generate a plant characteristic data set (as described above) for the maize plant. In another exemplary embodiment, the memory device **220** may be used to store a plant characteristic data set (comprising, for example, plant profile data; a plant multi-spectral image taken from a top-view perspective, or other plant characteristic data set data point) for a typical weed plant (such as that generally shown in FIG. 7B). The stored plant characteristic data sets for such “plants of interest” may then be used as comparative examples as the system of the present invention is used to identify the plant of interest by its distinguishing phenotype and/or mark the plant of interest by its location within the agricultural environment.

As described further below with respect to the method and computer program product embodiments of the present invention, the computer device **200** of the system of the present invention may also be engaged in an “identify” mode wherein the computer device **200** identifies the plant **10** by comparing the generated plant characteristic data set (taken in real-time or near-real time from the sensor assembly **100** and associated components (such as the multi-spectral device **130**)) with the stored plant characteristic data set (stored in the memory device **220**, for example) of the known plant of interest. Thus, the computer device **220**, working in conjunction with the sensor assembly **100** and other components of the system of the present invention, may identify selected plants of interest as the sensor assembly **100** is advanced on a row axis **20** such that the system may rapidly identify and catalog the location, count, and physical traits of the selected plants of interest. Thus, the system of the present invention may allow for the identification and/or counting of maize or

other crops, weeds, non-native or invasive plant species, and/or any other particular plant of interest within the agricultural environment.

According to some embodiments, one or more computer devices **200** may be distributed within the system for controlling the sensor assembly **100** and other
5 system components as well as storing plant characteristic data and identifying particular plants based upon such data. For example, in some system embodiments of the present invention, distributed processing techniques may be utilized wherein a first computer device **200** (comprising, for example, a microcontroller) may be used for pre-processing plant characteristic data taken from the sensor assembly **100** and/or
10 other system components (such as the multi-spectral device **130**, distance sensors **140a-c**, etc.). The first computer device may then be capable of compiling and/or refining an overall plant characteristic data set and sending the plant characteristic data set to a second computer device **200** (such as a main controller device) for subsequent storage and/or identification processes as described below in the method
15 and computer program product embodiments of the present invention (see, *e.g.*, steps **1610** and **1620** of FIG. **16**).

Furthermore, some components of the system of the present invention may generate data that may be especially useful for tracking the expression of certain phenotypes within and among various genotypes including, but not limited to,
20 genetically modified organisms (GMO's) or non-genetically-modified plant species that have been selectively bred to express certain phenotypic responses. For example, some maize plants may be selectively bred or genetically-modified to express larger stem diameters (to resist wind break, for example). According to some system embodiments of the present invention, an opposing pair of distance sensors **140b**,
25 **140c** (as shown in FIGS. **2** and **3**) may be used in conjunction with the computer device **200** to determine the stalk or stem diameter of a maize plant and catalog the location of specific plants that exhibit the increased diameter. Similar phenotype tracking may be accomplished using other components of the system of the present invention such as the multi-spectral device **130**, which may detect certain leaf-pattern
30 and/or color phenotypes. In addition, the spectral signature generated by the multi-spectral device **130** (see FIG. **5**, for example, may be used to identify plants **10** with higher levels of chlorophyll, thicker leaves, and/or other physical traits that may be indicated by subtle changes in spectral signature.

The present invention also includes methods for measuring physical characteristics of individual plants **10** and/or groups of plants **10** positioned generally in a row defining a row axis **20** wherein each plant **10** in the row defines a stem axis **30** extending substantially vertically from the row axis **20** in an agricultural environment. FIG. **8** shows a flow chart of one method embodiment of the present invention, wherein step **810** includes providing a profile sensor assembly **100** including an emitter array **110** and a receiver array **120** disposed substantially opposite and parallel to the emitters for receiving a plurality of signals emitted by the emitter array **110**. Step **810** also includes providing a computer device **200** in communication with the profile sensor assembly **100**. Step **820** comprises positioning the sensor assembly **100** relative to the row of plants such that the receivers **120a** and emitters **110a** are positioned on opposite sides of the row axis **20** (as shown from above in FIG. **2**, for example). Furthermore, step **830** comprises emitting the plurality of signals from the emitters **110a** such that a portion of a plant **10** in the row obscures at least a portion of the plurality of signals. For example, step **830** may comprise emitting a light signal that may be obscured by a stem or leaf component of the plant such that step **840** comprises receiving a portion of the plurality of signals at the receivers **120a** such that said receivers **120a** generate a plant profile data set comprising a plurality of positive data points corresponding to a received signal (*i.e.*, a signal that proceeds uninterrupted from an emitter **110a** to a corresponding receiver **120a**) and a plurality of negative data points corresponding to the signals obscured by the portion of the plant **10**. Step **850** comprises generating a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from the plurality of receivers **120a** such that the plant characteristic data set may be used to measure the physical characteristics of the row of plants **10**. For example, the plant profile data may be used to generate a binary image **210** of the plant **10** as shown in FIG. **4**.

For example, as shown generally in FIG. **9**, according to some method embodiments, the providing step **810** further comprises providing a user interface **210** in communication with the computer device **200**, and the method may further comprise the following steps: step **910**, including generating a binary image based on the plant characteristic data set; step **920**, including displaying the binary image to a user via the user interface **210** (such as a display in communication with the computer

device **200**); and step **930**, including adding the binary image (shown, for example, in the display **210** of FIG. 4) to the plant characteristic data set.

According to some method embodiments, as shown generally in FIG. **10**, the generating step **910**, may be accomplished by the computer device **200** of the present invention, which may compile the vertical locations of the positive and negative data points generated with the receiver array **120** over time as the sensor assembly **100** is advanced along the row axis **20** to generate a side profile image **210** of the plant **10**. As shown in FIG. **10** the method may further comprise step **1010** which includes advancing the sensor assembly **100** along the row axis **20** (as shown in FIG. 4, for example). In such method embodiments, the emitting step (step **830**) may further comprise repeatedly emitting the signals at a selected rate, and the generating step (step **850**) may further comprise generating a two-dimensional profile of the plant by compiling the plant profile data set generated by said receivers at a plurality of longitudinal points along the row axis **20**. Furthermore, step **1020** comprises adding the generated two-dimensional profile of the plant to the plant characteristic data set. Furthermore, in some embodiments, the generating step **850** may further comprise generating two-dimensional profiles for a variety of plants as the sensor assembly **100** is advanced so as to count a number of a plurality of plants in a given stand and/or row. The generated count may then be stored by the computer device **200** so as to collect and maintain a count of a particular plant of interest.

As described above with respect to the system embodiments of the present invention, various sensors and components may be used to generate a variety of plant characteristic data points to be included in the plant characteristic data set compiled by the computer device **200** of the present invention that may supplement the profile data, side profile image, and/or two-dimensional profile of the plant **10** that may be generated by the emitter array **110** and receiver array **120** of the sensor assembly **100**. For example, the system of the present invention may also comprise one or more distance sensors **140a**, **140b**, **140c** (as shown generally in FIGS. 2 and 3), for determining distances between the distance sensors (which may be operably engaged with the sensor assembly **100**) and a stem (defining the stem axis **30**, for example) and/or other plant structure of the plant **10**. Thus, according to an alternative method embodiment, as shown generally in FIG. **11**, the method may further comprise step **1110** for locating a position of the stem axis **30** relative to the sensor assembly **100**

using one or more of the distance sensors **140a**, **140b**, **140c**, and step **1120** for adding the located position of the stem axis **30** to the plant characteristic data set. Some distance sensors **140a** may also be operably engaged with a top portion **102** of the sensor assembly **100** (see FIG. **3**) such that the method embodiments of the present invention may also comprise locating a position of a leaf structure or a plant's **10** tallest point relative to a top-mounted distance sensor **140a** configured to emit a light signal downward toward the plant **10** as the sensor assembly **100** is advanced on the row axis **10**.

According to another method embodiment of the present invention, shown generally in FIG. **12**, the method may further comprise, in step **1210**, capturing a multi-spectral image (using a multi-spectral device **130**, as described above) of the plant **10** from a position above the plant **10** so as to differentiate the plant **10** from a plurality of surrounding materials (such as soil, dust, fog, or other material). Step **1220** further comprises adding the multi-spectral image to the plant characteristic data set. Thus, the computer device **200** of the present invention may integrate the two-dimensional profile image (see element **210** shown in FIG. **4**) with a multi-spectral image (see, for example, FIG. **6B**) in the complete plant characteristic data set such that the plant **10** physical profile characteristics may be cataloged with a side profile and a corresponding top-view profile (see FIG. **7A** for a top and side view profile of a typical maize plant). As described above, the capturing process of step **1210** may be accomplished by the combination of a camera image (see FIG. **6A**, for example) with a spectrograph of the same or similar field of view (see FIG. **6C**, for example) in order to generate the enhanced multi-spectral image as shown in FIG. **6B**. Thus, the generating step **1210** may generate an enhanced multi-spectral top-view image of the plant **10** as the sensor assembly is advanced over the plant **10** that may reveal a detailed profile of the leaf pattern of the plant **10** regardless of the soil, dust, or other materials in the vicinity of the plant due to the differences in spectral signature between the plant material and surrounding materials that are highlighted by the spectrograph. Furthermore, step **1210** may be performed with the aid of the computer device **200** for more accurate integration of the camera image with the spectrograph to provide the multi-spectral image.

Some system embodiments of the present invention (as shown in FIG. **2**, for example) include a sensor assembly **100** that is carried by a wheeled carriage having

at least one wheel **101** and corresponding axle wherein a shaft encoder **150** operably engaged with the axle. Thus, some method embodiments of the present invention (shown in FIG. **13**, further comprise step **1310** for transmitting a location data set from the shaft encoder **150** to a computer device **200** to determine a distance along the row axis **20**, and step **1320** for adding the location data set to the plant characteristic data set. Thus, steps **1310** and **1320** may be performed to determine and catalog the location of a particular plant **10** along the row axis **20** (which may be defined relative to a “home” position defined by a field edge, fence, greenhouse wall, road, or other landmark and/or barrier). Other method embodiments of the present invention (shown generally in FIG. **14**, further comprise step **1410** for determining a geographical position of the plant **10** (to supplement or replace the determination of the linear position of the plant as shown in step **1310**; above) using a global positioning system (GPS) device **160** (that may be mounted and/or co-located with the multi-spectral device **130** and/or top-mounted distance sensor **140a** (see FIG. **2**) such that the GPS device may accurately record precise GPS coordinates as the plant **10** is detected). Step **1420** further comprises adding the determined position of the plant **10** to the plant characteristic data set. Thus, step **1420** may link plants **10** having certain detected physical traits or phenotypes to a distinct geographical location that may be accurately plotted to within a few centimeters, depending upon the GPS device **160** used.

FIG. **15** shows a method for “teaching” the sensor assembly **100** of the present invention comprising step **1510** for storing the plant characteristic data set of a known plant of interest in a memory device **220** in communication with the computer device **200**. Step **1510** thus allows the computer device to associate a particular plant characteristic data set with a selected plant of interest (such as a targeted weed type having distinct physical properties, or a maize plant with a certain preferred phenotype.) The “teaching” step depicted as step **1510** of FIG. **15** thus enables the computer device to identify, in real-time or near-real-time, the plant **10** being evaluated by the sensor assembly **100** by comparing the generated plant characteristic data set (generated in near-real-time) with the stored plant characteristic data set of the known plant of interest (that has been “taught” to the computer device **200** as part of step **1510**. FIG. **16** depicts the plant identification step **1610** described above. Step

1610 may be accomplished using one or more of the distinct data points within the plant characteristic data set.

Furthermore, the plant identification step **1610** may be performed in conjunction with a counting step such that the sensor assembly **100** (in cooperation with the computer device **200**) may be rendered capable of maintaining a count of several different plants of interest (identified, for example, in step **1610** by particular plant characteristic data sets) during a single “pass” of the sensor assembly **100** through a stand of plants that may include, for example, a stand of crop plants interspersed with weeds and/or invasive plant species. Thus, such method embodiments may be used to assess the population of crop plants in a particular stand versus the relative population of weeds of interest in the same general area of a stand or research plot. As described herein with respect to the system embodiments, the counting step may comprise counting a number of plants per a physical unit (such as per unit area, per row, per research plot, for example) such that the method may further comprise determining a density of a particular type of plant (such as a selected crop plant and/or weed) that may be present in a given physical unit (such as a row or a particular research plot).

As described herein, plant characteristic data sets may be populated with images (as depicted in steps **930**, **1020**, and **1220**), plant location data (as depicted in steps **1120**, **1320**, **1420**), plant spectrographic data (generated in step **1210**), and other data types such that the computer device **200** may be capable, in some method and computer program embodiments of selecting one or more of the data types within the plant characteristic data set that provide the strongest correlation with the “learned” or stored characteristics of the selected plant of interest. Thus, the methods of the present invention may provide a robust and repeatable process for accurately identifying and locating plants of interest in a working agricultural environment such that the results of such method may be further used by users for accurately marking weeds for automated removal and/or locating individual plants having a desirable and/or selected phenotype.

In addition to providing systems and methods, the present invention also provides computer program products for performing the operations described above. The computer program products have a computer readable storage medium having computer readable program code embodied in the medium. With reference to FIG. 1,

the computer readable storage medium may be part of the memory device **220** and may implement the computer readable program code to perform the above discussed operations.

In this regard, FIGS. **8-16** are block diagram illustrations of methods, systems
5 and program products according to the invention. It will be understood that each block or step of the block diagram and combinations of blocks in the block diagram can be implemented by computer program instructions. These computer program instructions may be loaded onto a computer or other programmable apparatus to produce a machine, such that the instructions which execute on the computer or other
10 programmable apparatus are capable of implementing the functions specified in the block diagram, flowchart or control flow block(s) or step(s). These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article
15 of manufacture including instructions which implement the function specified in the block diagram, flowchart or control flow block(s) or step(s). The computer program instructions may also be loaded onto a computer or other programmable apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the
20 instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the block diagram, flowchart or control flow block(s) or step(s).

Accordingly, blocks or steps of the block diagram, flowchart or control flow illustrations support combinations of sets of computer instructions for performing the
25 specified functions, combinations of steps for performing the specified functions and program instructions for performing the specified functions. It will also be understood that each block or step of the block diagram, flowchart or control flow illustrations, and combinations of blocks or steps in the block diagram, flowchart or control flow illustrations, can be implemented by special purpose hardware-based
30 computer systems which perform the specified functions or steps, or combinations of special purpose hardware and computer instructions.

Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the

teachings presented in the foregoing descriptions and the associated drawings.

Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are
5 employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

WHAT IS CLAIMED IS:

1. A system for measuring physical characteristics of a plant in an agricultural environment, the system comprising:

a sensor assembly including a plurality of emitters and a plurality of receivers
5 disposed substantially opposite and parallel to said plurality of emitters for receiving a plurality of signals emitted by said emitters such that said receivers and said emitters may be positioned on opposite sides of the plant;

a computer device in communication with said sensor assembly for detecting the reception of signals by said receivers;

10 wherein said emitters emit the plurality of signals such that a portion of the plant obscures at least a portion of the plurality of signals;

wherein said computer device receives a plant profile data set generated by said plurality of receivers comprising a plurality of positive data points corresponding to a received signal and a plurality of negative data points

15 corresponding to the portion of the plurality of signals obscured by the plant; and

wherein said computer device generates a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from said plurality of receivers such that the plant characteristic data set may be used to measure the physical characteristics of the plant.

20

2. A system according to Claim 1, wherein said computer device further controls said emitters to emit the plurality of signals.

3. A system according to Claim 1, wherein said sensor assembly
25 comprises at least one of:

an industrial light curtain;

a plurality of photodiodes substantially aligned with a corresponding plurality of optical sensors; and

combinations thereof.

30

4. A system according to Claim 1, further comprising a movable assembly operably engaged with said sensor assembly for advancing said sensor assembly along a row of plants including the plant and defining a row axis, and

wherein said computer device further controls said emitters to repeatedly emit the signals at a selected rate and wherein said computer device further generates a two-dimensional profile of the plant by compiling the plant profile data set generated by said receivers at a plurality of longitudinal points along the row axis, and wherein said
5 computer device further adds the generated two-dimensional profile of the plant to the plant characteristic data set.

5. A system according to Claim 1, wherein said movable assembly comprises at least one of:
10 a wheeled carriage;
a trailer;
an attachment for carriage by a mobile agricultural mechanism; and
combinations thereof.

15 6. A system according to Claim 1, further comprising a user interface in communication with said computer device and wherein said computer device further generates a binary image based on the plant characteristic data set and displays the binary image to a user via said user interface and wherein said computer device
further adds the binary image to the plant characteristic data set.

20 7. A system according to claim 1, further comprising a distance sensor disposed on the sensor assembly such that the distance sensor measures a distance to a portion of the plant, and wherein said computer device is in communication with said distance sensor for locating a position of the portion relative to said sensor assembly
25 and wherein said computer device further adds the located position of the portion of the plant to the plant characteristic data set.

8. A system according to Claim 1, further comprising a multi-spectral device operably engaged with a top portion of said sensor assembly for capturing a
30 multi-spectral image of the plant from a position above the plant so as to differentiate the plant from a plurality of surrounding materials, and wherein said computer device is in communication with said multi-spectral device for receiving the multi-spectral

image, and wherein said computer device further adds the multi-spectral image to the plant characteristic data set.

5 9. A system according to Claim 1, wherein said sensor assembly further comprises a locator device in communication with said computer device for transmitting a location data set to said computer device to determine a location of the plant, and wherein said computer device further adds the location data set to the plant characteristic data set.

10 10. A system according to Claim 9, wherein said locator device is at least one of:

 an optical encoder;
 a laser encoder;
 a dead-reckoning device comprising a gyroscope and/or an accelerometer;
15 a global positioning system device; and
 combinations thereof.

 11. A system according to Claim 4, wherein said movable assembly comprises at least one axle and wherein said sensor assembly further comprises a
20 shaft encoder operably engaged with said axle and in communication with said computer device for transmitting a location data set to said computer device to determine a distance along the row of plants, and wherein said computer device further adds the location data set to the plant characteristic data set.

25 12. A system according to Claim 1, further comprising a global positioning system device in communication with said computer device for determining a position of the plant using a global positioning system, and wherein said computer device further adds the position of the plant to the plant characteristic data set.

30 13. A system according to Claim 1, further comprising a memory device in communication with said computer device for storing the plant characteristic data set of a known plant of interest in the memory device.

14. A system according to Claim 13, wherein said computer device further identifies the plant by comparing the generated plant characteristic data set with the stored plant characteristic data set of the known plant of interest.

5 15. A system according to Claim 1, wherein said computer device further maintains a count of a number of a plurality of plants for which a corresponding plurality of plant characteristic data sets are generated.

10 16. A system according to Claim 15, wherein said computer device further determines the count of the number of the plurality of plants located in at least one physical unit based at least in part on the corresponding plurality of plant characteristic data sets.

15 17. A system according to Claim 16, wherein the at least one physical unit is selected from the group consisting of:

a row;
an agricultural plot; and
combinations thereof

20 18. A method for measuring physical characteristics of a plant in an agricultural environment, the method comprising:

providing a sensor assembly including a plurality of emitters and a plurality of receivers disposed substantially opposite and parallel to said plurality of emitters for receiving a plurality of signals emitted by said emitters and a computer device in
25 communication with said profile sensor assembly;

positioning said sensor assembly relative to the plant such that said receivers and said emitters are positioned on opposite sides of the plant;

emitting the plurality of signals from said emitters such that a portion of the plant obscures at least a portion of the plurality of signals;

30 receiving a portion of the plurality of signals at said receivers such that said receivers generate a plant profile data set comprising a plurality of positive data points corresponding to a received signal and a plurality of negative data points corresponding to the signals obscured by the portion of the plant; and,

generating a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from said plurality of receivers such that the plant characteristic data set may be used to measure the physical characteristics the plant.

5

19. A method according to Claim 18, further comprising:

advancing said sensor assembly along a row of plants including the plant and defining a row axis, wherein the emitting step further comprises repeatedly emitting the signals at a selected rate, and wherein the generating step further comprises
10 generating a two-dimensional profile of the plant by compiling the plant profile data set generated by said receivers at a plurality of longitudinal points along the row axis; and

adding the generated two-dimensional profile of the plant to the plant characteristic data set.

15

20. A method according to Claim 18, wherein said providing step further comprises providing said plurality of emitters extending substantially parallel to a stem axis of the plant.

20

21. A method according to Claim 18, wherein the providing step further comprises providing a user interface in communication with said computer device, the method further comprising:

generating a binary image based on the plant characteristic data set;

displaying the binary image to a user via said user interface; and

25

adding the binary image to the plant characteristic data set.

22. A method according to Claim 18, wherein said sensor assembly further comprises a distance sensor, the method further comprising:

30 locating a position of the portion of the plant relative to said sensor assembly using said distance sensor; and

adding the located position of the portion of the plant to the plant characteristic data set.

23. A method according to Claim 18, wherein said sensor assembly further comprises a multi-spectral device, the method further comprising:

capturing a multi-spectral image of the plants from a position above the plant so as to differentiate the plant from a plurality of surrounding materials; and

5 adding the multi-spectral image to the plant characteristic data set.

24. A method according to Claim 18, wherein said sensor assembly further comprises a locator device in communication with said computer device; the method further comprising:

10 transmitting a location data set from said locator device to said computer device to determine a location of the plant; and

adding the location data set to the plant characteristic data set.

25. A method according to Claim 19, wherein said sensor assembly is
15 carried by a movable assembly having at least one axle and wherein said sensor assembly further comprises a shaft encoder operably engaged with said axle, the method further comprising:

transmitting a location data set from said shaft encoder to said computer device to determine a distance along the row of plants; and

20 adding the location data set to the plant characteristic data set.

26. A method according to Claim 18, wherein said sensor assembly further comprises a global positioning system device, the method further comprising:

determining a position of the plant using a global positioning system; and

25 adding the determined position of the plant to the plant characteristic data set.

27. A method according to Claim 18, wherein the providing step further comprises providing a memory device in communication with said computer device, the method further comprising storing the plant characteristic data set of a known
30 plant of interest in the memory device.

28. A method according to Claim 27, further comprising identifying the plant by comparing the generated plant characteristic data set with the stored plant characteristic data set of the known plant of interest.

5 29. A method according to Claim 18, further comprising:
counting of a number of a plurality of plants for which a corresponding plurality of plant characteristic data sets are generated; and
storing the counted number of the plurality of plants.

10 30. A method according to Claim 29, further comprising determining the number of the plurality of plants located in at least one physical unit based at least in part on the corresponding plurality of plant characteristic data sets.

15 31. A method according to Claim 30, wherein the at least one physical unit is selected from the group consisting of:
a row;
an agricultural plot; and
combinations thereof.

20 32. A computer program product for controlling a computer device in communication with a sensor assembly comprising a plurality of emitters and a corresponding plurality of receivers disposed substantially opposite and parallel to said emitters for receiving a plurality of signals emitted by said emitters to determine physical characteristics of a plant in an agricultural environment, wherein a portion of
25 a plant obscures at least a portion of the plurality of signals, the computer program product comprising a computer-readable storage medium having computer-readable program code instructions stored therein comprising:

a first set of computer instructions for receiving a portion of the plurality of signals at said receivers such that said receivers generate a plant profile data set
30 comprising a plurality of positive data points corresponding to a received signal and a plurality of negative data points corresponding to the signals obscured by the portion of the plant; and,

a second set of computer instructions for generating a plant characteristic data set containing plant characteristic data based at least in part on the plant profile data received from said plurality of receivers such that the plant characteristic data set may be used to measure the physical characteristics of the plant.

5

33. A computer program product according to Claim 32, wherein said sensor assembly is advanced along a row of plants including the plant and defining a row axis, the computer program product further comprising:

a third set of computer instructions for controlling said emitters to repeatedly
10 emit the signals at a selected rate, and wherein said second set of computer instructions further comprises a fourth set of computer instructions for generating a two-dimensional profile of the plant by compiling the data generated by said first set of computer instructions at a plurality of longitudinal points along the row axis; and
a fifth set of computer instructions for adding the generated two-dimensional
15 profile of the plant to the plant characteristic data set.

34. A computer program product according to Claim 32, further comprising:

a sixth set of computer instructions for generating a binary image based on the
20 plant characteristic data set;
a seventh set of computer instructions displaying the binary image to a user via said user interface; and
an eighth set of computer instructions for adding the binary image to the plant characteristic data set.

25

35. A computer program product according to Claim 32, wherein said sensor assembly further comprises a distance sensor, the computer program product further comprising:

a ninth set of computer instructions for locating a position of the portion of the
30 plant relative to said sensor assembly using said distance sensor; and
a tenth set of computer instructions for adding the located position of the portion of the plant to the plant characteristic data set.

36. A computer program product according to Claim 32, wherein said sensor assembly further comprises a multi-spectral device, the computer program product further comprising:

5 an eleventh set of computer instructions for capturing a multi-spectral image of the plants from a position above the plant so as to differentiate the plant from a plurality of surrounding materials; and

a twelfth set of computer instructions for adding the multi-spectral image to the plant characteristic data set.

10 37. A computer program product according to Claim 32, wherein said sensor assembly further comprises a locator device in communication with said computer device; the method further comprising:

a thirteenth set of computer instructions for transmitting a location data set from said locator device to said computer device to determine a location of the plant;
15 and

a fourteenth set of computer instructions for adding the location data set to the plant characteristic data set.

20 38. A computer program product according to Claim 33, wherein said sensor assembly is carried by a movable assembly having at least one axle and wherein said sensor assembly further comprises a shaft encoder operably engaged with said axle and in communication with said computer device, the computer program product further comprising:

a fifteenth set of computer instructions for transmitting a location data set from
25 said shaft encoder to said computer device to determine a distance along the row of plants; and

a sixteenth set of computer instructions for adding the location data set to the plant characteristic data set.

30 39. A computer program product according to Claim 32, wherein said sensor assembly further comprises a global positioning system device, the computer program product further comprising:

a seventeenth set of computer instructions for determining a position of the plant using a global positioning system; and

an eighteenth set of computer instructions for adding the determined position of the plant to the plant characteristic data set.

5

40. A computer program product according to Claim 32, wherein said computer device further comprises a memory device, the computer program product further comprising a nineteenth set of computer instructions for storing the plant characteristic data set of a known plant of interest in the memory device.

10

41. A computer program product according to Claim 40, further comprising a twentieth set of computer instructions for identifying the plant by comparing the generated plant characteristic data set with the stored plant characteristic data set of the known plant of interest.

15

42. A computer program product according to Claim 32, further comprising:

a twenty-first set of computer instructions for counting of a number of a plurality of plants for which a corresponding plurality of plant characteristic data sets are generated; and

20

a twenty-second set of computer instructions for storing the counted number of the plurality of plants.

43. A computer program product according to Claim 42, further comprising a twenty-third set of computer instructions for determining the number of the plurality of plants located in at least one physical unit based at least in part on the corresponding plurality of plant characteristic data sets.

25

44. A computer program product according to Claim 43, wherein the at least one physical unit is selected from the group consisting of:

a row;

an agricultural plot; and

combinations thereof.

30




Fig. 1




Fig. 2





Fig. 3

*Fig. 4*




Fig. 5




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 7A







Fig. 7B


Page 8/16

*Fig. 8*


Page 9/16

*Fig. 9*


Page 10/16

*Fig. 10*


Page 11/16

*Fig. 11*


Page 12/16

*Fig. 12*


Page 13/16

*Fig. 13*


Page 14/16

*Fig. 14*

Page 15/16

*Fig. 15*

Page 16/16

*Fig. 16*

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2006/029558

A. CLASSIFICATION OF SUBJECT MATTER
 INV. G01B11/24 A01B69/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G01B A01G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 2002 101770 A (KAWAMURA ELECTRIC INC) 9 April 2002 (2002-04-09) abstract	1-44
A	DE 42 20 913 C2 (BINDER JUERGEN [DE] BINDER JUERGEN DIPL ING FH [DE]) 5 January 1995 (1995-01-05) abstract	1-44



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

23 November 2006

Date of mailing of the international search report

30/11/2006

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Sonius, Michiel

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2006/029558

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
JP 2002101770 A	09-04-2002	NONE	
DE 4220913 C2	05-01-1995	DE 4220913 A1	05-01-1994