

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
21 February 2008 (21.02.2008)

PCT

(10) International Publication Number  
WO 2008/019885 A1(51) International Patent Classification:  
*G01C 21/32* (2006.01)    *G01C 21/26* (2006.01)

(74) Common Representative: EISENBERG, Jacob; Tom-Tom International B.V., Rembrandtplein 35, NL-1017 CT Amsterdam (NL).

(21) International Application Number:  
PCT/EP2007/007311

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date: 15 August 2007 (15.08.2007)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(25) Filing Language: English

**Published:**

(26) Publication Language: English

— with international search report

(30) Priority Data:

0616211.9                    15 August 2006 (15.08.2006)    GB  
60/901,309                    15 February 2007 (15.02.2007)    US


(71) Applicant (for all designated States except US): TOM-TOM INTERNATIONAL B.V. [NL/NL]; Rembrandtplein 35, NL-1017 CT Amsterdam (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GEELEN, Pieter [NL/NL]; TomTom International B.V., Rembrandtplein 35, NL-1017 CT Amsterdam (NL). JURGENS, Sven [NL/CA]; 100 St George Street, N3R 1V6 Brantford Ontario (CA). JONES, Rory [GB/NL]; Rapenburgerstraat 91hs, NL-1011 VL Amsterdam (NL).

*[Continued on next page]*

(54) Title: A METHOD OF GENERATING IMPROVED MAP DATA FOR USE IN NAVIGATION DEVICES



(57) Abstract: An end-user can input a correction to a map error, directly on the device. The device is then able to use the correction without external processing of the correction. Hence, it is no longer necessary for an end-user to simply report errors to the map vendor over a web link, then wait for that map vendor to verify the error, update its maps and finally supply the end-user with updates - a cycle that can take months and sometimes years to complete. Instead, the navigation device can use the correction immediately. End-users can also share corrections with other end-users and also with a shared remote server that aggregates, validates and distributes corrections.

WO 2008/019885 A1



---

- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

## A METHOD OF GENERATING IMPROVED MAP DATA FOR USE IN NAVIGATION DEVICES

### FIELD OF THE INVENTION

This invention relates to a method of generating improved map data for use in navigation devices. Navigation devices include GPS based electronic personal navigation devices.

### DESCRIPTION OF THE PRIOR ART

Map data for electronic navigation devices, such as GPS based personal navigation devices like the GO™ from TomTom International BV, comes from specialist map vendors such as Tele Atlas NV. This map data is specially designed to be used by route guidance algorithms, typically using location data from the GPS system. For example, roads can be described as lines – i.e. vectors (e.g. start point, end point, direction for a road, with an entire road being made up of many hundreds of such sections, each uniquely defined by start point/end point direction parameters). A map is then a set of such road vectors, data associated with each vector (speed limit; travel direction etc.) plus points of interest (POIs), plus road names, plus other geographic features like park boundaries, river boundaries etc, all of which are defined in terms of vectors. All map features (e.g. road vectors, POIs etc.) are typically defined in a co-ordinate system that corresponds with or relates to the GPS co-ordinate system, enabling a device's position as determined through a GPS system to be located onto the relevant road shown in a map and for an optimal route to be planned to a destination.

To construct this map database, Tele Atlas starts with basic road information from various sources, such as the Ordnance Survey for roads in England. It also has a large, dedicated team of vehicles driving on roads, plus personnel checking other maps and aerial photographs, to update and check its data. This data constitutes the core of the Tele Atlas map database. This map database is being continuously enhanced with geo-referenced data. It is then checked and published four times a year to device manufacturers like TomTom.

Despite the huge resources that go into updating and verifying these maps, the data for some geographic areas may be a year or more out of date.

In addition to the ongoing improvements described above, end-users can directly report map errors to Tele Atlas using Tele Atlas' web site. Device manufacturers like TomTom also capture and forward map error reports from their users in this way. These error reports are generally just in a free text format, so that considerable effort has to be expended in working out what the error really means and what exact location they relate to. Once verified as a real error, the appropriate correction is validated and then included in a future map release. The correction may eventually find itself in an end-user device a year or more after first being notified or, in some cases, not at all.

It is also known to store a 'trace' of a journey planned and completed using a GPS satellite navigation device (see for example the 'GPS track submission' functionality offered by ALK Technologies of Princeton, USA). This trace is a record of the complete route taken by a vehicle, using geo-coded data. The user can then send this trace data back to the device vendor; it is then used to improve the accuracy and completeness of the map database. For example, the precise position of a road or a turning may not be accurately captured on a map used by a device; the aggregated tracks for people taking that road or turning will enable a more accurate position to be determined; future map releases by the device vendor can incorporate the correction.

Reference may also be made to collaborative mapping projects, frequently called 'wikimaps'. Wikimaps do not however generate 'map data' as we define that term – i.e. map data that is suitable for route guidance algorithms to plot a route on a road system to a destination.

### **SUMMARY OF THE INVENTION**

The invention is map data suitable for use with an electronic navigation device, the map data being structured to (i) enable an end-user to input a correction to the map data, directly on the device; and (ii) to allow use of the correction without processing of the correction external to the device.

Hence, it is no longer necessary for an end-user to be restricted to reporting errors to the map vendor over a web link, then waiting for that map vendor to verify the error, update its maps

and supply the update – a cycle that can take months and sometimes years to complete. Instead, the end-user decides on a suitable correction and then inputs that correction directly into the navigation device.

In an implementation, the navigation device can actually use the correction without external processing – e.g. without processing or verification by the map vendor. Use of the correction by the device can, in relative terms, be ‘immediate’. The term ‘immediate’ should not be construed as instantaneously, but as simply meaning soon after the correction has been input. There can be intervening steps, such as the user verifying that the correction should be used, turning the device on and then off etc.

Inputting the correction automatically causes a new route to be calculated. Hence, imagine an end-user driving along a route that his navigation device has planned. The device tells him to take the next right turn. But a no-right turn sign has recently been placed at that junction. The end-user rapidly touches the touch screen controlled navigation device with his finger; this completely replaces the moving navigation map with the main menu of large, graphical icons. One menu item is labeled ‘Map Correction’. He touches this icon. This causes a new menu screen to be displayed, which includes the main types of map correction. One of them is the traffic sign for a ‘no-right turn’. He touches this icon. The device correlates this to the route instruction ‘turn right into x road’ which it had planned and stored. The device is programmed by the user touching the ‘no right –turn’ traffic icon to remove that turn from the planned route and to automatically plan a new route that does not include the right turn. It also adds a new data item to the node in the map data stored on the device defining the junction into road x, that there is no right turn into road x from the applicable connecting roads. This correction to the map data loaded onto the device will be automatically used by this device in future route planning. After the end-user returns home, he takes his navigation device and places it into a PC dock; this automatically opens an application on his PC that enables him to upload all the map corrections he has made on his device to a central server; likewise, the corrections made by the tens of thousands of other users driving on routes covered by maps loaded onto his device (e.g. whole of Europe; or whole of USA; etc) will be automatically downloaded to his device, so long as they meet trust or validity criteria defined by that end-user: for example, the end-user might only want map corrections actually validated by TomTom, or by users who

have become trusted users because of the quality of their map corrections. These third party map corrections are stored in the map database, which is, as noted above, structured to accommodate corrections alongside the original map data.

So for example, a node such as a turning into a road will have various fields associated with it. Pre-existing fields could include the name of the junction; any time-based turn restrictions etc. To implement the invention, one of the fields could be specifically for corrections from the user of the device. Another field could be for corrections downloaded to the device. These map corrections fields could also have multiple attributes, such as a unique ID number, or a number uniquely linked to the device itself, or the date of creation of the correction. Similarly, a road is defined as a vector in the map database; it is made up of numerous segments, joining each node (a node is typically a junction or change in direction of the road). Each segment will in the map database be associated with various fields, such as name, speed limit, direction etc. To implement the invention, each segment is augmented with further fields for map corrections input by the user.

Note that in the present invention, there is no need to capture an error as such at all; instead it is the correction as determined by an end-user that is captured. This invention is therefore predicated on the insight that merely getting end-users to capture and report map errors is not the solution to rapidly improving the quality of map data. Instead, this invention describes turning over the actual map updating process to the wider community of ordinary users. It may additionally be possible for an end-user to report errors in the normal way; for many years this has been possible directly onto navigation devices. An additional map error reporting feature in one implementation is that individual map errors, like individual map corrections, are uniquely identified to allow tracking and handling. In addition, each map error report, like each map correction, can be linked to a device ID; this allows errors and corrections from each user to be tracked and enables a history of errors and corrections for users (or their devices) to be built up. This in turn allows users with a history of early and accurate errors or corrections to be treated as 'trusted' or for their input to be prioritized in a validation process.

End-users are, as noted above, able to share their map corrections with other end-users: this implementation is called TomTom Map Share<sup>TM</sup>. Map Share leverages the very large

community of users of TomTom portable navigation devices and the huge number of journeys made by them every day using their TomTom navigation devices. This insight applies the concept of user-generated content (and related web 2.0 concepts) known from on-line communities such as youtube.com. But until now, this concept has not been applied to the digital map creation process.

It should be noted that the invention encompasses corrections to map data that is used in route guidance algorithms. Map data that is not used in route guidance algorithms as such may in addition be corrected; for example POIs may be added. However, since adding POIs to a device is known, that is not within the scope of the present invention. Adding or correcting POIs is merely then an additional correction that can be made; but that is not an inventive type of map correction.

In an implementation, the navigation device is a portable stand-alone GPS navigation device with route guidance capability, such as the GO or ONE series device from TomTom International BV, or any other kind of portable information device, such as a mobile telephone or PDA. But equally, it could be a device integrated into a vehicle, or a computing device such as a static desktop PC (including a laptop) running navigation software (which term includes mapping software which does not actually deliver dynamic route guidance but instead simply mapping – where the user is. Also, the navigation software could run locally on the client device or run on a server remote from the client device). The PC can then dock with a portable navigation device with a route guidance capability and transfer the corrections to the portable navigation device.

Typical features of such a navigation device are:

- A user interface allowing users to create corrections to a digitally stored map;
- A user interface that allows users to include or exclude map corrections from route calculations;
- A user interface that allows user to view their corrected map data on the digital map
- A set of correction categories that allow users to associate map corrections with one or more transportation types;

- The ability to share map corrections with other users, for example via a content aggregation service. Shared maps are available for use (e.g. by a route planning algorithm or map display engine) as soon as they are downloaded.

## BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described with reference to the accompanying drawings, in which:

**Figure 1** is the main error reporting screen displayed by a navigation device;

**Figure 2** is the screen shown that allows users to define the type of error they wish to capture and report;

**Figure 3** is a screen shot from a navigation device implementing the present invention; the screen shot shows a plan map view and a status bar running along the bottom of the display;

**Figure 4** is a screen shot from the navigation device implementing a 3-D view;

**Figure 5** is a screen shot from the navigation device showing a navigation menu;

**Figures 6A and 6B** are perspective views of the navigation device; and

**Figure 7** is a schematic view of the system architecture for the navigation device;

**Figure 8** is a block diagram of components in the navigation device;

**Figure 9** is a diagram of the electrical subassemblies in the **Figure 8** navigation device.

## DETAILED DESCRIPTION

The present invention will be described with reference to an implementation called Map Share. Map Share will allow users to fix and also to share and report map errors using GO personal navigation devices from TomTom International B.V. The user enters the correction (or map fix) into the navigation device. The map fix is then applied locally in the device to supplement the map data used by the device in routing and displaying roads, POIs etc. The map fix is immediately available. The map fix can be reported to a TomTom server by the device in a number of ways: the device may have an integral communications capability (e.g. wireless cellular system that can send data to the server), may be able to send data over a short range wireless link to a mobile telephone which in turn sends the data to the server, may be able to

dock with an internet connected PC that can communicate with the server, or may itself be that internet connected PC. The server can then aggregate all corrections from all users, validate corrections, and distribute the corrections to other users, and share the corrections with one or more map vendors.

When fully implemented, this feedback could replace map vendor updates as the primary mechanism for updating map data in TomTom products.

The scope of one implementation of Map Share is to provide user friendly, on-device tools allowing the user to:

- Block and un-block streets on their map
- Modify the traffic direction of streets on their map
- Add and modify street names on their map
- Modify speed limits of roads on their map

Hence, the corrections directly affect how the routing calculation algorithms operate – i.e. they are used when calculating a route to a destination. Map Share also allows the user to:

- Add safety camera locations to the map
- Share map corrections with other users
- Download map corrections from other users
- Create map error reports for large errors.

In addition to on-device corrections, the same correction features for all the above correction types can be made available using a desktop computer application that is capable of connecting to the device, e.g. in order to store corrections.

In addition to on-device features, improvements are possible to the existing TomTom map error reporting tool, which is web based:

- Map error reporting will be made easier to find within the TomTom Support Website
- Map error reporting tools will be added to the TomTom Home application
- Users will receive feedback on the map errors that they have reported.

- TomTom will be able to pre-prioritise errors before sending them to its map supplier, e.g. TeleAtlas.

As explained earlier, important features of the Map Share implementation are:

- to do map corrections, error reporting etc. *on the device*
- to make certain corrections take *immediate* effect (e.g. those meeting user-defined criteria)
- to allow users to exchange corrections with others

On a GO navigation device, this can be implemented by the device displaying a menu item '**Make changes to the map**', as shown in **Figure 1A**. The consequences of selecting this item are discussed below. There are 2 further menu items that will be described first.

First, the menu item '**Exchange Changes**' allows the user to initiate an upload of the user's own changes, and download other people's changes to the device. Upload can be via a mobile telephone with a GPRS wireless link that links to the GO device over a Bluetooth network or via an Internet connected PC that the GO device is docked with.

Secondly, the menu item '**Preferences About changes**' determines which changes to enable. Selecting this item can cause the device to display a menu screen, with check boxes for the user to indicate applicable types of changes to enable:

Which changes should be enabled:

- [x] your own changes
- [x] recent changes
- [ ] last year's changes / made on other maps
- [x] only if reported more than once
- [x] only from trusted sources

1365 of 2635 available changes enabled

If the user selects the '**Make changes to map**' icon by touching it, it takes the user to a submenu which offers INSTANT-EFFECT options to change the map – plus the option to REPORT an error (if it is not covered by self-action). These include, as shown in **Figure 1B**:

- Add/change street name: if a user selects this, then the device could, for example, display a list of names of streets currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode); the user could select the street to be re-named and then enter the new name via an on-screen keyboard.
- Block Street: if a user selects this, then the device could, for example, display a list of names of streets currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode); the user could select the street to be blocked.
- Change traffic direction (not shown): if a user selects this, then the device could, for example, display a list of names of streets currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode) together with the traffic direction; the user could select the street whose traffic direction is to be altered.
- Change speed limit: if a user selects this, then the device could, for example, display a list of names of streets currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode) together with applicable speed limits; the user could select the street whose street limit is to be altered and then select the appropriate new speed limit from a menu.
- Un-block street: if a user selects this, then the device could, for example, display a list of names of blocked streets currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode); the user could select the street to be unblocked.

In addition, it is possible, selecting the 'Edit/delete POI' icon to reach a deeper sub-menu with graphical options for the following:

Rename a POI

Move a POI

Add a POI to a category

Delete a POI

Re-categorize a POI

In each case, the device could, for example, display a list of names of POIs currently being displayed by the map (or that would be displayed if the device were in the normal navigation mode); the user could select the relevant POI and then edit or delete that POI. These POIs are typically those supplied by the map vendor but can include POIs downloaded by the user (e.g. speed cameras).

A further menu item is to 'Report other error'. This enables complaints, missing roads etc. to be reported. Typical functions will enable the user to pick a location, select from a list of typical issues, allow user to add free text commentary etc.

## Other features

- Users can create "private" fixes for their map and "shared" fixes that are also sent to TomTom for aggregation.
- Each map fix is stored independently
- All map fixes are highly compressible for OTA distribution
- All map fixes are HIGHLY secure (such that it is not possible to manually reverse engineer the format) to ensure that competitors cannot use fixes made on TomTom devices to correct their own maps.
- Fixes are stored in a map-independent form
  - Map fixes are preserved during map upgrades
  - Map fixes can be applied to maps from different vendors
- Map fixes can be automatically removed if the area related to the fix has changed in a new release of the map data (as in this case we assume that the map error has been fixed by the map supplier).
- Map fixes do NOT permanently modify the user's map data.
- Users can choose which kinds of changes they use (e.g. "use only my changes" or "use my changes and those from TomTom" or "use changes in a selected language").
- TomTom maintains map fix databases for each released map version (Note: users with new maps can receive fixes reported on older maps, but users of old maps will NOT be able to receive fixes reported on newer maps).
- TomTom creates an aggregation system so that map fixes and reports can be collected and shared with other users.

- TomTom creates a “trust” system so that the validity or credibility of map fixes and reports can be assessed. Users who report good errors on a regular basis may become “trusted”, and their fixes are offered to all users without the need for validation. These user may also be asked to validate fixes submitted by other users.
- TomTom endorses fixes sent by users (once they have been validated).

**Figure 2** shows schematically the core software modules deployed in a navigation device implementing the invention. The display 21 is a touch screen display that the user enters a destination address into in the conventional manner. That address data input is handled by the UI module 22 and sent to the navigation/route planning module 23. Route planning module 23, taking a GPS feed from GPS module 24, plans a route using map data from the encrypted, compressed map data that the device was shipped with (or was otherwise supplied from the map vendor, such as Tele Atlas). The present invention is then implemented as follows: the user enters a map correction as and when needed, using a touch screen interaction, touching large graphical icons, as exemplified by **Figures 1A** and **1B**, into display 21. The UI module 22 captures the map fix and sends it to a map fix store 26. As soon as the map fix is in the map fix 26 store, it is made available to the route planning module 22 and the UI module 22. If the map fix requires re-planning of even the current route being driven, then that will happen automatically (if the user configures that option). For example, the device might plan a route that requires the user to turn into a street: when the turning is approached, the user finds that it has recently been made a ‘no entry’ street. The user can enter an appropriate map correction: a new route, taking into account the no entry street, is then immediately planned and appropriate route guidance given. Likewise, if the user plans a completely new route to another destination, the new route will also take the map fix into account. If the map fix should affect how the map should appear (for example, re-naming a road, showing a new POI, such as a speed camera), then that new appearance will be immediately present. Automatic use of the correction is not mandatory though; some users may prefer for route calculation etc. to exclude map corrections.

**Appendix 1** describes a typical device that can implement the present invention. **Appendix 2** are the high level requirements for Map Share.

## Appendix 1

The present invention can be implemented in an integrated navigation device from TomTom B.V. called GO. GO deploys navigation software called Navigator (or Navcore) and has an internal GPS receiver; Navigator software can also run on a touch screen (i.e. stylus controlled) Pocket PC powered PDA device, such as the Compaq iPaq. It then provides a GPS based navigation system when the PDA is coupled with a GPS receiver. The combined PDA and GPS receiver system is designed to be used as an in-vehicle navigation system.

The invention may also be implemented in any other arrangement of navigation device, such as one with an integral GPS receiver/computer/display, or a device designed for non-vehicle use (e.g. for walkers) or vehicles other than cars (e.g. aircraft). The navigation device may implement any kind of position sensing technology and is not limited to GPS; it can hence be implemented using other kinds of GNSS (global navigation satellite system) such as the European Galileo system. Equally, it is not limited to satellite based location/velocity systems but can be deployed using ground-based beacons or any other kind of system that enables the device to determine its geographic location.

Navigator software, when running on a PDA, results in a navigation device that causes the normal navigation mode screen shown in **Figure 3** to be displayed. This view provides driving instructions using a combination of text, symbols, voice guidance and a moving map. Key user interface elements are the following: a 2-D map 1 occupies most of the screen. The map shows the user's car and its immediate surroundings, rotated in such a way that the direction in which the car is moving is always "up". Running across the bottom quarter of the screen is the status bar 2. The current location of the device, as the device itself determines using conventional GPS location finding and its orientation (as inferred from its direction of travel) is depicted by an arrow 3. The route calculated by the device (using route calculation algorithms stored in device memory as applied to map data stored in a map database in device memory) is shown as darkened path 4 superimposed with arrows giving the travel direction. On the darkened path 4, all major actions (e.g. turning corners, crossroads, roundabouts etc.) are schematically

depicted by arrows 5 overlaying the path 4. The status bar 2 also includes at its left hand side a schematic 6 depicting the next action (here, a right turn). The status bar 2 also shows the distance to the next action (i.e. the right turn -- here the distance is 220 meters) as extracted from a database of the entire route calculated by the device (i.e. a list of all roads and related actions defining the route to be taken). Status bar 2 also shows the name of the current road 8, the estimated time before arrival 9 (here 2 minutes and 40 seconds), the actual estimated arrival time 10 (11.36am) and the distance to the destination 11 (1.4Km). The GPS signal strength is shown in a mobile-phone style signal strength indicator 12. A 3-D map view is also possible, as shown in **Figure 4**.

If the user touches the screen 13, then a navigation screen main menu (not shown) is displayed; from this menu, other core navigation functions within the Navigator application can be initiated or controlled. Allowing core navigation functions to be selected from a menu screen that is itself very readily called up (e.g. one step away from the map display to the menu screen) greatly simplifies the user interaction and makes it faster and easier.

The area of the touch zone which needs to be touched by a user is far larger than in most stylus based touch screen systems. It is designed to be large enough to be reliably selected by a single finger without special accuracy; i.e. to mimic the real-life conditions for a driver when controlling a vehicle; he or she will have little time to look at a highly detailed screen with small control icons, and still less time to accurately press one of those small control icons. Hence, using a very large touch screen area associated with a given soft key (or hidden soft key, as in the centre of the screen 13) is a deliberate design feature of this implementation. Unlike other stylus based applications, this design feature is consistently deployed throughout Navigator to select core functions that are likely to be needed by a driver whilst actually driving. Hence, whenever the user is given the choice of selecting on-screen icons (e.g. control icons, or keys of a virtual keyboard to enter a destination address, for example), then the design of those icons/keys is kept simple and the associated touch screen zones is expanded to such a size that each icon/key can unambiguously be finger selected. In practice, the associated touch screen zone will be of the order of at least 0.7 cm<sup>2</sup> and will typically be a square zone. In normal navigation mode, the device displays a map. Touching the map (i.e. the touch sensitive display) once (or twice in a different implementation) near to the screen centre (or any part of the

screen in another implementation) will then call up either directly (i.e. the next level down) or indirectly (i.e. two or more levels down) a navigation menu (see **Figure 5**) with large icons corresponding to various navigation functions, such as the option to calculate an alternative route, and re-calculate the route so as to avoid the next section of road (useful when faced with an obstruction or heavy congestion); or recalculate the route so as to avoid specific, listed roads.

The actual physical structure of the device is fundamentally different from a conventional embedded device in terms of the memory architecture (see system Architecture section below). At a high level it is similar though: memory stores the route calculation algorithms, map database and user interface software; a microprocessor interprets and processes user input (e.g. using a device touch screen to input the start and destination addresses and all other control inputs) and deploys the route calculation algorithms to calculate the optimal route. ‘Optimal’ may refer to criteria such as shortest time or shortest distance, or some other user-related factors.

More specifically, the user inputs his start position and required destination in the normal manner into the Navigator software running on the PDA using a virtual keyboard. The user then selects the manner in which a travel route is calculated: various modes are offered, such as a ‘fast’ mode that calculates the route very rapidly, but the route might not be the shortest; a ‘full’ mode that looks at all possible routes and locates the shortest, but takes longer to calculate etc. Other options are possible, with a user defining a route that is scenic – e.g. passes the most POI (points of interest) marked as views of outstanding beauty, or passes the most POIs of possible interest to children or uses the fewest junctions etc.

Roads themselves are described in the map database that is part of Navigator (or is otherwise accessed by it) running on the PDA as lines – i.e. vectors (e.g. start point, end point, direction for a road, with an entire road being made up of many hundreds of such sections, each uniquely defined by start point/end point direction parameters). A map is then a set of such road vectors, plus points of interest (POIs), plus road names, plus other geographic features like park boundaries, river boundaries etc, all of which are defined in terms of vectors. All map features (e.g. road vectors, POIs etc.) are defined in a co-ordinate system that corresponds or

relates to the GPS co-ordinate system, enabling a device's position as determined through a GPS system to be located onto the relevant road shown in a map.

Route calculation uses complex algorithms that are part of the Navigator software. The algorithms are applied to score large numbers of potential different routes. The Navigator software then evaluates them against the user defined criteria (or device defaults), such as a full mode scan, with scenic route, past museums, and no speed camera. The route which best meets the defined criteria is then calculated by a processor in the PDA and then stored in a database in RAM as a sequence of vectors, road names and actions to be done at vector endpoints (e.g. corresponding to pre-determined distances along each road of the route, such as after 100 meters, turn left into street x).

**Figures 6A and 6B** are perspective views of an actual implementation of a navigation device. The navigation device is a unit that includes display, internal GPS receiver, microprocessor, power supply and memory systems. The device sits on an arm, which itself is secured to the car dashboard using a large suction cup.

### System Architecture

In contrast to conventional embedded devices which execute all the OS and application code in place from a large mask ROM or Flash device, an implementation of the present invention uses a new memory architecture. **Figure 7** schematically depicts the device. The device, indicated generally at 51, includes conventional items such as a microprocessor 56, power source 57, display and related drivers 58. In addition, it includes a SD card reader 53; a SD card 52 is shown slotted into position. The device 51 has internal DRAM 54 and XIP Flash 55 and.

The device hence uses three different forms of memory:

1. A small amount of internal XIP (eXecute In Place) Flash ROM 55. This is analogous to the PC's BIOS ROM and will only contain a proprietary boot loader, E<sup>2</sup> emulation (for UID and manufacturing data) and splash screen bit maps. This is estimated to be 256 KB in size and would be on a slow 8 bit wide SRAM interface.

2. The main system RAM (or DRAM) memory 54, this is analogous to the PC's main memory (RAM). This will be where all the main code executes from as well as providing the video RAM and workspace for the OS and applications. **Note:** No persistent user data will be stored in the main system RAM (like a PC) i.e. there will be no "Ram drive". This RAM will be exclusively connected to a 32bit 100MHz synchronous high-speed bus.
3. Non-volatile storage, analogous to the PC's hard disk. This is implemented as removable NAND flash based SD cards 52. These devices do not support XIP. All the OS, application, settings files and map data will be permanently stored on SD cards

On boot up the proprietary boot loader 55 will prompt for the user to insert the supplied SD card 52. When this is done, the device will copy a special system file from the SD card 52 into RAM 54. This file will contain the Operating System and navigation application. Once this is complete control will be passed to the application. The application then starts and access non-volatile data e.g. maps from the SD card 52.

When the device is subsequently switched off, the RAM 54 contents is preserved so this boot up procedure only occurs the first time the device is used.

## GO product specification

### Introduction

GO is a stand-alone fully integrated personal navigation device. It will operate independently from any connection to the vehicle.

### Target markets

GO is intended to address the general personal navigation market. In particular it is designed to extend the market for personal navigation beyond the "early adopter" market. As such it is a complete stand-alone solution; it does not require access to a PC, PDA or Internet connection. The emphasis will be on completeness and ease of use.

Although GO is a complete personal navigation solution it is primarily intended for in vehicle use. The primary target market is anybody who drives a vehicle either for business or pleasure.

To successfully address this market GO must satisfy the following top-level requirements:

1. Acceptable price point - Appropriate compromise between product features and cost.
2. Simplicity – Installation and operation of GO will be simple and intuitive, all major functions should be accomplished by an average non PC-literate user without recourse to the product manual.
3. Flexibility – All map data and operating programs will be supplied on plug in memory cards. The device can easily be extended to cover different locals.
4. Reliability – Although in-car navigation systems are not considered safety critical components users will come to rely on GO. It will be engineered to all relevant automotive environmental standards. In addition it will be tolerant to short GPS coverage outages.

### **Channels**

- Consumer electronics retail outlets
- Automotive accessory outlets
- Specialist car accessory fitting garages

### **Product summary**

GO is an in-vehicle personal navigation device. It is designed as an appliance, that is, for a specific function rather than a general purpose one. It is designed for the consumer after-sales automotive market. It will be simple to use and install by the end user, although a professional fitting kit will be optionally supplied.

The principal features are:

- Built on standard commodity PocketPC 2002 components
- Standard PocketPC 3.5" 1/4VGA transreflective TFT LCD display mounted in landscape orientation
- ROMless soft-boot memory architecture
- Highly integrated ARM9 200MHz CPU
- SD card memory slot for application and map data storage
- Integrated GPS receiver and antenna
- Integrated two axis accelerometer for simple dead reckoning

- Power, audio, debug and external GPS antenna connections made through docking connector on base of unit
- Embedded Linux OS with no GUI layer, application provides its own UI
- Very simple touch screen UI optimised for finger use
- High quality integrated speaker for voice instructions
- Internal rechargeable Li-Ion battery giving at least five hours of continuous operation

### **Operating System**

GO will use a customised version of embedded Linux. This will be loaded from an SD card by a custom boot-loader program which resides in Flash memory

### **Hard buttons**

GO will have only one hard button, the power button. It is pressed once to turn on or off GO. The UI will be designed so that all other operations are easily accessible through the pen based UI.

There will also be a concealed hard reset button.

### **Architecture**

GO architecture is based around a highly integrated single chip processor designed for mobile computing devices. This device delivers approximately 200 MIPS of performance from an industry standard ARM920T processor. It also contains all the peripherals required excluding the GPS base-band. These peripherals include DRAM controller, timer/counters, UARTs, SD interface and LCD controller.

The main elements of this architecture are:

- Microprocessor running at 200MHz
- 32MB or 64MB of fast synchronous DRAM (SDRAM) with low power self refresh.  
Arranged as two devices on a 32 bit wide 100MHz bus
- SD card interface for all non-volatile storage including the OS (No RAM drive)
- Native (bare metal) boot loader stored in 256KB of NOR Flash. This Flash device will contain a boot sector which is write protected to store protected data such as unique product ID's and manufacturing data.
- Debug UART (RS232 3V levels) connected to the docking connector
- USB client for PC connectivity

- Integrated GPS receiver
- Integrated two axis accelerometer
- Optional integrated Bluetooth transceiver for PDA and mobile phone connectivity
- High quality audio through I<sup>2</sup>S codec and amplifier

Figure 8 is the GO block diagram.

### Power management

GO will be powered from an integrated Li-Ion 2200 mAH rechargeable battery. This battery can be charged, and the device powered (even if the battery contains no charge) from an externally supplied +5V power source. This external +5V power source is supplied via the docking connector or a DC jack socket.

This +5V supply will be generated from the vehicle's main supply rail or from a mains adapter externally. The device will be turned on and off by a single button. When the device is turned off the DRAM contents will be preserved by placing the RAM in self-refresh so that when switched on GO will resume from where it was switched off. There will also be a wake-up signal available through the docking connector, this can be used to auto-switch on GO when the vehicle ignition is switched on.

There will also be a small hidden reset switch.

### System Memory architecture

In contrast to conventional embedded devices which execute all the OS and application code in place from a large mask ROM or Flash device, GO will be based on a new memory architecture which is much closer to a PC.

This will be made up of three forms of memory:

4. A small amount of XIP (eXecute In Place) Flash ROM. This is analogous to the PC's BIOS ROM and will only contain a proprietary boot loader, E<sup>2</sup> emulation (for UID and manufacturing data) and splash screen bit maps. This is estimated to be 256 KB in size and would be on a slow 8 bit wide SRAM interface.
5. The main system memory, this is analogous to the PC's main memory (RAM). This will be where all the main code executes from as well as providing the video RAM and workspace for the OS and applications. **Note:** No persistent user data will be stored in the main system RAM (like a PC) i.e. there will be no "Ram drive". This RAM will be

exclusively connected to a 32bit 100MHz synchronous high-speed bus. GO will contain two sites for 16 bit wide 256/512Mbit SDRAM's allowing memory configurations of 32MB (16 bit wide) 64MB 32 bit wide and 128 MB (32 bit wide).

6. Non-volatile storage, analogous to the PC's hard disk. This is implemented as removable NAND flash based SD cards. These devices do not support XIP. All the OS, application, settings files and map data will be permanently stored on SD cards

#### **Audio**

A 52 mm diameter speaker is housed in GO to give good quality spoken instructions. This will be driven by an internal amplifier and audio codec. Audio line out will also be present on the docking connector.

#### **SD Memory slot**

GO will contain one standard SD card socket. These are used to load system software and to access map data.

#### **Display**

GO will use a transreflective 3.5" TFT backlit display. It will be a 'standard' 1/4VGA display as used by PocketPC PDA's. It will also contain a touch panel and bright CCFL backlight.

#### **Power supplies**

##### **Power supply – AC adapter socket**

4.75V to 5.25V (5.00V +/- 5%) @ 2A

##### **Power supply – Docking connector**

4.75V to 5.25V (5.00V +/- 5%) @ 2A

#### **Variants**

It shall be possible to assemble and test the following variants of GO:

##### **Standard (Bluetooth depopulated, 32Mbyte RAM)**

In the Standard variant the Bluetooth function is not populated, and 32 Mbytes RAM is fitted.

##### **Bluetooth option (Future variant)**

The product design should include Bluetooth although it is not populated in the standard variant to minimise BOM cost. The design should ensure that all other functions (including GPS RF performance) operate without degradation when the Bluetooth function is operating.

##### **64Mbyte RAM option (Future variant)**

The product design should ensure it is possible to fit 64Mbyte RAM instead of 32Mbyte.

#### **Subassemblies**

GO consists of the following electrical subassemblies, shown in **Figure 9**.

### RF cable

The RF cable feeds the RF signal from an external GPS antenna (which connects to GO via the RF docking connector) to the RF PCB where the GPS module is situated.

External connectors

### Docking Connectors

Two Docking Connectors provide an interface to external Docking Stations.

#### *Docking Connector #1 pinout*

Pin	Signal	Dir	Type	Description
1	GND	-	-	Signal and power GND
2	GND	-	-	
3	DOCKSNS1	I/P	PU	Docking Station Sense [0,1] – These signals are connected to pull-up resistors within the unit. The Docking Station pulls either or both of these signals to GND to indicate the presence and type of Docking Station.
4	DOCKSNS0	I/P	PU	
5	AUDIOL	O/P		Audio line outputs (Left and Right) to connect to car audio system.
6	AUDIOR	O/P		
7	MUTE	O/P	O/D	The unit pulls this line to GND to signal the car audio system to mute itself while the unit is issuing a voice command.
8	IGNITION	I/P	PD	Ignition sense.
9	DOCKPWR	I/P	PWR	+5V power from the Docking Station to simultaneously power the unit and charge the battery.
10	DOCKPWR	I/P	PWR	

PWR Power connection  
 O/D Open-Drain output

PU Pull-Up resistor within the unit  
 PD Pull-Down resistor within the unit

***Docking Connector #2 pinout***

Pin	Signal	Dir	Type	Description
1	TXD	O/P	UART	3V logic level UART signals
2	RXD	I/P	UART	
3	RTS	O/P	UART	
4	CTS	I/P	UART	
5	GND	-	PWR	
6	nTRST	I/P	JTAG	CPU JTAG signals for test and configuration
7	TMS	I/P	JTAG	
8	TCK	I/P	JTAG	
9	TDI	I/P	JTAG	
10	TDO	O/P	JTAG	

**RF Docking Connector**

The RF Docking Connector allows connection of an external active GPS antenna via a Docking Station.

**AC adapter socket**

The AC adapter socket allows power to be supplied from a low cost AC adapter or CLA (Cigarette Lighter Adapter).

**USB connector**

The USB connector allows connection to a PC by means of a standard mini USB cable.

**SD card socket**

A hard locking SD card socket suitable for high vibration applications supports SDIO, SD memory and MMC cards.

(Although GO provides hardware support for SDIO, software support will not be available at the time of product introduction)

**Processor**

The processor is the ARM920T based SOC (System on chip) operating at approx 200Mhz.

**RAM**

GO will be fitted with RAM to the following specification:

Type	SDRAM with low-power refresh (“mobile” SDRAM)
Total memory	32 Mbyte (standard) or 64 Mbyte (future option)
Bus width	32-bit
Minimum speed	100Mhz
Maximum self refresh current	500 $\mu$ A per device
Configuration	2 x 16-bit wide CSP sites

**Flash Memory**

GO will be fitted with a minimum of 256kbyte of 16-bit wide Flash Memory to contain the following:

- Boot loader code to enable loading of O/S from SD card
- Factory set read-only protected manufacturing parameters (e.g. manufactured date) and unique ID (E2PROM emulation)
- User specific settings (E2PROM emulation)

The following devices can be used depending on price and availability.:

**GPS internal antenna**

The GPS internal antenna is attached directly to the RF PCB.

**GPS external (active) antenna switching**

When an external antenna is connected via the RF Docking Connector, the GPS antenna source is automatically switched to the external antenna.

**Accelerometer**

A solid state accelerometer is connected directly to the processor to provide information about change of speed and direction.

**Auxiliary functions**

## **Ignition synchronization**

### *Ignition wakeup*

A rising edge on the Docking Station IGNITION signal will wakeup the unit. The IGNITION signal may be connected to a 12V or 24V vehicle battery.

### *Ignition state monitoring*

The state of the Docking Station IGNITION signal is detected and fed to a GPIO pin to allow software to turn off the unit when the ignition signal goes low.

## **Standard peripherals**

The following peripherals will be included as standard with GO.

- Simple docking shoe. Mounts GO and allows charging through a DC jack. No other connectivity is included in the simple dock.
- Cigarette lighter power cable connecting to GO through the DC jack socket or simple docking shoe.
- Mini USB cable for PC connectivity
- Universal mains adapter for connection to DC Jack socket

## **Optional peripherals**

The following optional peripherals will be available at or after the time of launch of GO

- Active antenna kit. Contains a GPS active antenna and a docking shoe with GPS RF connector and cable fitted. For self installation when an external antenna is required.
- Professional vehicle docking kit. For fitting by professional installation only. Allows direct connection to vehicle supply, audio system and active antenna via a vehicle interface box.

## Appendix 2

### Map Share High Level Requirements (0.40)

#### Introduction

TomTom strives to offer the most accurate map data available to its customers. Currently, map updates are made by TomTom map suppliers, and TomTom is able to feed back errors in some maps via a reporting tool to Tele Atlas. This situation is far from ideal as it may take several map revisions before a map error is fixed, and all fixes made as a result of TomTom error reports are also shared with competitors. In order for TomTom to offer map updates in a timelier manner, a new system of map error reporting and correction is required. These improvements will be delivered through the Map Share project.

#### 1.1 Scope

This document describes high level requirements of the Map Share project.

## 2 High Level Requirements

This section describes the high level requirements of Map Share.

### 2.1 User Requirements

This section describes the user requirements for Map Share.

#### 2.1.1 *Map Corrections*

Some map errors can be corrected immediately by the user. This section describes the user requirements relating to map corrections.

##### 2.1.1.1 On-Device Map Corrections

The user shall be able to make map corrections on their NavCore device.

##### 2.1.1.2 TomTom Home Map Corrections

The user shall be able to make map corrections within the Navigator control of the TomTom Home application.

### ***2.1.2 Map Correction Types***

This section describes the user requirements relating to the types of map correction that can be made.

#### **2.1.2.1 Add Safety Camera**

The user shall be able to add the locations of safety cameras on the map.

Note: it is already possible to report safety cameras in this way, however, the implementation must be adjusted to simplify the process of reporting, make it consistent with other map corrections and allow users to see the safety cameras that they have reported immediately.

#### **2.1.2.2 Block Roads**

The user shall be able to block roads on the map.

#### **2.1.2.3 Un-Block Roads**

The user shall be able to un-block roads on the map.

#### **2.1.2.4 Modify Traffic Direction**

The user shall be able to modify the traffic direction properties of roads on the map. Specifically the user shall be able to:

- Change a two-way road into a one-way road (in either direction)
- Change a one-way road to a two-way road
- Change the direction of a one-way road to the other direction.

#### **2.1.2.5 Add Road**

The user shall be able to add a road (consisting of one or more nodes) on the map.

#### **2.1.2.6 Connect Roads**

The user shall be able to connect 2 points on the map and define this new link as a new road.

#### **2.1.2.7 Add Street Names**

The user shall be able to add street names to un-named roads on the map.

#### **2.1.2.8 Modify Street Names**

The user shall be able to modify the names of roads on the map.

### **2.1.2.9 Modify Speed Limits**

The user shall be able to modify the maximum speed of roads on the map.

### **2.1.3 *Availability of On-Device Corrections***

Once map corrections are present on the NavCore device, they must be made available to the user. This section describes the user requirements relating to the availability of on-device corrections.

#### **2.1.3.1 Availability of Private Corrections**

The user shall be able to use private corrections as soon as they are recorded.

#### **2.1.3.2 Availability of Public Corrections**

The user shall be able to use public corrections as soon as they have been downloaded to the device.

### **2.1.4 *Using Map Corrections***

As some map corrections may have been made by other TomTom owners, the user must be able to select which corrections to use when calculating routes. This section describes the user requirements relating to the use of map corrections on the user's device.

#### **2.1.4.1 Safety Camera Warnings**

The user shall be able to choose whether to receive warnings for private and/or public reported safety cameras.

#### **2.1.4.2 Use of Private Map Corrections**

The user shall be able to use or ignore their Private map corrections whenever they plan a route that includes a correction.

#### **2.1.4.3 Use of Public Map Corrections**

The user shall be able to use or ignore their Public map corrections whenever they plan a route that includes a correction.

#### **2.1.4.4 Automatic Map Correction Use**

The user shall be able to configure their device such that private and/or public corrections from one or more categories are automatically included within route calculations. The user shall be informed that they are using corrections. The user might receive an audible or visual indication when corrections effecting route planning are in use. The user might need to agree to using of map corrections e.g. by pressing an appropriate button on the PND.

#### **2.1.4.5 Route Recalculation**

The user shall be able to recalculate routes to include or exclude map corrections.

#### **2.1.4.6 Map Correction Removal**

The user shall be able to edit or remove a map correction from their device.

### **2.1.5 *Map Error Reporting***

Some map errors are too complicated or large in scale to make corrections on the device itself. These errors need to be reported to TomTom, so that we (or our map suppliers) can take corrective action. This section describes the user requirements relating to map error reporting.

#### **2.1.5.1 On-Device Map Error Reporting**

The user shall be able to create map error reports on their device and upload these to the TomTom PLUS server.

Note: the user shall NOT be able to create map error reports while driving.

Note: it would be acceptable to offer users a list of pre-defined error types when creating error reports on the device.

#### **2.1.5.2 TomTom Home Map Error Reporting**

The user shall be able to create map error reports within the Navigator control of the TomTom Home and upload these to the TomTom PLUS server.

Note: the user should NOT have to register as a TomTom customer in order to create a map error report.

### **2.1.5.3 Importing On-Device Error Reports in TomTom Home**

The user shall be able to import map error reports captured on their device to the TomTom Home application. The user shall be able to edit these reports and then upload them to the TomTom PLUS server.

### **2.1.5.4 Map Error Report Feedback**

The user shall be given feedback regarding their map error reports.

## **2.1.6 *Automatic Map Error Identification***

In some circumstances it is possible for the TomTom device to suggest corrections to the user, based on their use of the product. This section describes the user requirements relating to automatic identification of map errors.

### **2.1.6.1 Automatic Road Block Suggestion**

The user shall be prompted to block roads that they chose to avoid within route plans on multiple occasions.

### **2.1.6.2 Automatic Road Creation Suggestion**

The user shall be prompted to add a road on the map if they drive through a map area that is not marked as a road on multiple occasions.

### **2.1.6.3 Automatic Name Road Suggestion**

The user shall be prompted to add a name to unnamed roads on the map if they plan routes to such a road on multiple occasions.

### **2.1.6.4 Automatic Modify Speed Limit Suggestion**

The user shall be prompted to modify the speed limit of a road if they drive along it at a significantly different speed from that stated in the map data on multiple occasions.

## **2.1.7 *Map Correction Sharing***

Users of Map Share may wish to share their corrections with other TomTom owners. This section describes the user requirements relating to the user's ability to share map corrections with other TomTom owners.

#### **2.1.7.1 Private Map Corrections**

The user shall be able to create corrections for their personal use only. These corrections shall NOT be sent to the TomTom PLUS server.

#### **2.1.7.2 Public Map Corrections**

The user shall be able to create corrections that are shared with other TomTom owners. These corrections shall be uploaded to the TomTom PLUS server and made available to other Map Share users.

#### **2.1.7.3 Public Map Correction Community Categorisation**

The user shall be able to categorise their public map corrections according to the user community for which it is applicable. The following community categories shall be made available:

- All users
- All motorists
- Heavy goods vehicle drivers
- Motorcyclists
- Limited speed vehicle drivers
- Pedestrians
- Bicycles

Other community categories are also possible, such as categories according to language or region.

#### **2.1.7.4 Trusted User Status**

The user shall be able to acquire “trusted user” status, based upon the number and quality of map corrections that they upload.

#### **2.1.7.5 Map Fix Information**

The user shall be informed if they attempt to report a map correction that has been corrected in a newer version of the map data that they are using. The user shall also be informed how they can purchase the updated map.

### ***2.1.8 Map Correction Retrieval***

In order to use public map corrections the user must retrieve them from the TomTom PLUS server. This section describes the user requirements relating to map correction retrieval.

#### **2.1.8.1 Public Map Correction Retrieval**

The user shall be able to download public map corrections from the TomTom PLUS server to their device, and to the TomTom Home application.

#### **2.1.8.2 Public Map Correction Community Category Retrieval**

The user shall be able to download public map corrections from one or more community categories.

Note: Public correction community categories are defined in section 2.1.7.3.

#### **2.1.8.3 Public Map Correction Source Category Retrieval**

The user shall be able to download public map corrections from one or more community source categories.

Note: Public correction source categories are defined in section 2.2.1.5.

#### **2.1.8.4 Public Map Correction Supplier Category Retrieval**

The user shall be able to download public map corrections from one or more map supplier source categories. A supplier category shall be provided for each TomTom map supplier.

#### **2.1.8.5 Public Map Correction Location Category Retrieval**

The user shall be able to download public map corrections from one or more location categories.

Note: The following categories shall be available:

- All maps
- All maps on device
- Currently loaded map on device

## 2.2 Technical Constraints

Some features within Map Share must be implemented in a specific way in order to address the user's requirements and protect TomTom's interests. This section describes all known technical constraints placed upon the V1 scope of Map Share.

### 2.2.1 *Public Map Correction Management*

In order to allow users to make informed decisions relating to public map corrections, Map Share must manage these corrections. This section describes the constraints relating to map correction categorisation.

#### 2.2.1.1 **Map Correction Aggregation**

TomTom shall aggregate all public map corrections sent to the TomTom PLUS server.

#### 2.2.1.2 **Map Correction Analysis**

Public map corrections shall be analysed in order to assess their source, and their validity such as applicability and trustworthiness.

#### 2.2.1.3 **Map Correction Distribution**

TomTom shall distribute all public map corrections to Map Share users upon request.

#### 2.2.1.4 **Map Correction Removal**

TomTom shall assess the applicability of each map correction with respect to each map supplied to users. If a map correction is found not to be applicable for a given map then it shall be removed from the aggregated map corrections and NOT distributed to users of this map.

#### 2.2.1.5 **Map Correction Source Categories**

Map corrections held on the TomTom PLUS server shall be categorised by source so that the user can be informed of the relative trustworthiness of the correction's source.

##### 2.2.1.5.1 *TomTom Endorsement*

TomTom shall be able to endorse specific map corrections and these shall be represented to the user in a specific category.

#### ***2.2.1.5.2 Single User Reports***

Map corrections that have been reported by a single user shall be represented to other users in a specific category.

#### ***2.2.1.5.3 Multiple User Reports***

Map corrections that have been reported by more than one user shall be represented to other users in specific categories. Specifically, the following categories shall be represented:

- 2 – 5 user reports
- More than 5 user reports

#### ***2.2.1.5.4 Trusted User Reports***

Map corrections that have been reported by trusted users shall be represented to other users in a specific category.

#### ***2.2.1.5.5 Community Endorsement***

Map Share users shall be able to endorse map corrections made by other TomTom owners and evidence of these endorsements shall be represented to the user.

### ***2.2.2 Data Format***

In order to gain (and maintain) a competitive advantage from Map Share, it is imperative that map correction data is held in a structured, re-usable and secure way. This section describes the constraints relating to security.

#### ***2.2.2.1 Unique Identification***

Each map correction shall be uniquely identified.

#### ***2.2.2.2 Time Stamp***

Each map correction captured on the device shall be time stamped with the time at which it was input and/or reported.

### **2.2.2.3 Modularity**

Each map correction shall be stored in a form that allows it to be applied to the map independently of all other map corrections (i.e. NavCore shall be able to decide on a per-correction basis whether the correction should be applied to the map and represented to the user).

### **2.2.2.4 Non-Permanent Modification**

Map corrections shall NOT make a permanent modification to the user's map data.

### **2.2.2.5 Data Compression**

Map corrections shall be highly compressible to allow fast and cheap distribution over wireless networks.

### **2.2.2.6 Data Encryption**

Map corrections shall be highly encrypted such that it is not possible for the data format to be reverse engineered.

### **2.2.2.7 Data Integrity**

Map corrections shall be stored in such a way that they are retained though a map upgrade process.

### **2.2.2.8 Future Map Version Compatibility**

Map corrections shall be compatible with future map versions, such that corrections made on older versions of a map can be applied to the latest version.

### **2.2.2.9 Previous Map Version Incompatibility**

Map corrections shall NOT be compatible with previous map versions. It shall NOT be possible to apply a map correction made on the current map version with a previous map version.

### **2.2.2.10 Map Supplier Independence**

Map corrections shall be independent of map supplier, such that map corrections can be applied to maps from different suppliers.

### **2.2.2.11 Tele Atlas API Compatibility**

Map corrections shall be stored in a format that is compatible with the Tele Atlas map reporting API such that TomTom is capable of sending correctly formatted reports to Tele Atlas if it wishes to do so.

### **2.2.3 *On-Device Map Correction Handling***

In order to ensure that map corrections are correctly handled on the user's device, certain rules must be applied. This section describes the constraints relating to on-device map correction handling.

#### **2.2.3.1 Automatic Map Correction Omission**

Map corrections created on previous map versions shall be checked to see if they are applicable to the currently loaded map on the user's device. Map corrections that are not applicable shall NOT be used within route calculations.

### **2.2.4 *Map Error Report Management***

In order to manage map error reports in a more effective manner, TomTom must implement method for aggregating and prioritising error reports. This section describes the constraints relating to map error report management.

#### **2.2.4.1 Map Error Report Format**

All map error reports shall be created in a format that is compatible with the Tele Atlas map error reporting API.

#### **2.2.4.2 Map Error Report Aggregation**

TomTom shall aggregate all map error reports from user devices, TomTom Home and the TomTom website.

#### **2.2.4.3 Map Error Report Prioritisation**

TomTom shall assess all map error reports and assign priorities to these, such that the most serious errors are clearly highlighted. These priorities shall be communicated to TomTom map suppliers when submitting error reports to them.

#### **2.2.4.4 Tele Atlas API Compatibility**

Map error reports shall be stored in a format that is compatible with the Tele Atlas map reporting API such that TomTom is capable of sending correctly formatted reports to Tele Atlas if it wishes to do so.

#### **Omissions**

This section describes the high level requirements that have been omitted from the V1 scope of Map Share.

### **2.3 User Requirements**

This section describes the omitted user requirements for Map Share.

#### **2.3.1 *Map Correction Types***

This section describes the map correction types that have been omitted from the V1 scope of Map Share.

##### **2.3.1.1 Modify City/Place Names**

The user shall be able to modify the names of cities (and other places) on the map.

##### **2.3.1.2 Block Roads for Transportation Types**

The user shall be able to block access to a road for one or more transportation types. Specifically the user shall be able to block access for the following transportation types:

- All motor vehicles
- Pedestrians
- Heavy Goods Vehicles
- Bicycles

##### **2.3.1.3 Un-block Roads for Transportation Types**

The user shall be able to un-block access to a road for one or more transportation types. Specifically the user shall be able to un-block access for the following transportation types:

- All motor vehicles
- Pedestrians
- Heavy Goods Vehicles
- Bicycles

#### **2.3.1.4 Modify Road Class**

The user shall be able to modify the “class” of roads on the map.

Note: road classes are used to define the properties of roads and are used within route calculation.

#### **2.3.1.5 Add Turn Restrictions**

The user shall be able to add turn restrictions to roads on the map.

#### **2.3.1.6 Remove Turn Restrictions**

The user shall be able to remove turn restrictions applied to roads on the map.

#### **2.3.1.7 Add House Numbers**

The user shall be able to add house numbers (either a single number or a range) to roads on the map.

#### **2.3.1.8 Modify House Numbers**

The user shall be able to modify the location of house numbers (either a single number or a range) applied to roads on the map.

#### **2.3.1.9 Modify Average Speed**

The user shall be able to modify the average speed of roads on the map.

#### **2.3.1.10 Add Toll to Road**

The user shall be able to mark a road on the map as a toll road.

#### **2.3.1.11 Remove Toll from Road**

The user shall be able to remove the presence of a toll from roads on the map.

#### **2.3.1.12 Add Signposts**

The user shall be able to add signpost information to roads on the map.

#### **2.3.1.13 Modify Signposts**

The user shall be able to modify the properties of signpost information associated with roads on the map.

### **2.3.1.14 Remove Signposts**

The user shall be able to remove signpost information associated with roads on the map.

### **2.3.1.15 Modify POI Locations**

The user shall be able to modify the location of POI on the map.

### **2.3.1.16 Modify POI Names**

The user shall be able to modify the names of POI on the map.

### **2.3.1.17 Modify POI Category**

The user shall be able to modify the category of POI on the map.

### **2.3.1.18 Remove POI**

The user shall be able to remove POI from the map.

### **2.3.1.19 Modify Motorway Exit Numbers**

The user shall be able to modify the exit numbers of motorways on the map.

### **2.3.1.20 Modify Post Code**

The user shall be able to modify the post code associated with a road on the map.

### **2.3.1.21 Add Road Height Restrictions**

The user shall be able to add road height restrictions to roads on the map.

### **2.3.1.22 Add Road Width Restrictions**

The user shall be able to add road width restrictions to roads on the map.

### **2.3.1.23 Add Road Weight Restrictions**

The user shall be able to add road weight restrictions to roads on the map.

## **2.3.2 *Map Error Reporting***

Some map errors are too complicated or large in scale to make corrections on the device itself. These errors need to be reported to TomTom, so that we (or our map suppliers) can take corrective action. This section describes the user requirements relating to map error reporting.

### 2.3.2.1 TomTom Website Map Error Reporting

The user shall be able to create map error reports within TomTom Support Website and upload these to the TomTom PLUS server.

- Users should not need to register as a TomTom customer in order to create a map error report
- A graphical user interface should be made available to allow easier selection of map error locations
- Feedback should be given to the user regarding the status of their report

## 2.4 Technical Constraints

Some features within Map Share must be implemented in a specific way in order to address the user's requirements and protect TomTom's interests. This section describes all known technical constraints that have been omitted from the V1 scope of Map Share.

### 2.4.1 *Map Error Reporting*

This section describes all known technical constraints relating to map error reporting that have been omitted from the V1 scope of Map Share.

#### 2.4.1.1 Map Error Reporting to Tele Atlas

TomTom shall implement the Tele Atlas map error reporting API and use this as the reporting mechanism for all reports to Tele Atlas.

## CLAIMS

1. Map data suitable for use with an electronic navigation device, the map data being structured to (i) enable an end-user to input a correction to the map data, directly on the device; and (ii) to allow use of the correction without processing of the correction external to the device.
2. The map data according to Claim 1, wherein the map data is structured as a database and multiple nodes in the map database are structured such that each node has a field or attribute to hold a correction input by an end-user.
3. The map data according to any one of the preceding Claims, wherein the map data is structured as a database and multiple segments in the map database are structured such that each segment has a field or attribute to hold a correction input by an end-user.
4. The map data according to any one of the preceding Claims, wherein the device is adapted to share one or more map corrections input to that device with other navigation devices; and the device is adapted to download or otherwise receive map corrections created by different end-users operating the other navigation devices and wherein the map data is structured to hold those map corrections created by the different end-users.
5. The map data according to any one of the preceding Claims, wherein the map data is structured such that a map correction is categorised according to the user community for which it is applicable so that downloads of corrections to a navigation device can be limited to the applicable category or categories.
6. The map data according to Claim 5, wherein the categories include one or more of the following:
  - All users
  - All motorists
  - Heavy goods vehicle drivers

- Motorcyclists
- Limited speed vehicle drivers
- Pedestrians
- Bicycles

7. The map data according to any one of the preceding Claims, wherein a correction is associated with a level of trust.

8. The map data according to any one of the preceding Claims, wherein a correction is automatically used by the device for route planning performed by the device.

9. The map data according to any one of the preceding Claims, wherein a correction is associated with a unique identifier.

10. The map data according to any one of the preceding Claims, wherein a correction is associated with an identifier that is unique to the device.

11. The map data according to any one of the preceding Claims, wherein a correction is associated with a time stamp defining when the correction was input.

12. The map data according to any one of the preceding Claims, wherein the correction is stored in a modular format that enables the correction to be applied in a routing algorithm independently of other corrections.

13. The map data according to any one of the preceding Claims, wherein the correction is to block a street.

14. The map data according to any one of the preceding Claims, wherein the correction is to unblock a street.

15. The map data according to any one of the preceding Claims, wherein the correction is to change a speed or speed limit applicable to a street.


16. The map data according to any one of the preceding Claims, wherein there is a further correction to rename, move, add, delete, alter the telephone associated with or re-categorise a POI.
17. The map data according to any one of the preceding Claims, wherein the correction is to add or change a name applicable to a city, part of a city, street or a part of a street.
18. The map data according to any one of the preceding Claims, wherein the correction is to change a direction of traffic property of a road.
19. The map data according to any one of the preceding Claims, wherein the correction is to add a road or connect two roads.
20. The map data according to any one of the preceding Claims, wherein the user can associate a correction with one or more transportation types.
21. The map data according to any one of the preceding Claims, wherein the correction is to block access for one or more of: a motor vehicle; pedestrians; heavy goods vehicles; bicycles.
22. The map data according to any one of the preceding Claims, wherein the correction is to add a turn restriction to a road.
23. The map data according to any one of the preceding Claims, wherein the correction is to remove a turn restriction.
24. The map data according to any one of the preceding Claims, wherein the correction is to add or modify house numbers.
25. The map data according to any one of the preceding Claims, wherein the correction is to mark a road as a toll road.

26. The map data according to any one of the preceding Claims, wherein the correction is to remove an indication that a road is a toll road.
27. The map data according to any one of the preceding Claims, wherein the correction is to add or modify signpost information for a road.
28. The map data according to any one of the preceding Claims, wherein the correction is to modify motorway exit numbers.
29. The map data according to any one of the preceding Claims, wherein the correction is to modify a postcode associated with a location.
30. The map data according to any one of the preceding Claims, wherein the correction is to add or modify a height, weight or width restriction.
31. The map data according to any one of the preceding Claims, wherein the correction is compressed for OTA distribution.
32. The map data according to any one of the preceding Claims, wherein the correction is securely encoded.
33. The map data according to Claim 32, wherein the correction is encoded in a way that is not specific to any one supplier of the map data.
34. The map data according to any one of the preceding Claims, wherein the correction does not permanently affect the map data stored on the device.
35. The map data according to Claim 34, wherein the correction can be automatically removed if the area related to the fix has changed in a new release of the map data.


36. The map data according to any one of the preceding Claims, wherein the correction is sent to a server which aggregates other corrections sent to it to produce improved map data.

37. The map data according to Claim 36, wherein corrections are analysed as to source, applicability and trustworthiness to produce improved map data.

1/10




*Fig. 1A*



*Fig. 1B*

**2/10**



*Fig. 2*

3/10






Fig. 3

4/10


*Fig. 4*

5/10




*Fig. 5*

6/10



*Fig. 6A*

7/10



*Fig. 6B*

8/10




Fig. 7

9/10




Fig. 8

10/10




Fig. 9

# INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2007/007311

**A. CLASSIFICATION OF SUBJECT MATTER**  
 INV. G01C21/32  
 ADD. G01C21/26

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
**G01C**

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**EPO-Internal, WPI Data**

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 530 025 A (HARMAN INT IND [US]) 11 May 2005 (2005-05-11) column 2, line 51, paragraph 9 – column 14, line 49, paragraph 56; figures 1-5 -----	1-37
X	JP 09 145383 A (MATSUSHITA ELECTRIC IND CO LTD) 6 June 1997 (1997-06-06) the whole document -----	1,2,19
A	-----	3-18, 20-37
A	US 6 453 233 B1 (KATO NORIKO [JP]) 17 September 2002 (2002-09-17) column 3, line 25 – column 10, line 33; figures 1-3 ----- -/-	1-37

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&\* document member of the same patent family

Date of the actual completion of the international search

5 December 2007

Date of mailing of the international search report

13/12/2007

Name and mailing address of the ISA/  
 European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
 Fax: (+31-70) 340-3016

Authorized officer

Springer, Oliver

**INTERNATIONAL SEARCH REPORT**

International application No PCT/EP2007/007311
---

**C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 300 654 A (BOSCH GMBH ROBERT [DE]) 9 April 2003 (2003-04-09) column 1, line 28, paragraph 4 – column 4, line 46, paragraph 15; claims 1,5-11; figures 1-3 ----- DE 197 42 414 A1 (MANNESMANN AG [DE]) 1 April 1999 (1999-04-01) column 1, line 23 – column 4, line 54; figure 1 -----	1-37
A	JP 09 090869 A (HITACHI SOFTWARE ENG) 4 April 1997 (1997-04-04) the whole document -----	1-37

**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No

PCT/EP2007/007311

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 1530025	A	11-05-2005	US	2005102098 A1		12-05-2005
JP 9145383	A	06-06-1997	JP	3391171 B2		31-03-2003
US 6453233	B1	17-09-2002	JP	2001075967 A		23-03-2001
EP 1300654	A	09-04-2003	DE	10148224 A1		30-04-2003
DE 19742414	A1	01-04-1999	AU	1021399 A		12-04-1999
			WO	9915857 A1		01-04-1999
			EP	1017965 A1		12-07-2000
JP 9090869	A	04-04-1997	JP	2863118 B2		03-03-1999