



(51) International Patent Classification:

A61N 1/372 (2006.01)

(21) International Application Number:

PCT/EP2020/087635

(22) International Filing Date:

22 December 2020 (22.12.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20150879.3 09 January 2020 (09.01.2020) EP

(71) Applicant: **BIOTRONIK SE & CO. KG** [DE/DE]; W-
ermannkehre 1, 12359 Berlin (DE).

(72) Inventor: **DOERR, Thomas**; Alpenrosenweg 43a, 12437
Berlin (DE).

(74) Agent: **Biotronik Corporate Service SE CorporateIntel-
lectual Property**; GALANDER, Marcus, Sieversufer 7-9,
12359 Berlin (DE).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN,
KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW,


SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: IMPLANTABLE MEDICAL DEVICE HAVING A COMMUNICATION COMPONENT



(57) Abstract: An implantable medical device (1), comprises a primary communication component (15) for establishing a communication connection with an external communication arrangement (2) outside of a patient (P). The external communication arrangement (2) is a mesh network comprising a multiplicity of nodes (20), wherein the primary communication component (15) is configured to act as an additional node in the mesh network for exchanging data with at least one of the multiplicity of nodes (20) of the mesh network, and wherein at least one of the nodes (20) of the mesh network is formed by a lighting device, which regularly are present within an environment, in which the patient (P) regularly stays.

5 IMPLANTABLE MEDICAL DEVICE HAVING A COMMUNICATION COMPONENT

The present invention relates to an implantable medical device according to the preamble of claim 1 and to a system comprising an implantable medical device.

10

An implantable medical device of this kind comprises a primary communication component for establishing a communication connection with an external communication arrangement outside of a patient.

15

An implantable medical device of this kind may for example be a therapeutic device, for example a pacemaker device, a defibrillator device or a neuro-stimulation device, or may be a diagnostic device, such as a sensor device for measuring a patient parameter such as a pressure, a temperature or electrical signals for example relating to an electrocardiogram within a patient. An implantable medical device of this kind also may be a recording
20 device, such as a loop recorder cooperating with a sensor device for recording measurement data, or may be a pump device, such as an implantable medication pump or the like.

25

Generally, an implantable medical device of the kind concerned herein shall communicate
with an external communication device, the external device generally being a dedicated
device configured to establish a secure, dedicated communication connection to the
implantable medical device for example making use of a specific communication protocol,
such as for example the MICS protocol. The external communication device may for
example be in communication connection with a public communication network, such that
30 via the external communication device and the public communication network data may be
transferred in between the implantable medical device and for example a data center, the
medical device for example being enabled to transmit measurement data or status

information relating to the operation of the medical device towards the data center, and to receive control data, for example relating to a configuration of the medical device for performing an operation, from the data center. The data center may be accessible by a user, such that a user may access measurement data obtained from the medical device and may
5 in addition enter or modify control data for controlling operation of the medical device.

In that a specific external device for establishing a communication with the medical device is required, the connectivity of the medical device is limited. For example, a communication connection in between the medical device and the outside data center for
10 transferring data towards the data center and for receiving data from the data center can only be established if the external communication device is in communication connection with the medical device, requiring for example a close proximity of the external communication device with the medical device. If the medical device for example is
15 implanted in a patient and the patient is in a home environment, a communication connection to the medical device may only be established if the implanted medical device may communicate with the dedicated external communication device, and hence may depend on a functional status of the external communication device and on the location of the external communication device with respect to the patient and thus the medical device.

20 WO 2017/172391 A1 describes systems and methods for detecting changes or fluctuations in an analyte concentration signal that are abnormal. Signals herein may be monitored, and information regarding detected changes can be recorded and analyzed for transmitting alerts and notifications. A sensor herein may for example comprise a telemetry module for establishing a communication connection.

25

US 2018/0063851 A1 describes methods and systems for dynamic allocation of communication channels among multiple wireless networks. By means of such systems interference mitigation and control among a plurality of wireless protocols operating in an environment may be provided, a communication network for example being a mesh
30 network of Internet-of-Things (IoT) devices.

It is an object of the instant invention to provide an implantable medical device and a system comprising an implantable medical device which allow for a communication of the implantable medical device while potentially alleviating the need for a dedicated external communication device, with the potential of an improved connectivity of the implantable
5 medical device.

This object is achieved by means of an implantable medical device comprising the features of claim 1.

10 Accordingly, the external communication arrangement is a mesh network comprising a multiplicity of nodes, wherein the primary communication component is configured to act as an additional node in the mesh network for exchanging data with at least one of the multiplicity of nodes of the mesh network.

15 The implantable medical device is enabled to communicate with a communication network in the shape of a mesh network, which is formed outside of the patient and may be present for example in a home environment of the patient. The mesh network may for example be formed by devices which do not serve a medical function, such as lighting devices or the like, which regularly are present within a home environment of a patient or another
20 environment, in which a patient regularly stays, such as a work environment or the like.

Because communication with the implantable medical device is established via an external communication network which is not dedicated and specifically adapted for a communication with the implantable medical device, the connectivity for the implantable
25 medical device can be improved, improving hence for example the access to the medical device in an implanted state in a patient without the patient having to take special care for enabling a communication connection between the medical device and a dedicated communication device.

30 In one embodiment, the primary communication component of the implantable medical device may be configured to establish a bi-directional communication connection to the at least one node of the multiplicity of nodes of the mesh network. The implantable medical

device hence may transfer data towards one or multiple nodes of the mesh network, and may receive data from one or multiple nodes of the mesh network. In this way, data may be transmitted from the medical device towards the outside, for example relating to measurement data or status data, and in addition data may be received by the medical device, for example relating to control data for controlling operation of the medical device.

In one embodiment, the mesh network is a Bluetooth mesh network, wherein the primary communication component is configured to establish a Bluetooth communication connection with one or multiple nodes of the mesh network. The Bluetooth mesh network may for example be defined by the Bluetooth mesh standard, namely the Mesh Profile Bluetooth Specification, revision 1.0.1 dated January 21, 2019 as prepared by the Mesh Working Group and as defining fundamental requirements for enabling an interoperable mesh networking solution for Bluetooth low energy wireless technology.

The implantable medical device, in one embodiment, hence is enabled to communicate within the Bluetooth frequency band in between 2,402 GHz und 2,480 GHz (corresponding to the so-called ISM band).

In one embodiment, the primary communication component may be configured to act as a Bluetooth low-power node within the mesh network, a low-power node in a Bluetooth mesh network typically cooperating with one or multiple so-called friend nodes within the mesh network, such friend nodes for example being enabled to store messages destined for the low-power node and to forward the messages to the low-power node upon specific request from low-power node.

In one embodiment, the implantable medical device comprises a secondary communication component configured to establish a communication connection to an external communication device different than the mesh network. Hence, in addition to the primary communication component which serves to establish a communication connection to the external communication arrangement in the shape of the mesh network, the implantable medical device comprises a secondary communication component, which is enabled to establish a second communication connection to an outside device independent of the mesh

network. The external communication device for communicating with the secondary communication component of the implantable medical device may for example be a dedicated communication device or a portable or non-portable general communication device such as a smart phone, a tablet computer, a laptop computer or a PC. By means of the additional communication connection established in between the implantable medical device and the external communication device, for example control data may be transmitted to the implantable medical device, the control data serving to control operation of the primary communication component of the implantable medical device, for example to switch on or off a communication with the mesh network or for configuring a communication function for the communication with the mesh network via the primary communication component.

Hence, via the secondary communication component of the implantable medical device an additional communication connection may be established and may allow for controlling operation of the primary communication component for communicating with the mesh network, wherein in addition also a data transfer, for example for transmitting measurement information or status data towards the outside or for receiving control information for controlling the general operation of the implantable medical device, may take place via the communication connection established via the secondary communication component.

In another aspect, a system comprises an implantable medical device of the kind described above and an external communication arrangement forming a mesh network comprising a multiplicity of nodes, the implantable medical device being enabled to communicate with the mesh network, which for example may be a Bluetooth mesh network.

In one embodiment, herein, at least one of the multiplicity of nodes of the mesh network may be a so-called friend node, which is configured to store messages destined for the primary communication component of the implantable medical device and to forward the messages to the primary communication component of the implantable medical device upon receiving a request notification from the primary communication component of the implantable medical device. Whereas the primary communication component of the

implantable medical device may serve as a Bluetooth low-power node within the mesh network and hence is enabled for a low power operation, the friend node may have an increased power consumption and may for example be connected to a regular power supply network. In order to save energy, a communication in between the low-power node and the friend node may not be continuously established, but only in case a data transfer is desired, for example in regular periods throughout a day, wherein the friend node cooperating with the low-power node buffers messages destined for the low-power node for transmission once the low-power node indicates to the friend node that it wishes to receive the messages.

10

The primary communication component of the implantable medical device acting as a low-power node within the mesh network may cooperate with one or multiple friend nodes.

In one embodiment, at least one of the nodes of the mesh networks is formed by a non-medical device, for example by a lighting device in a household environment. Nowadays, within a household environment lighting devices (for example in the shape of light bulbs or other lamps) may for example be interconnected by a mesh network in order to control operation of the lighting devices, for example to adjust a brightness or color of the lighting devices.

20

Other devices of non-medical origin may in addition or alternatively form nodes of the mesh network, such as smart communication devices or household devices, for example kitchen devices or entertainment devices (TV, stereo etc.).

In one embodiment, the mesh network comprises a mesh gateway, also denoted as mesh router or relay node, which connects the mesh network to a public communication network. The implantable medical device hence, via the mesh network, may be connected to a public communication network for communicating for example with a data center connected to the public communication network. In this way, the implantable medical device may for example transmit data towards the data center or receive data from the data center using a connectivity via the mesh network.

30

A mesh network in this respect may use a so-called message flooding, in that messages destined to the implantable medical device or messages originating from the implantable medical device are transferred through the mesh network by forwarding each message from one node to the other, until a desired destination is reached, e.g. the implantable
5 medical device or a mesh gateway (mesh router).

In one embodiment, the implantable medical device is configured to receive for example firmware data via the mesh network, such firmware data for example providing for a firmware update of the implantable medical device. Alternatively or in addition, the
10 implantable medical device may receive configuration data via the mesh network, the configuration data for example serving to program an operation of the implantable medical device, such as a measuring operation or a therapeutic operation, for example a stimulation operation for performing a stimulation in a pacemaker device or a neuro-stimulation device.

15 In one embodiment, the implantable medical device is configured to transmit measurement information relating to a measurement performed by the implantable medical device to the mesh network and via the mesh network towards the outside. The implantable medical device may for example comprise a sensor device, such as an electrode, a pressure sensor
20 or a temperature sensor, for performing a measurement such as an electrocardiogram measurement, a pressure measurement, a temperature measurement or another measurement.

25 Alternatively or in addition, the implantable medical device may be configured to transmit communication status information relating to a communication status for communicating with the mesh network, and/or system status information relating to an operational status of the implantable medical device for performing a diagnostic or therapeutic function. By means of communication status information for example a request for message transmission towards the implantable medical device may be transmitted. By means of
30 operational status information the implantable medical device may transmit information relating to a general status of the implantable medical device, for example indicating an

energy level of the implantable medical device, or relating to a specific operation, such as a therapeutic operation, for example a pacemaker function or a neuro-stimulation function.

5 Via the mesh network data may be transmitted or received by the implantable medical device in a continuous or discontinuous fashion. In one embodiment, to reduce an energy consumption a communication between the implantable medical device and the mesh network is enabled only in specific communication periods, for example in regular, discrete communication periods, for example at multiple times throughout an hour, a day or a week. The implantable medical device herein may be configured to control its energy
10 budget by limiting a communication with the mesh network, such that energy consumption is reduced by the implantable medical device, hence preventing an excessive discharging of an energy storage in the shape of a battery and enabling for a prolonged operation of the medical device in an implanted state within a patient.

15 In one embodiment, the system comprises a localization function for localizing the implantable medical device using the mesh network. Generally, nodes within a mesh network may be localized according to an exchange of messages in between the nodes. For example, one node may transmit a message towards another node, wherein in the message for example a transmit power is indicated. By measuring the reception power at the
20 receiving node and by triangulating information received from multiple nodes, a node may be localized according to the message exchange within the mesh network.

By means of such localization function, the implantable medical device may localize itself within the mesh network, or other nodes may localize the implantable medical device. A
25 localization function hence may be carried out by each node of the mesh network, including the implantable medical device.

If the implantable medical device is enabled to localize itself using a localization function, it may adapt its configuration according to localization information.

30

By localizing the implantable medical device within the mesh network, the implantable medical device and hence the patient can be tracked and monitored, wherein in addition the

locations of multiple medical devices implanted in a variety of patients may be analyzed for supply-chain management purposes.

The object underlying the invention shall subsequently be explained in more detail with
5 reference to the embodiments shown in the drawings. Herein:

Fig. 1 shows a schematic drawing of a medical device in the shape of a monitoring device in an implanted state in a patient;

10 Fig. 2 shows a schematic drawing of an implantable medical device in the shape of a monitoring device;

Fig. 3 shows a connectivity of an implantable medical device for communicating with an outside data center, according to a prior approach;

15

Fig. 4 shows a connectivity of an implantable medical device for communicating with an outside data center, making use of a mesh network;

20

Fig. 5 shows a schematic drawing of a medical device in communication connection with a mesh network; and

Fig. 6 shows an embodiment of an implantable medical device in communication with a mesh network and in addition with another external communication device.

25

Fig. 1 shows an implantable medical device 1 in an implanted state within a patient P. The implantable medical device 1 functions for example as a therapeutic or diagnostic device, for example a monitoring device, and is implanted within or close to the heart H of the patient P or at another location within the patient's body, the implantable medical device 1
30 being enabled to communicate with an external communication arrangement 2 to transfer and/or receive data to respectively from the external communication arrangement 2.

The implantable medical device 1 for example may have the shape of a diagnostic device, such as a sensor device or a recording device, for example a loop recorder configured to record data. Alternatively, the implantable medical device 1 may be a therapeutic implant, such as a pacemaker or defibrillator, or a pumping device, such as an implantable medication pump.

A medical device 1 in the shape of e.g. a monitoring device shall remain within a patient P over a prolonged period of time, for example several months or even years. For this, the medical device 1 shall operate in an energy-efficient manner, in that for example a data communication is not enabled continuously, but in dedicated periods of time in order to transmit and receive data throughout such dedicated periods of time, for example at multiple times an hour, a day or a week. At the same time, a communication of the medical device 1 with an external communication arrangement 2 shall be easy to establish and shall not for example be limited by connectivity restrictions in between the medical device 1 and a dedicated communication equipment.

Referring now to Fig. 2, an implantable medical device 1 in one embodiment comprises a processor device 11 cooperating with a sensor device 12 for sensing a sensing signal relating to activity of a patient's heart H. The sensor device 12 may for example comprise an electrode for electrically sensing electrical signals originating from the heart H and in particular corresponding to ventricular contractions of the heart H, such that by means of the medical device 1 a signal in the shape of an electrocardiogram may be recorded.

The implantable medical device 1 in the embodiment of Fig. 2 in addition comprises a memory device 13 serving to store recorded data, an energy storage 14 in the shape of a battery and a primary communication component 15 in the shape of electronic circuitry for establishing a communication connection to an external communication arrangement 2 for transferring data to the external communication arrangement 2 and for receiving e.g. control commands or programming data, for example relating to certain settings of the medical device 1, from the external communication arrangement 2.

The medical device 1 comprises a housing 10 which encapsulates the components received within in a fluid-tight manner.

Referring now to Fig. 3, in a conventional scenario an implantable medical device 1 is
5 configured to communicate with an external communication arrangement 2 in the shape of
an external communication device which is a specifically configured and dedicated for
communication with the medical device 1, using for example the MICS communication
protocol designed for allowing a communication with diagnostic and therapeutic medical
implants and body-worn devices. The external communication device in this scenario may
10 for example be a portable or non-portable device, such as a smart phone, having installed a
software and communication circuitry allowing for a communication using the MICS
protocol, wherein the external communication device is for example wirelessly connected
to a base station 3 of a wireless communication network, and via the wireless
communication network to a public communication network 4. In this way, data may be
15 transferred to and received from the medical device 1, wherein a data communication may
be established between the medical device 1 and a data center 5 connected to the public
communication network 4, the data center 5 being enabled to collect data from the medical
device 1 and to transfer for example control data towards the medical device 1 for
controlling operation of the medical device 1.

20

The data center 5 may be accessible by a user U, such that a user, for example a physician,
may access data provided by the medical device 1, for example measurement data or
diagnostic or therapeutic status information, via the data center 5, or may enter or modify
control data for transmission to the medical device 1 for controlling operation of the
25 medical device 1.

Instead of having the medical device 1 communicating with a dedicated, specifically
configured external communication device as in the scenario of Fig. 3, in a proposed
approach a communication connection to the medical device 1, in an implanted state within
30 a patient, is established using a mesh network, in particular a Bluetooth mesh network.
Referring now to Fig. 4, in this approach a medical device 1 is in communication
connection with an external communication arrangement 2 in the shape of a mesh network,

wherein the mesh network is connected to a public communication network 4, to which also a data center 5 is connected (as in the scenario of Fig. 3), the data center 5 being user-accessible to transfer data to and receive data from the medical device 1.

5 Referring now to Fig. 5, an external communication arrangement 2 in the shape of a mesh network comprises a multiplicity of nodes 20, which are interconnected for communication in a meshing fashion. Herein, multiple nodes 20 may communicate with multiple other nodes 20, a transmission of messages taking place by a so-called flooding in that one message is relayed from one node 20 to another node 20 and from the other node 20 on to
10 a further node 20, such that the message propagates through the mesh network 2 until it reaches a desired destination.

In the scenario of Figs. 4 and 5, the medical device 1, in an implanted state within a patient P, forms a node of the external communication arrangement 2 in the shape of the mesh
15 network and hence is enabled to communicate with one or multiple other nodes 20 of the mesh network.

If the mesh network is a Bluetooth mesh network, the medical device 1, with its primary communication component 15, may form a Bluetooth low-power node, the communication
20 component 15 of the medical device 1 cooperating with one or multiple other nodes 20 in the shape of so-called friend nodes, which do not have restricted energy requirements as the Bluetooth low-power node, but enable an energy-efficient operation of the Bluetooth low-power node. For example, a node 20 in the shape of a friend node may be enabled to buffer messages destined for the medical device 1 acting as a Bluetooth low-power node,
25 wherein the messages are forwarded to the medical device 1 only once the communication component 15 sends a request notification to the friend node to forward the buffered messages.

The mesh network, in the embodiment of Fig. 5, comprises a mesh gateway, also denoted
30 as mesh router or relay node, which provides for a connection to a public communication network 4, to which also the data center 5 is (directly or indirectly) connected. Hence, via the mesh network and the public communication network 4 the medical device 1 is

operatively connected to the data center 5, such that data may be transferred from the medical device 1 to the data center 5 or, the other way around, from the data center 5 to the medical device 1.

5 For example, the medical device 1 may be configured to receive firmware data from the data center 5, for providing for example a firmware update of the medical device 1.

Alternatively or in addition, the medical device 1 may be configured to receive control data, for example for modifying a configuration of the medical device 1 or for
10 programming an operation of the medical device 1, for example a diagnostic or therapeutic function.

Alternatively or in addition, the medical device 1 may be configured to transfer data towards the data center 5, such data relating to diagnostic or therapeutic information, for
15 example measurement data relating to a measurement or operational data relating to an ongoing therapeutic function, for example a stimulation function or the like.

The mesh network may also enable a localization function. For example, according to a general setup of a mesh network, in particular a Bluetooth mesh network, nodes 20 within
20 the mesh network may be localized, for example by a message exchange in between the various nodes 20. For example, a message sent from one node 20 to another node 20 may contain a transmit power information, wherein the receiving node 20 may measure a receive power and from the receive power may derive information about a distance from the sending node 20. By using a triangulation, then, a location information can be derived
25 for that node 20.

In this way a medical device 1 can be localized, wherein the medical device 1 may, according to a localization information, adapt its settings, or a medical device 1 and hence a patient P may be tracked.

30

The mesh network may for example be formed in a home environment 6 at the home of a patient P, wherein nodes 20 of the mesh network other than the medical device 1 for

example are formed by non-medical devices, for example lighting devices (such as light bulbs or lamps), home appliances or entertainment equipment being enabled to establish and communicate within e.g. a Bluetooth mesh network.

5 Referring now to Fig. 6, in one embodiment the medical device 1, in addition to the primary communication component 15, comprises a secondary communication component 16, which is configured to communicate with an external communication device 7 different and separate from the communication arrangement 2 in the shape of the mesh network. The communication device 7 is external to the patient and is for example a portable or non-
10 portable device, such as a smart phone, a tablet computer, a laptop computer or a PC.

Via the communication device 7, for example control data may be sent to the medical device 1, such control data allowing for a control of the primary communication component 15, for example to switch on or off a communication connection with the
15 communication arrangement 2 in the shape of the mesh network. Hence, via the communication device 7 a communication using the mesh network may be controlled or modified, wherein in addition a data transfer, for example relating to measurement data or status information, from the medical device 1 to the communication device 7 may be possible.

20

The idea underlying the invention is not limited to the embodiments described above, but can be implemented in an entirely different fashion.

By means of the approach described herein a connectivity to a medical device implanted in
25 a patient may be improved, wherein a data communication with a medical device may be established in a cheap, reliable way allowing for limited restrictions in everyday life for a patient, a patient potentially not being even aware of a medical device being in communication connection with an external network for establishing a data communication.

30

List of reference numerals

	1	Implantable medical device
	10	Housing
5	11	Processor device
	12	Sensor device
	13	Memory device
	14	Energy storage
	15	Primary communication component
10	16	Secondary communication component
	2	External communication arrangement (mesh network)
	20	Network nodes
	21	Mesh gateway
	3	Base station
15	4	Public communication network
	5	Data center
	6	Home environment
	7	Communication device
	U	User

Claims

1. An implantable medical device (1), comprising:
a primary communication component (15) for establishing a communication
5 connection with an external communication arrangement (2) outside of a patient (P);
characterized in that the external communication arrangement (2) is a mesh
network comprising a multiplicity of nodes (20), wherein the primary
communication component (15) is configured to act as an additional node in the
mesh network for exchanging data with at least one of the multiplicity of nodes (20)
10 of the mesh network, and wherein at least one of the nodes (20) of the mesh network
is formed by a lighting device, which regularly are present within an environment, in
which the patient (P) regularly stays.
2. The implantable medical device (1) of claim 1, **characterized in** that the primary
15 communication component (15) is configured to establish a bi-directional
communication connection to said at least one of the multiplicity of nodes (20) of the
mesh network.
3. The implantable medical device (1) of claim 1 or 2, **characterized in** that the mesh
20 network is a Bluetooth mesh network, wherein the primary communication
component (15) is configured to establish a Bluetooth communication connection
with the at least one of the multiplicity of nodes (20) of the mesh network.
4. The implantable medical device (1) of one of claims 1 to 3, **characterized in** that the
25 primary communication component (15) is configured to act as a Bluetooth low-
power node.
5. The implantable medical device (1) of one of the preceding claims, **characterized by**
a secondary communication component (16) configured to establish a
30 communication connection to an external communication device (7) different than
the mesh network.

6. The implantable medical device (1) of claim 5, **characterized in** that the secondary communication component (16) is configured to receive control data via said communication connection to the external communication device (7) for controlling the primary communication component (15).
- 5
7. A system, comprising an implantable medical device (1) of one of the preceding claims and an external communication arrangement (2) forming a mesh network comprising a multiplicity of nodes (20).
- 10
8. The system of claim 7, **characterized in** that said at least one of the multiplicity of nodes (20) of the mesh network is a friend node configured to store messages destined for the primary communication component (15) of the implantable medical device (1) and to forward said messages to the primary communication component (15) of the implantable medical device (1) upon receiving a request notification from
15 the primary communication component (15) of the implantable medical device (1).
9. The system of claim 7 or 8, **characterized in** that at least one of the nodes (20) of the mesh network is formed by a non-medical device.
- 20
10. The system of one of claims 7 to 9, **characterized in** that the mesh network comprises a mesh gateway (21) which connects the mesh network to a public communication network (4).
- 25
11. The system of claim 10, **characterized by** a data center (5) connected to the mesh network via the public communication network (4), wherein the implantable medical device (1) is configured to transmit data towards the data center (5) or receive data from the data center (5) via the mesh network.
- 30
12. The system of one of claims 7 to 11, **characterized in** that the implantable medical device (1) is configured to receive at least one of firmware data and configuration data from said at least one of the multiplicity of nodes (20) of the mesh network.

13. The system of one of claims 7 to 12, **characterized in** that the implantable medical device (1) is configured to transmit at least one of measurement information relating to a measurement performed by the implantable medical device (1), communication status information relating to a communication status for communicating with the mesh network, and system status information relating to an operational status of the implantable medical device (1) for performing a diagnostic or therapeutic function to said at least one of the multiplicity of nodes (20) of the mesh network.
14. The system of one of claims 7 to 13, **characterized in** that the implantable medical device (1) is configured to carry out a localization function for localizing the implantable medical device (1) using the mesh network, or at least one of said multiplicity of nodes (20) is configured to carry out a localization function for localizing the implantable medical device (1).




FIG. 1






FIG. 2






FIG. 5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2020/087635

A. CLASSIFICATION OF SUBJECT MATTER INV. A61N1/372 ADD.		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols) A61N		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) EPO-Internal, WPI Data		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 043 508 B1 (MEDTRONIC INC [US]) 7 August 2013 (2013-08-07) paragraphs [0020], [0021], [0023], [0026], [0030], [0031], [0035] - [0056]; figures 1,3,5 -----	1-14
X	US 2013/154851 A1 (GASKILL ROBERT J [US] ET AL) 20 June 2013 (2013-06-20) paragraph [0042] - paragraph [0417] -----	1-14
X	US 2016/321400 A1 (DURRANT IAN [US] ET AL) 3 November 2016 (2016-11-03) paragraph [0082] - paragraph [0183] -----	1-14
X	US 2011/152970 A1 (JOLLOTA JAMES [US] ET AL) 23 June 2011 (2011-06-23) paragraph [0021] - paragraph [0113] -----	1-14
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents :		
"A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed		"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family
Date of the actual completion of the international search <p align="center">1 February 2021</p>		Date of mailing of the international search report <p align="center">10/02/2021</p>
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016		Authorized officer <p align="center">Sopelana Martínez, J</p>

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2020/087635

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
EP 2043508	B1	07-08-2013	EP 2043508 A2 WO 2008002748 A2	08-04-2009 03-01-2008

US 2013154851	A1	20-06-2013	US 2009058635 A1 US 2009058636 A1 US 2009062887 A1 US 2009063193 A1 US 2011273287 A1 US 2013147622 A1 US 2013154851 A1 US 2013310896 A1 US 2014062718 A1 US 2015206408 A1	05-03-2009 05-03-2009 05-03-2009 05-03-2009 10-11-2011 13-06-2013 20-06-2013 21-11-2013 06-03-2014 23-07-2015

US 2016321400	A1	03-11-2016	CN 107615396 A EP 3278256 A1 JP 2018509995 A US 2016321400 A1 WO 2016160841 A1	19-01-2018 07-02-2018 12-04-2018 03-11-2016 06-10-2016

US 2011152970	A1	23-06-2011	NONE	
