



- (51) International Patent Classification:
B23B 29/034 (2006.01)
- (21) International Application Number:
PCT/EP2017/051973
- (22) International Filing Date:
31 January 2017 (31.01.2017)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
16162248.5 24 March 2016 (24.03.2016) EP
- (71) Applicant: SANDVIK INTELLECTUAL PROPERTY
AB [SE/SE]; SE-811 81 Sandviken (SE).
- (72) Inventor: KARLSSON, Robin; Kyrkogatan 29, SE-803
11 Gävle (SE).
- (74) Agent: JEDLÖV, Cecilia; 811 81 Sandviken (SE).
- (81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN,
KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA,
MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG,
NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS,
RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY,
TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))*

[Continued on next page]

(54) Title: A BORING TOOL




Fig 1

(57) Abstract: A boring tool comprises a tool body (2) rotatable around a central rotation axis (C). A slider member (5) is arranged movably inside the tool body along a path (P) extending transversely to the rotation axis (C). An insert pocket is associated with the slider member to move therewith and configured to receive a cutting insert (9) with a cutting edge (11) which projects from the tool body transversely to the rotation axis (C). A motor member (12) is connected to the slider member and controllable to move the slider member transversely to the rotation axis (C) for changing the distance of the cutting edge (11) to the rotation axis (C). The motor member (12) is arranged inside the tool body together with the slider member in a cutting part (14) of the tool body at a front end thereof. The motor member is arranged in parallel with the transversal extension of the slider member along said path.



Published:

— *with international search report (Art. 21(3))*

A BORING TOOL

TECHNICAL FIELD OF THE INVENTION

- 5 The present invention relates to a boring tool comprising
- a tool body including a front end and a rear end, between
which a central rotation axis extends around which the tool
body is rotatable in a direction of rotation,
 - a slider member which is arranged movably inside the tool
10 body along a path extending transversely to said rotation axis,
 - an insert pocket associated with the slider member to move
therewith and configured to receive a cutting insert to be se-
cured therein by a fastening member, which cutting insert has
a cutting edge and projects from the tool body transversely to
15 said rotation axis,
 - a motor member connected to the slider member and con-
trollable to move the slider member transversely to said ro-
tation axis for changing the distance of the cutting edge of the
cutting insert to said rotation axis and by that the radius to be
20 created in a hole of a workpiece when bored by rotation of the
tool body, and
 - a control unit configured to control the motor member to move
the slider member.
- 25 Such a boring tool is used for carrying out the machining process
of enlarging an already existing hole by means of rotating a tool
body provided with one or more cutting inserts. The process is
commonly performed in order to achieve accurate dimensions,
tight tolerances or a certain surface finish. Typical boring tool
30 bodies are often supplied with a radially adjustable cutting edge
that enables a variable cutting diameter as well as the possibility
to compensate for wear of the cutting insert.

35 Traditionally, the adjustment of the diameter of the hole to be ob-
tained by the boring action is done manually by the machine op-
erator, through e.g. turning an adjustment screw on the tool
body. In an environment where productivity is paramount, the
manual adjustment procedure for boring tools is considered time

consuming and accordingly undesirable. Such an adjustment demands an operator to physically stop the machining operation and contact the boring tool.

5 It has for that sake been suggested to adjust said diameter by providing the boring tool with a motor member controllable to move the slider member transversely to the rotation axis of the tool body for changing the distance of the cutting edge of the cutting insert to this rotation axis. "Transversely" is here not to be
10 interpreted as "perpendicularly", although that would in most cases be preferred, but a movability in a direction changing the distance of the cutting edge of the cutting insert to the rotation axis and by that the radius to be created in a hole of a work piece when bored by rotation of the tool body. Providing the boring
15 tool with such a motor member eliminates the need for operators to physically reach into the machine or remove the boring tool from the machine to adjust the tool diameter. This means that the adjustment procedure for a boring tool is considerably faster, more robust and more secure.

20

BACKGROUND ART

EP 2 095 897 B1 discloses a boring tool of the type defined in the introduction. The arrangement of the motor member in this
25 tool makes it possible to move a cutting insert thereof transversely to the rotation axis of the tool body for carrying out corrections for wear of the cutting insert but not for carrying out any substantial adjustment of the radius to be created in a hole of a work piece when bored by rotation of the tool body.

30

SUMMARY OF THE INVENTION

The object of the present invention is to provide a boring tool of the type defined in the introduction being improved in at least
35 some aspect with respect to such boring tools already known.

This object is according to the invention obtained by providing such a boring tool with the features listed in the characterizing part of appended patent claim 1.

- 5 By arranging the motor member inside the tool body together with the slider member in a cutting part of the tool body at the front end of the tool body and in parallel with the transversal extension of the slider member along said path the arrangement of the motor member and slider member inside the tool body may
10 be very compact while still providing for a possibility of substantial adjustments of the radius to be created in a hole of a work piece when bored by rotation of the tool body. That the motor member is arranged in parallel with said transversal extension means here along and beside this transversal extension and the
15 motor may also have parts coinciding with said path, for instance by an arrangement of the motor member coaxially with respect to a theoretical axis defining said path. Such an arrangement of the motor member with respect to the slider member enables considerable movements of the slider member along said path in spite
20 of the fact that the motor member is arranged inside the tool body and in the cutting part of the tool body.

- According to an embodiment of the invention the slider member is movable by action of the motor member along said path between two end positions corresponding to a said boring radius at
25 the outermost end position exceeding the boring radius at the innermost end position by at least 10%, 10%-60%, 20%-50% or 30%-50%. By providing the possibility to make adjustments of a radius to be created in a hole of a work piece when bored by rotation of the tool body by at least 10% the same boring tool with
30 the same tool body may be used for providing holes with substantially different diameters which makes it possible to save time and by that costs with respect to a need of changing boring tool and/or tool body for each change of diameter of holes to be
35 bored. An adjustability of said boring radius by more than 60% would result in a need of complicated transmissions and/or de-

signs of members connecting the motor member to the slider member making the boring tool less simple and robust.

5 According to an embodiment of the invention the control unit comprises a micro controller arranged inside the tool body in said cutting part thereof. The arrangement of the control unit in the cutting part contributes to make the system for obtaining adjustment of the radius to be created in a hole of a workpiece when bored by rotation of the tool body compact.

10

According to an embodiment of the invention the micro controller is configured to communicate with a device located externally of the tool body so as to receive set values of boring diameters to be achieved by rotation of the tool body and to control the motor member to move the slider member to positions corresponding thereto. This makes it easy and comfortable to carry out said adjustments by sending orders from said device to the micro controller located inside the tool body through an operator or even automatically through suitable software.

20

According to an embodiment of the invention the microcontroller is configured to communicate with a said device by wireless communication. Such communication means may for instance use the Low Energy (LE) Bluetooth protocol for transmission of data from said device to the micro controller. The device may for instance be a PC, a smartphone or a tablet. The wireless communication means facilitates the handling of the boring tool, since no cables connecting a said device with the interior of the tool body have to be considered.

30

According to an embodiment of the invention the boring tool comprises an energy storing member, such as an electric battery, arranged inside the tool body and connected to provide electric energy to the function of the micro controller and the motor. This feature means that no cables from an external source of electric power have to be connected to the interior of the tool body, which makes the handling of the boring tool less complicated.

35

According to an embodiment of the invention the boring tool further comprises a sensor arranged inside the tool body and configured to sense the position of the slider member with respect to a fixed part of the tool body giving evidence of the position of said slider member along said path and send information about the position sensed to the control unit, and the control unit is configured to compare the value of the position sensed with a position value to be obtained for a boring radius to be set and control the motor member to move the slider member so as to obtain correspondence of these two position values. This enables obtention of high resolutions of adjustments of the radius to be created in a hole of a workpiece when bored by a rotation of the tool body, such as in the order of 0.5 μm or even finer. Thus, having such a sensor measuring the actual position of the slider member along said path enables an increased authenticity and in some cases also an increased accuracy with respect to measuring arrangements being based on measuring the number of turns made by a motor axis causing movement of the slider member.

According to an embodiment of the invention the motor member is configured to drive a member thereof to rotate or to carry out a linear translation movement so as to move the slider member. These are suitable ways of operation of the motor member.

According to an embodiment of the invention the motor member is configured to cause movement of the slider member by rotating a threaded member in engagement with a thread of the slider member, of a member arranged to move with the slider member or of a member fixed with respect to the tool body. Such a design of members for obtaining a transmission of movement from the motor member to the slider member will result in a high accuracy by simple means.

According to an embodiment of the invention the slider member is hollow and the motor member is arranged inside the slider member, which results in a very compact combination of slider

member and motor member requiring little space inside the cutting part of the tool body while still obtaining a possibility to carry out big adjustments.

- 5 According to an embodiment of the invention the motor member is arranged inside a hollow screw with an external thread in engagement with an inner thread of a member fixed to the slider member, and the motor member is configured to rotate said screw so as to move this and by that the slider member along
10 said path. This constitutes a simple way of realizing a compact arrangement of the motor member and the slider member while providing for said big adjustments.

- 15 According to an embodiment of the invention the motor member is arranged beside the slider member within an enlarged perimeter around the slider member. This constitutes another possibility to obtain a compact design of the combination of motor member and slider member inside the tool body and still a possibility to obtain said big adjustments.

- 20 According to an embodiment of the invention the motor member is configured to drive a part thereof to rotate around a rotation axis extending in parallel with said path. Such an arrangement of the motor member makes it easy to transmit movements from
25 movable parts thereof to the slider member, which may through an embodiment of the invention be obtained by configuring the motor member to rotate a gear in engagement with another gear so as to rotate a threaded member in engagement with another threaded member, in which one of these threaded members is
30 connected to the slider member so as to cause movement of the slider member along said path by rotation of said gears.

- Other advantageous features as well as advantages of the present invention appear from the description following below.

35

BRIEF DESCRIPTION OF THE DRAWINGS

With reference to the appended drawings, below follows a specific description of embodiments of the invention cited as examples.

In the drawings:

5

Fig 1 is a simplified and partially sectioned view of a boring tool according to a first embodiment of the invention with an insert thereof in a position corresponding to a smallest boring radius,

10

Fig 2 is a view of the tool shown in Fig 1 with said insert in a position corresponding to a larger boring radius,

Fig 3 is a simplified perspective view of the boring tool shown in Fig 1 and 2 used to illustrate the operation thereof,

15

Fig 4 is a view corresponding to that of Fig 1 of a boring tool according to a second embodiment of the invention, and

20

Fig 5 is an enlarged view of the motor member, the slider member and a transmission acting between these in the embodiment shown in Fig 4.

25

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

A boring tool 1 according to a first embodiment of the invention is shown in Fig 1-3 and reference is made in parallel to these figures when now describing the design of the boring tool. The boring tool has a tool body 2 including a front end 3 and a rear end 4, between which a central rotation axis C extends around which the tool body is rotatable in a direction of rotation R. A slider member 5 is arranged movably inside the tool body along a path P (see dashed line in Fig 1) extending transversely to the rotation axis C while being directed perpendicularly thereto. An insert

30

35

pocket 6 (see Fig 3) is associated with the slider member to move therewith by being arranged on a part 7 secured to the slider member 5 by a screw 8. The insert pocket is configured to receive a cutting insert 9 to be secured therein by a fastening member 10. The cutting insert has a cutting edge 11 and projects from the tool body transversely to the rotation axis C thereof so as to carry out a boring action on walls of a hole in a workpiece when rotating the tool body around the rotation axis C.

10 A motor member 12 in the form of an electric motor is arranged inside the slider member, which is hollow by having a cavity 13, in a cutting part 14 of the tool body at the front end 3 thereof. The motor member 12 is configured to rotate an axle 15 being coaxially arranged with respect to said path P and secured to a hollow screw 16 inside which the motor member 12 is arranged.

The hollow screw 16 has an external thread 17 in engagement with an internal thread 18 of a nut 19 fixed with respect to the slider member 5. Thus, rotation of the hollow screw 16 caused by rotation of the axle 15 by operation of the motor member 12 will cause the slider member 5 to move in a direction transversely to the axis of rotation C of the tool body by the turning of the hollow screw 16 in the nut 19. The distance of the cutting edge 11 of the cutting insert 9 to the rotation axis C and by that the radius to be created in a hole of a workpiece when bored by rotation of the tool body may be adjusted by such movement. Fig 1 shows an innermost end position of the slider member, while Fig 2 shows a nearly outermost end position of the slider member resulting in a said radius exceeding the radius of the tool according to Fig 1 by approximately 25 %.

The boring tool also has a control unit in the form of a micro controller 20 arranged inside the tool body in the cutting part 14 thereof, and this micro controller is configured to control the motor member to move the slider member. The micro controller is configured to communicate with the device 21, here a laptop, located externally of the tool body so as to receive set values of

boring diameters to be achieved by rotation of the tool body and to control the motor member to move the slider member to positions corresponding thereto. The micro controller 20 is configured to communicate with such an external device, which may also be
5 for example a smartphone or a tablet, by wireless communication means, such as by the Low Energy (LE) Bluetooth protocol. An electric battery 22 is arranged inside the tool body and connected to provide electric energy to the function of the micro controller 20 and the motor member and also a sensor 23 schematically
10 indicated in Fig 2, arranged inside the tool body and configured to sense the position of the slider member 5 with respect to a fixed part of the tool body giving evidence of the position of the slider member along said path P and send information about the position sensed to the micro controller 20. The micro controller is
15 configured to compare the value of the position sensed with the position value to be obtained for a boring radius to be set in accordance with instructions received from the external device 21 and control the motor member to move the slider member so as to obtain correspondence of these two position values. Integra-
20 tion of such a sensor 23 measuring the actual position of the slider member makes it possible to get high accuracy also for big boring diameter adjustments of the boring tool.

Fig 4 and 5 illustrate a boring tool according to a second embodiment of the invention, and components of this boring tool having
25 correspondence with components in the first embodiment have been provided with the same reference numerals added with prime. The motor member 12' is in this embodiment arranged beside the slider member 5' within an enlarged perimeter around
30 the slider member and is configured to drive a part thereof in the form of an axle 15' to rotate around a rotation axis A extending in parallel with said path P. The motor member is configured to rotate a gear 24 in engagement with another gear 25 so as to rotate a threaded member in the form of a ball screw 26 in en-
35 gagement with another threaded member in the form of a ball nut 27, which is fixed with respect to the slider member 5'. Thus, rotation of the ball screw 26 will cause the slider member 5' to

move along said path P for changing the distance of the cutting edge 11' of the cutting insert 9' to the rotation axis C of the boring tool and by that the radius to be created in a hole of a work-piece when bored by rotation of the tool body.

5

The invention is of course not restricted to the embodiments thereof described above, but many possibilities to modifications thereof would be apparent to a person with skill in the art without departing from the scope of the invention as defined in the appended claims.

10

The motor member is in the embodiments described above a rotational electrical motor, but it may be of any conceivable type, such of a linear translation type.

15

Claims

1. A boring tool comprising
- 5 • a tool body (2, 2') including a front end (3) and a rear end (4), between which a central rotation axis (C) extends around which the tool body is rotatable in a direction of rotation (R),
- 10 • a slider member (5, 5') which is arranged movably inside the tool body along a path (P) extending transversely to said rotation axis,
- 15 • an insert pocket (6) associated with the slider member to move therewith and configured to receive a cutting insert (9, 9') to be secured therein by a fastening member (10), which cutting insert has a cutting edge (11, 11') and projects from the tool body transversely to said rotation axis,
- 20 • a motor member (12, 12') connected to the slider member (5, 5') and controllable to move the slider member transversely to said rotation axis for changing the distance of the cutting edge (11, 11') of the cutting insert to said rotation axis and by that the radius to be created in a hole of a workpiece when bored by rotation of the tool body, and
- 25 • a control unit (12, 12') configured to control the motor member to move the slider member (5, 5'),
- 30 **characterized** in that the motor member (12, 12') is arranged inside the tool body together with the slider member (5, 5') in a cutting part (14) of the tool body at said front end, and that the motor member is arranged in parallel with said transversal extension of the slider member (5, 5') along said path (P).
2. A boring tool according to claim 1, **characterized** in that the slider member (5, 5') is movable by action of the motor member (12, 12') along said path (P) between two end positions corresponding to a said boring radius at the outermost end position exceeding the boring radius at the innermost
- 35

end position by at least 10%, 10%-60%, 20%-50% or 30%-50%.

- 5 3. A boring tool according to claim 1 or 2, **characterized** in that the control unit comprises a micro controller (20) arranged inside the tool body in said cutting part (14) thereof.
- 10 4. A boring tool according to claim 3, **characterized** in that the micro controller (20) is configured to communicate with a device (23) located externally of the tool body (2) so as to receive set values of boring diameters to be achieved by rotation of the tool body and to control the motor member (12, 12') to move the slider member (5, 5') to positions corresponding thereto.
- 15 5. A boring tool according to claim 4, **characterized** in that the micro controller (20) is configured to communicate with a said device (23) by wireless communication means.
- 20 6. A boring tool according to any of claims 3-5, **characterized** in that it comprises an energy storing member (22), such as an electric battery, arranged inside the tool body and connected to provide electric energy to the function of the micro controller (20) and the motor member (12, 12').
- 25 7. A boring tool according to any of the preceding claims, **characterized** in that it further comprises a sensor (23, 23') arranged inside the tool body and configured to sense the position of the slider member (5, 5') with respect to a fixed part of the tool body giving evidence of the position of said slider member along said path (P) and send information about the position sensed to the control unit (20), and that the control unit is configured to compare the value of the position sensed with a position value to be obtained for a boring radius to be set and control the motor member (12, 12') to move the slider member (5, 5') so as to obtain correspondence of these two position values.
- 30
- 35

8. A boring tool according to any of the preceding claims, **characterized** in that the motor member (12, 12') is configured to drive a member (15, 15') thereof to rotate or to carry out a linear translation movement so as to move the sliding member (5, 5').
9. A boring tool according to any of the preceding claims, **characterized** in that the motor member (12, 12') is configured to cause movement of the slider member (5, 5') by rotating a threaded member (16, 26) in engagement with a thread of the slider member, of a member arranged to move with the slider member or of a member fixed with respect to the tool body.
10. A boring tool according to any of the preceding claims, **characterized** in that the slider member (5) is hollow and the motor member (12) is arranged inside the slider member.
11. A boring tool according to claim 11, **characterized** in that the motor member (12) is arranged inside a hollow screw (16) with an external thread (17) in engagement with an inner thread (18) of a member (19) fixed to the slider member (5), and that the motor member is configured to rotate said screw (16) so as to move this and by that the slider member (5) along said path (P).
12. A boring tool according to any of claims 1-10, **characterized** in that the motor member (12') is arranged beside the slider member (5') within an enlarged perimeter around the slider member.
13. A boring tool according to claim 13, **characterized** in that the motor member (12') is configured to drive a part (15') thereof to rotate around a rotation axis (A) extending in parallel with said path (P).

14. A boring tool according to claim 14, **characterized** in that the motor member (12') is configured to rotate a gear (24) in engagement with another gear (25) so as to rotate a threaded member (26) in engagement with another threaded member (27), in which one of these threaded members is connected to the slider member (5') so as to cause movement of the slider member along said path (P) by rotation of said gears (24, 25).

1/5




Fig 1




Fig 2

3/5





Fig 3



4/5




Fig 4

5/5




Fig 5

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/051973

A. CLASSIFICATION OF SUBJECT MATTER
INV. B23B29/034
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B23B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 2 095 897 B1 (COMAU SPA [IT]) 22 December 2010 (2010-12-22) cited in the application paragraph [0016] paragraph [0014] - paragraph [0015] paragraph [0006] paragraph [0007] -----	3-6
X	JP 3 252996 B2 (KITAMURA MACHINERY CO LTD) 4 February 2002 (2002-02-04) abstract; figures -----	1,2,8,9
A	US 2012/058871 A1 (NAKAMURA EIJI [JP] ET AL) 8 March 2012 (2012-03-08) abstract; figures -----	10,11,14
X	----- -/-	1



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 March 2017

Date of mailing of the international search report

10/04/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Rabolini, Marco

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/051973

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6 053 082 A (RUPP GERHARD [DE] ET AL) 25 April 2000 (2000-04-25) figures	1

A	CH 351 015 A (GENEVOISE INSTR PHYSIQUE [CH]) 31 December 1960 (1960-12-31) figures	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2017/051973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2095897	B1	22-12-2010	AT 492364 T 15-01-2011
		CN 101518874 A 02-09-2009	
		EP 2095897 A1 02-09-2009	
		KR 20090092217 A 31-08-2009	
		US 2009215598 A1 27-08-2009	
JP 3252996	B2	04-02-2002	JP 3252996 B2 04-02-2002
		JP H08155705 A 18-06-1996	
US 2012058871	A1	08-03-2012	CN 102441818 A 09-05-2012
		EP 2425922 A2 07-03-2012	
		JP 5703639 B2 22-04-2015	
		JP 2012055983 A 22-03-2012	
		US 2012058871 A1 08-03-2012	
US 6053082	A	25-04-2000	DE 19813615 A1 25-11-1999
		US 6053082 A 25-04-2000	
CH 351015	A	31-12-1960	CH 351015 A 31-12-1960
		DE 1193768 B 26-05-1965	
		GB 926536 A 22-05-1963	