(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

WIPOIPCT

(43) International Publication Date 25 July 2013 (25.07.2013)

- (21) International Application Number: PCT/US20 13/022094
- (22) International Filing Date: 18 January 2013 (18.01.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 61/588,3 10 19 January 2012 (19.01.2012) US
- (71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, Ohio 45202 (US).
- (72) Inventor: BREYFOGLE, Laurie, Ellen; 1 Procter & Gamble Plaza, Cincinnati, Ohio 45202 (US).
- (74) Agent: GUFFEY, Timothy B.; c/o THE PROCTER & GAMBLE COMPANY, Global Patent Services, 299 East 6th Street, Sycamore Building, 4th Floor, Cincinnati, Ohio 45202 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

(10) International Publication Number WO 2013/109850 A2

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind & regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— witho_{unit} in the fiber of the sector is the best of the computed by the sector of the sector of

(54) Title: METHODS FOR SMOOTHING WRINKLES AND SKIN TEXTURE IMPERFECTIONS



(57) Abstract: A skin smoothing composition that has from about 0.5 to about 4% sodium silicate as measured by silica content $(S1O_2)$ and from about 0.1% to about 4.0% of a polyvalent silicate. The composition is provided in a carrier, for example, from about 10 to 98% water, and can be in the form of a water gel or oil-in-water emulsion. Further, the weight ratio of sodium silicate to the polyvalent silicate is equal to or greater than 0.7. and the polyvalent silicate is a silicate clay selected from the group consisting of bentonite, laponite, smectite, and kaolinite. Kits containing these compositions and methods of using these compositions are also provided.

METHODS FOR SMOOTHING WRINKLES AND SKIN TEXTURE IMPERFECTIONS

FIELD OF THE INVENTION

5 The present invention relates to personal care compositions, and methods of use thereof, which exhibit adhesion and contraction of skin to smooth and flatten wrinkles and texture imperfections.

BACKGROUND OF THE INVENTION

- 10 Visible wrinkles, particularly those on the face and around the eyes, are one of the most prevalent and undesirable signs of aging. Many consumer products and procedures are devoted to hiding or reducing wrinkles. These products and procedures can be simple and inexpensive, for example, applying make-up, particularly a primer or colored foundation, to simply cover the wrinkles on a consumer's skin. Far more expensive and drastic procedures, such as surgical face lifts and Botox injections are also used to reduce the appearance of wrinkles on the face. There are a plethora of lotions and creams which purport to hydrate the skin making it more supple and reducing the appearance of wrinkles. Some of these liquid products contain active ingredients, for example niacinamide, that help repair and rejuvenate skin over time. All of these products and procedures have drawbacks.
- 20 Foundation and other make-up products are often visible, offer minimal texture benefits, and have no lasting effect on the skin. Once the make-up is removed, the skin is the same in appearance as before the make-up was applied. Liquid products can have chronic, acute or both effects on the skin. Hydration and optical effects are common acute benefits, and these benefits wear-off over time. Chronic actives may rejuvenate or repair the skin over time. These chronic benefits take time to occur and are incremental improvements. There are limits to how effective these chronic benefits can be. Plastic surgery and injections of chemicals have a more pronounced, immediate and dramatic effect on the look of a consumer's skin, but these procedures can be very expensive and come with many risks. Plastic surgery has the same risk of failure as any other surgical procedure, including disfigurement.
- 30 Attempts have been made to develop new categories of products to improve the appearance of skin without the drawbacks of existing products and procedures. One such family of products can be generally classified as "adhesive, contractile film formers". Film formers are chemical compositions that when applied to skin, leave a pliable, cohesive and continuous covering. A select group of film formers are also adhesive to skin and even contractile.

Wrinkles, in their simplest form, are crevices or valleys in the skin. When an adhesive, contractile film former is applied, the skin at the bottom of the valley or crevice may be pulled to the surface, causing skin look smooth and wrinkle-free. The drawbacks of existing adhesive, contractile film forming products include discomfort caused by the contraction of the skin, irritation of the skin, cracking of the film as the consumer uses her face muscles, incompatibility with other cosmetic products in her regimen, and visibility of the film which is often whitish and noticeable. Curing or reducing one of these problems has, in the past, exacerbated one of the

other problems.

5

Sodium silicate is an adhesive, contractile film forming ingredient used today. High 10 levels of sodium silicate can result in high to moderate skin contraction, resulting in high to moderate immediate wrinkle reduction. Unfortunately, however, the more sodium silicate used, the more skin irritation observed and the more brittle (less durable) the dried film. One skilled in the art may attempt to use plasticizers to combat the problem of a brittle film, however, as stated above resolving this issue exacerbates others—in this case whiteness increases and contraction is 15 reduced. Thus, these solutions are not acceptable to the consumer.

Thus, there is a continuing desire to provide compositions and methods of treatment that can improve the appearance of skin, more specifically, reduce the appearance of wrinkles on skin, while balancing the correct amount of skin contraction, film flexibility, lack of film whiteness, contraction resiliency, compatibility with other cosmetic products, and lack of skin imitation. These and other improvements over the art on provided by the present invention.

20 irritation. These and other improvements over the art are provided by the present invention.

SUMMARY OF THE INVENTION

There is provided a skin smoothing composition that has from about 0.5 to about 4% sodium silicate as measured by silica content $(Si0_2)$ and from about 0.1% to about 4.0% of a polyvalent silicate. The compositions of this invention may comprise at least one plasticizer present in the composition at from about 1% to about 20%, by weight. Additionally, the levels of sodium silicate, polyvalent silicate, and plasticizer are to be balanced according to these ratios (a) sodium silicate (Si02) to polyvalent silicate ratio equal to or greater than 0.7, and/or (b) total silicate (sodium silicate + polyvalent silicate) to total plasticizer ratio equal to or less than 1.8. The composition is provided in a carrier, for example, from about 10 to 98% water, and can be in the form of a water-based formulation, such as a water gel, oil-in-water emulsion, or a composition comprising one or both of these forms.

In one aspect of this invention the sodium silicate has a molar ratio of Si02:Na20 ratio of 3.3 or less, and the polyvalent silicate is a silicate clay selected from the group consisting of bentonite, laponite, smectite, and kaolinite. It is preferred that the polyvalent silicate is stable at a pH of greater than 10. The plasticizer can be, for example, an alkyl mono-glycol or di-glycol containing 3 to 5 carbon atoms. Further, the plasticizer can be propylene glycol.

Other optional ingredients in the compositions include polysaccharide thickeners, for example, xanthan gum, and from about 0.001% to about 5% of a particulate materials selected from the group consisting of colored and uncolored pigments, interference pigments, inorganic powders, organic powders, composite powders, optical brightener particles, and mixtures thereof. Skin care actives are also preferred for use in the compositions of the present invention and can be selected from the group consisting of vitamin B compounds, vitamin C compounds, vitamin E compounds, peptides, sugar amines, natural botanical extract, oil control agents, skin lightening agents, and combinations thereof, more preferably from the group consisting of niacinamide, palmitoyl-lysine-threonine, palmitoyl-lysine-threonine-lysine-serine, N-

10 acetyl-D-glucosamine, salicylic acid, dehydroacetic acid, sodium dehydroacetate, hexamidine compounds, and combinations thereof.

According to in vitro tests predictive of in vivo performance, the compositions of this invention exhibit contraction from about 0.2 to about 0.9 inches, whiteness equal to or lower than 40, loss of contraction equal to or lower than 20%, and polar component surface energy equal to or lower than $35 \gamma \rho/mJ/m^2$. Further, the films formed by the compositions of the present invention exhibit a balance of all factors mentioned in the previous sentence, which can be expressed using a multivariable equation such as performed in calculating the Overall Performance Score, which is lower than 2.8 for consumer preferred executions.

In another aspect of this invention there is provided a kit that has a skin smoothing composition comprising from about 0.5% to about 4% sodium silicate as measured by silica content (SiO_2) , from about 0.1% to about 4.0% of a polyvalent silicate, and from about 10% to 98% water, wherein the composition is in the form of a water-based formulation, such as, a water gel or oil-in-water emulsion. The kit further comprises at least one additional component selected from the group consisting of an oil-in-water emulsion, water-in oil emulsion, thickened water gel, thickened oil mixture and wherein these compositions are in the form of skin care compositions or colored cosmetic compositions. Further, the kit contains instructions for complying with a regimen to provide a benefit to keratinous tissue. The kit can optionally contain additional components selected from the group consisting of applicators, delivery implements, or powered delivery devices to deliver the personal care composition to skin.

15

5

In response to the technical problems identified in the Background of The Invention, the present invention provides compositions and kits that provide films with excellent initial and lasting contraction, are flexible, transparent, and non-irritating. The levels of polyvalent silicate (clay), sodium silicate, and plasticizer are balanced to achieve an improvement in initial and lasting contraction without added or excessive stiffness, whiteness, or irritation. When the polyvalent silicate, sodium silicate, and plasticizer levels are properly balanced (Silicate (Si02): polyvalent silicate equal to or greater than 0.7, total silicate (sodium silicate + polyvalent silicate) to total glycol ratio equal to or less than 1.8) it has been surprisingly learned this carries the additional advantages of both lowering the whiteness of the film, and improving the contraction resiliency. Additionally, in a kit context, when the skin smoothing composition is applied to skin in conjunction with application of a relatively hydrophilic formulation, the level of contraction, and thus wrinkle reduction benefit, increases. This insight enables an increase in contraction without the addition of sodium silicate and the baggage therewith associated.

Further forms of the present invention will be appreciated in the detailed description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention can be better understood with reference to the following drawings and 5 description. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. Moreover, in the figures, like reference numerals designate corresponding parts throughout the different views. In the drawings:

FIG. 1 is an exploded, and partially cut away view of an applicator suitable for applying skin smoothing compositions in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

All percentages and ratios used herein are by weight of the total composition and all measurements made are at 25°C, unless otherwise designated. All numeric ranges are inclusive of narrower ranges; delineated upper and lower range limits are interchangeable to create further ranges not explicitly delineated.

The compositions of the present invention can comprise, consist essentially of, or consist of, the essential components as well as optional ingredients described herein. As used herein, "consisting essentially of means that the composition or component may include additional

ingredients, but only if the additional ingredients do not materially alter the basic and novel characteristics of the claimed compositions or methods.

The term "apply" or "application" as used in reference to a composition, means to apply or spread the compositions of the present invention onto a substrate such as the human skin surface or epidermis.

5

The term "dermatologically acceptable" as used herein means that the compositions or components described are suitable for use in contact with human skin tissue without undue toxicity, incompatibility, instability, allergic response, and the like.

The term "safe and effective amount" as used herein means an amount of a compound or 10 composition sufficient to significantly induce a positive benefit.

The term "facial skin surface" as used herein refers to one or more of forehead, periorbital, cheek, perioral, chin, and nose skin surfaces. While facial skin surfaces are of concern and are exemplified herein, other skin surfaces may be treated with the compositions of the present invention, for example, surfaces typically not covered by clothing such as facial skin surfaces, hand and arm skin surfaces, foot and leg skin surfaces, and neck and chest skin surfaces

(e.g., decolletage).

The terms "stable" and "stability" as used herein mean a composition which is substantially unaltered in chemical state, physical homogeneity and/or color when the composition is at a temperature of from about 1°C to about 40°C.

20

25

15

Compositions

The present invention relates to various compositions and, more specifically, to compositions for application to a skin surface. The compositions may be in a wide variety of product forms that include, but are not limited to, solutions, suspensions, lotions, creams, gels, toners, sticks, pencil, sprays, aerosols, ointments, cleansing liquid washes and solid bars, pastes, foams, powders, mousses, wipes, strips, patches, hydrogels, film-forming products, facial and skin masks (with and without insoluble sheet), make-up such as foundations, eye liners, and eye shadows, and the like. The composition form may follow from the particular dermatologically acceptable carrier chosen, if present in the composition.

30

Film Forming Composition

The skin smoothing compositions of this invention comprise from about 0.5 to about 4% sodium silicate as measured by silica content (SiO₂) and from about 0.1% to about 4.0% of a polyvalent silicate. The polyvalent silicate is an silicate clay selected from the group consisting

WO 2013/109850

5

6

of bentonite, laponite, smectite, and kaolinite. It is preferred that the polyvalent silicate is stable at a pH of greater than 10.0. Preferred film forming compositions form a non-tacky film which is removable with water used with cleansers such as soap. The ratio silica to polyvalent silicate is preferably from about 0.70 to about 4.0, more preferably from about 1.0 to about 3.0, even more preferably from about 1.0 to about 2.0. It is preferred the overall film forming composition has a pH of 10.0, more preferably greater than 10.5, and even more preferably greater than 11.0.

In addition to the silica and polyvalent silicate film formers of the present invention, the film forming composition can optionally comprise film forming polymers. Examples of suitable optional film forming polymeric materials include:

a) sulfopolyester resins, such as AQ sulfopolyester resins, such as AQ29D, AQ35S, AQ38D,

AQ38S, AQ48S, and AQ55S (available from Eastman Chemicals);

- b) polyvinylacetate/polyvinyl alcohol polymers, such as Vinex resins available from Air Products, including Vinex 2034, Vinex 2144, and Vinex 2019;
- c) acrylic resins, including water dispersible acrylic resins available from National Starch under the trade name "Dermacryl", including Dermacryl LT;
- d) polyvinylpyrrolidones (PVP), including Luviskol K17, K30 and K90 (available from BASF), water soluble copolymers of PVP, including PVP/VA S-630 and W-735 and PVP/dimethylaminoethylmethacrylate Copolymers such as Copolymer 845 and Copolymer 937 available from ISP, as well as other PVP polymers disclosed by E.S. Barabas in the Encyclopedia of Polymer Science and Engineering, 2 Ed. Vol. 17 pp. 198-257;
- 15 e) polyurethanes, including Polyderm PE-PA, available from Alzo International Inc.;
 - f) co-polymerized amido ester compounds, including Polyderm PPG-17, available from Alzo International Inc.;
 - g) acrylic latex dispersions;
 - h) high molecular weight silicones such as dimethicone and organic-substituted dimethicones,

20 especially those with viscosities of greater than about 50,000 mPas;

- i) high molecular weight hydrocarbon polymers with viscosities of greater than about 50,000 mPas;
- j) polysaccharide gums such as xanthan gum, dehydroxanthan gum, cellulose derivatives, crosslinked-xanthan gum, hydroxypropyl xanthan gum, undecylenoyl xanthan gum,
- 25 deacetylated xanthan gum, guar gum, cellulose gum, carrageenan, hydroxylpropyl methyl cellulose, and sodium carboxymethyl chitin;
 - k) organosiloxanes, including organosiloxane resins, fluid diorganopolysiloxane polymers and silicone ester waxes.

7

Examples of these optional polymers are found in PCT publication Nos. W096/33689, published 10/31/96; WO97/17058, published 5/15/97; and US Patent No. 5,505,937 issued to Castrogiovanni et al. 4/9/96, all incorporated herein by reference. Additional film forming polymers suitable for use herein include the water-insoluble polymer materials in aqueous emulsion and water soluble film forming polymers described in PCT publication No. W098/18431, published 5/7/98, incorporated herein by reference. Examples of high molecular weight hydrocarbon polymers with viscosities of greater than about 50,000mPas include polybutene, polybutene terephthalate, polydecene, polycyclopentadiene, and similar linear and branched high molecular weight hydrocarbons.

- 10 Optional film forming polymers include organosiloxane resins comprising combinations of R3S1O1/2 "M" units, R2S1O "D" units, RS1O3/2 "T" units, S1O2 "Q" units in ratios to each other that satisfy the relationship $RnSiO_{(4_{-n})}/2$ where n is a value between 1.0 and 1.50 and R is methyl. Note that a small amount, up to 5%, of silanol or alkoxy functionality may also be present in the resin structure as a result of processing. The organosiloxane resins must be solid 15 at about 25°C and have a molecular weight range of from about 1,000 to about 10,000 grams/mole. The resin is soluble in organic solvents such as toluene, xylene, isoparaffins, and cyclosiloxanes or the volatile carrier, indicating that the resin is not sufficiently crosslinked such that the resin is insoluble in the volatile carrier. Particularly preferred are resins comprising repeating monofunctional or R3SiOiy2 "M" units and the quadrofunctional or S1O2 "Q" units, otherwise known as "MQ" resins as disclosed in U.S. Patent 5,330,747, Krzysik, issued July 19, 20 1994, incorporated herein by reference. In the present invention the ratio of the "M" to "Q" functional units is preferably about 0.7 and the value of n is 1.2. Organosiloxane resins such as these are commercially available such as trimethylsiloxysilicate / cyclomethicone D5 Blend
- available from GE Toshiba Silicone, Wacker 803 and 804 available from Wacker Silicones Corporation of Adrian Michigan, KP545 from Shin-Etsu Chemical and G. E. 1170-002 from the General Electric Company. In the present invention, by having film forming polymer mainly in the second layer, the film forming polymer will exist in a higher concentration at a localized area, and thereby forming a film of higher film intensity when applied to the skin, compared to the remainder of the composition. Such concentrated area of high film intensity provides improved adhesion of the entire composition to the skin. Namely, by providing the film forming polymer mainly in the second layer, the amount of film forming polymer included in the entire composition can be reduced, or if the same amount of film forming polymer is formulated in the

second layer, an entire composition having improved adhesion is obtained. In a preferred

embodiment, the content level of film forming polymer in the second layer is from about 0.1% to about 20%, preferably from about 0.5% to about 10%, more preferably from about 1% to about 8%.

Plasticizer

5

10

The compositions of this invention may comprise at least one plasticizer present in the composition at from about 1% to about 20%, preferably from about 1% to about 15%, more preferably 2% to about 10% by weight. The plasticizer can be, for example, an alkyl mono-glycol or di-glycol containing 3 to 5 carbon atoms. Further the plasticizer can be propylene glycol. The plasticizers herein are selected from the group consisting of polyhydric alcohols, water soluble alkoxylated nonionic polymers, and mixtures thereof. Polyhydric alcohols useful herein include glycerin, propylene glycol, 1,3- butylene glycol, 1,3 propanediol, dipropylene glycol, diglycerin, sodium hyaluronate, polypropanediol and mixtures thereof.

Commercially available plasticizers herein include: glycerin available from Asahi Denka; propylene glycol with tradename LEXOL PG-865/855 available from Inolex, 1.2-PROPYLENE

15 GLYCOL USP available from BASF; 1,3-butylene glycol available from Kyowa Hakko Kogyo; dipropylene glycol with the same tradename available from BASF; 1,3 propane diol with tradename ZEMEA from DuPont Company; polypropanediol with tradename CERENOL H250 from DuPont Company; diglycerin with tradename DIGLYCEROL available from Solvay GmbH; sodium hyaluronate with tradename ACTIMOIST available from Active Organics,

20 AVIAN SODIUM HYALURONATE series available from Intergen, HYALURONIC ACID Na available from Ichimaru Pharcos.

Dermatologically Acceptable Carrier

The compositions of the present invention may also comprise a dermatologically acceptable carrier (which may be referred to as "carrier") for the composition. The phrase "dermatologically acceptable carrier", as used herein, means that the carrier is suitable for topical application to the keratinous tissue, has good aesthetic properties, is compatible with the actives in the composition, and will not cause any unreasonable safety or toxicity concerns. In one embodiment, the carrier is present at a level of from about 50% to about 99%, about 60% to about 98%, about 70% to about 98%, or, alternatively, from about 80% to about 95%, by weight of the composition.

The carrier can be in a wide variety of forms. Non-limiting examples include simple solutions (e.g.), aqueous, organic solvent, or oil based), emulsions, suspensions, and solid forms (e.g.), gels, sticks, flowable solids, or amorphous materials). In certain embodiments, the dermatologically acceptable carrier is in the form of an emulsion or suspension. Emulsion or

suspension may be generally classified as having a continuous aqueous phase (e.g., oil-in-water and water-in-oil-in-water) or a continuous oil phase (e.g., water-in-oil and oil-in-water-in-oil). The oil phase of the present invention may comprise silicone oils, non-silicone oils such as hydrocarbon oils, esters, ethers, and the like, and mixtures thereof.

5

Emulsions may further comprise an emulsifier. The composition may comprise any suitable percentage of emulsifier to sufficiently emulsify the carrier. Suitable weight ranges include from about 0.1% to about 10% or about 0.2% to about 5% of an emulsifier, based on the Suitable weight of the composition. Emulsifiers may be nonionic, anionic or cationic. emulsifiers are disclosed in, for example, U.S. Patent 3,755,560, U.S. Patent 4,421,769, and

10 McCutcheon's Detergents and Emulsifiers, North American Edition, pages 317-324 (1986). Suitable emulsions may have a wide range of viscosities, depending on the desired product form. The carrier may further comprise a thickening agent as are well known in the art to provide compositions having a suitable viscosity and rheological character.

Pigments and Powders

25

30

15 The compositions of the present invention can comprise from about 5% to about 45%, preferably from about 5% to about 30% of a pigment powder component. The pigments included in the pigment powder component herein may be hydrophobic in nature, or hydrophobically treated. By keeping the level of pigment component low, the entire composition maintains flexibility to accommodate other components which provide spreadability, 20 moisturization, and fresh and light feel. The species and levels of the pigments are selected to provide, for example, shade, coverage, good wear performance, and stability in the composition.

Pigments useful for the pigment component herein are inorganic and organic powder such as talc, mica, sericite, synthetic fluorphlogopite, pearl pigments such as alumina, barium sulfate, calcium secondary phosphate, calcium carbonate, coverage titanium oxide, finely divided titanium oxide, zirconium oxide, normal particle size zinc oxide, hydroxy apatite, iron oxide, iron titanate, ultramarine blue, Prussian blue, chromium oxide, chromium hydroxide, cobalt oxide, cobalt titanate, titanium oxide coated mica; organic powder such as polyester, polyethylene, polystyrene, methyl methacrylate resin, cellulose, 12-nylon, 6-nylon, styreneacrylic acid copolymers, polypropylene, vinyl chloride polymer, tetrafluoroethylene polymer, boron nitride, fish scale guanine, laked tar color dyes, and laked natural color dyes. Such pigments may be treated with a hydrophobical treatment agent, including: silicone such as

methicone, dimethicone, and perfluoroalkylsilane; fatty material such as stearic acid and disodium hydrogenated glutamate; metal soap such as aluminium dimyristate; aluminium hydrogenated tallow glutamate, hydrogenated lecithin, lauroyl lysine, aluminium salt of

perfluoroalkyl phosphate, and aluminium hydroxide as to reduce the activity for titanium dioxide, and mixtures thereof. Such pigments may also be coated with substances considered more hydrophilic such as polysaccharides, caprylyl silane, or polyethylene oxide silane treatments.

5

- Commercially available pigment powder component includes coverage titanium dioxide, such as SI-T-CR-50Z, Si-Titanium Dioxide IS, SA-Titanium Dioxide CR-50, SI-FTL-300 and SA/NAI-TR-10, all of them are available from Miyoshi Kasei, iron oxide and cyclopentasiloxane and dimethicone and disodium hydrogenated glutamate: SA/NAI-Y-10/D5(70%) / SA/NAI-R-10/D5(65%) / SA/NAI-B-10/D5(75%) available from Miyoshi Kasei, iron oxide and disodium
- 10 hydrogenated glutamate: SA/NAI-Y-10 / SA/NAI-R-10 / SA/NAI-B-10 available from Miyoshi Kasei, iron oxide and methicone: SI Mapico Yellow Light Lemon XLO / SI Pure Red Iron Oxide R-1599 / SI Pure Red Iron Oxide R-3098 / SI Pure Red Iron Oxide R-4098 / SI Black Iron Oxide No.247 available from Daito Kasei, alumina and titanium dioxide and methicone: SI-LTSG30AFLAKE H (5%) LHC available from Miyoshi Kasei, talc and methicone: SI-Talc
- 15 JA13R LHC available from Miyoshi Kasei, mica and methicone: SI Mica available from Miyoshi Kasei, dimethicone: SA-SB-300 available from Miyoshi Kasei, mica and methicone: SI Sericite available from Miyoshi Kasei, mica and dimethicone: SA Sericite available from Miyoshi Kasei, mica and C9-15 Fluoroalcol Phosphates and Triethoxy Caprylylsilane: FOTS-52 Sericite FSE available from Daito Kasei, Talc and C9-15 Fluoroalcol Phosphates and triethoxy
- 20 caprylylsilane: FOTS-52 Talc JA-13R available from Daito Kasei, boron nitride and methicone: SI02 Boron Nitride SHP-6 available from Daito Kasei, boron nitride and C9-15 fluoroalcol phosphates and triethoxy caprylylsilane: FOTS-52 Boron Nitride available from Daito Kasei, mica and titanium dioxide and methicone: SI Sericite TI-2 available from Miyoshi Kasei, mica and titanium dioxide and methicone: SI Mica TI-2 available from Miyoshi Kasei, talc and titanium dioxide and methicone: SI Talc TI-2 available from Miyoshi Kasei, lauroyl lysine: AMIHOPE LL available from Ajinomoto, synthetic fluorphlogopite and methicone: PDM-5L(S)
 - / PDM-IOL(S) / PDM-20L(S) / PDM-40L(S) available from Topy Industries.

Adhesive Agents

The compositions of the present invention can comprise from about 0.1% to about 10%, 30 preferably from about 0.1% to about 2% of an adhesive agent. The species and levels of the adhesive agents are selected to provide, for example, a more flexible, longer-lasting benefit to composition, and/or better compatibility with other skin care or cosmetic formulations.

Examples of suitable adhesive agents include polyure thanes, including Polyderm PE-PA, available from Alzo International Inc.; co-polymerized amido ester compounds, including Polyderm PPG-17, available from Alzo International Inc.; and Acrylic Latex Dispersions.

Skin Active Agents

5

The compositions of the present invention may comprise a skin active agent which provides a particular skin care benefit characteristic of the usage of the skin care product. Herein, skin care benefit may include benefits related to appearance or make-up of the skin. The skin care active can provide acute (immediate and short lived) benefits, or chronic (long term and longer lasting) benefits.

10 The term "skin active agent" as used herein, means an active ingredient which provides a cosmetic and/or therapeutic effect to the area of application on the skin. The skin active agents useful herein include skin lightening agents, anti-acne agents, emollients, non-steroidal anti-inflammatory agents, topical anaesthetics, artificial tanning agents, anti-microbial and anti-fungal actives, skin soothing agents, sun screening agents, skin barrier repair agents, anti-wrinkle agents, anti-skin atrophy actives, lipids, sebum inhibitors, sebum inhibitors, skin sensates, protease inhibitors, anti-itch agents, hair growth inhibitors, desquamation enzyme enhancers, anti-glycation agents, and mixtures thereof. When included, the present composition comprises from about 0.001% to about 20%, preferably from about 0.1% to about 10% of at least one skin active agent.

20 The type and amount of skin active agents are selected so that the inclusion of a specific agent does not affect the stability of the composition. For example, hydrophilic agents may be incorporated in an amount soluble in the aqueous phase, while lipophilic agents may be incorporated in an amount soluble in the oil phase.

Other skin active agents purported to exhibit expression-line relaxing benefits for use in 25 the present invention include, but are not limited to, Lavandox available from Barnet Products Corporation; Thallasine 2, available from BiotechMarine; Argireline NP, available from Lipotec; Gatuline In-Tense and Gatuline Expression, available from Gattefosse; Myoxinol LS 9736 from BASF Chemical Company, Syn-ake, available from DSM Nutritional Products, Inc.; and Instensyl®, available from Silab, Inc; Sesaflash[™], available from Seppic Inc.

30

Skin lightening agents useful herein refer to active ingredients that improve hyperpigmentation as compared to pre-treatment. Useful skin lightening agents herein include ascorbic acid compounds, vitamin $_{\rm B \ 3}$ compounds, azelaic acid, butyl hydroxyanisole, gallic acid and its derivatives, glycyrrhizinic acid, hydroquinone, kojic acid, arbutin, mulberry extract, and

mixtures thereof. Use of combinations of skin lightening agents is believed to be advantageous in that they may provide skin lightening benefit through different mechanisms.

Ascorbic acid compounds useful herein include ascorbic acid per se in the L-form, ascorbic acid salt, and derivatives thereof. Ascorbic acid salts useful herein include, sodium, potassium, lithium, calcium, magnesium, barium, ammonium and protamine salts. Ascorbic acid derivatives useful herein include, for example, esters of ascorbic acid, and ester salts of ascorbic acid. Particularly preferred ascorbic acid compounds include 2-o-D-glucopyranosyl-L-ascorbic acid, which is an ester of ascorbic acid and glucose and usually referred to as L-ascorbic acid 2glucoside or ascorbyl glucoside, and its metal salts, and L-ascorbic acid phosphate ester salts such as sodium ascorbyl phosphate, potassium ascorbyl phosphate, magnesium ascorbyl phosphate, and calcium ascorbyl phosphate. Commercially available ascorbic compounds include magnesium ascorbyl phosphate available from Showa Denko, 2-o-D-glucopyranosyl-Lascorbic acid available from Hayashibara and sodium L-ascorbyl phosphate with tradename STAY C available from Roche.

15

Vitamin B₃ compounds useful herein include, for example, those having the formula:



wherein R is -CONH₂ (*e.g.*, niacinamide) or -CH₂OH (*e.g.*, nicotinyl alcohol); derivatives thereof; and salts thereof. Exemplary derivatives of the foregoing vitamin B₃ compounds include nicotinic acid esters, including non-vasodilating esters of nicotinic acid, nicotinyl amino acids, nicotinyl alcohol esters of carboxylic acids, nicotinic acid N-oxide and niacinamide Noxide. Preferred vitamin B₃ compounds are niacinamide and tocopherol nicotinate, and more preferred is niacinamide. In a preferred embodiment, the vitamin B₃ compound contains a limited amount of the salt form and is more preferably substantially free of salts of a vitamin B₃ compound. Preferably the vitamin B₃ compound contains less than about 50% of such salt, and is more preferably essentially free of the salt form. Commercially available vitamin B₃ compounds that are highly useful herein include niacinamide USP available from Reilly.

Other hydrophobic skin lightening agents useful herein include ascorbic acid derivatives such as ascorbyl tetraisopalmitate (for example, VC-IP available from Nikko Chemical), ascorbyl palmitate (for example available from Roche Vitamins), ascorbyl dipalmitate (for 30 example, NIKKOL CP available from Nikko Chemical); undecylenoyl phenyl alanine (for example, SEPrWHITE MSH available from Seppic); octadecenedioic acid (for example,

ARLATONE DIOIC DCA available from Uniquema); Oenothera biennis sead extract, and pyrus malus (apple) fruit extract, Water and Myritol 318 and butylene glycol and tocopherol and sscorbil tetraisopalmitate and Paraben and Carbopol 980 and DNA / SMARTVECTOR UV available from COLETICA, magnesium ascorbyl phosphate in hyaluronic filling sphere available from COLETICA and mixtures thereof.

5

10

25

30

Other skin active agents useful herein include those selected from the group consisting of N-acetyl D-glucosamine, panthenol (e.g., DL panthenol available from Alps Pharmaceutical Inc.), tocopheryl nicotinate, benzoyl peroxide, 3-hydroxy benzoic acid, flavonoids (e.g., flavanone, chalcone), farnesol, phytantriol, glycolic acid, lactic acid, 4-hydroxy benzoic acid, acetyl salicylic acid, 2-hydroxybutanoic acid, 2-hydroxypentanoic acid, 2-hydroxyhexanoic acid,

- cis-retinoic acid, trans-retinoic acid, retinol, retinyl esters (e.g., retinyl propionate), phytic acid, N-acetyl-L-cysteine, lipoic acid, tocopherol and its esters (e.g., tocopheryl acetate: DL-a-tocopheryl acetate available from Eisai), azelaic acid, arachidonic acid, tetracycline, ibuprofen, naproxen, ketoprofen, hydrocortisone, acetominophen, resorcinol, phenoxyethanol,
 phenoxypropanol, phenoxyisopropanol, 2,4,4'-trichloro-2'-hydroxy diphenyl ether, 3,4,4'-trichlorocarbanilide, octopirox, lidocaine hydrochloride, clotrimazole, miconazole, ketoconazole, neomycin sulfate, theophylline, and mixtures thereof. In a preferred example, the content level of a skin active agent is from about 0.001% to about 20%, more preferably from about 0.1% to
- 20 Optional Components

about 10%

The compositions hereof may further contain additional components such as those conventionally used in topical products, e.g., for providing aesthetic or functional benefit to the composition or skin, such as sensory benefits relating to appearance, smell, or feel, therapeutic benefits, or prophylactic benefits (it is to be understood that the above-described required materials may themselves provide such benefits).

These components may include, but are not limited to, materials purported to smooth, firm or lift sagging or wrinkled skin including: Quicklift, available from BASF Chemical Company; Syntran PC5100, available from Interpolymer Corporation; Glycolift, available from Solabia USA Inc.; Alguard, available from Frutarom; Easyliance, from Soliance; and Phytodermina Lifting code 9002, available from Istituto Ricerche Applicate.

The CTFA Cosmetic Ingredient Handbook, Second Edition (1992) describes a wide variety of nonlimiting cosmetic and pharmaceutical ingredients commonly used in the industry, which are suitable for use in the topical compositions of the present invention. Such other materials may be dissolved or dispersed in the composition, depending on the relative solubilities of the components of the composition.

UV Protection Powder

UV protection powder provides UV protection benefit in the composition. UV protection 5 powder has a particle size of less than 100nm, which size provide very little coverage effect to the skin. The composition of each layer of the present invention may comprise from about 0% to about 20%, preferably from about 0.1% to about 10% of a UV protection powder, such as micronized titanium dioxide and micronized zinc oxide. The powder included in the pigment component herein is typically hydrophobic in nature, or hydrophobically treated.

10 Commercially available UV protection powder is titanium dioxide and methicone SI-TTO-S-3Z available from Miyoshi Kasei, titanium dioxide and dimethicone and aluminum hydroxide and stearic acid: SAST-UFTR-Z available from Miyoshi Kasei, Zinc oxide : Finex series available from Sakai Chemical Industry.

UV Absorbing Agent

15

20

agent.

The compositions of the present invention may comprise a safe and effective amount of a UV absorbing agent. A wide variety of conventional UV protecting agent are suitable for use herein, such as those described in U.S. Patent 5,087,445, Haffey et al, issued February 11, 1992; U.S. Patent 5,073,372, Turner et al, issued December 17, 1991; U.S. Patent 5,073,371, Turner et al., issued December 17, 1991; and Segarin, et al, at Chapter VIII, pages 189 et seq., of Cosmetics Science and Technology (1972). When included, the present composition comprises from about 0.5% to about 20%, preferably from about 1% to about 15% of a UV absorbing

UV absorbing agent useful herein includes, for example, 2-ethylhexyl-pmethoxycinnamate (commercially available as PARSOL MCX), butylmethoxydibenzoyl-25 methane. 2-hydroxy-4-methoxybenzo-phenone, 2-phenylbenzimidazole-5-sulfonic acid. octyldimethyl-p-aminobenzoic acid, octocrylene, 2-ethylhexyl N,N-dimethyl-p-aminobenzoate, acid, 2-phenylbenzimidazole-5-sulfonic p-aminobenzoic acid, octocrylene, oxvbenzone. homomenthyl salicylate, octyl salicylate, 4,4'-methoxy-t-butyldibenzoylmethane, 4-isopropyl dibenzoylmethane, 3-benzylidene camphor, 3-(4-methylbenzylidene) camphor, Eusolex[™] 6300,

30 Octocrylene, Avobenzone (commercially available as Parsol 1789), and mixtures thereof. <u>Thickener</u>

Useful for the present invention is a thickener. Thickeners can be used for solidifying solid water-in-oil form compositions of the present invention. When used, the thickener is kept

to about 15% of the composition. The thickeners useful herein are selected from the group consisting of fatty compounds, gelling agents, inorganic thickeners and mixtures thereof. The amount and type of thickeners are selected according to the desired viscosity and characteristics of the product. These characteristics may include a synergistic effect between the thickener and the film forming ingredients, thereby enhancing product/film adhesion, contraction, or flexibility, while decreasing whiteness.

5

Thickening agents which can be used in the present invention include, but are not limited to, cross-linked polyacrylates such as Carbopol.TM. (Goodrich); polyacrylate copolymers such as SepiMAX ZEN (Seppic, Inc.); modified acrylate copolymers such as Sepiplus S (Seppic, Inc.)

10 polymeric carboxylates including modified and unmodified starches, polysaccharide gums such as xanthan gum (e.g. CP Kelco's Keltrol CGT and Keltrol T630, Jungbunzlauer's Xanthan Gum), dehydroxanthan gum (e.g. Amaze XT from AkzoNobel), gallactomanan (Solagum Tara from Seppic), and cellulose derivatives (e.g. Natrosol 250). Gums may also include, but are not limited to, crosslinked-xanthan gum, hydroxypropyl xanthan gum, undecylenoyl xanthan gum,

15 deacetylated xanthan gum, guar gum, cellulose gum, carrageenan, hydroxylpropyl methyl cellulose, and sodium carboxymethyl chitin.

Polymers useful herein include swellable, lightly to moderately crosslinked polyvinyl pyrrolidones (PVP) such as ACP-1120 (International Specialty Products), acrylate copolymers/crosspolymers/blends such as acrylate/steareth-20 itaconate copolymer (Structure

20 2001 from AkzoNobel), acrylates/C 10-30 alkyl acrylates copolymer (Amaze XT from AkzoNobel), acrylic acid/VP crosspolymer (Ultrathix PI00 from International Specialty Products).

Fatty compounds useful herein include stearic acid, palmitic acid, stearyl alcohol, cetyl alcohol, behenyl alcohol, stearic acid, palmitic acid, the polyethylene glycol ether of stearyl alcohol or cetyl alcohol having an average of about 1 to about 5 ethylene oxide units, and mixtures thereof. Preferred fatty compounds are selected from stearyl alcohol, cetyl alcohol, behenyl alcohol, the polyethylene glycol ether of stearyl alcohol having an average of about 2 ethylene oxide units (steareth-2), the polyethylene glycol ether of cetyl alcohol having an average of about 2 ethylene oxide units, and mixtures thereof.

30

The gelling agent useful as thickeners of the present invention include esters and amides of fatty acid gellants, hydroxy acids, hydroxy fatty acids, other amide gellants, and crystalline gellants. N-acyl amino acid amides useful herein are prepared from glutamic acid, lysine, glutamine, aspartic acid and mixtures thereof.

Radiant Powder

Radiant powder is a pigment that is particularly effective in providing radiant look to the skin, by having a gloss level of more than 7.0. Gloss level is a parameter which can be measured by a known method using the opacity charts available from THE LENETA COMPANY, Drawdown bar (0.003μ u\eta and 0.006μ u\eta), solvent (KP-545 available from Shin-Etsu Chemical Co., Ltd.), Gloss Checker IG-320 available from HORIBA.

5

25

The radiant powder useful herein includes pearl pigments, such as mica and titanium dioxide and dimethicone: SA-Timiron MP-1001 and SA-Flamenco Orange available from Miyoshi Kasei, Titanium Dioxide and Mica and Alumina and Silica and Demethicone / Methicone Copolymer and Iron Oxide: Relief Color Pink P-2 available from CATALYSTS & CHEMICALS IND. CO., LTD., mica, synthetic mica, boron nitride and specified particle talc

- CHEMICALS IND. CO., LTD., mica, synthetic mica, boron nitride and specified particle talc having an average particle size of about 20μιη and a gloss level of about 7.2 (0.003μιη on white back), 33.0 (0.006μιη on white back), about 8.5 (0.003μιη on black back) and about 10.3 (0.006μιη on black back). Specified particle talc has a higher gloss level and a lower transparency level than normal particle talc. Specifically, the gloss level of specified particle talc is about 130% to 200% vs. normal particle talc and the transparency level of specified particle talc is about 10% to 100% vs. normal particle talc. Transparency level can be measured by a known method using the opacity charts available from THE LENETA COMPANY, Drawdown
- bar (0.003μιη and 0.006μιη), solvent (KP-545 available from Shin-Etsu Chemical Co., Ltd.),
 Spectraflash available from Datacolor. Commercially available specified particle talc is
 available from Miyoshi Kasei Inc. under the trade name of SI-TALC CT-20.

In a single layer formulation, because other powders, such as coverage titanium dioxide, contained in the formulation may overwhelm the radiant powder effect, to achieve the radiant look effect, a typical level of radiant powder is as high as 5%. In the present invention, by formulating the radiant powder mainly in the second layer and coverage titanium dioxide in the first layer, and providing the first and second layers in a manner such that they can be simultaneously applied on the skin, the skin care product of the present invention can provide satisfied radiant appearance effect with lower level of radiant powder. As a result, there is provided more flexibility in product formulation. Compared to a single layer product, a multiple layer product comprising lower level of radiant powder has a better spreadability and light feel

30 on the skin. In a preferred example, the content level of radiant powder in the second layer is from about 5% to about 25%, more preferably from about 10% to about 20% by weight of the composition of the second layer. When calculated based on the total weight of the first layer and the second layer, the preferred content level of radiant powder is from about 0.5% to about 5%. Soft Focus Powder

17

Soft focus powder is a pigment that is particularly effective in providing a soft focus effect to the composition, namely natural finish yet having good coverage for minimizing the appearance of skin troubles, when incorporated in a defined amount. Specifically, the soft focus powder herein must meet two parameter criteria to provide such an effect. First, both the Total

- 5 Luminous Transmittance (Tt) and Diffuse Luminous Transmittance (Td) of the pigment are relatively high. The soft focus powder has a Total Luminous Transmittance (Tt) of from about 40 to about 94 and a Diffuse Luminous Transmittance (Td) of from about 28 to about 38. Without being bound by theory, it is believed that, by having such high Tt and Td values, the soft focus powder exhibits a high transparency, thereby providing an overall natural finish.
 10 Second, the soft focus powder has a relatively high Haze value {(Td / Tt) x 100} of from about
- 32 to about 95. Without being bound by theory, it is believed that, by having such high Haze value, the contrast between lighted area of the skin and shaded area of the skin (such as pores and wrinkles) is minimized for reducing the appearance of the trouble areas.
- Total Luminous Transmittance (Tt), Diffuse Luminous Transmittance (Td), and Haze 15 value {(Td / Tt) x 100} can be measured and calculated by the artisan by reference to ASTM D 1003-00 "Standard Test Method for Haze and Luminous Transmittance of Transparent Plastics". Although the pigments herein are not plastics, the same principles of this specific standard test can be applied.
- The soft focus powder useful herein includes polymethyl/methacrylate (PMMA), silica, 20 hybrid pigments such as alumina treated mica, titanium dioxide treated talc, titanium dioxide treated mica, vinyl dimethicone/methicone silsesquioxane crosspolymer, alumina, barium sulfate and synthetic mica. Commercially available soft focus powder useful herein includes alumina treated mica having the trade name SA Excel Mica JP2 available from Miyoshi Kasei, which has a Total Luminous Transmittance (Tt) of about 87, Diffuse Luminous Transmittance (Td) of 25 about 28, and Haze value {(Td / Tt) x 100} of about 32.

Similar to radiant powder, when formulated with coverage titanium dioxide in a single layer, the content level of a soft focus powder shall be as high as 5% to achieve noticeable natural look effect. However, in the present invention, by formulating soft focus powder mainly in the second layer and coverage titanium dioxide in the first layer, and providing the first and second layers in a manner such that they can be simultaneously applied on the skin, the skin care product of the present invention can provide satisfied natural look effect with relatively low level

of soft focus powder. As a result, the cost of the product can be controlled while also providing more flexibility in product formulation. In a preferred example, the content level of soft focus powder in the second layer is from about 2% to about 25%, more preferably from about 5% to

about 20% based on the composition of the second layer. When calculated on the basis of the total weight of the first layer and the second layer, the preferred content level of soft focus powder is from about 0.5% to about 4%, more preferably from about 1% to about 3%.

Silicone Elastomer

5

10

Soft focus silicone elastomer is crosslinked siloxane elastomer which is particularly effective in providing soft focus effect to the skin. In other words, when incorporated in a cosmetic product a defined amount of silicone elastomer, the silicone elastomer can provide natural finish yet having good coverage for minimizing the appearance of skin troubles. Specifically, silicone elastomer has lower matte level compared with other silicone oil. Matte level is a parameter reflecting soft focus effect, i.e. natural finish of a cosmetic material. The lower the matte level is, the better natural finish the material can provide. Matte level of silicone

lower the matte level is, the better natural finish the material can provide. Matte level of sincone elastomer used in the present application is less than about 40. Matte level can be measured by the PG-IM gloss meter (Incidence angle / Reflection angle: 60/60°) made by Nihon Denshoku Kogyo. Commercially available silicone elastomer useful in the present application includes a silicone elastomer having the tradename KSG-16 available from Shinetsu, which has a matte

level of about 37.

Silicone elastomer suitable for use herein can be emulsifying or non-emulsifying crosslinked siloxane elastomer or mixtures thereof. The term "non-emulsifying" as used herein, defines crosslinked organopolysiloxane elastomer from which polyoxyalkylene units are absent.

The term "emulsifying" as used herein, means crosslinked organopolysiloxane elastomer having at least one polyoxyalkylene (e.g., polyoxyethylene or polyoxypropylene) unit. Non-emulsifying elastomer useful in the present invention is formed via crosslinking organohydroenpolysiloxane with an alpha, omega-diene. Emulsifying elastomer herein includes polyoxyalkylene modified elastomer formed via crosslinking from organohydrogenpolysiloxane with polyoxyalkylene diene or organohydrogenpolysiloxane containing at least one polyether group crosslinked with an alpha, omega-diene. Emulsifying crosslinked organopolysiloxane elastomer can notably be chosen from the crosslinked polymer described in US Patents 5,412,004, 5,837,793, and 5,811,487. In addition, an emulsifying elastomer comprised of dimethicone copolyol crosspolymer (and dimethicone) is available from Shin Etsu under the tradename KSG-21.

30

Non-emulsifying elastomer is dimethicone/vinyl dimethicone crosspolymer. Such dimethicone/vinyl dimethicone crosspolymer is supplied by a variety of suppliers including Dow Corning (DC 9040 and DC 9041), General Electric (SFE 839), Shin Etsu (KSG-15, 16, 18 [dimethicone/phenyl vinyl dimethicone crosspolymer]), and Grant Industries (GRANSILTM line of elastomer). Cross-linked organopolysiloxane elastomer useful in the present invention and

processes for making them are further described in U.S. Patent 4,970,252, 5,760,116, and 5,654,362. Additional crosslinked organopolysiloxane elastomer useful in the present invention is disclosed in Japanese Patent Application JP 61-18708, assigned to Pola Kasei Kogyo KK. Commercially available elastomer preferred for use herein is Dow Coming's 9040 silicone elastomer blend, Shin Etsu's KSG-21, and mixtures thereof.

5

10

15

Similar to the radiant powder, when formulated with coverage titanium dioxide in a single layer, the content level of a silicone elastomer shall be as high as 10% to achieve noticeable natural look effect. However, in the present invention, by formulating a silicone elastomer mainly in the second layer and coverage titanium dioxide in the first layer, and providing the first and second layers in a manner such that they can be simultaneously applied on the skin, the skin care product of the present invention can provide satisfied natural look effect with lower level of silicone elastomer. As a result, the cost of the product can be controlled while also providing more flexibility in product formulation. In a preferred example, the content level of silicone elastomer in the second layer is from about 1% to about 20%, preferably from about 2% to about 15%. When calculated based on the total weight of the first layer and the second layer, the preferred content level of silicone elastomer is from about 0.5% to about 8%, more preferably from about 1% to about 5%.

Oil Absorbing Powder

Oil absorbing powder is a pigment that is particularly effective in absorbing oil, and 20 thereby can be included in the present composition for absorbing excessive sebum from the skin. Specifically, the oil absorbing powder herein has an oil absorbency of at least about 100mf/100g, preferably at least about 200mf/100g. Oil absorbency is a unit well known to the artisan, and which can be measured via: JIS K5101 No.21 "Test Method for Oil Absorbency Level".

Oil absorbing powder useful herein includes spherical silica, and methyl methacrylate copolymer. Commercially available spherical oil absorbing pigments useful herein include spherical silica with tradename SI-SILDEX H-52 available from Miyoshi Kasei, Inc. having an oil absorbency of more than 200mf/100g, vinyl dimethicone/methicone silsesquioxane crosspolymer with tradename KSP-100 and KSP-101 available from ShinEtsu Chemical having an oil absorbency of more than 200mf/100g, and methyl methacrylate copolymer with tradename SA-GMP-0820 available from GANZ Chemical and surface treated by Miyoshi Kasei, Inc. having an oil absorbency of more than 100mf/100g. Typically, inclusion of oil absorbing powder for oil shine control may provide a composition with unfavorable spreadability performance. However, in the present invention, by including oil absorbing powder mainly in the second layer, the unfavorable spreadability performance can be improved. In a preferred

example, the content level of an oil absorbing powder in the second layer is from about 1% to about 10%, more preferably from about 3% to about 5%.

Sebum Solidifying Powder

Sebum solidifying powder useful herein include those comprising a base substance which is coated with low crystalline zinc oxide, amorphous zinc oxide, or mixtures thereof, wherein the zinc oxide is from about 15% to about 25% by weight of the sebum solidifying powder. The base substance may be any organic or inorganic substances that are useful for cosmetic use, including those listed below under "Pigment Powder Component". The sebum solidifying powder herein can be suitably made according to the methods disclosed in US 2002/0031534 Al,

- 10 herein incorporated by reference. The sebum solidifying powder may be surface treated. The sebum solidifying powder useful herein have the ability to solidify sebum, i.e., are effective in adsorbing free fatty acid, diglyceride, and triglyceride, and solidifying them by forming zinc salts thereof, such that a film is formed within about 30 minutes. Moreover, the originally glossy sebum changes appearance into a matte film. Such capability can be distinguished from other oil
- 15 absorbing powder, which are not selective in the type of oil to be absorbed, and do not form a film after absorbing oil, thus may leave glossy gels and pastes after absorbing the sebum. Change in appearance provides a noticeable signal to the user that sebum has been controlled. Sebum solidifying effect may be conveniently measured by mixing a certain amount of powder with a certain amount of artificial sebum, mixing for a certain period of time, and allowing
- 20 standing until solidified or showing matte appearance. The time taken for the mixture to solidify or to change appearance is recorded. The shorter the time taken to solidify or change appearance, the higher the solidifying effect is of the powder.

Commercially available sebum solidifying powder useful herein includes mica coated with hydroxyapatite, 20% zinc oxide with tradename PLV-20, and the same powder surface 25 treated with methicone with tradename SI-PLV-20, both available from Miyoshi Kasei, Inc. Typically, inclusion of sebum solidifying powder for oil shine control may provide a composition with unfavorable spreadability performance. However, in the present invention, by including sebum solidifying powder mainly in the second layer, the unfavorable spreadability performance can be improved. In a preferred example, the content level of sebum solidifying 30 powder in the second layer is from about 0.2% to about 10%, preferably from about 1% to about

Methods of Treatment

7%.

Various methods of treatment, application, regulation, or improvement may utilize the aforementioned compositions. Application of the present compositions can occur on any skin

surface of the body. Skin surfaces of the most concern tend to be those not typically covered by clothing such as facial skin surfaces, hand and arm skin surfaces, foot and leg skin surfaces, and neck and chest skin surfaces (e.g., decolletage). In particular, application may be on a facial skin surface including the forehead, perioral, chin, periorbital, nose, and/or cheek skin surfaces.

5

Many regimens exist for the application of the composition to the skin. The composition may be applied at least once a day, twice a day, or on a more frequent daily basis, during a treatment period. When applied twice daily, the first and second applications are separated by at least 1 to about 12 hours. Typically, the composition may be applied in the morning and/or in the evening before going out in public.

10

30

The step of applying the composition to the skin may be done by localized application to an area that contains wrinkles. In reference to application of the composition, the term "localized", "local", or "locally" mean that the composition is delivered the targeted area (such as an area of skin containing wrinkles) while minimizing delivery to skin surface not requiring treatment. The composition may be applied and lightly massaged into the skin. It is recognized 15 that localized application does allow for a reasonable amount of the composition to be applied to areas adjacent the wrinkles to be treated (i.e., the composition is unlikely to be applied or to remain within the boundary of the wrinkles without some spreading). The form of the

composition or the dermatologically acceptable carrier should be selected to facilitate localized

While certain embodiments of the present invention contemplate applying a application. 20composition locally to a wrinkled area, it will be appreciated that compositions of the present invention can be applied more generally or broadly to one or more facial skin surfaces to reduce the appearance of wrinkles within those facial skin regions. Likewise, the compositions of the present invention can be applied as a continuous film, or in patterns. Striations, patterned spots or random application of the compositions may be desirable. Applicators, as described below, 25 may be beneficial assisting in patterned deposition.

The regimen may optionally begin with a cleansing step. The consumer can wash her face with a suitable cleanser (e.g., Olay Purifying Mud Lathering Cleanser, available from The Procter & Gamble Company, Cincinnati, OH), and gently dry her skin with a towel. Another optional step to the treatment regimens of this invention include applying a moisturizer, examples of which are given below in Table 3 and are commercially available (e.g., Olay Natural White UV Moisturizing Lotion SPF 15, available from The Procter & Gamble Company, Cincinnati, OH). The moisturizer can be applied to the skin before the skin smoothing composition, after the skin smoothing composition, or both. This moisturizer may or may not contain oils or pigment. Another optional step to the treatment regimens of this invention include

dependent on the order of regimen product application to skin and compositions.

applying a make-up primer or color cosmetic examples of these are given and commercially available (e.g. Olay Simply Ageless Serum Primer, Covergirl Clean Liquid Makeup, Covergirl Simply Powder Foundation, available from The Procter & Gamble Company, Cincinnati, OH). As indicated in the examples, the color foundation step may be in a liquid, powder or transitional form. The extent of adhesion and contractile ability of the skin smoothing composition is

5

30

Applicators

In some embodiments, the composition may be delivered by a variety of applicators appropriate for localized and general application. By way of example, a suitable applicator may

- 10 be a dropper and bottle that contains the composition. A pen-like wand with a housing that may contain the composition can also be used. The wand may comprise a handle, a stem, and an applicator head. The applicator head may comprise fibers, foam, cotton, a roller ball or any other suitable material that may releasably hold the composition. For example these may include, but are not limited to those described in published US Patent Application 2005/0025558 Al, to
- 15 Raymond J. Severa, which application is assigned to Bonne Bell, Inc. or US Patent 5,851,079, to Richard L. Horstman, which application is assigned to The Procter & Gamble Co. One preferred foam for use in any applicator described herein is the gradient foam described in published US Patent Application 2009/0180826 Al, to Gordon Guay, which application is assigned to The Procter & Gamble Co.
- 20 A simple cotton swab can apply the composition locally to the wrinkled area. Other suitable applicators include SH-0127 pen applicator available from Shya Hsin Plastic Works, Inc., Taiwan and either the Xpress Tip or liquid filled swab available from SwabPlus, Inc., China. The applicator may be configured to easily apply the composition to wrinkled areas having an approximate diameter between about 2 mm and about 20 mm and allowing for a dosed amount of the composition of between about 0.01 to about 2 mg/cm² or between about 0.1 to about 1 mg/cm².

A narrow-tip tube with a body to hold the composition and a narrow dispensing tip may also be used. This embodiment may be considered a pre-loaded dropper. The composition may be stored within the body and dispensed through the pointed tip. Fig. 1 illustrates an exploded and partially cut away applicator 10 suitable for use in the present invention. Cap 12 is removable and protects composition applicator tip 14. Tip 14 may be made of felt, sponge, porous polymeric material and the like. The remaining parts of applicator 10 can be made of any of a variety of known materials, for example, metal, plastic, polymers, and the like. Tip 14 is held in place by holder 16 which is attached to applicator body 20 about applicator neck 18. Composition cavity 24 holds the skin smoothing compositions of the present invention. Tip 14 should be in fluid communication with cavity 24 to ensure the composition flows to the tip 14. Option plunger 22 may be used to urge the skin smoothing composition toward the tip 14. Holder 16 and neck 18 should seal to insure the skin smoothing composition does not leak out. The seal between holder 16 and neck 18 can be achieved by threading, snapping, gluing, and the

like. The seal can be permanent or releasable.

While some methods described herein contemplate applying the compositions of the present invention with an applicator, it will be appreciated that applicators are not required and the compositions of the present invention can also be applied directly by using one's finger or in other conventional manners.

Examples

5

10

15

Table 1 below gives seven Examples according to the present invention, compared to six commercially available products. Web sites for the six commercially available products are listed below Table 1.

Product	Monovalent Silicate (reported as Si0 ₂) %	Polyvalent Silicate %	Ratio of Monovalent Silicate (Si02):Poly- valent Silicate	Total Glycol Level	Ratio of Total Silicate (Monovalent + Poly¬ valent):Total glycol
Example 1	1.0	0.5	2.0	8.1	0.2
Example 2	1.0	1.2	0.8	3.0	0.7
Example 3	0.7	0.4	1.8	6.3	0.2
Example 4	1.6	2.2	0.7	7.4	0.5
Example 5	3.0	3.0	1.0	3.0	2.0
Example 6	1.0	0.5	2.0	8.1	0.2
Example 7	1.0	0.5	2.0	8.1	0.2
Commercially Available Products					
Hydroxatone Instant Effect	1.4	5.2	0.3	1.3	5.1
Serious Skin Care FIRMA-FACE XR [™] Skin Tightener	3.5	10.0	0.4	0.2	67.5
Peter Thomas Roth Instant FIRMx (G10- A25744-01)	2.1	17.8	0.1	7.4	2.7
Flawless Effect Instant Facial Wrinkle Remover + Free Rejuvenating Eye Cream (G10-A25744- 02)	2.2	5.4	0.4	4.3	1.8

Table 1

24

Renoir No Lines	4.7	8.0	0.6	4.8	2.6
Wrinkle Cream Facelift					
in a Bottle					

http://www.hydroxatone.com/product.card.php3/ame=Hydroxatone_<u>Instant_Effect</u> http://beaatyJbsnxoin/serious-sldn-care-firma-face-xr-all-ove<u>r-skin-tightener_m-10045817_xp.aspx</u> http://www.peterthomasroth.com/p-193-instarit-firmx.aspx

5 <u>http://www.flawlesseffect.corn/</u> http://boydsnyc.com/nolines.aspx

> Table 2 below lists measured values for Contraction, Whiteness, Loss of Contraction and a calculated value weighting all four previous components in a single Overall Performance score. The seven examples according to the present invention are compared to the six competitive

products from Table 1. All values were measured at 70 °F and 40% relative humidity.

1 able 2							
	Contraction	Whiteness	Loss of	Overall			
	(%)		Contraction	Performance			
			(%)	Score			
Example 1	82	29	2	2.4			
Example 2	70	26	0	2.1			
Example 3	61	26	0	2.0			
Example 4	94	26	4	2.5			
Example 5	100	28	2	3.2			
Example 6	71	40	0	2.1			
Example 7	58	24	0	2.2			
Commercially Available Products							
Hydroxatone Instant Effect	75	56	19	4.1			
Serious Skin Care FIRMA-FACE XR™ Skin Tightener	81	46	22	3.6			
Peter Thomas Roth Instant FIRMx	106	59	100	5.3			
Flawless Effect Instant Facial Wrinkle Remover	63	56	23	4.0			
Renoir No Lines Wrinkle Cream Facelift in a Bottle	69	25	68	2.8			

Table 2

Table 3 below gives seven Examples according to the present invention.

10

Skin Smoothing Composition	Water	Magnesiu m Aluminum Silicate *A	Propylene Glycol	Butylene Glycol	Pentylen e Glycol	Xanthan Gum *B	Sodium Silicate Solution *C	Iron Oxide Dispersion *D
Example 1	Q.S.	0.5	8.1	_	_	2.1	3.5	<0.1
Example 2	Q.S.	1.2	3.0	_		2.4	3.5	<0.1
Example 3	Q.S.	0.4	6.3	_	Ι	1.7	2.6	<0.1
Example 4	Q.S.	2.2	7.4	_	_	2.6	5.6	<0.1
Example 5	Q.S.	3.0	3.0	_	_	0.5	10.5	<0.1
Example 6	Q.S.	0.5	_	8.1		2.1	3.5	<0.1
Example 7	Q.S.	0.5	_	_	8.1	2.1	3.5	<0.1

*A -Veegum HS, available from R.T. Vanderbilt Company, Inc, Norwalk, CN.

*B - Keltrol CGT, available from CP Kelco, Atlanta, GA.

*C - N Clear Sodium Silicate, available from PQ Corporation, Valley Forge, PA.

*D - GLW55GRAP, available from Kobo Products, Inc., South Plainfield, NJ.

5

10

For Examples 1-7, in a suitable container, combine the water and magnesium aluminum silicate. Hydrate the magnesium aluminum silicate by inputting sufficient energy in the form of heat and/or shear. When fully hydrated, cool to < 30 °C, then add propylene glycol to the container, stir until blended. Slowly add in xanthan gum and mix using a suitable mixer (e.g., propeller blade, IKA T25) until the xanthan gum is fully hydrated and batch appears homogenous. Blend in the sodium silicate, then iron oxide dispersion. Stir until homogeneous. Test Methods

15

To measure "contraction", as used herein, one measures the distance in inches (in) 5 between two ends of a foam substrate after treatment with a skin smoothing composition. The foam substrate is a 3 mm thick open-cell polyurethane commercially available from Filtrona Porous Technologies as Medisponge 50 PW (the low strain or Young's modulus of this foam is 38.248 kPa) cut to 1 x 4 cm. In a 70 °F +/- 2°C, 40% +/- 2% relative humidity environment, with the foam substrate on a Teflon coated surface, 150 μ L of the skin smoothing composition is

20 dotted evenly atop the substrate, then lightly (-30 g pressure) spread across the substrate to cover the entire surface. The treated substrate is then allowed to dry 24 hours in this constant temperature/humidity environment. Then the projected distance between the ends of the foam

10

substrate is measured with a ruler in inches. This procedure is performed in replicates of 3 or more and the values averaged.

The identical procedure detailed in the previous paragraph is also performed simultaneously with the Example 5 formulation. This data is used to normalize foam lot variability differences.

Then the following math is performed: "Contraction" = $[1.6 - (D_{samp} i_e - D_{sxampie 5}) / 1-6]$ *100, where $D_{samp} i_e$ is the projected distance in inches of the sample of interest, and $D_{sxampie 5}$ is the projected distance in inches of Example 5. In this calculation the the value 1.6 is used because it is the distance in inches of a foam strip devoid of contraction. Values greater than 100% indicate the sample has greater contraction than our reference point, Example 5; values less than 100% indicate the sample has less contraction than Example 5.

To measure the "loss of contraction," as used herein, one measures the distance in inches (in) between two ends of a foam substrate following treatment with a skin smoothing composition then repeated physical manipulation thereof. The treated foam substrates of the 15 "contraction" method (described above) are repeatedly pressed into a flat orientation to determine the "loss of contraction". Subsequent to measuring "contraction", in a 70 °F +/- 2°C, 40% +/- 2% relative humidity environment, the treated foam substrates are placed singly, flat, between two glass microscope slides, then a 305 g weight applied atop the upper glass slide for 10 seconds. The weight is removed for 10 seconds, then applied and removed in the same 10 20 second increments 2 additional cycles. The foam substrate is removed from the glass slides, set on a Teflon-coated surface, then after 10 minutes, the projected distance in inches (in) between two ends of a foam substrate measured using a ruler. This projected distance is then normalized similarly to the 'contraction' values, using the following equation "Repeat Insult Contraction" = [1.6 - (RID_{samp} ie - Dsxampie 5) / 1-6] *100, where RID_{samp} ie is the projected distance in inches of

25 the sample of interest following the repeat insult procedure, and DExample 5 is the projected distance in inches of Example 5 absent of the repeat insult protocol. Then one final calculation is performed: "Loss of Contraction" = "Contraction" - "Repeat Insult Contraction".

To measure "Whiteness", as used herein, one measures the opacity or lightness/darkness intensity. For the purposes of the present invention, color is defined according to a value on the 30 CIELAB color system, which is based on the XYZ color system, defined by the Commission Internationale de l'Eclairage (CIE system) to provide a manner of objectively representing perceived color and color differences. X, Y and Z can be expressed in a variety of manners, or "scales," one of which is the Hunter scale. The Hunter scale has three variables, L, a, and b, which correlate mathematically to X, Y and Z, as described by Robertson, A.R. in "The CIE

10

27

1976 Color Difference Formulas," *Color Research Applications*, vol. 2, pp. 7-11 (1977). The compositions of the present invention may be analyzed with a Microflash integrating sphere spectrophotometer from DataColor International, Lawrenceville, NJ, USA, which generates values for L, a, and b. The value for "a" correlates to a value along the red-green (horizontal) axis, and the value for "b" correlates to a value along the blue-yellow (vertical) axis. For example, a blue-colored sample will have a negative b-value, whereas a red-colored sample will have a positive a-value. A more positive or negative value represents a more intense color. The value for "L" is an indicator of lightness and/or darkness, and correlates to a value along the z-axis, which is perpendicular to both the horizontal and vertical axes. An "L" of 0 is black and 100 a diffuse white. It is "L" that is used as a determinant of the film's "whiteness."

To measure the whiteness of a film it must first be drawn. Herein, "drawn" means that the composition is applied onto at least a portion of the black portion of an opacity chart (Form 2A, Leneta Company of Manwah, NJ or the equivalent thereof, of which the top half is black and the bottom half is white) and spread into a film having a thickness of approximately 0.003 inches using a film applicator (e.g., as commercially available from BYK Gardner of Columbia, Maryland, or the equivalent thereof). The whiteness is then measured on the black portion of the opacity chart after the drawn film is allowed to dry for 24 hours under conditions of 70 °F +/-2°C, 40% +/- 2% relative humidity using a spectrophotometer (e.g., Microflash integrating sphere spectrophotometer, specular-reflections included). Again, whiteness is used in reference

20 to the "L" value of the drawn films. A higher number indicates the product looks white against the black background, while a lower number indicates the product is less white and/or more translucent, allowing greater visibility of the black background. Whiteness determinations are performed in replicates of 2.

The term "Overall Performance Score" is calculated using the contraction, whiteness, and 25 loss of contraction data. The Overall Performance Score is calculated using the following equation, Overall Performance Score = (Contraction / 100) + (Whiteness / 18) + (% Loss of Contraction / 100)). For example, for Example 1 this is (82 / 100) + (29 / 18) + (2 / 100) = 2.4. In this equation the whiteness value is divided by 18 as this is the approximate value of a completely invisible film.

30

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

28

Every document cited herein, including any cross referenced or related patent or application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and 10 described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore intended to cover in the appended claims all such changes and modifications that are within the scope of this invention.

CLAIMS

What is claimed is:

- 1. A skin smoothing composition comprising:
 - a) From about 0.5 to about 4% sodium silicate as measured by silica content (SiO_2) ;
 - b) from about 0.1% to about 4.0% of a polyvalent silicate;
 - c) from about 10 to 98% water; and
- wherein the ratio of the weight of the sodium silicate to the polyvalent silicate is equal to or greater than 0.7 and the composition is in the form of a water gel or oil-in-water emulsion.
- 2. A skin smoothing composition comprising:
 - a) From about 0.5 to about 4% sodium silicate as measured by silica content (Si0 $_2$);
 - b) from about 0.1% to about 4.0% of a polyvalent silicate;
 - c) from about 1 to about 20%, by weight of a plasticizer;
 - d) from about 10 to 98% water; and

wherein the ratio of the weight of the sodium silicate plus polyvalent silicate to plasticizer is less than 1.8 and the composition is in the form of a water gel or oil-in-water emulsion.

- 3. The composition of claim 1, wherein the sodium silicate, as measured by silica content (Si02) to polyvalent silicate ratio is equal to or greater than 0.9.
- 4. The composition of claim 1, wherein the polyvalent silicate is a silicate clay selected from the group consisting of bentonite, laponite, smectite, kaolinite and mixtures thereof.
- 5. The composition of claim 4, wherein the polyvalent silicate is stable in compositions having a pH greater than 10.
- 6. The composition of claim 1, further comprising at least one plasticizer.
- 7. The composition of claim 6, wherein the plasticizer is present from about 1 to 20% by weight.

15

10

5

- 8. The composition of claim 6, wherein the plasticizer is an alkyl mono-glycol or di-glycol.
- 9. The composition of claim 6, wherein the plasticizer structure contains 3 to 5 carbon atoms.

10. The composition of claim 6, wherein the plasticizer is propylene glycol.

- 11. The composition of claim 1, further comprising at least one polysaccharide thickener.
- 12. The composition of claim 11, wherein the polysaccharide thickener is xanthan gum.
- 13. The composition of claim 1, further comprising from about 0.001% to about 5% of a particulate material selected from the group consisting of colored and uncolored pigments, interference pigments, inorganic powders, organic powders, composite powders, optical brightener particles, and mixtures thereof.
- 14. The composition of claim 1, further comprising at least one skin care active.
- 15. The composition of claim 14, wherein the skin care active is selected from the group consisting of vitamin B compounds, vitamin C compounds, vitamin E compounds, peptides, sugar amines, natural botanical extract, oil control agents, skin lightening agents, and mixtures thereof.
- 16. The composition of claim 14, wherein the skin care active is selected from the group consisting of niacinamide, palmitoyl-lysine-threonine, palmitoyl-lysine-threonine-threonine-lysine-serine, N-acetyl-D-glucosamine, salicylic acid, dehydroacetic acid, sodium dehydroacetate, hexamidine compounds, and mixtures thereof.
- 17. The composition of claim 2, wherein the polyvalent silicate is a silicate clay selected from the group consisting of bentonite, laponite, smectite, kaolinite and mixtures thereof.
- 18. The composition of claim 17, wherein the polyvalent silicate is stable in compositions having a pH greater than 10.
- 19. The composition of claim 2, wherein the plasticizer is an alkyl mono-glycol or di-glycol.

- 31
- 20. The composition of claim 2, wherein the plasticizer structure contains 3 to 5 carbon atoms.
- 21. The composition of claim 2, wherein the plasticizer is propylene glycol.
- 22. The composition of claim 2, further comprising at least one polysaccharide thickener.
- 23. The composition of claim 22, wherein the polysaccharide thickener is xanthan gum.
- 24. The composition of claim 2, further comprising from about 0.001% to about 5% of a particulate material selected from the group consisting of colored and uncolored pigments, interference pigments, inorganic powders, organic powders, composite powders, optical brightener particles, and mixtures thereof.
- 25. The composition of claim 2, further comprising at least one skin care active.
- 26. The composition of claim 25, wherein the skin care active is selected from the group consisting of vitamin B compounds, vitamin C compounds, vitamin E compounds, peptides, sugar amines, natural botanical extract, oil control agents, skin lightening agents, and mixtures thereof.
- 27. The composition of claim 26, wherein the skin care active is selected from the group consisting of niacinamide, palmitoyl-lysine-threonine, palmitoyl-lysine-threonine-threonine-lysine-serine, N-acetyl-D-glucosamine, salicylic acid, dehydroacetic acid, sodium dehydroacetate, hexamidine compounds, and mixtures thereof.
- 28. A kit comprising a first composition and a second composition, wherein:
 - i) the first composition is a skin smoothing composition in the form of a water gel or oil-in-water emulsion and the skin smoothing composition comprises:
 - a) From about 0.5 to about 4% sodium silicate as measured by silica content (Si0 $_2$);
 - b) from about 0.1% to about 4.0% of a polyvalent silicate;
 - c) from about 10 to 98% water; and

ii) the second composition comprises at least one component selected from the group consisting of an oil-in-water emulsion, water-in-oil emulsion, thickened water gel,

thickened oil phase, encapsulated oil phase, solid oil phase, and mixtures thereof, wherein the second composition is a skin care composition or colored cosmetic composition; and

iii) instructions for complying with a regimen to provide a benefit to keratinous tissue.

29. A kit comprising:

a personal care composition comprising: a skin smoothing composition comprising:

- a) From about 0.5 to about 4% sodium silicate as measured by silica content (SiO $_2$);
- b) from about 0.1% to about 4.0% of a polyvalent silicate;
- c) from about 10 to 98% water;

wherein the composition is in the form of a water gel or oil-in-water emulsion; and

- d) at least one additional component selected from the group consisting applicators, delivery implements, or powered delivery devices to deliver the personal care composition to skin;
- e) instructions for complying with the combination of the personal care composition with one of the components to provide a benefit to keratinous tissue.

30. A kit comprising:

a personal care composition comprising: a skin smoothing composition comprising:

- a) From about 0.5 to about 4% sodium silicate as measured by silica content (SiO $_2$);
- b) from about 0.1% to about 4.0% of a polyvalent silicate;
- c) from about 10 to 98% water;

wherein the composition is in the form of a water gel or oil-in-water emulsion; and suspends or is suspended in at least one additional component selected from the group consisting of an one oil-in-water emulsion, water-in oil emulsion, thickened water gel, and mixtures thereof, wherein these compositions are in the form of skin care compositions or colored cosmetic compositions.

31. The composition of claim 1, further comprising

a) from about 0.1% to about 3% of a polysaccharide thickener;

wherein the composition is in the form of a water gel or oil-in-water emulsion; and the composition forms a film on skin that exhibits a

b) contraction from about 25 to about 150%;

- c) whiteness equal to or lower than 40;
- d) a loss of contraction equal to or lower than 20%;
- e) and an overall performance score lower than 2.8.
- 32. The composition of claim 31, wherein the film exhibits polar component surface energy equal to or lower than $35 \gamma p/mJ/m^2$, when measured at 70 °F and 40% relative humidity.
- 33. A personal care composition comprising:
 - a) from about 0.5 to about 2% sodium silicate as measured by silica content (Si0 $_2$);
 - b) from about 0.1% to about 3.0% of a polyvalent silicate;
 - c) from about 6% to about 8% of a plasticizer;
 - d) from about 0.1% to about 3% of a polysaccharide thickener;
 - e) from about 10 to 98% water;

wherein the composition is in the form of a water gel or oil-in-water emulsion; and the composition forms a film on skin that exhibits a

- f) contraction from about about 50 to about 125%;
- g) whiteness equal to or lower than 40;
- h) a loss of contraction equal to or lower than 15%;
- i) and an overall performance score lower than 2.7.

1/1

