

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028121 A1**

(51) International Patent Classification<sup>7</sup>: **B05B 11/00**, 7/00

**Franciskus** [NL/NL]; Krabbehoek 13, NL-5348 MS Heesch (NL).

(21) International Application Number:

PCT/NL2004/000660

(74) **Agent: TABELING, Marcella, Maria, Josefa**; Arnold & Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).

(22) International Filing Date:

23 September 2004 (23.09.2004)

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

1024350

23 September 2003 (23.09.2003) NL

(71) **Applicant** (*for all designated States except US*): **R+D INJECTOR AG** [CH/CH]; Zugerstrasse 76b, CH-6340 Baar (CH).


(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) **Inventor**; and

(75) **Inventor/Applicant** (*for US only*): **BROUWER, Markus**,

[Continued on next page]

(54) **Title**: DISPENSER FOR CONCENTRATED INJECTION



(57) **Abstract**: A dispenser, particularly suitable for a liquid container, comprising a liquid pump provided with an inlet having an inlet valve and an outlet having an outlet valve, an air pump provided with an inlet having an inlet valve and an outlet having an outlet valve, a mixing chamber which is in communication with the outlet of each pump, and a dispensing part provided with an outflow channel with an outflow opening, wherein the outflow channel is in communication with the mixing chamber, and wherein the outlet valve of the air pump is arranged adjacent to the outlet of the liquid pump.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## DISPENSER FOR CONCENTRATED INJECTION

The invention relates to a dispenser, particularly suitable for a liquid container, comprising a liquid pump provided with an inlet having an inlet valve and an outlet having an outlet valve, an air pump  
5 provided with an inlet having an inlet valve and an outlet having an outlet valve, a mixing chamber which is in communication with the outlet of each pump, and a dispensing part provided with an outflow channel with an outflow opening, wherein the outflow channel is in  
10 communication with the mixing chamber.

Such a dispenser can be used to dispense a spray or a foam. Such a dispenser preferably produces a spray or foam of the highest possible quality, which entails the air bubbles in the spray or the foam being  
15 distributed as finely and uniformly as possible.

A dispenser of the present type is known from EP 0 618 147. The outlet valve of the air pump is adjacent to the outlet of the liquid pump.

The object of the present invention is to  
20 improve known dispensers.

The present invention provides for this purpose a dispenser which is characterized in that the outlet valve for air, which is adjacent to an outlet for the liquid pump, is formed by a flexible wall. Although  
25 a minimal leakage need not affect the functioning of the dispenser, the flexible wall seals. In the case of some liquids a sudden opening of the air valve to generate an "explosion" of air is found to be necessary to obtain a good foam or spray. Such an outlet valve for air can be  
30 manufactured in relatively simple and inexpensive manner.

The air in the air pump is compressed, and the pressure therefore increases. When a determined pressure

difference is reached over the air valve, it will open. The resistance which must be overcome is here the valve resistance and the underlying liquid pressure of liquid flowing past the valve. The air can hereby be injected  
5 under great pressure directly into the liquid. Experiments have shown that a spray or foam of improved quality can hereby be obtained. The flexible wall is movable in the liquid flow.

The outlet valve of the air pump is preferably  
10 positioned relative to the outlet of the liquid pump such that when the valve is opened the air is introduced almost transversely of the liquid flow. Experiments have once again shown that this enhances the quality of the spray or the foam.

15 In a further embodiment according to the invention the outlet of the liquid pump comprises a liquid chamber which, as seen in flow direction, is situated after the outlet valve of the liquid pump and which is provided with a central opening which debouches  
20 in the mixing chamber. During compression of the air in the air pump the liquid chamber is filled with liquid from the liquid container. Via the central opening in the liquid chamber the liquid flows into the mixing chamber where, after sufficient build-up of pressure,  
25 air is introduced into the liquid.

The mixing chamber preferably comprises a central outlet opening which debouches in the outflow channel of the dispensing part. The air-liquid mixture is thus forced to leave the mixing chamber through a  
30 relatively small opening. This also enhances the quality of the foam or the spray.

In a preferred embodiment a flexible wall is arranged between the liquid chamber and the mixing chamber. In the static situation the valve seals around  
35 the central outlet opening of the mixing chamber.

The central opening of the liquid chamber is preferably in open communication with the outflow channel of the dispensing part. Liquid leaves the liquid chamber through the central opening in the direction of  
5 the outflow channel.

The dispenser according to the invention is particularly intended as foam dispenser, wherein a foam-forming element is arranged in the outflow channel.

The foam-forming element is preferably  
10 arranged in the outflow channel such that the foam flowing through the outflow channel passes through the foam-forming element at least twice. A finer and more uniform foam is hereby found to result which is unsurpassed by any known foam-forming unit. The  
15 production process is furthermore simpler since only one foam-forming element is arranged for two passages, which has the effect of saving costs.

For a further improvement in the foam quality, a further foam-forming element can be arranged, as seen  
20 in the flow direction, before or after the foam-forming element that is passed through twice. In a particularly advantageous embodiment according to the invention, the final foam-forming element, as seen in the flow direction, is preferably arranged in the outflow  
25 opening. The foam-forming element forms resistance at the outer end of the dispensing part, so that the foam does not spurt out of the outflow channel, and thereby remains more stable.

Finally, the invention relates to a dispenser  
30 assembly consisting of a liquid container and a dispenser according to the invention.

The invention will be further elucidated hereinbelow with reference to the accompanying drawings. In the drawings:

Figure 1 shows a perspective, partly cut-away dispenser assembly according to the invention;

Figure 2 shows a perspective view in cross-section of a detail of a foam dispenser according to a  
5 first embodiment;

Figure 3 shows a perspective view in cross-section of a detail of a foam dispenser according to a second embodiment;

Figures 4A and 4B are partly cross-sectional  
10 views of the dispenser shown in figures 2 and 3 with respectively closed and open outlet valve for air.

A dispenser assembly 1 according to the present invention comprises a cylindrical liquid  
container 2 which has therein a liquid 3 for atomizing  
15 or foaming and on which is arranged a dispenser 4 (figure 1). Dispenser 4 comprises a pump 6 for air and a pump 8 for liquid, which are each provided with an inlet and an outlet. Air pump 6 is in communication with the environment via opening 9 (figure 2), while liquid pump  
20 8 is in communication with the content 3 of liquid container 2 via hose 10. Dispenser 4 further comprises a mixing chamber 14 which is in communication with both the air pump 6 and the liquid pump 8. The outlet of mixing chamber 14 is formed by a central outlet opening  
25 15 in wall 20. The outlet of liquid pump 8 comprises an outlet valve 16 and a liquid chamber 12 which is located thereabove and provided with a central opening 13 debouching in mixing chamber 14. An outlet valve 18 for air is located in the outlet of air pump 6 (figure 2).

30 The top part of the assembly comprises a dispensing part 22, comprising an outflow channel 24 with an outflow opening 26. Outflow channel 24 runs from mixing chamber 14 to outflow opening 26. In this channel 24 are arranged one (figure 2) or two (figure 3) foam-  
35 forming elements, in the shown preferred embodiment in

the form of relatively fine-mesh screens 28,30.  
Reference is made in respect of these screens, and in particular in respect of specific dimensioning thereof, to patent application NL 1022633, the content of which is incorporated herein.

The opening 9 for admitting air into air pump 6 is provided in dispensing part 22. The inlet of air pump 6 further comprises an air chamber 32. The air inlet is bounded by inlet valve 34. A compression chamber 36 for air is arranged between inlet valve 34 and outlet valve 18 for air.

The outlet valve 18 for air is formed by a flexible wall which forms a wall for both liquid chamber 12 and mixing chamber 14. In the static situation the flexible wall 18 seals round the central outlet opening 15 of mixing chamber 14. The flexible wall is provided with central opening 13 which forms the outlet of liquid chamber 12. This central opening 13 is in open communication with outflow channel 24 of dispensing part 22 via mixing chamber 14 and the central outlet opening 15 of mixing chamber 14.

On the underside of flexible wall 18 there are provided stop means 38 with which the outlet valve 16 for liquid comes into contact in the maximum opened position. Stop means 38 serve to prevent the outlet valve 16 for liquid influencing the operation of outlet valve 18 for air. These stops also ensure that the outlet valve 16 for liquid does not close off the liquid flow. During the downward stroke of dispenser 4 the outlet valve 16 is lifted by the liquid flow. These ribs 38 are arranged to prevent the valve 16 sealing the outflow opening 13.

The manner in which dispenser 4 and assembly 1 are further constructed is described and shown in

international patent application WO 02/42005 of applicant. The content hereof is likewise incorporated.

The operation of assembly 1 will be elucidated with reference to figures 4A and 4B. In figure 4A the outlet valve 18 for air is shown in the static situation. In the static situation the valve 18 seals round outlet opening 15 of mixing chamber 14. Air is situated in compression space 36 and owing to the sealing cannot displace to mixing chamber 14. Liquid is situated in liquid chamber 12. Via central opening 13 of liquid chamber 12 and the central outlet opening 15 of mixing chamber 14 the liquid chamber 12 is in open communication with outflow channel 24. The pressure in the liquid chamber is therefore equal to atmospheric pressure. In this situation the user presses on dispensing part 22. Dispensing part 22 is hereby moved downward relative to container 12 while co-displacing the pistons (not shown) of air pump 6 and liquid pump 8. During a downward stroke of dispensing part 22 the air in compression space 36 is compressed. The pressure will hereby increase. When the pressure in compression space 36 has reached a predetermined value, the resistance of air valve 18 can be overcome, and flexible wall 18 can bend downward, whereby an open connection is created between compression space 36 and mixing chamber 14. At that moment the air under pressure will be injected with great force into the liquid flow which comes from liquid chamber 12 through central opening 13, mixing chamber 14 and the central outlet opening 15 of mixing chamber 14. Because the outlet valve 18 of the air pump is positioned relative to the outlet of liquid pump 8, the air is introduced practically transversely of the liquid flow when valve 18 is opened. The position with opened air valve 18 is shown in figure 4B. Because air escapes from compression space 36, the pressure will fall until

eventually the resistance of valve 18 is no longer overcome. Valve 18 will then close (figure 4A). Reference is made to WO 02/42005 for the further operation of dispenser assembly 1.

- 5           The central outlet opening 15 of mixing chamber 14 preferably has a diameter of between about 0.5 and 4 mm, more preferably a diameter of between about 1 and 2 mm. The highly concentrated injection of air into the liquid channel creates an intensive mixing.
- 10   It has been shown experimentally that this produces a higher quality of foam. It is possible, owing to pressure differences over air valve 18 during injection, that there occurs high-frequency opening and closing of valve 18.
- 15           Instead of opening 9 in the side wall of dispenser 4, it is also possible to connect air pump 6 to the environment via a gap (not shown) arranged between cap 40 and side wall 42. Situated under cap 40 is a tube which serves as chimney and allows the air
- 20   from the gap through to air chamber 32. This construction is shown in figure 3 of NL 1022633.

Although the invention in the drawings is elucidated for the purpose of making foam, the invention is not limited to foam. The concentrated injection of

25   air by means of an outlet valve located adjacently of the outlet for liquid can also be applied for the purpose of making a spray.

## CLAIMS

1. Dispenser, particularly suitable for a liquid container, comprising:

- 5     - a liquid pump provided with an inlet having an inlet valve and an outlet having an outlet valve,  
      - an air pump provided with an inlet having an inlet valve and an outlet having an outlet valve,  
      - a mixing chamber which is in communication with the  
10     outlet of each pump, and  
      - a dispensing part provided with an outflow channel with an outflow opening, wherein the outflow channel is in communication with the mixing chamber, **characterized in that** the outlet valve of  
15     the air pump, which is adjacent to the outlet of the liquid pump, is formed by a flexible wall.

2. Dispenser as claimed in claim 1, wherein the outlet valve of the air pump is positioned relative  
20 to the outlet of the liquid pump such that when the valve is opened the air is introduced almost transversely of the liquid flow.

3. Dispenser as claimed in claim 1 or 2,  
25 wherein the outlet of the liquid pump comprises a liquid chamber which, as seen in flow direction, is situated after the outlet valve of the liquid pump and is provided with a central opening which debouches in the mixing chamber.

30

4. Dispenser as claimed in any of the foregoing claims, wherein the mixing chamber comprises a central outlet opening which debouches in the outflow channel of the dispensing part.

35

5. Dispenser as claimed in any of the foregoing claims, wherein the flexible wall is arranged , between the liquid chamber and the mixing chamber.

5           6. Dispenser as claimed in claim 5, wherein in the static situation the flexible wall seals around the central outlet opening of the mixing chamber.

7. Dispenser as claimed in any of the claims  
10 3-6, wherein the central opening of the liquid chamber is in open communication with the outflow channel of the dispensing part.

8. Foam dispenser as claimed in any of the  
15 foregoing claims, further comprising a foam-forming element arranged in the outflow channel.

9. Foam dispenser as claimed in claim 8,  
wherein the foam-forming element is arranged in the  
20 outflow channel such that the foam flowing through the outflow channel passes through the foam-forming element at least twice.

10. Foam dispenser as claimed in claim 8 or 9,  
25 wherein a further foam-forming element is arranged, as seen in the flow direction, before the foam-forming element in the outflow channel.

11. Foam dispenser as claimed in any of the  
30 claims 8-10, wherein a further foam-forming element is arranged, as seen in the flow direction, after the foam-forming element or the foam-forming elements in the outflow channel.

10

12. Foam dispenser as claimed in claim 11, wherein the final foam-forming element as seen in the flow direction is arranged in the outflow opening.

5           13. Dispenser assembly consisting of a liquid container and a dispenser, wherein the dispenser is formed by a dispenser as claimed in any of the claims 1-12.

10




FIG. 1




FIG. 2






FIG. 3

4/5

FIG. 4A

5/5

FIG. 4B

# INTERNATIONAL SEARCH REPORT

/NL2004/000660

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC 7 B05B11/00 B05B7/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) IPC 7 B05B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 057 176 A (HORVATH WILLIAM) 8 November 1977 (1977-11-08) the whole document	1, 2, 13
A	EP 0 618 147 A (BESPAK PLC) 5 October 1994 (1994-10-05) cited in the application column 11, line 2 - line 11 column 15, line 17 - line 28	1-4, 7, 13
A	EP 1 199 105 A (GUALA DISPENSING S P A) 24 April 2002 (2002-04-24) the whole document	8, 9, 13
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filing date but later than the priority date claimed *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&* document member of the same patent family		
Date of the actual completion of the international search 17 January 2005		Date of mailing of the international search report 26/01/2005
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016		Authorized officer van der Bijl, S

# INTERNATIONAL SEARCH REPORT

Information on patent family members

NL2004/000660

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4057176	A	08-11-1977	AU 1577776 A	12-01-1978
			BE 844197 A1	17-01-1977
			CA 1043304 A1	28-11-1978
			DE 2632675 A1	03-02-1977
			DE 7622920 U1	08-06-1977
			ES 449932 A1	01-07-1977
			FR 2317969 A1	11-02-1977
			GB 1509827 A	04-05-1978
			IT 1066044 B	04-03-1985
			JP 52038620 A	25-03-1977
			NL 7607953 A	20-01-1977
			SE 7608055 A	19-01-1977
EP 0618147	A	05-10-1994	US 5348189 A	20-09-1994
			AT 152686 T	15-05-1997
			CN 1103012 A ,B	31-05-1995
			DE 69310496 D1	12-06-1997
			DE 69310496 T2	16-10-1997
			EP 0618147 A2	05-10-1994
			ES 2101236 T3	01-07-1997
			JP 6254445 A	13-09-1994
EP 1199105	A	24-04-2002	EP 1199105 A1	24-04-2002
			DE 60100013 D1	19-09-2002
			DE 60100013 T2	03-04-2003
			ES 2182815 T3	16-03-2003
			US 2003015552 A1	23-01-2003