



US 20070203045A1

(19) **United States**

(12) **Patent Application Publication**  
**Schweitzer et al.**

(10) **Pub. No.: US 2007/0203045 A1**

(43) **Pub. Date: Aug. 30, 2007**

(54) **AZEOTROPIC COMPOSITIONS  
COMPRISING FLUORINATED COMPOUNDS  
FOR CLEANING APPLICATIONS**

(76) Inventors: **Melodie A. Schweitzer**, Wilmington,  
DE (US); **Allen Capron Sievert**,  
Elkton, MD (US); **Joan Ellen Bartelt**,  
Wilmington, DE (US); **Barbara  
Haviland Minor**, Elkton, MD (US)

Correspondence Address:

**E I DU PONT DE NEMOURS AND  
COMPANY  
LEGAL PATENT RECORDS CENTER  
BARLEY MILL PLAZA 25/1128  
4417 LANCASTER PIKE  
WILMINGTON, DE 19805 (US)**

(21) Appl. No.: **11/712,165**

(22) Filed: **Feb. 28, 2007**

**Related U.S. Application Data**

(60) Provisional application No. 60/777,350, filed on Feb.  
28, 2006.

**Publication Classification**

(51) **Int. Cl.**  
**C09K 5/04** (2006.01)

(52) **U.S. Cl.** ..... **510/411; 252/67**

(57) **ABSTRACT**

The present invention relates to compositions comprising fluorinated olefins or fluorinated ketones, and at least one alcohol, halocarbon, hydrofluorocarbon, or fluoroether. In one embodiment, these compositions are azeotropic or azeotrope-like. In another embodiment, these compositions are useful in cleaning applications as a degreasing agent or defluxing agent for removing oils and/or other residues from a surface.

**AZEOTROPIC COMPOSITIONS COMPRISING  
FLUORINATED COMPOUNDS FOR CLEANING  
APPLICATIONS**

CROSS REFERENCE(S) TO RELATED  
APPLICATION(S)

[0001] This application claims the benefit of priority of U.S. Provisional Application 60/777,350, filed Feb. 28, 2006.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to compositions comprising fluorinated olefins, or fluorinated ketones, and at least one alcohol, halocarbon, fluoroalkyl ether, or hydrofluorocarbon and combinations thereof. These compositions are azeotropic or azeotrope-like and are useful in cleaning applications as a defluxing agent and for removing oils or residues from a surface.

[0004] 2. Description of Related Art

[0005] Flux residues are always present on microelectronics components assembled using rosin flux. As modern electronic circuit boards evolve toward increased circuit and component densities, thorough board cleaning after soldering becomes a critical processing step. After soldering, the flux-residues are often removed with an organic solvent. De-fluxing solvents should be non-flammable, have low toxicity and have high solvency power, so that the flux and flux-residues can be removed without damaging the substrate being cleaned. Further, other types of residue, such as oils and greases, must be effectively removed from these devices for optimal performance in use.

[0006] Alternative, non-ozone depleting solvents have become available since the elimination of nearly all previous CFCs and HCFCs as a result of the Montreal Protocol. While boiling point, flammability and solvent power characteristics can often be adjusted by preparing solvent mixtures, these mixtures are often unsatisfactory because they fractionate to an undesirable degree during use. Such solvent mixtures also fractionate during solvent distillation, which makes it virtually impossible to recover a solvent mixture of the original composition.

[0007] Azeotropic solvent mixtures may possess the properties needed for these de-fluxing, de-greasing applications and other cleaning agent needs. Azeotropic mixtures exhibit either a maximum or a minimum boiling point and do not fractionate on boiling. The inherent invariance of composition under boiling conditions insures that the ratios of the individual components of the mixture will not change during use and that solvency properties will remain constant as well.

[0008] The present invention provides azeotropic and azeotrope-like compositions useful in semiconductor chip and circuit board cleaning, defluxing, and degreasing processes. The present compositions are non-flammable, and as they do not fractionate, will not produce flammable compositions during use. Additionally, the used azeotropic solvent mixtures may be re-distilled and re-used without composition change.

BRIEF SUMMARY OF THE INVENTION

[0009] The present invention relates to compositions comprising fluorinated ketones and at least two compounds selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons. In one embodiment, the at least two compounds are selected from the group consisting of:

[0010] n-propylbromide;

[0011] trichloroethylene;

[0012] tetrachloroethylene;

[0013] trans-1,2-dichloroethylene;

[0014] methanol;

[0015] ethanol;

[0016] n-propanol;

[0017] isopropanol;

[0018]  $C_4F_9OCH_3$ ;

[0019]  $C_4F_9OC_2H_5$ ;

[0020] HFC-43-10mcc;

[0021] HFC-365mfc

[0022] and combinations thereof.

[0023] In one embodiment, the compositions are azeotropic or azeotrope-like. Additionally, the present invention relates to processes for cleaning surfaces and for removing residue from surfaces, such as integrated circuit devices.

DETAILED DESCRIPTION OF THE  
INVENTION

[0024] Applicants specifically incorporate by reference the entire contents of all cited references in this disclosure. Further, when an amount, concentration, or other value or parameter is given as either a range, preferred range, or a list of upper preferable values and lower preferable values, this is to be understood as specifically disclosing all ranges formed from any pair of any upper range limit or preferred value and any lower range limit or preferred value, regardless of whether ranges are separately disclosed. Where a range of numerical values is recited herein, unless otherwise stated, the range is intended to include the endpoints thereof, and all integers and fractions within the range. It is not intended that the scope of the invention be limited to the specific values recited when defining a range.

[0025] In one embodiment, the present invention relates to compositions comprising compounds having the formula E- or Z- $R^1CH=CHR^2$  (Formula I), wherein  $R^1$  and  $R^2$  are, independently, C1 to C5 perfluoroalkyl groups, and at least one alcohol, halocarbon, fluoroalkyl ethers, or hydrofluorocarbon. Examples of  $R^1$  and  $R^2$  groups include, but are not limited to,  $CF_3$ ,  $C_2F_5$ , n- $C_3F_7$ , i- $C_3F_7$ , n- $C_4F_9$ , n- $C_5F_{11}$ , and i- $C_4F_9$ . Exemplary, non-limiting Formula I compounds are presented in Table 1.

TABLE 1

Code	Structure	IUPAC Name
F11E	$\text{CF}_3\text{CH}=\text{CHCF}_3$	1,1,1,4,4,4-hexafluoro-2-butene
F12E	$\text{CF}_3\text{CH}=\text{CHC}_2\text{F}_5$	1,1,1,4,4,5,5,5-octafluoro-2-pentene
F13E	$\text{CF}_3\text{CH}=\text{CH}(\text{n-C}_3\text{F}_7)$	1,1,1,4,4,4,5,5,6,6,6-decafluoro-2-hexene
F13iE	$\text{CF}_3\text{CH}=\text{CH}(\text{i-C}_3\text{F}_7)$	1,1,1,4,4,5,5,5-heptafluoro-4-(trifluoromethyl)-2-pentene
F22E	$\text{C}_2\text{F}_5\text{CH}=\text{CHC}_2\text{F}_5$	1,1,1,2,2,5,5,6,6,6-decafluoro-3-hexene
F14E	$\text{CF}_3\text{CH}=\text{CH}(\text{n-C}_4\text{F}_9)$	1,1,1,4,4,5,5,6,6,7,7,7-dodecafluorohept-2-ene
F23E	$\text{C}_2\text{F}_5\text{CH}=\text{CH}(\text{n-C}_3\text{F}_7)$	1,1,1,2,2,5,5,6,6,7,7,7-dodecafluorohept-3-ene
F23iE	$\text{C}_2\text{F}_5\text{CH}=\text{CH}(\text{i-C}_3\text{F}_7)$	1,1,1,2,2,5,5,6,6,6-nonafluoro-5-(trifluoromethyl)hex-3-ene
F15E	$\text{CF}_3\text{CH}=\text{CH}(\text{n-C}_5\text{F}_{11})$	1,1,1,4,4,5,5,6,6,7,7,8,8,8-tetradecafluorooct-2-ene
F24E	$\text{C}_2\text{F}_5\text{CH}=\text{CH}(\text{n-C}_4\text{F}_9)$	1,1,1,2,2,5,5,6,6,7,7,8,8,8-tetradecafluorooct-3-ene
F33E	$\text{n-C}_3\text{F}_7\text{CH}=\text{CH}(\text{n-C}_3\text{F}_7)$	1,1,1,2,2,3,3,6,6,7,7,8,8,8-tetradecafluorooct-4-ene
F3i3iE	$\text{i-C}_3\text{F}_7\text{CH}=\text{CH}(\text{i-C}_3\text{F}_7)$	1,1,1,2,5,5,6,6,6-octafluoro-2,5-bis(trimethylfluoro)hex-3-ene
F33iE	$\text{n-C}_3\text{F}_7\text{CH}=\text{CH}(\text{i-C}_3\text{F}_7)$	1,1,1,2,5,5,6,6,7,7,7-undecafluoro-2(trifluoromethyl)hept-3-ene
F34E	$\text{n-C}_3\text{F}_7\text{CH}=\text{CH}(\text{n-C}_4\text{F}_9)$	1,1,1,2,2,3,3,6,6,7,7,8,8,9,9,9-hexadecafluoronon-4-ene
F3i4E	$\text{i-C}_3\text{F}_7\text{CH}=\text{CH}(\text{n-C}_4\text{F}_9)$	1,1,1,2,5,5,6,6,7,7,8,8,8-triskaidecafluoro-2(trifluoromethyl)oct-3-ene
F44E	$\text{n-C}_4\text{F}_9\text{CH}=\text{CH}(\text{n-C}_4\text{F}_9)$	1,1,1,2,2,3,3,4,4,7,7,8,8,9,9,10,10,10-octadecafluorodec-5-ene

[0026] Compounds of Formula I may be prepared by contacting a perfluoroalkyl iodide of the formula  $\text{R}^1\text{I}$  with a perfluoroalkyltrihydroolefin of the formula  $\text{R}^2\text{CH}=\text{CH}_2$  to form a trihydroiodoperfluoroalkane of the formula  $\text{R}^1\text{CH}_2\text{CHR}^2$ . This trihydroiodoperfluoroalkane can then be dehydroiodinated to form  $\text{R}^1\text{CH}=\text{CHR}^2$ . Alternatively, the olefin  $\text{R}^1\text{CH}=\text{CHR}^2$  may be prepared by dehydroiodination of a trihydroiodoperfluoroalkane of the formula  $\text{R}^1\text{CHICH}_2\text{R}^2$  formed in turn by reacting a perfluoroalkyl iodide of the formula  $\text{R}^2\text{I}$  with a perfluoroalkyltrihydroolefin of the formula  $\text{R}^1\text{CH}=\text{CH}_2$ .

[0027] Said contacting of a perfluoroalkyl iodide with a perfluoroalkyltrihydroolefin may take place in batch mode by combining the reactants in a suitable reaction vessel capable of operating under the autogenous pressure of the reactants and products at reaction temperature. Suitable reaction vessels include those fabricated from stainless steels, in particular of the austenitic type, and the well-known high nickel alloys such as Monel® nickel-copper alloys, Hastelloy® nickel based alloys and Inconel® nickel-chromium alloys. Alternatively, the reaction may take place in semi-batch mode in which the perfluoroalkyltrihydroolefin reactant is added to the perfluoroalkyl iodide reactant by means of a suitable addition apparatus such as a pump at the reaction temperature.

[0028] The ratio of perfluoroalkyl iodide to perfluoroalkyltrihydroolefin should be between about 1:1 to about 4:1, preferably from about 1.5:1 to 2.5:1. Ratios less than 1.5:1 tend to result in large amounts of the 2:1 adduct as reported by Jeanneaux, et. al. in Journal of Fluorine Chemistry, Vol. 4, pages 261-270 (1974).

[0029] Temperatures for contacting of said perfluoroalkyl iodide with said perfluoroalkyltrihydroolefin are preferably

within the range of about 150° C. to 300° C., more preferably from about 170° C. to about 250° C., and most preferably from about 180° C. to about 230° C. Pressures for contacting of said perfluoroalkyl iodide with said perfluoroalkyltrihydroolefin are preferably the autogenous pressure of the reactants at the reaction temperature.

[0030] Suitable contact times for the reaction of the perfluoroalkyl iodide with the perfluoroalkyltrihydroolefin are from about 0.5 hour to 18 hours, preferably from about 4 to about 12 hours.

[0031] The trihydroiodoperfluoroalkane prepared by reaction of the perfluoroalkyl iodide with the perfluoroalkyltrihydroolefin may be used directly in the dehydroiodination step or may preferably be recovered and purified by distillation prior to the dehydroiodination step.

[0032] In yet another embodiment, the contacting of a perfluoroalkyl iodide with a perfluoroalkyltrihydroolefin takes place in the presence of a catalyst. In one embodiment, a suitable catalyst is a Group VIII transition metal complex. Representative Group VIII transition metal complexes include, without limitation, zero valent  $\text{NiL}_4$  complexes, wherein the ligand, L, can be a phosphine ligand, a phosphite ligand, a carbonyl ligand, an isonitrile ligand, an alkene ligand, or a combination thereof. In one such embodiment, the  $\text{Ni(0)L}_4$  complex is a  $\text{NiL}_2(\text{CO})_2$  complex. In one particular embodiment, the Group VIII transition metal complex is bis(triphenyl phosphine)nickel(0) dicarbonyl. In one embodiment, the ratio of perfluoroalkyl iodide to perfluoroalkyltrihydroolefin is between about 3:1 to about 8:1. In one embodiment, the temperature for contacting of said perfluoroalkyl iodide with said perfluoroalkyltrihydroolefin in the presence of a catalyst, is within the range of about 80° C. to about 130° C. In another embodiment, the temperature is from about 90° C. to about 120° C.

[0033] In one embodiment, the contact time for the reaction of the perfluoroalkyl iodide with the perfluoroalkyltrihydroolefin in the presence of a catalyst is from about 0.5 hour to about 18 hours. In another embodiment, the contact time is from about 4 to about 12 hours.

[0034] The dehydroiodination step is carried out by contacting the trihydroiodoperfluoroalkane with a basic substance. Suitable basic substances include alkali metal hydroxides (e.g., sodium hydroxide or potassium hydroxide), alkali metal oxide (for example, sodium oxide), alkaline earth metal hydroxides (e.g., calcium hydroxide), alkaline earth metal oxides (e.g., calcium oxide), alkali metal alkoxides (e.g., sodium methoxide or sodium ethoxide), aqueous ammonia, sodium amide, or mixtures of basic substances such as soda lime. Preferred basic substances are sodium hydroxide and potassium hydroxide.

[0035] Said contacting of the trihydroiodoperfluoroalkane with a basic substance may take place in the liquid phase preferably in the presence of a solvent capable of dissolving at least a portion of both reactants. Solvents suitable for the dehydroiodination step include one or more polar organic solvents such as alcohols (e.g., methanol, ethanol, n-propanol, isopropanol, n-butanol, isobutanol, and tertiary butanol), nitriles (e.g., acetonitrile, propionitrile, butyronitrile, benzonitrile, or adiponitrile), dimethyl sulfoxide, N,N-dimethylformamide, N,N-dimethylacetamide, or sulfolane. The choice of solvent depends on the solubility of the basic

substance, the solubility of the perfluoroalkyl iodide, and the solubility of the perfluoroalkyltrihydroolefin as well as the boiling point of the product, and the ease of separation of traces of the solvent from the product during purification. Typically, ethanol or isopropanol are good solvents for the reaction. Separation of solvent from the product may be effected by distillation, extraction, phase separation, or a combination of the three.

[0036] Typically, the dehydroiodination reaction may be carried out by addition of one of the reactants (either the basic substance or the trihydroiodoperfluoroalkane) to the other reactant in a suitable reaction vessel. Said reaction vessel may be fabricated from glass, ceramic, or metal and is preferably agitated with an impellor or other stirring mechanism.

[0037] Temperatures suitable for the dehydroiodination reaction are from about 10° C. to about 100° C., preferably from about 20° C. to about 70° C. The dehydroiodination reaction may be carried out at ambient pressure or at reduced or elevated pressure. Of note are dehydroiodination reactions in which the compound of Formula I is distilled out of the reaction vessel as it is formed.

[0038] Alternatively, the dehydroiodination reaction may be conducted by contacting an aqueous solution of said basic substance with a solution of the trihydroiodoperfluoroalkane in one or more organic solvents of lower polarity such as an alkane (e.g., hexane, heptane, or octane), aromatic hydrocarbon (e.g., toluene), halogenated hydrocarbon (e.g., methylene chloride, ethylene dichloride, chloroform, carbon tetrachloride, or perchloroethylene), or ether (e.g., diethyl ether, methyl tert-butyl ether, tetrahydrofuran, 2-methyl tetrahydrofuran, dioxane, dimethoxyethane, diglyme, or tetraglyme) in the presence of a phase transfer catalyst. Suitable phase transfer catalysts include quaternary ammonium halides (e.g., tetrabutylammonium bromide, tetrabutylammonium hydrosulfate, triethylbenzylammonium chloride, dodecyltrimethylammonium chloride, and tricaprylmethylammonium chloride), quaternary phosphonium halides (e.g., triphenylmethylphosphonium bromide and tetraphenylphosphonium chloride), cyclic ether compounds known in the art as crown ethers (e.g., 18-crown-6 and 15-crown-5).

[0039] Alternatively, the dehydroiodination reaction may be conducted in the absence of solvent by adding the trihydroiodoperfluoroalkane to one or more solid or liquid basic substance(s).

[0040] Suitable reaction times for the dehydroiodination reactions are from about 15 minutes to about six hours or more depending on the solubility of the reactants. Typically the dehydroiodination reaction is rapid and requires about 30 minutes to about three hours for completion.

[0041] The compound of formula I may be recovered from the dehydroiodination reaction mixture by phase separation, optionally after addition of water, by distillation, or by a combination thereof.

[0042] In another embodiment, the invention relates to compositions comprising perfluoroethyl isopropyl ketone (1,1,1,2,2,4,5,5,5-nonafluoro-4-(trifluoromethyl)-3-pentanone, (PEIK) and at least two compounds selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons. PEIK has CAS Reg. No. 756-13-8) and is available from 3M™ (St. Paul, Minn.).

[0043] In yet another embodiment, the invention relates to compositions comprising nonafluoro-1-hexene (3,3,4,4,5,5,6,6,6-nonafluoro-1-hexene), (PFBE), and at least one compound selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons and combinations thereof. 3,3,4,4,5,5,6,6,6-Nonafluoro-1-hexene, also known as HFC-1549fz, has CAS Registry Number 19430-93-4 and is available from E.I. DuPont de Nemours & Co (Wilmington, Del.).

[0044] In yet another embodiment, the invention relates to a process for cleaning surfaces using azeotropic or azeotrope-like compositions comprising a fluorinated olefin, or a fluorinated ketone and at least one compound selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons.

[0045] The fluoroolefins of Table 1, PEIK, and PFBE may be combined with the compounds listed in Table 2 to form the present inventive compositions. The at least one compound selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, or hydrofluorocarbons to be combined with PFBE shall not be an alcohol, trans-1,2-dichloroethylene alone, C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub> alone, HFC-43-10mee alone, HFC-365mfc alone, or a mixture of trans-1,2-dichloroethylene and C<sub>4</sub>F<sub>9</sub>OC<sub>2</sub>H<sub>5</sub>.

TABLE 2

Name	Chemical formula	Synonym (or abbreviation)	CAS registry number
<u>Halocarbons</u>			
trichloroethylene	CHCl=CCl <sub>2</sub>	TCE	79-01-6
tetrachloroethylene (or perchloroethylene)	CCl <sub>2</sub> =CCl <sub>2</sub>	PCE	127-18-4
n-propylbromide	CH <sub>3</sub> CH <sub>2</sub> CH <sub>2</sub> Br	nPBr	
trans-1,2-dichloroethylene	CHCl=CHCl	t-DCE	156-60-5
<u>Alcohols</u>			
methanol	CH <sub>3</sub> OH	MeOH	67-56-1
ethanol	CH <sub>3</sub> CH <sub>2</sub> OH	EtOH	64-17-5
n-propanol	CH <sub>3</sub> CH <sub>2</sub> CH <sub>2</sub> OH	n-PrOH	71-23-8
isopropanol	CH <sub>3</sub> CH(OH)CH <sub>3</sub>	IPA	67-63-0

TABLE 2-continued

Name	Chemical formula	Synonym (or abbreviation)	CAS registry number
<u>Fluoroethers</u>			
mixture of isomers- 1,1,1,2,2,3,3,4,4- nonafluoro-4- methoxybutane and 2-(methoxy- difluoromethyl)- 1,1,1,2,3,3,3- heptafluoropropane	CF <sub>3</sub> CF <sub>2</sub> CF <sub>2</sub> CF <sub>2</sub> OCH <sub>3</sub> and (CF <sub>3</sub> ) <sub>2</sub> CFCF <sub>2</sub> OCH <sub>3</sub>	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	163702-07-6 and 163702-08-7
mixture of isomers- 1-ethoxy- 1,1,2,2,3,3,4,4,4- nonafluorobutane and 2-(ethoxy- difluoromethyl)- 1,1,1,2,3,3,3- heptafluoropropane	CF <sub>3</sub> CF <sub>2</sub> CF <sub>2</sub> CF <sub>2</sub> OC <sub>2</sub> H <sub>5</sub> and (CF <sub>3</sub> ) <sub>2</sub> CFCF <sub>2</sub> OC <sub>2</sub> H <sub>5</sub>	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	163702-05-4 and 163702-06-5
<u>Hydrofluorocarbons</u>			
1,1,1,2,3,4,4,5,5,5- decafluoropentane	CF <sub>3</sub> CHFCHF <sub>2</sub> CF <sub>3</sub>	HFC-43-10mee	
1,1,1,3,3- pentafluorobutane	CF <sub>3</sub> CH <sub>2</sub> CF <sub>2</sub> CH <sub>3</sub>	HFC-365mfc	

[0046] The compounds listed in Table 2 are commercially available from chemical supply houses. C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub>, and C<sub>4</sub>F<sub>9</sub>OC<sub>2</sub>H<sub>5</sub> are available from 3M™ (St. Paul, Minn.). HFC-43-10mee is available from E.I. DuPont de Nemours & Co (Wilmington, Del.). HFC-365mfc is available from Solvay-Solexis.

[0047] The compositions of the present invention may be prepared by any convenient method by combining the desired amounts of the individual components. A preferred method is to weigh the desired component amounts and thereafter combining the components in an appropriate vessel. Agitation may be used, if desired.

[0048] The compositions of the present invention comprise azeotropic or azeotrope-like compositions containing one of the fluoroolefins listed in Table 1, PEIK, or PFBE, and at least one of the compounds selected from the group consisting of: trichloroethylene; tetrachloroethylene; trans-1,2-dichloroethylene; n-propylbromide; methanol; ethanol; n-propanol; isopropanol; C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub>; C<sub>4</sub>F<sub>9</sub>OC<sub>2</sub>H<sub>5</sub>; HFC-43-10mee; HFC-365mfc; and combinations thereof. The exception thereto being that according to the compositions of the present invention, PFBE is not combined with an alcohol, trans-1,2-dichloroethylene alone, C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub> alone, HFC-43-10mee alone, HFC-365mfc alone, or a mixture of trans-1,2-dichloroethylene or C<sub>4</sub>F<sub>9</sub>OC<sub>2</sub>H<sub>5</sub>.

[0049] As used herein, an azeotropic composition is a constant boiling liquid admixture of two or more substances wherein the admixture distills without substantial composition change and behaves as a constant boiling composition. Constant boiling compositions, which are characterized as azeotropic, exhibit either a maximum or a minimum boiling point, as compared with that of the non-azeotropic mixtures of the same substances. Azeotropic compositions as used herein include homogeneous azeotropes which are liquid admixtures of two or more substances that behave as a single substance, in that the vapor, produced by partial evaporation

or distillation of the liquid, has the same composition as the liquid. Azeotropic compositions as used herein also include heterogeneous azeotropes where the liquid phase splits into two or more liquid phases. In these embodiments, at the azeotropic point, the vapor phase is in equilibrium with two liquid phases and all three phases have different compositions. If the two equilibrium liquid phases of a heterogeneous azeotrope are combined and the composition of the overall liquid phase calculated, this would be identical to the composition of the vapor phase.

[0050] As used herein, the term "azeotrope-like composition" also sometimes referred to as "near azeotropic composition," means a constant boiling, or substantially constant boiling liquid admixture of two or more substances that behaves as a single substance. One way to characterize an azeotrope-like composition is that the vapor produced by partial evaporation or distillation of the liquid has substantially the same composition as the liquid from which it was evaporated or distilled. That is, the admixture distills/refluxes without substantial composition change. Another way to characterize an azeotrope-like composition is that the bubble point vapor pressure of the composition and the dew point vapor pressure of the composition at a particular temperature are substantially the same. Herein, a composition is azeotrope-like if, after 50 weight percent of the composition is removed such as by evaporation or boiling off, the difference in vapor pressure between the original composition and the composition remaining after 50 weight percent of the original composition has been removed by evaporation or boil off is less than 10 percent.

[0051] In cleaning apparatus, such as vapor degreasers or defluxers, some loss of the cleaning compositions may occur during operation through leaks in shaft seals, hose connections, soldered joints and broken lines. In addition, the working composition may be released to the atmosphere during maintenance procedures on equipment. If the composition is not a pure compound or azeotropic or azeotrope-

like composition, the composition may change when leaked or discharged to the atmosphere from the equipment, which may cause the composition remaining in the equipment to become flammable or to exhibit unacceptable performance. Accordingly, it is desirable to use as a cleaning composition a single fluorinated hydrocarbon or an azeotropic or azeotrope-like composition that fractionates to a negligible degree upon leak or boil-off.

[0052] The azeotropic compositions of one embodiment of the present invention are listed in Table 3.

TABLE 3

Comp A	Comp B	wt % A	wt % B	T(C)
F14E	methanol	85.1	14.9	59.1
F14E	isopropanol	87.1	12.9	66.9
F14E	ethanol	87.9	12.1	65.2
F14E	t-DCE	44.3	55.7	44.0
F14E	nPBr	54.4	45.6	66.6
F24E	methanol	72.1	27.9	63.4
F24E	isopropanol	78.1	21.9	74.1
F24E	ethanol	79.2	20.8	71.8
F24E	t-DCE	24.5	75.5	45
F24E	nPBr	25.7	74.3	70.2
F24E	PCE	85.2	14.8	89.9
F24E	TCE	65.0	35.0	75.9
PEIK	methanol	97.0	3.0	43.5
PEIK	isopropanol	96.7	3.3	45.5
PEIK	ethanol	96.8	3.2	44.7
PEIK	t-DCE	72.9	27.1	34.7
PEIK	43-10mee	73.2	26.8	47.7
PEIK	365mfc	38.8	61.2	38.1
PFBE	methanol	92.2	7.8	50.6
PFBE	isopropanol	95.2	4.8	56.3
PFBE	ethanol	94.8	5.2	55.2
PFBE	t-DCE	52.8	47.2	41.3
PFBE	nPBr	82.3	17.7	57.1
F22E	methanol	95.8	4.2	43.7
F22E	isopropanol	98.0	2.0	47.2
F22E	ethanol	97.6	2.4	46.6
F22E	t-DCE	71.0	29.0	43.9
F22E	nPBr	87.0	13.0	43.3
F22E	43-10mee	89.8	10.2	47.9
F22E	365mfc	29.3	70.7	39.2
F13iE	methanol	95.5	4.5	44.4
F13iE	isopropanol	97.8	2.2	48.0
F13iE	ethanol	97.4	2.6	47.5
F13iE	t-DCE	70.2	29.8	34.4
F13iE	nPBr	86.4	13.6	44.0
F13iE	43-10mee	95.3	4.7	48.8
F13iE	365mfc	24.6	75.4	39.5
F313iE	methanol	85.0	15.0	59.8
F313iE	isopropanol	89.2	10.8	70.0
F313iE	ethanol	89.0	11.0	67.8
F313iE	t-DCE	44.1	55.9	44.5
F313iE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	22.8	77.2	75.7
F313iE	nPBr	67.4	32.6	61.3
F13E	methanol	94.4	5.6	47.3
F13E	isopropanol	96.9	3.1	51.9
F13E	ethanol	96.5	3.5	51.1
F13E	t-DCE	66.3	33.7	36.3
F13E	nPBr	83.7	16.3	47.1
F13E	43-10mee	59.5	40.5	52.3
F314E	t-DCE	7.6	92.4	47.6
F314E	methanol	42.8	57.2	65.4
F314E	isopropanol	57.8	42.2	81.0
F314E	ethanol	58.7	41.3	77.3
F314E	nPBr	31.9	68.1	69.6
F44E	nPBr	8.1	91.9	70.9

[0053] Additionally in another embodiment, the azeotropic compositions of the present invention may include ternary and quaternary azeotropic compositions comprising compounds from Table 2. Examples without limitation of

these higher order azeotropic compositions are exemplified in Table 4 along with the atmospheric pressure boiling points for the compositions.

TABLE 4

Comp A	Comp B	Comp C	wt % A	wt % B	wt % C	T(C.)
F14E	t-DCE	methanol	34.4	59.0	6.6	39.9
F14E	t-DCE	ethanol	41.9	55.1	3.0	43.2
F24E	t-DCE	methanol	10.3	80.3	9.4	41.0
F24E	t-DCE	ethanol	24.8	70.9	4.3	43.0
PEIK	t-DCE	methanol	71.5	26.4	2.1	33.0
PEIK	t-DCE	ethanol	73.0	25.7	1.3	34.2
PEIK	t-DCE	43-10mee	57.0	26.9	16.1	34.3
PEIK	t-DCE	365mfc	43.7	24.1	32.2	32.6
PFBE	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	40.1	47.5	12.4	41.3
F22E	t-DCE	methanol	67.9	29.7	2.4	32.6
F22E	t-DCE	365mfc	45.4	27.2	27.4	33.0
F13iE	t-DCE	methanol	66.9	30.6	2.5	33.0
F13iE	t-DCE	43-10mee	69.8	29.8	0.4	34.4
F13iE	t-DCE	365mfc	41.9	27.8	30.3	33.3
F313iE	t-DCE	methanol	32.9	60.2	6.9	40.1
F313iE	t-DCE	ethanol	41.1	56.3	2.6	43.8
F13E	t-DCE	methanol	62.2	34.7	3.1	34.5
F13E	t-DCE	43-10mee	48.0	33.2	18.8	36.1
F13E	t-DCE	365mfc	23.1	30.3	46.6	34.4

[0054] The binary azeotrope-like compositions of the present invention are listed in Table 5.

TABLE 5

Comp A	Comp B	wt % A	wt % B	T(C)
F14E	Methanol	60-99	1-40	59.1
F14E	Isopropanol	70-99	1-30	66.9
F14E	Ethanol	72-99	1-28	65.2
F14E	t-DCE	1-75	25-99	44.0
F14E	nPBr	1-99	1-99	66.6
F14E	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
F14E	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-99	1-99	50
F14E	43-10mee	1-99	1-99	50
F24E	Methanol	1-91	9-99	63.4
F24E	Isopropanol	57-91	9-43	74.1
F24E	Ethanol	57-92	8-43	71.8
F24E	t-DCE	1-63	37-99	46.1
F24E	nPBr	1-70	30-99	70.2
F24E	PCE	61-99	1-39	89.9
F24E	TCE	40-84	16-60	75.9
F24E	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-99	1-99	50
PEIK	Methanol	91-99	1-9	43.5
PEIK	Isopropanol	57-99	1-16	45.5
PEIK	Ethanol	85-99	1-15	44.7
PEIK	t-DCE	50-88	12-50	34.7
PEIK	4310mcee	1-99	1-99	47.7
PEIK	365mfc	1-99	1-99	38.1
PEIK	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
PFBE	Methanol	80-99	1-20	50.6
PFBE	Isopropanol	83-99	1-17	56.3
PFBE	Ethanol	83-99	1-17	55.2
PFBE	t-DCE	21-79	21-79	41.3
PFBE	nPBr	44-99	1-55	57.1
PFBE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
PFBE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-99	1-99	50
PFBE	43-10mee	1-99	1-99	50
PFBE	365mfc	1-99	1-99	50
F22E	Methanol	86-99	1-14	43.7
F22E	Isopropanol	88-99	1-12	47.2
F22E	Ethanol	88-99	1-12	46.6
F22E	t-DCE	48-87	13-52	33.9
F22E	nPBr	64-99	1-36	43.3
F22E	43-10mee	1-99	1-99	47.9
F22E	365mfc	1-99	1-99	39.2
F22E	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50

TABLE 5-continued

Comp A	Comp B	wt % A	wt % B	T(C)
F13iE	Methanol	86-99	1-14	44.4
F13iE	Isopropanol	87-99	1-13	48.0
F13iE	Ethanol	88-99	1-12	47.5
F13iE	t-DCE	46-86	14-54	34.4
F13iE	nPBr	64-99	1-36	44.0
F13iE	43-10mee	1-99	1-99	48.8
F13iE	365mfc	1-99	1-99	39.5
F13iE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
F3i3iE	Methanol	57-99	1-43	59.8
F3i3iE	Isopropanol	73-99	1-27	70.0
F3i3iE	Ethanol	73-99	1-27	67.8
F3i3iE	t-DCE	1-76	24-99	44.5
F3i3iE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-99	1-99	75.7
F3i3iE	nPBr	43-86	14-57	61.3
F3i3iE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
F13E	Methanol	84-99	1-16	47.3
F13E	Isopropanol	86-99	1-14	51.9
F13E	Ethanol	86-99	1-14	51.1
F13E	t-DCE	42-84	16-58	36.3
F13E	nPBr	61-99	1-39	47.1
F13E	43-10mee	1-99	1-99	52.3
F13E	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-99	1-99	50
F13E	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-99	1-99	50
F13E	365mfc	1-99	1-99	50
F3i4E	t-DCE	1-69	31-99	47.6
F3i4E	Methanol	1-89	11-99	65.4
F3i4E	Isopropanol	1-88	12-99	81
F3i4E	Ethanol	1-89	11-99	77.3
F3i4E	nPBr	1-72	28-99	69.6
F44E	nPBr	1-70	30-99	70.9

[0055] In addition to the binary azeotrope-like compositions in the preceding table, higher order (ternary or quaternary) azeotrope-like compositions are included in the present invention. Examples without limitation of ternary or higher order azeotrope-like compositions are given in Table 6.

TABLE 6

Comp A	Comp B	Comp C	wt % A	wt % B	wt % C	T(C)
F14E	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-70	20-70	1-70	50
F14E	t-DCE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-70	29-90	1-60	50
F14E	t-DCE	43-10mee	1-80	15-60	1-80	50
F14E	t-DCE	365mfc	1-70	10-60	1-80	50
F14E	t-DCE	Methanol	1-70	29-98	1-30	39.9
F14E	t-DCE	ethanol	1-70	29-98	1-20	43.2
F24E	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-70	20-70	1-70	50
F24E	t-DCE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-60	30-80	1-60	50
F24E	t-DCE	Methanol	1-50	40-98	1-25	41.0
F24E	t-DCE	ethanol	1-60	39-98	1-20	45.0
PEIK	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-70	20-50	1-70	50
PEIK	t-DCE	Methanol	50-85	14-49	1-9	33.0
PEIK	t-DCE	ethanol	50-85	14-49	1-9	34.2
PEIK	t-DCE	43-10mee	1-85	10-65	1-80	34.3
PEIK	t-DCE	365mfc	1-85	1-55	1-85	32.6
PFBE	t-DCE	43-10mee	1-70	20-60	1-79	50
PFBE	t-DCE	365mfc	1-70	15-60	1-80	50
PFBE	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-75	24-75	1-70	41.3
F22E	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-70	29-70	1-70	50
F22E	t-DCE	43-10mee	1-80	19-60	1-80	50
F22E	t-DCE	Methanol	45-85	14-54	1-10	32.6
F22E	t-DCE	365mfc	1-89	10-60	1-85	33.0
F13iE	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-75	24-70	1-70	50
F13iE	t-DCE	Methanol	45-85	14-54	1-10	33.0
F13iE	t-DCE	43-10mee	1-89	10-60	1-80	34.4
F13iE	t-DCE	365mfc	1-89	10-60	1-84	33.3
F3i3iE	t-DCE	Methanol	1-70	29-95	1-25	40.1
F3i3iE	t-DCE	ethanol	1-65	34-98	1-15	43.8

TABLE 6-continued

Comp A	Comp B	Comp C	wt % A	wt % B	wt % C	T(C)
F3i3iE	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-69	30-70	1-69	50
F3i3iE	t-DCE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-69	30-80	1-69	50
F13E	t-DCE	Methanol	45-80	19-54	1-10	34.5
F13E	t-DCE	43-10mee	1-85	14-60	1-80	36.1
F13E	t-DCE	365mfc	1-85	14-60	1-80	34.4
F13E	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-80	19-70	1-70	50
F3i4E	t-DCE	C <sub>4</sub> F <sub>9</sub> OCH <sub>3</sub>	1-30	25-69	30-69	50
F3i4E	t-DCE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-50	30-98	1-60	50
F44E	t-DCE	C <sub>4</sub> F <sub>9</sub> OC <sub>2</sub> H <sub>5</sub>	1-70	1-60	29-98	50

[0056] In yet another embodiment of the invention, the compositions of the present invention may further comprise an aerosol propellant. Aerosol propellants may assist in delivering the present compositions from a storage container to a surface in the form of an aerosol. Aerosol propellant is optionally included in the present compositions in up to 25 weight percent of the total composition. Representative aerosol propellants comprise air, nitrogen, carbon dioxide, difluoromethane (HFC-32, CH<sub>2</sub>F<sub>2</sub>), trifluoromethane (HFC-23, CHF<sub>3</sub>), difluoroethane (HFC-152a, CHF<sub>2</sub>CH<sub>3</sub>), trifluoroethane (HFC-143a, CH<sub>3</sub>CF<sub>3</sub>; or HFC-143, CHF<sub>2</sub>CH<sub>2</sub>F), tetrafluoroethane (HFC-134a, CF<sub>3</sub>CH<sub>2</sub>F; HFC-134, CHF<sub>2</sub>CH<sub>2</sub>F), pentafluoroethane (HFC-125, CF<sub>3</sub>CHF<sub>2</sub>), heptafluoropropane (HFC-227ea, CF<sub>3</sub>CHFCF<sub>3</sub>), pentafluoropropane (HFC-245fa, CF<sub>3</sub>CH<sub>2</sub>CHF<sub>2</sub>), dimethyl ether (CH<sub>3</sub>OCH<sub>3</sub>), or mixtures thereof.

[0057] In an embodiment of the invention, the present inventive azeotropic compositions are effective cleaning agents, defluxers and degreasers. In particular, the present inventive azeotropic compositions are useful when de-fluxing circuit boards with components such as Flip chip,  $\mu$ BGA (ball grid array), and Chip scale or other advanced high-density packaging components. Flip chips,  $\mu$ BGA, and Chip scale are terms that describe high density packaging components used in the semi-conductor industry and are well understood by those working in the field.

[0058] In another embodiment the present invention relates to a process for removing residue from a surface or substrate, comprising: contacting the surface or substrate with a composition of the present invention and recovering the surface or substrate from the composition.

[0059] In a process embodiment of the invention, the surface or substrate may be an integrated circuit device, in which case, the residue comprises rosin flux or oil. The integrated circuit device may be a circuit board with various types of components, such as Flip chips,  $\mu$ BGAs, or Chip scale packaging components. The surface or substrate may additionally be a metal surface such as stainless steel. The rosin flux may be any type commonly used in the soldering of integrated circuit devices, including but not limited to RMA (rosin mildly activated), RA (rosin activated), WS (water soluble), and OA (organic acid). Oil residues include but are not limited to mineral oils, motor oils, and silicone oils.

[0060] In the inventive process, the means for contacting the surface or substrate is not critical and may be accomplished by immersion of the device in a bath containing the composition, spraying the device with the composition or wiping the device with a substrate that has been wet with the

composition. Alternatively, the composition may also be used in a vapor degreasing or defluxing apparatus designed for such residue removal. Such vapor degreasing or defluxing equipment is available from various suppliers such as Forward Technology (a subsidiary of the Crest Group, Trenton, N.J.), Trek Industries (Azusa, Calif.), and Ultronix, Inc. (Hatfield, Pa.) among others.

[0061] An effective composition for removing residue from a surface would be one that had a Kauri-Butanol value (Kb) of at least about 10, preferably about 40, and even more preferably about 100. The Kauri-Butanol value (Kb) for a given composition reflects the ability of said composition to solubilize various organic residues (e.g., machine and conventional refrigeration lubricants). The Kb value may be determined by ASTM D-1133-94.

[0062] The following specific examples are meant to merely illustrate the invention, and are not meant to be limiting in any way whatsoever.

#### EXAMPLES

##### Example 1

##### Synthesis of

1,1,1,4,4,5,5,6,6,7,7,7-dodecafluorohept-2-ene  
(F14E)

##### Synthesis of $C_4F_9CH_2CHICF_3$

[0063] Perfluoro-n-butyliodide (180.1 gm, 0.52 moles) and 3,3,3-trifluoropropene (25.0 gm, 0.26 moles) were added to a 400 ml Hastelloy™ shaker tube and heated to 200° C. for 8 hours under autogenous pressure which increased to a maximum of 428 PSI. After cooling the reaction vessel to room temperature, the product was collected. The product of this reaction and two others carried out in substantially the same manner, except that one of the reactions had twice the quantity of reactants, were combined and distilled to give 322.4 gm of  $C_4F_9CH_2CHICF_3$  (52.2° C./35 mm, 70% yield).

##### Conversion of $C_4F_9CH_2CHICF_3$ to F14E

[0064] A 2 liter round bottom flask equipped with a stirring bar and packed distillation column and still head was charged with isopropyl alcohol (95 ml), KOH (303.7 gm, 0.54 moles) and water (303 ml).  $C_4F_9CH_2CHICF_3$  (322.4 gm, 0.73 mole) was added dropwise via addition funnel to the aqueous KOH/IPA mixture at room temperature. The reaction was then heated to 65-70° C. to recover the product by distillation. The distilled was collected, washed with sodium metabisulfite and water, dried over  $MgSO_4$  and then distilled through a 6-inch (15.2 cm) column packed with glass helices. The product, F14E (173.4 gm, 76% yield), boils at 78.2° C. It was characterized by NMR spectroscopy ( $^{19}F$ :  $\delta$ -66.7 (CF<sub>3</sub>, m, 3F), -81.7 (CF<sub>3</sub>, m, 3F), -124.8 (CF<sub>2</sub>, m, 2F), -126.4 (CF<sub>2</sub>, m, 2F), -114.9 ppm (CF<sub>2</sub>, m, 2F);  $^1H$ : 6.58d)

##### Example 2

Synthesis of 1,1,1,2,2,5,5,6,6,7,7,8,8,8-tetradecafluorooct-3-ene (F24E)

##### Synthesis of $C_4F_9CHICH_2C_2F_5$

[0065] Perfluoroethyl iodide (220 gm, 0.895 mole) and 3,3,4,4,5,5,6,6-nonafluorohex-1-ene (123 gm, 0.50 mole)

were added to a 400 ml Hastelloy™ shaker tube and heated to 200° C. for 10 hours under autogenous pressure. The product from this and two others carried out under substantially similar conditions were combined and washed with two 200 mL portions of 10 wt % aqueous sodium bisulfite. The organic phase was dried over calcium chloride and then distilled to give 277.4 gm of  $C_4F_9CH_2CHICF_3$  (79-81° C./67-68 mm Hg) in 37% yield.

##### Conversion of $C_4F_9CHICH_2C_2F_5$ to F24E

[0066] A 1 L round bottom flask equipped with a mechanical stirrer, addition funnel, condenser, and thermocouple was charged with  $C_4F_9CHICH_2C_2F_5$  (277.4 gm, 0.56 moles) and isopropanol (217.8 g). The addition funnel was charged with a solution of potassium hydroxide (74.5 g, 1.13 moles) dissolved in 83.8 g of water. The KOH solution was added dropwise to the flask with rapid stirring over the course of about one hour as the temperature slowly increased from 21° C. to 42° C. The reaction mass was diluted with water and the product recovered by phase separation. The product was washed with 50 mL portions of 10 wt % aqueous sodium bisulfite and water, dried over calcium chloride, and then distilled at atmospheric pressure. The product, F24E (128.7 gm, 63%) boils at 95.5° C. and was characterized by NMR ( $^{19}F$ :  $\delta$ -81.6 (CF<sub>3</sub>, m, 3F), -85.4 (CF<sub>3</sub>, m, 3F), -114.7 (CF<sub>2</sub>, m, 2F), -118.1 (CF<sub>2</sub>, m, 2F), -124.8 ppm (CF<sub>2</sub>, m, 2F), -126.3 ppm (CF<sub>2</sub>, m, 2F);  $^1H$ :  $\delta$ 6.48; chloroform-d solution).

##### Example 3

Synthesis of 1,1,1,4,5,5,5-Heptafluoro-4-(trifluoromethyl)-pent-2-ene (F13iE)

##### Synthesis of $CF_3CHICH_2CF(CF_3)_2$

[0067]  $(CF_3)_2CFI$  (265 gm, 0.9 moles) and 3,3,3-trifluoropropene (44.0 gm, 0.45 moles) were added to a 400 ml Hastelloy™ shaker tube and heated to 200° C. for 8 hours under autogenous pressure which increased to a maximum of 585 psi. The product was collected at room temperature to give 110 gm of  $(CF_3)_2CFCH_2CHICF_3$  (76-77° C./200 mm) in 62% yield.

##### Conversion of $(CF_3)_2CFCH_2CHICF_3$ to F13iE

[0068] A 500 ml round bottom flask equipped with a stirring bar and connected to a short path distillation column and dry ice trap was charged with isopropyl alcohol (50 ml), KOH (109 gm, 1.96 moles) and water (109 ml). The mixture was heated to 42° C. and  $(CF_3)_2CFCH_2CHICF_3$  (109 gm, 0.28 moles) was added dropwise via an addition funnel. During the addition, the temperature increased from 42 to 55° C. After refluxing for 30 minutes, the temperature in the flask increased to 62° C. and the product was collected by distillation. The product was collected, washed with water, dried with  $MgSO_4$ , and distilled. The product, F13iE (41 gm, 55% yield), boils at 48-50° C. and was characterized by NMR ( $^{19}F$ :  $\delta$ -187.6 (CF, m 1F), -77.1 (CF<sub>3</sub>, m 6F), -66.3 (CF<sub>3</sub>, m 3F); chloroform-d solution).

##### Example 4

##### Synthesis of $C_4F_9CHICH_2C_2F_5$

[0069] 3,3,4,4,5,5,6,6,6-Nonafluorohex-1-ene (20.5 gm, 0.0833 mole), bis(triphenyl phosphine)nickel(0) dicarbonyl



(0.53 g, 0.0008 mole), and perfluoroethylidide (153.6 gm, 0.625 mole) were added to a 210 ml Hastelloy™ shaker tube and heated at 100° C. for 8 hours under autogenous pressure. Analysis of the product by GC-MS indicated the presence of C4F9CHICH2C2F5 (64.3 GC area %) and the diadduct (3.3 GC area %); the conversion of 3,3,4,4,5,5,6,6,6-nonafluorohex-1-ene was 80.1%

Example 5

De-Fluxing

[0070] The compositions of the present invention are effective for cleaning ionic contamination (flux residue) from a surface. The test used to determine surface cleanliness involved the following steps:

[0071] 1. A rosin flux was painted liberally onto a FR-4 test board (an epoxy printed wiring board with tracing made of tinned copper).

[0072] 2. The board so treated was then heated in an oven at about 175 ° C. for about 1-2 minutes to activate the rosin flux.

[0073] 3. The board was then immersed in solder (Sn63, a 63/37 Sn/lead solder) at about 200° C. for about 10 seconds.

[0074] 4. The board was then cleaned by immersion in the boiling cleaning composition for about 3 minutes and providing gentle movement of the board. The board was then immersed in a fresh, room temperature bath of cleaning composition to rinse for about 2 minutes.

[0075] 5. The board was then tested for residual ionics with an Omega Meter 600 SMD ionic analyzer.

[0076] The cleaning performance was determined by weighing the board prior to deposition of the flux, after the deposition of the flux and then after the cleaning procedure. The results are given in Table 7.

TABLE 7

Composition (wt %)	Dry weight (grams)	Wet weight (grams)	Post dry weight (grams)	% soil removed
PEIK/t-	5.4951	5.5689	5.5010	92%
DCE/MeOH	5.0578	5.1401	5.0613	96%
(71.5/26.4/	5.4815	5.5554	5.4846	96%
2.1)	3.3450	5.4124	5.3483	95%
		Average		95%

Example 6

Metal Cleaning

[0077] Stainless steel (type 316) 2"x3" coupons that have been grit blasted to provide an unpolished surface were pre-cleaned and oven dried to remove any residual soil. The tare weight of each coupon was determined to 0.1 mg. A small amount of mineral oil was applied with a swab, the coupon was then re-weighed to obtain the "loaded" weight. The coupon was then cleaned by immersion into a boiling cleaning composition for 1 minute, held in vapor for 30 seconds and then air dried for 1 minute. The coupon was then re-weighed and the percent of soil removed calculated using the 3 recorded weights. The results are shown in Table 8.

TABLE 8

Composition (wt %)	Dry weight (grams)	Wet weight (grams)	Post Dry weight (grams)	Percent Soil removed
PEIK/t-DCE	21.588	21.6238	21.5881	100
(72.9/27.1)	21.5882	21.62.17	21.5877	101
	21.2181	21.3160	21.2180	100
		Average		100

[0078] The results show efficient removal of mineral oil residue from stainless steel surfaces by the compositions of the present invention.

Example 7

Metal Cleaning

[0079] Stainless steel (type 316) 2"x3" coupons that have been grit blasted to provide an unpolished surface were pre-cleaned and oven dried to remove any residual soil. The tare weight of each coupon was determined to 0.1 mg. A small amount of DC 200 Silicone was applied with a swab, the coupon was then re-weighed to obtain the "loaded" weight. The coupon was then cleaned by immersion into a boiling cleaning composition for 1 minute, held in vapor for 30 seconds and then air dried for 1 minute. The coupon was then weighed and the percent of soil removed is calculated using the 3 recorded weights. The results are shown in Table 9.

TABLE 9

Composition (wt %)	Dry weight (grams)	Wet weight (grams)	Post Dry weight (grams)	Percent Soil removed
PEIK/t-DCE	21.2183	21.26343	21.2183	100
(72.9/27.1)	19.0196	19.0461	19.0198	99
	21.3960	21.4480	21.3963	99
		Average		100

[0080] The results show efficient removal of silicone residue from stainless steel surfaces by the compositions of the present invention.

Example 8

Metal Cleaning Efficacy

[0081] Stainless steel (type 316) 2"x3" coupons that have been grit blasted to provide an unpolished surface were pre-cleaned and oven dried to remove any residual soil. Each coupon was weighed to 4 places to obtain a tare weight. A small amount of mineral oil was applied with a swab, the coupon is then weighed to obtain the "loaded" weight. The coupon was then cleaned by immersion into a boiling cleaning composition for 1 minute, held in vapor for 30 seconds and then air dried for 1 minute. The coupon was then weighed and the percent of soil removed is calculated using the 3 recorded weights. The results are shown in Table 10.

TABLE 10

Composition (wt %)	Dry weight (grams)	Wet weight (grams)	Post Dry weight (grams)	Percent Soil removed
PEIK/MeOH (97.0/3.0)	21.2968	21.3525	21.3029	89
	21.2470	21.62678	21.2530	71
	21.5313	21.5656	21.5417	70
		Average		77

[0082] The results show efficient removal of mineral oil residue from stainless steel surfaces by the compositions of the present invention.

## Example 9

## Metal Cleaning Efficacy

[0083] Stainless steel (type 316) 2"×3" coupons that have been grit blasted to provide an unpolished surface were pre-cleaned and oven dried to remove any residual soil. Each coupon was weighed to 4 places to obtain a tare weight. A small amount of DC 200 Silicone was applied with a swab, the coupon is then weighed to obtain the "loaded" weight. The coupon was then cleaned by immersion into a boiling cleaning composition for 1 minute, held in vapor for 30 seconds and then air dried for 1 minute. The coupon was then weighed and the percent of soil removed is calculated using the 3 recorded weights. The results are shown in Table 11.

TABLE 11

Composition (wt %)	Dry weight (grams)	Wet weight (grams)	Post Dry weight (grams)	Percent Soil removed
PEIK/MeOH (97.0/3.0)	20.9536	20.9902	20.9536	100
	21.1531	21.1889	21.1528	101
	20.6276	20.6735	20.6285	98
		Average		100

[0084] The results show efficient removal of silicone residue from stainless steel surfaces by the compositions of the present invention.

What is claimed is:

1. A composition comprising perfluoroethylisopropyl ketone (1,1,1,2,2,4,5,5,5-nonafluoro-4-(trifluoromethyl)-3-pentanone (PEIK)) and at least two compounds selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons.

2. A composition as in claim 1, wherein said composition is an azeotropic or azeotrope-like composition comprising perfluoroethylisopropyl ketone (1,1,1,2,2,4,5,5,5-nonafluoro-4-(trifluoromethyl)-3-pentanone (PEIK)) and at least two compounds selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons.

3. An azeotropic or azeotrope-like composition as in claim 2 wherein the at least two compounds selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons are either methanol, ethanol, iso-propanol, n-propanol, trans-1,2-dichloroethylene,

trichloroethylene, tetrachloroethylene, C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub>, C<sub>4</sub>F<sub>9</sub>OC<sub>2</sub>H<sub>5</sub>, HFC-43-10mee, or HFC-365mfc in any combination.

4. An azeotropic or azeotrope-like composition as in claim 2, wherein the composition comprises an azeotropic or azeotrope-like composition selected from the group consisting of:

about 50 to about 85 weight percent perfluoroethyl-isopropyl ketone, about 14 weight percent to about 49 weight percent trans-1,2-dichloroethylene, and about 1 to about 9 weight percent methanol;

about 50 to about 85 weight percent perfluoroethyl-isopropyl ketone, about 14 weight percent to about 49 weight percent trans-1,2-dichloroethylene, and about 1 to about 9 weight percent ethanol;

about 1 to about 85 weight percent perfluoroethyl-isopropyl ketone, about 10 weight percent to about 65 weight percent trans-1,2-dichloroethylene, and about 1 to about 80 weight percent HFC-43-10mee;

about 1 to about 85 weight percent perfluoroethyl-isopropyl ketone, about 1 weight percent to about 55 weight percent trans-1,2-dichloroethylene, and about 1 to about 85 weight percent HFC-365mfc; and

about 1 to about 70 weight percent perfluoroethyl-isopropyl ketone, about 20 weight percent to about 50 weight percent trans-1,2-dichloroethylene, and about 1 to about 70 weight percent C<sub>4</sub>F<sub>9</sub>OCH<sub>3</sub>.

5. An azeotropic or azeotrope-like composition as in claim 2, wherein the composition comprises an azeotropic or azeotrope-like composition selected from the group consisting of

71.5 weight percent perfluoroethyl-isopropyl ketone, 26.4 weight percent trans-1,2-dichloroethylene, and 2.1 weight percent methanol having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 33.0° C.;

73.0 weight percent perfluoroethyl-isopropyl ketone, 25.7 weight percent trans-1,2-dichloroethylene, and 1.3 weight percent ethanol having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 34.2° C.;

57.0 weight percent perfluoroethyl-isopropyl ketone, 26.9 weight percent trans-1,2-dichloroethylene, and 16.1 weight percent HFC-43-10mee having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 34.3° C.;

43.7 weight percent perfluoroethyl-isopropyl ketone, 24.1 weight percent trans-1,2-dichloroethylene, and 32.2 weight percent HFC-365mfc having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 32.6° C.;

6. A process for cleaning, comprising:

a. contacting a surface comprising a residue with the composition of claim 1 and

b. recovering the surface from the composition.

7. The composition of claim 1 further comprising an aerosol propellant.

8. The composition of claim 7 wherein the aerosol propellant is selected from the group consisting of air, nitrogen,

carbon dioxide, difluoromethane, trifluoromethane, difluoroethane, trifluoroethane, tetrafluoroethane, pentafluoroethane, heptafluoropropane, and pentafluoropropane.

9. A process for cleaning comprising:

(a) contacting a surface comprising a residue with an azeotropic or azeotrope-like composition comprising perfluoroethylisopropyl ketone (1,1,1,2,2,4,5,5,5-nonafluoro-4-(trifluoromethyl)-3-pentanone (PEIK)) and at least one compound selected from the group consisting of alcohols, halocarbons, fluoralkyl ethers, and hydrofluorocarbons.

(b) recovering the surface from the composition.

10. A process as in claim 9 wherein the at least one compound selected from the group consisting of alcohols, halocarbons, fluoroalkyl ethers, and hydrofluorocarbons is either methanol, ethanol, iso-propanol, n-propanol, trans-1,2-dichloroethylene, trichloroethylene, tetrachloroethylene,  $C_4F_9OCH_3$ ,  $C_4F_9OC_2H_5$ , HFC-43-10mee, HFC-365mfc or combinations thereof.

11. A process as in claim 9 wherein the the azeotropic or azeotrope-like composition is selected from the group consisting of:

about 91 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 9 weight percent methanol;

about 85 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 15 weight percent ethanol;

about 57 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 43 weight percent isopropanol;

about 1 to about 15 weight percent ethanol;

about 50 to about 88 weight percent perfluoroethyl-isopropyl ketone, and about 12 to about 50 weight percent trans-1,2-dichloroethylene;

about 1 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 99 weight percent HFC-43-10mee;

about 1 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 99 weight percent HFC-365mfc; and

about 1 to about 99 weight percent perfluoroethyl-isopropyl ketone, and about 1 to about 99 weight percent  $C_4F_9OCH_3$ .

12. A process as in claim 9 wherein the azeotropic or azeotrope-like composition is an azeotropic composition selected from the group consisting of:

97.0 weight percent perfluoroethyl-isopropyl ketone, 3.0 weight percent methanol having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 43.5° C.;

96.8 weight percent perfluoroethyl-isopropyl ketone, 3.2 weight percent ethanol having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 44.7° C.;

96.7 weight percent perfluoroethyl-isopropyl ketone, 3.3 weight percent isopropanol having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 45.5° C.;

72.9 weight percent perfluoroethyl-isopropyl ketone, 27.1 weight percent trans-1,2-dichloroethylene having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 34.7° C.;

73.2 weight percent perfluoroethyl-isopropyl ketone, 26.8 weight percent HFC-43-10mee having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 47.7° C.; and

38.8 weight percent perfluoroethyl-isopropyl ketone, 61.2 weight percent HFC-365mfc having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 38.1° C.;

13. A process as in claim 9 wherein wherein the azeotropic or azeotrope-like composition azeotropic composition is:

52.8 weight percent perfluoroethyl-isopropyl ketone, 47.2 weight percent trans-1,2-dichloroethylene having a vapor pressure of about 14.7 psia (101 kPa) at a temperature of about 41.3° C.;

14. The process of claim 9 wherein said residue comprises an oil.

15. The process of claim 9 wherein said residue comprises a rosin flux.

16. The process of claim 9 wherein said surface is an integrated circuit device.

\* \* \* \* \*