



US012027229B2

(12) **United States Patent**
Balasubramanian et al.

(10) **Patent No.:** **US 12,027,229 B2**

(45) **Date of Patent:** **Jul. 2, 2024**

(54) **HIGH SPEED DIFFERENTIAL ROM**

(56) **References Cited**

(71) Applicant: **Texas Instruments Incorporated**,
Dallas, TX (US)

(72) Inventors: **Suresh Balasubramanian**, Dallas, TX
(US); **David J. Toops**, Dallas, TX (US)

(73) Assignee: **Texas Instruments Incorporated**,
Dallas, TX (US)

U.S. PATENT DOCUMENTS

6,462,998	B1	10/2002	Proebsting	
6,504,778	B1	1/2003	Uekubo	
7,012,846	B2	3/2006	Balasubramanian et al.	
7,016,245	B2	3/2006	Balasubramanian et al.	
10,056,151	B1	8/2018	Vining	
2002/0021605	A1*	2/2002	Harada	G11C 29/24 365/201
2008/0025089	A1*	1/2008	Scheuerlein	G11C 17/18 365/185.03
2008/0031054	A1	2/2008	Lehmann et al.	
2010/0124089	A1	5/2010	Ali et al.	
2014/0140121	A1	5/2014	Clinton	
2014/0185401	A1	7/2014	Yang et al.	

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 145 days.

(21) Appl. No.: **17/877,954**

(22) Filed: **Jul. 31, 2022**

(65) **Prior Publication Data**

US 2023/0267969 A1 Aug. 24, 2023

OTHER PUBLICATIONS

PCT Search Report, Application No. PCT/US2023/013200, dated May 9, 2023. 3 pages.

* cited by examiner

Primary Examiner — Han Yang

(74) *Attorney, Agent, or Firm* — Andrew R. Ralston;
Frank D. Cimino

Related U.S. Application Data

(60) Provisional application No. 63/311,677, filed on Feb. 18, 2022.

(51) **Int. Cl.**
G11C 7/06 (2006.01)
G11C 7/10 (2006.01)
G11C 7/12 (2006.01)
H03K 19/173 (2006.01)


(52) **U.S. Cl.**
CPC **G11C 7/062** (2013.01); **G11C 7/1069**
(2013.01); **G11C 7/12** (2013.01); **H03K**
19/1737 (2013.01)

(58) **Field of Classification Search**
CPC G11C 7/062; G11C 7/1069; G11C 7/12
See application file for complete search history.

(57) **ABSTRACT**

A semiconductor device includes a ROM, a differential sense amplifier and a multiplexer logic circuit. The ROM has memory cells in rows along word lines and columns along bit lines, and a reference column having reference transistors along a reference bit line. The multiplexer logic circuit couples a selected bit line to a first differential amplifier input and couples the reference bit line to the second differential amplifier input and controls a reference current of the reference bit line to be between a first bit line current of a programmed memory cell and a second bit line current of an unprogrammed memory cell.

18 Claims, 16 Drawing Sheets






FIG. 1




FIG. 1A-2




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2









FIG. 5













1100

FIG. 11



1200

FIG. 12



HIGH SPEED DIFFERENTIAL ROM

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority to and benefit of U.S. Provisional Patent Application No. 63/311,677, filed on Feb. 18, 2022, and titled “High Speed Differential ROM”, the contents of which are hereby fully incorporated by reference.

BACKGROUND

The disclosed subject matter relates to read-only memory (ROM). ROM is used in many systems for storing firmware, software, or other computer executable instructions, as well as for data storage in a processor-based electronic system or device. Example ROM memories include a field effect transistor (FET) device programmed to one of two distinguishable electrical states and having a gate connected to an associated word line, a grounded source, and a drain connected to a bit line for a programmed cell and disconnected from the bit line for an unprogrammed cell. Reduced ROM read access times can improve system performance, but faster read access is a tradeoff versus ROM bit cell area with smaller ROM bit cells having better density and slower performance due to increased local mismatch, whereas larger ROM bit cells exhibit faster performance at the expense or increased circuit area and also increased bit line loading with increased leakage. Improved read time performance with little or no tradeoff in circuit area and leakage would benefit system performance.

SUMMARY

In one aspect, a semiconductor device includes a ROM, a differential sense amplifier, and a multiplexer logic circuit. The ROM has a plurality of memory cells in an array arranged in respective rows along word lines and columns along bit lines, with a column of the array having reference cells along a reference bit line. The memory cells include one of a corresponding plurality of cell transistors configured in a first state to conduct a first bit line current along the respective bit line when selected or in a second state to conduct a second bit line current that is less than the first bit line current. The differential sense amplifier is configured to generate a differential output voltage signal between first and second differential outputs based on first and second differential input currents at respective first and second amplifier inputs. The multiplexer logic circuit is configured to selectively couple a selected bit line to the first amplifier input, couple a reference current to the second amplifier input via the reference bit line, and control the reference current to be between the first bit line current and the second bit line current.

In another aspect, a method of forming a semiconductor device includes forming transistors in or over a semiconductor layer and forming a metallization structure with transistor interconnections to form a read-only memory (ROM), a differential sense amplifier, and a multiplexer logic circuit configured to selectively couple a selected bit line to a first amplifier input, couple a reference current to a second amplifier input via a reference bit line, and control the reference current to be between a first bit line current of a programmed cell and a second bit line current of an unprogrammed cell.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a simplified schematic diagram of an electronic device with a ROM, a differential sense amplifier, and a multiplexer logic circuit.

FIGS. 1A-1 and 1A-2 show a schematic diagram illustrating details of an example implementation of the ROM, the differential sense amplifier, and the multiplexer logic circuit.

FIG. 1B is a schematic diagram of a programmed cell in the ROM.

FIG. 1C is a schematic diagram of an unprogrammed cell in the ROM.

FIG. 1D is a simplified schematic diagram of an example digital processing system.

FIG. 2 is a flow diagram of a method of fabricating an electronic device.

FIGS. 3 and 4 are partial side elevation views of the electronic device of FIG. 1 undergoing fabrication processing according to the method of FIG. 2.

FIG. 5 is a flow diagram of a method of reading a ROM cell.

FIG. 6 is a graph of voltage signals in the electronic device during a memory read operation to read an unprogrammed memory cell.

FIG. 7 is a graph of voltage and current signals in the electronic device during a memory read operation to read the unprogrammed memory cell.

FIG. 8 is a graph of voltage signals in the electronic device during a memory read operation to read a programmed memory cell.

FIG. 9 is a graph of voltage and current signals in the electronic device during a memory read operation to read the programmed memory cell.

FIG. 10 is a graph of access time performance.

FIG. 11 is a graph of capacitance and read power performance.

FIG. 12 is a graph of ROM circuit area.

DETAILED DESCRIPTION

In the drawings, like reference numerals refer to like elements throughout, and the various features are not necessarily drawn to scale. Also, the term “couple” or “couples” includes indirect or direct electrical or mechanical connection or combinations thereof. For example, if a first device couples to or is coupled with a second device, that connection may be through a direct electrical connection, or through an indirect electrical connection via one or more intervening devices and connections. One or more operational characteristics of various circuits, systems and/or components are hereinafter described in the context of functions which in some cases result from configuration and/or interconnection of various structures when circuitry is powered and operating. Unless otherwise stated, “about,” “approximately,” or “substantially” preceding a value means ± 10 percent of the stated value.

Referring initially to FIGS. 1-1D, FIGS. 1, 1A-1, and 1A-2 show an electronic device **100**, e.g. a memory system, with an address decoder and read logic circuit **101** and a ROM **102** (e.g., labeled “MEMORY ARRAY”) having an array of memory cells **104** with respective programming features **105**. The memory cells **104** are arranged in columns along respective bit lines **106** and rows along respective word lines **108**. In the example of FIGS. 1, 1A-1, and 1A-2, the ROM **102** has an integer number N columns of memory cells **104** and corresponding bit lines **106** with respective bit

line voltage signals BL0, BL0, . . . , BLN-1, and an integer number M rows and corresponding word lines **108** with respective word line voltage signals WL0, WL1, . . . , WLM-1, where N and M can be any positive integers and may and need not be equal. Each of the memory cells **104** includes a corresponding instance of a cell transistor **109**. In the illustrated example, the cell transistors **109** are n-channel field effect transistors (FETs) having a source coupled to a reference voltage node VSS, a gate coupled to the respective word line **108** and a drain coupled to the respective programming feature **105**. Different types of cell transistors **109** may be used in other implementations, including without limitation, p-channel FETs, bipolar transistors, or cell diodes. In one example, the programming features **105** can be fuses or antifuses. The programming features **105** are coupled between the drain of the respective cell transistor **109** and the respective bit line **106**. As used herein, the individual cell transistors **109** are configured in a first state or a second state by the configuration of the respective programming feature **105**.

As used herein, a respective cell transistor **109** is configured in the first state (e.g., representing binary data value of 0) and is referred to as a programmed memory cell **104** by the respective programming feature being configured to electrically connect the cell transistor drain to the respective bit line **106**, and the cell transistor **109** is configured in the second state (e.g., representing binary data value of 1) and is referred to as an unprogrammed memory cell **104** by the respective programming feature being configured such that the cell transistor drain is not connected to the respective bit line **106**. The cells **104** in the first state (e.g., data 0, programmed) conduct a first bit line current I1 along the respective bit line **106** when selected, and the cells **104** in the second state (e.g., data 1, unprogrammed) conduct a second bit line current I2 along the respective bit line **106** when selected. (See FIGS. 1B and 1C infra and associated description.) For programmed cells **104**, the cell transistor **109** is connected to the respective bit line **106** and when selected by a gate signal on the respective word line **108**, the cell transistor **109** conducts the first current I1 from the bit line **106** to the reference voltage node VSS. In contrast, selection of an unprogrammed memory cell **104** does not provide any additional current flow path to the VSS node, and the first bit line current I1 of a programmed cell **104** is greater than the second bit line current I2 of an unprogrammed memory cell **104**. In the illustrated example, the first current I1 and the second current I2 are both negative, and the first current I1 is more negative (has a greater negative amplitude) than the second current I2. In this and other examples, the absolute value of the first current I1 is greater than the absolute value of the second current I2.

The electronic device **100** includes a multiplexer logic circuit **110** (e.g., labeled "MUX LOGIC") having a discharge circuit **111** with discharge transistors **112** coupled to the respective bit lines **106**. In the illustrated example, the discharge transistors **112** are n-channel FETs having a source coupled to the reference voltage VSS, a gate coupled to a discharge control input **113**, and a drain coupled to the respective bit line **106**. Different types of discharge transistors **112** may be used in other implementations, including without limitation, p-channel FETs, bipolar transistors, etc.

The multiplexer logic circuit **110** also includes a select circuit **114** having a row of bit select transistors **115** with source terminals coupled to the respective bit lines **106**. The address decoder and read logic circuit **101** has outputs that generate voltage signals to operate the memory cells **104** and the multiplexer logic circuit **110** for memory read operations

when the electronic device **100** is powered and operating. In a memory read operation, the address decoder and read logic circuit **101** provides the word line voltage signals WL0, WL1, . . . , WLM-1 to the gates of the cell transistors **109** to selectively activate a selected row of memory cells **104** along a selected word line **108**. In the illustrated example using n-channel FET cell transistors **109**, the address decoder and read logic circuit **101** provides the word line voltage signal for the selected word line **108** at a first voltage to turn on the cell transistors **109** of the selected row and provides the word line voltage signals for the non-selected word lines **108** at a second voltage that is lower than the first voltage to turn off the cell transistors **109** of the non-selected rows.

The address decoder and read logic circuit **101** also selectively provides a discharge voltage signal DIS to the discharge control input **113** to discharge the bit lines **106** at the beginning of a read operation. In the illustrated example with n-channel FET discharge transistors **112**, the address decoder and read logic circuit **101** provides the discharge voltage signal DIS at a first voltage to turn on the discharge transistors **112** and bring the respective bit lines **106** to or near the potential of the reference voltage node VSS, and then provides the discharge voltage signal DIS at a second voltage that is lower than the first voltage to subsequently turn off the discharge transistors **112**. The bit select transistors **115** are coupled between a first amplifier input **122** and the respective bit lines **106**.

A column of the array of the ROM **102** provides a reference for differential sensing, referred to as a reference column. The final array column in one example provides the reference column of the array in the illustrated example. In other implementations, another column of the array forms the reference column. The select circuit **114** includes three reference select transistors **116** in the reference column, and the ROM **102** includes a reference bit line (RBL) **117** of the reference column, which has a reference bit line voltage signal BLREF. The reference select transistors **116** have gate terminals connected to a reference select input **118**, and the reference column of the array has reference transistors **119** along the reference bit line **117**. The discharge circuit **111** includes a reference discharge transistor **112**. The reference discharge transistor **112** in the illustrated example is an n-channel FET having a drain coupled to the reference bit line **117**, a gate coupled to the discharge control input **113**, and a source coupled to the reference voltage VSS. Different types of discharge transistors **112** may be used in other implementations, including without limitation, p-channel FETs, bipolar transistors, etc. In the illustrated example, the reference discharge transistor **112** and the discharge transistors **112** along the N memory bit lines **106** are of similar size to one another, e.g. have about a same first gate width. In this or another example, the cell transistors **109** of the memory cells **104** and the reference transistors **119** along a reference bit line **117** are of similar size to one another, e.g. have about a same second gate width. In these or another example, the bit select transistors **115** and the reference select transistors **116** are of similar size to one another, e.g., have about a same third gate width. The first, second and third gate widths may be about the same, or may be different from each other in various examples.

The address decoder and read logic circuit **101** includes outputs coupled to the respective gates of the bit select transistors **115** and an output coupled to the reference select input **118**. The address decoder and read logic circuit **101** in the illustrated example provides select voltage signals SEL0, SEL1, . . . , SELN-1 to select one of the columns along a

selected bit line **106** during a memory read operation, and concurrently provides a reference select voltage signal RSEL to select the reference column during a memory read operation using differential sensing. In the illustrated example using n-channel FET select transistors and n-channel FET reference select transistors **116**, the address decoder and read logic circuit **101** provides the select voltage signal SEL for the selected bit line **106** and the reference select voltage signal RSEL at a first voltage to turn on the bit select transistor **115** of the selected column and to turn on the reference select transistors **116**, and the address decoder and read logic circuit **101** provides the select voltage signals SEL of the non-selected columns at a second voltage that is lower than the first voltage to turn off the bit select transistors **115** of the non-selected columns.

The electronic device **100** includes a differential sense amplifier **120**. The differential sense amplifier **120** has the first amplifier input **122** and a second amplifier input **124** to sense a differential current signal from the multiplexer logic circuit **110** during memory read operations. The differential sense amplifier **120** has a first amplifier output **126** (S OUT), a second amplifier output **128** (SOUTZ), and an enable input **129** that receives an enable voltage signal ENN from the address decoder and read logic circuit **101**. In operation, the differential sense amplifier **120** generates a differential output voltage signal S OUT, SOUTZ between the first and second amplifier outputs **126**, **128** based on a differential input current signal based on currents of the first and second amplifier inputs **122** and **124**. In operation during a memory read operation, the multiplexer logic circuit **110** selectively couples a selected one of the bit lines **106** to the first amplifier input **122** and couples the reference bit line **117** to the second amplifier input **124**.

The example differential sense amplifier **120** in FIG. 1A-1 is connected to a supply voltage VDD, and provides the differential output voltage signal SOUT, SOUTZ to a latch **130** during memory read operations. The latch **130** includes a data output that provides an output signal DATA that represents the data or state of the selected memory cell **104** (e.g., data 0, programmed or data 1, unprogrammed). In one example, the address decoder and read logic circuit **101** chooses a selected word of the ROM **102** and sequentially selects individual cell bit lines **106** of the selected word line **108** and uses a single differential sense amplifier **120** to sequentially read the individual cell data bits. In another implementation, multiple differential sense amplifiers **120** can be used for concurrent reading of multiple bits of a selected word line **108**. The differential sense amplifier **120** includes pull up transistors **131** and **132**. In the illustrated example, the transistors **131** and **132** are p-channel FETs with sources coupled to the supply voltage VDD and gates coupled to the enable input **129**. The differential sense amplifier **120** also includes left-side and right-side inverter circuits, with upper p-channel FETs **133** and **134** and lower n-channel FETs **135** and **136**, respectively. The transistors **133** and **135** form a first inverter circuit in a left circuit branch of the differential sense amplifier **120**, and the transistors **134** and **136** form a second inverter circuit in a right circuit branch. The differential sense amplifier **120** also includes output buffer inverters **137** and **138** having inputs coupled to the gates of the respective first and second inverter circuits. The output buffer inverter **137** has an output coupled to the second amplifier output **128** to provide the output voltage signal SOUTZ based on a right-side bit voltage signal BITR, and an output of the output buffer inverter **138** is coupled to the first amplifier output **126** to provide the output voltage signal SOUT based on a left-side

bit voltage signal BITL. In a memory read operation, following discharging of the bit lines **106** by the discharge circuit **111**, the address decoder and read logic circuit **101** asserts a selected word line **108** and asserts a selected one of the select voltage signals as well as the reference select signal RSEL to turn on the bit select transistor **115** of the selected column and to turn on the reference select transistors **116** to couple the selected bit line **106** to the first amplifier input **122** and to couple the reference bit line **117** to the second amplifier input **124**.

The multiplexer logic circuit **110** also controls a reference current IR of the reference bit line **117** to be between the first bit line current I1 and the second bit line current I2 during a memory read operation. In one example, the multiplexer logic circuit **110** controls the reference current IR of the reference bit line **117** to be approximately half the first bit line current I1 (e.g., 45% to 55% of the first bit line current I1). As shown in the example of FIG. 1A-1, the select circuit **114** has three reference select transistors **116** coupled in series between the second amplifier input **124** and the reference bit line **117**, and the reference select transistors **116** are of similar size to the bit select transistors **115**, e.g., have about a same gate width. In this example, the three series connected reference select transistors **116** control the reference current IR of the reference bit line **117** to be approximately half the first bit line current I1. This facilitates differentiation during memory read operations of current IB1 conducted by a selected cell transistor **109** of a cell **104** that has been programmed by connection to the respective bit line **106** by the programming feature **105**, from the current of a selected unprogrammed cell transistor **109** that is disconnected from the respective bit line **106**. In one implementation, the reference bit line **117** can be coupled to the second amplifier input **124** of multiple differential sense amplifiers **120** that are concurrently used to read respective bits from a selected word line **108**, with the multiplexer logic circuit **110** including corresponding bit select transistors **115** routed to the respective first amplifier inputs **122** of the respective differential sense amplifiers **120**. This approach can reduce the circuit area significantly compared to differential sensing in which each selected cell has a corresponding bit line and complement bit line for sensing.

The control of the reference current IB by the multiplexer logic circuit **110** to be between the first and second currents I1 and I2, and in particular approximately half the first current I1, facilitates accurate cell state reading largely independent of the ratio between the first and second currents I1 and I2. The cell state reading is also largely independent of the cell leakage current levels in the array because of the substantial similarity in sizing of the memory cell transistors **109** and the reference transistors **119**, and the leakage current becomes common for both the bit lines **106** and the reference bit line **117**. Another advantage of the electronic device **100** is improved memory read times, wherein differential sensing is much faster than single ended voltage or current sensing which require full voltage swings during read operations. In addition, the described examples do not need blocking architecture or segmentation of the array into multiple blocks in order to achieve faster performance. This further advantage also facilitates reduction in circuit routing complexity, thereby potentially saving one level of a multilevel interconnect routing (e.g., metallization) structure in the fabrication of the electronic device **100**. Moreover, the reference bit line **117** used for differential sensing has the same or similar electrical characteristics as the respective bit lines **106** due to matching and fabrication of the respective transistors **115** and **119** of substantially

similar sizes, which reduces local mismatch variation effects. In addition, the reference bit line 117 in certain implementations is common for multiple cell bit lines 106, resulting in avoidance or mitigation of mismatch effects compared with creating the reference outside the array where the local mismatch variation may be much larger.

Referring also to FIGS. 1B and 1C, FIG. 1B shows a programmed memory cell 104 in the ROM 102, and FIG. 1C shows an unprogrammed memory cell 104 in the ROM 102. For the program memory cell 104 in FIG. 1B, the cell transistor 109 is electrically coupled to the bit line 106 by the programming feature 105. When the selected word line 108 is asserted (e.g., at a first voltage), the selected cell transistor 109 is turned on and conducts bit line current IB at the first current I1 from the bit line 106 to the reference voltage node VSS. For the unprogrammed memory cell 104 in FIG. 1C, the cell transistor 109 is electrically disconnected from the bit line 106 (e.g., the programming feature 105 is an open circuit). In this case, when the selected word line 108 is asserted (e.g., at the first voltage), the selected cell transistor 109 is turned on but does not conduct any current from the bit line 106, and the bit line current IB represents leakage current at the second current I2, which is significantly lower than the first current I1 for a programmed cell 104.

FIG. 1D shows an example digital processing system 140 in which several aspects of the ROM apparatus and differential sensing may be implemented. The system 140 represents an example digital processing system in which the electronic device 100 may be implemented according to another aspect. The system 140 may contain one or more processors such as a central processing unit (CPU) 141, a random-access memory (RAM) 142, the electronic device 100, a graphics controller 144, a display unit 145, a network interface 146, and an input interface 147. In one example, the electronic device 100 implements a compiler ROM. The example of FIG. 1D includes the electronic device 100 as described above, having an implementation of the address decoder and read logic circuit 101 that generates word line voltage signals on the word lines 108, the ROM 102 with bit lines 106, the multiplexer logic circuit 110, the differential sense amplifier 120 and the latch 130 as described above. In one implementation, the components except the display unit 145 may communicate with each other a communication path 143, which may contain several buses, such as the address bus 103 and a data bus. The CPU 141 may execute instructions stored in the compiler ROM electronic device 100, for example, during booting-up of the system 140. The CPU 141 also executes instructions (after boot-up) stored in the RAM 142 to perform a specific task. The CPU 141 may contain multiple processing units, with each processing unit potentially being designed for a specific task. Alternatively, the CPU 141 may contain only a single processing unit. The graphics controller 144 generates and provides display signals (e.g., in RGB format) to the display unit 145 based on data/instructions received from the CPU 141. The display unit 145 contains a display screen to display the images defined by the display signals. The input interface 147 may correspond to a keyboard and/or mouse, and generally enables a user to provide inputs. The network interface 146 enables some of the inputs (and outputs) to be provided on a network. In general, the display unit 145, the input interface 147 and the network interface 146 enable a user to interface with the system 140.

Referring now to FIGS. 2-4, FIG. 2 shows a method 200 of fabricating an electronic device, and FIGS. 3 and 4 show the electronic device 100 undergoing fabrication processing according to the method 200. The method 200 includes

fabricating or otherwise forming transistors, such as the transistors 109, 112, 115, and 131-138 described above, on or in a semiconductor layer at 202. FIG. 3 shows one example, in which semiconductor processing 300 is performed that forms transistors on and/or in a semiconductor surface layer 302 above a semiconductor wafer substrate 301. As shown in the partial view of FIG. 3, the electronic device 100 includes p-channel FETs such as the transistor 131, as well as n-channel FETs 109 and 119, which in this example are of substantially similar sizes to one another (e.g., having about a same gate width).

At 204, interconnections are fabricated as part of forming a metallization structure with transistor interconnections to form a read-only memory, such as the ROM 102, the differential sense amplifier 120, and the multiplexer logic circuit 110. FIG. 4 shows one example, in which a metallization process 400 is performed that fabricates a multilevel metallization structure 402 on the semiconductor surface layer 302, including metal level structures M1, M2, M3, M4, and M5 in an example 5 level structure 402. In other implementations, different numbers of levels can be included in the metallization structure 402. The metallization structure fabrication at 204 in one example includes forming the programming features 105 in FIGS. 1 and 1A above.

The ROM 102 has the array of memory cells 104 arranged in rows along the respective word lines 108 and columns along the respective bit lines 106, the respective memory cells 104 include a cell transistor 109, and the reference column of the array has reference transistors 119 along a reference bit line 117 as illustrated and described above. In addition, the differential sense amplifier 120 has the first amplifier input 122, the second amplifier input 124, the first amplifier output 126, and the second amplifier output 128, and the differential sense amplifier 120 is configured to generate the differential output voltage signal SOUT, SOUTZ across the first and second amplifier outputs 126, 128 based on the differential input current signal of the first and second amplifier inputs 122, 124. The multiplexer logic circuit 110 is configured to selectively couple the selected one of the bit lines 106 to the first amplifier input 122 and to couple the reference bit line 117 to the second amplifier input 124.

In addition, the memory cells 104 programmed in the first state are configured to conduct the first bit line current I1 along the respective bit line 106 when selected, the memory cells 104 programmed in the second state are configured to conduct the lower second bit line current I2 along the respective bit line 106 when selected, and the multiplexer logic circuit 110 is configured to control the reference current IR of the reference bit line 117 to be between the first bit line current I1 and the second bit line current I2.

In one implementation, the method 200 includes programming the read-only memory cells 104 at 206. In another implementation, the programming at 206 is omitted, for example, to be performed by an end user. The method 200 further includes die separation and packaging at 208 to complete the electronic device 100.

In one or more implementations, as discussed above, the multiplexer logic circuit 110 is configured to control the reference current IR of the reference bit line 117 to be approximately half the first bit line current I1. In these or other implementations, the multiplexer logic circuit 110 includes the select circuit 114 with the row of bit select transistors 115 coupled between the first amplifier input 122 and the respective bit lines 106, and three reference select transistors 116 coupled in series between the second ampli-

fier input **124** and the reference bit line **117**. In these or further implementations, the bit select transistors **115** and the reference select transistors **116** are of similar size to one another (e.g., have about a same gate width). In various implementations, moreover, the cell transistors **109** and the reference transistors **119** are of similar size to one another as discussed above in connection with FIGS. 1, 1A-1, and 1A-2.

Referring now to FIGS. 5-11, FIG. 5 shows of a method **500** of reading a ROM cell, such as the memory cells **104** illustrated and described above in connection with FIGS. 1, 1A-1, and 1A-2. The method **500** includes selecting a row and column according to an address at **502**, for example, using the address decoder and read logic circuit **101** and the multiplexer logic circuit **110** as described above. In one implementation, the method further includes discharging memory array and reference column bit lines at **504**, for example, using the discharge circuit **111** in FIG. 1A-1. The method **500** continues at **506** with coupling a selected bit line **106** of the ROM **102** to the first amplifier input **122** of the differential sense amplifier **120**, as well as coupling the reference bit line **117** of the ROM **102** to the second amplifier input **124** of the differential sense amplifier **120** at **508**. At **510**, the method **500** includes controlling the reference current I_R of the reference bit line **117** to be between the first bit line current I_1 of a programmed ROM memory cell **104** and the second bit line current I_2 of an unprogrammed ROM memory cell **104**. In one implementation, the method **500** includes controlling the reference current I_R of the reference bit line **117** at **510** to be approximately half the first bit line current I_1 .

Referring now to FIGS. 6-9, FIGS. 6 and 7 show graphs of signals in the electronic device **100** during a memory read operation to read an unprogrammed memory cell, and FIGS. 8 and 9 show graphs of signals in the electronic device **100** during a memory read operation to read a programmed memory cell.

For the case of an unprogrammed selected memory cell **104**, a graph **600** in FIG. 6 includes a clock curve **601** (e.g., labeled "CLK") with a rising edge at the beginning of an example read operation, as well as a curve **602** showing the enable voltage signal ENN from the address decoder and read logic circuit **101**. The graph **600** also includes a curve **603** showing a selected bit line voltage signal BL, a curve **604** showing the reference bit line voltage signal BLREF, a curve **605** showing the left-side bit voltage signal BITL at the input of the output buffer inverter **138** in FIG. 1A-1, a curve **606** showing the right-side bit voltage signal BITR at the input of the output buffer inverter **137**, and a curve **607** that shows the output voltage signal SOUTZ at the second amplifier output **128** (FIG. 1A).

A graph **700** in FIG. 7 includes the clock curve **601** and the curve **602** showing the enable voltage signal ENN, as well as a curve **701** that shows the selected bit line current I_B that goes to approximately $-65 \mu\text{A}$ in response to the discharge circuit **111** discharging the selected bit line **106** and transitions to the second current I_2 prior to the sense amplifier being enabled by the rising edge of the ENN curve **602**. The graph **700** also has a reference bit line current curve **702** that shows the current I_R that is greater (e.g., more negative) than the second current I_2 when the amplifier is enabled by the rising edge of the ENN curve **602**. In response to the rising edge of the enable voltage signal ENN (curve **602**), the differential sense amplifier **120** detects the lower current I_2 of the selected bit line (curve **701** in FIG. 7) compared with the higher reference bit line current I_R (curve **702** in FIG. 7), and the output voltage signal SOUTZ

rises as shown by the curve **607** in FIG. 6. As a result, the output signal SOUT at the first amplifier output **126** in FIG. 1 falls (not shown in FIGS. 6 and 7). In one implementation, the address decoder and read logic circuit **101** of FIG. 1 asserts the enable voltage signal ENN (e.g., curve **602**) a predetermined time after the rising edge of the clock curve **601** to allow sufficient current differential establishment with some design margin timing. In this case, the bit line voltage BL saturates at approximately the supply voltage VDD minus a threshold voltage V_T since there is no path to the reference voltage node VSS, and the weak reference pulldown current I_R is sufficient to trip the differential sense amplifier **120**.

The differential sensing detects the alternate condition in a read operation of a programmed cell **104** as shown in FIGS. 8 and 9. For this case, a graph **800** in FIG. 8 includes a clock curve **801** (e.g., labeled "CLK") with a rising edge at the beginning of an example read operation, as well as a curve **802** showing the enable voltage signal ENN from the address decoder and read logic circuit **101**. The graph **800** also includes a curve **803** showing a selected bit line voltage signal BL, a curve **804** showing the reference bit line voltage signal BLREF, a curve **805** showing the left-side bit voltage signal BITL at the input of the output buffer inverter **138** in FIG. 1A-1, a curve **806** showing the right-side bit voltage signal BITR at the input of the output buffer inverter **137**, and a curve **808** that shows the output voltage signal SOUT at the first amplifier output **126**. A graph **900** in FIG. 9 includes the clock curve **801** and the curve **802** showing the enable voltage signal ENN, along with a curve **901** that shows the selected bit line current I_B that transitions from zero to approximately $-65 \mu\text{A}$ in response to the discharge circuit **111** discharging the selected bit line **106** and then falls to the first current I_1 prior to the sense amplifier being enabled by the rising edge of the ENN curve **802**. The graph **900** also includes a reference bit line current curve **902** that shows the current I_R that is less than the first current I_1 when the amplifier is enabled by the rising edge of the ENN curve **802**. In response to the rising edge of the enable voltage signal ENN (curve **802**), the differential sense amplifier **120** detects the higher (e.g., more negative) current I_1 of the selected bit line (curve **901** in FIG. 9) compared with the lower reference bit line current I_R (curve **902** in FIG. 9) and the output voltage signal SOUT rises as shown by the curve **808** in FIG. 8. As a result, the output signal SOUTZ at the second amplifier output **128** falls (not shown in FIGS. 8 and 9).

Referring also to FIGS. 10-12, FIG. 10 shows a graph **1000** of access time performance, including a curve **1001** showing the access time as a function of the number of words read for a single bit line voltage sensing circuit (not shown), a curve **1002** showing the access time performance for a single bit line current sensing circuit (not shown), and a curve **1003** that shows the access time performance for differential sensing in the example electronic device **100** using the differential sense amplifier **120** with the multiplexer logic circuit **110** controlling the reference bit line current I_R as described above. As shown in FIG. 10, the described examples provide a significant performance improvement in terms of reduced access time.

FIG. 11 shows a graph **1100** of capacitance and read power performance, including a curve **1102** for a single bit line current sensing circuit (not shown), and a curve **1103** that shows the reduced capacitance, and thus the reduced power consumption of the electronic device **100** having the differential sense amplifier **120** and the multiplexer logic circuit **110** with controlled reference bit line current I_R .

11

FIG. 12 shows a graph 1200 of ROM circuit area showing the significant circuit area benefits of the example electronic device 100 with the differential sense amplifier 120 and the reference current control features of the multiplexer logic circuit 110. The graph 1200 includes a curve 1201 showing the memory circuitry area for the single bit line voltage sensing implementation (not shown), a curve 1202 that shows memory circuit area for the single bit line current sensing approach (not shown), and a curve 1203 that shows the memory circuit area for the example electronic device 100 having the differential sense amplifier 120 with the multiplexer logic circuit 110 controlling the reference bit line current IR. As shown in the graph 1200, the illustrated examples provide significant benefits allowing reduced circuit area, and increased circuit and power density in the electronic device 100. Although the differential architecture of the sense amplifier 120 require some additional circuit area, the memory design does not require separation of the memory array into blocks as was needed in single bit line voltage or current sensing approaches to reduce access times, and the disclosed examples are advantageous with respect to reduced circuit area overall in addition to the access time advantages shown in FIG. 10 and the power performance advantages illustrated in FIG. 11.

Modifications are possible in the described examples, and other implementations are possible, within the scope of the claims.

What is claimed is:

1. A semiconductor device, comprising:
 - a read-only memory (ROM) having a plurality of memory cells in an array arranged in rows along respective word lines and columns along respective bit lines, a reference column of the array having reference transistors along a reference bit line, the memory cells including one of a corresponding plurality of cell transistors configured in a first state or in a second state, the cell transistors in the first state configured to conduct a first bit line current along the respective bit line when selected, the cells in the second state configured to conduct a second bit line current along the respective bit line when selected, and the first bit line current greater than the second bit line current;
 - a differential sense amplifier configured to generate a differential output voltage signal between first and second differential outputs based on first and second differential input currents at respective first and second amplifier inputs; and
 - a multiplexer logic circuit configured to selectively couple a selected one of the bit lines to the first amplifier input, couple a reference current to the second amplifier input via the reference bit line, and control the reference current to be between the first bit line current and the second bit line current.
2. The semiconductor device of claim 1, wherein the multiplexer logic circuit is configured to control the reference current of the reference bit line to be approximately half the first bit line current.
3. The semiconductor device of claim 2, wherein the multiplexer logic circuit includes a select circuit having a row of bit select transistors coupled between the first amplifier input and the respective bit lines, and a plurality of reference select transistors coupled in series between the second amplifier input and the reference bit line, the bit select transistors and the reference select transistors having about a same first gate width.

12

4. The semiconductor device of claim 3, wherein the cell transistors and the reference transistors have about a same second gate width.

5. The semiconductor device of claim 4, wherein the multiplexer logic circuit includes a discharge circuit having discharge transistors coupled to the respective bit lines, and a reference discharge transistor coupled to the reference bit line, the discharge transistors configured to discharge the bit lines during a read operation, and the reference discharge transistor configured to discharge the reference bit line during the read operation.

6. The semiconductor device of claim 2, wherein the cell transistors and the reference transistors have about a same gate width.

7. The semiconductor device of claim 1, wherein the multiplexer logic circuit includes a select circuit having a row of select transistors coupled between the first amplifier input and the respective bit lines, and a plurality of reference select transistors coupled in series between the second amplifier input and the reference bit line, the select transistors and the reference select transistors having about a same gate width.

8. The semiconductor device of claim 7, wherein the multiplexer logic circuit includes a discharge circuit having discharge transistors coupled to the respective bit lines, and a reference discharge transistor coupled to the reference bit line, the discharge transistors configured to discharge the bit lines during a read operation, and the reference discharge transistor configured to discharge the reference bit line during the read operation.

9. The semiconductor device of claim 7, wherein the gate width is a first gate width, and the cell transistors and the reference transistors have about a same second gate width.

10. The semiconductor device of claim 1, wherein the cell transistors and the reference transistors have about a same gate width.

11. The semiconductor device of claim 1, wherein the multiplexer logic circuit includes a discharge circuit having discharge transistors coupled to the respective bit lines, and a reference discharge transistor coupled to the reference bit line, the discharge transistors configured to discharge the bit lines during a read operation, and the reference discharge transistor configured to discharge the reference bit line during the read operation.

12. A method of forming a semiconductor device, the method comprising:

forming transistors in or over a semiconductor substrate; and

forming a metallization structure with transistor interconnections to form a read-only memory (ROM), a differential sense amplifier, and a multiplexer logic circuit, the ROM having a plurality of memory cells in an array arranged in rows along respective word lines and columns along respective bit lines, the memory cells including one of a corresponding plurality of cell transistors, a reference column of the array having reference transistors along a reference bit line, the differential sense amplifier configured to generate a differential output voltage signal between first and second differential outputs based on first and second differential input currents at respective first and second amplifier inputs, and the multiplexer logic circuit configured to selectively couple a selected one of the bit lines to the first amplifier input and couple the reference bit line to the second amplifier input,

wherein the cell transistors programmed in a first state conduct a first bit line current along the respective bit

13

line when selected, the cell transistors programmed in a second state conduct a second bit line current along the respective bit line when selected, the first bit line current is greater than the second bit line current, and the multiplexer logic circuit is configured to control a reference current of the reference bit line to be between the first bit line current and the second bit line current.

13. The method of claim **12**, wherein the multiplexer logic circuit is configured to control the reference current of the reference bit line to be approximately half the first bit line current.

14. The method of claim **13**, wherein the multiplexer logic circuit includes a select circuit having a row of bit select transistors coupled between the first amplifier input and the respective bit lines, and a plurality of reference select transistors coupled in series between the second amplifier input and the reference bit line, the bit select transistors and

14

the reference select transistors having about a same first gate width.

15. The method of claim **13**, wherein the cell transistors and the reference transistors have about a same gate width.

16. The method of claim **12**, wherein the multiplexer logic circuit includes a select circuit having a row of select transistors coupled between the first amplifier input and the respective bit lines, and a plurality of reference select transistors coupled in series between the second amplifier input and the reference bit line, the select transistors and the reference select transistors having about a same gate width.

17. The method of claim **16**, wherein the gate width is a first gate width, and the cell transistors and the reference transistors have about a same second gate width.

18. The method of claim **12**, wherein the cell transistors and the reference transistors have about a same gate width.

* * * * *