



US011518132B2

(12) **United States Patent**
Sager

(10) **Patent No.:** **US 11,518,132 B2**

(45) **Date of Patent:** ***Dec. 6, 2022**

(54) **BOX AND METHOD OF CONSTRUCTING THE SAME**

(71) Applicant: **DOME ZERO INC.**, Lexington, MA (US)

(72) Inventor: **Yildiray Sager**, Lexington, MA (US)

(73) Assignee: **Dome Zero Inc.**, Lexington, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/206,383**

(22) Filed: **Mar. 19, 2021**

(65) **Prior Publication Data**

US 2021/0316522 A1 Oct. 14, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/790,997, filed on Feb. 14, 2020, now Pat. No. 10,967,598, which is a (Continued)

(51) **Int. Cl.**
B65D 3/20 (2006.01)
B31C 1/08 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B31B 50/28** (2017.08); **B31B 50/20** (2017.08); **B31B 50/622** (2017.08); **B31C 1/083** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC B31B 50/28; B31B 50/20; B31B 50/622; B31C 1/083; B31C 11/04; B32B 29/005;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

726,894 A * 5/1903 Ferres F16L 9/16
138/144

1,502,864 A 7/1924 Milligan
(Continued)

FOREIGN PATENT DOCUMENTS

CN 201120970 Y 9/2008
GB 1331630 9/1973
(Continued)

OTHER PUBLICATIONS

European Examination Report Response filed Apr. 6, 2021 for European Application No. 18848687.2; 14 Pages.

(Continued)


Primary Examiner — Christopher R Demeree

(74) *Attorney, Agent, or Firm* — Daly, Crowley, Mofford & Durkee, LLP

(57) **ABSTRACT**

A box suitable for the packaging of a consumer product is formed by helically wrapping an elongated continuous strip of material around a mandrel to form a main body with a plurality of bands. In one embodiment, adjacent bands partially overlie one another to form a multi-paneled main body with an open top end and an open bottom end. An adhesive is disposed within the region of contact between adjacent bands to retain the shape of the main body. First and second sets of slots are formed in the main body to create flaps dimensioned to selectively enclose the open top and bottom ends, respectively. To define the flaps and promote pivotal articulation, the main body is also preferably provided with score lines. By adjusting the configuration of the mandrel, a customized box can be constructed that is sized to receive a consumer product with limited wasted space.

6 Claims, 12 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 16/113,114, filed on Aug. 27, 2018, now Pat. No. 10,603,862.
- (60) Provisional application No. 62/550,301, filed on Aug. 25, 2017, provisional application No. 62/550,122, filed on Aug. 25, 2017.

(51) Int. Cl.

B31C 11/04 (2006.01)
B32B 29/00 (2006.01)
B32B 29/08 (2006.01)
B65D 5/355 (2006.01)
B65D 5/08 (2006.01)
B31B 50/28 (2017.01)
B31B 50/62 (2017.01)
B31B 50/20 (2017.01)
B31B 110/35 (2017.01)
B31B 120/70 (2017.01)

(52) U.S. Cl.

CPC **B31C 11/04** (2013.01); **B32B 29/005** (2013.01); **B32B 29/08** (2013.01); **B65D 3/20** (2013.01); **B65D 5/0005** (2013.01); **B65D 5/08** (2013.01); **B31B 2110/35** (2017.08); **B31B 2120/70** (2017.08); **B32B 2439/62** (2013.01)

(58) Field of Classification Search

CPC B32B 29/08; B65D 53/20; B65D 5/005; B65D 5/08; B65D 3/266
 USPC 229/101.1, 202; 156/195, 192, 184; 220/648; 493/299
 See application file for complete search history.

(56) References Cited**U.S. PATENT DOCUMENTS**

1,975,428 A * 10/1934 John B65D 59/04 206/430
 2,016,273 A 10/1935 Atwood
 2,179,504 A 11/1939 Hasbrook
 2,262,242 A 11/1941 Lenox
 2,315,217 A 3/1943 Obiglio
 2,697,387 A 12/1954 Falconer
 3,137,437 A 6/1964 Svensson
 3,322,156 A 5/1967 Stuart
 3,380,147 A 4/1968 McDonald
 3,523,635 A 8/1970 Croley et al.
 3,861,984 A 1/1975 Poulson
 4,349,110 A 9/1982 Hayashi
 4,872,590 A 10/1989 Sasaki et al.
 5,184,996 A 2/1993 Rode et al.
 5,286,246 A 2/1994 Weder et al.
 5,393,582 A 2/1995 Wang et al.
 5,484,100 A 1/1996 Rigby
 5,495,810 A 3/1996 Yoshii
 5,566,530 A 10/1996 Johnstone et al.
 6,250,908 B1 6/2001 Foos
 6,939,424 B1 9/2005 Takala et al.
 7,971,610 B2 * 7/2011 Booth F16L 9/045 138/131
 8,870,055 B2 * 10/2014 Backman B65D 75/58 229/101.1
 9,561,929 B2 * 2/2017 Mellin B31C 1/00
 10,213,998 B2 * 2/2019 Wegmann B32B 38/1858
 10,308,392 B2 6/2019 Ogawa et al.
 2003/0106895 A1 * 6/2003 Kalal B65D 81/3893 220/9.2
 2005/0236463 A1 10/2005 Boldrini et al.
 2007/0235100 A1 10/2007 Tomerlin et al.
 2008/0236765 A1 10/2008 Sager
 2009/0320999 A1 12/2009 Sekar et al.

2010/0121312 A1 5/2010 Gielenz et al.
 2011/0067775 A1 3/2011 Simonsohn
 2015/0115022 A1 4/2015 Iwegbu
 2015/0336325 A1 11/2015 Glasberg et al.
 2016/0039551 A1 2/2016 Aganovic et al.
 2016/0060014 A1 3/2016 Timmers et al.
 2017/0112028 A1 4/2017 Millman et al.

FOREIGN PATENT DOCUMENTS

GB 1347244 2/1974
 JP S55 104621 U 7/1980

OTHER PUBLICATIONS

Non-Final Office Action for U.S. Appl. No. 16/113,114, dated Jun. 11, 2019, 6 pages.
 Response to Office Action dated Jun. 11, 2019 for U.S. Appl. No. 16/113,114; Response filed Sep. 10, 2019, 10 pages.
 Final Office Action for U.S. Appl. No. 16/113,114, dated Oct. 1, 2019, 8 pages.
 Supplemental Response to Final Office Action for Pilot Program for U.S. Appl. No. 16/113,114, dated Dec. 5, 2019, 13 pages.
 Response to Final Office Action dated Oct. 1, 2019 for U.S. Appl. No. 16/113,114; Response filed Dec. 1, 2019; 13 Pages.
 RCE and Second Supplemental Response to Advisory Action for U.S. Appl. No. 16/113,114, dated Jan. 2, 2020, 12 pages.
 Notification of Transmittal to the International Search Report and Written Opinion of the ISA, International Search Report and Written Opinion dated Dec. 21, 2018 for International Application No. PCT/US2018/048153, 10 pages.
 Notification of Transmittal to the International Search Report and Written Opinion of the ISA, International Search Report and Written Opinion dated Oct. 18, 2018 for International Application No. PCT/US2018/048082, 10 pages.
 Notification Concerning Transmittal of the International Preliminary Report on Patentability (Chapter I of the Patent Cooperation Treaty) dated Mar. 5, 2020 for International Application No. PCT/US2018/048153, 7 pages.
 Notification Concerning Transmittal of the International Preliminary Report on Patentability (Chapter I of the Patent Cooperation Treaty) dated Mar. 5, 2020 for International Application No. PCT/US2018/048082, 2 pages.
 Non-Final Office Action for U.S. Appl. No. 16/113,586, dated Jun. 11, 2020, 17 pages.
 European Search Report, dated Jul. 1, 2020 for International Application No. 18848687.2, 8 pages.
 Response to Search Opinion filed on Nov. 18, 2020 for European Application No. 18848687.2; 18 pages.
 Non-Final Office Action dated Sep. 1, 2020 for U.S. Appl. No. 16/790,997; 12 Pages.
 Preliminary Amendment dated Feb. 14, 2020 for U.S. Appl. No. 16/790,997; 7 Pages.
 Response to Office Action dated Sep. 1, 2020 for U.S. Appl. No. 16/790,997; Response filed on Nov. 30, 2020; 14 Pages.
 U.S. Final Office Action dated Dec. 9, 2020 for U.S. Appl. No. 16/790,997; 5 Pages.
 Response to Final Office Action dated Dec. 9, 2020 for U.S. Appl. No. 16/790,997; Response filed on Jan. 19, 2021; 5 Pages.
 Notice of Allowance dated Feb. 2, 2021 for U.S. Appl. No. 16/790,997; 6 Pages.
 Advisory Action dated Dec. 13, 2019 for U.S. Appl. No. 16/113,114; 7 Pages.
 Notice of Allowance dated Jan. 24, 2020 for U.S. Appl. No. 16/113,114; 7 Pages.
 Response to Non-Final Office Action dated Jun. 11, 2020 for U.S. Appl. No. 16/113,586; Response filed Jul. 31, 2020; 7 Pages.
 Notice of Allowance dated Aug. 26, 2020 for U.S. Appl. No. 16/113,586; 10 Pages.
 European Examination Report dated Mar. 23, 2021 for European Application No. 18848687.2; 4 Pages.

(56)

References Cited

OTHER PUBLICATIONS

Response to Examination Report dated Mar. 23, 2021 for European Application No. 18848687.2; Response filed on Apr. 6, 2021; 2 Pages.

Exam Report dated Aug. 12, 2021 for European Application No. 18848687.2; 5 pages.

Response to Communication dated Aug. 12, 2021 filed on Jan. 12, 2022 for European Application No. 18848687.2; 20 pages.

* cited by examiner




Fig. 1(a)




Fig. 1(b)




Fig. 2(a)




Fig. 2(b)

Fig. 3




Fig. 4




Fig. 5




Fig. 6(b)

Fig. 6(a)




Fig. 7




Fig. 8(a)







Fig. 8(b)

Fig. 9






Fig. 12(a)

Fig. 12(b)




Fig. 13




Fig. 14(a)





Fig. 14(b)




Fig. 15




Fig. 16(a)




Fig. 16(b)




Fig. 16(c)




Fig. 16(d)




Fig. 16(e)




Fig. 16(f)

1

BOX AND METHOD OF CONSTRUCTING THE SAME

FIELD OF THE INVENTION

The present invention relates generally to the packaging and shipment of consumer products and, more particularly, to boxes used in the packaging and shipment of consumer products.

BACKGROUND OF THE INVENTION

The proliferation of e-commerce has created a commensurate increase in need for packaging solutions that are appropriate in the shipment of consumer products. Nonetheless, despite the growing demand for effective shipment packaging, online purchase fulfillment remains most commonly processed using single-use, fixed-size boxes.

E-commerce shipment boxes are most commonly constructed from a preformed, unitary blank that is constructed of a rigid, durable and inexpensive material, such as cardboard or plastic. The blank is shaped to define a plurality of panels that are typically separated by areas of weakness, such as fold lines. Accordingly, as part of the assembly process, the blank is folded about the fold lines to erect the box, with the shape secured through the use of interlocking panels and/or an adhesive.

Although well-known and widely used in the art, boxes formed from a preformed blank, as described above, suffer from a notable drawback. Notably, boxes formed from a preformed blank are fixed in size and thereby incapable of dimensional variability. However, due to the near limitless variety of different products currently available online, packaging requirements can vary considerably depending upon the size and shape of the items ultimately shipped to the purchaser.

As a result, online businesses and e-commerce fulfillment centers often maintain a comprehensive inventory of differently dimensioned boxes. Yet, it has been found that online purchase fulfillment remains largely incapable of packaging and shipping products within an appropriately-sized box. Rather, current studies have indicated online purchases are most commonly packaged in an inefficient fashion, with the average e-commerce package containing approximately 40% of empty, or void, space.

The aforementioned inefficiency in the packaging of products ordered online has been found to create a number of notable shortcomings.

As a first shortcoming, the use of a container that is considerably larger than the products packaged therein results in a corresponding increase in packaging costs. In particular, a greater amount of material is required to form the box itself, with the amount of excess packaging material often exceeding 15% of the amount of corresponding material required to construct an ideally-sized package. Additionally, a substantial amount of package filler is typically needed to fill in the empty space within a conventional e-commerce box to prevent product movement and potential damage during shipment, with the amount of excess package filler often exceeding 60% of the amount of corresponding package filler needed in an ideally-sized package.

As a second shortcoming, the use of a container that is considerably larger than the products packaged therein results in a corresponding increase in transportation costs. Notably, storage and delivery costs are typically directly proportional to the size and/or weight of a shipped item. Therefore, an unnecessarily oversized package creates trans-

2

portation inefficiencies (i.e. increased weight and smaller payloads) for couriers that are, in turn, often financially borne by the consumer. In fact, it has been found that the transportation cost associated with traditional, inefficiently-sized, e-commerce packages often exceeds 20% of the corresponding transportation cost for an ideally-sized package.

SUMMARY OF THE INVENTION

It is an object of the invention to provide a new and improved box for use in the packaging and shipment of consumer products.

It is another object of the present invention to provide a box as described above that can be modified dimensionally to receive consumer products with limited wasted space.

It is yet another object of the present invention to provide a box as described above that has a limited number of parts, is inexpensive to manufacture and is easy to use.

Accordingly, as a feature of the invention, there is provided a box, comprising (a) a continuous strip wound in a helical configuration so as to define a main body with a plurality of bands, (b) wherein adjacent bands are coupled together to render the main body unitary in construction.

As another feature of the invention, there is provided a method of constructing a box, the method comprising the steps of (a) winding a continuous strip in a helical configuration so as to define a main body with a plurality of bands, and (b) coupling together adjacent bands to secure the shape of the main body.

Various other features and advantages will appear from the description to follow. In the description, reference is made to the accompanying drawings which form a part thereof, and in which is shown by way of illustration, an embodiment for practicing the invention. The embodiment will be described in sufficient detail to enable those skilled in the art to practice the invention, and it is to be understood that other embodiments may be utilized and that structural changes may be made without departing from the scope of the invention. The following detailed description is therefore, not to be taken in a limiting sense, and the scope of the present invention is best defined by the appended claims.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, wherein like reference numerals represent like parts;

FIG. 1(a) is a top perspective view of a first embodiment of a box constructed according to the teachings of the present invention, the box being shown with its top and bottom flaps positioned open;

FIG. 1(b) is an enlarged, fragmentary, perspective view of the box shown in FIG. 1(a), taken within circled region A to more closely illustrate one of the vertical slots in the box body;

FIGS. 2(a) and 2(b) are front plan and left side views, respectively, of the box shown in FIG. 1(a) at an intermediary stage of its construction, the box being shown with a limited selection of its partially overlapping bands for ease of illustration;

FIG. 3 is an enlarged, fragmentary, left end view of the box shown in FIG. 2(b), taken within circled region B to more closely illustrate the helical arrangement between adjacent bands of the box body;

FIG. 4 is top perspective view an adjustable size-mandrel that is designed to facilitate construction of the box shown in FIG. 1;

FIG. 5 is a top perspective view of the box shown in FIG. 1 at an intermediary stage of its construction;

FIGS. 6(a) and 6(b) are front plan and right-side views, respectively, of the box shown in FIG. 1, the box being shown with score lines to more closely illustrate the pivotability of top and bottom flaps;

FIG. 7 is an enlarged, fragmentary, front plan view of the box shown in FIG. 6(a), taken within circled region C to more closely illustrate the details of one of the score lines;

FIGS. 8(a) and 8(b) are front plan and left side views, respectively, of a second embodiment of a box constructed according to the teachings of the present invention, the box being shown at an intermediary stage of its construction for ease of illustration;

FIG. 9 is an enlarged, fragmentary, left end view of the box shown in FIG. 8(b), taken within circled region D to more closely illustrate the alternative means for securing adjacent bands of the box body;

FIGS. 10(a) and 10(b) are front plan and left side views, respectively, of a third embodiment of a box constructed according to the teachings of the present invention, the box being shown at an intermediary stage of its construction for ease of illustration;

FIG. 11 is an enlarged, fragmentary, left end view of the box shown in FIG. 10(b), taken within circled region E to more closely illustrate an alternative interface between adjacent bands of the box body;

FIGS. 12(a) and 12(b) are front plan and left side views, respectively, of a fourth embodiment of a box constructed according to the teachings of the present invention, the box being shown at an intermediary stage of its construction for ease of illustration;

FIG. 13 is an enlarged, fragmentary, left end view of the box shown in FIG. 12(b), taken within circled region F to more closely illustrate an alternative, interlocking-type interface between adjacent bands of the box body;

FIGS. 14(a)-(c) are rear perspective, rear plan, and left end views, respectively, of a strip of material constructed according to the teachings of the present invention, the strip of material being particularly well suited for use in constructing a box through a helical winding process;

FIG. 15 is a left end, section view of a box panel formed using the strip of material shown in FIG. 14(a), wherein adjacent bands are shown slightly spaced apart for ease of illustration; and

FIGS. 16(a)-(f) are a series of top, right side, perspective views of the box body shown in FIG. 5 at various stages of enclosing its open top using a creasing technique to form a set of top panels.

DETAILED DESCRIPTION OF THE INVENTION

Box 11

Referring now to FIG. 1(a), there is shown a first embodiment of a box constructed according to the teachings of the present invention, the box being defined generally by reference numeral 11. As will be explained in detail below, box 11 is uniquely designed to allow for dimensional variability during its construction and thereby receive a wide variety of different consumer products with limited wasted space, which is a principal object of the present invention. In this manner, the size and shape of box 11 can essentially be customized for the particular consumer products to be retained therein.

As defined herein, the term “box” denotes any enclosable packaging that is appropriately configured to store and transport one or more consumer products without any restriction to shape, size or material. For instance, use of the term “box” herein is not restricted to a container in the shape of a polyhedron (i.e. formed with multiple planar faces), but rather encompasses all conceivable packaging configurations, such as tubular packaging boxes and envelope-type shipping containers.

Box 11 comprises an elongated, continuous strip 13 that is constructed of a rigid and durable material suitable for use in packaging applications, such as a heavy-duty, paper-based, packaging material (e.g. cardboard) or plastic. Notably, strip 13 may be formed using a corrugated cardboard material to provide box 11 with an adequate degree of structural integrity and strength, as will be explained further in detail below.

Strip 13 is wound counterclockwise in a helical configuration to form a unitary box, or main body 15, with a plurality of individual bands, or turns, 17. In the present embodiment, box body 15 is represented as comprising eight separate bands 17-1 thru 17-8. However, as will be explained in detail below, the number of turns 17 is selected based upon the desired height of box 11 (i.e. to fittingly receive the intended product to be packaged) and, as such, is intended to be modified to suit the particular needs of the intended application.

As defined herein, the term “helical” denotes that strip 13 is wrapped about a common central axis, in either a clockwise or counterclockwise direction, to form three-dimensional box body 15. The resultant box body 15 achieved from the helical wrapping of strip 13 can therefore include regions that are flattened and/or curved in any representation.

In the present embodiment, box body 15 is a four-sided member comprising a front panel 19-1, a rear panel 19-2, a first side panel 19-3 and a second side panel 19-4 that together define an interior cavity 21 that can be accessed through an open top end 23 and/or an open bottom end 25. As will be explained further below, box body 15 is slotted and scored so as to define a set of top flaps 27 configured to selectively enclose open top end 23 and a set of bottom flaps 29 configured to selectively enclose open bottom end 25.

Referring now to FIGS. 2(a) and 2(b), strip 13 comprises a flattened front surface 31, a flattened rear surface 33, a narrow top edge 35 and a narrow bottom edge 37. As shown herein, strip 13 is preferably of uniform thickness along the majority of its length. However, as will be explained further below, the leading and trail ends of strip 13 are preferably cut, or otherwise tapered, to render both (i) the distal edge of all top flaps 27 generally coplanar, and (ii) the distal edge of all bottom flaps 29 generally coplanar.

As seen most clearly in FIG. 3, each successive, or adjacent, band 17 partially overlies its predecessor. For instance, as shown herein, band 17-4 partially overlies band 17-3, with rear surface 33 of band 17-4 along its bottom edge 37 in contact with front surface 31 of band 17-3 along its top edge 35. In this manner, further helical winding of strip 13 can be performed, as needed, to construct box 11 at the desired height.

It should be noted that both the width of strip 13 as well as the degree of overlap between successive bands 17 can be modified, as needed, to attain the panel strength and visual appearance required for the designated application.

As shown, an adhesive 41 is preferably disposed within the region of contact between adjacent bands 17 of box body

5

15. In this manner, the adhesive bond established between adjacent bands 17 fixedly secures box body 15 in the desired shape.

In the present embodiment, adhesive 41 is preferably in the form of a quick-dry adhesive that is applied as a thin continuous strip onto front surface 31 along top edge 35 during the strip dispensing process, as seen most clearly in FIGS. 2(a) and 2(b). However, it is to be understood that adhesive 41 represents any type bonding substance that can be used to facilitate construction of box 11. For instance, adhesive 41 may alternatively be in the form of a pressure-sensitive adhesive that is coated onto front surface 31 of strip 13 along top edge 35 at the time of its manufacture. In this scenario, adhesive 41 would only activate when adjacent bands 17 are drawn into contact with one another under sufficient pressure (e.g. during the helical winding process). As another example, adhesive 41 may be in the form of a water-activated adhesive.

Method of Constructing Box 11

Due to its unique method of construction, box 11 can be customized in configuration to receive a wide variety of different consumer products with limited wasted space. The preferred sequence of steps in the process of constructing box 11 is set forth in detail below.

Specifically, as the first step in the process of constructing box 11, a supply of material strip 13 is provided. As referenced above, strip 13 is preferably constructed out of any heavy-duty material that is suitable for use in the packaging of consumer products. To facilitate dispensing and minimize storage requirements, material strip 13 is preferably supplied in the form of a relatively compact reel (not shown).

Next, a mandrel, or form, is utilized to define the basic geometric configuration of the box to be constructed. Referring now to FIG. 4, a size-adjustable mandrel 51 is shown that includes a plurality of vertical posts, or towers, 53 that define the general footprint of the desired box 11 (i.e. towers 53 define the location of the inner corners of box 11). Preferably, each post 53 is capable of being individually displaced relative to the remaining posts 53 in multiple directions to create a virtually boundless variety of potential box configurations.

However, it should be noted that the box construction process of the present invention is not limited to size-adjustable mandrel 51. Rather, the box construction process of the present invention could be implemented using any type of mandrel, whether fixed in size or reconfigurable, without departing from the spirit of the present invention. Accordingly, it is to be understood, that size-adjustable mandrel 51 is provided herein for illustrative purposes only and any reference herein is strictly to assist in the understanding of the novel box construction process.

To commence the box forming process, strip 13 is wound around mandrel 51 in a helical configuration, as shown in FIG. 4, to create box body 15 with bands 17. As referenced previously, quick-dry adhesive 41 is preferably applied to front surface 31 of strip 13 along top edge 35 immediately prior to the helical winding process (e.g. after initial dispensing from a reel) to secure the shape of main body 15.

In the present embodiment, successive bands 17 are disposed to overlie one another through a region of contact, with successive bands 17 being bonded together by adhesive 41 disposed therebetween. However, as will be explained further in detail below, adjacent bands 17 could be alternatively arranged (i.e. in a non-overlapping fashion) without

6

departing from the spirit of the present invention. Additionally, it should be briefly noted that alternative and/or supplemental means for securing adjacent bands 17 could be implemented to fix the shape of box body 15, as will be explained further in detail below.

Once box body 15 is of a height suitable for the consumer products to be packaged therein (while compensating for the width of top and bottom flaps 27 and 29 to be subsequently formed therefrom), strip 13 is cut from the remainder of its supply reel. Thereafter, leading end 13-1 and trail end 13-2 are preferably trimmed (i.e. tapered in width) to form a narrow wedge-like tip, as seen most clearly in FIG. 5. In this manner, each of open top end 23 and open bottom end 25 of box body 15 is rendered generally coplanar, the benefit of which will become apparent below.

With box body 15 formed in the manner set forth above, vertical slots are formed in box body 15 to create flaps for selectively enclosing open top end 23 and open bottom end 25. Specifically, referring back to FIGS. 1(a) and 1(b), a first set of vertical slots 61-1 is formed in open top end 23 of box body 15 at the juncture, or corner, of adjacent panels 19. Similarly, a second set of vertical slots 61-2 is formed in open bottom end 23 of box body 15 at the juncture, or corner, of adjacent panels 19.

In this manner, box 11 is constructed to include front panel 19-1, rear panel 19-2, first side panel 19-3 and second side panel 19-4 which together define an interior cavity 21 that is accessible through either open top end 23 or open bottom end 25. Additionally, box 11 includes set of pivotable top flaps 27-1 thru 27-4 which are dimensioned to selectively enclose open top end 23 and set of pivotable bottom flaps 29-1 thru 29-4 which are dimensioned to selectively enclose bottom end 25, the entire set of flaps 27 and 29 being illustrated in FIGS. 6(a) and 6(b).

As seen most clearly in FIG. 1(b), each slot 61 is of a fixed depth D that is suitable for creating appropriately dimensioned flaps 27 and 29. Also, each slot 61 is preferably of a width W that prevents interference between adjacent top and bottom flaps 27 and 29, while, at the same time, ensures adequate enclosure of open top and bottom ends 23 and 25 when pivoted closed.

Referring now to FIGS. 6(a), 6(b) and 7, a horizontal notch 63, generally C-shaped in lateral cross-section, is formed in the exterior of box body 15 as a line separating, or defining, the proximal edge of each of flaps 27 and 29 from its adjacent panel 19 (i.e. linearly between the terminal ends of adjacent upper and lower slots 61). As such, each linear notch, or score line, 63 creates a region of weakness which facilitates folding of flaps 27 and 29.

In the present embodiment, box 11 is represented as a regular slotted container, or RSC, wherein (i) top flaps 27-1 thru 27-4 are of the same size and shape as bottom flaps 29-1 thru 29-4, respectively, and (ii) each pair of outer lengthwise flaps (i.e. top flap pair 27-1 and 27-3 as well as bottom flap pair 29-1 and 29-3) are one-half of the width of box 11 and thereby align in abutment at the center of its corresponding box opening. However, it is to be understood that box 11 is not limited to any particular flap style. Rather, box body 15 could be cut and scored to define alternative flap styles without departing from the spirit of the present invention.

Upon completion of the aforementioned slotting and scoring processes, the outer dimensions, or footprint, of mandrel 51 is temporarily contracted to the extent necessary that box 11 can be easily removed therefrom. Thereafter, to package the desired products within box 11, bottom flaps 29 are first pivoted closed and are, in turn, secured together using a suitable adhesive, such as tape. The desired product

is then deposited within interior cavity **21** through open top end **23**. Due to the customized sizing of box **11**, interior cavity **21** is dimensioned to fittingly receive the product with minimal excess space. Afterwards, top flaps **27** are pivoted closed and secured together with a suitable adhesive material, thereby completing the customized packaging of the designated product.

Alternate Embodiments and Design Modifications

The invention described in detail above is intended to be merely exemplary and those skilled in the art shall be able to make numerous variations and modifications to it without departing from the spirit of the present invention. All such variations and modifications are intended to be within the scope of the present invention as defined in the appended claims.

For instance, it should be noted that box **11** is not limited to the use of an adhesive **41** disposed between overlapped regions of adjacent bands **17** to secure the shape of box body **15**. Rather, supplemental or replacement means for securing the shape of box body **15** could be implemented without departing from the spirit of the present invention.

Notably, referring now to FIGS. **8(a)**, **8(b)**, and **9**, there is shown a second embodiment of a box constructed according to the teachings of the present invention, the box being identified generally by reference numeral **111**. As can be seen, box **111** is similar to box **11** in that box **111** comprises a material strip **113** that is wound in a helical configuration to form a box body **115** with partially overlapping bands **117-1** thru **117-4**. However, box **111** differs from box **11** in that, in place of adhesive **41**, the shape of box body **115** is secured using externally applied lengths of tape **119**. For instance, as seen most clearly in FIG. **9**, first and second lengths of tape **119-1** and **119-2** are applied to the interior and exterior panel surfaces, respectively, of box body **115** over adjacent bands **117-3** and **117-4**. As can be appreciated, tape **119** not only helps secure the shape of box body **115** but also provides the added benefit of smoothing out the interior and exterior panel surfaces of box body **115** (i.e. creating a smoothened surface across the overlapped region of successive bands **117**).

Furthermore, in lieu of an adhesive, alternative means for securing together adjacent bands **117** of box body **115** could be achieved without departing from the spirit of the present invention. For example, if strip **113** is formed using a plastic material, localized ultrasonic welding may be applied within the region of contact between adjacent bands **117** to create a permanent bond therebetween.

Additionally, it should be noted that box **11** need not be constructed with successive bands **17** arranged in a partially overlapping configuration. Rather, the interface between adjacent bands **17** of box body **15** could be modified without departing from the spirit of the present invention.

For example, referring now to FIGS. **10(a)**, **10(b)** and **11**, there is shown a third embodiment of a box constructed according to the teachings of the present invention, the box being identified generally by reference numeral **211**. As can be seen, box **211** is similar to box **111** in that box **211** comprises a material strip **213** that is wound in a helical configuration to form a box body **215** with a plurality of bands **217-1** thru **217-4**. However, box **211** differs from box **111** in the nature of the interface, or contact region, between adjacent bands **217**.

Specifically, in lieu of a partially overlapping interface between adjacent bands, box body **215** is formed by disposing each successive band **217** in direct vertical alignment

with its predecessor to create a substantially planar, panel wall surface, as shown in FIG. **10(b)**. In other words, as seen most clearly in FIG. **11**, bottom edge **219** of band **217-4** is disposed in direct contact against top edge **221** of previous band **217-3** such that interior surface **223** and exterior surface **225** of all bands **217** within a panel of box body **215** lie generally flush with one another (i.e. in coplanar alignment). Arranged as such, first and second bands of tape **229-1** and **229-2** are preferably applied to the interior surface **223** and exterior surface **225**, respectively, of box body **215** across adjacent bands **217** to secure the shape of box body **215**.

It should be noted that material strip **213** may be modified to ensure proper alignment between adjacent bands **217** which are vertically aligned in the manner set forth in FIGS. **10(a)**, **10(b)** and **11**. Notably, referring now to FIGS. **12(a)**, **12(b)** and **13**, there is shown a fourth embodiment of a box constructed according to the teachings of the present invention, the box being identified generally by reference numeral **311**. As can be seen, box **311** is similar to box **211** in that box **311** comprises a material strip **313** that is wound in a helical configuration to form a box body **315** with a plurality of bands **317-1** thru **317-4**, whereby each successive band **317** is positioned in direct vertical alignment with its predecessor to create a substantially planar wall surface, as shown in FIG. **12(b)**. However, box **311** differs from box **211** in that material strip **313** is modified to create a unique mating, or interlocking, relationship within the region of contact between successive bands **317**.

Specifically, as seen most clearly in FIG. **13**, material strip **313** includes a bottom edge **319** and a top edge **321** with complementary stepped surfaces. Accordingly, during formation of box **311**, bottom edge **319** of each band **317** matingly engages top edge **321** of its predecessor. Once arranged as such, first and second bands of tape **329-1** and **329-2** are preferably applied to the interior surface **323** and exterior surface **325**, respectively, of box body **315** across adjacent bands **317** to secure the shape of box body **315**.

As can be appreciated, the unique, interlocking mating relationship between top edge **321** of a first band **317** (e.g. band **317-3**) and bottom edge **319** of the next successive band (e.g. band **317-4**) ensures proper alignment between adjacent bands **317**, thereby resulting in a flush, or coplanar, interior panel surface **323** as well as a flush, or coplanar, exterior panel surface **325**. Additionally, the interlocking relationship between top edge **321** of a first band **317** and bottom edge **319** of the next successive band serves to increase the connective strength between adjacent bands **317** as compared to previous embodiments.

It should be noted that a corrugated version of material strip **313** could be implemented to provide box body **313** with adequate strength and rigidity for conventional shipping applications. For instance, referring now to FIGS. **14(a)-(c)**, there is shown a corrugated material strip **413** that is particularly well-suited for use in forming box body **313**.

Specifically, material strip **413** comprises first and second linerboards **415-1** and **415-2** between which is disposed a corrugated layer **417**. As will be explained further in detail below, each of linerboards **415** extends beyond an opposing edge of corrugated layer **417** to create an extension, or lip, that overlies the seam between adjacent layers of strip **413** when wound in a helical configuration.

Each of linerboards **415** is preferably constructed from a generally planar sheet of paper-based material. As such, first linerboard **415-1** comprises a top edge **419-1**, a bottom edge **421-1**, a front surface **423-1** and a rear surface **425-1**.

Similarly, second linerboard **415-2** comprises a top edge **419-2**, a bottom edge **421-2**, a front surface **423-2** and a rear surface **425-2**.

Corrugated layer **417** is constructed from a sheet of fluted material that affords strip **413** with the necessary rigidity and durability for routine packaging applications. Corrugated layer **417** comprises a top edge **427**, a bottom edge **429**, a front surface **431** and a rear surface **433**. As seen most clearly in FIG. **14(c)**, corrugated layer **417** is sandwiched directly between first and second linerboards **415-1** and **415-2** and is permanently secured thereto with a suitable adhesive (not shown) to render material strip **413** a unitary item.

As a feature of the present invention, top edge **419-1** of first linerboard **415-1** extends beyond top edge **427** of corrugated layer **417**. Similarly, bottom edge **421-2** of second linerboard **415-2** extends beyond bottom edge **429** of corrugated layer **417**. At the same time, bottom edge **421-1** of first linerboard **415-1** lies generally flush with bottom edge **429** of corrugated layer **417** and top edge **419-2** of second linerboard **415-2** lies generally flush with top edge **427** of corrugated layer **417**.

As a result, top edge **419-1** of first linerboard **415-1** and bottom edge **421-2** of second linerboard **415-2** form extensions that allow for a near seamless vertical abutment of successive bands when material strip **413** is wound in a helical configuration. In particular, as shown in FIG. **15**, with strip **413** helically wrapped as a plurality of vertically aligned bands, top edge **419-1** of linerboard **415-1** for a first band of material **413-1** overlies the seam, or junction, between a second band of material **413-2** disposed in direct vertical alignment therewith. Additionally, bottom edge **421-2** of linerboard **415-2** for second band of material **413-2** overlies the seam with first band of material **413-1** upon the opposing surface. As such, the junction between bands **413-1** and **413-2** is rendered clean and seamless.

It should be noted that strip **413** is not limited to a construction with a single corrugated layer. Rather, it is to be understood that strip **413** could incorporate additional corrugated layers, each disposed directly between an adjacent pair of linerboards, without departing from the spirit of the present invention. However, it should be noted that in each implementation with multiple corrugated walls, the outermost linerboards preferably include opposing, offset extensions to allow for seamless vertical abutment of successive bands when the material strip is wound in a helical configuration.

Lastly, it should be noted that the present invention is not limited to the use of vertical slots **61** to define top and bottom sets of flaps **27** and **29** in box body **15**. Rather, alternative means for forming top and bottom flaps **27** and **29** in box body **15** could be implemented without departing from the spirit of the present invention. For instance, a series of creases could be incorporated into box body **15** to create

areas of weakness through which box body **15** can be folded to create flaps capable of enclosing open top end **23** and/or an open bottom end **25**.

More specifically, as shown in FIG. **16(a)**, a series of contiguous, horizontal, linear creases **511-1** can be formed in each panel **19** of box body **15** to create a set of top flaps **527-1** thru **527-4** which are designed to selectively enclose open top end **23**. Additionally, a pair of diagonal creases **511-2** is formed in opposing side flaps **527-3** and **527-4**. As seen most clearly in FIGS. **16(b)-(d)**, creases **511-2** enable small flaps **527-3** and **527-4** to fold inward, or collapse. In this capacity, long flaps **527-1** and **527-2** are able to pivot inward. As seen most clearly in FIGS. **16(e)** and **16(f)**, long flaps **527-1** and **527-2** are suitably dimensioned to enclose open top end **23** of box body **15**.

For ease of illustration only, the creasing technique described in detail above is applied to box body **15** to enclose open top end **23**. However, it is to be understood that a similar creasing technique could be applied to box body **15** to enclose open bottom end **25** without departing from the spirit of the present invention.

What is claimed is:

1. A box, comprising:

a continuous strip wound in a helical configuration so as to define a main body and a plurality of flaps, the main body including a plurality of bands, and each of the plurality of flaps including at least a portion of a band; wherein adjacent bands are coupled together to render the main body unitary in construction and a trailing end of the strip is trimmed at an angle, so as to render a distal edge of the plurality of flaps coplanar, the trailing end being part of at least one of the plurality of flaps.

2. The box of claim 1, wherein the main body includes at least one notch or score formed on an exterior surface of the main body, the at least one notch or score being arranged to create a region of weakness that facilitates a folding of one or more of the plurality of flaps, the at least one notch or score being formed over at least two adjacent bands that are coupled together.

3. The box of claim 1, wherein the continuous strip comprises a layer of corrugated material that is disposed between a first layer of material and a second layer of material.

4. The box of claim 3, wherein the first layer of material is arranged to form a lip that overlies a seam of adjacent ones of the plurality of bands when the continuous strip is wound in the helical configuration so as to define the main body.

5. The box of claim 3, wherein adjacent bands of the main body are in contact with one another and engage with one another through a mating interface.

6. The box of claim 5, wherein adjacent bands of the main body are partially overlapping.

* * * * *