



US 20080246536A1

(19) **United States**

## **(12) Patent Application Publication**

Chang et al.

(10) Pub. No.: US 2008/0246536 A1

(43) **Pub. Date:**

Oct. 9, 2008

(54) **TWO-PHASE CHARGE PUMP CIRCUIT  
WITHOUT BODY EFFECT**

(75) Inventors: **Wu-Chang Chang**, Hsinchu Hsien (TW); **Yin-Chang Chen**, Hsinchu Hsien (TW)

Correspondence Address:  
**BACON & THOMAS, PLLC**  
**625 SLATERS LANE, FOURTH FLOOR**  
**ALEXANDRIA, VA 22314-1176 (US)**

(73) Assignee: **EMEMORY TECHNOLOGY INC., HSINCHU (TW)**

(21) Appl. No.: 11/730,955

(22) Filed: **Apr. 5, 2007**


## Publication Classification

(51) **Int. Cl.**  
**G05F 3/02** (2006.01)

(52) U.S. Cl. .... 327/537

(57) **ABSTRACT**

A two-phase charge pump circuit without the body effect includes a voltage boost stage, an input stage connected to the voltage boost stage, and a high-voltage generator connected to the input stage. Each of the circuits can consist of NMOS or PMOS transistors. The body of each NMOS transistor is connected to an NMOS switch. The body of each PMOS transistor is connected to a PMOS switch. By providing an appropriate driving signal to each NMOS or PMOS switch, the body of each NMOS transistor can be switched to a lower voltage level and the body of each PMOS transistor is switched to a higher voltage level. This can prevent the body effect from occurring.






FIG. 1




FIG.2




FIG.3




FIG.4




FIG. 5




FIG. 6




FIG.7




FIG. 8




FIG.9  
PRIOR ART




FIG.10  
PRIOR ART

## TWO-PHASE CHARGE PUMP CIRCUIT WITHOUT BODY EFFECT

### BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The invention relates to a two-phase charge pump circuit and, in particular, to the one in which the body of each NMOS or PMOS is independently connected to a switch in order to switch to a relative low or high voltage level at an appropriate time, preventing the body effect from occurring.

[0003] 2. Description of Related Art

[0004] To reduce energy consumption, the power specification of integrated circuits (IC) is re-designed to work under a lower voltage level. For example, the IC power specification was 5 volts before. It is now reduced to 3.3 volts or even lower than 2 volts. Although using a lower voltage to supply power can reduce the energy consumption, there are still situations where larger voltages are needed. Take the flash memory as an example. It requires a larger negative voltage for erasing. The larger voltage is supplied by a charge pump circuit. Aside from outputting a negative voltage, there are also charge pump circuits that can output high-level positive voltages.

[0005] With reference to FIG. 9, U.S. Pat. No. 6,384,669 discloses a charge pump circuit consisted of NMOS transistors. The driving signal of each NMOS transistor in the circuit is given in FIG. 10. The structure of the charge pump circuit is symmetric between upper and lower portions. In this circuit, the body of each NMOS transistor is connected to the ground without any other further processing. Therefore, each NMOS transistor has an obvious body effect. Due to the existence of the body effect, a voltage to make each NMOS transistor conductive has to be even higher. Therefore, one has to take into account the voltage tolerance of the transistors.

### SUMMARY OF THE INVENTION

[0006] Existing charge pump circuits cannot have effective controls over the body of each NMOS or PMOS transistor. Therefore, the body of each transistor still has the body effect. The invention solves this problem.

[0007] An objective of the invention is to provide a two-phase charge pump circuit without the body effect. The body of the NMOS transistor automatically switches to a lower voltage level, while the body of the PMOS transistor automatically switches to a higher voltage level. Therefore, the invention can prevent the body effect from occurring. To achieve the above objective, the charge pump circuit receives a set of first input signal and second input signal with opposite phases.

[0008] The charge pump circuit includes: a first voltage boost stage, a second voltage boost stage, an input stage, and a high-voltage generator.

[0009] The first voltage boost stage includes a first PMOS charge transistor that has a body, a gate, a first terminal, and a second terminal. The body is connected to two switches. The first terminal and the second terminal thereof are connected to a first control node and an input node, respectively.

[0010] The second voltage boost stage includes a second PMOS charge transistor that has a body, a gate, a first terminal and a second terminal. The body is connected with two switches. The first terminal and the second terminal thereof are connected to a second control node and the input node, respectively.

[0011] The input stage includes two NMOS charge transistors connected in series. The connecting point is an input node. The body of each NMOS charge transistor is connected with two switches. One end of the first NMOS charge transistor is connected to a third control node. One end of the second NMOS charge transistor is connected to a fourth control node.

[0012] The high-voltage generator includes two PMOS output transistors. The body of each PMOS output transistors is connected with two switches. One end of the first PMOS output transistors is connected to the third control node. One end of the second PMOS output transistor is connected to the fourth control node. The other ends of the two PMOS output transistors are connected to an output node.

[0013] The first input signal and the second input signal are provided to the first voltage boost stage and the second voltage boost stage. The two switches of the first voltage boost stage, the two switches of the second voltage boost stage, and the four switches of the input stage are controlled by the voltage on the first or second control node. The bodies of the first PMOS charge transistor and the second PMOS charge transistor are always switched to a higher voltage level. The bodies of the two NMOS charge transistors are always switched to a lower voltage level.

[0014] In another embodiment of the invention, the PMOS/NMOS transistors can be replaced by NMOS/PMOS transistors to form a charge pump circuit that provides a negative voltage output.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is a detailed circuit of a charge pump of a first embodiment in accordance with the invention;

[0016] FIG. 2 shows wave forms of the circuit in FIG. 1;

[0017] FIG. 3 is a block diagram of a multi-stage charge pump circuit comprised of many stages of the charge pump of FIG. 1 connected in series;

[0018] FIG. 4 is a schematic view how a logic device for generating input signal is connected according to the invention;

[0019] FIG. 5 is a detailed circuit of a charge pump of a second embodiment in accordance with the present invention;

[0020] FIG. 6 is a detailed circuit of a charge pump of a third embodiment in accordance with the present invention;

[0021] FIG. 7 shows the working wave forms of the circuits in FIGS. 5 and 6;

[0022] FIG. 8 is a block diagram of a multi-stage charge pump circuit comprised of many stages of the charge pump circuits of FIGS. 5 and 6 connected in series;

[0023] FIG. 9 is a detailed circuit of a conventional charge pump circuit; and

[0024] FIG. 10 shows wave forms of control signals for the charge pump circuit in FIG. 9.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0025] With reference to FIGS. 1 and 2, a first embodiment of a single-stage charge pump circuit 100 is composed of NMOS and PMOS transistors. No particular restrictions need to be imposed on the connections of the source or drain of each transistor. The source and drain can be interchanged without affecting the spirit of the invention. Therefore, they will be referred to as the first terminal and the second terminal in the following description.

[0026] Input signals for the charge pump circuit **100** are a set of opposite-phase signals PH\_A and PH\_B. In this embodiment, the input signals PH\_A, PH\_B are non-overlap continuous square waves, with their voltage levels alternating between 0 and VDD. The charge pump circuit **100** has a symmetric structure between the upper and lower portions. The charge pump circuit **100** has a first voltage boost stage **10**, a second voltage boost stage **20**, an input stage **30**, and a high-voltage generator **40**.

[0027] The first voltage boost stage **10** is connected to the input signal PH\_A via a first capacitor C1. The first voltage boost stage **10** includes a first PMOS charge transistor **11**, a first switch **12**, and a second switch **13**. The first terminal and the gate of the first PMOS charge transistor **11** are connected to the first capacitor C1. The first switch **12** and the second switch **13** are both the PMOS transistors. The bodies of the two switches **12**, **13** and their first terminals are connected to the body of the first PMOS charge transistor **11**. The second terminal of the first switch **12** is connected to the first capacitor C1. The second terminal of the second switch **13** is connected to the second terminal of the first PMOS charge transistor **11**.

[0028] The second voltage boost stage **20** is connected to the other input signal PH\_B via the second capacitor C2. It includes a second PMOS charge transistor **21**, a third switch **22**, and a fourth switch **23**. The first terminal and the gate of the second PMOS charge transistor **21** are connected to the second capacitor C2. The third switch **22** and the fourth switch **23** are both PMOS transistors. The bodies of the two switches **22**, **23** and their first terminals are connected to the body of the second PMOS charge transistor **21**. The second terminal of the third switch **22** is connected to the second capacitor C2. The second terminal of the fourth switch **23** is connected to the second terminal of the second PMOS charge transistor **21**.

[0029] The input stage **30** mainly comprises a first NMOS charge transistor **31** and a second NMOS charge transistor **32** connected in series. The first terminals of the two NMOS charge transistors **31**, **32** are connected to the node VIN. The node VIN is imposed with a voltage equal to or higher than VDD. The second terminal of the first NMOS charge transistor **31** is connected to the input signal PH\_A via a third capacitor C3. The second terminal of the second NMOS charge transistor **32** is connected to the input signal PH\_B via a fourth capacitor C4. The body of the first NMOS charge transistor **31** is also connected with a set of NMOS switches **311**, **312**. The bodies of the two NMOS switches **311**, **312** are both connected to the body of the first NMOS charge transistor **31**. One end of the switch **311** is connected to the third capacitor C3. One end of the other switch **312** is connected to the node VIN. For the second NMOS charge transistor **32**, its body is connected with a set of NMOS switches **321**, **322** as well. The connection method is symmetric to the two switches **311**, **312** of the first NMOS charge transistor **31**. Therefore, the description is not repeated here again.

[0030] The high-voltage generator **40** is connected with the input stage **30**. It consists of two PMOS output transistors **41**, **42**. Its first terminal is connected to the first/second NMOS charge transistor **31**, **32** of the input stage and the third/fourth capacitors C3, C4. The second terminals of the two PMOS output transistors **41**, **42** are connected to a form a high-voltage output terminal VOUT. Each body of the two PMOS output transistors **41**, **42** are provided with a set of PMOS switches **411**, **412**, **421**, **422**. The body of the first set of

switches **411**, **412** and the body of the first PMOS output transistor **41** are connected. The body of the second set of switches **421**, **422** and the body of the second PMOS output transistor **42** are connected.

[0031] Before introducing operations of the above-mentioned circuit, the voltages on the following nodes are defined. The wave forms of the voltages on the nodes can be obtained from FIG. 2.

[0032] BOOSTA1 (first control node): This is the voltage on the node where the first PMOS charge transistor **11** and the capacitor C1 are connected in the first voltage boost stage **10**.

[0033] BOOSTB1 (second control node): This is the voltage on the node where the second PMOS charge transistor **21** and the second capacitor C2 are connected in the second voltage boost stage **20**.

[0034] BOOSTA (third control node): This is the voltage on the node where the first NMOS charge transistor **31** and the capacitor C3 are connected in the input stage **30**.

[0035] BOOSTB (fourth control node): This is the voltage on the node where the second NMOS charge transistor **32** and the capacitor C4 are connected in the input stage **30**.

[0036] The two voltages of BOOSTA1 and BOOSTB1 are used as the gate control voltages for the switches in the charge pump circuit. Take the upper portion of the circuit as an example. The gates of the first switch **12** and the second switch **13** in the first PMOS charge transistor **11** are controlled by BOOSTB1 and BOOSA1. The two NMOS switches **311**, **312** connected by the first NMOS charge transistor **31** are controlled by BOOSTB1 and BOOSA1. The two PMOS switches **411**, **412** in the first PMOS output transistor **41** use BOOSTB and BOOSTA as their gate control signals.

[0037] As shown in FIG. 2, the switches connected to the disclosed PMOS or NMOS transistor can automatically switch to a high or low voltage level, so that the bodies of the PMOS transistor or NMOS transistor can be continuously connected to a high or low voltage level. For the PMOS transistor, its body has to be connected to the high voltage level in the circuit, and the NMOS transistor has to be constantly connected to the low voltage level in the circuit.

[0038] I. When the input signal PH\_A is a high voltage VDD, the other input signal PH\_B is a low voltage 0. In this case, the voltage level at the BOOSTA node is VDD+VIN. The voltage level at the BOOSTB node is VIN. From another point of view, the voltage at BOOSTA1 is VDD+VIN-V<sub>TH</sub> and the voltage at BOOSTB1 is VIN-V<sub>TH</sub>, where V<sub>TH</sub> is the threshold voltage of the transistor.

[0039] For the first PMOS charge transistor **11** of the first voltage boost stage **10**, its first terminal has a voltage of VDD+VIN-V<sub>TH</sub> and its second terminal has a voltage of VIN. Therefore, the body should switch to the higher one of the two. The gate of the first switch **12** receives a voltage of VIN-V<sub>TH</sub>, and the gate of the second switch **13** receives a voltage of VDD+VIN-V<sub>TH</sub>. Therefore, the first switch **12** is on while the second switch **13** is off. After the first switch **12** is on, the body of the first PMOS charge transistor **11** is connected to the higher voltage level of VDD+VIN-V<sub>TH</sub> via the first switch **12**.

[0040] For the second PMOS charge transistor **21** of the second voltage boost stage **20**, its first terminal has a voltage of VIN-V<sub>TH</sub> while its second terminal has a voltage of VIN. So the body should switch to the higher voltage of the two, VIN. The gate of the third switch **22** receives a voltage of VDD+VIN-V<sub>TH</sub>, and the gate of the fourth gate **23** receives a voltage of VIN-V<sub>TH</sub>. Therefore, the third switch **22** is off and

the fourth switch **23** is on. As the fourth switch **23** is on, the body of the second PMOS charge transistor **21** switches to a higher voltage VIN via the fourth switch **23**.

[0041] In the input stage **30**, the first terminal of the first NMOS charge transistor **31** has a voltage of VIN and the second voltage has a voltage of VDD+VIN. Therefore, its body switches to the lower of the two, VIN. The gate of the NMOS switch **311** connected to the first NMOS transistor **31** is connected to the voltage of  $VIN - V_{TH}$ . The gate of the other NMOS switch **312** is connected to the voltage of  $VDD + VIN - V_{TH}$ . Therefore, only the NMOS switch **312** is on. The first NMOS transistor **31** thus switches to the lower voltage VIN. [0042] Likewise, the second NMOS transistor **32** in the input stage **30**, the first PMOS transistor **41** in the high-voltage generator **40**, and the body of the second PMOS transistor can be appropriately switched to a lower or high voltage level.

[0043] II. When the input signal PH\_A is a low voltage level 0, the other input signal PH\_B is a high voltage level VDD. In this time sequence, the circuit action is exactly opposite to the above-mentioned stage I. Each NMOS transistor or PMOS transistor can use the correspondingly connected switch to switch to an appropriate voltage level.

[0044] As shown in FIG. 3, after serially connecting several stages of the charge pump circuits **100** in FIG. 1, one obtains an even higher output voltage. Suppose N stages of charge pump circuits **100** are connected in series. The final output voltage VPP is  $(N+1) \times VDD$ . The two output terminals of an input signal generating unit **50** provide the two opposite-phase input signals PH\_A and PH\_B to each stage of the charge pump circuits **100**. As shown in FIG. 4, the input signal generating unit **50** is equivalent to an SR flip-flop.

[0045] Please refer to FIG. 5 for another embodiment of the disclosed single-stage charge pump circuit **200** that outputs a negative voltage. The difference between the current embodiment and the previous one is in that its first voltage dropping stage **10a**, second voltage dropping stage **20a**, and negative voltage generator **40a** all comprise NMOS transistors. Therefore, the switches correspondingly connected to the NMOS transistors also comprise NMOS transistors. In particular, the device in the input stage **30a** is replaced by PMOS transistors. The switches connected to the PMOS transistors also comprise PMOS transistors.

[0046] Using the PMOS transistor as the charge transistor in the input stage enables the single-stage charge pump circuit **200** in FIG. 5 to be a first stage charge pump circuit. However, the second, third, . . . , N-th stage circuits are preferably the one shown in FIG. 6. Each device in the charge pump circuit **300** of FIG. 6 comprises the NMOS transistor, including the input stage **30b**. In the first voltage dropping stage **10b**, a third NMOS discharge transistor **14b** is inserted between the first capacitor C1 and the node VIN, in addition to the original first NMOS discharge transistor **11b**. Its body is connected to the first switch **12b** and the second switch **13b**. The gate of the NMOS discharge transistor **14b** is connected to a second capacitor C2, controlled by the voltage signal **BOOSTB1**. In the second voltage dropping stage **20b**, a fourth NMOS discharge transistor **24b** is connected between the capacitor C2 and the node VIN as well. The gate of the NMOS transistor **24b** is connected to the capacitor C1, controlled by the voltage signal **BOOSTA1**. The control signals for FIGS. 5 and 6 are shown in FIG. 7.

[0047] As shown in FIG. 8, the single-stage charge pump circuits **200**, **300** in FIGS. 5 and 6 can be connected in series

to form a multi-stage circuit for providing a negative output voltage. The first-stage charge pump circuit **200** uses the circuit in FIG. 5. In the subsequent stages, the circuit in FIG. 6 is employed. Finally, the output voltage  $V_{BB} = -NxVDD$ .

[0048] In summary, the disclosed two-phase charge pump circuit uses a mixed structure of NMOS and PMOS charge/discharge transistors and output transistors. Both ends of the body of each charge/discharge transistor are connected to two switches also comprised of NMOS or PMOS transistors. Using appropriate control signals, one of the switches is on so that the NMOS and PMOS charge/discharge transistor or the body of the output transistor can be constantly switched to a lower voltage level (for the NMOS transistors) or a higher voltage level (for the PMOS transistors). As the voltage of the body can be effectively controlled, the body effect can be avoided.

What is claimed is:

1. A two-phase charge pump circuit without the body effect that are controlled by a first input signal and a second input signal of opposite phases, the charge pump circuit comprising:

a first voltage boost stage comprising a first PMOS charge transistor with a body, a gate, a first terminal, and a second terminal, the body being connected to two switches, and the first terminal and the second terminal of the first PMOS charge transistor respectively connected to a first control node and an input node;

a second voltage boost stage comprising a second PMOS charge transistor with a body, a gate, a first terminal, and a second terminal, the body being connected to two switches, the first terminal and the second terminal of the second PMOS charge transistor respectively connected to a second control node and the input node;

an input stage comprising a first and a second NMOS charge transistors connected in series with their connecting node as the input node, a body of each NMOS charge transistor being connected to two switches; the first NMOS charge transistor having a first terminal connected to a third control node and the second NMOS charge transistor having a first terminal connected to a fourth control node; and

a high-voltage generator comprising a first and a second PMOS output transistors,

the first PMOS output transistor having a body connected to two switches and having a first terminal connected to the third control node;

the second PMOS output transistor having a body connected to two switches and having a first terminal connected to the fourth control node; and

the first output PMOS transistor and the second output PMOS transistor both having a second terminals connected to an output node;

wherein the first input signal and the second input signal are respectively provided to the first voltage boost stage and the second voltage boost stage; the two switches of the first voltage boost stage, the two switches of the second voltage boost stage, and the four switches of the input stage are controlled by the voltage on the first control node or the second control node so that the body of the first and second PMOS charge transistor is constantly switched to a relative high voltage level and the body of the two NMOS charge transistors is constantly switched to a relative low voltage level.

**2.** The two-phase charge pump circuit without the body effect as claimed in claim **1**, wherein

the two switches connected to the body of the first PMOS charge transistor are first PMOS switch and second PMOS switch;

the two switches connected to the body of the second PMOS charge transistor are third PMOS switch and fourth PMOS switch;

the two switches connected to the body of the first NMOS charge transistor are first NMOS switch and second NMOS switch; and

the two switches connected to the body of the second NMOS charge transistor are third NMOS switch and fourth NMOS switch.

**3.** The two-phase charge pump circuit without the body effect as claimed in claim **2**, wherein

the first terminal and the gate of the first PMOS charge transistor are connected to a first capacitor to form the first control node, and the first capacitor is further connected to the first input signal;

the bodies and first terminals of the first PMOS switch and the second PMOS switch are connected to the body of the first PMOS charge transistor, with the second terminal of the first PMOS switch connected to the first control node and the second terminal of the second PMOS switch connected to the input node;

the first terminal and the gate of the second PMOS charge transistor are connected to a second capacitor to form the second control node, and the other end of the second capacitor is connected to the second input signal;

the bodies and first terminals of the third PMOS switch and the fourth PMOS switch are connected to the body of the second PMOS charge transistor, with the second terminal of the third PMOS switch connected to the second control node and the second terminal of the fourth PMOS switch connected to the input node; and

the gates of the first PMOS switch and the fourth PMOS switch are connected to the second control node, and the gates of the second PMOS switch and the third PMOS switch are connected to the first control node.

**4.** The two-phase charge pump circuit without the body effect as claimed in claim **3**, wherein

the gate of the first NMOS charge transistor in the input stage is connected to the second control node, the first terminal of the first NMOS charge transistor is connected to a third capacitor to form the third control node and the other end of the third capacitor is connected to the first input signal, and the second terminal of the first NMOS charge transistor is connected to the input node;

the gate of the second NMOS charge transistor in the input stage is connected to the first control node, the first terminal of the second NMOS charge transistor is connected to a fourth capacitor to form the fourth control node and the other end of the fourth capacitor is connected to the second input signal, and the second terminal of the second NMOS charge transistor is connected to the input node;

the first terminals and the bodies of the first NMOS switch and the second NMOS switch are connected to the body of the first NMOS charge transistor, with the gate of the first NMOS switch connected to the second control node and the gate of the second NMOS switch connected to the first control node; and

the first terminals and the bodies of the third NMOS switch and the fourth NMOS switch are connected to the body of the second NMOS charge transistor, with the gate of the third NMOS switch connected to the first control node and the gate of the fourth NMOS switch connected to the second control node.

**5.** The two-phase charge pump circuit without the body effect as claimed in claim **4**, wherein

the gate of the first PMOS output transistor of the high-voltage generator is connected to the fourth control node and the two switch gates of the first PMOS output transistor are connected respectively to the third control node and the fourth control node; and

the gate of the second PMOS output transistor of the high-voltage generator is connected to the third control node and the two switch gates of the second PMOS output transistor are connected respectively to the third control node and the fourth control node.

**6.** A two-phase charge pump circuit without the body effect that receives a first input signal and a second input signal of opposite phases, the charge pump circuit comprising:

a first voltage dropping stage, which includes a first NMOS discharge transistor with a body, a gate, a first terminal, and a second terminal, the body being connected to two switches, and the first terminal and the second terminal of the first NMOS discharge transistor being connected to a first control node and an input node, respectively;

a second voltage dropping stage, which includes a second NMOS discharge transistor with a body, a gate, a first terminal, and a second terminal, the body being connected to two switches, the first terminal and the second terminal of the second NMOS discharge transistor being connected to a second control node and the input node;

an input stage, which includes two PMOS discharge transistors connected in series with their connecting node being the input node, the body of each PMOS discharge transistor being connected to two switches with one end of the first PMOS discharge transistor connected to a third control node and one end of the second PMOS discharge transistor connected to a fourth control node; and

a negative-voltage generator, which includes two NMOS output transistors, the body of each of the NMOS output transistors being connected to two switches with one end of the first NMOS output transistor connected to the third control node and one end of the second NMOS output transistor being connected to the fourth control node, and the other ends of the two NMOS output transistors being connected to an output node;

wherein the first input signal and the second input signal are provided to the first voltage dropping stage and the second voltage dropping stage, respectively, the two switches of the first voltage dropping stage, the two switches of the second voltage dropping stage, and the four switches of the input stage are controlled by the voltage on the first control node or the second control node so that the body of the first/second NMOS discharge transistor is constantly switched to a lower voltage level and the body of the two PMOS discharge transistors is constantly switched to a higher voltage level.

**7.** The two-phase charge pump circuit without the body effect as claimed in claim **6**, wherein

the two switches connected to the body of the first NMOS discharge transistor are first NMOS switch and second NMOS switch;

the two switches connected to the body of the second NMOS discharge transistor are third NMOS switch and fourth NMOS switch;

the two switches connected to the body of the first PMOS discharge transistor are first PMOS switch and second PMOS switch; and

the two switches connected to the body of the second PMOS discharge transistor are third PMOS switch and fourth PMOS switch.

**8.** The two-phase charge pump circuit without the body effect as claimed in claim 7, wherein

the first terminal and the gate of the first NMOS discharge transistor are connected to a first capacitor to form the first control node, and the other end of the first capacitor is connected to the first input signal;

the bodies and first terminals of the first NMOS switch and the second NMOS switch are connected to the body of the first NMOS discharge transistor, with the second terminal of the first NMOS switch connected to the first control node and the second terminal of the second NMOS switch connected to the input node;

the first terminal and the gate of the second NMOS discharge transistor are connected to a second capacitor to form the second control node, and the other end of the second capacitor is connected to the second input signal; the bodies and first terminals of the third NMOS switch and the fourth NMOS switch are connected to the body of the second NMOS discharge transistor, with the second terminal of the third NMOS switch connected to the second control node and the second terminal of the fourth NMOS connected to the input node; and

the gates of the first NMOS switch and the fourth NMOS switch are connected to the second control node, and the gates of the second NMOS switch and the third NMOS switch are connected to the first control node.

**9.** The two-phase charge pump circuit without the body effect as claimed in claim 8, wherein

the gate of the first PMOS discharge transistor in the input stage is connected to the second control node, the first terminal of the first PMOS discharge transistor is connected to a third capacitor to form the third control node and the other end of the third capacitor is connected to the first input signal, and the second terminal of the first PMOS discharge transistor is connected to the input node;

the gate of the second PMOS discharge transistor in the input stage is connected to the first control node, the first terminal of the second PMOS discharge transistor is connected to a fourth capacitor to form the fourth control node and the other end of the fourth capacitor is connected to the second input signal, and the second terminal of the second PMOS discharge transistor is connected to the input node;

the first terminals and the bodies of the first PMOS switch and the second PMOS switch are connected to the body of the first PMOS discharge transistor, with the gate of the first PMOS switch connected to the second control node and the gate of the second PMOS switch connected to the first control node; and

the first terminals and the bodies of the third PMOS switch and the fourth PMOS switch are connected to the body

of the second PMOS discharge transistor, with the gate of the third PMOS switch connected to the first control node and the gate of the fourth PMOS switch connected to the second control node.

**10.** The two-phase charge pump circuit without the body effect as claimed in claim 9, wherein

the gate of the first NMOS output transistor of the negative-voltage generator is connected to the fourth control node and the two switch gates of the first NMOS output transistor are connected respectively to the third control node and the fourth control node; and

the gate of the second NMOS output transistor of the negative-voltage generator is connected to the third control node and the two switch gates of the second NMOS output transistor are connected respectively to the third control node and the fourth control node.

**11.** A two-phase charge pump circuit without the body effect that receives a first input signal and a second input signal of opposite phases, the charge pump circuit comprising:

a first voltage dropping stage, which includes a first NMOS discharge transistor and a third NMOS discharge transistor, each of which having a body, a gate, a first terminal, and a second terminal, the body of the first NMOS discharge transistor being connected to two switches, the first terminal and the second terminal of the first NMOS discharge transistor being connected respectively to a first control node and an input node, the first terminal and the second terminal of the third NMOS discharge transistor being connected respectively to the first control node and the input node, the gate of the third NMOS discharge transistor is connected to the second control node, and the body of the third NMOS discharge transistor is connected to the body of the first NMOS discharge transistor;

a second voltage dropping stage, which includes a second NMOS discharge transistor and a fourth NMOS discharge transistor, each of which having a body, a gate, a first terminal, and a second terminal, the body of the second NMOS discharge transistor being connected to two switches, the first terminal and the second terminal of the second NMOS discharge transistor being connected respectively to a second control node and the input node, the first terminal and the second terminal of the fourth NMOS discharge transistor being connected respectively to the second control node and the input node, the gate of the fourth NMOS discharge transistor is connected to the first control node, and the body of the fourth NMOS discharge transistor is connected to the body of the second NMOS discharge transistor;

an input stage, which includes two NMOS discharge transistors connected in series with their connecting node being the input node, the body of each NMOS discharge transistor being connected to two switches with one end of the fifth NMOS discharge transistor connected to a third control node and one end of the sixth NMOS discharge transistor connected to a fourth control node; and

a negative-voltage generator, which includes two NMOS output transistors, the body of each of the NMOS output transistors being connected to two switches with one end of the first NMOS output transistor connected to the third control node and one end of the second NMOS output transistor being connected to the fourth control

node, and the other ends of the two NMOS output transistors being connected to an output node; wherein the first input signal and the second input signal are provided to the first voltage dropping stage and the second voltage dropping stage, respectively, the two switches of the first voltage dropping stage, the two switches of the second voltage dropping stage, and the four switches of the input stage are controlled by the voltage on the first control node or the second control node so that the bodies of the first/third NMOS discharge transistor and the second/fourth NMOS discharge transistors are constantly switched to a lower voltage level.

**12.** The two-phase charge pump circuit without the body effect as claimed in claim **11**, wherein

the two switches connected to the body of the first/third NMOS discharge transistor are first NMOS switch and second NMOS switch;

the two switches connected to the body of the second/fourth NMOS discharge transistor are third NMOS switch and fourth NMOS switch;

the two switches connected to the body of the fifth NMOS discharge transistor in the input stage are fifth NMOS switch and sixth NMOS switch; and

the two switches connected to the body of the sixth NMOS discharge transistor are seventh NMOS switch and eighth NMOS switch.

**13.** The two-phase charge pump circuit without the body effect as claimed in claim **12**, wherein

the first terminal and the gate of the first NMOS discharge transistor are connected to a first capacitor to form the first control node, and the other end of the first capacitor is connected to the first input signal;

the bodies and first terminals of the first NMOS switch and the second NMOS switch are connected to the body of the first NMOS discharge transistor, with the second terminal of the first NMOS switch connected to the first control node and the second terminal of the second NMOS switch connected to the input node;

the first terminal and the gate of the second NMOS discharge transistor are connected to a second capacitor to form the second control node, and the other end of the second capacitor is connected to the second input signal;

the bodies and first terminals of the third NMOS switch and the fourth NMOS switch are connected to the body of the second NMOS discharge transistor, with the second terminal of the third NMOS switch connected to the second control node and the second terminal of the fourth NMOS connected to the input node; and

the gates of the first NMOS switch and the fourth NMOS switch are connected to the second control node, and the gates of the second NMOS switch and the third NMOS switch are connected to the first control node.

**14.** The two-phase charge pump circuit without the body effect as claimed in claim **13**, wherein

the gate of the fifth NMOS discharge transistor is connected to the first control node, the first terminal of the fifth NMOS discharge transistor is connected to a third capacitor to form the third control node and the other end of the third capacitor is connected to the first input signal, and the second terminal of the fifth NMOS discharge transistor is connected to the input node;

the gate of the sixth NMOS discharge transistor is connected to the second control node, the first terminal of the sixth NMOS discharge transistor is connected to a fourth capacitor to form the fourth control node and the other end of the fourth capacitor is connected to the second input signal, and the second terminal of the sixth NMOS discharge transistor is connected to the input node;

the first terminals and the bodies of the fifth NMOS switch and the sixth NMOS switch are connected to the body of the fifth NMOS discharge transistor, with the gate of the fifth NMOS switch connected to the second control node and the gate of the sixth NMOS switch connected to the first control node; and

the first terminals and the bodies of the seventh NMOS switch and the eighth NMOS switch are connected to the body of the sixth NMOS discharge transistor, with the gate of the seventh NMOS switch connected to the first control node and the gate of the eighth NMOS switch connected to the second control node.

**15.** The two-phase charge pump circuit without the body effect as claimed in claim **14**, wherein

the gate of the first NMOS output transistor in the negative-voltage generator is connected to the fourth control node and the two switch gates connected to the first NMOS output transistor are connected to the third control node and the fourth control, respectively; and

the gate of the second NMOS output transistor in the negative-voltage generator is connected to the third control node and the two switch gates connected to the second NMOS output transistor are connected to the third control node and the fourth control, respectively.

\* \* \* \* \*