



- (51) International Patent Classification:
A61M 5/14 (2006.01)
- (21) International Application Number:
PCT/US2014/019430
- (22) International Filing Date:
28 February 2014 (28.02.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13/784,615 4 March 2013 (04.03.2013) US
- (71) Applicant: BAYER MEDICAL CARE INC. [US/US]; 1 Bayer Drive, Indianola, PA 15051 (US).
- (72) Inventors: MARSH, Charles; 215 Meadowbrook Drive, Cranberry Township, PA 16066 (US). MCCUTCHEN, Larry; 3006 Wildwood Road Ext., Allison Park, PA 15101 (US).
- (74) Agents: KENT, Joseph et al.; 1 Bayer Drive, Indianola, PA 15051 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

- (54) Title: METHODS AND SYSTEMS FOR DOSING CONTROL IN AN AUTOMATED FLUID DELIVERY SYSTEM

FIG. 1



(57) Abstract: Methods and systems for dispensing a fluid using an automated fluid delivery system are disclosed. A pump may be configured to force an aliquot of fluid into a fluid delivery channel. A processor may receive values of a property for the aliquot and the source of the aliquot. The processor may use the values to determine the volume of the aliquot. The determined volume is compared by the processor against an expected volume to establish the amount of fluid being pumped by the pump per unit, such as time or revolutions. The processor controls operation of the pump to dispense a predetermined dose based on the amount of fluid being pumped by the pump per unit.

METHODS AND SYSTEMS FOR DOSING CONTROL IN AN AUTOMATED FLUID DELIVERY SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of United States Application No. 13/784,615, filed March 4, 2013 and entitled “Methods and Systems for Dosing Control in an Automated Fluid Delivery System,” and which is incorporated herein in its entirety.

BACKGROUND

[0002] Automated fluid delivery systems, such as infusion systems, operate to administer medication to a patient in carefully measured doses. Such infusion systems may deliver fluids in a manner that is often more cost effective and reliable than if performed manually by medical staff. Accurate dosing is important, especially for particular fluids, such as radiopharmaceuticals where high precision is required to ensure that the patient is not exposed to too much radioactive material. Typical automated infusion systems pump the fluid using an infusion pump through a delivery tube and into a patient’s venous system through a needle or catheter. A common infusion pump is the peristaltic pump that operates by deforming the delivery tube to force the fluid from a fluid source toward the patient.

[0003] The automated infusion process is often controlled using various parameters, such as infusion rate and duration, dose volume, patient weight, and medication units and concentration. However, these parameters are affected by the specific components and operating characteristics of the infusion system equipment. Conventional automated dosing techniques do not adequately adjust for these variances, which may lead to inaccurate delivery of medical fluids to patients.

SUMMARY

[0004] The invention described in this document is not limited to the particular systems, methodologies or protocols described, as these may vary. The terminology used herein is for the purpose of describing particular embodiments only, and is not intended to limit the scope of the present disclosure.

[0005] It must be noted that as used herein and in the appended claims, the singular forms “a,” “an,” and “the” include plural reference unless the context clearly dictates otherwise. Unless defined otherwise, all technical and scientific terms used herein have the

same meanings as commonly understood by one of ordinary skill in the art. As used herein, the term “comprising” means “including, but not limited to.”

[0006] In an embodiment, a system for dispensing a fluid may comprise a pump configured to force an aliquot of fluid from a fluid source into a fluid delivery channel and at least one sensor configured to measure a sample value of a property of the aliquot. A computing device in communication with the pump and the at least one sensor may comprise a processor and a non-transitory, computer-readable storage medium in operable communication with the processor. The computer-readable storage medium may contain one or more programming instructions that, when executed, cause the processor to: receive the sample value, receive a source value of the property for the fluid source, determine a sample volume of the aliquot based on a comparison of the sample value and the source value, and control operation of the pump to dispense a predetermined dose of the fluid based on a comparison of the sample volume with an expected volume.

[0007] In an embodiment, a method of dispensing a fluid may comprise providing a pump configured to force an aliquot of fluid from a fluid source into a fluid delivery channel. A processor may receive a source value of a property for the fluid source and a sample value of the property for the aliquot measured by at least one sensor. The processor may determine a volume of the aliquot based on a comparison of the sample value of the property and the source value of the property. The operation of the pump may be controlled by the processor to dispense a predetermined dose of the fluid based on a comparison of the sample volume with an expected volume.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 depicts an illustrative automated fluid delivery system according to an embodiment.

[0009] FIG. 2 depicts an illustrative peristaltic pump that may be used in automated fluid delivery systems configured according to some embodiments.

[0010] FIG. 3 depicts illustrative fluid delivery channels having different dimensional properties.

[0011] FIG. 4 depicts an illustrative automated fluid delivery system control screen according to some embodiments.

[0012] FIG. 5 depicts a flow diagram of a method of dispensing a fluid according to an embodiment.

[0013] FIG. 6 depicts a block diagram of illustrative internal hardware that may be used to contain or implement program instructions according to an embodiment.

DETAILED DESCRIPTION

[0014] The terminology used in the description is for the purpose of describing the particular versions or embodiments only, and is not intended to limit the scope.

[0015] The present disclosure is directed toward dosage control in an automated fluid delivery system, such as an automated infusion system. In one embodiment, a fluid delivery pump is used to pump a fluid being delivered to a patient through the automated fluid delivery system. An illustrative and non-restrictive example of a fluid delivery pump is a peristaltic pump. According to some embodiments, the automated fluid delivery system may compare a property of the fluid in a fluid source with the same property of the fluid in a fluid delivery channel of the automated fluid delivery system. This comparison may be used to determine the sample volume of the fluid in the fluid delivery channel. This volume may be compared with an expected or standard volume to correlate operation of the pump with volume of the fluid pumped into the fluid delivery channel. The automated fluid delivery system may operate to control the pump based on this comparison. In an embodiment, the automated fluid delivery system may be configured to deliver a radiopharmaceutical. In this embodiment, the property may comprise radioactivity of a volume of the radiopharmaceutical. A non-limiting example of an automated fluid delivery system is the Intego™ positron emission tomography (PET) infusion system provided by Bayer Medical Care Inc. of Indianola, Pennsylvania.

[0016] FIG. 1 depicts an illustrative automated fluid delivery system according to an embodiment. As shown in FIG. 1, an automated fluid delivery system **100** may include a fluid delivery apparatus **105** configured to deliver a medical fluid to a patient. In an embodiment, the fluid delivery apparatus **105** may comprise an infusion apparatus. The fluid delivery apparatus **105** may have a medical fluid source **130** arranged therein and configured to hold a volume of the medical fluid. For example, some diagnostic imaging procedures, such as PET and single-photon emission computed tomography (SPECT), require that a patient receive radioactive contrast agents, also called radiopharmaceuticals, to obtain images. In a radiopharmaceutical infusion system, the medical fluid source **130** may be in the form of a shielded vial or “pig,” such as a tungsten shielded vial. In another example, the medical fluid source **130** may comprise an infusion bag, such as an intravenous (IV) bag. Embodiments provide that the medical fluid may comprise any fluid capable of being

delivered to a patient through an automated fluid delivery system, including, without limitation, saline, chemotherapy drugs, radiopharmaceuticals, and contrast agents and combinations thereof.

[0017] The medical fluid source **130** may be in fluid communication with a pump **115** through a fluid delivery channel **135**. Although the medical fluid source **130** is depicted in FIG. 1 as being located within the fluid delivery apparatus **105**, embodiments are not so limited. The medical fluid source **130** may be located outside of the fluid delivery apparatus **105** in fluid communication with the fluid delivery apparatus through the fluid delivery channel **135**. Accordingly, the fluid delivery channel **135** may be located at least partially outside of the fluid delivery apparatus **105**. Some embodiments provide that the fluid delivery channel **135** may include more than one section and the sections may have different characteristics. For example, the fluid delivery channel **135** may be made of one type of material and have a particular diameter, thickness, or other property at a certain section and may be made of another material and/or have a different diameter, thickness, or other property at a different section.

[0018] Operation of the pump **115** draws the fluid out of the medical fluid source **130** and pumps it toward a dispensing element **120**. Embodiments may be configured to operate with any type of pump known to those having ordinary skill in the art or that may be developed in the future that may operate as described herein. Illustrative pumps include, without limitation, turbine pumps, peristaltic pumps, diaphragm pumps, screw pumps, syringe pumps, and centrifugal pumps. The dispensing element **120** may be configured to deliver the medical fluid to a patient through the fluid delivery channel **135**, such as a needle or catheter.

[0019] A controller **125** may be in communication with the pump **115**. The controller **125** may generally comprise a processor, a non-transitory memory or other storage device for housing programming instructions, data or information regarding one or more applications, and other hardware, including, for example, the central processing unit (CPU) **605**, read only memory (ROM) **610**, random access memory **615**, communication ports **640**, controller **620**, and/or memory device **625** depicted in FIG. 6 and described below in reference thereto. The controller **125** may be configured to receive information from the pump **115**, such as the speed of the pump. Certain aspects of the pump **115** may be directed by the controller **125**, such as the number of rotations, speed, linear travel distance, and/or active status (e.g., on/off, energized/de-energized, active/idle, etc.). In an embodiment, the controller **125** may execute pump control software configured to control operation of the pump **115**. For example, the

control software may be configured to operate the pump for a specified amount of time, number of rotations, or linear travel distance to displace a particular volume of the medical fluid.

[0020] The fluid delivery apparatus **105** may be operatively coupled with a computing device **110**. Embodiments provide that the computing device **110** may comprise the illustrative internal hardware depicted in FIG. 6 and described below in reference thereto. In an embodiment, the computing device **110** comprises a pump controller. In another embodiment, the computing device **110** comprises a stand-alone computing device in communication with the fluid delivery apparatus **105**. The computing device **110** may be configured to store or access data associated with operation of the fluid delivery apparatus **105**, such as patient information, medical fluid information, and operational information of apparatus components. The data may be stored in one or more databases on the computing device **110** and/or in a medical information system accessible by the computing device.

[0021] In an embodiment, the computing device **110** may execute one or more software programs (e.g., control software) for operating the fluid delivery apparatus **105**. For example, the one or more software programs may present a user interface on a display device (not shown) connected to the computing device **110** for medical staff operation of the fluid delivery apparatus **105**. For instance, an operator may start and/or stop infusion and view information associated with the infusion process from the user interface. An illustrative user interface is depicted in FIG. 4 and described in more detail herein. According to some embodiments, the computing device **110** may be in communication with the controller **125**. The computing device **110** may receive information from the controller **125**, such as but not limited to, pump control information, sample value information, source value information etc. and may provide for operator control of the pump **115** directly or through the controller **125**. In an embodiment, the control software may operate to control the automated fluid delivery system and/or components thereof. For instance, the control software may be configured to direct the controller **125** and/or the pump **115** to operate for a specified amount of time, number of rotations, linear travel distance, or any other type of pump operation capable of controlling the displacement of a particular volume of the medical fluid.

[0022] One or more sensors **140** may be positioned in and/or around the fluid delivery apparatus **105** to obtain information associated with the medical fluid. The one or more sensors **140** may be positioned at various places, such as in or around the medical fluid source **130**, the fluid delivery channel **135**, or any other location suitable to obtain information about the medical fluid as it travels through the fluid delivery apparatus **105**.

The one or more sensors **140** may include any type of sensor capable of measuring a property of interest, including, without limitation, concentration, radioactivity, salinity, conductance, optical properties, analyte concentration, and combinations thereof. Illustrative sensors include, but are not limited to, temperature sensors, pressure sensors, radioactivity sensors, optical sensors, analyte sensors, concentration sensors, flow sensors, and combinations thereof. The computing device **110** and/or the controller **125** may be in communication with the one or more sensors **140** such that they may receive information detected by the one or more sensors, for example, for use by software applications executing on the computing device and/or the controller.

[0023] According to some embodiments, information obtained from the one or more sensors **140** (e.g., “sensor information”) may be used alone or in combination with other available information to determine properties about the medical fluid being dispensed by the fluid delivery apparatus **105**. This information may be used to determine, for instance, whether the correct dose of the medical fluid is being dispensed to a patient. In one embodiment, the sensor information may be used in combination with fluid data, such as historical data or data calculated by one or more software programs being executed by the computing device **110**. In an embodiment, the sensor information may comprise information about the medical fluid in the fluid delivery channel **135** and the fluid data may comprise information about the medical fluid in the medical fluid source **130** or historical data relating thereto, such as a value or a property of an aliquot of the fluid.

[0024] Embodiments described herein may include automated fluid delivery systems, such as an automated fluid delivery system, comprising various types of pumps. FIG. 2 depicts an illustrative peristaltic pump that may be used in automated fluid delivery systems according to some embodiments. As shown in FIG. 2, a peristaltic pump **205** may include a pump casing **210** housing a rotor **235**. A fluid delivery channel **225** may enter the pump casing **210** through an inlet **215**, coil around the inside of the pump casing, and exit through an outlet **220**. In an embodiment, the fluid delivery channel **225** may comprise a flexible and deformable tube, such as a polyvinyl chloride (PVC) tube. The fluid delivery channel **225** may be in fluid communication with a source of a medical fluid (not shown) on the inlet **215** side and a fluid dispensing unit (not shown) on the outlet **220** side.

[0025] The rotor **235** may be connected to a roller **240** that rotates with rotor. The roller **240** may be in contact with the fluid delivery channel **225** within the housing **210**, compressing the fluid delivery tube at the point of contact. This compression in combination with the rotation of the rotor **235** forces the medical fluid through the fluid delivery channel

225 from the inlet **215** toward the outlet **220**. Embodiments are not limited to the particular rotor **235** and roller **240** configuration depicted in FIG. 2, as other peristaltic pump rotors may operate according to embodiments described herein. For example, the rotor itself, or one or more portions thereof, may be configured to be in contact with a fluid delivery channel in a manner similar to the roller **240** depicted in FIG. 2. In another example, the rotor **235** and/or the roller **240** may include fins, rollers or other components configured to provide smooth compression and fluid delivery through the fluid delivery channel **225**.

[0026] The amount of fluid progressing through the fluid delivery channel **225** is dependent on, among other things, the rotational speed of the rotor **235**, degree of rotation of rotor **235**, and the cross-sectional area of the fluid delivery channel. In some instances, pumping efficiency may be related to occlusion of the fluid delivery channel **225**, which may be a function of the wall thickness of the fluid delivery channel and the minimum gap between the rotor and the interior **230** of the pump casing **210**. In a conventional medical infusion system, the speed of the fluid delivery pump, or infusion pump, may be fixed as it is generally assumed that the dimensional properties of the fluid delivery channels do not vary appreciably across manufacturers or even within the same manufacturer. Illustrative dimensional properties that may vary between different fluid delivery channels include outer diameter, wall thickness, and inner diameter. In addition, process variation in the production of a fluid delivery channel may also lead to variability in properties thereof. As such, dimensional properties may vary along the length of the fluid delivery channel itself. Changes in these properties will have an effect on the amount of medical fluid delivered through the fluid delivery channel for a given speed and/or rotational distance of the pump rotor. Such process variation may lead to significant errors in fluid volume delivery, especially for fine control of small volumes of medical fluid.

[0027] FIG. 3 depicts illustrative fluid delivery channels having different dimensional properties. As shown in FIG. 3, fluid delivery channels **305**, **310**, **315** may have different dimensional properties, such as wall thickness, inner diameter, and outer diameter. For instance, a fluid delivery pump of an automated fluid delivery system may have been designed to operate with the “standard” outer diameter **330** and inner diameter **335** of fluid delivery channel **310**. In addition, the control software of the automated fluid delivery system may have been configured to control the fluid delivery pump with a fluid delivery channel having such standard dimensional properties. The thickness of a fluid delivery channel may be calculated by $(\text{outer diameter} - \text{inner diameter})/2$ and the cross-sectional area may be calculated by $\pi((\text{inner diameter})/2)^2$. The amount of fluid pumped through a fluid

delivery channel will be affected by the thickness and cross-sectional area thereof. For instance, for an automated fluid delivery system using a peristaltic pump, such as the peristaltic pump depicted in FIG. 2, the thickness of the fluid delivery channel may affect the amount of compression by the rotor and/or roller. The cross-sectional area may affect the volume of fluid travelling through the fluid delivery channel for a given pump speed and/or rotational distance.

[0028] Fluid delivery channel **305** may have the same inner diameter **325** as standard fluid delivery channel **310**, but may have a greater outer diameter **320**. As such, fluid delivery channel **305** may have the same cross-sectional area, but will have a different thickness. Fluid delivery channel **315** may have a greater inner diameter **345** and a smaller outer diameter **340** than standard fluid delivery channel **310**. Accordingly, fluid delivery channel **315** may have a greater cross-sectional area and a smaller thickness than standard fluid delivery channel **305**. The variability of fluid delivery channel dimensional properties may lead to unknown changes in fluid flow through the fluid delivery channel. Due to this variability, it is necessary to adjust the control of the pump to provide a consistent volume regardless of the dimensional properties of the fluid delivery channel.

[0029] FIG. 4 depicts an illustrative automated fluid delivery system control screen according to some embodiments. As shown in FIG. 4, an automated fluid delivery system control screen **405** may be configured to display fluid delivery information such as the amount of available medical fluid **420**, requested medical fluid properties **410**, and patient information **415**. The embodiment depicted in FIG. 4 is for an automated fluid delivery system, such as an automated infusion system, configured to deliver a radiopharmaceutical to a patient. As such, the medical fluid information **420** may comprise information about the volume of the radiopharmaceutical and any fluids being combined therewith, the requested fluid properties **410** may comprise the requested radioactivity, and the patient information **415** may comprise the patient weight. The control screen **405** may provide one or more functions to an automated fluid delivery system operator, such as system preparation **425**, procedure information **430** and patient preparation **435**. In addition, various other fluid delivery process control functions and information may be presented to an operator through the control screen **405**, such as functions to start or stop the process, access data, and/or verify the configuration of the process.

[0030] According to some embodiments, the control screen **405** may be presented on a display device operatively coupled with a computing device in communication with the automated fluid delivery system, such as the computing device **110** and the fluid delivery

apparatus **105** depicted in FIG. 1. The control screen **405** may be in communication with or may be a component of control software configured to operate the automated fluid delivery system and/or components thereof (e.g., the pump and/or pump controller).

[0031] It is important to ensure that a patient receives a proper dose of the medical fluid during the fluid delivery process. As such, the control of the fluid delivery pump should be established before the patient begins to receive the medical fluid through the automated fluid delivery system. According to some embodiments, adjustment of the operation of the fluid delivery pump may be managed through the control software configured to operate the automated fluid delivery system and/or components thereof. The operation of the fluid delivery pump may need to be adjusted, for instance, due to variations in the dimensional properties of the fluid delivery channel. Embodiments provide that adjustments to the operation of the fluid delivery pump may be implemented when the fluid delivery channel is being primed with the medical fluid, such as through the patient preparation **435** function available from the control screen **405**. Priming allows the fluid delivery channel to be pre-filled with fluid before injection, preventing unwanted air from being introduced into the patient's vasculature.

[0032] In an embodiment, the fluid delivery pump may be a peristaltic pump used to deliver a radiopharmaceutical to a patient through the automated fluid delivery system. Illustrative and non-restrictive examples of radiopharmaceuticals include ^{64}Cu diacetyl-bis(N4-methylthiosemicarbazone) (e.g., ATSM or Copper 64), ^{18}F -fluorodeoxyglucose (FDG), ^{18}F -fluoride, 3'-deoxy-3'-[^{18}F]fluorothymidine (FLT), ^{18}F -fluoromisonidazole (FMISO), gallium, technetium-99m, indium-113m, strontium-87m, and thallium.

[0033] The control software may be configured to turn the rotor a specified number of whole or partial rotations to displace a specified volume (e.g., an aliquot) of the radiopharmaceutical. The number of rotations determined by the control software may be based on one or more pump coefficients, such as a volume-per-revolution coefficient. In another embodiment, the control software may be configured to operate the pump for a specified time based on a volume-per-time coefficient as the pump coefficient. The radioactivity of any particular volume of the radiopharmaceutical may be measured along the path of the fluid delivery channel using one or more sensors (such as sensors **140** depicted in FIG. 1). Non-limiting examples of sensors include silicon diodes, silicon PIN diode radiation sensors, avalanche diodes, scintillators, photomultipliers, solid state crystals, semiconductors, Geiger tubes, ionization-chamber radiation detectors, silicon photodiodes, microdischarge-based radiation detectors, sodium iodide crystal radiation detectors, bismuth tri-iodide crystal

radiation detectors, or cadmium tellurium and cadmium zinc tellurium semiconductor crystal radiation detectors, and combinations thereof.

[0034] The peristaltic pump may rotate the specified number of full or partial rotations, for example, when priming the fluid delivery channel, to displace a volume of the radiopharmaceutical into the fluid delivery channel. The aliquot of radiopharmaceutical displaced in the fluid delivery channel may be measured for a sample value of the property, such as sample total radioactivity. The source value of the property, such as source radioactivity of the radiopharmaceutical stored in the medical fluid source may be received by the control software. For example, the medical fluid source radioactivity may be measured by a sensor, may be entered into the control software by an operator, and/or may be determined by a formula (e.g., based on the radioactivity when delivered to the medical facility and the time between delivery and infusion). If the activity of the radiopharmaceutical in the medical fluid source from which the aliquot was extracted is known, then the sample total radioactivity in the aliquot may be used to determine the aliquot volume. The calculated volume of the aliquot may be compared with an expected volume by the control software. The control software may then rescale or adjust the pump coefficient value for the volume-per-revolution coefficient according to the measured radioactivity of the aliquot.

[0035] Measurement of one or more properties of the aliquot in the fluid delivery channel may be performed on one aliquot or in certain embodiments on two or more aliquots over a period of time. Measurement of the one or more properties of two or more aliquots of fluid over a period of time may result in a more accurate measured value for the one or more properties, for example by calculating an average for the measurements. In certain embodiments, the system may measure one or more properties of multiple aliquots delivered over a period of time to determine the sample value of each of the multiple aliquots. In specific embodiments, the measurement of the one or more properties may occur continuously as the fluid is delivered by the system. In specific embodiments, the value of the property, for example radioactivity of a radiopharmaceutical, may change over time, for example due to radioactive decay. Measurement of the property in two or more aliquots, or continuous measurement in certain embodiments, may allow the system to adjust or correct the calculated values and volumes as the value of the property changes. Known values, such as rate of radioactive decay (half-life) of the radiopharmaceutical may be incorporated into the calculations to determine accurate values and/or volumes.

[0036] According to embodiments, the process for determining the proper pump coefficient, such as the volume-per-revolution coefficient or the volume-per-time coefficient may be performed for each fluid delivery channel set, may be performed multiple times to determine a statistical average, and/or may be performed before each new patient.

[0037] The control software may have use default pump coefficient (C_d), for example, based on operating the fluid delivery pump under standard conditions. In one embodiment, C_d may be used to calculate a corrected pump coefficient (C_c) using, for example, the measured sample value or a property, such as, radioactivity of the radiopharmaceutical (M), standard pump movement (K) and assay concentration (A) according to the following: $C_c = M/(K \times A)$. Embodiments provide that C_c and C_d may represent volume-per-revolution coefficients, for instance, having units of milliliters (mL)/revolution, M may have units of mCi or MBq, and A may have units of mCi/mL or MBq/mL. In another embodiment, C_c may be determined by applying an alpha (α) filter mechanism to C_d instead of through direct measurement.

[0038] The variable K may have units that depend on the type of fluid delivery pump. For example, for a peristaltic pump, the units of K may have units of pump revolutions. In another example, K may have units of encoder counts or linear travel distance for a syringe pump. In essence, C_c may be configured as a measure of a volume/native pump movement metric used to command the pump. In a non-limiting example, a target dose T may comprise the target dose amount wherein dosing is volume based, and the pump may be commanded to pump a certain volume in mL using the following equation:

pump revolutions = $C_c(\text{mL/rev}) \times [T (\text{mCi}) / A (\text{mCi/mL})]$. This process may provide an intermediate estimate of volume for fluid accounting, which may rely on an accurate estimate of A for proper dose measurement. According to some embodiments, C_c may be measured directly when setting up a fluid delivery system using a small number of known motor movements as opposed to assuming a default value C_d and applying corrections after a dose intended for patient fluid delivery has already been extracted.

[0039] In an embodiment, an alpha filter may be used with multiple measurements to arrive at a final coefficient. For instance, instead of assigning $C_c = M/K \times A$ directly, $C_c[n]$ may be set as $C_c[n] = C_c[n-1] \times (1-\alpha) + \alpha \times M/K \times A$, where alpha is a value between 0 and 1. This process may converge slower, but may prevent a single measurement from causing the measurement system to destabilize. In general, the process may operate to average multiple readings into the final corrected coefficient instead of making a direct assignment based on a single reading.

[0040] As described herein, embodiments may provide for activity-based dosing as opposed to conventional volume-based dosing. An automated fluid delivery system may be configured to tune dosage volumes based on concentration measurements. In an embodiment, dosing measurements may comprise a plot of activity ingress to achieve optimal amount of dose in the fluid delivery channel and as a visual indication of these measurements, for instance, for fault diagnosis. For example, $T = (C_d)(K)(A)$ and $M = (C_c)(K)(A)$ and, therefore, $T = MC_d / C_c$. The following may be formulated based on the foregoing calculations: $C_c = ((M)(C_d))/T = ((M)(C_d))/((C_d)(K)(A))$.

[0041] For activity based dosing, C_c may be measured during the initial concentration check as $C_c = M/K$. In an embodiment, M/K may have units of mCi/rev. In another embodiment, the activity measurements may be MBq, mCi, or other concentration units and the units of native motor motion may depend on the type of pump and control mechanism, as described above. For example, M/K may have units of mCi/millimeter for a syringe pump. In activity based dosing, the motor may be commanded to move T/C_c revolutions to extract the proper dose amount, allowing for accurate dosing without an accurate or less accurate estimate of source concentration A . In a non-limiting example, the coefficient may be tuned using the process $C_c(\text{new}) = C_c(\text{current}) * M/T$, where M is the measured activity and T is the target activity. This correction process may be applied when dosing regardless of the dosing method (e.g., regardless of the units of C_c).

[0042] FIG. 5 depicts a flow diagram of a method of dispensing a fluid according to an embodiment. As shown in FIG. 5, a fluid may be forced 505 from a fluid source toward a dispensing element through a fluid delivery channel using a pump. For example, a peristaltic pump may rotate a specified number of full or partial rotations to move an aliquot of a medical fluid into a fluid delivery channel from a fluid source. In an embodiment, the specified number of rotations may be enough to move a sample volume of the fluid into the fluid delivery channel and not enough to dispense the fluid to a patient. The medical fluid may comprise a radiopharmaceutical, such as a contrast agent for a nuclear imaging procedure. A processor may receive 510 a sample value of a property of the fluid in the fluid delivery tube. For a radiopharmaceutical, the sample value may comprise the radioactivity of the aliquot in the fluid delivery channel as measured by one or more sensors accessible by the processor. A source value of the property for the fluid source may be received 515 by the processor. The source value may be obtained from the fluid source through various methods, including through measurement by a sensor, data entry by an operator, calculation based on properties of the fluid source, and combinations thereof.

[0043] The processor may determine **520** a sample volume of the fluid in the fluid delivery channel based on a comparison of the sample value and the source value. For instance, the radioactivity of the fluid source may be compared with the radioactivity of the fluid in the fluid delivery channel to determine the volume of the fluid in the fluid delivery channel. Operation of the pump may be controlled **525** to dispense a predetermined dose of the fluid based on comparing the sample volume with an expected volume. For example, the comparison of the sample volume and the expected volume may be used to adjust, calibrate, or otherwise correct the operation of the pump to dispense a predetermined dose of the fluid to a patient. For instance, automated fluid delivery system control software may be configured to rotate the pump rotor X times to dispense a predetermined amount (e.g., mL, mCi, etc.) of the fluid to achieve the predetermined dose. The amount of the fluid required for the dose may depend on various factors, such as whether the dose is determined by concentration, radioactivity, and the like. For example, for a radiopharmaceutical, the dose may be an amount of radioactivity, while for a medicine in solution, the dose may be a particular volume (e.g., mL) of the fluid. The comparison of the sample volume with the expected volume may reveal that rotating the pump rotor X times may dispense more/less than the predetermined dose. As such, the number of times to rotate the pump rotor may be adjusted by the control software to rotate the pump rotor the correct number of times (e.g., X × adjustment coefficient) to dispense the predetermined dose or amount of the fluid.

[0044] FIG. 6 depicts a block diagram of exemplary internal hardware that may be used to contain or implement program instructions, such as the process steps discussed above in reference to FIG. 5, according to an embodiment. A bus **600** serves as the main information highway interconnecting the other illustrated components of the hardware. CPU **605** is the central processing unit of the system, performing calculations and logic operations required to execute a program. CPU **605**, alone or in conjunction with one or more of the other elements disclosed in FIGS. 1 and 6, is an exemplary processing device, computing device or processor as such terms are using in this disclosure. Read only memory (ROM) **610** and random access memory (RAM) **615** constitute exemplary memory devices.

[0045] A controller **620** interfaces with one or more optional memory devices **625** to the system bus **600**. These memory devices **625** may include, for example, an external or internal DVD drive, a CD ROM drive, a hard drive, flash memory, a USB drive or the like. As indicated previously, these various drives and controllers are optional devices.

[0046] Program instructions, software or interactive modules for providing the digital marketplace and performing analysis on any received feedback may be stored in the ROM

610 and/or the RAM **615**. Optionally, the program instructions may be stored on a tangible computer readable medium such as a compact disk, a digital disk, flash memory, a memory card, a USB drive, an optical disc storage medium, such as a Blu-ray™ disc, and/or other recording medium.

[0047] An optional display interface **630** may permit information from the bus **600** to be displayed on the display **635** in audio, visual, graphic or alphanumeric format.

Communication with external devices may occur using various communication ports **640**.

An exemplary communication port **640** may be attached to a communications network, such as the Internet or an intranet. Other exemplary communication ports **640** may comprise a serial port, a RS-232 port, and a RS-485 port.

[0048] The hardware may also include an interface **645** which allows for receipt of data from input devices such as a keyboard **650** or other input device **655** such as a mouse, a joystick, a touch screen, a remote control, a pointing device, a video input device and/or an audio input device.

[0049] It will be appreciated that various of the above-disclosed and other features and functions, or alternatives thereof, may be desirably combined into many other different systems or applications. It will also be appreciated that various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which alternatives, variations and improvements are also intended to be encompassed by the following claims.

CLAIMS

What Is Claimed Is:

1. A system for dispensing a fluid, comprising:
 - a pump configured to force an aliquot of fluid from a fluid source into a fluid delivery channel;
 - at least one sensor configured to measure a sample value of a property of the aliquot;
 - a processor in communication with the pump and the at least one sensor; and
 - a non-transitory, computer-readable storage medium in operable communication with the processor, wherein the computer-readable storage medium contains one or more programming instructions that, when executed, cause the processor to:
 - receive the sample value,
 - receive a source value of the property for the fluid source,
 - determine a sample volume of the aliquot based on a comparison of the sample value and the source value, and
 - control operation of the pump to dispense a predetermined dose of the fluid based on a comparison of the sample volume with an expected volume.
2. The system of claim 1, wherein the computer-readable storage medium further contains one or more programming instructions that, when executed, cause the processor to determine a pump coefficient based on the comparison of the sample volume with the expected volume, the pump coefficient being configured to indicate a volume of fluid forced into the fluid delivery channel per unit.
3. The system of claim 2, wherein the pump coefficient comprises a volume-per-time coefficient.
4. The system of claim 2, wherein the pump coefficient comprises a volume-per-revolution coefficient.
5. The system of claim 2, wherein the one or more programming instructions that, when executed, cause the processor to control operation of the pump further comprise one or more programming instructions that, when executed, cause the processor to control operation of the pump using the pump coefficient.

6. The system of claim 2 wherein the one or more programming instructions that, when executed, cause the processor to control operation of the pump further comprise one or more programming instructions that, when executed, cause the processor to adjust the pump coefficient to correspond with dispensing the predetermined dose.
7. The system of claim 1, wherein the expected volume comprises a volume of the fluid forced by the pump under standard conditions.
8. The system of claim 1, wherein the fluid is selected from one of saline, chemotherapy drugs, radiopharmaceuticals, contrast agents, and combinations thereof.
9. The system of claim 1, wherein the pump is selected from the following: a turbine pump, a peristaltic pump, a diaphragm pump, a screw pump, a syringe pump, and a centrifugal pump.
10. The system of claim 1, wherein the pump comprises a peristaltic pump arranged to contact at least a portion of the fluid delivery channel such that operation of the pump compresses the at least a portion of the fluid delivery channel and forces the fluid from the fluid source toward a dispensing element through the fluid delivery channel,
wherein the sample volume of the aliquot is affected by at least one dimensional property of the fluid delivery channel.
11. The system of claim 10, wherein the at least one dimensional property comprises an inner diameter.
12. The system of claim 10, wherein the at least one dimensional property comprises an outer diameter.
13. A method of dispensing a fluid, comprising:
providing a pump configured to force an aliquot of fluid from a fluid source into a fluid delivery channel;
receiving, by a processor, a source value of a property for the fluid source and a sample value of the property for the aliquot measured by at least one sensor;

determining, by the processor, a sample volume of the aliquot based on a comparison of the sample value of the property and the source value of the property; and

controlling, by the processor, operation of the pump to dispense a predetermined dose of the fluid based on a comparison of the sample volume with an expected volume.

14. The method of claim 13, further comprising determining, by the processor, a pump coefficient based on the comparison of the sample volume with the expected volume, the pump coefficient being configured to indicate a volume of fluid forced into the fluid delivery channel per unit.

15. The method of claim 14, wherein the pump coefficient comprises a volume-per-time coefficient.

16. The method of claim 14, wherein the pump coefficient comprises a volume-per-revolution coefficient.

17. The method of claim 14, wherein controlling operation of the pump further comprises controlling the pump using the pump coefficient.

18. The method of claim 14, wherein controlling operation of the pump further comprises adjusting the pump coefficient to correspond with dispensing the predetermined dose.

19. The method of claim 13, wherein the expected volume comprises a volume of the fluid forced by the pump under standard conditions.

20. The method of claim 13, wherein the pump is selected from the group consisting of a turbine pump, a peristaltic pump, a diaphragm pump, a screw pump, a syringe pump, and a centrifugal pump.




FIG. 1

2/5




FIG. 2




FIG. 3

3/5




FIG. 4

4/5




FIG. 5

5/5




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US2014/019430

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - A61M 5/14 (2014.01)

USPC - 604/19

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC(8) - A61M 1/00, A61M 5/00, A61M 5/14, A61M 5/142 (2014.01)

USPC - 604/19, 604/67, 604/93.01, 604/123, 604/890.1

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

CPC - A61M 1/00, A61M 5/00, A61M 5/14 (2014.02)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Orbit, Google Patents, Google

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 616587 A1 (BUCK et al) 18 January 2006 (18.01.2006) entire document	1, 7-11, 13, 19, 20

Y		2-6, 12, 14-18
Y	WO 1999/23386 A (SAHLIN et al) 14 May 1999 (14.05.1999) entire document	2-6, 14-18
Y	US 5,217,355 A (HYMAN et al) 08 June 1993 (08.06.1993) entire document	12



Further documents are listed in the continuation of Box C.



* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

04 June 2014

Date of mailing of the international search report

24 JUN 2014

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Blaine R. Copenheaver

PCT Helpdesk: 571-272-4300

PCT OSP: 571-272-7774