

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 February 2003 (20.02.2003)

PCT

(10) International Publication Number
WO 03/014942 A1

(51) International Patent Classification⁷: **G06F 12/08**,
H04L 12/28

(21) International Application Number: PCT/EP01/09640

(22) International Filing Date: 3 August 2001 (03.08.2001)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **SALO, Juha** [FI/FI]; Noppakatu 6 b 3, FIN-20660 Littainen (FI). **AALTONEN, Janne** [FI/FI]; Hirvikoirankatu 15, FIN-20900 Turku (FI).

(74) Agents: **HAWS, Helen** et al.; Nokia IPR Department, Nokia House, Summit Avenue, Farnborough, Hampshire HU14 0NG (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD, SYSTEM AND TERMINAL FOR DATA NETWORKS WITH DISTRIBUTED CACHES



(57) Abstract: The present invention provides a method of accessing data on a network from a user terminal having a local store and wherein the network is accessed via a service provider, comprising: requesting data; determining whether the requested data is available from the local store and if the data is not available from the local store requesting the requested data from the service provider; and receiving, at the local store, a selection of data from the service provider.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

METHOD, SYSTEM AND TERMINAL FOR DATA NETWORKS WITH DISTRIBUTED CACHES

The present invention relates to improvements in network configuration and, more particularly, to improving the system performance, especially in remote
5 network access.

Use of the Internet is expanding rapidly, however the speed of access can still be frustratingly slow. One of the reasons for this is the way in which information is accessed from the Internet, as outlined in Figure 1. A home
10 user with a user terminal 108 typically connects to the Internet 100 using a dial-up connection 110 to an Internet service provider (ISP) 102, via a telecommunications network 112. When the user terminal 108 requests data from the Internet 100, the ISP 102 will first try to supply that information from large caches 106 which are maintained by the ISP. The caches are huge
15 storage devices, which can typically store many terabytes of data. If the required data is not available in the cache, the ISP requests the data from the Internet and supplies the data to the user terminal 108. The connection 104 between the ISP and the Internet is costly, and is one of the reasons why ISPs maintain such caches. The requested data may be stored in the cache
20 so that if the same data is requested by another user at a later date, the ISP can source the data directly, without having connect to the Internet directly. One of the downsides with such a system is that all data is sourced from the ISP, and data which is not in the ISP cache must be sourced from the Internet. Consequently, retrieving data can be slow.

25

Currently, a number of Internet browsers, such as Microsoft Internet Explorer and Netscape Navigator, which run on user terminals, keep a local copy of data requested from the ISP. In this way, data which is requested frequently by a user should be available locally, without having to access the ISP. Whilst
30 such a solution can increase the amount of data which is sourced locally, no improvement in performance is achieved when requesting data which has not previously been requested by a user, as such data must still be sourced from

the ISP in the manner described above. Similarly, when such data as, for example, the pages of an electronic newspaper which are updated daily or hourly are requested, the local copy is likely to be out-of-date. The present solution is not satisfactory for frequently changing data, as such data must still
5 be sourced from the ISP to ensure that it is up-to-date.

Accordingly, one aim of the present invention is to overcome the above mentioned problems.

10 According to a first aspect of the present invention, there is provided a method of accessing data on a network from a user terminal having a local store, wherein the network is accessed via a service provider, and wherein the service provider maintains a cache of data available on the network, comprising: requesting data; determining whether the requested data is
15 available from the local store and if the data is not available from the local store requesting the requested data from the service provider; and receiving, at the local store, a selection of data from the service provider.

According to a second aspect of the present invention, there is provided a
20 user terminal for accessing data on a network, the user terminal having a local store, and wherein the network is accessed via a service provider and wherein the service provider maintains a cache of data available on the network, comprising: means for requesting data; a processor for determining whether the requested data is available from the local store; a transceiver for
25 requesting the requested data from the service provider when the requested data is not available from the local store; means for receiving a selection of data from the service provider and storing the received data in the local store.

Advantageously, the present invention speeds up user access of the most
30 frequently accessed or most popular information. By keeping a local copy at the user terminal of selected information from the ISP cache increases the probability that requested data is available locally, without having to access the ISP. Additionally, information may be accessed free of charge without

having to connect to an ISP. Further benefits include reducing the demand on existing dial-up servers, since much of the requested information will be sourced locally. For the ISP, the present invention may be used as a further revenue source by charging users for receiving local cache data.

5

The invention will now be described, by way of example only, with reference to the accompanying diagrams, in which:

Figure 1 is a block diagram showing an overview of a system according to the prior art;

10

Figure 2 is a block diagram showing an embodiment of a user terminal according to the present invention;

Figure 3 is a block diagram showing an embodiment of a service provider according to the present invention;

15 Figure 4 is a block diagram showing an overview of a system according to an embodiment of the present invention; and

Figure 5 is a block diagram showing one embodiment of the user terminal 200 in greater detail.

20 Figure 1 is a block diagram showing an overview of a system according to the prior art, as described above.

Figure 2 is a block diagram showing a first embodiment of a user terminal according to the present invention. The user terminal 108 of Figure 1 is replaced by a user terminal 200 comprising a local cache 202. The local cache 202 can be any storage device with a high capacity, and preferably allows rapid access to the data stored thereon. In a preferred embodiment of the present invention the cache is a high capacity hard disk drive.

25

30 The present invention is based on the concept that a selection of the data stored on the ISP cache 106 is downloaded onto the local cache 202. When a user terminal requests data from the Internet, the local cache is checked first of all to see if the requested data is present. If it is present, the data is

sourced from the local cache. If the data is not in the local cache, a connection is made with the ISP in the normal manner and the data is sourced by the ISP. By storing a selection of data locally at the user terminal speeds up access times for data which is present in the cache. Requested
5 data which was sourced from the ISP may optionally be stored in the local cache 202.

The way in which data is selected for use in the local cache is described below.

10

Figure 3 is a block diagram showing an embodiment of a service provider according to the present invention. The ISP 500 is similar to the ISP 102 of Figure 1 but additionally comprises an analyser module 502 for keeping and analysing statistics of the usage of the data stored in the caches 106. For
15 example, each time data is requested, by any user, from one of the caches 106, the analyser keeps track of the number of times that data has been requested (this is commonly referred to as the number of hits).

The analyser 502 effectively classifies the cached data according to
20 popularity, and enables all requested data to be ranked according to the number of hits. The analyser can logically reorganise the data on the caches 106 according to the rank, or alternatively may keep a separate listing of ranked data and a link to the actual location of that data on the cache.

25 The data stored in the ISP cache is based on the requested data from all the user terminals which connect to the ISP. In this way, given the large numbers of users who use an ISP, there is a high probability that the data requested by any individual user will be present in the ISP cache. Caches typically use a renewal algorithm to regularly remove data which has not been accessed
30 recently, thereby ensuring that predominantly only popular information is stored in the cache.

According to one embodiment of the present invention the ISP 500 can arrange for a selection of the ISP cache to be transmitted to the local cache. The part of the ISP cache transmitted could be, for example, 10Gb of the data with the most hits. If the user terminal receiving this data has a cache smaller
5 than the amount of data being transmitted, it is preferred that the local cache is filled with the most popular data first.

In an alternative embodiment, the ISP cache can be classified into data of different subject areas, and the data in each subject area can be further
10 ranked according to the number of hits. In this embodiment, all of the data is transmitted to the local cache, and the processor 406 of the user terminal decides whether to accept data from each category depending on predefined user preferences. In yet a further alternative embodiment, the ISP can store user preferences for each user terminal, and download the selection of cache
15 data only to those user terminals with matching preferences, using for example a multicast protocol.

By storing the most popular data of the ISP cache in the local cache increases the likelihood that the data required by the user will be found in the local
20 cache.

The present invention provides a number of embodiments offering different ways in which the selected data may be downloaded from the ISP to the local
25 cache.

In one embodiment, the selected data is downloaded over the normal dial-up connection 110. In a further, preferred, embodiment, the user terminal is adapted to receive data from a broadcast or broadband network, as exemplified in Figure 4. Any suitable point-to-point network could also be
30 used. In this embodiment, the ISP 500 transmits the selection of data for downloading to the local cache to the network 300 from where the data is transmitted to one or more user terminals. Examples of suitable networks include digital video broadcast (DVB) and synchronous digital subscriber line

(ADSL). In the case of a broadcast network, such as a DVB network, the very high bandwidths and large coverage makes this an ideal medium for transmitting the selection of data to a large number of user terminals.

- 5 The user terminal is preferably arranged to receive the selection of data based on a predetermined schedule, for example, to allow the data to be downloaded overnight or at another time when the user terminal is not in use. Obviously, the user terminal would have to be powered-up in order to receive such a transmission.

10

Figure 5 is a block diagram showing one embodiment of the user terminal 200 in greater detail. The user terminal 200 comprises a transceiver 404 for connecting with an ISP via a telecommunications network, as shown in Figure 3. A receiver 402 is also provided for receiving data from a second network, such as a broadband or broadcast network, as described above. A processor 406 controls the receiver 402, the transceiver 404, a user interface 408, a display 410 and a local cache 202. The user interface 408 and the display 410 enable the user to operate the user terminal as will be appreciated by those skilled in the art. The receiver 402 can be any suitable receiver for receiving data from the network 300. For example, if the network 300 is a DVB network, the receiver 402 is a DVB receiver. The receiver 402 receives a selection of data from the ISP cache and stores the received data, or part of the received data, in the cache 202. Subsequently, when a user requests data from the Internet, the processor first of all checks to see whether the data is available in the cache 202. If the data is available, it is sourced from the cache, otherwise a connection with the ISP is made via the transceiver 404 and the data is sourced from the ISP. The processor 406 also includes a scheduler to enable the selection of data to be received by the receiver 402 and stored in the cache 202 as appropriate. The scheduler may also include timers which can be arranged to power-on the user terminal at a predetermined time in order to receive a scheduled transmission of data. The user terminal 200 also includes an analyser 412, the function of which is described below.

The selection of data from the ISP cache to be downloaded to the local user terminal cache is of prime importance. If the data on the local cache is not representative of the type of the data the user is likely to try and access, then browsing times may well be reduced, due to the additional step of determining whether requested data is present on the local cache, prior to connection to the ISP.

As previously mentioned, the cache of an ISP may typically have a capacity of many terabytes, whereas the local cache is likely to be in the order of tens of gigabytes. Additionally, different user terminals are likely to have caches of differing sizes.

As a result of present invention, much of the data requested by the user will be sourced from the local cache, not from the ISP, eliminating the need to connect to the ISP and greatly increasing performance. In order to maintain accurate usage statistics on the ISP cache, for example for classifying the data according to the number of hits, the user terminal preferably needs to collect the usage data and to provide the ISP with the statistics. Additionally, many Internet pages contain adverts, hits counters and the like, for which the usage statistics also need to be accurately reported back to the advertisers. The analyser 412 shown in Figure 5 performs just such tasks. The statistical information from the analyser 412 can be fed back to the ISP via the transceiver 404, either on an ad-hoc basis whilst connected to the ISP or, alternatively, this task could be scheduled to take place overnight or when the user terminal is not in use.

The user terminal 200 of Figure 5 may additionally comprise a security module (not shown) under control the processor 406 which is used to scramble the contents of the local cache. Since the local cache represents the most frequently requested data from a number of different users, it could be possible to analyse the cache data to discover the kind of data other users are requesting. If the majority of users of an ISP work, for example, for one company, other users of the ISP could possibly determine, from the local

cache, information which could be prejudicial to that company. Scrambling of the local cache would prevent such analysis, and would help protect the privacy of users. Those skilled in the art will appreciate that there are numerous ways in which such scrambling could be performed, and such techniques will not be discussed herein.

In yet a further embodiment of the present invention, the selection of data transmitted by the service provider could alternatively be determined by the service provider according to parameters other than based on the usage statistics of data in the ISP cache. For example, the service provider may provide its own data to user terminals, for example, data which is supplied from a private network. In a further example, the ISP could search the Internet for information about specific topics, and transmit this information to specific users of groups of users. For example, a chemical research centre may wish to receive only information about chemical research, and would not be interested in receiving information regarding other topics.

The frequency at which the local cache is updated may be changed depending on, for example, different subscription levels paid by a user. On a basic subscription level, the local cache may only be updated nightly, whereas for a premium user the cache may be updated several times a time. Additionally, it may be possible for a user to request a download of cache data at an alternative time.

The present invention can be applied to both home user terminals, using for example a telephone dial-up connection, and to mobile user terminals. Mobile user terminals could use, for example, the wireless application protocol (WAP), and could connect to an ISP via any kind of typical mobile communication protocol, including GSM, GPRS, WCDMA, etc.

CLAIMS

1. A method of accessing data on a network from a user terminal having a local store and wherein the network is accessed via a service provider,
5 comprising:
requesting data;
determining whether the requested data is available from the local store
and if the data is not available from the local store requesting the
requested data from the service provider; and
10 receiving, at the local store, a selection of data from the service provider.
2. The method of claim 1, wherein the service provider maintains a cache of data available on the network and further wherein the selection of data from the service provider is a selection of data from the cache of data.
15
3. The method of claim 1 or 2, further comprising, selecting a portion of the cache for transmission to the user terminal.
4. The method of claim 2, wherein in the step of selecting further comprises
20 classifying data in the cache according to popularity and selecting a selection of classified data.
5. The method of claim 4, further comprising storing, at the user terminal, a number of predefined user preferences and further wherein the step of
25 receiving is adapted to only receiving data having a classification which matches the defined user preferences.
6. The method of claim 3 or 4, further comprising storing, at the service provider, a number of predefined user preferences and transmitting the
30 selection of data to a user terminal based upon the stored user preferences.

7. The method of any preceding claim, wherein the step of receiving is adapted to receive the selection of data according to a predetermined schedule.
- 5 8. The method of any preceding claim, further comprising encrypting the contents of the local store.
9. The method of any preceding claim, wherein the steps of requesting data and supplying the requested data are adapted for requesting data via a
10 first telecommunications network.
10. The method of any preceding claim, wherein the step of receiving the selection of data is adapted for receiving the data via a second telecommunications network.
- 15 11. The method of claim 10, wherein the first telecommunications network is a point-to-point network.
12. The method of claim 10 or 11, wherein the second telecommunications
20 network is a broadcast network.
13. A user terminal for accessing data on a network, the user terminal having a local store, and wherein the network is accessed via a service provider and wherein the service provider maintains a cache of data available on
25 the network, comprising:
means for requesting data;
a processor for determining whether the requested data is available from the local store;
a transceiver for requesting the requested data from the service provider
30 when the requested data is not available from the local store;
means for receiving a selection of data from the service provider and storing the received data in the local store.

14. The user terminal of claim 13, further comprising means for storing user preferences and wherein the means for receiving the selection of data is adapted to receive data corresponding to the stored user preferences.
- 5 15. The user terminal of claim 13 or 14, further comprising a scheduler to control the means for receiving to thereby receive the selection of data according to a predetermined schedule.
- 10 16. The user terminal of claims 13, 14 or 15, further comprising encryption means for encrypting and decrypting the contents of the local store.
17. The user terminal of any of claims 13 to 16, wherein the transceiver is adapted for use with a first telecommunications network.
- 15 18. The user terminal of any of claims 13 to 17, wherein the means for receiving is adapted for use with a second telecommunications network.
19. The user terminal of claims 17 or 18, wherein the first telecommunications network is a point-to-point network.
- 20 20. The user terminal of claims 17, 18, or 19, wherein the second telecommunications network is a broadcast network.
21. The user terminal of any of claims 13 to 20, wherein the means for receiving the selection of data is the transceiver.
- 25 22. A system for accessing data on a network according to any preceding claim.
- 30 23. A user terminal for accessing data on a network from a user terminal having a local store, and wherein the network is accessed via a service provider, comprising:
means for requesting data from the network;

a processor for determining whether the requested data is available from the local store and if the data is not available from the local store requesting the requested data from the service provider;
a receiver for receiving a selection of data from the service provider, the
5 selection of data being as determined by the service provider and containing data not exclusively based on the data requested by the user terminal.

24. A method of accessing data on a network from a user terminal having a
10 local store and wherein the network is accessed via a service provider, comprising:
requesting data;
determining whether the requested data is available from the local store and if the data is not available from the local store requesting the
15 requested data from the service provider; and
receiving, at the local store, a collection of data from the service provider, the collection of data being as determined by the service provider and containing data based not exclusively on the data requested by the user terminal.

20

25. A method of accessing data on a network substantially as hereinbefore described with reference to the Figures 2 to 5.

26. A user terminal for accessing data on a network substantially as
25 hereinbefore described with reference to the Figures 2 to 5.

27. A system for accessing data on a network substantially as hereinbefore described with reference to the Figures 2 to 5.

1 / 3







FIG. 2

2 / 3






FIG. 5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/09640

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G06F12/08 H04L12/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F H04L H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 0 010 061 A (MATSUMOTO H) 26 July 2001 (2001-07-26) page 2, column 2, line 52 -page 4, column 2, line 65 page 5, column 2, line 55 -page 6, column 1, line 35; claims 1,2,6; figure 4 abstract ---	1-9, 13-17, 21-24
X	WO 00 42519 A (EDGIX CORP) 20 July 2000 (2000-07-20) page 2, line 7 -page 3, line 20 page 4, line 22 -page 8, line 3; claims 1,6,7; figures 1,2 abstract --- -/--	1-4, 7-13, 15-24

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

19 February 2002

Date of mailing of the international search report

19. 03. 2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Kristoffer Ogebjer

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 01/09640

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	W0 99 48009 A (SKYCACHE INC) 23 September 1999 (1999-09-23) page 4, line 15 -page 6, line 9 page 16, line 1 -page 17, line 9; figures 1,2 abstract ---	1-4, 7-13, 15-24
A	EP 1 059 763 A (HUGHES ELECTRONICS CORP) 13 December 2000 (2000-12-13) page 3, line 55 -page 4, line 24 page 5, line 1 - line 29 page 6, line 5 - line 40 page 7, line 20 -page 8, line 48; figures 1,4,5 abstract ---	1-24
A	EP 0 836 145 A (AT & T CORP) 15 April 1998 (1998-04-15) page 2, column 2, line 1 - line 30 page 3, column 1, line 1 -column 4, line 51; figure 1 abstract ---	1-24
X	US 013 088 A (MATSUMOTO H) 9 August 2001 (2001-08-09) page 2, column 1, line 22 -page 4, column 1, line 35 page 4, column 2, line 27 -page 5, column 1, line 45; claims 1,2; figure 2 abstract -----	1-9, 13-17, 21-24

INTERNATIONAL SEARCH REPORT

International application No.
PCT/EP 01/09640

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: **25-27**
because they relate to subject matter not required to be searched by this Authority, namely:
see FURTHER INFORMATION sheet PCT/ISA/210
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box I.1

Claims Nos.: 25-27

According to rule 6.2 (a) claims shall not, except where absolutely necessary, relay, in respect of the technical features of the invention, on references to the description or drawings. In particular, they shall not relay on such references as: "as illustrates in figure.... of the drawings."

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/09640

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 0010061	A	NONE	
WO 0042519	A	20-07-2000	
		AU 2847700 A	01-08-2000
		WO 0042519 A1	20-07-2000
		AU 1953301 A	18-06-2001
		WO 0142941 A1	14-06-2001
WO 9948009	A	23-09-1999	
		US 5987233 A	16-11-1999
		AU 2905599 A	11-10-1999
		BR 9908772 A	05-12-2000
		EP 1073962 A1	07-02-2001
		WO 9948009 A1	23-09-1999
EP 1059763	A	13-12-2000	
		EP 1059763 A2	13-12-2000
EP 0836145	A	15-04-1998	
		US 5931904 A	03-08-1999
		CA 2217370 A1	11-04-1998
		EP 0836145 A2	15-04-1998
		JP 10214239 A	11-08-1998
		US 6240447 B1	29-05-2001
US 013088	A	NONE	