



EP 1 739 203 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
03.01.2007 Bulletin 2007/01

(51) Int Cl.:
C23C 8/20 (2006.01)

(21) Application number: **06253302.1**

(22) Date of filing: **26.06.2006**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IS IT LI LT LU LV MC NL PL PT RO SE SI
SK TR**
Designated Extension States:
AL BA HR MK YU

(30) Priority: **28.06.2005 US 694759 P
11.10.2005 US 247874**

(71) Applicant: **The General Electric Company
Schenectady NY 12345 (US)**

(72) Inventor: **Bruce, Robert William
Loveland, Ohio 45140 (US)**

(74) Representative: **Pedder, James Cuthbert et al
London Patent Operation,
General Electric International, Inc.,
15 John Adam Street
London WC2N 6LU (GB)**

(54) Titanium treatment to minimize fretting

(57) A method for surface treating a titanium gas turbine engine component. The method includes providing a gas turbine engine component having a titanium-containing surface. The component is heated to a temperature sufficient to diffuse carbon into the titanium and below 1000 °F. The surface is contacted with a carbon-containing gas to diffuse carbon into the surface to form carbides. Thereafter, the carbide-containing surface is

coated with a lubricant comprising a binder and a friction modifier. The binder preferably including titanium oxide and the friction modifier preferably including tungsten disulfide. The coefficient of friction between the surface and another titanium-containing surface is less than about 0.6 in high altitude atmospheres.

EP 1 739 203 A1

Description

[0001] The present invention is directed to a method for surface treating titanium and titanium alloys. In particular, the invention is drawn to surface treating gas turbine engine components.

[0002] A gas turbine engine generally operates by pressurizing air in a compressor and mixing the air with fuel in a combustor. The air/fuel mixture is ignited and hot combustion gasses result, which flow downstream through a turbine section. The compressor typically includes compressor disks having airfoils dovetailed into the compressor disk. The compressor may include multiple disks, each having a plurality of airfoils.

[0003] Each of the compressor disk and the airfoils typically contain titanium, usually in the form of a titanium alloy. The titanium-to-titanium surface contact is susceptible to fretting wear and fretting fatigue. Fretting is the degradation of the surface usually resulting from localized adhesion between the contacting surfaces as the surfaces slide against each other. The problem of fretting is magnified in systems having a titanium-containing surface contacting another titanium-containing surface. For example, in a titanium compressor disk and titanium airfoil system, the fretting fatigue may result from movement of the dovetail of the airfoil within the slot in the compressor disk. As the disk rotates at a higher rotational speed, the centrifugal force on the airfoil urges the blade to move outward and slip along the surface of the dovetail. As the disk rotates at a lower rotational speed, the centrifugal force on the airfoil is less and the airfoil may slip inward toward the compressor disk. A second source of movement resulting in fretting fatigue in the dovetail system is the vibration from the airfoil. Aerodynamic forces may result in oscillation of the airfoil within the dovetail slot. The oscillation translates to high frequency vibration through the airfoil to the dovetail portion of the airfoil. As the airfoil vibrates, the surface of the dovetail section of the airfoil slides against the surface of the slot of the compressor disk, resulting in fretting fatigue.

[0004] In an attempt to solve the fretting wear and fatigue problem, the titanium dovetail surface of the airfoil may be shot-peened to create compressive stress in the airfoil surface. The increased compressive stress on the surface results in increased hardness, which reduces the adhesion between surfaces thereby reducing the fretting fatigue and wear. However, the shot-peening process requires expensive equipment, additional processing steps and may result in surfaces having variability in roughness and dimensional accuracy. In addition, the shot-peened surface provides insufficient resistance to fretting fatigue and wear.

[0005] In another attempt to solve the fretting wear and fatigue problem, a coating of CuNiIn, aluminum bronze or a MoS₂ lubricant may be coated onto the airfoil's dovetail surface to provide a surface that experiences less adhesion between surfaces. The application of lubricants such as MoS₂ provides some protection from localized

adhesion, but the lubricants alone, without additional coating layers, fail to provide sufficient resistance to fretting fatigue and wear.

[0006] Carburizing is a method that has been used to increase hardness of a surface. It is a well-known method for hardening steel surface to improve wear properties. Known carburizing methods take place at high temperatures, including temperatures of greater than about 1700 °F (927 °C). High temperature carburization methods suffer from the drawback that the method requires expensive, specialized equipment, capable of operating under high temperatures. High-temperature thermal treatments of blade dovetails and disks preclude use of conventional carburizing practices.

[0007] What is needed is an inexpensive, low-temperature titanium treatment that reduces fretting fatigue and wear that does not suffer from the drawbacks of the prior art.

[0008] The present invention includes a method for surface treating a gas turbine engine component comprising a titanium or titanium alloy. The method includes providing a gas turbine engine component having a titanium-containing surface. The component is heated to a temperature sufficient to diffuse carbon into the titanium and below 1000 °F. The surface is contacted with a carbon-containing gas to diffuse carbon into the surface to form carbides and/or interstitial carbon. Thereafter, the carbon-containing surface may be coated with a lubricant to further reduce the coefficient of friction between surfaces. The coefficient of friction between the surface and another titanium-containing surface is preferably less than about 0.6.

[0009] In accordance with the present invention, a metallic surface comprising titanium is carburized, under controlled conditions, using carbon-containing gases, such as methane, propane, ethylene or acetylene gas or combinations thereof as the carburizing agent in order to form stable carbides and/or interstitial carbon at a controlled, preselected distance below the surface and/or diffuse the carbon interstitially in the titanium matrix. The carbides formed in the surface harden the surface, providing a reduced coefficient of friction, and reducing fretting.

[0010] Another embodiment of the present invention includes a gas turbine engine component having a titanium-containing compressor disk. The compressor disk including a surface containing carbides and/or interstitial carbon and a lubricant coating thereon having a binder and a friction modifier. The binder preferably including titanium oxide and the friction modifier preferably including tungsten disulfide.

[0011] Another embodiment of the present invention includes a gas turbine engine component having a titanium-containing airfoil. The airfoil including one or more surfaces that contain carbides and/or interstitial carbon and a lubricant coating thereon.

[0012] While the present invention contemplate the formation of titanium carbide, titanium alloys may include

other carbide forming elements, such as, for example, vanadium. For example, alloys containing vanadium treated according to the present invention may include vanadium carbides, in addition to titanium carbides.

[0013] One advantage of an embodiment according to the present invention is that the method according to the present invention decreases the susceptibility of the surface to fretting.

[0014] Another advantage of an embodiment of the present invention is that the method provides a hardened surface having carbides and/or interstitial carbon, which resist corrosion.

[0015] Another advantage of an embodiment of the present invention that the method according to the present invention provides a hardened surface that is resistant to erosion.

[0016] Another advantage of an embodiment of the present invention is that the carburization takes place at a low temperature, below 1000 °F, which reduces the cost of equipment required to produce the carburized zone.

[0017] Another advantage of an embodiment of the present invention is that the surfaces subjected to fretting wear and fatigue may be replaced less often, decreasing servicing cost and reliability.

[0018] The invention will now be described in greater detail, by way of example, with reference to the drawings, in which:-

FIG. 1 is a cutaway view of a section of a known high-pressure compressor for a turbine engine according to the present invention

FIG. 2 shows a perspective view of a compressor disk according to an embodiment of the present invention.

FIG. 3 shows a cutaway view of an airfoil dovetail positioned in a slot of a compressor disk according to the present invention.

FIG. 4 shows an enlarged cross-sections taken from FIG. 3 showing an embodiment of the present invention.

FIG. 5 shows an enlarged cross-sections taken from FIG. 3 showing an alternate embodiment of the present invention.

FIG. 6 shows an enlarged cross-sections taken from FIG. 3 showing an alternate embodiment of the present invention.

FIG. 7 shows an enlarged cross-sections taken from FIG. 3 showing an alternate embodiment of the present invention.

FIG. 8 shows an enlarged cross-section taken from

FIG. 3 showing an alternate embodiment of the present invention.

FIG. 9 shows an enlarged cross-section taken from FIG. 3 showing an alternate embodiment of the present invention.

[0019] FIG. 1 is a cutaway view of a section of a high-pressure compressor for a turbine engine according to the present invention. The compressor includes a plurality of blades 100. The blades 100 include an airfoil 101 and a dovetail 103, which is positioned within dovetail slots 105 in a compressor disk 107. The dovetail 103 of the blade 100 retains the blade 100 during operation of the gas turbine engine. The blade 100 and the compressor disk 107 according to the invention include titanium and have one or more surfaces that are in frictional contact that are carburized to produce a surface having a carburized zone 401 (see FIGs. 4-9). In addition, one or more of the surfaces of the dovetail 103 and dovetails slots 105 of the compressor disk 107 may be coated with a lubricant coating 601 (see FIGs. 6-9). Although FIG. 1 illustrates a compressor disk 107 and blade 100, any titanium or titanium alloy surface may be treated according to an embodiment of the invention

[0020] FIG. 2 shows a perspective view of a compressor disk 107 according to an embodiment of the present invention, wherein FIG. 2 shows dovetail slots 105 into which the dovetail 103 section of blades 100 are positioned. The surfaces of dovetail slots 105 are subjected to sliding friction with dovetail 103 of blades 100 and are susceptible to fretting. The surface of compressor disk 107 includes a carburized zone 401 and, optionally, a lubricant coating 601 (see FIGs. 4-9).

[0021] FIG. 3 shows a cutaway view of a blade 100 positioned in dovetail slots 105 of compressor disk 107 according to an embodiment of the present invention. At least a portion of the surface of slot 105 is in frictional contact with at least a portion of the surface of dovetail 103. As the gas turbine engine operates, the centrifugal forces provided by the variation of the rotational speed of the compressor disk 107 results in rubbing between the surface of the dovetail 103 and the surface of the dovetail slot 105 in the compressor disk 107. The coefficient of friction between the surfaces of the dovetail 103 and the surface of the slot 105 are preferably maintained below 0.6. Preferably, the coefficient of friction is below 0.4. More preferably, the coefficient of friction is below 0.2. The lowering of the coefficient of friction is a result of the hardened surface resulting from the carburization. The carburized zone 401 (see FIGs. 4-9) has a greater hardness than an untreated titanium-containing surface. In addition, the application of a lubricant coating 601 (see FIGs. 6-9) further decreases the coefficient of friction. The additional lowering of the coefficient of friction is a result of the tribological properties of components of the lubricant coating 601.

[0022] FIGs. 4-9 shows enlarged cross-sections taken

from region 301 from FIG. 3 illustrating alternate coating arrangements according to the present invention. The cross sections in FIGs 4-9 each include a dovetail slot 105 of compressor disk 107 and dovetail 103 in frictional contact. The surface of the dovetail slot 105 of compressor disk 107 and the surface of the dovetail 103 form opposed surfaces onto which a carburized zone 401 and lubricant coating 601 may be applied. FIGs. 4-9 illustrate alternate locations for placement of the carburized zone 401 and lubricant coating 601. Lubricant coating 601 may be disposed on the dovetail 103, the dovetail slot 105 of the compressor disk 107, a carburized dovetail 103 or a carburized dovetail slot 105 of the compressor disk 107 or on a combination thereof. The optional coating 601 may include, but is not limited to, graphite, CuNiIn, aluminum bronze or MoS₂. Although a space has been shown between the coatings on the compressor disk 107 and the dovetail 103 in FIGs. 4-9, the space is merely illustrative of the placement of the coatings. The coating systems on each of the surface of the dovetail slot 105 and the dovetail 103 are in frictional contact, wherein the surfaces are adjacent and experience sliding or rubbing. Also, FIGs. 4-9 are shown having thicknesses of the carburized zone 401 and lubricant coating 601 that is merely illustrative and does not indicate the relative thickness of the carburization zone 401 or the lubricant coating 601.

[0023] FIG. 4 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an embodiment of the present invention. FIG. 4 includes dovetail 103 interfacing with the dovetail slot 105 of compressor disk 107. Surface 403 of the dovetail slot 105 of compressor disk 107 and surface 409 of dovetail 103 have each been carburized and include carburized zone 401. Surface 405 includes the surface of the carburization coating 401 on the compressor disk and is in frictional contact with surface 407. Surface 407 is the surface of the carburized zone 401 on surface 409 of dovetail 103. The embodiment shown in FIG. 4 has the benefit that carburized zone 401 is provided on both the dovetail and compressor disk 107 providing hardened sliding surfaces that slide against each other providing desirable tribological properties. In particular, the combination of the hard, wear resistant carburized zone 401 sliding against each other provide a low coefficient of friction and increased fretting resistance.

[0024] FIG. 5 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an alternate embodiment of the present invention. FIG. 5 includes dovetail 103, dovetail slot 105 of compressor disk 107, as shown in FIG. 4. Surface 403 of the dovetail slot 105 of compressor disk 107 has been carburized and includes carburized zone 401. Surface 405 includes the surface of the carburized zone 401 on the dovetail slot 105 on compressor disk 107 and is in frictional contact with surface 409 of dovetail 103. The embodiment shown in FIG. 5 has the benefit that the carburized zone 401 is coated only on the compressor disk 107. Therefore, the application of carburized zone 401 requires less equipment

and labor than applying carburized zone 401 to both the compressor disk 107 and the blade 100.

[0025] FIG. 6 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an alternate embodiment of the present invention. FIG. 6 includes dovetail 103, dovetail slot 105 of compressor disk 107, as shown in FIG. 4. Surface 403 of the dovetail slot 105 of compressor disk 107 has been carburized and includes carburized zone 401. Lubricant coating 601 is disposed on surface 405 of the carburized zone 401. Surface 603 of lubricant coating 601 is in frictional contact with surface 409 of dovetail 103. The embodiment shown in FIG. 6 has the benefit that the carburized zone 401 and lubricant coating 601 are coated only on the compressor disk 107. Therefore, the production of carburized zone 401 requires less equipment and labor than producing carburized zone 401 to both the dovetail slot of compressor disk 107 and the airfoil. In addition, the compressor disk 107 is protected from fretting damage, whereas the less expensive, easier to replace blade 100 has not been specially treated. The carburized zone 401 and lubricant coating 601 provide protection of the compressor disk 107 and blade 100 system, while not adding expense to the blades 100.

[0026] FIG. 7 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an alternate embodiment of the present invention. FIG. 7 includes dovetail 103, dovetail slot 105 of compressor disk 107, as shown in FIG. 4. Surface 409 of dovetail 103 of blade 100 has been carburized and includes carburized zone 401. Lubricant coating 601 is disposed on surface 407 of the carburized zone 401. Surface 603 of lubricant coating 601 is in frictional contact with surface 403 of the dovetail slot 105 of compressor disk 107. The embodiment shown in FIG. 7 has the benefit that the carburized zone 401 and lubricant coating 601 are coated only on dovetail 103 of blade 100. Coating only the dovetail 103 has the advantage that the blades 100 may easily be removed from the compressor disk 107 in order to be coated according to the present invention. The compressor disk 107 and blade 100 system of the present invention may be retrofitted into existing gas turbine engines by removing the blades 100 from the compressor disks 107, wherein the removal of the compressor disk 107 from the engine is not necessary. In this embodiment, the dovetail 103 may provide the resistance to fretting without requiring the removal or replacement of the compressor disks 107 from the engine.

[0027] FIG. 8 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an alternate embodiment of the present invention. FIG. 8 includes dovetail 103, dovetail slot 105 of compressor disk 107, as shown in FIG. 4. Surface 403 of the dovetail slot 105 of compressor disk 107 has been carburized and includes carburized zone 401. Lubricant coating 601 is disposed on surface 409 of the dovetail 103. Surface 603 of lubricant coating 601 is in frictional contact with surface 405 of carburized zone 401 on the dovetail slot 105 of com-

pressor disk 107. The embodiment shown in FIG. 8 has the benefit that the carburized zone 401 is present on the dovetail slot 105 of compressor disk 107 protecting the surface from fretting. In addition, the dovetail 103 of blade 100 is coated with lubricant coating 601. The lubricant coating 601 may be easily replaced by removing the blade 100 from compressor disk 107 and coating the lubricant coating 601 onto dovetail 103 of blade 100. The lubricant coating 601 in this embodiment permits the easy replacement of the lubricant coating 601 in the event that the lubricant coating 601 wears thin or wears completely off.

[0028] FIG. 9 shows an enlarged cross-section taken from region 301 from FIG. 3 showing an alternate embodiment of the present invention. FIG. 9 includes dovetail 103, dovetail slot 105 of compressor disk 107, as shown in FIG. 4. Surface 403 of dovetail slot 105 of compressor disk 107 has been carburized and includes carburized zone 401. Surface 409 of dovetail 103 of blade 100 has also been carburized and includes carburized zone 401. Lubricant coating 601 is disposed on surface 407 of the carburized coatings 401, both on the dovetail 103 of blade 100 and on the dovetail slot 105 of compressor disk 107. Surface 603 of lubricant coating 601 on the carburized zone 401 on the dovetail slot 105 of compressor disk 107 is in frictional contact with surface 603 of lubricant coating 601 on the carburized zone 401 on the dovetail 103 of blade 100. The embodiment shown in FIG. 9 has the benefit that the carburized coating 401 and lubricant coating 601 are present on both the dovetail 103 of blade 100 and on the dovetail slot 105 on compressor disk 107, providing additional protection against fretting on both surfaces. In this embodiment, the coatings have additional protection against the lubricant coating 601 wearing off due to the two lubricant coatings 601. In addition, this embodiment permits the opposed hard, wear resistant carburized zone 401 surfaces to slide against each other provide a low coefficient of friction and increased fretting resistance with the addition fretting resistance provided by the lubricant coatings 601 disposed thereon.

[0029] The present invention also provides methods for carburizing a metallic surface comprising titanium. In one embodiment, titanium-containing blade 100 or compressor disk 107 for use in a gas turbine engine is subjected to carburizing. The surface for coating according to the present invention is preferably a titanium alloy. In one embodiment of the invention, the titanium alloy is Ti-6-4 titanium alloy having about 6 wt% aluminum, about 4 wt% vanadium and balance essentially titanium. Other suitable alloys for use in the blade 100 include, but are not limited to Ti-4-4-2 (about 4 wt% aluminum, about 4 wt% molybdenum, and about 2 wt% tin), Ti-6-2-4-2 (about 6 wt% aluminum, about 2 wt% molybdenum, about 4 wt% zirconium and about 2 wt% tin), Ti-8-1-1 (about 8 wt% aluminum, about 1 wt% molybdenum, and about 1 wt% vanadium). Other suitable alloys for use in the compressor disk 107 include, but are not limited to

Ti-17 (about 5 wt% aluminum, about 4 wt% chromium, about 4 wt% molybdenum, about 2 wt% zirconium and about 2 wt% tin) and Ti-6-2-4-2 (about 6 wt% aluminum, about 2 wt% molybdenum, about 4 wt% zirconium and about 2 wt% tin). Other suitable alloys for fabrication of compressor disk 107 for use with blades 100 having a carburized zone 401 include, but are not limited to, nickel-based alloys, such as INCONEL® 718, R-95, or R-88. INCONEL® is a federally registered trademark owned by Huntington Alloys Corporation of Huntington, West Virginia. The composition of INCONEL® 718 is well-known in the art and is a designation for a nickel-based superalloy comprising about 18 weight percent chromium, about 19 weight percent iron, about 5 weight percent niobium + tantalum, about 3 weight percent molybdenum, about 0.9 weight percent titanium, about 0.5 weight percent aluminum, about 0.05 weight percent carbon, about 0.009 weight percent boron, a maximum of about 1 weight percent cobalt, a maximum of about 0.35 weight percent manganese, a maximum of about 0.35 weight percent silicon, a maximum of about 0.1 weight percent copper, and the balance nickel. R-95 includes a composition having about 8% cobalt, about 13% chromium, about 3.5% molybdenum, about 3.5% tungsten, about 3.5% aluminum, about 2.5% titanium, about 3.5% niobium, about 0.03% boron, about 0.03% carbon, about 0.03% zirconium, up to about 0.01% vanadium, up to about 0.3% hafnium, up to about 0.01% yttrium and the balance essentially nickel. R-88 includes a composition having about 13% cobalt, about 16% chromium, about 4% molybdenum, about 4% tungsten, about 2% aluminum, about 3.7% titanium, about 0.75% niobium, about 0.4% zirconium, about 0.06% carbon, about 0.010% boron and the balance essentially nickel.

[0030] In accordance with the present invention, a metallic surface comprising titanium is carburized, under controlled conditions, using carbon-containing gases, such as methane, propane, ethylene gas, acetylene, carbon dioxide, carbon monoxide or combinations thereof as the carburizing agent in order to form stable carbides at a controlled, preselected distance below the surface. The carbides may include titanium carbides, vanadium carbides and mixtures thereof, including titanium-vanadium carbide complexes. These gases may be mixed in combination, or non-reactive gases such as argon, helium, or hydrogen may be added in order to control the reactivity of the carburizing gases. The titanium carbide formed in the surface hardens the surface, providing a reduced coefficient of friction, and reducing fretting. The concentration and/or presence of interstitial carbon in the titanium matrix can also be a controlling factor in the process.

[0031] The present invention may include a step of cleaning the article surface. Cleaning the article surface entails removing a portion or substantially all oxides from the surface of the substrate and preventing the reformation of oxides from the surface that is to be carburized. The surface to be carburized is preferably free of oxides.

Removing oxides can be accomplished by mechanical or chemical methods that do not damage or otherwise adversely affect the substrate surface. The mechanical or chemical oxide removal methods may be any oxide removal methods known in the art, including but not limited to grit blasting or chemical etching. After such cleaning, the surfaces may be cleaned with a suitable solvent, while avoiding the formation of oxides. While oxides are to be avoided, it may be desirable to mask portions of the surface in order to prevent these portions from being carburized. This may be desirable for any one of a number of reasons, such as titanium containing surfaces that are not in contact with other titanium containing surfaces and/or may not be susceptible to fretting or wear. Therefore, when desirable, the portion that does not require carburization may be masked.

[0032] Although masking may be provided to surface portions of the compressor disk 107 and/or the blade 100, the carburizing of the entire compressor disk 107 and/or blade 100 may provide the compressor disk 107 and blade 100 with desirable surface properties. For example, an airfoil 101 portion of a blade 100 having a carburized zone 401 may be resistant to corrosion due to the presence of carbides and/or interstitial carbon at the surface. The resistance to corrosion is desirable for airfoils 101 and compressor disks 107 due to the fact that the airfoils 101 and compressor disks may contact air that includes water and/or corrosion accelerators, such as salt. In addition, the carburizing of the entire compressor disk 107 and/or blade 100 may provide the compressor disk 107 and blade 100 with protection against erosion due to the hardened, wear-resistant carburized zone 401. The resistance to erosion is desirable, for example, for airfoils 101 and compressor disks 107 due to contact with air that includes abrasive material, such as sand or dirt. Therefore, the method of the present invention may advantageously be utilized to coat the entire compressor disk 107 and/or blade 100.

[0033] The cleaned article is then loaded into a furnace suitable for performing the carburization process. Suitable furnaces include vacuum furnaces or furnaces that can maintain a controlled atmosphere. The furnace is heated to a temperature sufficient to permit the diffusion of carbon into titanium, and less than about 1000°F (538 °C). Preferably, the furnace is heated to about 750°F (400 °C). After the titanium-containing article has reached the carburization temperature, the carburizing gases may be introduced into the furnace by any method that prevents the introduction of oxygen. In addition, introduction of the carburizing gases should be such that the concentration of the carbon-containing gas may be varied. When maintaining a controlled atmosphere, the atmosphere must be non-oxidizing, as oxidation of the article surface and reaction of the carburizing gas with oxygen must be prevented during heat-up to the carburizing temperature and during carburizing. Once the carburizing temperature is approached, the carburizing gas, methane, propane, ethylene or acetylene, is introduced into the furnace. These

carburizing gases may be introduced below the carburizing temperature with hydrogen or to gradually replace hydrogen, but should not be added at a temperature or in a volume that will result in excessive soot formation.

- 5 The carburizing gas is provided to ensure sufficient carbon is present at the article surface for desired carburization so that carbon is diffused and is formed in a layer having titanium carbide and/or carbon diffused interstitially. The carbides and/or interstitial carbon increase the
- 10 hardness of the surface and reduce fretting. As the hardness of the surface increases, the incident of localized adhesion between titanium-containing surfaces is reduced. The reduction in localized adhesion results in a greater resistance to fretting fatigue and wear. The duration, temperature and concentration of carbon in the carbon-containing gas of the carburization process may be controlled to limit the depth of carbide layer formation. The amount of carbon present in the layer is sufficient to provide the titanium-containing surface with a reduced
- 15 susceptibility to fretting when in contact with other titanium-containing surfaces. The amount of carbon present in the carburized zone 401 includes an amount of carbon that is greater than the carbon present in a conventional carburized surface that was carburized at high temperatures, such as temperatures greater than about 1000 °F.
- 20 **[0034]** Carburization is continued until the desired carburization depth is reached at which time the operation is stopped by introducing an inert gas to the furnace. Carburization depth is temperature, time and concentration dependent, wherein the resultant depth may be governed by the laws of mass transfer and, in particular, Fick's first and second law of diffusion. Carburization ceases when the surface temperature of the article is less than the temperature at which carbon diffuses. The
- 25 depth of the carburization varies based upon a variety of factors including the time the article is exposed to the carbon-containing gas, the concentration of the carbon in the carbon-containing gas and the temperature of the article. A preferable depth for the carburization coating
- 30 401 is up to about 0.01 inches. More preferably up to about 0.001 inches. The carburization process according to the invention takes place for a time up to about 1500 hours for the desired carburization coating 401 depth to be achieved. Preferably, the carburization takes place
- 35 for a time up to about 1000 hours.
- 40 **[0035]** The carburization process is completed by purging the chamber of the carburizing gas. This can be accomplished by stopping the flow of the carburizing gas and introducing an inert gas, nitrogen or hydrogen into the chamber. This also serves to cool the article. Any masking present on the surface may be removed.
- 45 **[0036]** As will be recognized by those skilled in the art, several operating parameters can be varied, therefore these parameters must be controlled to control the desired carbide layer thickness. These parameters include, but are not limited to gas flow rate, which determines
- 50 partial gas pressure, temperature, type of furnace, working zone size, work load and time.

[0037] After processing and cooling, the work load, may comprise a plurality of articles, can be removed from the work zone. Any optional masking may be removed before or after the application of the optional lubricant coating 601. Masking may be removed by any suitable means that does not adversely affect the substrate surface, such as chemical stripping, mechanical means such as blasting, or other known methods consistent with the masking material.

[0038] Compressor disks 107 and blades 100 that comprise titanium are particularly suitable for use with the method of the present invention. Carburized compressor disks 107 and/or dovetails 103 coated with a lubricant coating 601 provide desirable tribological properties. The present invention utilizes the combination of the relatively hard carburized zone 401 in combination with a relatively soft, lubricious lubricant coating 601, which may be placed on surfaces susceptible to wear. Suitable surfaces include component surfaces within a compressor of a gas turbine engine. The carburized zone 401 reduces the coefficient of friction between the compressor disk 107 and blade 100. The lubricant coating 601 further reduces the coefficient of friction between the compressor disk 107 and the blade 100, reducing localized adhesion between the surfaces, thereby reducing fretting.

[0039] The coefficient of friction is preferably maintained in the wear system of the dovetail slot 105 and dovetail 103 equal to or less than 0.6 and preferably equal or less than 0.4. More preferably, the coefficient of friction is maintained in the wear system of the dovetail slot 105 and dovetail 103 equal to or less than 0.2. The coefficient of friction is measured between the two surfaces rubbing against each other. In the embodiments of the present invention shown in FIGs. 4-9, the coefficient of friction between the dovetail 103 of blade 100 and dovetail slot 105 of compressor disk 107, is less than or equal to about 0.6. The compressor disk 107 and blade 100 may be fabricated from any suitable material, including but not limited to metals and metal alloys. Preferred materials include titanium and its alloys. Other suitable alloys include, but are not limited to, nickel-based alloys, such as INCONEL® 718. In addition, compressor disks 107 may be fabricated from nickel-based alloys, such as R-95 and R-88.

[0040] In another embodiment of the present invention, additives may be included in the lubricant coating 601 to provide additional desirable properties for the coating system. The additional additive is an additive that provides desirable properties, such as increased lubricity, increased adhesion of the lubricant coating 601 to the surface, or increased coating uniformity, to the composition. Suitable additional additives include, but are not limited to, polytetrafluoroethylene, adhesion promoters, dispersing agents and combinations thereof. Examples of additional additives include graphite, molybdenum sulfide, molybdenum diselenide and copper.

[0041] Alternate systems that find use with the present

invention include titanium-containing components of the gas turbine engine, including actuator mechanisms, dovetail surfaces elsewhere in the engine and other surfaces where a low coefficient of friction is required or desirable.

5 In particular, the present invention finds use in applications susceptible to fretting, including applications where one titanium-containing surface slides against a second titanium-containing surface. Treatment of one or both of the surfaces in frictional contact reduces 10 the coefficient of friction, while also reducing fretting fatigue and wear.

Claims

1. A method for surface treating a titanium-containing substrate comprising:
providing a substrate having a surface comprising titanium;
heating the substrate to a temperature sufficient to diffuse carbon into the titanium and less than about 1000 °F; and
20 contacting the surface with a carbon-containing gas for a period of time sufficient to diffuse carbon into the substrate to form a surface layer comprising one or more of carbides and interstitial carbon.
2. The method of claim 1, wherein the substrate is a titanium-containing alloy selected from the group consisting of Ti-6-4, Ti-17, Ti-4-4-2, Ti-6-2-4-2, Ti-8-1-1 and titanium-containing superalloys.
3. The method of claim 1, further comprising cleaning the substrate prior to contacting the substrate with the carbon-containing gas.
4. The method of claim 1, wherein the carbon-containing gas includes a gas selected from the group consisting of methane, propane, ethylene gas, acetylene, carbon dioxide, carbon monoxide and combinations thereof.
5. The method of claim 4, wherein the carbon-containing gas further includes a non-reactive gas selected from the group consisting of argon, helium, or hydrogen.
6. The method of claim 1, wherein the carbon-containing gas is acetylene.
7. The method of claim 1, wherein the carbon-containing gas is carbon dioxide.
8. The method of claim 1, wherein the carbon-containing gas is carbon monoxide.

9. The method of claim 1, wherein the contacting step takes place for up to about 1500 hours.

10. The method of claim 6, wherein the contacting step takes place for up to about 1000 hours. 5

10

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2






FIG. 3






FIG. 6




FIG. 7




FIG. 8




FIG. 9



DOCUMENTS CONSIDERED TO BE RELEVANT			CLASSIFICATION OF THE APPLICATION (IPC)
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	
X	JP 07 090541 A (DEMUTETSUKU KK) 4 April 1995 (1995-04-04) * abstract * -----	1-10	INV. C23C8/20
X	JP 2002 371348 A (TANAKA KK; SDC KK) 26 December 2002 (2002-12-26) * abstract * -----	1-10	
X	JP 2003 041359 A (TANAKA KK; SDC KK) 13 February 2003 (2003-02-13) * abstract * -----	1-10	
A	US 5 891 267 A (SCHAEFFER JON C [US] ET AL) 6 April 1999 (1999-04-06) * claims 1,6 *	1-10	
A	GB 2 053 744 A (MOTOREN TURBINEN UNION) 11 February 1981 (1981-02-11) * claims 1,2 *	1-10	
			TECHNICAL FIELDS SEARCHED (IPC)
			C23C
The present search report has been drawn up for all claims			
2	Place of search	Date of completion of the search	Examiner
	The Hague	17 October 2006	Elsen, Daniel
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 06 25 3302

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-10-2006

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
JP 7090541	A	04-04-1995		NONE		
JP 2002371348	A	26-12-2002		NONE		
JP 2003041359	A	13-02-2003		NONE		
US 5891267	A	06-04-1999	EP	0987347 A1	22-03-2000	
			JP	3474788 B2	08-12-2003	
			JP	2000119868 A	25-04-2000	
GB 2053744	A	11-02-1981	DE	2929634 A1	29-01-1981	
			FR	2461762 A1	06-02-1981	
			NL	8003868 A	23-01-1981	