



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 963 484 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
02.10.2002 Bulletin 2002/40

(21) Application number: **98903333.7**

(22) Date of filing: **03.02.1998**

(51) Int Cl.7: **D21H 17/71**
// D21H17/07, D21H17/09,
D21H17/16, D21H17/17,
D21H17/24, D21H17/42,
D21H17/68

(86) International application number:
PCT/SE98/00192

(87) International publication number:
WO 98/033979 (06.08.1998 Gazette 1998/31)

(54) **SIZING OF PAPER**

LEIMEN VON PAPIER

PROCEDE DE COLLAGE DE PAPIER

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB IT LI NL PT SE
Designated Extension States:
SI

(30) Priority: **05.02.1997 EP 97850017**
05.02.1997 EP 97850016
30.12.1997 SE 9704931

(43) Date of publication of application:
15.12.1999 Bulletin 1999/50

(73) Proprietors:
• **AKZO NOBEL N.V.**
6800 SB Arnhem (NL)
• **Eka Chemicals AB**
445 80 Bohus (SE)
Designated Contracting States:
SE

(72) Inventors:
• **FRÖLICH, Sten**
S-436 39 Askim (SE)
• **LINDGREN, Erik**
S-445 34 Bohus (SE)
• **SIKKAR, Rein**
S-448 34 Floda (SE)

(74) Representative: **Jönsson, Christer**
Eka Chemicals AB,
Patent Department,
Box 11556
100 61 Stockholm (SE)

(56) References cited:
EP-A- 0 208 667 **EP-A- 0 220 941**
EP-A- 0 275 851 **EP-A- 0 418 015**
WO-A-96/17127 **US-A- 3 046 186**
US-A- 4 240 935

EP 0 963 484 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates to sizing of paper and more specifically to dispersions of cellulose-reactive sizing agents, their preparation and use.

Background

[0002] Cellulose-reactive sizing agents, such as those based on alkyl ketene dimer (AKD) and alkenyl succinic anhydride (ASA), are widely used in papermaking at neutral or slightly alkaline stock pH's in order to give paper and paper board some degree of resistance to wetting and penetration by aqueous liquids. Paper sizes based on cellulose-reactive sizing agents are generally provided in the form of dispersions containing an aqueous phase and finely divided particles or droplets of the sizing agent dispersed therein. The dispersions are usually prepared with the aid of a dispersant system consisting of an anionic compound, e.g. sodium lignosulfonate, in combination with a high molecular weight amphoteric or cationic polymer, e.g. cationic starch, polyamine, polyamideamine or a vinyl addition polymer, Depending on the overall charge of the compounds of the dispersant system, the size dispersions will be cationic or anionic in nature. However, dispersions of these types usually exhibit rather poor stability and high viscosity, even at relatively low solids contents, which evidently lead to difficulties in handling the dispersions, for example on storage and in use. A further drawback is that the products have to be supplied as low concentration dispersions which further increases the costs of transportation of the active sizing agent.

[0003] Cellulose-reactive sizing agents generally provide good sizing with low dosages of the sizing agent. However, it has been experienced that the efficiency of conventional cellulose-reactive sizing agents is deteriorated when they are used with stocks having a high cationic demand and containing substantial amounts of lipophilic wood extractives, such as, for example, resin acids, fatty acids, fatty esters, triglycerides, etc. Due to the anionic character of lipophilic substances containing carboxylate or carboxylic acid groups, stocks containing substantial amounts of lipophilic extractives usually have a rather high cationic demand. It has been found that the lipophilic substances can be detrimental to the adsorption of sizing agents onto the fibres which may cause the poor sizing results. In order to improve sizing with such stocks the papermaker has had to increase the dosage of sizing agent, which of course is less favourable economically and can increase the accumulation of sizing agent in the white water recirculating in the papermaking process. These problems are even more pronounced in paper mills where white water is extensively recirculated with the introduction of only low amounts of fresh water into the process, thereby increasing the cationic demand and the accumulation of lipophilic extractives and non-retained sizing agent in the white water and the stock to be dewatered.

[0004] EP-A-275851 relates to an aqueous sizing dispersion containing a disperse phase in the form of a sizing agent mixture consisting of a rosin material and a synthetic sizing agent, and a polyaluminium compound.

[0005] EP-A-208667 refers to an aqueous sizing dispersion containing a disperse phase in the form of a sizing agent mixture consisting of rosin material and a synthetic sizing agent.

[0006] WO-A-96/17127 relates to an anionic sizing dispersion containing a cellulose-reactive sizing agent.

[0007] EP-A-220941 discloses a dry composition comprising a ketene dimer and an encapsulating agent which can be selected from gelatin, tristearin, gum arabicum, sugar, ethyl cellulose, carboxymethylcellulose, polyacrylamides, silicates, polyethers, polyesters, polyamides, starches and polyvinyl alcohol.


The Invention

[0008] In accordance with the present invention it has been found that improved stability and sizing characteristics can be obtained with aqueous dispersions of cellulose-reactive sizing agents in which the sizing agent is dispersed in the aqueous phase by means of a dispersant system comprising a low molecular weight cationic compound having a molecular weight less than 10000 and an anionic stabilizer which is an anionic polyelectrolyte. The size dispersions of this invention exhibit excellent stability and low viscosity and they are particularly useful with papermaking stocks having a high cationic demand and/or containing high levels of lipophilic substances. It has also been found that improved sizing can be obtained by using such dispersions in papermaking processes where white water is extensively recirculated. More specifically, the present invention relates to an aqueous dispersion containing a cellulose-reactive sizing agent and a dispersant system comprising a low molecular weight cationic organic compound having a molecular weight less than 10000 and an anionic stabilizer which is an anionic polyelectrolyte its preparation and use, as further defined in claims 1 to 16.

[0009] The present size dispersions makes it possible to produce paper with improved sizing over conventional size dispersions at a corresponding dosage of cellulose-reactive sizing agent and to use a lower dosage of cellulose-reactive sizing agent to attain a corresponding level of sizing. The possibility of using lower amounts of sizing agent to attain in-specification sizing reduces the risk of accumulation of non-adsorbed sizing agents in the white water recirculating in the process, thereby reducing the risk of aggregation and deposition of the sizing agent on the paper machine. The

present invention thus offers substantial economic and technical benefits.

[0010] The cellulose-reactive sizing agent according to the invention can be selected from any of the cellulose-reactive sizing agents known in the art. Suitably the sizing agent is selected from the group consisting of hydrophobic ketene dimers, ketene multimers, acid anhydrides, organic isocyanates, carbamoyl chlorides and mixtures thereof, preferably ketene dimers and acid anhydrides, most preferably ketene dimers. Suitable ketene dimers have the general formula (I) below, wherein R¹ and R² represent saturated or unsaturated hydrocarbon groups, usually saturated hydrocarbons, the hydrocarbon groups suitably having from 8 to 36 carbon atoms, usually being straight or branched chain alkyl groups having 12 to 20 carbon atoms, such as hexadecyl and octadecyl groups. Suitable acid anhydrides can be characterized by the general formula (II) below, wherein R³ and R⁴ can be identical or different and represent saturated or unsaturated hydrocarbon groups suitably containing from 8 to 30 carbon atoms, or R³ and R⁴ together with the -C-O-C- moiety can form a 5 to 6 membered ring, optionally being further substituted with hydrocarbon groups containing up to 30 carbon atoms. Examples of acid anhydrides which are used commercially include alkyl and alkenyl succinic anhydrides and particularly isoctadecenyl succinic anhydride.



[0011] Suitable ketene dimers, acid anhydrides and organic isocyanates include the compounds disclosed in US-A-4,522,686. Examples of suitable carbamoyl chlorides include those disclosed in US-A-3,887,427.

[0012] In addition to the cellulose-reactive sizing agent, the size dispersions may also contain a non-cellulose-reactive sizing agent. Examples of suitable sizing agents of this type include rosins, e.g. fortified and/or esterified rosin, waxes, fatty acid and resin acid derivatives, e.g. fatty amides and fatty esters, e.g. glycerol triesters of natural fatty acids.

[0013] The dispersions of this invention contain a dispersant, or dispersant system, comprising a cationic organic compound having a molecular weight less than 10000 and an anionic stabilizer which is an anionic polyelectrolyte. The compounds are preferably bound together by the force of electrostatic attraction, thereby representing a coacervate dispersant. When used in combination, these compounds are effective as a dispersant for the sizing agent although the cationic compound and/or the anionic compound do not have to be effective as a dispersant when used singly. Particularly preferred dispersions of this invention include those containing a cationic surfactant and an anionic stabilizer, as defined hereinafter. In a preferred embodiment of the invention, the dispersion is anionic, i.e. the dispersant system has an overall anionic charge.

[0014] The cationic compound contains one or more cationic groups of the same or different types and include cationic compounds having one cationic group and cationic compounds having two or more cationic groups, i.e. cationic polyelectrolytes. Examples of suitable cationic groups include sulfonium groups, phosphonium groups, acid addition salts of primary, secondary and tertiary amines or amino groups and quaternary ammonium groups, for example where the nitrogen has been quaternized with methyl chloride, dimethyl sulfate or benzyl chloride, preferably acid addition salts of amines/amino groups and quaternary ammonium groups. Cationic polyelectrolytes can have a degree of substitution varying over a wide range; the degree of cationic substitution (DS_C) can be from 0.01 to 1.0, suitably from 0.1 to 0.8 and preferably from 0.2 to 0.6.

[0015] Suitable cationic organic compounds for use in this invention include cationic compounds capable of functioning as a surfactant and/or dispersing agent and/or coupling agent between the particle or droplet of sizing agent and the anionic stabilizer. Preferably the cationic compound is a surfactant. Preferred cationic surfactants include compounds having the general formula R₄N⁺ X⁻, wherein each R group is independently selected from (i) hydrogen; (ii) hydrocarbon groups, suitably aliphatic and preferably alkyl groups, having from 1 to about 30 carbon atoms, preferably from 1 to 22 carbon atoms; and (iii) hydrocarbon groups, suitably aliphatic and preferably alkyl groups, having up to about 30 carbon atoms, preferably from 4 to 22 carbon atoms, and being interrupted by one or more heteroatoms, e.g. oxygen or nitrogen, and/or groups containing a heteroatom, e.g. carbonyl and acyloxy groups; where at least one, suitably at least three and preferably all of said R groups contain carbon atoms; suitably at least one and preferably at least two of said R groups containing at least 7 carbon atoms, preferably at least 9 carbon atoms and most preferably at least 12 carbon atoms; and wherein X⁻ is an anion, typically a halide like chloride, or an anionic group present in the anionic compound of the dispersant, e.g. where the surfactant is a protonated amine of the formula R₃N wherein R and N are as defined above. Examples of suitable surfactants include dioctyldimethylammonium chloride, didecyldimethylammonium chloride, dicocodimethylammonium chloride, cocobenzyltrimethylammonium chloride, coco(fractionated)benzyltrimethylammonium chloride, octadecyl trimethylammonium chloride, dioctadecyl dimethylammonium chloride, dihexadecyl dimethylammonium chloride, di(hydrogenated tallow)dimethylammonium chloride, di(hydrogenated tallow)benzyltrimethylammonium chloride, (hydrogenated tallow)benzyltrimethylammonium chloride, dioleyldimeth-

ylammonium chloride, and di(ethylene hexadecanecarboxylate)dimethylammonium chloride. Particularly preferred cationic surfactants thus include those containing at least one hydrocarbon group with from 9 to 30 carbon atoms and notably quaternary ammonium compounds.

5 **[0016]** Further preferred cationic surfactants include quaternary di- and poly-ammonium compounds containing at least one hydrocarbon group, suitably aliphatic and preferably alkyl, with from 9 to 30 carbon atoms, preferably from 12 to 22 carbon atoms. Examples of suitable surfactants of this type include N-octadecyl-N'-dimethyl-N'-trimethyl-propylene-diammonium dichloride.

10 **[0017]** Preferred cationic polyelectrolytes further include low molecular weight cationic organic polymers, optionally degraded, e.g. those derived from polysaccharides like starches and guar gums, cationic condensation products like cationic polyurethanes, polyamideamines, e.g. polyamideamine-epichlorohydrin copolymers, polyamines, e.g. dimethylamine-epichlorohydrin copolymers, dimethylamine-ethylenediamine-epichlorohydrin copolymers, ammonia-ethylenedichloride copolymers, vinyl addition polymers formed from monomers with cationic groups, e.g. homopolymers and copolymers of diallyldimethylammonium chloride, dialkylaminoalkyl acrylates, methacrylates and acrylamides (e.g. dimethylaminoethyl acrylates and methacrylates) which usually are present as acid addition salts or quaternary ammonium salts, optionally copolymerized with non-ionic monomers including acrylamide, alkyl acrylates, styrene and acrylonitrile and derivatives of such monomers, vinyl esters, and the like.

15 **[0018]** The molecular weight of the cationic organic compound generally can be up to about 10,000, usually up to about 5,000, suitably up to about 3,000 and preferably up to about 800. The molecular weight is usually at least about 200. Suitable cationic surfactants may have a molecular weight up to about 3,000 and preferred cationic surfactants have a molecular weight between about 200 and about 800.

20 **[0019]** Suitable anionic stabilizers for use in this invention include anionic compounds functioning as stabilizers and/or being effective in combination with the cationic compound to stabilize the sizing agent in an aqueous phase as well as anionic compounds known as useful as dispersants in the preparation of size dispersions. Preferably the anionic compound is water-soluble or water-dispersible. The anionic stabilizer can be selected from organic or inorganic compounds and it can be derived from natural or synthetic sources. The anionic stabilizer of the dispersant system contains one or more anionic groups of the same or different types and include anionic compounds having one anionic group and anionic compounds having two or more anionic groups, herein referred to as an anionic polyelectrolyte. The term anionic polyelectrolyte is meant to include also anionic compounds acting as a polyelectrolyte, e.g. through chemical non-ionic interaction or attraction. In a preferred embodiment, the anionic stabilizer is an anionic polyelectrolyte. Examples of suitable anionic groups, i.e. groups that are anionic or rendered anionic in water, include phosphate, phosphonate, sulphate, sulphonate, sulphonic acid and carboxylic acid groups and salts thereof, usually ammonium or alkali metal (generally sodium) salts. The anionic groups can be native or introduced by means of chemical modification in known manner. The anionic stabilizer can have a degree of anionic substitution (DS_A) varying over a wide range; the DS_A can be from 0.01 to 1.4, suitably from 0.1 to 1.2 and preferably from 0.2 to 1.0. Anionic polyelectrolytes may contain one or more cationic groups as long as it has an overall anionic charge.

25 **[0020]** In a preferred embodiment, the anionic stabilizer is selected from organic compounds. Suitable anionic stabilizers of this type include polymeric compounds such as those based on polysaccharides like starches, guar gums, celluloses, chitins, chitosans, glycans, galactans, glucans, xanthan gums, mannans, dextrans, etc., preferably phosphorylated, sulphonated and carboxylated polysaccharides, as well as synthetic organic polymers like condensation products, e.g. anionic polyurethanes and polymeric anionic compounds based on naphthalene, e.g. condensed naphthalene sulfonates, and further vinyl addition polymers formed from monomers with anionic groups, e.g. acrylic acid, methacrylic acid, maleic acid, itaconic acid, crotonic acid, vinylsulfonic acid, sulfonated styrene and phosphates of hydroxyalkyl acrylates and methacrylates, optionally copolymerized with non-ionic monomers including acrylamide, alkyl acrylates, styrene and acrylonitrile as well as derivatives of such monomers, vinyl esters, and the like. Particularly preferred organic anionic stabilizers include anionic polysaccharides, e.g. cellulose-derivatives like carboxymethyl celluloses, condensed naphthalene sulfonates, anionic acrylamide-based polymers and polymers based on acrylic acid and similar acid monomers.

30 **[0021]** In a preferred embodiment of the invention, the anionic stabilizer is hydrophobe-modified and contains one or more hydrophobic groups, suitably being a hydrophobically modified polysaccharide, preferably carboxymethyl cellulose. Examples of suitable groups include hydrophobic substituents containing from 4 to about 30 carbon atoms, notably hydrophobic amide, ester and ether substituents comprising a saturated or unsaturated hydrocarbon chain of at least 4 and preferably from 8 to 30 carbon atoms, optionally being interrupted by one or more heteroatoms, e.g. oxygen or nitrogen, and/or groups containing a heteroatom, e.g. carbonyl or acyloxy. Suitable anionic polysaccharides, anionic hydrophobically modified polysaccharides and methods of introducing hydrophobic substituents into polysaccharides are for example disclosed in US-A-4,687,519 and WO-A-94/24169.

35 **[0022]** In another preferred embodiment, the anionic stabilizer is selected from inorganic anionic materials, preferably anionic inorganic polyelectrolytes such as, for example, compounds containing silicon atoms, e.g. various forms of condensed or polymerized silicic acid which have negative hydroxyl groups, e.g. oligomeric silicic acid, polysilicic

acid, polysilicates and polyaluminiumsilicates.

[0023] The anionic stabilizer can also be selected from microparticulate material where both organic and inorganic anionic materials are encompassed. Suitable particulate materials of this type include highly cross-linked anionic vinyl addition polymers, e.g. acrylamide-based and acrylate-based polymers, anionic condensation polymers, e.g. melamine-sulfonic acid sols, inorganic silica-based materials, e.g. materials of the type present in aqueous silica-based sols like silica sols, aluminated silica sols, aluminiumsilicate sols, polysilicate microgels and polyaluminiumsilicate microgels, as well as silica gels and precipitated silica. The microparticulate material preferably is colloidal, i.e. in the colloidal range of particle size. The colloidal particles suitably have a particle size from about 1 nm to about 80 nm, preferably from 2 to 35 nm and most preferably from 2 to 10 nm.

[0024] The molecular weight of the anionic compound can be varied over a broad range from a few hundreds or thousands to several millions. Usually the molecular weight is above 200 and suitably above 500, whereas the upper limit is usually 10 million and preferably 2 million. In a preferred embodiment, the molecular weight is up to about 50,000.

[0025] The amount of cationic and anionic compounds present in the dispersion according to the invention can be varied over a broad range depending on, among other things, type and charge density of the cationic and anionic materials, type of sizing agent, desired anionicity/cationicity and solids content of the resulting dispersion. The present dispersion is suitably anionic and hereby is meant that the anionic charge of the anionic stabilizer is greater than the cationic charge of the cationic compound. In the dispersion, the cationic compound can be present in an amount of up to 100% by weight, usually from 0.1 to 20% by weight, suitably from 1 to 10% by weight and preferably from 2 to 7% by weight, based on the sizing agent, and the anionic stabilizer can be present in an amount of up to 100% by weight, usually from 0.1 to 20% by weight, suitably from 0.2 to 10% by weight and preferably from 0.3 to 6% by weight, based on the sizing agent, where the overall charge of the cationic compound and the anionic stabilizer which are present in the dispersions preferably is anionic or negative.

[0026] It has been found that the present dispersions can be prepared in high solids contents and yet exhibit very good stability on storage and low viscosity. Accordingly, this invention provides size dispersions with improved storage stability, higher solids content and/or lower viscosity. A further benefit observed with the present dispersions is improved dilute stability which means less aggregation of the particles or droplets of sizing agent, thereby forming lower levels of bigger aggregates having lower sizing efficiency, as well as less deposition of the hydrophobic sizing agent on the paper machine and less wire contamination, thereby reducing the need for maintenance of the paper machine. The present dispersions generally can have sizing agent contents of from about 0.1 to about 50% by weight and suitably above 20% by weight. Dispersions containing a ketene dimer sizing agent according to the invention may have ketene dimer contents within the range of from 5 to about 50% by weight and preferably from about 10 to about 35% by weight. Dispersions, or emulsions, containing an acid anhydride sizing agent according to the invention may have acid anhydride contents within the range from 0.1 to about 30% by weight and usually from about 1 to about 20% by weight.

[0027] The sizing dispersions according to the invention can be produced by mixing an aqueous phase with the anionic stabilizer, the cationic compound and the sizing agent, preferably at a temperature where the sizing agent is liquid, and homogenizing the mixture so obtained, suitably under pressure. Suitable temperatures for ketene dimer sizing agents are from about 55°C to 95°C whereas lower temperatures can be employed for acid anhydrides. The obtained emulsion, which contains droplets of sizing agent normally having a size of from 0.1 to 3.5 µm in diameter, is then cooled. In addition to the above-mentioned components other materials can also be incorporated into the size dispersions, such as, for example, anionic and non-ionic dispersing agents and stabilizers, extenders, e.g. urea and urea derivatives, and preservative agents. It will be appreciated that the negative and positive charges of the compounds of the dispersant system can be formed in situ, for example by contacting the compounds with one another and/or by mixing the compounds with an aqueous phase and/or by lowering pH of the aqueous phase. For instance, the loss of a hydrogen from an acid group will form an anionic charge, and a basic amine or an amino group can be rendered cationic by protonation or abstraction of a hydrogen. Accordingly, it is possible to start with uncharged compounds in preparing the dispersion. For example, an organic compound with basic amino groups or a basic amine of the formula R_3N can be used, where the corresponding ammonium moiety $R_4N^+ X^-$ be formed in the preparation process, where R, N and X can be as defined above.

[0028] It has further been found that the components of the present dispersions can be easily homogenized in the presence of an aqueous phase. Usually less energy and lower shear forces are required in this process compared to processes for preparing conventional dispersions and hereby simplified equipment can be employed. Therefore, a further method of preparing the present dispersions comprises (i) mixing the cellulose-reactive sizing agent with the dispersant system comprising the anionic stabilizer and the cationic compound, as defined above, to obtain an intermediate composition, and (ii) homogenizing the intermediate composition in the presence of an aqueous phase, as described above. It is preferred that the components are homogeneously mixed in stage (i). The sizing agent used in stage (i) may be solid although it is preferred that it is liquid in order to simplify homogeneous mixing. If desired, the intermediate composition can be removed after the mixing stage (i), and optionally be cooled for solidification, to form a substantially water-free intermediate size composition which enables simplified shipping in an economically attractive

manner. At the location of intended use, or elsewhere, the size composition can be homogenized in the presence of water in conventional manner. This method is especially attractive when preparing dispersions of ketene dimers and acid anhydrides, the latter of which are usually prepared in the paper mill in direct connection to its use as a sizing agent in the production of paper. The provision of a storage-stable water-free size composition thus offers considerable economic and technical benefits. The present invention thus also relates to a substantially water-free size composition comprising a cellulose-reactive sizing agent, a cationic organic compound and an anionic stabilizer, where the cationic and anionic compounds when used in combination are effective as a dispersant system for the sizing agent in an aqueous phase, its preparation and use, as further defined in claims 15, 19 to 21.

[0029] The components that are present in the composition according to the invention, i.e., the cellulose-reactive sizing agent, the cationic compound and the anionic stabilizer, preferably are as defined above. The present composition is substantially water-free and hereby is meant that a small amount of water can be present; the water content can be from 0 up to 10% by weight, suitably less than 5% by weight and preferably less than 2%. Most preferably it contains no water. The composition preferably contains the cellulose-reactive sizing agent in a predominant amount, based on weight, i.e. at least 50% by weight, and suitably the composition has sizing agent content within the range of from 80 to 99.8% by weight and preferably from 90 to 99.7% by weight. The cationic compound, preferably a surfactant, and the anionic stabilizer can be present in the size composition in amounts defined above with respect to the dispersions where the percentages are based on the weight of sizing agent. In the composition, the anionic stabilizer can be present in an amount of up to 100% by weight, usually from 0.1 to 20% by weight, suitably from 0.2 to 10% by weight and preferably from 0.3 to 6% by weight, based on the sizing agent, and the cationic compound, e.g. a surfactant, can be present in an amount of up to 100% by weight, usually from 0.1 to 20% by weight, suitably from 1 to 10% by weight and preferably from 2 to 7% by weight, based on the sizing agent, where the overall charge of the cationic compound and the anionic stabilizer that are present in the composition preferably is negative or anionic.

[0030] The dispersions according to the invention can be used in conventional manner in the production of paper using any type of cellulosic fibres and they can be used both for surface sizing and internal or stock sizing. The term "paper", as used herein, is meant to include not only paper but all types of cellulose-based products in sheet and web form, including, for example, board and paperboard. The stock contains cellulosic fibres, optionally in combination with mineral fillers, and usually the content of cellulosic fibres is at least 50% by weight, based on dry stock. Examples of mineral fillers of conventional types include kaolin, china clay, titanium dioxide, gypsum, talc and natural and synthetic calcium carbonates such as chalk, ground marble and precipitated calcium carbonate. The present invention also relates to a method for the production of paper in which an aqueous dispersion, as defined above, is used as a surface or stock size. Suitably the amount of cellulose-reactive sizing agent either added to the stock containing cellulosic fibres, and optional fillers, to be drained on a wire to form paper, or applied on the paper surface as a surface size, usually at the size press, is from 0.01 to 1.0% by weight, based on the dry weight of cellulosic fibres and optional fillers, preferably from 0.05 to 0.5% by weight, where the dosage is mainly dependent on the quality of the pulp or paper to be sized, the cellulose-reactive sizing agent used and the level of sizing desired.

[0031] The dispersions of this invention, notably the anionic dispersions, are particularly useful in stock sizing of pulp having a high cationic demand and/or containing substantial amounts of lipophilic substances, for example stocks prepared from wood-containing and recycled pulps, for example where recirculation of white water is extensive. Examples of lipophilic substances commonly found in paper pulp include anionic and non-ionic lipophilic substances, such as, for example, resin acids, fatty acids, fatty esters, triglycerides, etc. The amount of lipophilic substances may be at least 10 ppm and up to about 100 ppm, usually at least 20 ppm, suitably at least 30 ppm and preferably at least 50 ppm, measured as ppm DCM by means of extraction using DCM (dichloromethane) in known manner. The cationic demand can be at least 50, suitably at least 100 and preferably at least 150 $\mu\text{eq/litre}$ stock filtrate. The cationic demand can be measured in conventional manner, for example by means of a Mutek Particle Charge Detector using a stock filtrate obtained from a raw stock filtered through a 1.6 μm filter and poly(diallyldimethylammonium chloride) as a titrant. Further, the present dispersions are preferably used in papermaking processes where white water is extensively recirculated, i.e. with a high degree of white water closure, for example where from 0 to 30 tons of fresh water are used per ton of dry paper produced, usually less than 20, suitably less than 15, preferably less than 10 and notably less than 5 tons of fresh water per ton of paper. Recirculation of white water in the process preferably takes place by mixing the white water with cellulosic fibres, preferably in the form of a stock or suspension, before or after the addition of the sizing dispersion, e.g. to form the stock to be dewatered. Fresh water can be introduced in the process at any stage; for example, it can be mixed with cellulosic fibres in order to form the stock, and it can be mixed with a stock containing cellulosic fibres to dilute it so as to form the stock to be dewatered, before or after mixing the stock with white water and before or after the addition of the sizing dispersion.

[0032] Chemicals conventionally added to the stock in papermaking such as retention aids, aluminium compounds, dyes, wet-strength resins, optical brightening agents, etc., can of course be used in conjunction with the present dispersions. Examples of aluminium compounds include alum, aluminates and polyaluminium compounds, e.g. polyaluminium chlorides and sulphates. Examples of suitable retention aids include cationic polymers, anionic inorganic ma-

terials in combination with organic polymers, e.g. bentonite in combination with cationic polymers, silica-based sols in combination with cationic polymers or cationic and anionic polymers. Particularly good stock sizing can be obtained when using the dispersions of the invention in combination with retention aids comprising cationic polymers. Suitable cationic polymers include cationic starch, guar gum, acrylate-based and acrylamide-based polymers, polyethyleneimine, dicyandiamide-formaldehyde resins, polyamines, polyamidoamines and poly(diallyldimethyl ammoniumchloride) and combinations thereof. Cationic starch and cationic acrylamide-based polymers are preferably used, either alone or in combination with each other or with other materials. In a preferred embodiment of the invention, the dispersions are used in combination with a retention system comprising at least one cationic polymer and anionic silica-based particles. The present dispersions can be added before, between, after or simultaneously with the addition of the cationic polymer or polymers. It is also possible to pre-mix the size dispersion with a retention aid, e.g. a cationic polymer like cationic starch or a cationic acrylamide-based polymer, or an anionic silica-based material, prior to introducing the mixture thus obtained into the stock. Accordingly, the dispersion can be prepared just prior to introducing it into the stock by bringing into contact a size dispersion containing the cationic compound, preferably a cationic surfactant, with an anionic silica-based material, for example as defined above.

[0033] The invention is further illustrated in the following examples, which, however, are not intended to limit the same. Parts and % relate to parts by weight and % by weight, respectively, unless otherwise stated.

Example 1

[0034] Anionic alkyl ketene dimer (AKD) dispersions according to the invention were prepared by mixing di(hydrogenated tallow) dimethylammonium chloride, which is a cationic surfactant commercially available under the trade name Querton 442, Akzo Nobel, with molten AKD at 70°C, passing the mixture through a homogenizer in the presence of an aqueous solution of an anionic stabilizer and then cooling the dispersion so obtained. The pH of the dispersion was adjusted to about 5 by addition of acid. The anionic stabilizer used in this Example was an anionic fatty amide-modified carboxymethyl cellulose (FACMC) containing a hydrophobic substituent derived from N-hydrogenated tallow-1,3-diaminopropan prepared according to the disclosure of WO-A-94/24169. The FACMC had a degree of carboxylic substitution of 0.6 and a degree of hydrophobic substitution of 0.1. The dispersions contained AKD particles with an average particle size of about 1 µm which were anionically charged, as shown by a negative zeta potential determined by means of a ZetaMaster S Version PCS. The AKD content of the dispersions were 30%. Dispersion No. 1 contained 3% of cationic surfactant and 1% of anionic stabilizer, both based on the weight of AKD. Dispersion No. 2 contained 7% of cationic surfactant and 1% of anionic stabilizer, both based on the weight of AKD.

Example 2

[0035] The general procedure of Example 1 was repeated except that a condensated sodium naphthalenesulphonate commercially available under the trade name Orotan™ SN, Rohm & Haas Company, was used as the anionic stabilizer and different proportions of the compounds of the dispersion was employed. Dispersion No. 3 obtained in this Example had an AKD content of 30% and contained 6% of anionic stabilizer and 4% of cationic surfactant, both based on the weight of AKD. The dispersion contained AKD particles with an average particle size of about 1 µm which were anionically charged, determined as above.

Example 3

[0036] Stability of the anionic dispersions according to Examples 1 and 2 was tested as follows: The dispersion was diluted with water to give a dispersion containing 40 ppm of AKD. In some of the tests 10 ppm of stearic acid was added in order to raise the content of lipophilic substances and the cationic demand. The dilute dispersion was placed in a jar equipped with a device for turbidity measurements, a loop, circulation means and heating and cooling means. A set volume of the dilute dispersion was circulated in the loop while automatically recording the turbidity and subjecting the dispersion to a heating and cooling cycle for a set time period of 45 minutes. The temperature of the dispersion was raised from 20°C to 62°C and then lowered again to 20°C. Turbidity is affected by particle size and the difference in turbidity of the dispersion before and after a temperature cycle is a measure of the ability of the dispersed particles to withstand growth by agglomeration and thus a measure of the stability of the dispersion. The difference in turbidity (ΔT) is calculated as follows: $\Delta T = (\text{final turbidity} / \text{initial turbidity}) \times 100$. The higher the ΔT the better the stability.

[0037] Two standard dispersions were also tested for comparison purposes; Ref. 1 is an anionic AKD dispersion containing a dispersant system comprising sodium lignosulphonate and cationic starch where the lignosulphonate is present in ionic excess; Ref. 2 is a cationic AKD dispersion also containing sodium lignosulphonate and cationic starch but where the cationic starch is present in ionic excess. Table 1 gives the results obtained.

Table 1

Dispersion No.	Stearic acid [ppm]	ΔT
1	-	53
1	10	40
2	-	79
2	10	66
3	-	72
3	10	55
Ref. 1	-	45
Ref. 1	10	32
Ref. 2	-	35
Ref. 2	10	6

[0038] As is shown in Table 1 the ΔT values of the dispersions of this invention were considerably higher than those of the standard dispersions which accordingly are indicative of better dilute stability.

Example 4

[0039] Sizing efficiency of size dispersions according to Example 3 was evaluated in this Example. Paper sheets were prepared according to the standard method SCAN-C23X for laboratory scale. The papermaking stock used contained 80% of 60:40 bleached birch/pine sulphate and 20% of chalk to which 0.3 g/l of $\text{Na}_2\text{SO}_4 \cdot 10\text{H}_2\text{O}$ was added. Stock consistency was 0.5% and pH 8.0. The size dispersions were used in conjunction with a commercial retention and dewatering system, Compozil™, comprising cationic starch and an anionic aluminium-modified silica sol which were added to the stock separately; the cationic starch was added in an amount of 8 kg/ton, based on dry stock, and the silica sol was added in an amount of 0.8 kg/ton, calculated as SiO_2 and based on dry stock

[0040] Cobb values, measured according to TAPPI standard T 441 OS-63, obtained in the tests are set forth in Table 2. The dosage of AKD is based on dry stock.

Table 2

Dispersion No.	AKD dosage [kg/ton]	Cobb 60 [g/m ²]
1	0.45	54
1	0.60	27
Ref. 1	0.45	80
Ref. 1	0.60	30
Ref. 2	0.45	68
Ref. 2	0.60	31

[0041] Table 2 demonstrates the improvement in paper sizing obtained with the size dispersion according to the invention.

Example 5

[0042] Sizing efficiency was evaluated according to the procedure of Example 4 except that the stock contained precipitated calcium carbonate as a filler instead of chalk, and the dosage of cationic starch was 12 kg/ton, based on dry stock. In some of the tests 10 ppm of stearic acid was added to the stock in order to raise the the cationic demand and the lipophilic substance content of the stock. The results are set forth in Table 3.

Table 3

Dispersion No.	AKD dosage [kg/ton]	Stearic acid [ppm]	Cobb 60 [g/m ²]
1	0.45	-	32
1	0.60	-	28
1	0.75	-	26

EP 0 963 484 B1

Table 3 (continued)

Dispersion No.	AKD dosage [kg/ton]	Stearic acid [ppm]	Cobb 60 [g/m ²]
1	0.45	10	62
1	0.60	10	36
1	0.75	10	27
Ref. 1	0.45	-	50
Ref. 1	0.60	-	32
Ref. 1	0.75	-	30
Ref. 1	0.45	10	103
Ref. 1	0.60	10	76
Ref. 1	0.75	10	35

[0043] As is evident from Table 3, Dispersion No. 1 according to the invention generally gave much better sizing than the dispersion Ref. 1 used for comparison, and considerably improved sizing effect was obtained when the stock contained a substantial amount of lipophilic substances.

Example 6

[0044] A water-free size composition according to the invention was prepared by dry mixing 93 parts of AKD pellets with 3 parts of cationic surfactant according to Example 1 and 4 parts of anionic stabilizer according to Example 2. This dry mixture was later added to hot water and the aqueous mixture so obtained was heated to 80°C, pumped through a high shear pump and then cooled to room temperature. The resulting anionic dispersion, Dispersion No. 4, had an AKD content of 20% and an average particle size of about 1 µm. Sizing efficiency was evaluated as in Example 4, except that the cationic starch addition amounted to 12 kg/ton, based on dry stock. The results are given in Table 4.

Table 4

Dispersion No.	AKD dosage [kg/ton]	Cobb 60 [g/m ²]
4	0.30	58
4	0.40	30
Ref. 1	0.30	84
Ref. 1	0.40	65
Ref. 2	0.30	66
Ref. 2	0.40	40

[0045] Table 4 demonstrates the improvement in paper sizing obtained with the size dispersion according to the invention.

Example 7

[0046] An AKD dispersion according to the invention having a dispersant system comprising a cationic surfactant and an anionic stabilizer in the form of an inorganic microparticulate material was evaluated in this test series.

[0047] The dispersion was prepared by pre-blending at 75°C 0.2 g of cocoamine commercially available under the trade name Armeen C™, which is a mixture of amines of the formula RNH₂ wherein R is C₁₂-C₁₈ hydrocarbons, and 1.0 g, calculated as SiO₂, of an aqueous sol of aluminium-modified silica of the type disclosed in US-A-5,368,833, and then adding 25 g of AKD and acid to adjust pH to 4.0. The aqueous mixture was homogenized using an Ultra Turrax and then cooled. The dispersion obtained, Dispersion No. 5, had an AKD content of 25% by weight and contained a dispersant system which was anionic in nature.

[0048] Sizing efficiency of the dispersion was evaluated according to the procedure of Example 4 using a similar stock at pH 8.1 and using the standard AKD dispersion Ref. 2 for comparison. The results are set forth in Table 5 where the dosage of AKD is based on dry stock.

Table 5

Dispersion No.	AKD dosage [kg/ton]	Cobb 60 [g/m ²]
5	0.3	58
5	0.5	30
5	0.6	28
Ref. 2	0.3	73
Ref. 2	0.5	33
Ref. 2	0.6	30

Example 8

[0049] An AKD dispersion according to the invention was prepared and evaluated in a similar manner to Example 7 except that the anionic stabilizer used in this Example was a melamine-sulfonic acid sol, prepared in accordance with the teachings of WO-A-96/34027. Dispersion No. 6 was prepared from 0.4 g of cocoamine, 2 g of melamine-sulfonic acid, 30 g of AKD and water up to 100 g. The results of the sizing tests are shown in Table 6 where the dosage of AKD is based on dry stock.

Table 6

Dispersion No.	AKD dosage [kg/ton]	Cobb 60 [g/m ²]
6	0.4	39
6	0.5	28
6	0.6	22
Ref. 2	0.4	50
Ref. 2	0.5	35
Ref. 2	0.6	25

Example 9

[0050] Ease of manufacture of dispersions according to the invention was evaluated by preparing anionic AKD dispersions at different AKD contents. Dispersions of the invention were prepared by homogenising a mixture of 0.8% by weight of di(hydrogenated tallow)dimethylammonium chloride, 1.6% by weight of condensated sodium naphthalenesulphonate, 77.6% by weight of water and 20% by weight of AKD for a set time using an Ultra Turrax mixer at 15.000 rpm and then cooling the dispersion so obtained for 2 hours. Similar dispersions were prepared in the same manner at different AKD contents in order to provide dispersions with AKD contents of 10, 20, 30 and 40% by weight. The dispersions are denoted Inv. followed by the AKD content in % by weight.

[0051] Standard AKD dispersions were manufactured for comparison purposes in the same manner and under the same conditions by homogenising a mixture of 1.0% by weight of cationic starch, 0.25% by weight of sodium lignosulfonate, 89% by weight of water and 10% by weight of AKD. Similar dispersions were prepared at different AKD contents in order to provide standard dispersions with AKD contents of 10, 20, 30 and 40% by weight. The dispersions are denoted Ref. 3 followed by the AKD content in % by weight.

[0052] Particle size and viscosity were assessed in conventional manner. Table 7 shows the results obtained.

Table 7

AKD Dispersion No.	Particle size (μm)	Viscosity (cps)
Inv. - 10%	2.98	10
Inv. - 20%	3.12	20
Inv. - 30%	3.50	20
Inv. - 40%	3.50	25
Ref. 3 - 10%	4.31	15
Ref. 3 - 20%	4.52	20
Ref. 3 - 30%	5.20	25
Ref. 3 - 40%	5.57	40

[0053] Table 3 demonstrates that the dispersions according to the invention were easier to manufacture; a lower viscosity was obtained at corresponding AKD contents and a smaller particle size was obtained using the same amount of energy to set surfaces free. Compared to the standard dispersion, less energy and lower shear forces are thus required according to this invention in order to manufacture dispersions with equal particle size. In addition, an increase in stirrer speed to 25.000 rpm considerably reduced the particle size of the dispersions according to the invention to be within the range of from 1 to 2 μm .

Claims

1. Aqueous dispersion of a sizing agent, **characterised in that** it contains a cellulose-reactive sizing agent and a dispersant system comprising a low molecular weight cationic organic compound having a molecular weight less than 10,000 and an anionic stabilizer which is an anionic polyelectrolyte.
2. Aqueous dispersion according to claim 1, **characterised in that** the cationic organic compound is present in an amount of from 0.1 to 20% by weight, based on the sizing agent, and the anionic stabilizer is present in an amount of from 0.1 to 20% by weight, based on the sizing agent.
3. Aqueous dispersion according to claim 1 or 2, **characterised in that** the cationic organic compound is a cationic surfactant.
4. Aqueous dispersion according to claim 3, **characterised in that** the cationic surfactant has a molecular weight of from 200 to 800.
5. Aqueous dispersion according to claim 3 or 4, **characterised in that** the cationic surfactant is selected from primary, secondary, tertiary and quaternary ammonium compounds containing at least one hydrocarbon group with from 9 to 30 carbon atoms.
6. Aqueous dispersion according to claim 3, 4 or 5, **characterised in that** the cationic surfactant is selected from dioctyldimethylammonium chloride, didecyldimethylammonium chloride, dicocodimethylammonium chloride, cocobenzyltrimethylammonium chloride, coco(fractionated)benzyltrimethylammonium chloride, octadecyl trimethylammonium chloride, dioctadecyl dimethylammonium chloride, dihexadecyl dimethylammonium chloride, di(hydrogenated tallow)dimethylammonium chloride, di(hydrogenated tallow)-benzyltrimethylammonium chloride, (hydrogenated tallow)benzyltrimethylammonium chloride, dioleyldimethylammonium chloride, di(ethylene hexadecane-carboxylate)dimethylammonium chloride, and N-octadecyl-N'-dimethyl-N'-trimethyl-propylene-diammonium dichloride.
7. Aqueous dispersion according to claim 1 or 2, **characterised in that** the cationic organic compound is a cationic polyelectrolyte.
8. Aqueous dispersion according to any of the preceding claims, **characterised in that** the anionic stabilizer is an organic compound.
9. Aqueous dispersion according to any of claims 1 to 7, **characterised in that** the anionic stabilizer is an inorganic silica-based material.
10. Aqueous dispersion according to claim 1, 2 or 8, **characterised in that** the anionic stabilizer is selected from anionic polyurethanes, condensated naphthalene sulfonates, polymeric anionic compounds based on polysaccharides, vinyl addition polymers formed from monomers with anionic groups, optionally being copolymerized with non-ionic monomers, and anionic organic microparticulate materials.
11. Aqueous dispersion according to any of the preceding claims, **characterised in that** the dispersion is anionic.
12. Aqueous dispersion according to any of the preceding claims, **characterised in that** the sizing agent is a ketene dimer or an acid anhydride.
13. A method for the preparation of an aqueous dispersion of a cellulose-reactive sizing agent, **characterised in that** the cellulose-reactive sizing agent is homogenized in the presence of an aqueous phase and a dispersant system

comprising a low molecular weight cationic organic compound having a molecular weight less than 10,000 and an anionic stabilizer which is an anionic polyelectrolyte.

- 5 14. A method according to claim 13, **characterised in that** in the cationic organic compound is derived from an uncharged organic polymer with basic amino groups or from a basic amine, where the corresponding cationic ammonium moiety is formed in the method.
- 10 15. A method according to claim 13, which comprises providing a substantially water-free composition containing the cellulose-reactive sizing agent, the cationic organic compound and the anionic stabilizer, and homogenizing the composition in the presence of an aqueous phase.
- 15 16. Use of an aqueous dispersion according to any one of claims 1 to 12 as a stock sizing agent or surface sizing agent in the production of paper.
- 20 17. A process for the production of paper by addition of an aqueous dispersion of a sizing agent to a stock containing cellulosic fibres and optional fillers, dewatering the stock on a wire to obtain paper and white water, **characterised in that** the dispersion is an aqueous dispersion according to any of claims 1 to 12.
- 25 18. A process according to claim 17, **characterised in that** the white water is recirculated in the process, and optionally fresh water is introduced, to form the stock containing cellulosic fibres to be dewatered, the amount of fresh water introduced being less than 30 tons per ton of paper produced.
- 30 19. A Substantially water-free composition containing a cellulose-reactive sizing agent, a low molecular weight cationic organic compound having a molecular weight less than 10,000 and an anionic stabilizer which is an anionic polyelectrolyte.
- 35 20. A composition according to claim 19, **characterised in that** the cationic organic compound is present in an amount of from 0.1 to 20% by weight, and the anionic stabilizer is present in an amount of from 0.1 to 20% by weight, both based on the cellulose-reactive sizing agent, where the overall charge of the cationic compound and the anionic stabilizer is negative.
21. Use of the composition according to claim 19 or 20 for the preparation of an aqueous dispersion of a cellulose-reactive sizing agent according to any of claims 1 to 12.

Patentansprüche

- 40 1. Wäßrige Dispersion eines Leimungsmittels, **dadurch gekennzeichnet, daß** es ein Leimungsmittel, welches für Cellulose reaktiv ist, und ein Dispersionsmittelsystem, welches eine kationische organische Verbindung mit niedrigem Molekulargewicht, welche ein Molekulargewicht von weniger als 10.000 besitzt und ein anionisches Stabilisierungsmittel, welches ein anionischer Polyelektrolyt ist, enthält.
- 45 2. Wäßrige Dispersion gemäß Anspruch 1, **dadurch gekennzeichnet, daß** die kationische organische Verbindung in einer Menge von 0,1 bis 20 Gew.%, basierend auf dem Leimungsmittel, und das anionische Stabilisierungsmittel in einer Menge von 0,1 bis 20 Gew.%, basierend auf dem Leimungsmittel, anwesend ist.
- 50 3. Wäßrige Dispersion gemäß Anspruch 1 oder 2, **dadurch gekennzeichnet, daß** die kationische organische Verbindung ein kationisches Tensid ist.
- 55 4. Wäßrige Dispersion gemäß Anspruch 3, **dadurch gekennzeichnet, daß** das kationische Tensid ein Molekulargewicht von 200 bis 800 besitzt.
5. Wäßrige Dispersion gemäß Anspruch 3 oder 4, **dadurch gekennzeichnet, daß** das kationische Tensid ausgewählt ist aus primären, sekundären, tertiären und quartären Ammoniumverbindungen, welche mindestens eine Kohlenwasserstoffgruppe mit 9 bis 30 Kohlenstoffatomen enthält.
6. Wäßrige Dispersion gemäß den Ansprüchen 3, 4 oder 5, **dadurch gekennzeichnet, daß** das kationische Tensid ausgewählt ist aus Dioctyldimethylammoniumchlorid, Didecyldimethylammoniumchlorid, Dicocodimethylammoni-

umchlorid, Cocobenzyltrimethylammoniumchlorid, fraktioniertes Cocobenzyltrimethylammoniumchlorid, Oktadecyltrimethylammoniumchlorid, Dioktadecyltrimethylammoniumchlorid, Dihexadecyltrimethylammoniumchlorid, Di(hydrierter Talg)-dimethylammoniumchlorid, Di(hydrierter Talg)-benzylmethylammoniumchlorid, (Hydrierter Talg)-benzyltrimethylammoniumchlorid, Dioleyldimethylammoniumchlorid, Di(ethylenhexadecancarboxylat)dimethylammoniumchlorid und N-oktadecyl-N'-dimethyl-N'-dimethylpropylen-diammoniumdichlorid.

5

7. Wäßrige Dispersion gemäß Anspruch 1 oder 2, **dadurch gekennzeichnet, daß** die kationische organische Verbindung ein kationischer Polyelektrolyt ist.

10

8. Wäßrige Dispersion gemäß einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, daß** das anionische Stabilisierungsmittel eine organische Verbindung ist.

15

9. Wäßrige Dispersion gemäß einem der Ansprüche 1 bis 7, **dadurch gekennzeichnet, daß** das anionische Stabilisierungsmittel ein anorganisches Material ist, welches auf Siliziumdioxid basiert.

20

10. Wäßrige Dispersion gemäß den Ansprüchen 1, 2 oder 8, **dadurch gekennzeichnet, daß** das anionische Stabilisierungsmittel ausgewählt ist aus anionischen Polyurethanen, kondensierten Naphthalinsulfaten, polymeren anionischen Verbindungen, welche auf Polysacchariden basieren, Vinyladditionspolymeren, welche aus Monomeren mit anionischen Gruppen gebildet werden, welche gegebenenfalls mit nicht-ionischen Monomeren copolymerisiert sind, und aus anionischen, organischen Mikropartikeln bestehenden Materialien.

25

11. Wäßrige Dispersion gemäß einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, daß** die Dispersion anionisch ist.

30

12. Wäßrige Dispersion gemäß einem der vorstehenden Ansprüche, **dadurch gekennzeichnet, daß** das Leimungsmittel ein Ketendimer oder ein Säureanhydrid ist.

35

13. Verfahren zur Herstellung einer wäßrigen Dispersion eines Leimungsmittels, welches mit Cellulose reaktiv ist, **dadurch gekennzeichnet, daß** das Leimungsmittel, welches für Cellulose reaktiv ist in Gegenwart einer wäßrigen Phase und einem Dispersionsmittelsystem, welches eine kationische organische Verbindung mit niedrigem Molekulargewicht, welche ein Molekulargewicht von weniger als 10.000 besitzt und ein anionisches Stabilisierungsmittel, welches ein anionischer Polyelektrolyt ist, homogenisiert wird.

40

14. Verfahren gemäß Anspruch 13, **dadurch gekennzeichnet, daß** die kationische organische Verbindung von einem ungeladenen organischen Polymer mit basischen Aminogruppen oder von einem basischen Amin abgeleitet wird, wobei der entsprechende kationische Ammoniumrest in dem Verfahren gebildet wird.

45

15. Verfahren gemäß Anspruch 13, welches das Bereitstellen einer im wesentlichen wasserfreien Zusammensetzung, welche das Leimungsmittel, welches für Cellulose aktiv ist, die kationische, organische Verbindung und das anionische Stabilisierungsmittel enthält, und Homogenisieren der Zusammensetzung in Gegenwart einer wäßrigen Phase, umfaßt.

50

16. Verwendung einer wäßrigen Dispersion gemäß einem der Ansprüche 1 bis 12 als Leimungsmittel für Faserrohstoff oder Oberflächenleimungsmittel bei der Herstellung von Papier.

55

17. Verfahren zur Herstellung von Papier durch Zusatz einer wäßrigen Dispersion eines Leimungsmittels zu einem Cellulosefasern und gegebenenfalls Papierfüllstoff enthaltenden Faserrohstoff, Entwässern des Faserrohstoffs auf einem Sieb, um Papier und Kreislaufwasser (Weißwasser) zu erhalten, **dadurch gekennzeichnet, daß** die Dispersion eine wäßrige Dispersion gemäß einem der Ansprüche 1 bis 12 ist.

18. Verfahren gemäß Anspruch 17, **dadurch gekennzeichnet, daß** in dem Verfahren das Kreislaufwasser (Weißwasser) dem Kreislauf wieder zugeführt wird und gegebenenfalls Frischwasser eingeführt wird, um den Cellulosefasern enthaltenden Faserrohstoff zu bilden, welche entwässert wird, wobei die Menge an eingeführtem Frischwasser weniger als 30 Tonnen pro Tonne hergestelltem Papiers beträgt.

19. Im wesentlichen wasserfreie Zusammensetzung enthaltend ein Leimungsmittel, welches für Cellulose reaktiv ist, eine kationische, organische Verbindung mit niedrigem Molekulargewicht, welche ein Molekulargewicht von weniger als 10.000 besitzt, und ein anionisches Stabilisierungsmittel, welches ein anionischer Polyelektrolyt ist.

20. Zusammensetzung gemäß Anspruch 19, **dadurch gekennzeichnet, daß** die kationische, organische Verbindung in einer Menge von 0,1 bis 20 Gew. % und das anionische Stabilisierungsmittel in einer Menge von 0,1 bis 20 Gew.%, beides basierend auf dem Leimungsmittel, welches für Cellulose reaktiv ist, wobei die Gesamtladung der kationischen Verbindung und des anionischen Stabilisierungsmittels negativ ist.

21. Verwendung der Verbindung gemäß den Ansprüchen 19 oder 20 zur Herstellung einer wäßrigen Dispersion eines Leimungsmittels, welches für Cellulose reaktiv ist, gemäß einem der Ansprüche 1 bis 12.

Revendications

1. Dispersion aqueuse d'un agent de collage, **caractérisée en ce qu'elle** contient un agent de collage réagissant avec des celluloses et un système dispersant comprenant un composé organique cationique de faible masse moléculaire, présentant une masse moléculaire inférieure à 10 000, et un agent stabilisant anionique qui est un polyélectrolyte anionique.

2. Dispersion aqueuse selon la revendication 1, **caractérisée en ce que** le composé organique cationique est présent en une quantité de 0,1 à 20 % en poids, par rapport à l'agent de collage, et l'agent stabilisant anionique est présent en une quantité de 0,1 à 20 % en poids, par rapport à l'agent de collage.

3. Dispersion aqueuse selon la revendication 1 ou 2, **caractérisée en ce que** le composé organique cationique est un tensioactif cationique.

4. Dispersion aqueuse selon la revendication 3, **caractérisée en ce que** le tensioactif cationique présente une masse moléculaire de 200 à 800.

5. Dispersion aqueuse selon la revendication 3 ou 4, **caractérisée en ce que** le tensioactif cationique est choisi parmi les composés amines primaires, secondaires, tertiaires et ammoniums quaternaires contenant au moins un groupe hydrocarboné qui comporte de 9 à 30 atomes de carbone.

6. Dispersion aqueuse selon la revendication 3, 4 ou 5, **caractérisée en ce que** le tensioactif cationique est choisi parmi le chlorure de dioctyldiméthylammonium, le chlorure de didécyldiméthylammonium, le chlorure de dicocodiméthylammonium, le chlorure de cocobenzyl diméthylammonium, le chlorure de coco (fractionné)benzyl diméthylammonium, le chlorure d'octadécyltriméthylammonium, le chlorure de dioctadécyl diméthylammonium, le chlorure de dihexadécyl diméthylammonium, le chlorure de di(groupe dérivé du suif hydrogéné)diméthylammonium, le chlorure de di(groupe dérivé du suif hydrogéné)benzylmethylammonium, le chlorure de (groupe dérivé du suif hydrogéné)benzyl diméthylammonium, le chlorure de dioléyldiméthylammonium, le chlorure de di(hexadécanecarboxylate d'éthylène)diméthylammonium, et le dichlorure de N-octadécyl-N-diméthyl-N'-triméthylpropylènediammonium.

7. Dispersion aqueuse selon la revendication 1 ou 2, **caractérisée en ce que** le composé organique cationique est un polyélectrolyte cationique.

8. Dispersion aqueuse selon l'une quelconque des revendications précédentes, **caractérisée en ce que** l'agent stabilisant anionique est un composé organique.

9. Dispersion aqueuse selon l'une quelconque des revendications 1 à 7, **caractérisée en ce que** l'agent stabilisant anionique est un matériau minéral à base de silice.

10. Dispersion aqueuse selon la revendication 1, 2 ou 8, **caractérisée en ce que** l'agent stabilisant anionique est choisi parmi les polyuréthanes anioniques, les naphthalène-sulfonates condensés, les composés anioniques polymériques à base de polysaccharides, des polymères d'addition vinyliques formés à partir de monomères présentant des groupes anioniques, que l'on peut faire éventuellement copolymériser avec des monomères non ioniques, et des matériaux microparticulaires organiques anioniques.

11. Dispersion aqueuse selon l'une quelconque des revendications précédentes, **caractérisée en ce que** la dispersion est anionique.

12. Dispersion aqueuse selon l'une quelconque des revendications précédentes, **caractérisée en ce que** l'agent de collage est un dimère de cétène ou un anhydride d'acide.
- 5 13. Procédé de préparation d'une dispersion aqueuse d'un agent de collage réagissant avec des celluloses, **caractérisé en ce que** l'on homogénéise l'agent de collage réagissant avec des celluloses en présence d'une phase aqueuse et d'un système dispersant comprenant un composé organique cationique de faible masse moléculaire, présentant une masse moléculaire inférieure à 10 000, et un agent stabilisant anionique qui est un polyélectrolyte anionique.
- 10 14. Procédé selon la revendication 13, **caractérisé en ce que** le composé organique cationique est dérivé d'un polymère organique non chargé présentant des groupes amino basiques, ou d'une amine basique, le fragment ammonium cationique correspondant étant formé au cours du procédé.
- 15 15. Procédé selon la revendication 13, qui comprend le fait de fournir une composition pratiquement non-aqueuse contenant un agent de collage réagissant avec des celluloses, un composé organique cationique et un agent stabilisant anionique, et le fait d'homogénéiser la composition en présence d'une phase aqueuse.
- 20 16. Utilisation d'une dispersion aqueuse selon l'une quelconque des revendications 1 à 12, comme agent de collage dans la pâte ou agent de collage superficiel dans la production de papier.
- 25 17. Procédé de production de papier par addition d'une dispersion aqueuse d'un agent de collage à une pâte contenant des fibres de cellulose et des charges éventuelles, déshydratation de la pâte sur une toile métallique pour obtenir du papier et de l'eau blanche, **caractérisé en ce que** la dispersion est une dispersion aqueuse selon l'une quelconque des revendications 1 à 12.
- 30 18. Procédé selon la revendication 17, **caractérisé en ce que** l'on remet en circulation l'eau blanche dans le procédé, et **en ce que** l'on introduit éventuellement de l'eau fraîche pour former une pâte contenant des fibres cellulosiques à déshydrater, la quantité d'eau fraîche introduite étant inférieure à 30 tons par ton de papier produit.
- 35 19. Composition pratiquement non-aqueuse contenant un agent de collage réagissant avec des celluloses, un composé organique cationique de faible masse moléculaire, présentant une masse moléculaire inférieure à 10 000, et un agent stabilisant anionique qui est un polyélectrolyte anionique.
- 40 20. Composition selon la revendication 19, **caractérisée en ce que** le composé organique cationique est présent en une quantité de 0,1 à 20 % en poids, et l'agent stabilisant anionique est présent en une quantité de 0,1 à 20 % en poids, les pourcentages étant donnés par rapport à l'agent de collage réagissant avec des celluloses, la charge globale du composé cationique et de l'agent stabilisant anionique étant négative.
- 45 21. Utilisation d'une composition selon la revendication 19 ou 20, pour préparer une dispersion aqueuse d'un agent de collage réagissant avec des celluloses selon l'une quelconque des revendications 1 à 12.
- 50
- 55