

(51) International Patent Classification:
G11C 7/00 (2006.01)(21) International Application Number:
PCT/IB2011/053429(22) International Filing Date:
2 August 2011 (02.08.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
584335 2 August 2010 (02.08.2010) NZ
590227 24 December 2010 (24.12.2010) NZ
592029 30 March 2011 (30.03.2011) NZ(71) Applicant (for all designated States except US): **3FISH LIMITED** [NZ/NZ]; 292 Durham Street, Christchurch 8014 (NZ).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WYN-HARRIS, Jeremy** [NZ/NZ]; 27 Cox Street Merivale, Christchurch 8014 (NZ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: IDENTITY ASSESSMENT METHOD AND SYSTEM

Figure 2



(57) Abstract: A method, system and software for assessing an entity (15) at a first user terminal (13) connected to a data network (10). A control system (11) is used to receive an access request (101) from the entity (15) or an assessing user (16) at a second user terminal (14). The control system (11) invokes or facilitates transmission of at least one unpredictable prompt (18) to the entity (15) for a performance of a visible prompted action (20). A video recording (21) of the prompted action performance is stored in a data store (61) and an automated assessment is made of the video recording (21) and/or a transmission of said video recording (21) and details of the prompt (18) is made to a second user terminal (14) for viewing and assessment by an assessing user (16).



-
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

IDENTITY ASSESSMENT METHOD AND SYSTEM

Technical Field

The present invention relates to user identity assessment methods and systems.

Background Art

Distributed communication technology has rapidly advanced as its benefits in business, government and other human endeavours become ever more apparent. Teleconferencing and videoconferencing is used frequently in business, government, military, education and other professional and non-professional organizations as a means for providing communication between separated individuals. The use of videoconferencing has also become a commonplace facet in the personal life of many users, communicating via video-link over the internet, mobile phone or other networks.

In particular, the use of internet and mobile social networks as a means of communication between individuals has rapidly increased in popularity. In an increasing proportion of users, social networks have become the primary means of communication with people outside the users' immediate physical vicinity. Social networks offer a method of communication that benefits many users. However, social networks have also been abused by criminals and other malicious individuals to harm other users through deceitful practices such as the use of false or misleading identities. Malicious users may portray themselves to be another person to solicit money from another user or to deceive vulnerable individuals into a personal meeting for nefarious purposes.

As used herein, the term "social network" can be interpreted include the now ubiquitous social networks such as Facebook™ and LinkedIn™, as well as any networks created indirectly through collaboration in online gaming, online forums, relationship facilitation services (e.g. 'dating sites'), virtual 'worlds' and similar formal and informal networks.

Such social networking sites allow people to interact with each other online using:

- their own true identity,
- an alias that may or may not be tied to their real identity, or
- a false identity.

The use of aliases or false identities can often be harmless and even overt, e.g. as in gaming applications. However, aliases or false identities can also cause problems as they provide the ability for dishonest people to assume an identity in order to conceal, deceive, or mislead others in some way. This deception can be used to gain trust of vulnerable individuals (for example young people or children) whom would not usually interact with people outside their age group, especially on issues of personal relationships or finances. Similarly, on interpersonal dating sites it is possible for members to have profile pictures that are not accurate representations or may even be of another person entirely. Thus, other users are deceived as to the true identity of the other person.

Social networking accounts may also be hijacked by criminals and used to discredit the reputation of the legitimate owner or analyzed to extract sensitive information from the legitimate owner's account or their contacts.

While passwords may provide some level of security, many users are incautious with password security and often use simplistic, easily guessed passwords.

Typical network assessment methods rely on a simple text-based user-ID and password combination to verify an entity as an authorised user. However, such a text-based system of authentication provides no means for an assessing user to verify that an entity has not compromised the authorised user's account.

Using text as a means of communication in Social networks also does not provide visual verification of the registered user, thus providing a means for presenting a fraudulent persona to other users, e.g. a paedophile may create a network account with false details and pictures and thereby present themselves as having a different appearance or being the same age as potential victims. Although more difficult to achieve than in text-based communication, users can also be deceived by voice impersonations in audio communication.

It will be apparent that people may communicate using conventional video communication which reduces the possibility of deception, i.e. the assessing user can compare the video images of the entity to the authorised user's profile picture or their own personal knowledge. However, many people prefer not to use live video communication for a variety of reasons, including maintaining a level of privacy during their online interactions, or not wanting others to see their facial expressions and body language during communication. Hence text-based communication has proved by far more popular than video communication on data networks.

While other complex authentication methods may be used, e.g. biometric scanning, retina recognition, these systems generally require specialised hardware and/or software which may not be available or practical to many applications. Thus, numerous authentication systems have been devised to foil or at least hinder unauthorised hijacking of user accounts. Examples of common advanced authentication systems include:

- character recognition systems to stop automated hacking by computer software;
- multiple sequences of user-specific questions, e.g. "what city were you born in?"
- physical code sheets or the like, typically sent to the user's verified address from which a code is requested by the network to authenticate the user;
- physical code generator devices time-synchronised with the network;

However, none of these systems are fail-safe as they all rely on the user taking precautions to avoid using common, easy to remember answers or preventing theft of the physical code devices.

Such systems also do not help in social networks or relationship facilitation services (e.g. online 'dating' networks) where users can simply set up a user account with a false identity and credentials. Although traditional methods of authenticating users, e.g. through background vetting, photo-ID comparisons or the like have been widely employed in the past, such methods are expensive and impractical for most social networks. Users of social networks may be distributed in numerous different countries, with differing privacy laws which may preclude vetting assessments.

Thus, there are generally two major risks associated with communication over existing communication networks.

Firstly, there is a risk that an unauthorised entity obtains access to another user's network account or device and then communicates with other users who mistakenly believe the imposter is in fact genuine.

Secondly, there is a risk a fraudulent entity would create a network account or profile with false details, thereby providing a means to deceive other.

It would thus be advantageous to provide a method and system for improved authentication/assessment for users in accessing secure data, data networks and remote communication with other users.

All references, including any patents or patent applications cited in this specification are hereby incorporated by reference. No admission is made that any reference constitutes prior art. The discussion of the references states what their authors assert, and the applicants reserve the right to challenge the accuracy and pertinence of the cited documents. It will be clearly understood that, although a number of prior art publications are referred to herein; this reference does not constitute an admission that any of these documents form part of the common general knowledge in the art, in New Zealand or in any other country.

It is acknowledged that the term 'comprise' may, under varying jurisdictions, be attributed with either an exclusive or an inclusive meaning. For the purpose of this specification, and unless otherwise noted, the term 'comprise' shall have an inclusive meaning - i.e. that it will be taken to mean an inclusion of not only the listed components it directly references, but also other non-specified components or elements. This rationale will also be used when the term 'comprised' or 'comprising' is used in relation to one or more steps in a method or process.

It is an object of the present invention to address the foregoing problems or at least to provide the public with a useful choice.

Further aspects and advantages of the present invention will become apparent from the ensuing description which is given by way of example only.

Disclosure of Invention

According to a first aspect of the present invention there is provided a method of assessing an *entity* at a first *user terminal* connected to a *data network*, said method utilising a *control system* operable to perform the steps of:

- a) receiving an *access request* from at least one of:
 - said *entity*;
 - an assessing *user* at a second *user terminal* connected to the *data network*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* for a performance of a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) performing;

- an automated assessment of said video recording; and/or
- an invocation or facilitation of a transmission of said video recording from said *data store* and details of said *prompt* to a second *user terminal* for viewing and assessment by an *assessing user*.

Preferably, said *control system* receives an *assessment signal* from said *assessing user* and/or from said automated assessment.

Preferably, steps b) and c) are performed synchronously.

According to a second aspect of the present invention, there is provided a method of assessment of an *entity* at a first *user terminal* connected to a *data network*, said assessment performed by an *assessing user* at a second *user terminal* connected to the *data network*, the *control system* operable to perform the steps of:

- a) receiving an *access request* from said *entity* or said *assessing user*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* to perform a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking or facilitating transmission of said video recording from said *data store* and details of said *prompt* to said second *user terminal* for viewing and assessment by said *assessing user*;
- e) receiving from said *assessing user* an *assessment signal*.

According to a third aspect of the present invention, there is provided a *control system* for facilitating entity assessment of an *entity* at a first *user terminal* connected to a *data network*, said *control system* including a computer system with a computer processor coupled to a system memory and programmed with computer readable instructions executable to perform the following procedures:

- a) receiving and processing data relating to an *access request* from at least one of:
 - said *entity*;
 - an *assessing user* at a second *user terminal* connected to the *data network*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* for said *entity* to perform a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) performing:
 - an automated assessment of said video recording; and/or
 - invocation or facilitation of transmission of said video recording from said *data store* and details of said *prompt* to an second *user terminal* for viewing and assessment by an *assessing user*.

According to a fourth aspect of the present invention there is provided a *control system* for enabling entity assessment of an *entity* at a first *user terminal* connected to a *data network*, said assessment performed by an *assessing user* at a second *user terminal* connected to the *data network*, said *control system* including a computer system with a computer processor coupled to a system memory and programmed with computer readable instructions executable to perform the following procedures:

- a) receiving and processing data relating to an *access request* from said *entity* or said *assessing user*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* to perform a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking or facilitating transmission of said video recording from said *data store* and details of said *prompt* to said second *user terminal* for viewing and assessment by said *assessing user*;
- e) receiving from said *assessing user* an *assessment signal*.

According to a fifth aspect of the present invention, there is provided computer software for enabling entity assessment of an *entity* at a first *user terminal* connected to a *data network*, said computer software embodied in computer-readable instructions executable to perform the following procedures:

- a) processing data relating to an *access request* from at least one of:
 - said *entity*;
 - an *assessing user* at a second *user terminal* connected to the *data network*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* to perform a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) performing:

- an automated assessment of said video recording; and/or
- invoking or facilitating transmission of said video recording from said *data store* and details of said *prompt* to a second *user terminal* for viewing and assessment by an *assessing user*.

According to a sixth aspect of the present invention there is provided computer software for enabling assessment of an *entity* at a first *user terminal* connected to a *data network*, said assessment performed by an *assessing user* at a second *user terminal* connected to the *data network*, said computer software embodied in computer-readable instructions executable to perform the following procedures:

- a) receiving and processing data relating to an *access request* from said *entity* or said *assessing user*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* for said *entity* to perform a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking or facilitating transmission of said video recording from said *data store* and details of said *prompt* to said second *user terminal* for viewing and assessment by said *assessing user*;
- e) receiving and processing an *assessment signal* received from said *assessing user*.

As used herein, the term “*entity*” should be understood to refer to any person, organisation or virtual entity.

A “*user*”, as referred to herein is any *entity* accessing the *data network*, including “*registered users*” and “*unregistered users*”.

A “*registered user*”, as referred to herein is a *user* of the *data network* that has a set of *identifying characteristics* (and preferably other user details) stored in one or more related user records collectively forming a “*user account*” in a database in a *data store* accessible by the *control system*. Axiomatically, an “*unregistered user*” is a *user* that has no such credentials or account but otherwise has some form of access to the first *user terminal* and/or *data network*.

The term “*identifying characteristics*” as used herein refers to any characteristic of an *entity* that can be used to identify the *entity*, either singly or in combination with other characteristics. Exemplary *identifying characteristics* include name, gender, age, occupation, country-of-residence, nationality, profile image/photo, height, hair colour, eye colour, educational, sporting and health history and the like.

A “*persona*” as used herein refers to the aspect of an *entity*’s character that is portrayed to or perceived by the *assessing user*. The *identifying characteristics* of a *user account* may collectively act as a “*persona*” portraying a *user* or other *entity*. Additionally, a *persona* may be provided by external sources, e.g. famous persons may have an associated *persona* but may not be a *user* of the *data network*.

The “*prompt*” provided to the *entity* is *unpredictable* so that a believable pre-prepared response cannot be fabricated by an imposter.

It will be appreciated that reference herein to “*unpredictable*” prompts should also be understood to include random and pseudo-random prompts or any predetermined non-random selection of a prompt that prevents the *entity* from knowing which prompt will be provided.

As used herein, the term “*data network*” should be understood to refer to any electronic network having a *control system* capable of receiving and transmitting data from *user terminals*. A *data network* may thus be considered to include virtual private networks (VPN), the internet, telephone/cellular networks, local area (LAN), wide area (WAN), wireless, WIFI, satellite, radio, UHF, VHF, infrared, mesh networks, Bluetooth, ZigBee or any other network having one or more *control systems* and connected terminals.

The *data network* preferably includes a “*virtual network*” formed from connections between multiple *users* connected to the *data network*. Examples of *virtual networks* include: social networks, gaming, banking/financial, relation facilitation services (e.g. dating websites), government, commercial, organisational, military, academic, entertainment or the like. Typical “*virtual networks*” are normally embodied in related data records in a database. Each data record preferably corresponds to a *registered user* or a *user terminal* and groups of data records relating to the same *registered user* or *user terminal* form a “*user account*”.

Preferably, said *virtual network* may include a *relationship facilitation service* for allowing *users* to communicate with each other for the purposes of forming a relationship, e.g. a ‘dating’ or ‘matching’ service.

As used herein, the term “*user terminal*” refers to any device or collection of devices, at least one of which is capable of connecting to the *control system* to communicate on the *data network* and by way of example, includes a computer, mobile computing device, cellular phone, e-reader, tablet, PDA, games console, or combinations thereof. The *user terminal* may also be embodied in separate devices, e.g. a display capable of receiving data as well as a separate, distinct computer device for transmitting data.

It should be appreciated that the *entity* and *assessing user* may be located at the same *user terminal* at different time periods or may be at different *user terminals*, whether in the same location or remote to each other, thus the ‘first *user terminal*’ may be the same as the ‘second

user terminal in some circumstances and therefore it should be appreciated that reference herein to a “second *user terminal*” can be interpreted to include the “first *user terminal*” and vice versa.

The *control system* is preferably a computer server and/or system configured to receive and process the *access request* from a *user terminal*. It will be appreciated that the *control system* may comprise multiple distributed computing resources. Preferably, the *control system* may include a “cloud-computing” based system. As used herein, the term “cloud-computing” refers to a computing capability that provides an abstraction between the computing resource and its underlying technical architecture (e.g., servers, storage and networks), enabling on-demand network access to a group of configurable computing resources.

It should be appreciated that the *control system* may have system memory and a processor for executing software. It should be appreciated that these computing resources need not be in the same location, e.g. the *control system* may be a virtual system using ‘cloud-computing’ resources with distributed processors, software and memory resources.

Preferably, where the *data network* includes an internet social network, said *control system* may include one or more social network servers and a database.

In addition the *data network* may be connected to a third party or remote *control system* capable of sending and receiving data from the *data network*.

As used herein the term “*access request*” may refer to any request for “access” to data, a *virtual network*, communication with *users*, or to the *data network* itself and includes, but is not limited to direct or indirect:

- access to the *data network*;
- access, e.g. a ‘log-in’, to a *virtual network* e.g. a social network, relationship facilitation service, blog, chat-room, RSS feed, forum, data-sharing network or similar.
- access to publish information;
- access to a data resource;
- access to a *user terminal*, e.g. a log-in to a computer operating system;
- acceptance of a *contract*, e.g. a license, terms of use, purchase offer.
- access to communication with another *user*, e.g. sending of an instant message, e-mail, SMS message, dialling of phone number or VOIP network (e.g. Skype®) identifier;
- access to recover lost passwords or login information.

Preferably, the *prompt* is provided to the *entity* in conjunction with an *access request* provided in the form of a *contract* or offer of *contract*. The *contract* may be an agreement, deed, item, product, software, license, service, competition or any other application otherwise requiring a signature, agreement or the like. Thus, the video recording may be used as a video ‘signature’ or ‘record’ of acceptance, acknowledgement or rejection of the *contract*. Acceptance or acknowledgement of the *contract* may be indicated by performing the *prompted visible actions* correctly, and/or performing an action indicating acceptance, e.g. the prompt may include “make a ‘thumbs-up’ gesture if you agree to the terms of this license.

Preferably, the *control system* stores the *contract* and associated *video recording* in records related to the *accessed user account* or alternatively stores a record in the database linking the *contract* with the *video recording*. Thus, in the event of a dispute, the *control system* may retrieve the *contract* and associated *video recording* to allow assessment. The *assessing user* or automated assessment may thus be able to assess the *video recording* to determine that the *entity* was presented with the *contract* and indicated their acceptance or rejection. Thus, in some applications, the *video recording* may be used as a *signature* by which the *entity* can be identified.

In one embodiment of the present invention the *first user terminal* may be a user-operable device such as an operating system, vehicle, machinery or the like. Preferably, the *access request* is to access said user-operable device said *entity* is provided access to operate said user-operable device only if said *control system* classifies said *entity* positively. The user-operable device may thus be secured from unauthorised access or operation. The present invention may be used similarly to a security system to restrict access to an operating system, vehicle, machinery or the like, wherein the *entity* is assessed before being allowed to access or operate that system, vehicle or machinery.

The *access request* need not be received directly from the *entity* or *assessing user* and may instead be received via another *user*, *entity*, server, system, proxy or network.

Reference herein to “invoke”, “invoking”, “invoked” and “invocation” with respect to a procedure related to the *control system* should be understood to refer to any method, act or process for causing the relevant procedure to be carried out and includes:

- directly conducting the relevant procedure;
- generating and/or transmitting a signal or data that triggers the relevant procedure;
- generating and/or transmitting a signal or data to another system that performs the relevant procedure.

Reference herein to “facilitating transmission” should be interpreted to include generating and/or transmitting a signal or data that is used in transmission of data in and/or between a *data store*, the *control system* and/or *user terminal*.

The “*visible prompted action*” includes any body action that can be visually observed (and optionally verified) as occurring and by way of example, may include: facial gestures, hand and other body gestures. Body actions involving hands, face and other body parts are visible and normally easily recognisable and thus are particularly suited to the present invention. Accordingly, the *visible prompted action* preferably excludes typing, writing or other data input to the first user terminal.

To aid clarity and avoid prolixity, reference herein has been made to a single “video recording” being made, however, this should not be seen to be limiting and it should be understood that reference to a “video recording” in the singular also includes multiple recordings.

The video recording is referred to herein as being received from the first *user terminal* accessed by the *entity*. However, it should be appreciated that this recording may also be passed through intermediary servers, proxies, terminals, networks, routers or similar before reaching the *control system* and should not be seen to be limited to direct transmission from the *user terminal*.

As referred to herein the term “*data store*” refers to a local, remote and/or distributed *data store* accessible by the *control system* and by way of example includes digital storage media such as a computer hard drive, solid-state memory, computer RAM, ROM, volatile flash memory, non-volatile flash memory or the like. The *data store* may be located at a *user terminal*, at the *control system* or remotely.

It should be appreciated that the term “store” with respect to data should be understood to include permanent or temporary storage, caching, streaming or the like, e.g. it may not be necessary to store the entire video recording in some applications and instead the video recording could be streamed directly in packets to the automated assessment or second *user terminal*.

As used herein the term “video recording” should be understood to refer to any electronic recording of moving visual elements and is preferably a digital recording.

The “video recording” is preferably capable of being streamed or downloaded to/from a *user terminal*.

It will be appreciated that reference to “receiving” and “providing” includes the various modes of transmitting/receiving electronic data, e.g. streaming, uploading, downloading and can be made across any wired or wireless communication medium.

The “*assessment signal*” may be any form of electronic signal or data capable of being read by said *control system* and by way of example may include a signal or data generated by a java-script control, compiled Adobe Flash® application, HTML, text message, *user-interface* control or button or any other type of *user* input control or sensor that can accept and infer *user* commands. A hand or body gesture may also form a *user* input that is interpreted by a gesture recognition system as an *assessment signal*, e.g. a ‘thumbs up’ gesture may be interpreted as an *assessment signal* with a positive indication.

Preferably, upon receiving the *access request*, the *control system* determines a *user account* (hereinafter “*accessed user account*”) corresponding to credentials provided by the first *user terminal*. Such credentials may be manually or automatically entered at the first *user terminal* by the *entity* or alternatively may be stored or cached on the first *user terminal* or *control system* and processed by the *control system* when the *access request* is made.

The term “*classification*”, as used herein, refers to a determination made by the *control system* upon receiving and processing an *assessment signal*. Preferably, the *control system* generates data representing the *classification* made. The *classification* may take many forms but typically will be ‘positive’, ‘negative’ or ‘inconclusive’.

It should be appreciated that the *assessing user* need not necessarily be another *user* having the same security or authorisation status as the *entity*, i.e. the *assessing user* may be a security official or other ‘*super-user*’ assigned to assess entities. This ‘*super-user*’ assessment system may be useful, for example, in banking or financial systems where an *entity* attempts to access financial accounts relating to the *accessed user account*, i.e. a *super-user* may be an employee assigned by the bank/finance provider to assess the *entity* in the aforementioned method.

Preferably, the *assessing user* is a *registered user*.

Preferably, the *control system* at least partially controls data transmission between said *user terminals* via the *data network*.

Preferably, the *entity* may only have data access to the first *user terminal* and/or *data network* if they provide user credentials corresponding to a said *user account*. Such provision of *user* credentials may be provided manually or automatically by the *entity* or alternatively may be stored or cached on the first *user terminal* or *control system* and processed by the *control system* when the *access request* is made.

The *assessment signal* preferably includes at least one positive, negative or inconclusive *assessment signal*.

The assessment may be based on a number of factors and therefore numerous circumstances may lead to a positive, negative or inconclusive *assessment signal* being made. The aspects to be assessed by the *assessing user* or automated assessment preferably includes at least one of the following assessments:

- *Actions assessment*- e.g. whether or not said *entity's* prompted performance is a valid response to said *prompt*.

Thus, the *assessment signal* may be used as an indication of whether the *entity* in the video recording is the same *entity* present when the *access request* was made and therefore provide other *users* with the reassurance that the person they communicate with is the *entity* shown in the video recording.

It will be appreciated that the *assessing user* may determine the validity of the prompted action based on a number of factors, including:

- the response time of the *entity* to the *prompt*;
- the accuracy of the performance to the corresponding *prompt* instructions;
- any personal prior knowledge of the appearance and behaviour of the *user* corresponding to the *accessed user account*, and/or
- their intrinsic human assessment of the genuineness of the performance.

Thus, for example, if a *persona* that corresponds to the *accessed user account* is known to the *assessing user*, the *assessing user* may be able to discern that errors or even high accuracy in the *entity's* performed *prompts* are in or out of character with their knowledge of the *persona*. Consequently, the *assessing user's* interpretation of an *entity's* prompted performance may differ according to any prior knowledge of the corresponding *persona*.

- *Visual assessment* – e.g. whether or not the *entity* has been assessed as having a characteristic the same or similar to at least one *identifying characteristic* of said *accessed user account*.

An assessment may, by way of example, be made by comparing the *entity* in the video recording with a profile image, name, gender, residence location, occupation and/or other *identifying characteristic* of the *accessed user account*. Thus, other *users* may be reassured that the *entity* they communicate corresponds to the *persona* portrayed by the *accessed user account* and not an imposter.

- *Persona assessment* – e.g. whether or not the *entity* is recognised as corresponding to the *persona* of the *accessed user account*.

Thus, while the *assessing user* may believe the *entity* validly performs the prompted action and matches sufficient *identifying characteristics* of the *accessed user account* (i.e. a 'positive' *Actions assessment* and *visual assessment*), the *assessing user* may not recognise the *entity* as matching the *persona* portrayed or expected. This may indicate that the *entity* does not match the *persona* that the *assessing user* anticipated, e.g. there may be many entities genuinely purporting to be *users* having the name "John Smith" that the *assessing user* may assess as having valid actions and matching profiles, but are not recognised by the *assessing user*.

- *General assessment* – e.g. the video recording may be assessed for authenticity to determine if the video appears tampered with or is otherwise suspicious. A *general assessment* may also be made of the *entity* to assess any other factors not covered by the *actions assessment*, *visual assessment* or *persona assessment*.

Preferably, the *assessment signal* includes, for each type of assessment made, a positive, negative or inconclusive signal.

Preferably, said *control system* uses the *assessment signal* to classify, or contribute to a determination to classify said *entity*.

Preferably, the *classification* of the *entity* is determined by the *assessment signal*. Examples of potential *classifications* are outlined in table 1 below.

TABLE 1

Actions Assessment	Visual Assessment	Classification
Positive	Positive	Positive

Positive	Negative	Negative
Negative	Positive	Negative
Negative	Negative	Negative

Preferably, the assessment also includes an indication of whether the *assessing user* recognises the *entity* and the *classification* of the *entity* is as outlined in table 2 below.

TABLE 2

<i>Actions Assessment</i>	<i>Visual Assessment</i>	<i>Persona Assessment</i>	<i>Classification</i>
Positive	Positive	Positive	Positive
Positive	Positive	Negative	Inconclusive
Positive	Negative	Positive	Negative
Positive	Negative	Negative	Negative
Negative	Positive	Positive	Inconclusive
Negative	Positive	Negative	Negative
Negative	Negative	Positive	Negative
Negative	Negative	Negative	Negative

It should be appreciated that the *classifications* above may be altered to suit a particular application or security policy, e.g. in one embodiment, a negative *actions assessment* in table 2 may lead to a “negative” *classification*.

In some circumstances, an *assessment signal* may include an indication that an “inconclusive” assessment has been made, thereby indicating that a positive or negative assessment has not been made for some reason. An “inconclusive” assessment may occur, for example, where:

- a poor quality or incomplete video recording is received;
- there are insufficient or incomplete *identifying characteristics* in the *accessed user account*, and/or
- the *entity* is not recognised by the *assessing user*.

It should also be appreciated that different positive and negative *assessment signals* are not both required, e.g. the absence of a positive *assessment signal* may be interpreted as a negative *assessment signal* or vice versa.

According to one aspect, where a negative *persona assessment* is made (e.g. if the *entity* is not the person expected by the *assessing user*) then the *control system* may be configured to request the assessing user provide additional feedback about the *entity*. The *assessing user* may for example recognise the *entity* as corresponding to another *persona* known to the *assessing user*, the *assessing user* thereby identifying the *entity* as matching that other *persona* and not the *persona* portrayed by the *accessed user account*.

The *control system* can have numerous configurations for processing a negative *classification*. Example configurations may include one or more of the following procedures, whereby the *control system* may;

- record to the *accessed user account* that the *entity* has had a negative *classification*;
- invoke a warning notification for other *users* attempting to communicate with the *entity* that a negative *classification* has occurred. Other *users* will thus be warned that the *entity* may be an imposter and should not be communicated with, or at least should be treated with caution;
- block the *entity* from communication with other *users*;
- suspend or cancel the *accessed user account*;
- repeat steps b) – d) of the aforementioned method;
- repeat steps b) – e) of the aforementioned method;
- send a warning notification to a network administrator or other authority to investigate the *entity* and/or negative assessment;
- selectively restrict the type of communication allowed between the *entity* and other *users*. The *control system*, by way of example, may prohibit sending of photos and videos while permitting text-based communication;
- selectively restrict the type of access allowed or the extent of access, e.g. access to certain data on the *data network* may be restricted.

The *control system* can alternatively, or in addition, have a number of different configurations for processing negative *classifications* resulting from multiple user assessments or multiple negative *classifications*. As examples, these may include one or more of the following procedures whereby the *control system* may;

- i) record that the *accessed user account* has had multiple negative *classifications*. The number, or proportion of negative *classifications* made (indicating 'negative' overall assessments) can be used as a measure of the validity or 'trust' ranking of the *entity*, i.e. the greater the number (or higher proportion) of negative assessments, potentially the less trust-worthy the *entity* may be;
- ii) generate a warning notification for other *users*, the notification indicating that multiple negative *classifications* have been made for assessment attempts by the *entity*. The notification may include details of:
 - a. number of negative *classifications*;
 - b. number of negative *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by other *users*;
 - d. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - e. permutations and/or combinations of the above;
- iii) restrict the *entity's* access when a predetermined threshold is reached or exceeded of:
 - a. number of negative *classifications*;
 - b. number of negative *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by *users*;
 - d. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - e. permutations and/or combinations of the above;
- iv) suspend or cancel the *accessed user account* and prevent access when a predetermined threshold is reached or exceeded of:
 - a. number of negative *classifications*;
 - b. number of negative *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by other *users*;
 - d. a *assessment rating* assigned to the *entity* by other *users* where those other *users'* contribution to the *entity's* trust ranking is determined by the respective trust rankings of the contributing *users*;
 - e. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - f. permutations and/or combinations of the above;
- v) repeat steps b) to d) or b) to e) of the aforementioned method when a predetermined threshold is reached or exceeded of:
 - a. number of negative *classifications*;
 - b. number of negative *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by other *users*;
 - d. a *assessment rating* assigned to the *entity* by other *users* where those other *users'* contribution to the *entity's* trust ranking is determined by the respective trust rankings the contributing *users*;
 - e. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - f. permutations and/or combinations of the above;
- vi) A warning notification may be sent to a network administrator or other authority to investigate the negative assessment when a predetermined threshold is reached or exceeded of:
 - a. number of negative *classifications*;
 - b. number of negative *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by other *users*;
 - d. a *assessment rating* assigned to the *entity* by other *users* where those other *users'* contribution to the *entity's* trust ranking is determined by the respective trust rankings the contributing *users*;
 - e. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - f. permutations and/or combinations of the above.

The *control system* can have a number of configurations for processing a 'positive' assessment *classification*. As examples, these configurations may include one or more of the following procedures whereby the *control system* may:

- i) record to the *accessed user account* that a positive *classification* has been made;
- ii) invoke a notification for other *users* attempting to communicate with the *entity* that a positive *classification* has occurred;

- iii) permit communication between the *entity* and other *users*;
- iv) provide the *entity* with read and/or write access to the *accessed user account*;
- v) selectively restrict the type, format or medium of communication allowed between the *entity* and other *users*. The *control system*, by way of example, may prohibit sending of photos and videos while permitting text-based communication;
- vi) selectively permit/restrict the type of access allowed or the extent of access, e.g. access to certain data on the *data network* may be restricted.

The *control system* can alternatively, or in addition, have a number of different configurations for processing positive *classifications* from multiple *users* or multiple positive *classifications*. As examples, these configurations may include one or more of the following procedures, whereby the *control system* may:

- vii) record to the *accessed user account* that multiple positive *classifications* have been made. The number, or proportion of positive *classifications* made (indicating 'positive' overall assessments) can be used as a measure of the validity or 'trust' ranking of the *entity*, i.e. the greater the number (or higher proportion) of positive *classifications*, potentially the more trust-worthy the *entity* may be;
- viii) generate a notification for other *users* attempting to communicate with the *entity* that multiple positive *classifications* have been made for assessment attempts by the *entity*. The notification may include details of:
 - a. number of positive *classifications*;
 - b. number of positive *classifications* as a proportion of total positive and negative *classifications*;
 - c. a *assessment rating* assigned to the *entity* by other *users*;
 - d. time, date and/or location the negative and/or any positive *classifications* were made; and/or
 - e. permutations and/or combinations of the above.

The *control system* can have a number of configurations for processing an 'inconclusive' *classification* or *assessment signal*. As examples, these configurations may include one or more of the following procedures whereby the *control system* may:

- i) record to the *accessed user account* that an inconclusive *classification* has been made;
- ii) invoke a notification for other *users* attempting to communicate with the *registered user* that an inconclusive *classification* has occurred;
- iii) permit or restrict communication between the *entity* and other *users*;
- iv) restrict read and/or write access to the *accessed user account*;
- v) selectively restrict the type, format or medium of communication allowed between the *entity* and other *users*. The *control system*, by way of example, may prohibit sending of photos and videos while permitting text-based communication;
- vi) selectively permit/restrict the type of access allowed or the extent of access, e.g. access to certain data on the *data network* may be restricted;
- vii) advise the *entity* of the reason for the inconclusive assessment (e.g. poor video quality, "please enter gender") and *prompt* the *entity* to correct the problem.

The *control system* can alternatively, or in addition, have a number of different configurations for processing inconclusive *classifications* from multiple *users* or multiple inconclusive *classifications*. As examples, these configurations may include one or more of the following procedures, whereby the *control system* may:

- i) record to the *accessed user account* that multiple inconclusive *classifications* have been received. The number, or proportion of inconclusive *classifications* received can be used as a measure of the reliability of assessments of the *entity* or problems with the *accessed user account* or first *user terminal*, i.e. the greater the number (or higher proportion) of inconclusive *classifications*, potentially an *assessing user* is less able to make a satisfactory assessment;
- ii) generate a notification for other *users* attempting to communicate with the *entity* that multiple inconclusive *classifications* have been received for assessment attempts by the *entity*. The notification may include details of:
 - a. number of inconclusive *classifications*;
 - b. number of inconclusive *classifications* as a proportion of total *classifications*;
 - c. an *assessment rating* assigned to the *entity* by *assessing users*;

- d. time, date and/or location the inconclusive *classifications* were received; and/or
- e. permutations and/or combinations of the above.

iii) advise the *entity* of the reason for the inconclusive assessments (e.g. poor video quality, "please enter gender") and *prompt* the *entity* to correct the problem.

Preferably, at least one audio recording of said *visible prompted action* is recorded and stored, preferably with said video recording. The use of both video and audio recordings may further minimise the chance of deception as the *assessing user* will also be able to assess if the *entity* is making the audio (e.g. speaking) in synchronisation with the video showing the *entity* making the sounds. An audio recording also provides the *assessing user* with more potentially recognisable information about the *entity*, including their accent, tone and other voice characteristics. Additionally, the *prompt* may ask a question of the *entity* which, when answered, may provide interesting or important information to the *assessing user*.

In another embodiment, a sequence of touch or gesture-actions may also be recorded, i.e. via using a touch screen or a gesture recognition system such as the Microsoft™ Kinect™ system.

Preferably, the *prompt* is provided in a form selected from the group including: text, graphical objects, symbols, representations, audible sounds, video, animations, combinations and permutations thereof.

Preferably, the *prompt* is provided as text or images to improve rapid cognition relative to a dynamic *prompt* such as video, audio or animations. Preferably, the *prompt* is only provided to the *entity* for a predetermined duration. The duration may thus be set for particular *prompts* to ensure the *entity* has enough time to perform the prompted action. Preferably, the duration is less than thirty seconds and more preferably less than five seconds. It will be appreciated that the duration may be varied for a particular *prompt* depending on the time required for the *entity* to assimilate that *prompt* and then perform the corresponding *action*. Exemplary durations may be between one and ten seconds.

Preferably, multiple *prompts* are provided for the *entity* to perform corresponding actions, at least one said action being visible. The multiple *prompts* may be provided all at step b) of the aforementioned method or alternatively, the two steps b) and c) may be repeated for each individual *prompt*, e.g. a first *prompt* could be invoked (step b)) and then recorded and stored (step c)) and then a second *prompt* invoked (step b)) and recorded and stored (step c)).

It will be appreciated that the longer the *total prompt time* (i.e. time between the start of the first *prompt* and the end of the last *prompt*), the longer an *entity* must wait, which may prove overly burdensome or onerous for many types of *access request*. Therefore, in one preferred embodiment, the total time between the start of the first *prompt* and the end of the last *prompt* is less than thirty seconds and more preferably less than fifteen seconds. Preferably, at least three said *prompts* are provided. Three *prompts* permit a large number of unique combinations to avoid simple forgery without being overly onerous on the *entity*. However, this should not be seen to be limiting as the number of *prompts* may be changed to suit the application.

It will be appreciated that an 'imposter' *entity* trying to falsely obtain a positive *classification* in the aforementioned assessment method may try and obtain pre-recordings of another *entity* that has characteristics the same or similar to the *identifying characteristics* in the *accessed user account* or the *persona* the *accessed user account* portrays. The imposter may persuade the other *entity* to perform various actions and then try to provide these pre-recordings when prompted. If such an imposter is somehow able to obtain such a recording of for use in the assessment, the imposter may be able to deceive the *assessing user* with a single such recording. However, requiring a sequence of multiple *visible prompted actions* greatly reduces the risk of the assessment methods of the present invention being circumvented by an imposter obtaining pre-recordings of single actions.

In a further embodiment, the *prompts* may be provided in a time-delimited sequence so that the *entity* is required to perform each *visible prompted action* in a particular time sequence. By way of example, the timing of the *prompts* may be in synchronisation with a song, beat, tune or timer or may be provided at preset intervals, e.g. five seconds between each *prompt*.

Preferably, said *prompts* are provided to the *entity* with a time delay between each *prompt*. The time delays between each *prompt* are preferably selected from the range between zero seconds and five seconds.

In a further embodiment, the time delays between pairs of consecutive *prompts* differ and are preferably of an *unpredictable* length within a predetermined range, e.g. the time delay between first and second *prompts* may be five seconds while time delay between second and third *prompts* is ten seconds. This further minimises the risk of falsified pre-recordings being used to deceive other *users* as a pre-recording would

be evident if the actions are not appropriately synchronised with the *prompts*. Preferably, the details of the *prompts* provided to the assessing user and/or for analysis are provided in synchronisation with the video recording.

Preferably, the video recording may be controlled by the *control system*, e.g. the *control system* may invoke video capture by providing an instruction signal to a recording device (e.g. webcam and/or microphone) at the first *user terminal*, which then records the performance in real-time. This increases the difficulty of falsifying such recordings by using pre-recordings or other *user*-provided recordings will not be accepted as valid recordings. Further authentication methods for the recording can be used, e.g. the recording may be tagged with a time, date and IP address, geo-location marker or other time/location identification system. Details of the relevant *user terminal* could also be provided, e.g. serial number, vendor ID information or the like.

In one preferred embodiment the *control system* may invoke the *prompt* by providing computer-executable code or computer-readable data to software on the first *user terminal* which then generates the *prompt* accordingly. The code and/or data may also preferably indicate which *prompt* is to be displayed and time delays between pairs of consecutive *prompts*. Thus, it should be understood that reference herein to the *control system* invoking a *prompt* may also be interpreted to include the *user terminal* generating *prompts* on receiving an invocation signal or appropriate data from the *control system*. It will also be appreciated that the *control system* may send code or data to another computer system for generating a *prompt* which is then sent to the terminal.

In one embodiment, the *control system* may reject recordings if received after a predetermined time-period from when the *prompts* are invoked, thereby reducing the time and therefore potential for false recordings to be provided.

It will be appreciated that the aforementioned methods may be applied for communication between more than two *users*, e.g. the video recording may be provided to multiple different *users* for assessment of the *entity*. It will also be appreciated that the aforementioned methods may be performed for the second and subsequent *users* as well, i.e. the *assessing user* may also be assessed by the assessed *entity* and/or other *users*.

Preferably, the *control system* is configured to receive and process data relating to a *view request* from said *assessing user* to view said video recording before invoking or facilitating transmission of said video recording to said *assessing user*.

Preferably, the *data store* for storing the video recording is provided separately to the *user data store* containing the database. Preferably, said video recording is stored with a unique identifier. Storing the video recording separately to the database in the *user data store* ensures that if the 'video' *data store* is somehow accessed by an unauthorised *entity*, the video recording will not have *identifying characteristics* related to the accessed *user account*. The unique identifier may also be stored in the database against the accessed *user account* and so can be used by the *control system* to invoke or facilitate transmission of the matching video recording from the video *data store* when required.

In an alternative embodiment, the video recording may be stored in the database in the *user data store* in a database record related to the accessed *user account*.

Storage of the video recording alleviates the requirement for an immediate assessment of the *entity* and thus has one of the advantages of text-based communication, i.e. there is no requirement for both the *entity* and *assessing user* to be accessing the network or communications at the same time. The *control system* may, by way of example, conduct the steps b) to d) when the *entity* makes an *access request*. The video recording may then be stored in the *data store* and retrieved at a later time when requested by the *assessing user*, or alternatively may be provided automatically when the *assessing user* makes an *access request* for communication with the *entity* and/or accessed *user account* or *persona* portrayed by the accessed *user account*.

The aforementioned method, system and software may thus allow *users* to communicate primarily by text or audio to maintain real-time visual privacy from other *users* (by avoiding the need for real-time video communication) while also ameliorating the otherwise inherent risk of deceit, as the *assessing user* is able to visually verify that the *entity* is the same person as in the recording by matching the performance in the recording to the details of the prompted actions. If there is no match then this indicates the *entity* is trying to deceive the *assessing user* or at least may not be following the *prompt* instructions. Without such *prompt* generation and assessment, the *entity* may provide a false video recording and deceive the *assessing user*.

The *assessing user* can also visually verify whether the *entity* has characteristics the same or similar to the *identifying characteristics* of the accessed *user account*. A human's innate ability to recognise facial features and particularly expressions and body language provides a very efficient and accurate means of recognition. The *assessing user* can choose to reject the communication or take other action if the *entity* is negatively assessed. The *assessing user* may also choose to warn other *users*, a network administrator, police or other authority.

It will be appreciated that a video recording provides far more recognisable information about a person than a static image. A person's characteristic nuances can make it far easier to positively identify than relying on a static image.

The aforementioned method, system and software may thus provide an efficient 'peer-assessment' system that is more effective than text-based authentication systems and allows other *users* (peers) to conduct the assessment, which is in contrast to conventional systems which place the burden of assessment on the network provider or security software.

Users may provide active feedback to the system via an *assessment signal* which can be used to indicate whether an assessed *entity* is deemed to be genuine and should be positively classified. Alternatively, *users* can make an assessment without feedback and choose whether or not to communicate with the *entity* based on their own assessment.

In an alternative embodiment, the *assessing user* may be supplanted with an automated assessment system. Thus, according to another aspect of the present invention there is provided a method of assessing an *entity* at a first *user terminal* connected to a *data network*, said method utilising a *control system* operable to perform the steps of:

- a) receiving an *access request* from at least one of:
 - said *entity*;
 - a *user* at a second *user terminal* connected to the *data network*;
- b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* for a performance of a *visible prompted action*;
- c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking an automated assessment of said video recording;
- e) generating an *assessment signal* indicative of said assessment.

According to yet another aspect of the present invention there is provided a *control system* capable of assessing an *entity* at a first *user terminal* connected to a *data network*, said *control system* including a computer system with a computer processor coupled to a system memory and programmed with computer readable instructions executable to perform the following procedures:

- a) receive data relating to an *access request* from at least one of:
 - said *entity*;
 - a *user* at a second *user terminal* connected to the *data network*;
- b) invoke or facilitate transmission of at least one *unpredictable prompt* to said *entity* to perform a *visible prompted action*;
- c) invoke storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking an automated assessment of said video recording;
- e) generating an *assessment signal* indicative of said assessment.

Preferably, there is provided computer software for enabling assessment of an *entity* at a first *user terminal* connected to a *data network*, said computer software embodied in computer-readable instructions executable to perform the following procedures:

- a) process data relating to an *access request* from at least one of:
 - said *entity*;
 - a *user*, at a second *user terminal* connected to the *data network*;
- b) invoke, in response to receiving said *access request* data, at least one *unpredictable prompt* for said *entity* to perform a *visible prompted action*;
- c) invoke storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
- d) invoking an automated assessment of said video recording;
- e) generating an *assessment signal* indicative of said assessment.

Preferably, said automated assessment includes assessment by a gesture recognition system, wherein said *assessment signal* respectively includes a positive or negative indication of whether or not said *entity* validly performed said prompted action.

Preferably, said automated assessment includes assessment by a facial recognition system to analyse the *entity's* face with respect to an *identifying characteristic* in the accessed *user account* and wherein said *assessment signal* respectively includes a positive or negative indication of whether or not said *entity* is assessed as having a facial characteristic the same or similar to said *identifying characteristic*.

Preferably, said *identifying characteristic* includes a pre-recorded image, video recording and/or stored biometric data of a face.

Preferably, said *control system* classifies, or contributes to a determination to classify, said *entity*.

Preferably, said *control system* includes said gesture recognition system.

Preferably, said *control system* includes said facial recognition system.

In an alternative embodiment, the automated assessment may be conducted remotely to said *control system* while being invoked by said *control system*.

The *control system* preferably includes software algorithms in conjunction with one or more cameras at the first *user terminal* to record and assess the action performed and/or face of said *entity*.

Face and gesture recognition technology is well-known in the art and will not be described in detail herein. However, it will be appreciated that the face recognition system should be capable of detecting facial features and comparing with a reference image, video or biometric data to determine a correlation rating indicative of the similarity between the recorded face and a reference image or video. A gesture recognition system should be capable of detecting visible actions such as hand, facial and/or body gestures and comparing with reference actions or data to determine the gesture performed. The Microsoft™ Kinect™ system is an example of a system including both facial and gesture recognition systems.

In a further embodiment, the *control system* may be configured to assess the video recording using said facial recognition system and compare the recorded face with *identifying characteristics* of other *user accounts* in a *user database*. Thus, the *control system* may be capable of identifying multiple *user accounts* that have *identifying characteristics* the same or similar to the facial characteristics of the recorded *entity*, which may indicate that a single *entity* has multiple *user accounts*, e.g. the *entity* may have aliases. The network provider/administrator may then take appropriate action to investigate the *entity* and determined *user accounts* to determine whether the *entity* is falsely portraying themselves as multiple different people.

In another embodiment, the *control system* may preferably use said face recognition system to assess the *entity* and compare against a database of *user accounts* to identify a *user account* that has *identifying characteristics* that are the same or similar to the facial characteristics of the recorded *entity*. Thus, an *entity user* can be provided access to the *data network* by letting the facial recognition system 'recognise' them. Preferably, the *control system*, in conjunction with the gesture recognition system and/or face recognition system, is configured to determine when a *visible action* has been performed by said *entity* and invoke or facilitate transmission of another *prompt* to said *first user terminal* to perform another *visible action*. Thus, rather than providing multiple *prompts* in a predetermined time-sequence, the *control system* may determine when the next *prompt* is required based on the performance response to the previous *prompt*. The *control system* is however preferably configured to provide each *prompt* within a maximum time-limit from the previous *prompt* to thereby reduce the risk of an *entity* providing a pre-recorded *video recording* of the *prompted visible actions*. Preferably, said time limit is less than twenty seconds.

In another embodiment, the facial recognition system may be configured to analyse the recordings to:

- identify entities accessing the *data network* that have similar facial characteristics to each other, e.g. an *entity* may have access to multiple *user accounts* with one or both accounts being an alias, wherein the face recognition system can assess the video recording to identify any matching *identifying characteristics* to determine such duplicates and thereby provide administrators with the ability to remove; and/or
- compare the facial biometrics in the video recording with *identifying characteristics* stored against *user accounts* to identify the corresponding *entity* in the video recording. This method allows the *control system* to automatically recognise and retrieve *user identifying characteristics* which match the *entity* in the video recording. This method may also allow the *control system* to suggest to a *user* that other *users* with similar reference *identifying characteristics* may be genetically related or otherwise connected in some way.

The aforementioned automated methods, software and systems, may provide an assessment having many of the benefits of the earlier aforementioned methods requiring *user* assessment but without the requirement of an assessing. Thus, this automated assessment system may be useful in applications where an *assessing user* is not available and/or where other *users* cannot or should not be trusted as an *assessing user*. In banking applications for example, an ATM or online banking system may incorporate the automated *control system*, method and software as aforementioned to allow *users* to securely access their bank accounts.

Similarly, other applications where such an automated system may be useful may include:

- logging on to a computer, mobile device or other *user terminal*;

- accessing or operating a user-operable device such as a vehicle or machinery.
- smart phone access;
- physical access, e.g. through security doors;
- *virtual network* login.

In yet another embodiment, the aforementioned automated method, system and software may be utilised with a said *control system* located in a *user terminal* wherein the aforementioned automated assessment process is required in order to access said *user terminal*.

In another embodiment, the aforementioned methods may be used to assess the competency of the *entity*, e.g. the *prompt* may request the *entity* to perform a sobriety, fatigue or coordination test or other competency assessment, wherein *access* is granted only if the *control system* makes a positive *classification*.

It will be appreciated that there are numerous gesture-based competency tests to determine the physical and/or mental coordination of the *entity* and any of these tests may be used, e.g. one test includes a 'finger count' where the *entity* is prompted to touch each finger of their hand to their thumb and count with each touch (1, 2, 3, 4, 4, 3, 2, 1). The *assessment* made may incorporate a number of factors, including:

- degree of delay between the *prompt* and the *visible prompted action*;
- variation from calibrated reference actions;
- unprompted repetition of actions.

The aforementioned method may find particular application in *assessing* the authority and/or competency of *entities* attempting to operate machinery that is dangerous or has a high-skill requirement or vehicles such as military, industrial or service vehicles or the like. In vehicles for example, the vehicle ignition may not be operable until the *entity* has been assessed and a positive *classification* is made indicating the *entity* is authorised and deemed competent to operate that vehicle.

The aforementioned *control system* may be installed or connected to a military or para-military vehicle to prevent enemy combatants or other unauthorised *entities* from operating the vehicle.

The *control system* may preferably be configured to provide data to the *assessing user* or *automated assessment* indicating *visible actions* that are invalid responses to the *prompt*, e.g. the *prompt* may be "touch your nose" wherein if the *entity* uses their left hand the *visible prompted action* is deemed 'invalid' and a negative *classification* is made. Thus, the *control system* may be used with a set of rules that can assist the assessment and/or indicate coercion of an *entity* who has knowledge of those rules.

It should be appreciated that the various aforementioned methods, systems and software may be combined together in various iterations to suit a particular application.

The aforementioned aspects of the present invention may thus provide an enhanced form of *entity* assessment that negates many of the problems inherent in text-based *user-assessment* systems or live video communications.

Brief Description of Drawings

Further aspects and advantages of the present invention will become apparent from the following description which is given by way of example only and with reference to the accompanying drawings in which:

- Figure 1 shows a pictorial representation of two *users* communicating in a prior art *data network*;
- Figure 2 shows a schematic logic diagram of a network *control system* according to one embodiment of the present invention;
- Figure 3 shows a high-level flowchart representing a first stage of a method of 'peer assessment' of an *entity* according to one embodiment of the present invention;
- Figure 4 shows a high-level flowchart representing a second stage of the method of 'peer assessment' of figure 3;
- Figure 5 shows a high-level flowchart representing an alternative to the second stage of the method of *entity* assessment of figure 4;
- Figure 6 shows a schematic logic diagram of a network *control system* according to another embodiment of the present invention.
- Figure 7 shows a simplified pictorial representation of a *data network* and *control system* implementing a method of *entity* assessment according to one preferred embodiment of the present invention;
- Figure 8 shows the *data network* and method of figure 7 with one possible assessment;
- Figure 9 shows the *data network* and method of figure 7 with another possible assessment;
- Figure 10a shows a screenshot of an example of the initial stage of the method of 'peer assessment' of figures 3 and 4;

Figure 10b shows a screenshot of a *user* profile and their friends in one example of the method of 'peer assessment' of figures 3 and 4;

Figure 11 shows a high-level flowchart representing an automated method of *entity* assessment according to a second preferred embodiment.

Best Modes for Carrying out the Invention

Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings. While the present invention will be discussed in conjunction with the following embodiments, it will be understood that they are not intended to limit the present invention to these embodiments alone. On the contrary, the present invention covers alternatives, modifications, and equivalents which may be included within the spirit and scope of the present invention as described herein and as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, embodiments of the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present invention.

Some portions of the detailed descriptions which follow are presented in terms of procedures, logic blocks, processing, protocols and other symbolic representations of operations on data bits within a computer memory. These descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work. In the present application, a procedure, logic block, process, function, or the like, is a self-consistent sequence of steps or instructions leading to a desired result. Reference herein will also be made to various "algorithms" which should be understood to refer to one or more computer-implemented processes, procedures, functions and/or calculations that are capable of accessing, reading, processing, modifying, creating or otherwise manipulating data.

The "steps" of each method are those requiring physical manipulations of physical quantities. Usually, although not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated in a computer system.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing the terms such as "aborting," "accepting," "accessing," "adding," "adjusting," "analyzing," "applying," "assembling," "assigning," "balancing," "blocking," "calculating," "capturing," "combining," "comparing," "collecting," "creating," "debugging," "defining," "delivering," "depicting," "detecting," "determining," "displaying," "establishing," "executing," "filtering," "flipping," "generating," "grouping," "hiding," "identifying," "initiating," "interacting," "modifying," "monitoring," "moving," "outputting," "performing," "placing," "positioning," "presenting," "processing," "programming," "querying," "receiving," "removing," "repeating," "resuming," "sampling," "selecting," "simulating," "sorting," "storing," "subtracting," "suspending," "tracking," "transcoding," "transforming," "transferring," "transforming," "unblocking," "using," or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

To aid brevity and clarity, reference herein will also be made to hardware devices in the singular, however, such reference should be interpreted to also include multiple components forming the device and/or multiple devices sharing the function, e.g. reference herein to a "server" should be interpreted to include multiple servers, distributed servers, cloud-based servers and the like.

Figure 1 shows a known prior art *data network* (1) controlled by a *control system* provided in the form of server (2) accessible over a communication system such as the internet or other wired or wireless communication medium. *User terminals* (3, 4) are connected to, or routed by, the *data network* (1) by server (2) and are provided in this example in the form of notebook computers (3, 4). The server (2) is of a known type and generally includes at least one computer processor connected by a bus to a system memory and *data store* storing a database of *user records*. *User accounts* are formed from one or more database records relating to the same *user*. The server (2) is connected to the *user terminals* (3, 4) via wireless or wired communications systems and all are part of the wider World Wide Web or internet. The server (2) is operable to process computer program modules for processing data held in the system memory and/or *data store*. The system memory includes RAM, ROM and necessary program modules, e.g. an operating system. The system *data store*, such as a hard drive or virtual *data*

store, may also store program modules in addition to the database. The *user terminals* (3, 4) connect to the server (2) via a wired or wireless network of their Internet Service Provider (ISP). The *user terminals* (3, 4) may also have webcams (17). *Users* (5, 6) at the terminals (3, 4) can communicate with each other via the server (2).

A *virtual network* is provided in the form of a virtual social network (7), e.g. Facebook™, Match.com™, LinkedIn™ etc. The virtual social network (7) is formed from the interrelated collection of data records of *users*/members of the social network, i.e. all *users* are part of the larger social network. Each given *user* may have their own individual social network formed by storing a table of *user* identifiers against the given *user's* account, the *user* identifiers corresponding to other *users*/data records which the given *user* is connected to, e.g. the given *user's* "contacts". Social networks generally permit mutual communication via text, audio, static images and/or video that is stored and/or routed by the server (2).

Reference herein to the *entity* or other *user* "logging in" to the network (1) should also be interpreted to include Single Sign-On (SSO) systems such as OpenID® or similar systems where a *user* can 'log-on' to different networks using a single set of *user* credentials.

As described in the background art section, *users* (5, 6) accessing the *data network* (1) are typically only required to provide a combination of *user-name* and password for authentication. Once authenticated, the *user* (5 or 6) is free to communicate with their contacts and/or other *users*. There is typically no requirement for *users* (5, 6) to include independently verifiable statements about themselves. When a *user* (5 or 6) is 'signing-up', the social network (1) commonly only requires an email as a unique *user* identifier (ID) and does not verify that the other *identifying characteristics* or details the *user* (5 or 6) is entering are true. This limited authentication method allows *users* to create accounts with false details or access other *user's* accounts by finding out that other *user's* ID and password. There is thus no means for other *users* to verify the *identity* of a particular *user*, except for asking questions which both *users* know the answer to. However, even this method is not robust as a dishonest person may have already obtained the answers to those questions. Thus, paedophiles, imposters and other malicious *users* have taken advantage of such cursory security measures and have used social networks to deceive and harm other *users*.

Some social networks allow *users* to communicate by live bidirectional video transmission, e.g. 'video conferencing', to verify each other, though, as discussed above, this form of communication is undesirable for many *users* and must be performed 'live' with both *users* being present for effective assessment.

Figures 7-9 show example componentry for a *control system* provided in the form of server (11) and *user terminals* (13, 14) that may be used to implement preferred embodiments of the present invention.

The physical hardware involved for accessing and running the social network (8) on the *data network* (10) is generally comparable to the prior art system shown in **figure 1**, e.g. a *control system* is provided in the form of a server (11) and is connected to *user terminals* (13, 14) via a wired or wireless communication medium (not shown) thus providing for communication between an *entity* (15) and another *user* (16). The server (11) may store and/or route communications or set up a direct connection, such as a Virtual Private Network (VPN) or other internet tunnelling connection between the terminals (13, 14). Webcams (17) or other video/audio recording devices are provided at each *user terminal* (13, 14).

Figure 2 shows a more detailed logic diagram of the server (11) and a single *user terminal* (13 or 14).

The server (11) generally includes a computer processor (60), *data store* (61), network interface (62) (wireless or wired) and system memory (64) connected via a system bus (63). The system memory (64) includes Random Access Memory (RAM) (65) and Read Only Memory (ROM) (66) along with assets (67) including program modules (67a-m) and other assets (not shown) such as images, text, URLs, scripts and so forth. The program modules (67a-m) may of course be stored in *data store* (61) and loaded to RAM (65) during operation as needed. The *data store* (61) also contains a database of *user accounts* formed from related data records that correspond to a *user* (e.g. *entity* - 15 or *user* - 16). The *user accounts* preferably store *identifying characteristics* of the corresponding *registered user*, e.g. each *registered user's* account may contain records specifying the gender, age, occupation, country of residence, nationality, profile image etc. of the *registered user*.

An external *data store* (61a) is located remotely to the server (11) and can be used to store video recordings (21) with filenames acting as unique identifiers for each recording (21). The *data stores* (61a) and (61) can be used interchangeably for storing various data and thus, any reference to one *data store* (61) or (61a) will be appreciated as being substitutable with the other *data store* (61a) or (61) respectively.

An optional data access module may be included in the program modules (67a-m) for determining access parameters to the *data store* (61a). The external *data store* (61a) may take the form of another network server, Network Attached Storage (NAS), cloud storage or any other type of *data store*.

While reference herein is made to the use of a single server (11) it should be appreciated that multiple servers may be provided and the program modules (67) may be distributed amongst the multiple servers. Furthermore, the *data network* (10) may operate independently to the server (11) with a different *control system*/server and only access selected data from the server (11), *data store* (61a) or *user terminal* (13, 14) when required.

The *user terminals* (13, 14) also include a computer processor (70), *data store* (71), network interface (72) and system memory (74) connected via a system bus (73). The system memory (74) includes RAM (75) and ROM (76) along with executable program modules (77). The *user terminal* (13) also includes an operating system (78) program module and network browser module (79). The *user terminal* (13) additionally includes an optional Graphics Processing Unit (GPU) (81) which may also be integrated into the CPU (60). A video capture device (80) and *user input devices* (83) (e.g. mouse and keyboard, or touch-screen, etc) are also connected to system bus (73). The GPU (81) is connected to a display (82) via a video interface such as DVI, HDMI, DisplayPort or similar.

It should be appreciated that while other *user terminals* may be used that have predominantly the same components as *user terminal* (13, 14) other alternative example *user terminals* may have an integrated GPU (81) and processor (70), touch-screen or keypad input device or even no *data store*, instead having accessible network or cloud-based storage. Examples of *user terminals* (13, 14) include computers, servers, portable computers and tablets, mobile phones, game consoles, Automated Teller Machines, gambling machines, security screening terminals and indeed any device capable of computing data, recording video, generating *prompts* and transceiving data with server (11).

It should be appreciated that not all program modules (67a-j) may be required in each embodiment as described below, e.g. in the 'peer assessment' methods shown in **figures 4 and 5**, the facial recognition (67c) and gesture recognition (67d) modules may not be required. It will also be appreciated that the video recording (67g) and *prompt* generation (67a) modules may be located in the *user terminal* (13, 14) and run locally rather than on the server (11).

The methods of preferred embodiments of the present invention may be implemented using any applicable software platforms such as, but not limited to, Java®, Flash®, HTML5 or any other suitable software platform. In the present example described herein, the method is implemented using an Adobe Flash® application and example screenshots are shown in **Figure 10**. It will be appreciated that other software platforms and protocols may be used and the aforementioned platforms are merely provided as examples.

One preferred embodiment of a method (100) of *entity* assessment is shown in **figures 3 and 4**. The method is for assessing an *entity* (15) at a first *user terminal* (13) connected to a *data network* (10).

In broad terms the method utilises a *control system* provided in the form of server (11) operable to perform the steps of:

- a) receiving an *access request* from at least one of:
 - o (101) - the *entity* (15);
 - o (114) - an *assessing user* (16) at a second said *user terminal* (14).
- b) invoking (109) at least one *unpredictable prompt* (18) to said *entity* (15) to perform a *visible prompted action* (20);
- c) invoking storage (111) of at least one *video recording* (21) of said prompted action performance from said *entity* (15) in a *data store* (61a);
- d) invoking or facilitating transmission (119) of said *video recording* (21) from said *data store* (61a) and details of said *prompt* (18) to said *assessing user terminal* (14) for viewing and *assessment* by said *assessing user* (16);
- e) receiving (121) from said *assessing user* (16) an *assessment signal*.

Now with reference to **figures 3 and 4** the method of *entity* assessment is described in more detail. This method enables assessment of at least one *entity* (15) at a first *user terminal* (13) accessing a *data network* (10). The method utilises a *control system* provided in the form of server (11) operable to perform the steps of:

- (step 101) Receiving an *access request* from a first *user terminal* (13) from an *entity* (15) purporting to be a *registered user* of the social network (8) *entity* (15) and requesting access to the social network (8). The *access request* includes an initial "login" request (102).
- (step 102) The *entity* (15) will attempt to provide credentials to access a *user account* (hereinafter *accessed user account*) that corresponds to a *registered user*. The credentials provided are typically login credentials, e.g. a *user ID* and password. The data containing the credentials is sent to the server (11) from the first *user terminal* (13).
- (step 103) The server (11) receives the submitted credentials, and attempts to correlate with a *user account* stored in the database.

- (step 104) If the *user* ID and password combination does not match a *registered user's* account, the *access request* (101) is denied and the *entity* (15) notified. The *entity* (15) can then retry the *access request*, i.e. start again at step (101) or abandon the access. There may also be the option for the *entity* (15) to request a 'lost' password or reset password link to be sent to the *registered user's* e-mail address registered in database.
- (step 105) If the credentials do match a *registered user's* account, the initial login is read as a success and a login timestamp generated and stored in the database against the *accessed user account*.
- (step 106) The server (11) then determines whether the *entity* (15) requires assessment.
- (step 107) If the *entity* (15) requires assessment a request is sent to the first *user terminal* (13) to access a webcam (17) or other visual communication device. This request may be in the form of a Java remote method invocation, an HTTP GET/POST request (a URL request), an application specific request or similar.
- Alternatively, the *entity* (15) may be required to install software which is able to access the webcam (17) on behalf of the server (11). The webcam (17) is preferably controlled by the software (67) or web server (11) to prevent an imposter from making pre-recordings of one or more of the prompted actions (20) (described below) and then providing the pre-recordings to the server (11) in place of a 'live' webcam recording.
- (step 108) The webcam request is then processed by the first *user terminal* (13) and a reply sent to the server (11) indicating whether the first *user terminal* (13) has a webcam (17) or other recording device. The *entity* (13) may be required to press a physical or software 'button' to consent for the server (11) or local software to access the webcam (17).
- It will of course be appreciated that reference to a 'button' also includes software buttons such as a hyperlink, HTML form post, ActiveX control or other software control.
- If a webcam (17) is not available, the *access request* fails (104) and the *entity* (15) is denied access to the social network (8). Alternatively, the *entity* (15) may be provided with access to the social network (8) but will have a record on the corresponding *registered user's* account that the *entity* was not assessed and a notification (19) generated (112) for other *users* attempting to communicate with the *entity* (15).
- If a webcam (17) is available but the *entity* (15) denies access to the webcam (17) then the server (11) may treat the denial as a 'negative' *assessment signal*, classify the *entity* (15) negatively and/or may restrict access or take other action as required, as an *entity* (15) denying access to an available webcam may indicate an imposter.
- (step 109) If a webcam (17) is available, the server (11) implements the *prompt* generation module (67a) to pseudo-randomly select three actions from a populated list (22) of actions (20) stored in a table in *data store* (61). *Prompts* (18) for the selected actions (20), the sequence and the time delays between consecutive *prompts* (18), along with a timestamp and unique identifier, are stored in the database (50) against the corresponding *user account*. A script or executable is sent to the *user terminal* (13) which contains details of the *prompt* sequence to display and other parameters such as the unique identifier and any special instructions.
- The script is received at the first *user terminal* (13) and invokes the *prompt* display (67k) and video recording (67g) modules to operate using the information in the script.
- The time-delimited sequence of three *prompts* (18) is displayed on the first *user terminal* (13) to sequentially ask the *entity* (15) to perform the *visible prompted actions* (20), e.g. as shown in **figures 7-9** the predetermined actions (20) may be a sequence of facial expressions such as "smile", "unhappy" and "tongue out". The *prompts* (18) are displayed in sequence with the assigned time delay between each *prompt* (18).
- The predetermined actions (20) may be selected pseudo-randomly or alternatively, determined by an algorithm that selects actions based on particular criteria. In a given country for example, the list (22) of possible actions (20) for *users* may be limited by removing potentially offensive gestures. Similarly, the list (22) of actions (20) may be restricted or determined by the religion, ethnicity, sex, age, or any other *user identifying characteristic* stored in the corresponding *registered user's* account. As the actions (20) selected are *unpredictable*, an imposter would be unable to regularly anticipate the next *prompt* in order to create a falsified video recording to replace a live webcam (17) video. It should also be appreciated that the actions (20) may

include not only facial expressions but alternatively, or in addition – body gestures, sound or any other action visibly discernable and identifiable by an *assessing user*.

(step 110) the video recording (67g) module is run concurrently with displaying the *prompts* (18) enabling the webcam (17) to record a live, real-time performance of the *entity* (15). An example of the video capture screen (53) and *prompts* (18) is shown in **figure 10a**. The *entity* (15) is also able to review a playback of their video recording and can repeat the recording process if unsatisfied with the recording.

(step 111) Simultaneously (with steps (109) and (110)) the script from the server (11) implements the data storage (67l) module to stream the video data to *data store* (61a) which is stored with a unique identifier as the video filename. As another optional facet of *identity* information, the location and/or local time of first *user terminal* (13) may be determined and stored in the database (50) along with the corresponding *prompts* (18) or alternatively with the video recording (21) in *data store* (61a).

Alternative embodiments may have a video recording (21) formed as a composite of multiple individual recordings. The recordings (21) may be sent to the *data store* (61a) individually, or the recordings (21) may be continuous or joined together before being sent to the server (11). The recordings may be streamed to the server (11) or store (61a) or sent as an upload package.

The server (11) generates at least three *prompts* (18) to minimise the risk of the *entity* (15) providing pre-recordings or false recordings of a single or two predetermined actions (20). It will also be appreciated that any number of *prompts* (18) could be provided. Increasing the number of *prompts* (18) or possible actions (20) correspondingly minimises the ability for an impostor to provide pre-recordings of the corresponding *registered user* or another person performing those actions (20) in the correct sequence. The total number of unique sequences of *prompts* (18) and actions (20) possible are determined by the number of *prompts* (18) and number of different actions (20), according to the equation:

$P = n! / (n-k)!$ where $n \geq k$, P = number of unique sequences, n = number of different possible actions (20), k = number of *prompts* (18)

Thus, by way of example, three different predetermined actions (20) comprised of “smile”, “unhappy” and “tongue out” in a sequence of three *prompts* (18) could be provided in six unique sequences. Adding a choice of a further two different actions (20), e.g. “frown” and “wink”, would increase the number to sixty unique *prompt* sequences.

(step 112) In some circumstances the *entity* (15) may choose to defer or bypass the video login process (109-111) and proceed directly to access (113) the *data network* (10). The *entity* (15) may choose not to conduct the video login process (109-111) if, for example they do not have a webcam (17) or other recording device. However, it will be appreciated that bypassing of the video login process (109-111) also bypasses the benefits to other *users* of being able to visually assess the *entity* (15) logged on as a corresponding *registered user*.

Thus, the server (11) is configured to record (112) in the *registered user's* account that the *entity* (15) has not recorded a video login and has not been assessed but otherwise will treat the *entity* (15) as the corresponding *registered user*. When other *users*, e.g. *assessing user* (16), attempt to communicate with the *entity* (15) the server (11) sends the *assessing user* (16) a notification (19) that the *entity* (15) has no recorded video login and has not been assessed.

This notification (19) may, by way of example, be a message, warning, pop-up control, button or other visible/audible notification. The notification (19) may remain in effect until the *entity* (15) conducts the video login process (109-111). The video login process (109-111) may also be bypassed if the *registered user's* account indicates the *registered user* has special dispensation, or is otherwise not required to verify themselves, e.g. if the *registered user* is identified as a security administrator or the like.

(step 113) Once the *entity* (15) has finished the video login process (109-111) and the server (11) has stored the recording (21) the *access request* and video login process is complete and the *entity* (15) is provided access to the communication network (10). Alternatively, the *entity* (15) may view the recording (21) and repeat steps (109)-(111) if they are not satisfied with the recording.

Preferentially, this access process (100) is also completed by the *assessing user* (16) and each other *user* accessing the communication network (10) such that all, or at least most *users* have video recordings (21) for assessment.

Figure 4 shows an example of a second stage (100b) in a preferred embodiment of the present invention following the video login process (100a) of **figure 3**. This second stage (100b) includes the assessment process of the *entity* (15) by an *assessing user* (16). Hereinafter this embodiment shall be referred to as a 'peer assessment' embodiment reflecting the process of using an *assessing user* (16) i.e. a 'peer' to assess the *entity* (15).

- (step 114) The *entity* (15) and *assessing user* (16) have logged in (105) to the network (10) whereupon the *assessing user* (16) makes an *access request* for communication with the *entity* (15) or the *entity* (15) requests communication with the *assessing user* (16). The *access request* may take the form of an instant message, email, blog, forum posting, picture tagging, voice chat or any other communication. The *access request* (114) to the server (11) also contains *user data* identifying the *entity* (15) and *assessing user* (16).
- (step 115) Upon receiving the *access request*, the server (11) queries the database and *accessed user account* to determine if a timestamp (generated at (109)) exists for the last video login recording (21), and if so determines whether the timestamp is within a preset range, i.e. the *accessed user account* has a recent video login recording (21).
- (step 116) If a timestamp does not exist or the timestamp is outside the preset range, i.e. there is "No" recent video, the server (11) is configured to generate a warning notification (19) (e.g. as shown in **figure 8**) or retrieve a previously generated warning notification (generated as per step (112)), notifying other *users* that the *accessed user account* does not have a login video (21).
- The server (11) may also be configured to require a new video login (21) from *entity* (15) before the *entity* (15) can communicate with others as the *entity* (15). The requirement for an updated video may thereby reduce the opportunity of an imposter illegitimately accessing a *registered user's* account after the genuine *registered user* has already completed the video assessment process (100a) and then pretending to be the genuine *registered user*.
- The *assessing user* (16) may also choose to avoid/cancel communication with the *entity* (15) if the *accessed user account* does not have a recent login video (21).
- (step 117) If a recent video login (21) is available the server (11) provides an HTML file or similar to the *assessing user* (16) with the unique identifier for the recent video (21). The video retrieval module (67m) pre-fetches from *data store* (61a) the recent video recording (21) (or part thereof) that matches the unique identifier. A still image of part of the video (21) is displayed to the *assessing user* (16) who may then activate a 'VIEW' button or other control which is interpreted by *data store* (61a) as a "view request" of that video (21). It should be appreciated that the "view request" may be controlled by the *user terminal* (14), *data store* (61) or server (11) depending on where the video recording (21) is stored and how the system is configured.
- (step 118) If the *assessing user* (16) makes a 'view request' this invokes the transmission of the video (21) to the second *user terminal* (14) from *data store* (61a). The unique identifier is also used to retrieve the corresponding *prompts* (18) from server (11) for simultaneous synchronised display overlapping the video (21). Examples of the display of the video (21) and *prompts* (18) are shown in **figure 7** and **figure 9**. It will be appreciated however that the *prompts* (18) will not be displayed together and instead are displayed singularly in sequence with time delays between consecutive *prompts*. It should also be appreciated that the video (21) need not be pre-fetched and may instead be streamed or downloaded when the *view request* control is activated.
- The *assessing user* (16) is thus able to assess whether or not the recording (21) shows the *entity* (15) performing the predetermined actions in the correct sequence as is shown in **Figure 7**, or in an incorrect sequence such as shown in **figure 9**.
- (step 119) The *assessing user* (16) can alternatively choose not to make a *view request*. The server (11) may then allow (123) or block (125) communication over the social network (8) between the *assessing user* (16) and *entity* (15) depending on the security policies of the social network (8).
- (step 120) After viewing the recording (21) the *assessing user* (16) is asked to assess the *entity* (15) in the recording (21). Additionally, the *assessing user* (16) is preferably provided access to *identifying characteristics* of the *accessed user account*, e.g. the name and a profile picture of the *registered user*. If the *assessing user* (16) chooses not to assess the *entity* (15) the server

- (11) determines (119) whether or not to allow (121) or block (132) communication over the social network (8) between the *assessing user* (16) and *entity* (15)
- (step 121) If the *entity* (15) is assessed, the *assessing user* (16) provides an *assessment signal* which includes a positive, negative or inconclusive indication of whether or not they consider the video recording (21) and recorded *entity* (15) to be 'trustworthy' or potentially an 'imposter'. The *assessment signal* may be generated by selection of a button or other *user control*. The *assessment signal* is preferably composed of a number of individual *assessment signals* corresponding to the different possible assessments to be made. Examples of the assessment types preferably include the following:
- Actions assessment* – i.e. whether or not the *entity's* (15) actions (20) are a valid response to the *prompts* (18), e.g. did the *entity* (15) perform the correct actions (20) in the correct sequence given the *prompts* (18) made?
 - Visual assessment* – i.e. whether or not the *entity* (15) has been assessed as having the same or similar characteristics as the *identifying characteristics* of the *accessed user account*, e.g. does the *entity* (15) appear to match the profile image stored in the *accessed user account*?
 - Persona assessment* – i.e. whether or not the *entity* (15) is recognised as corresponding to the *persona* of the *accessed user account*, e.g. is the *entity* (15) the person who you expected?
- The *accessed user account* may portray a particular *persona* through various *identifying characteristics* such as name and location indicating a particular person. However, in some circumstances the *accessed user account* may be created by an *entity* (15) attempting to portray themselves as someone else, e.g. a famous actor/actress or politician. The *entity* (15) (who may be a valid *registered user*) may have common *identifying characteristics* (e.g. age, appearance, gender) to the *persona* portrayed and so the assessment at b) should have a positive result. However, the *assessing user* (16) may make the additional assessment that while some of the characteristics match, the *entity* (15) is not who was expected based on the *persona* portrayed. This *persona assessment* may also apply where the *persona* matches a relative or *personal acquaintance* of the *assessing user*.
- General assessment* – e.g. is the video recording (21) suspicious?
- The *assessing user* (16) may select from a range of assessments that provide differing information about the video recording (21) and *entity* (15). For example, the *assessment signal* provided may be processed by the server (11) as a "classification" for the *entity* based on the results of the above various assessments made by the *assessing user*.

The following Table 4 shows one example of the assessments made and potential resulting *classifications*:

Action Assessment	Visual Assessment	Persona Assessment	General Assessment	Classification
Positive	Positive	Positive	Positive	Positive
Positive	Positive	Positive	Negative	Negative
Positive	Positive	Negative	Positive	Inconclusive
Positive	Positive	Negative	Negative	Negative
Positive	Negative	Positive	Positive	Negative
Positive	Negative	Positive	Negative	Negative
Positive	Negative	Negative	Positive	Negative
Positive	Negative	Negative	Negative	Negative
Negative	Positive	Positive	Positive	Inconclusive
Negative	Positive	Positive	Negative	Negative
Negative	Positive	Negative	Positive	Inconclusive
Negative	Positive	Negative	Negative	Negative
Negative	Negative	Positive	Positive	Negative
Negative	Negative	Positive	Negative	Negative
Negative	Negative	Negative	Positive	Negative
Negative	Negative	Negative	Negative	Negative

The *classifications* can of course be altered to suit particular applications and security policies.

- (step 122) If the server (11) makes a positive *classification*, the server (11) may be configured to then record to the *accessed user account* that the *entity* (15) has been assessed positively. The server (11) may remove any existing warning notifications (19) and/or add a "positively assessed" notification (not shown) such that other *users* are able to see the *entity* (15) has been

positively assessed. The server (11) also records to the database in the accessed *user's* account the total number of positive *classifications* made.

- (step 123) Once a positive *classification* is made, the server (11) can allow the *entity* (15) to communicate with the *assessing user* (16) over the social network (8).
- (step 124) If the server (11) makes a negative *classification*, the server (11) then records to the *accessed user account* that a negative assessment has occurred, e.g. an imposter may have tried to communicate on the network (8). The server (11) may then generate a warning notification (19) for other *users* attempting to communicate with the *entity* (15). The server (11) also records the number of negative *classifications* made to the *accessed user account* in the database (50). An alert may also be provided to an administrator to investigate.
- The server (11) also queries the database (50) to determine the total number of negative *classifications* made and if the number (or ratio of negative to positive *classifications*) is over a preset threshold.
- (step 125) If the server (11) determines at (124) that the threshold is not exceeded, the server (11) may automatically prevent ('block') communication between the *entity* (15) and *assessing user* (16) for the duration of the first *user's* login period or other predetermined time period. The *entity* (15) is blocked from interacting with the *assessing user* (16), but as sufficient other *users* have not marked the *entity* (15) as suspicious (i.e. negative *classification* threshold not exceeded), the *entity* (15) remains logged in as the *registered user* and has the opportunity to interact with other *users* as per (130). Alternatively, the *entity* (15) may be asked to repeat the assessment process from step (109), i.e. they are given the opportunity to create a new login video (21).
- (step 126) If the server (11) determines at (124) that the threshold is exceeded the server (11) may automatically block communications between the *entity* (15) and any other *users* for the duration of the first *user's* login period or other predetermined time period. The server (11) also records to the *accessed user account* that communication has been 'blocked'.
- (step 127) The server (11) then queries the database and determines if the *entity* (15) has been previously blocked.
- (step 128) If the server (11) determines that the *entity* (15) has not been blocked previously, the server (11) may be configured to automatically log out the *entity* (15) and require the *entity* (15) perform the video login process (steps 107-111) upon their next login, i.e. the *entity* (15) is returned to step (101).
- (step 129) If the server (11) determines that the *entity* (15) has been blocked at least once previously, the server (11) may be configured to automatically suspend the *accessed user account* and/or notify a system administrator or other authority to investigate.
- (step 130) After assessment is complete at step (123) or if communication has been blocked (125) for the first time, the server (11) may be configured to determine (130) whether the *entity* (15) wants to communicate with other *users*, in addition to, or instead of the *assessing user* (16).
- (step 131) If the *entity* (15) does want to communicate with other *users*, the server (11) queries the database (50) for the *accessed user account* to determine if the number of positive *classifications* or ratio of positive to negative *classifications* is over a preset threshold.
- (step 132) If the *accessed user account* indicates that the positive *classification* threshold is not exceeded, i.e. the answer at step (131) is "No", the assessment process (115 onwards) is repeated for each additional *user* (replacing the *assessing user* (16) in the process with the additional *user*) until a sufficient number of positive *classifications* is reached.
- Alternatively, step (131) may be performed for every additional *user* or for randomly selected additional *users*.
- (step 133) If the *accessed user account* has a sufficient number of positive *classifications*, the *entity* (15) may be allowed to freely communicate with other *users*. However, such other *users* may be notified that the *entity* (15) has sufficient validations and the other *users* may still be able to request the *entity* (15) re-verify themselves and any other *users* for the duration of the first *user's* login period.
- In configurations where the *entity* (15) does not require communication with any other *users*, no further action is required in the process.
- (step 134) As an alternative to step (131), if the *entity* (15) does want to communicate with other *users*, the server (11) may require the assessment process (115 onwards) to be completed by the other *users*, i.e. the *entity* (15) is substituted with an 'additional

user'. Thus, once the *entity* (15) has accessed the communication network and been assessed positively they may be free to communicate with other positively assessed *users* and/or require other *users* to be assessed by the *entity* (15). This step (133) may be performed for every additional *user*, for a predefined number or for selected additional *users*.

(step 135) In some circumstances the *assessment signal* received may indicate an inconclusive assessment. The inconclusive *classification* may result from a mix of positive or negative assessments as detailed in Table 4 or where the *assessing user* otherwise explicitly indicates they cannot make a conclusive assessment, e.g. if the video quality is poor, there are insufficient *identifying characteristics* to make the visual and *persona* assessments or any other reason. Where an inconclusive *classification* is made the server (11) may be programmed to trigger an 'investigation' of the inconclusive *classification*. Such investigation may include:

- a. notifying an administrator or the like;
- b. requesting further information from the *assessing user*, e.g. why was the assessment inconclusive;
- c. requesting the *entity* (15) to repeat the video login procedure (100a);
- d. requesting the *assessing user* (16) repeat the assessment (120);
- e. another appropriate response.

As a result of the investigation (135) the *entity* (15) may be blocked (125), or allowed (123) to communicate with the *assessing user* (16).

While the aforementioned method of *entity* assessment shows the *prompts* (18) and recording process ((107) to (111)) taking place when the *entity* (15) is 'logging in' to the social network (8), it should be appreciated that these steps ((107) to (111)) may alternatively, or in addition, be required at any *access request* which will result in communication or other interaction between the *entity* (15) and another *user* or may be required on demand of the *assessing user* (16) or another *user*.

A specific computer software implementation of the aforementioned method of *entity* assessment shown in **figures 3 and 4** is now generally described. It should be appreciated that the following implementation is purely exemplary and numerous software platforms and configurations may be used without departing from the scope of the present invention. The hardware required has already been shown and described with respect to **figure 2**. To aid succinctness, notation herein to a forward slash (/) prefix should be understood to refer to a Uniform Resource Locator (URL) from the host website, e.g. "/example" refers to www.example.com/example.

- At least three tables are provided as part of the database (50) in *data store* (61). These tables include:
 - TBL_ACTIONS. Each TBL_ACTIONS record includes:
 - a *prompt* description of an action (20);
 - the time period that *prompt* (18) needs to be displayed for;
 - a '*prompt*' key;
 - TBL_ACTIONGROUP. This table is populated with the /get-clip script. Each TBL_ACTIONGROUP record includes:
 - three *prompt* keys from the TBL_ACTIONS table;
 - corresponding time period that the *prompts* (18) are displayed;
 - the order in which the *prompts* (18) are provided;
 - a timestamp with the date/time when the TBL_ACTIONGROUP record was created;
 - a *user* ID of the *accessed user account* on the social network (8);
 - a corresponding 'ActionGroup' key;
 - TBL_ASSESS. This table is populated with the /assessment script. Once the recording (21) has been viewed by the *assessing user* (16), the *assessing user* (16) assesses the *entity* (15) and selects a series of buttons respectively indicating positive, negative or inconclusive assessments for the 'actions', 'visual', '*persona*' and 'recording' assessments, each button generates a corresponding positive, negative or inconclusive *assessment signal*. Each TBL_ASSESS record includes:
 - the ActionGroup key;
 - the *user* ID of the *assessing user* (16);
 - a positive, negative or inconclusive *assessment classification* as determined according to Table 4 using the received *assessment signals*. Any received 'inconclusive' signal received results in an 'inconclusive' *classification*.

- a timestamp with the date/time when the *assessing user* (16) viewed the recording (21) and provided the *assessment signals*.
- In addition, the social network (8) has a database with *user accounts* corresponding to *registered users* and having such fields as: *user ID*, *user IDs* of other *users* accessible by that *registered user*, *identifying characteristics* and various other details. Such databases are known and will not be described further. The social network database may be formed as part of the server database (50) or may be provided separately with the server (11) and/or *user terminals* (13, 14) having at least partial access to the records.
- Two Flash™ applications are provided including a “*video playback module*” (67m) and a “*video recording module*” (67g). These modules are stored as SWF files in the server (11) and are served to the *user terminals* (13, 14) when the *user terminal* (13, 14) requests them. The *user terminals* (13, 14) are able to request these modules as they are referenced in HyperText Markup Language (HTML) which is served to the *user terminals* (13, 14) in a previous HyperText Transfer Protocol (HTTP) GET procedure when the *entity* (15) or *assessing user* (16) makes an *access request* (101) or (114).
- Hypertext Pre-processor (PHP) and HTML Scripts are provided. The PHP script is executed when the client (first *user terminal* (13)) does GET or POST requests. The PHP script can output HTML or Text. The PHP script can also run database queries. The scripts include:
 - /get-clip. When an *access request* (101) or (114) is made via a network browser (79) on the first *user terminal* (13) to the server (11) the /get-clip script causes the PHP engine on server (11) to query the database (50) and create a new record in TBL_ACTIONGROUP with the records described above. The ActionGroup key also forms the filename that the subsequent video recording (21) will be saved as when made. The video recording filename (ActionGroup key) is specified as a parameter to pass to the *video recording module* (67g) when it is executed. The *video recording module* (67g) then severs (if not already cached) and then loads the recording parameters.
 - /actionxml. Uses the ActionGroup key and queries TBL_ACTIONS to retrieve the corresponding sequence of *prompts* (18) which is then passed to the first *user terminal* (13) as an XML file. Using the ActionGroup key in the Flash™ applications rather than the *prompt keys* or *prompt* information ensures interception of the XML can't be used to identify the *prompts* (18) and therefore provide an *entity* (15) with a means for pre-recording a video with the correct *prompt* sequence before receiving the *prompts* (18).
 - /view-clips. When an *assessing user* (16) makes a communication request (114) from second *user terminal* (16) the /view-clips script is requested by browser (79). The /view-clips script extracts from the social network database the *assessing user's* ID, other accessible *user's* IDs and names, including the *entity* (15). An 'ActionGroup' query is run on the server database (50) for each *user ID* returned from the social network database query. The ActionGroup query returns any records from TBL_ACTIONSGROUP where the corresponding *user* has a related record and, if so, the most recent ActionGroup key (as determined from the corresponding timestamp) is returned as a parameter. The ActionGroup key is also the filename of the last video recording (21) and thus the /view-clips script ensures only *users* with a video recording (21) are returned by /view-clips and only with their most recent recordings. The ActionGroup key, *user ID* and *assessing user ID* is then passed as a parameter to the *video playback module* (67h) when it is executed.

The view recordings page (shown in **figure 10b**) is sent to *user terminal* (14) and the *video playback module* (67h) reads in the parameters and requests from the *data store* (61a) the corresponding video recording file (Flash Video (FLV)) over HTTP and the first frame of the video recording (21) is fetched and displayed on the browser (79) next to the corresponding *user's* name.

An *assessment rating* (51) is also calculated and retrieved by running a query of TBL_ASSESS using the ActionGroup key and calculating: $\text{Total positive classifications} / (\text{Total classifications}) * 100$

this thereby gives a percentage *assessment rating* (51). This *assessment rating* (51) is displayed as text next to the first frame of video recording (21) on browser (79).

- /assessment. This is a URL that the *video playback module* (67h) calls to record the *assessment signals* assigned to the *entity* (15) by the *assessing user* (16). The parameters passed with this script include the ActionGroup key, of *assessing user ID* and positive, negative assessment or inconclusive signals. The /assessment script checks for a valid ActionGroup key, and writes the appropriate record to TBL_ASSESS with the determined *assessment classification* and *assessing user ID*. The ActionGroup key will not be 'valid' if no matching key exists in TBL_ACTIONGROUP or the record in TBL_ACTIONGROUP has a timestamp outside a preset range, e.g. the record is too old.

The *video recording module* (67g) Flash™ application performs the following procedures:

- reads in a parameter from /get-clip. which is the ActionGroup key stored in TBL_ACTIONGROUP.
- issues a requests to /actionxml using the recording filename which returns the corresponding three *prompt* keys.
- starts the camera (17).
- starts streaming the video recording (21) over a Real Time Messaging Protocol (RTMP) to the *data store* (61a), which converts the stream to a Flash Video (FLV) file with the recording filename being the ActionGroup key.
- displays text "Please get ready".
- displays the *prompts* (18) in pseudo-random sequence with a time delay between each *prompt* (18) and a notification of time available to perform each *prompt* (18).
- a 'cue' timestamp is inserted into the video recording (21) stream when each *prompt* (18) is displayed, thereby indicating the time the *prompt* display started.
- stops streaming.
- shuts down.
- redirects first *user terminal* internet browser to a new page /view_clips where the *entity* is able to view their video recording (21).

The *video playback module* (67h) Flash™ application:

- reads in the parameters from /view-clip which include the most recent ActionGroup key for each corresponding *user*.
- issues a request to /actionxml using the ActionGroup key which returns the three *prompts* (18).
- requests the movie FLV over HTTP from *data store* (61a).
- waits until the *assessing user* (16) makes a *view request* (117) by selecting a "play" button on browser (79).
- plays the FLV video on the *user terminal* (14) browser (79). The corresponding *prompts* (18) are displayed when a cue timestamp is detected.
- asks the *assessing user* (16) to select buttons indicating positive, negative or inconclusive assessments for the 'actions', 'visual', 'persona' and 'recording' assessments .
- when the *assessing user* (16) selects a button then a HTTP request is made to /trust-response with the ActionGroup key, the *user* ID of the *assessing user* (16) and the *assessment signal*. The /assessment PHP script stores a record in TBL_ASSESS accordingly.

It will also be appreciated that the aforementioned method may be altered to suit the social network, security policies or similar. It should also be appreciated that the software may be constructed and run using different programming platforms, e.g. JavaScript™, HTML5, Microsoft™ Silverlight™ etc.

It will be appreciated that the aforementioned embodiments are particularly suited for use in general social networks, children's social networks, gaming networks and/or relationship facilitation services such as 'dating' websites.

The aforementioned assessment method (100a-b) may also require the *entity* (15) and/or *assessing user* (16) to perform an initial video login process (109-111) when registering an account in the database. The recording(s) (21) may then be stored on the server (11) and used as a reference recording. Thus, in the event of a dispute between *users* and/or where suspicious activity arises, another *user*, a network administrator, and/or an investigator can view the initial recording and compare with subsequent recordings to determine whether the person shown is the same in both.

There have been numerous instances of internet sites or social network profiles/accounts being set up by entities *impersonating* celebrities, public figures, companies or other public or private entities. These entities may then deceive other *users* as to their *identity* and/or tarnish the reputation of the person/*entity* they are *impersonating*. In such instances it is difficult to verify the authenticity of the *user* without directly contacting the supposed *entity* by alternative means, e.g. phone.

The present invention however may alleviate this problem by providing an assessment recording (21) (as previously described) showing *unpredictable prompts* (18) and an *entity* (15) performing (or not) the prompted visible actions (20). If the *entity* (15) shown in the recording (21) is assessed negatively(15), then other *users* will be aware the *accessed user account* may have been accessed by an imposter and can notify the network administrator, other authority or simply treat the *entity* as they want.

Figure 5 shows an alternative peer assessment method 100c that uses the initial method 100a and is generally similar to method 100b but differs in that no assessment (120 onwards) is required. Accordingly the same reference numerals are used for common steps in methods 100b and 100c.

In relationship facilitation services (e.g. dating and friend making websites) the primary goal of *users* is often to meet new people and assess those people for potential relationships. However, the aforementioned assessment methods (100b) require the *assessing user* (16) to make multiple assessments, e.g. *actions*, *visual*, *persona* and *general*, some of which may be overly onerous or impossible when assessing an *entity* (15) they have never met before. Therefore, the method (100c) is an embodiment which still provides many of the advantages of the aforementioned method (100b) but which does not require the *assessing user* (16) to provide an *assessment signal*, i.e. the *assessing user* (16) is free to choose whatever action to take based on their own assessments.

Thus, instead of an active assessment (121), the *assessing user* (16) on viewing the video recording (21) can make a choice (150) on whether or not to communicate with the *entity* (15) shown in the recording (21). If the *assessing user* (16) does not want to communicate, the server (11) is programmed to allow communication or not as described with respect to 100b. The method (100c) provides the *assessing user* (16) with the same information to assess the *entity* (15) as in the 100b method but without requiring active feedback from the *assessing user* (16) via the *assessment signal*. The burden on the server (11) is thus reduced relative to the method 100b. In one further embodiment, shown as optional step (151) in **figure 5**, the *assessing user* (16) may also select a *user interface button control* at the *assessing user terminal* (14) to generate a positive or negative *assessment signal* respectively indicating whether or not they positively assess the *entity* (15) or want to communicate with the *entity* (15). No further action is taken if the *assessment signal* is positive and the *entity* (15) and *assessing user* (16) are free to communicate. However, if the *assessment signal* is negative then the server (11) may prevent or restrict communication from the *entity* (15) to the *assessing user* (16) for the rest of the *entity's* login session, permanently, temporarily or until the *assessing user* (16) provides a positive *assessment signal*.

In the embodiments shown in **figures 2-5** the *control system server* (11) can be an integral part of the social network (8) to not only conduct the preferred procedures of the present invention but also the general procedures of a typical social network, e.g. storing *user data*, routing communications etc.

However, in another preferred embodiment of the present invention as shown in **figure 6**, the social network (8) may operate independently to the server (11). The server (11) instead acts as a proxy between the *user terminals* (13, 14) and social network (8). Acting as a proxy allows the server (11) to control access to the social network (8) and information passed between the *user terminals* (13, 14) and social network (8) without being required to operate the social network (8) itself.

The server (11) functioning as a proxy server will operate as described above with respect to **figures 2-5**, though it will be appreciated additional program modules may be needed to control transmission to and from the social network (8), intercept data and HTML and extract *user information* (e.g. a *user's* contact list) from the social network (8).

In operation, the embodiment of **figure 6** operates using substantially the same method as shown in **figures 3-5**, i.e. on receiving an *access request* from an *entity* (15) or *assessing user* (16) at *user terminals* (13, 14) the server (11) may present the *entity* (15) with the login screen to social network (8). If the correct credentials are entered the server (11) retrieves at least one *identifying characteristic* and optionally other details from the *accessed user account* on the social network (8) and passes to the *user terminal* (13). The *identifying characteristics* include name, gender, age, profile image, location, nationality, occupation. Other details may include profile information, contact list, *personal interests*, memberships and the like. The *entity* (15) making access is then able to access the social network information as per a direct access, except for where the *entity* (15) wants to communicate or share information with another *user* of social network (8) (or vice versa) and the *entity* (15) does not have a corresponding video recording (21) as determined by server (11).

When the server (11) determines an *access request* is made by an *entity* (15) without a corresponding video recording (21) the server (11) may restrict access or communication on the social network (8) by intercepting the HTML from the social network (8) and modifying it to warn any other *user*, e.g. *assessing user* (16), that the *entity* (15) does not have a video recording (21). The *entity* (15) is then prompted to go through the process (106) – (112) as shown in **figure 3** and then be assessed by the *assessing user* (16) as per the process of **figure 4**.

The server (11) may also apply the same access and communication restrictions as described with respect to the earlier embodiments if assessments with respect to an *entity* accessing a particular *accessed user account* are negative, e.g. marking *user* as suspicious, restricting communication, generating warning notifications and the like.

Also with respect to **figure 6**, another alternative embodiment is described where the *entity* assessment methods (100b, 100c) may be implemented via a software application such as a network browser extension or plugin, i.e. the server (11) does not act as a proxy but is linked to network browser (79) on the *user terminals* (13, 14). When the network browser (79) communicates an *access request* to social network (8) from an *entity* (15) or *assessing user* (16) at *user terminals* (13, 14 respectively) the network browser (79) may present the *entity* (15) with a login screen to server (11) which also provides access to the social network (8) if credentials matching a *registered user's* account are entered. If the correct credentials are entered the server (11) passes correct login details to the social network (8) via browser (79) and retrieves the social network HTML as per a direct access to the *accessed user account*. The *entity* (15) is then able to access the social network information as per a direct access except instances where the *entity* (15) wants to communicate or share information with another *user* of social network (8) (or vice versa) and the *entity* (15) does not have a corresponding video recording (21) as determined by the server (11). When such an *access request* is made by an *entity* (15) without a corresponding video recording, the browser (79) may restrict access or communication on the social network (8) by intercepting and storing data sent from that *entity* (15) until that *entity* (15) has performed the method steps (106) – (112) as shown in **figure 3** and been assessed as per the method (100b) of **figure 4**.

The browser (79) may also apply the same access and communication restrictions as described with respect to the earlier embodiments if assessments with respect to a particular *user* are negative, e.g. marking *user* as suspicious, restricting communication, generating warning notifications and the like. By way of example, parents may install such an application or browser extension on their child's computer to prevent direct access to specific social networks (8).

The embodiments illustrated with reference to **figure 6** thereby allow interaction on the social network (8) without requiring the server (11) be integrated with the social network (8) while helping to ensure that imposters are identified and *assessing users* are confident of the *identity*, or at least appearance of the *entity* they are communicating with.

The embodiments of **figure 6** are particularly useful where the social network (8) does not implement the *entity* assessment methods (100) of the present invention but the *users* (15, 16) still want to receive the benefits of using such an *entity* assessment method (100).

Figures 7-9 show the *data network* (10) with an internet social network (8) or *relationship facilitation service* (e.g. "dating website") with which the method of *entity* assessment according to one aspect of the present invention (shown in flow-chart form in **figures 3-5**) can be implemented.

Figure 7 shows an *entity* (15) being prompted with a sequence of three *unpredictable prompts* (18) to perform three visible actions (20) in the form of "smile", "unhappy" and "tongue out". A dashed arrow labelled "T" indicates the passage of time between *prompts* (18) or actions (20). The *prompts* (18) are displayed individually for a predetermined length of time, e.g. seven seconds. The *entity* (15) is asked to perform the actions (20) as the *prompts* are displayed (18) and the webcam (17) at first *user terminal* (13) simultaneously records the prompted action performance of the *entity* (15). The recording (21) is then stored and served to an *assessing user* (16) at second *user terminal* (14) who is able to view and assess the recording (21) as displayed at the second *user terminal* (14). **Figure 7** shows the circumstance where the *entity* (15) performs the correct actions in the correct sequence and thus the *assessing user* (16) is able to assess the *entity* (15) positively as having preformed the correct actions in the correct sequence.

Figure 8 provides the same initial situation as in **Figure 7** but no recording (21) is provided to the *assessing user* (16) which results in the *assessing user* (16) providing an "inconclusive" or "negative" assessment as they are unable to view the *entity* (15).

Figure 9 also provides the initial situation as in **Figure 7** but the *entity* (15) has performed the prompted actions (20) in an incorrect sequence. The *assessing user* (16) may thus assess the *entity* (15) negatively and choose not to communicate with the *entity* (15). An example of the video capture screen (53) and a single *prompt* (18) is shown in **figure 10a**. The *entity* (15) is also able to review a playback of their video recording and can repeat the recoding process if unsatisfied with the recording.

The server (11) configured for either methods 100b or 100c, may also be programmed to determine if a sufficient number of *users* provide negative assessments of the video recordings provided by the *entity* (15). The server (11) then will classify the *accessed user account* negatively, e.g. 'suspicious'. Depending on various configurations, the *entity* (15) may be logged out, the *accessed user account* suspended or other *users* (e.g. other members of internet dating services) can be warned that the *entity* (15) corresponding to the *accessed user account* is suspicious. In one embodiment vulnerable *users*, e.g. children, could be blocked from interacting with any *entity* (15) communicating from the *accessed user account*.

Thus, the aforementioned method may help identify imposters or other suspicious behaviour by providing a means for *users* to identify each other and note anything suspicious, thereby providing a greatly enhanced assessment system and moving the burden of advanced authentication from the network provider to the *users* of the network.

It will be appreciated that the aforementioned methods may differ in numerous ways without departing from the scope of the invention.

By way of example only, the video login steps (109-111) may be required at one, or multiple, or each:

- *access request*, including where *user* credentials are stored in cookies on the first *user terminal*;
- *access request* where the *entity* (15) or other *user* must enter access credentials.
- *access request* where the IP address of the first *user terminal* changes.
- *access request* where the physical login location of the first *user terminal* changes. This may be detected based on IP address, GPS, cellular network location detection methods of the first *user terminal*.
- n^{th} *access request*, per week or other time-frame.

In another example, if a particular *assessing user* (B) positively assesses (122) an *entity* (A) a predetermined number of times while a predetermined number of other *users* negatively (124) assess *user* (A), then the server (11) may store a record in the *assessing user's* account that *assessing user* (B) is classified negatively and may be suspicious, i.e. *assessing user* (B) may be attempting to falsely positively assess *user* (A).

Conversely, if an *assessing user* (B) provides a predetermined number of negative assessments of an *entity* (A) while a predetermined number of other *users* provide positive assessments, then the server (11) may store a record in *assessing user* (B)'s account that *assessing user* (B) may be suspicious, i.e. *user* (B) may be falsely attempting to prevent *entity* (A) from becoming positively assessed and communicating on the communication network.

The ratio of positive to negative assessments from an *assessing user* (16) and/or other *users* in relation to a particular *entity* (15) can be used not only as feedback on the validity of the *entity* (15) but also, potentially as feedback on the validity of the *assessing user* (16). The *entity* (15) and/or *assessing user* (16) may thus be assigned an *assessment rating* based on the ratio of positive to negative assessments made. As shown in **figure 10b**, this *assessment rating* (51) (shown as a % value) can be displayed on the web-page next to the profile picture of the corresponding *user account*. **Figure 10b** also shows an example image of the video recording (21) of the *entity* (15) and details of the other *users* accessible to the *entity* (15) i.e. *assessing user* (16a) and their contacts (16b, 16c) along with the first frame of their respective assessment recordings (21a, 21b, 21c). The *entity* (15) can view their contacts' (16a, 16b, 16c) recordings (21a, 21b, 21c) by clicking on the still images (21a, 21b, 21c). An *assessment rating* (51) is displayed for each *user* (16) and the total number of assessments (52) is also displayed.

Figure 10b may also form part of a first *user's* 'friends page' on a social network (8) such that the *entity* (15) (labelled "you") is able to easily view the *assessment ratings* (51) of the contacts recorded against the *accessed user account* as well as take the role of *assessing user* (16) in the assessment method (100a-b) to assess those contacts (16a, 16b, 16c). Similarly, the contacts (16a, 16b, 16c) will be able to view the *entity's* recording (21) to assess the *entity* (15).

Figure 11 shows a process flowchart (200) of an automated *entity* assessment method according to another preferred embodiment the present invention. This method (200) uses an automated face and gesture recognition system (not shown) instead of the *assessing user* (16) in the method shown in **figures 4-5**. The method (200) generally uses comparable hardware as shown in **figure 2** but with the further inclusion of gesture and face recognition software and necessary hardware, e.g. dual cameras, infrared illumination system and the like.

Such face and gesture recognition systems are well-known in the art and will not be described in further detail herein, except to state that the face recognition system needs to be capable of analyzing human facial features to compare with a reference source such as a video, image or biometric data. A match is determined if the correlation between the face detected and the reference source is sufficient. The gesture recognition system needs to be capable of detecting human facial and/or body gestures. An example of a suitable facial and gesture recognition system is the Microsoft™ Kinect™ system. The gesture recognition system may alternatively use additional apparatus, e.g. a traceable item that the *user* performs the gestures with. The traceable item thus negates the need for the gesture recognition system to recognize human body parts.

The method, system and software of the second embodiment (200) may also be used on proprietary hardware, e.g. the first *user terminal* (13) may be a kiosk, security door, banking ATM, mobile phone, or other device capable of accessing a *data network*.

In general the aforesaid second embodiment (shown in **figure 11**) involves the following steps:

- (step 201) Receiving an *access request* from an *entity* (15) from a first *user terminal* (13) for access to a *user account* on the *data network* (10).
- (step 202) The *access request* includes an initial "login" request (201) with submission of credentials including a *user ID* and password. A database (50) of *user accounts* is queried to identify a *user account* with a matching *user ID*.
- (step 203) The server (11) receives the submitted credentials and determines if they match the credentials as indicated by the *accessed user account*, and/or whether the *user ID* entered matches any *user account* in the database (50). If the credentials don't match, the login fails and the *entity* (15) is notified that the login has failed (215). The *entity* (15) is then returned to repeat the login process (201).
- (step 204) If the credentials do match, the initial login is read as a success. The next step (205) involves sending a request to the first *user terminal* (13) to access a webcam (17) or other recording device. This request may be in the form of a Flash™ application, remote method invocation, an HTTP GET/POST request (a URL request), an application specific request or similar. Alternatively, the *entity* (15) may be required to install software on the first *user terminal* (13) which then accesses the webcam (17) on behalf of the server (11). The webcam (17) is preferably controlled by the software or web server (11) to prevent pre-recordings being provided to the server (11) in place of a 'live' webcam recording.
- (step 205) The request is then processed by the first *user terminal* (13) and a reply sent to the server (11) indicating whether the first *user terminal* (13) has a video recording device (17).
If a video recording device (17) is not available, the *access request* fails (215) and the *entity* (15) is denied access to the *data network* (10), or only permitted restricted access.
- (step 206) If a video recording device (17) is available, the *control system* (11) accesses the *accessed user account* and queries the existence of pre-recorded biometrics extracted from a calibration process (213) that analyses the face and gesture biometrics of the *registered user* of the *accessed user account* when first registering. If no pre-recording exists the *entity* (15) is treated as the *registered user* and is asked to perform the calibration procedure (213) after step (206).
- (step 207) If the *control system* (11) locates existing biometrics a sequence of *unpredictable prompts* is invoked and the first of three *unpredictable prompts* (18) is displayed on the first *user terminal* (13) to ask the *entity* (15) to perform a visible action (20), e.g. as described with respect to the first embodiment (100).
- (step 208) The video recording device (17) then records the *entity* (15) performing the first prompted action (20).
- (step 209) The server (11) repeats steps (207 and 208) with a random time delay between each *prompt* (18) until three *prompts* (18) have been provided and recorded.
- (step 210) The recording is then analysed using the gesture recognition system. If the actions (20) performed by the *entity* (15) match reference gestures correlating to the *prompts* (18) provided and were performed in the correct sequence, then a positive *assessment signal* is generated for the *Actions assessment* (210) indicating the actions (20) were performed correctly. If an action (20) is recorded that does not match the corresponding *prompt* (18) or an action (20) is recorded out of sequence then a negative *assessment signal* is generated for the *Actions assessment* (210) indicating the prompted actions were performed incorrectly and the login request is denied (215).
- (step 211) The recording is then analysed using the facial recognition system. If the face of the *entity* (15) in the recording (21) surpasses a threshold level of correlation to *identifying characteristics* (e.g. the reference biometrics) stored in the database (50) then a positive *assessment signal* is generated indicating the *entity* (15) is visually assessed positively as correlating to the *accessed user account*.
- (step 212) The system also captures and updates the reference biometrics if a positive *classification* is made.
- (step 213) The calibration process (213) may involve two sub-procedures (not shown in **figure 11**), namely:
 - Requesting the *entity* (15) present their face to the video recording device (17) from varying angles and with various expressions. These reference videos are analysed by a face recognition algorithm to extract face biometrics/parameters, e.g. distance between eyes, nose size etc. These biometrics and the video are stored in the database (50) in the *accessed user account*, and

- *prompting the entity (15) to perform a series of gestures which are analysed using a gesture recognition algorithm to create reference gesture parameters that are stored in the database (50) in the first user's account record.*

After the calibration procedure (214) the *entity (15)* is logged into the *data network*.

(step 214) The *entity* is logged into the network (10) and provided access to the corresponding *user account* if the *entity's (15)* face and visible actions are assessed positively with respect to reference biometrics stored in the *accessed user account*.

The *entity (15)* is logged in (provided access) to the network (10):

- after the calibration procedure (213); or
- upon positive actions and visual assessments (210-211)

(step 215) As described above, the *entity (15)* is denied access if the server (11) makes:

- incorrect credentials received;
- no video recording device present;
- a negative actions assessment;
- a negative visual assessment.

The aforementioned method (200) provides an automated system of *entity* assessment that does not rely on an *assessing user (16)* to assess the *entity (15)*. The use of facial and gesture recognition systems instead of an *assessing user* may thus prove useful in many applications where an *entity* does not wish to, or is not required to, provide video to other *users* but requires access to the *data network (10)*, e.g. as previously mentioned, applications such as banking logins and so forth.

In a further embodiment, the facial recognition system may also be configured to analyse the face biometrics of the recorded *entity* and generate a "TAMPERED VIDEO" signal if the analysis indicates rapid changes in particular biometrics (e.g. distance between eyes) during the recording. Such changes may indicate a false video that is generated from multiple recordings 'stitched' together.

In a further embodiment (not shown) the method (200) may be used to access a *user terminal (13, 14)*, i.e. rather than accessing the *data network (10)* directly, the assessment method (200) may be used to access the *user terminal (13, 14)*. Subsequently the *user terminal (13, 14)* is therefore able to freely access the *data network (10)* or a further assessment process (100, 200) performed in order to gain access to the network (10).

In an alternative embodiment to the login steps (202) to (203), the server (11) may conduct steps to capture a video or image of the *entity (15)* and run the facial recognition algorithm (67c) to identify *user accounts* in database (50) with matching biometric data, if matching data is found the *entity (15)* may be automatically logged in to access the corresponding *user account*, thereby obviating the need to supply username and password credentials. Alternatively, the server (11) may run steps (207) to (210) and use the *video recording* captured to not only identify *user accounts* in database (50) with matching biometric data but also to determine if the actions were performed 'validly'. Thus the *entity* can be 'logged-in' while also having their prompted *actions* assessed.

Aspects of the present invention have been described by way of example only and it should be appreciated that modifications and additions may be made thereto without departing from the scope of the claims.

CLAIMS:

1. A method of assessing an *entity* at a first *user terminal* connected to a *data network*, said method utilising a *control system* operable to perform the steps of:
 - a) receiving an *access request* from at least one of:
 - said *entity*;
 - an *assessing user* at a second *user terminal* connected to the *data network*;
 - b) invoking or facilitating transmission of at least one *unpredictable prompt* to said *entity* for a performance of a *visible prompted action*;
 - c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
 - d) performing:
 - an automated assessment of said video recording; and/or
 - an invocation or facilitation of a transmission of said video recording from said *data store* and details of said *prompt* to a second *user terminal* for viewing and assessment by an *assessing user*.
2. The method as claimed in any one of the preceding claims, wherein the *visible prompted action* includes facial gestures, hand and/or other body gestures.
3. The method as claimed in claim 1 or claim 2, wherein the *data network* includes one or more related user records collectively forming a "*user account*" in a database in a *data store* accessible by the *control system* and wherein said *user account* includes a set of *identifying characteristics* relating to a *registered user*.
4. The method as claimed in any one of the preceding claims, wherein the *data network* includes a "*virtual network*" formed from connections between multiple *users* connected to the *data network*, said *virtual network* embodied in related data records in a database, each data record corresponding to a *registered user* or a *user terminal*.
5. The method as claimed in claim 3 or claim 4, whereupon receiving the *access request* at step a), the *control system* determines a *user account* (hereinafter "*accessed user account*") corresponding to credentials provided by the first *user terminal*.
6. The method as claimed in any one of the preceding claims, wherein the *control system* at least partially controls data transmission between said *user terminals* via the *data network*.
7. The method as claimed in any one of the preceding claims, wherein at least one audio recording of said *visible prompted action* is recorded and stored.
8. The method as claimed in any one of the preceding claims, wherein the first *user terminal* includes a touch screen or a gesture recognition system and said method includes the further step of recording a sequence of touch or gesture-actions.
9. The method as claimed in any one of the preceding claims, wherein the *prompt* is provided in a form selected from the group including: text, graphical objects, symbols, representations, audible sounds, video, animations, combinations and permutations thereof.
10. The method as claimed in claim 9, wherein the *prompt* is provided as text or images.
11. The method as claimed in any one of the preceding claims, wherein the *prompt* is only provided to the *entity* for a predetermined duration.
12. The method as claimed in any one of the preceding claims, wherein multiple *prompts* are provided for the *entity* to perform corresponding actions, at least one said action being visible.
13. The method as claimed in claim 12, wherein at least three said *prompts* are provided.
14. The method as claimed in claim 12 or claim 13, wherein the *prompts* are provided in a time-delimited sequence.
15. The method as claimed in any one of claims 12-14, wherein said *prompts* are provided to the *entity* with a time delay between each *prompt*.
16. The method as claimed in claim 15, wherein the time delay between pairs of consecutive *prompts* differ.
17. The method as claimed in claim 15 or claim 16, wherein the time delay between pairs of consecutive *prompts* are of an *unpredictable* length within a predetermined range.
18. The method as claimed in any one of the preceding claims, wherein steps b) and c) are performed synchronously.
19. The method as claimed in any one of the preceding claims, wherein at step b) the *control system* invokes the *prompt* by providing computer-executable code or computer-readable data to software on the first *user terminal* which then generates the *prompt* accordingly.

20. The method as claimed in any one of the preceding claims, wherein before step d) the *control system* receives and processes data relating to a *view request* from said *assessing user* to view said video recording.
21. The method as claimed in any one of the preceding claims, wherein the *data store* for storing the video recording is provided separately to a *user data store* containing a database of *user account* records.
22. The method of any one of the preceding claims, wherein said *control system* receives an *assessment signal* from said automated assessment.
23. The method of any one of the preceding claims, wherein said assessment is performed by said *assessing user* at a second *user terminal* connected to the *data network*, wherein at step d) the *control system* invokes or facilitates transmission of said video recording from said *data store* and details of said *prompt* to said second *user terminal* for viewing and assessment by said *assessing user* and includes the further step of:
 - a) receiving from said *assessing user* an *assessment signal*.
24. The method of claim 22 or claim 23, wherein the *assessment signal* includes at least one positive, negative or inconclusive *assessment signal*.
25. The method of claim 24, wherein said *control system* uses the *assessment signal* to classify, or contribute to a determination to classify said *entity* and said *classification* of the *entity* is determined by the *assessment signal*.
26. The method of claim 25, wherein the *control system* makes a negative *classification*.
27. The method of claim 26, wherein the *control system* records to an *accessed user account* that the *entity* has had a negative *classification*.
28. The method of claim 26 or claim 27, wherein the *control system* invokes a warning notification for other *users* attempting to communicate with the *entity* that a negative *classification* has occurred.
29. The method of any one of claims 26-28, wherein the *control system* blocks the *entity* from communication with other *users*.
30. The method of any one of claims 26-29, wherein the *control system* suspends or cancels an *accessed user account*.
31. The method of any one of claims 26-30, wherein the *control system* sends a warning notification to a network administrator or other authority to investigate the *entity* and/or negative assessment.
32. The method of any one of claims 26-31, wherein the *control system* selectively restricts the type of communication allowed between the *entity* and other *users*.
33. The method of any one of claims 26-32, wherein the *control system* selectively restricts the type of access allowed or the extent of access.
34. The method of any one of claims 22-33, wherein the *assessment signal* provides an indication of at least one of the following assessments:
 - *Actions assessment* – wherein the *entity's* prompted performance is assessed to determine if it is a valid response to said *prompt*.
 - *Visual assessment* – wherein the *entity* is assessed to determine if the *entity* has a characteristic the same or similar to at least one *identifying characteristic* of an *accessed user account*.
 - *Persona assessment* – wherein the *entity* is assessed to determine if the *entity* is recognised as corresponding to the *persona* of an *accessed user account*.
 - *General assessment* – wherein the video recording is assessed for authenticity.
35. The method of claim 34, wherein the *assessment signal* includes, for each type of assessment made, a positive, negative or inconclusive signal.
36. The method of claim 1, wherein at step d), the *control system* invokes an automated assessment of said video recording and generates an *assessment signal* indicative of said assessment.
37. The method of claim 36, wherein said automated assessment includes assessment by a gesture recognition system, wherein said *assessment signal* respectively includes a positive or negative indication of whether or not said *entity* validly performed said prompted action.
38. The method of claim 36 or claim 37, wherein said automated assessment includes assessment by a facial recognition system to analyse the *entity's* face with respect to an *identifying characteristic* in an *accessed user account* and wherein said *assessment signal* respectively

- includes a positive or negative indication of whether or not said *entity* is assessed as having a facial characteristic the same or similar to said *identifying characteristic*.
39. The method of claim 38, wherein said *identifying characteristic* includes a pre-recorded image, video recording and/or stored biometric data of a face.
 40. The method of claim 37, wherein said *control system* includes said gesture recognition system.
 41. The method as claimed in claim 38 or claim 39, wherein said *control system* includes said facial recognition system.
 42. The method as claimed in any one of claims 36-41, wherein the automated assessment is conducted remotely to said *control system* while being invoked by said *control system*.
 43. The method as claimed in any one of claims 38-39, wherein the *control system* is configured to assess the video recording using said facial recognition system and compare the recorded face with *identifying characteristics* of *user accounts* in a *user database*.
 44. The method as claimed in any one of claims 36-43, wherein said *control system* is located at said *first user terminal* and wherein automated assessment is required in order to access said *first user terminal*.
 45. A method as claimed in any one of claims 1-44, wherein the video recording is used as a *signature* by which the *entity* can be identified.
 46. The method of claim 45, wherein the *prompt* is provided to the *entity* in conjunction with a *contract* or offer of *contract*.
 47. The method of claim 46, wherein the *contract* is selected from the group comprising: an agreement, deed, item, product, software, license, service, competition.
 48. A *control system* for facilitating entity assessment of an *entity* at a *first user terminal* connected to a *data network*, said *control system* including a computer system with a computer processor coupled to a system memory and programmed with computer readable instructions executable to perform the following procedures:
 - a) receiving and processing data relating to an *access request* from at least one of:
 - said *entity*;
 - an *assessing user* at a second *user terminal* connected to the *data network*;
 - b) invoking or facilitating transmission of at least one *unpredictable prompt* for said *entity* to perform a *visible prompted action*;
 - c) invoking storage of at least one video recording of said prompted action performance from said *entity* in a *data store*;
 - d) performing:
 - an automated assessment of said video recording; and/or
 - invocation or facilitation of transmission of said video recording from said *data store* and details of said *prompt* to a second *user terminal* for viewing and assessment by an *assessing user*.
 49. The *control system* as claimed in any one of the preceding claims, wherein the *visible prompted action* includes facial gestures, hand and/or other body gestures.
 50. The *control system* as claimed in claim 48 or claim 49, wherein the *data network* includes one or more related user records collectively forming a "*user account*" in a database in a *data store* accessible by the *control system* and wherein said *user account* includes a set of *identifying characteristics* relating to a *registered user*.
 51. The *control system* as claimed in claim 48, wherein the *data network* includes a "*virtual network*" formed from connections between multiple *users* connected to the *data network*, said *virtual network* embodied in related data records in a database, each data record corresponding to a *registered user* or a *user terminal*.
 52. The *control system* as claimed in claim 50 or claim 51, whereupon receiving the *access request* at step a), the *control system* is configured to run an algorithm to determine a *user account* (hereinafter "*accessed user account*") corresponding to credentials provided by the *first user terminal*.
 53. The *control system* as claimed in any one of claims 48-52, wherein the *control system* at least partially controls data transmission between said *user terminals* via the *data network*.
 54. The *control system* as claimed in any one of claims 48-53, configured to provide the *prompt* in a form selected from the group including: text, graphical objects, symbols, representations, audible sounds, video, animations, combinations and permutations thereof.
 55. The *control system* as claimed in claim 54, wherein the *prompt* is text or images.

56. The *control system* as claimed in any one of claims 48-55, configured to invoke or facilitate transmission of the *prompt* for a predetermined duration.
57. The *control system* as claimed in any one of claims 48-56, configured to invoke or facilitate transmission of multiple said *prompts*.
58. The *control system* as claimed in claim 57, configured to invoke or facilitate transmission of at least three said *prompts*.
59. The *control system* as claimed in any one of claims 57-58, configured to invoke or facilitate transmission of the *prompts* in a time-delimited sequence.
60. The *control system* as claimed in any one of claims 57-59, configured to invoke or facilitate transmission of said *prompts* to the *entity* with a time delay between each *prompt*.
61. The *control system* as claimed in claim 60, wherein the time delay between pairs of consecutive *prompts* differs.
62. The *control system* as claimed in claim 61, wherein the time delay between pairs of consecutive *prompts* are of an *unpredictable* length within a predetermined range.
63. The *control system* as claimed in any one of claims 48-62, configured to perform steps b) and c) synchronously.
64. The *control system* as claimed in any one of claims 48-63, wherein at step b) the *control system* invokes the *prompt* by providing computer-executable code or computer-readable data to software on the first *user terminal* which then generates the *prompt* accordingly.
65. The *control system* as claimed in any one of claims 48-64, wherein before step d) the *control system* is configured to receive and process data relating to a *view request* from said *assessing user* to view said video recording.
66. The *control system* as claimed in any one of claims 48-65, wherein the *data store* for storing the video recording is provided separately to a *user data store* containing a database of *user account* records.
67. The *control system* as claimed in any one of claims 48-66, wherein said *control system* is configured to receive and process an *assessment signal* from said automated assessment.
68. The *control system* as claimed in any one of claims 48-67, wherein said assessment is performed by said *assessing user* at a second *user terminal* connected to the *data network*, wherein at step d) the *control system* invokes or facilitates transmission of said video recording from said *data store* and details of said *prompt* to said second *user terminal* for viewing and assessment by said *assessing user* and includes the further step of:
 - e) receiving from said *assessing user* an *assessment signal*.
69. The *control system* as claimed in claim 67 or claim 68, configured to use the *assessment signal* to classify, or contribute to a determination to classify said *entity* and wherein said *classification* of the *entity* is determined by the *assessment signal*.
70. The *control system* of claim 48, configured to invoke an automated assessment of said video recording at procedure d) and generate an *assessment signal* indicative of said assessment.
71. The *control system* of claim 70, including a gesture recognition system and wherein said automated assessment includes assessment by said gesture recognition system.
72. The *control system* of claim 71, wherein said *assessment signal* respectively includes a positive or negative indication of whether or not said *entity* validly performed said prompted action.
73. The *control system* of any one of claims 70-72, including a facial recognition system and wherein said automated assessment includes assessment by said facial recognition system to analyse the *entity's* face with respect to an *identifying characteristic* in an *accessed user account*.
74. The *control system* of claim 73, wherein said *identifying characteristic* includes a pre-recorded image, video recording and/or stored biometric data of a face.
75. The *control system* of claim 73 or claim 74, wherein said *assessment signal* respectively includes a positive or negative indication of whether or not the control system assesses said *entity* as having a facial characteristic the same or similar to said *identifying characteristic*.
76. The *control system* as claimed in any one of claims 48-76, located at said first *user terminal* and wherein said automated assessment is required in order for the *entity* to access said first *user terminal*.
77. Computer software for performing the method as claimed in any one of claims 1-47, said computer software embodied in computer-readable instructions executable to perform the steps of said method.


Figure 1 (Prior Art)


Figure 2


Figure 3


Figure 4


Figure 5


Figure 6


Figure 7


Figure 8


Figure 9

Figure 10a

This will take a short video of you and prompt you to perform a series of random actions. Please give this application permission to use your web camera.




**Figure 10b****View Clips**

Figure 11

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 11/53429

A. CLASSIFICATION OF SUBJECT MATTER

IPC(8) - G11C 7/00 (2011.01)

USPC - 726/26

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

USPC: 726/26

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
USPC: 707/705,999.002,999.107 | 726/26-30 (keyword limited; terms below)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

Electronic Database Searched: PubWEST(PGPB, USPT, EPAB, JPAB), Google Scholar

Search Terms Used: validate, verify, authenticate, confirm, login, logon, sign, log, on, in, user, person, individual, member, subscriber, customer, employee, agent, transmit, display, output, show, play, indicate, prompt, ask, mimic, request, motion, gesture, movement

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/0170776 A1 (Albertson et al.) 17 July 2008 (17.07.2008), see entire document; especially para [0005]-[0008], [0028]-[0033], [0035]-[0039], [0042]-[0047], [0050]-[0053], [0072], [0101], [0108]-[0112], Fig. 1-4, 6-7	1-2, 36-40, 48-49, 51, 70-74
A	US 2009/0259588 A1 (Lindsay) 15 October 2009 (15.10.2009), see entire document	1-2, 36-40, 48-49, 51, 70-74
A	US 2003/0154406 A1 (Honarvar et al.) 14 August 2003 (14.08.2003), see entire document	1-2, 36-40, 48-49, 51, 70-74
A	US 6,421,453 B1 (Kanevsky et al.) 16 July 2002 (16.07.2002), see entire document	1-2, 36-40, 48-49, 51, 70-74

☐ Further documents are listed in the continuation of Box C.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

03 January 2012 (03.01.2012)

Date of mailing of the international search report

09 JAN 2012

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US, Commissioner for Patents
P.O. Box 1450, Alexandria, Virginia 22313-1450

Facsimile No. 571-273-3201

Authorized officer:

Lee W. Young

PCT Helpdesk: 571-272-4300
PCT OSP: 571-272-7774

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 11/53429

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☒ Claims Nos.: 3-35, 41-47, 50, 52-69, 75-77
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.