




(86) **Date de dépôt PCT/PCT Filing Date:** 2007/02/27
(87) **Date publication PCT/PCT Publication Date:** 2007/09/07
(45) **Date de délivrance/Issue Date:** 2014/04/29
(85) **Entrée phase nationale/National Entry:** 2008/08/25
(86) **N° demande PCT/PCT Application No.:** US 2007/005151
(87) **N° publication PCT/PCT Publication No.:** 2007/100849
(30) **Priorités/Priorities:** 2006/02/27 (US60/777,138);
2006/02/27 (US60/777,203)

(51) **Cl.Int./Int.Cl.** **B29D 23/00** (2006.01),
B29C 33/00 (2006.01)
(72) **Inventeur/Inventor:**
SLAFER, W. DENNIS, US
(73) **Propriétaire/Owner:**
MICROCONTINUUM, INC., US
(74) **Agent:** G. RONALD BELL & ASSOCIATES

(54) **Titre : FORMATION D'OUTILS DE REPRODUCTION DE MOTIFS**
(54) **Title: FORMATION OF PATTERN REPLICATING TOOLS**



Metal or polymer copies can be made directly from original pattern or
from one another

(57) **Abrégé/Abstract:**

Systems, methods, and apparatus are disclosed for making patterning tools from one or more discrete elements. Such tools can have one or more "seams" or joints where the individual elements abut which can limit the tools' performance and utility in roll-to-roll manufacturing. Methods are described herein for producing "near-seamless" tools, that is, tools having seams that exhibit minimum disruption of the tool pattern and thus improved material produced by such tools. The patterning tools can be cylindrical and/or closed in shape.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
7 September 2007 (07.09.2007)

PCT

(10) International Publication Number
WO 2007/100849 A3(51) International Patent Classification:
B29D 11/00 (2006.01)(21) International Application Number:
PCT/US2007/005151(22) International Filing Date:
27 February 2007 (27.02.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/777,203 27 February 2006 (27.02.2006) US
60/777,138 27 February 2006 (27.02.2006) US(71) Applicant (for all designated States except US): **MI-CROCONTINUUM, INC.** [US/US]; 57 Smith Place, Cambridge, MA 02138 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SLAFER, W., Dennis** [US/US]; 99 Jason Street, Arlington, MA 02476 (US).(74) Agents: **KUSMER, Toby, H.** et al.; McDermott Will & Emery LLP, 28 State Street, Boston, MA 02109 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
10 April 2008

(54) Title: FORMATION OF PATTERN REPLICATING TOOLS



(57) **Abstract:** Systems, methods, and apparatus are disclosed for making patterning tools from one or more discrete elements. Such tools can have one or more "seams" or joints where the individual elements abut which can limit the tools' performance and utility in roll-to-roll manufacturing. Methods are described herein for producing "near-seamless" tools, that is, tools having seams that exhibit minimum disruption of the tool pattern and thus improved material produced by such tools. The patterning tools can be cylindrical and/or closed in shape.

WO 2007/100849 A3

FORMATION OF PATTERN REPLICATING TOOLS

BACKGROUND

[0002] A number of technology applications require the creation of precise relief structures having critical dimensions from the multi-micron to the nanometer size regime. Roll-to-roll (R2R) processes for reproducing such structures often utilize a patterning tool in the form of a cylinder or belt, and a number of methods for producing cylindrical tools are well known to the art, particularly in the graphic arts field. Typically such tools comprise one or more discrete pattern elements attached to the outer surface of a support member. See U.S. Patent No. 5,147,763; U.S. Patent No. 6,163,523; U.S. Patent No. 4,836,874; and U.S. Patent No. 4,486,363. Examples of seamed tools used in R2R optical disc fabrication include those disclosed in W.D. Slafer, M. Kime, and R. Monen, "Continuous Web Manufacturing of Thin-Coverslip Optical Media", SPIE Optical Data Storage '92, San Jose, CA, 12 Feb. 1992.

[0003] The seams that can result from forming patterning tools from discrete elements often represent a limitation in manufacturing processes that utilize such tools. Even in cases in which the pattern to be replicated is already composed of discrete elements (such as discs, cards, display screens, etc.), the seams can effect the production process, such as by causing "speed bumps" at the seam which cause pressure roller bouncing (especially at higher line speeds), trapping of processing fluid in low spots, "tenting" at high spots (resulting in non-contact between the substrate and the tool pattern), etc. Seams can also result in performance and visual limitations in the material being produced by such tools, for example in diffractive optical elements, large-area displays, embossed holographic foils and the like.

[0004] Because the creation of cylindrical patterning tools can be expensive and time consuming, particularly when a very precise and/or finely-detailed pattern is involved, it is very desirable to be able to quickly and inexpensively make precise replicas of such tools.

5 **SUMMARY**

[0005] The present disclosure addresses limitations of the prior art and provide improved systems, methods, and apparatus useful for forming cylindrical patterning tools from one or more discrete pattern-containing parts that are suitable for use in roll-to-roll manufacturing. Such tools are used for the replication of relief patterns in such areas as flexible electronics, holography, micro/nanostructure fabrication, micro/nanoprinting, and data storage, to name
10 a few. The shapes of the patterning tools can be cylindrical and/or continuous, such as a belt, cylinder, and/or drum configuration.

According to an aspect of the present invention, there is provided a relief pattern replication
15 tool comprising: one or more discrete elements having desired relief patterns configured with one common seam between adjacent pairs of the elements, wherein each discrete element is rectangular and has a length and width, wherein individual features of corresponding relief patterns on adjacent elements are aligned across a common seam that is linear and traverses the entire length or width, respectively, of each element of adjacent pairs of elements, and
20 wherein the relief patterns are three-dimensional relief patterns having desired features and are configured to be co-planar across the seam and within a desired height offset, wherein the desired features are configured for embossing.

BRIEF DESCRIPTION OF FIGURES

25 [0006] Aspects of the present disclosure may be more fully understood from the following description when read together with the accompanying drawings, which are to be regarded as illustrative in nature, and not as limiting. The drawings are not necessarily to scale, emphasis instead being placed on the principles of the disclosure. In the drawings:

[0007] FIG. 1A depicts a schematic view of apparatus and related process flow for forming metal or polymer replica copies from an original surface relief pattern or from one another;

[0008] FIG. 1B depicts a schematic view of apparatus and related process flow for drum formation and replication showing interconversion between internal and external patterns, where the process can begin with external master pattern or internal master pattern;

[0009] FIG. 2A depicts a fixture for improving surface flatness by minimizing effects of thickness variation at edges of abutted parts;

[0010] FIG. 2B is a schematic view depicting the joining of metal elements by laser welding to form externally patterned cylinder;

[0011] FIG. 3 depicts a step-and-repeat process for replicating discrete pattern element on continuous substrate strip using chemical, radiation curing, thermal or other imprint replication process;

[0012] FIG. 4 depicts a conversion of a strip of patterns ("original") into a single tool, where the original can be a selected material such as a metal, polymer, silicon, glass, photoresist, etc., and the tool (copy) can be a selected material such as metal or polymer;

[0013] FIG. 5 depicts a first fixture for holding a pattern to be copied, without damage, while first precision cuts are made using embedded reference marks, for subsequent transfer of the pattern to a second fixture;

[0014] FIG. 6 depicts a second fixture for holding a pattern to be copied, without damage, while second precision cuts are made using embedded reference marks;

[0015] FIG. 7 depicts a side view of a fixture similar to that of FIG. 6, showing pattern element, protective mask layer, and hold-down plate;

[0016] FIG. 8 depicts a configuration of a multiplicity of parts mounted in three fixtures similar to those of FIGS. 6-7, illustrating interconnection by precision slides;

[0017] FIG. 9 depicts a configuration similar to that of FIG. 8 with the addition of a "mask" to combined the fixtures to prevent/reduced metal plating or polymer replicating material from contacting fixture components;

[0018] FIG. 10 depicts a continuous part after separation from combined fixtures such as shown in FIGS. 8-9;

[0019] FIG. 11 depicts a pattern strip mounted in a two-piece shell fixture, with the pattern facing radially inward;

[0020] FIG. 12 depicts an alternative embodiment of a fixture for drum tool formation in accordance with the present disclosure;

[0021] FIG. 13 depicts an alternate embodiment of a two-piece drum forming fixture including two assembled semi-cylindrical shell halves and pattern elements;

[0022] FIG. 14 depicts a cylinder shell component configured for use in a three-piece drum forming fixture;

[0023] FIG. 15 depicts an expanded and disassembled configuration of a three-piece shell according to an embodiment of the present disclosure;

[0024] FIG. 16A depicts a schematic of process for separating an inner drum tool from an outer "mold" inside which the inner tool can be formed;

[0025] FIG. 16B depicts a technique for attaching cylindrical pattern to support ("sleeve") in accordance with an embodiment of the present disclosure; and

[0026] FIG. 17 depicts apparatus and corresponding motion as used for forming an externally patterned drum with a minimal seam, in accordance with a further embodiment of the present disclosure.

[0027] It should be understood by one skilled in the art that the embodiments depicted in the drawings are illustrative and variations of those shown as well as other embodiments described herein may be envisioned and practiced within the scope of the disclosure.

DETAILED DESCRIPTION

[0028] The present disclosure addresses limitations of the prior art and provides systems, methods, techniques, and apparatus useful for forming cylindrical patterning tools from one or more discrete pattern-containing parts that are suitable for use in roll-to-roll manufacturing.

[0029] Such patterning tools can be used for the replication of relief patterns that are utilized in such technical areas/fields as flexible electronics/circuitry, holography, micro/nanostructure fabrication, micro/nanoprinting, and data storage, to name a few examples. The shapes of the patterning tools can be cylindrical and/or continuous, such as a belt configuration. These patterning tools can be used for forming desired three-dimensional patterns in various media, and may be used for the mass-production of such media, as described below.

Definitions

[0030] As used for the present disclosure, the term "pattern" can denote a three-dimensional relief structure, such as shown in FIG. 1A, which depicts a schematic view of apparatus and related process 100A flow for forming metal 104 or polymer 106 replica copies from an original surface relief pattern 102 or from one another.

[0031] As used herein, the term "part" or "element" can denote a discrete substrate containing a pattern on one surface; the term "support" or "substrate" can denote a surface containing a pattern or patterned layer. A "mold" can refer to a surface containing a relief pattern which is used to create a part with a complementary relief pattern. A "replica" or "copy" can refer to a part made from a mold which has a

relief pattern complementary to that of the mold. A "tool" can denote a surface containing a relief pattern used to emboss or imprint multiple complementary copies of the tool pattern, such as shown and described for FIG. 1B, which depicts a schematic view of apparatus and related process flow 100B for drum formation and replication showing interconversion between internal and external patterns, where the process can begin with external master pattern or internal master pattern.

[0032] For the purposes of this disclosure, a "joint" can refer to the area wherein two edges abut, and a "seam" can refer to a joint that is physically connected by welding or bonding or other such means. An "improved seam" may refer to one having significantly reduced or minimal surface non-uniformities and discontinuities relative to seams of conventional tools, e.g., as formed using techniques shown as described for FIGS. 2A-2B. FIG. 2A depicts a: fixture for improving surface flatness by minimizing effects of thickness variation at edges of abutted parts. FIG. 2B is a schematic view depicting the joining of metal elements by laser welding to form externally patterned cylinder;

[0033] Further defining terms used in the present disclosure, a "continuous" patterned surface or cylinder can be one in which the substrate upon which the pattern is formed is essentially a single element. A "dry fitted" joint can refer to one in which the butted pattern edges are held against or positioned adjacent to one another by mechanical techniques without a need for welding or bonding.

[0034] As used herein a "step and repeat" process can include reference to formation of a continuous pattern of smaller abutted patterns by repeated imprinting of a patterned surface in a substrate, e.g., as shown and described or FIG. 3, which depicts a step-and-repeat process for replicating discrete pattern element on continuous substrate strip using chemical, radiation curing, thermal or other imprint replication process. "Registration" or "alignment" can refer to the positioning of adjacent parts to provide effective continuity of the patterns at a seam as if the seam

did not exist. A “patterned cylinder” in the context of this disclosure can refer to a closed band in the general shape of a belt having a pattern on one surface. The subset of a belt having circular symmetry is herein referred to as a “drum”.

General Considerations

[0035] In the most general terms, techniques for producing patterning tools according to the present disclosure include (i) the formation of discrete patterning tools having a three-dimensional relief pattern from one or more discrete elements (e.g., flat or non-flat), such as shown in FIGS. 1A-1B, and (ii) formation of continuous or quasi-continuous (e.g., cylindrically-shaped) tools from such elements, e.g., tool 6 in FIG. 1B and tool 210 in FIG. 2B.

[0036] An original relief pattern or template (herein referred to as the “master” pattern), can be used to form a first generation copy, e.g., as shown and described for FIG. 4, which depicts a conversion of a strip of patterns (“original”) into a single tool, where the original can be a selected material such as a metal, polymer, silicon, glass, photoresist, etc., and the tool (copy) can be a selected material such as metal or polymer.

[0037] A first generation copy can in turn can be used to form a second-generation copy. A third-generation copy (or subsequent-generation) can be made from the second-generation copy, etc., where each successive tool generation has the inverse pattern relative to the previous generation (FIGS. 1A-1B). In the optical disc and related fields, such tool generations are often called “fathers”, “mothers”, “sons”, etc., and the overall replication process and elements for a pattern are similarly referred to collectively as a “family tree.” FIG. 1A depicts a schematic of process flow for drum formation and replication showing interconversion (e.g., use for making a complimentary pattern) between internal and external patterns. As shown in FIG. 1B, a patterning forming process can begin with an external master pattern (1) or internal master pattern (3).

[0038] Methods, techniques, apparatus, and systems according to the present disclosure can include one or more of the following: the formation and use of multiple copies and multiple generations of an cylindrical pattern, the precise and accurate preparation of the edges of the individual pattern elements to enhance the combination thereof to form an extended pattern having seams with minimal artifacts, and the treatment of pattern elements and tools to enhance release of replicated parts and protect the patterned surfaces.

Master Pattern Creation

[0039] An original discrete pattern ("master") can be formed by any of a number of suitable techniques, including lithography, holography, direct e-beam or laser writing, ablation, embossing, etc. For example, the master pattern may consist of a substrate containing a layer with a component sensitive to actinic radiation, such as a photoresist typically used in optical or e-beam lithography (e.g., made by Shipley Company, etc.) and which can be positive or negative working. The resist can be coated on a silicon or other semiconductor wafer, or glass, quartz, polymer or other such substrate. The photoresist layer is patterned by standard techniques (e.g., exposure, development, post-processing, etc.) and the resulting relief pattern may be used as an etch mask to transfer the pattern to an underlying surface (silicon, glass, etc) through the use of a process such as plasma etching, or the pattern may be used as a template for making a next-generation copy relief copy, etc.

[0040] In another example, the pattern-forming layer can be an ablative material, such as for example, a polymer, dye polymer, or metal or alloy (e.g., Bi, Te or a Te alloy, etc.) or other suitable material that can be vaporized or physically deformed by the action of the incident radiation (laser, e-beam, particle beam, etc.). In a further example, the pattern-forming layer could consist of a soft polymeric or metallic material that can be deformed by the action of a precision stylus (atomic force microscopy - AFM, etc.) or suitable cutting tool. The pattern can be formed by

processes such as graphic art or ink-jet printing, where the relief pattern is built up by the addition of material ("additive" processes). Other suitable techniques for forming relief patterns according to the present disclosure can include but are not limited to thermal embossing, chemical embossing, imprint lithography, self-assembly, etc.

Creation of Multiple Pattern Copies and Generations

[0041] FIGS. 1A-1B illustrate systems, apparatus, and processes by which curved or cylindrical tools may be made, and include depiction of the formation of one or more flexible versions or generations of an original (flat) pattern. FIG. 1A depicts a schematic view of apparatus and related process flow for forming metal or polymer replica copies from an original surface relief pattern or from one another

[0042] FIG. 1B depicts a schematic view of apparatus and related process flow for drum formation and replication showing interconversion between internal and external patterns, where the process can begin with external master pattern or internal master pattern;

[0043] It is thus very useful to be able to make multiple, precise copies of an original pattern for the formation of cylindrical tools. Utilizing replicas of an original pattern offers several advantages, such as in cases where the original pattern is fragile or supported on a fragile or inflexible substrate (photoresist, glass, Si wafer, etc.), or when the original has the inverse symmetry ("mirror image") of the desired pattern, or when multiple identical copies are required (such as to form an extended tool), etc.

[0044] FIG. 10 depicts a continuous part after separation from combined fixtures such as shown in FIGS. 8-9. This can be used as direct tool, or as "mold" for subsequent tool. Note offsets in long edges are exaggerated to show affect of

precision alignment. These edges are non-critical but can optionally be trimmed straight.

[0045] A number of techniques for making precise copies of relief patterns can be utilized in accordance with the present disclosure, including the use of radiation curable polymeric materials (UV, e-beam, thermal), chemically/thermally curable materials (epoxies, silicones, anaerobics, etc.). Holographic techniques may be used to make copies, including techniques as available by Holographix LLC, etc). Another technique by which patterns may be accurately replicated is that of metal plating, such as by Ni electroforming or electroless deposition. Other suitable techniques, including chemical vapor deposition (CVD), may be used. During the 'parting' or separating process following replication, surface passivation, release coatings, and/or other means known to the art are often used to minimize damage to the original and replica parts.

[0046] The above techniques, as well as others, may be usefully employed in the formation of cylindrical patterning tools, in accordance with the present disclosure.

Precision Edge Preparation and Alignment/Registration of Patterns

[0047] It is a method of the present disclosure that the pattern elements used to form the patterning tool or replicas thereof have edges that are very uniformly and precisely cut and finished as a means of producing tools that are "near-seamless" (i.e., have seams that are minimally disruptive to the embossing/imprinting process for which they are used). The specific benefits of tools with such seams include higher material yields (less non-patterned "waste"/out-of-spec" material at or near the seams, reduction of contamination of "good" pattern areas by waste material generated at seams, fewer artifacts to cause "print-through", "blocking", or out-of-roundness in manufactured rolls, etc.), and extending tool life (reduced contamination of tool from seam-generated artifacts, less drum/roller "bounce" at

seams at higher speeds or nip pressures which interfere with efficient roll-to-roll machine operations, etc.).

[0048] Patterning applications frequently require alignment or registration of pattern features from one element to the next in order to produce extended or continuous patterns. Several techniques can be used to facilitate this requirement, such as: incorporation of specific features in the master pattern, use of characteristic elements intrinsic to the pattern itself, addition of fiducial (reference) elements to the pattern at a subsequent stage of the tool replication process, etc. Such alignment/registration features can take the form of guide patterns, rulers, reticle patterns, moiré patterns, diffractive patterns, etc., which can be used to optically or electronically guide a processing operation (diamond cutting, laser cutting, EDM wire burning, milling, grinding, shearing, water jet cutting, etc.) to produce a well-formed edge.

Joining Pattern Elements with Minimum Disruption

[0049] Techniques for joining individual elements described in the present disclosure can fall into two general categories: physically connecting by welding or adhesive bonding or other such means, and “dry fitting” by bring parts into intimate contact without bonding. Each approach offers specific benefits for specific applications.

Welding/Bonding

[0050] Techniques such as welding and bonding can be used to physically connect individual elements to form a strip, or closed form such as a belt or drum. In the case of metal parts, conventional welding generally results in a significant amount of damage near the weld caused by the typical large area that is heated during the process.

[0051] FIG 2A depicts a fixture for improving surface flatness by minimizing effects of thickness variation at edges of abutted parts. Patterned surfaces are protected with mask layer and loaded against reference surface from back side using compliant member (screws, springs, elastomer, etc.) prior to welding or bonding. Precision laser micro welding may be utilized according to the present disclosure to butt-weld parts having precisely finished edges, e.g., as depicted in FIG. 2B. FIG. 2B is a schematic view depicting the joining of metal elements by laser welding to form externally patterned cylinder. Each element is cut using marks embedded in pattern and all are then aligned to flat reference surface for welding to eliminate taper in finished drum. Laser micro welding using commercially available equipment, such as such as suitable Nd:YAG lasers, is capable of producing a very narrow weld line (commensurate with the laser spot size) with minimal material deformation beyond the joint, due to the ability of the laser to be focused to a very small spot and to utilize short duration pulses to minimize thermal damage. Preparation and cutting of the edges (in registration with the pattern, if necessary) of the individual parts is shown in FIGS. 5-6.

[0052] Other physical joining techniques include e-beam welding, adhesive bonding, solvent welding, etc. It should be noted that because butt-joining primarily uses the generally restricted surface area of the two edges being joined, reinforcement of the seams by adhesive bonding or soldering, etc., of a support strip to the underside of the part may be useful in extending the lifetime of such seams, particularly in applications where high loading forces or constant flexing may weaken a joint. Polymer parts can be welded using solvent, epoxies, UV or e-beam cured adhesives or thermal curing and may also use backside reinforcement techniques. Subsequent mounting, discussed below, of such reinforced joints may require compensation of the mounting part in the form of shallow trenches, etc., to enable the seam to lie flat on its underside support.

[0053] It is also a feature of the present disclosure to improve the surface flatness at the seam by the reduction or elimination of step height differences resulting from thickness variations of the individual parts. Polymer films commonly exhibit thickness (gauge) variations as a result of non-uniformities in the extrusion and film stretching processes, among other things, by which they are made. In electro-metal and electroless metal depositions, thickness variations result from electrical field or surface nucleation non-uniformities and fluctuations. The resultant thickness difference between butted parts is minimized or eliminated in this disclosure by clamping the elements with the patterned faces (suitably protected by an overcoat film or mask) against a flat (reference) surface during the joining operation using a compliant member, where force can be applied to the back surface of the parts by use of springs or elastomeric components, etc. (FIG. 2A). If alignment of the pattern across the parts is also required, the reference flat can be a transparent material (glass, etc.). By these techniques, the critical patterned surfaces are in the same plane, and any mismatch in thickness between the pieces being joined occurs as a step on the inside of the bond or weld. The mounting of a pattern cylinder with steps on its inner surface can be compensated for by use of a compliant (elastomeric layer, or epoxy/adhesive) layer or fill between the inner pattern surface and an inner support member (e.g., as compared with FIGS. 16A-16B).

Dry Fitting

[0054] Various techniques according to the present disclosure can be used for the formation of improved seams with minimum distortion or artifacts. Because melting of edge material (in the case of welding) or addition of material (in the case of adhesive bonding) is required to form a seam, in some situations there may be some area near the seam in which the pattern is obliterated, with the formation of a trench or ridge. Exemplary embodiments of the present disclosure, therefore, form and provide significantly improved seams between pattern elements by a process generally including: 1) the precise cutting and edge finishing of the individual

pattern elements (by one or more of edge preparation techniques described above), followed by 2) mechanical assembly ("dry fitting") of said individual parts, and with patterns in registration if required, followed by 3) the creation of a single continuous replica of the entire assembly of individual parts, using any of a number of methods known to the art.

[0055] Examples of embodiments of joining and/or preparing pattern segments according to the present disclosure are shown and described relative to FIGS. 5-9 herein, with reference characters shown. FIG. 5 depicts a first fixture for holding a pattern to be copied, without damage, while first precision cuts are made using embedded reference marks, for subsequent transfer of the pattern to a second fixture;

[0056] FIG. 6 depicts a second fixture for holding a pattern to be copied, without damage, while second precision cuts are made using embedded reference marks. These two edges can be and are preferably highly finished (by diamond turning, grinding, polishing, etc.) for precise fit to other pieces. Part is left on fixture during subsequent tool forming process.

[0057] FIG. 7 depicts a side view of a fixture similar to that of FIG. 6, showing pattern element, protective mask layer, and hold-down plate. Spring-loaded edge guide and hold-down plate keep part in place during edge finishing and subsequent tool forming process. "Stops" also serve to define/constrain the edges of the replicated part (either plated metal or polymer).

[0058] FIG. 8 depicts a configuration of a multiplicity of parts mounted in three fixtures similar to those of FIGS. 6-7, illustrating interconnection by precision slides. Patterns are aligned to one another using microscope/camera (not shown) and micrometer adjustments. Locking clamps are engaged after verification of alignment. Outer two edges may be finished with matching bevels for drum mounting.

[0059] FIG. 9 depicts a configuration similar to that of FIG. 8 with the addition of a "mask" to combined the fixtures to prevent/reduced metal plating or polymer replicating material from contacting fixture components. Outermost edges can have stops that give matching bevel if replicated strip is to be subsequently used in drum
5 fixture.

[0060] Suitable specific methods for making replica cylindrical tools by Ni electroforming, electroless deposition, radiation curing and other means are covered in detail in related Application No. 11/509,288, filed 24 August 2006.
10

[0061] For such exemplary embodiments, the edges of the individual components (e.g., pattern elements) can preferably be prepared in such a way as to minimize typical machining artifacts, such as burrs, nicks, warping, etc. which contribute to seam non-uniformities. This can be accomplished, as previously mentioned, by the
15 use of finishing techniques that produce very smooth cuts, including EDM wire burning, diamond cutting, precision grinding or shearing, water jet cutting, etc.). Post cut processing techniques, such as edge polishing, can be used to further improve the quality of the edge and hence the fit of the abutted parts.

20 [0062] Dry fitting techniques can benefit from the individual components being held securely during the formation of the continuous replica tool. Such holding of the pattern segments/elements can be accomplished by any of several techniques, including the use of mechanical (compression, etc.) clamping, vacuum or electrostatic hold-down, pressure sensitive adhesives (on the back but generally not
25 the edge of the part). In applications utilizing one or more magnetic metal substrates, magnetic clamping (including the use of strong Neodymium magnets, such a "N40" etc., with Ni tools) may be used. In addition, one or more of such holding techniques may be used simultaneously. For example, mechanical clamping may be used in conjunction with magnetic hold down, etc.

Continuous near-seamless drum tool

[0063] In a particular embodiment for forming a continuous near-seamless drum, the strip shown in FIG 10 (such as formed by techniques illustrated in FIGS. 5-9) is inserted (pattern facing inward) into an expanded two-piece drum shell fixture. See, e.g., FIG 11, which FIG. 11 depicts a pattern strip mounted in a two-piece shell fixture, with the pattern facing radially inward. Inner diameter of shell machined to match outer diameter of pattern strip after insertion. Edges of strip can be formed with matching bevel for precision fit.

[0064] By drawing the shell segments together, the strip is held in contact with the inner wall of the shell, and the strip edges in contact with each other, by compressive forces. It is a method of this disclosure that the length of the flat strip (e.g., as determined by the length of the fixture in FIG. 9) be such that when the strip element is inserted into the drum fixture and the drum fixture is closed, the outside diameter of the rolled strip and the inner diameter of the closed shell are essentially the same, thus the strip forms a virtually uninterrupted (near-seamless) cylinder, and subsequent tools made from it have likewise the same property.

[0065] For facilitation of the matching or alignment of the edges of the strip match up optimally within the shell fixture, the proper bevel angle formed by the butted ends of the strip when inserted into the shell is used in the flat fixture's end stops (FIG. 9) such that, when the strip is secured within the shell, a very precise near-invisible match is created. Replication of this "dry fitted" joint results in a further improved near-seamless drum tool.

[0066] FIG. 12 depicts an alternative embodiment of a fixture for drum tool formation in accordance with the present disclosure. Pattern part is mounted in curved semi-cylindrical fixture (after first 2 cuts have been made using 1st fixture, see e.g. Fig. 5). End stops are used to ensure edges will be cut perpendicular to first cut edge, and part is clamped in place. Excess part extending from fixture is trimmed

flush to shell using precision cutting techniques (diamond cutting, grinding, EDM, polishing, etc.).

[0067] As shown in FIG. 12, in exemplary embodiments the flat fixture shown in FIG. 6 can be replaced with a curved fixture. Once alignment is completed and the halves clamped securely, the curved clamp (FIG. 12) is extracted (clamping posts are located outside of the "active" pattern area), the protective mask is removed, and the fixture is ready for the replication process.

[0068] FIG. 13 depicts an alternate embodiment of a two-piece drum forming fixture including two assembled semi-cylindrical shell halves and pattern elements. Precision dovetail slides allow halves to move to allow pattern alignment and subsequent locking of fixtures in place (microscope camera optics and adjustment micrometer screws not shown).

[0069] Two such identical shell halves shown in FIG. 13 can be connected using dovetail slides or the like that allow, through the use of a micrometer screw or the like, one half to slide with respect to the other, thereby enabling alignment (with the use of proper optics) of the inner patterns.

[0070] The previously mentioned embodiment can be extended by the use of a shell with three segments or more segments as shown in FIGS. 14-15. FIG. 14 depicts a cylinder shell component configured for use in a three-piece drum forming fixture. By extension of this technique, drum shell fixture comprising any convenient number of elements can be used. FIG. 15 depicts an expanded and disassembled configuration of a three-piece shell according to an embodiment of the present disclosure. The use of three or more segments may be particularly useful for large drums where it may not be practical to form long strips, or where a multiplicity of patterns is required.

[0071] Aspects of the present disclosure can provide for the ready disassembly of a multi-part shell to extract the replicated tool. Similarly, an individual element that is damaged may be replaced without the need to replace the others.

[0072] In another embodiment, the continuous strip pattern formed in FIGS. 8-10 can be formed into a cylinder by joining of the ends to form a continuous cylinder by means of laser welding or other bonding method mentioned previously. This method offers a further improvement over the use laser welding or adhesive bonding to join each and every joint by the reduction the number of welds/bonds to one, which in some cases can be designed to correspond to a natural "break" in a pattern (e.g., separating large video displays or circuits comprised of multiple "near-seamless" joints by a larger laser/bonded joint).

Step-and-Repeat, Mosaic & Ganging

[0073] Embodiments of the present disclosure can function or operate to form a continuous strip substrate by the repeated replication and displacement ("step-and-repeat") of a smaller pattern onto the strip (FIG. 3), which can be formed into a continuous cylindrical tool by any of the means described herein. The replication operation can be accomplished by means known to the art, such as radiation, thermal, or chemical curing, etc. After an impression/replication is made, the tool is separated and the substrate is translated into a next position on the substrate. Precise alignment of pattern features (i.e., minimization of "stitching" errors) from one replica to the next is achieved by use of alignment marks embedded in the tool and precision optical and positioning equipment, e.g., as commercially available. By changing the master tool during the step-and-repeat process, a substrate having a multiplicity of different patterns ("mosaic") can be formed.

[0074] In another embodiment, the single strip element formed by the above means, or a multiplicity of individual elements that has been "ganged" (butted or joined by any of the methods of this disclosure) can be used to form another ("mirror

image”) continuous single strip element (FIG 4), again by means known to the art of electroforming, electroless deposition, polymer replication or any of the copying methods referred to in this disclosure.

[0075] Embodiments according to the present disclosure can function or be utilized to form a near-seamless pattern on the outer (or inner) surface of a cylindrical by the transfer of a complementary pattern (by any of the replicating/imprinting methods known to the art, such as thermal embossing, etc.) from a patterned cylinder of larger diameter (e.g., as shown for FIG. 17 described in further detail *infra*).

[0076] For patterning an external drum, the imprinting (transferring) “cylinder” can also be a sheet whose length is greater than the circumference of the support drum. Having a smaller circumference, the smaller drum will complete one revolution before the larger imprinting drum, and the imprinting drum is withdrawn as the smaller drum completes its single revolution.

Supporting Cylinder Tool

[0077] The cylindrical tools made by any of the methods of this disclosure can be mounted in a roll processing machine either directly (with no additional support) or with the use of an inner support member, for example, as described in one or more of the applications referenced in the Related Applications section, *supra*. Plated metal drums (e.g., Ni electroforms, etc.), typically 0.008-0.012 inches (8-12 mils) thick, being fairly strong, can be mounted directly, which offers the benefit of potentially quick machine insertion and removal. Metal drums and polymer tools can also be attached to an inner sleeve for additional support.

[0078] Embodiments of the present disclosure can function to form an improved mounting support for cylindrical tools by using a metal (or glass, ceramic, fiber or polymer) inner sleeve whose outer surface is coated by an elastomeric (compression) layer (as shown FIG. 16A). FIG. 16A depicts a schematic of process for separating an

inner drum tool from an outer "mold" inside which the inner tool can be formed. Inner part is cooled by circulation of chilled fluid (or other cooling technique) while outer part is heated. Differential thermal expansion/contraction allows the inner part to be withdrawn from the outer part without damage.

[0079] The outer diameter of this element is slightly larger than the inner diameter of the drum pattern tool, such that the simultaneous heating of the tool and/or cooling of the elastomer-coated sleeve will allow the cylindrical tool to fit over the sleeve, and be removed or attached to the sleeve as desired based on the controlled differential movement between the two parts.

[0080] In embodiments similar to that of FIG. 16A, upon return to room temperature, an interference fit is formed, which can allow securing/fixing of the tool to the sleeve. The elastomeric layer can be used to impart some flexibility to the drum tool, which is useful in pattern replication. The amount of flexibility can be broadly controlled by the durometer and thickness of the elastomeric layer. The compression layer can also be useful in compensating for step-height differences resulting from part thickness variations, as discussed above. In cases in which inner support elements (internal strips, et.) are used in joining the pattern elements, grooves may be cut into the elastomer or sleeve to accommodate the support strip.

[0081] FIG. 16B illustrated another technique for attaching a cylindrical tool to an inner support (sleeve). FIG. 16B depicts a technique for attaching cylindrical pattern to support ("sleeve") in accordance with an embodiment of the present disclosure. The externally patterned cylinder (e.g., #4 in Fig 1b) may be left in the fixture in which it was formed and mounted in the centralizing fixture. An inner (support) sleeve is precisely located (by means of dowel pins or other fixtures) so that it is concentric to the outer fixture, and a top seal is put in place. By means of vacuum, a sealing adhesive (epoxy, silicone, low melting "Wood's" metal, etc.) is drawn into the space between the inner support sleeve and the inner surface of the patterned

cylinder. After curing, the outer shell is disassembled and the pattern tool bonded to the support sleeve is released for mounting into a roll embossing machine.

[0082] In FIG. 16B, the externally patterned cylinder 1602 (e.g., similar to #4 in FIG. 1B) is left in the fixture in which it was formed and the complete assembly mounted in the centralizing fixture. The inner support sleeve is precisely located (by means of dowel pins or other) such that it is concentric with the inner surface (tool) of the outer fixture, and a top seal is put in place. By means of vacuum, a sealing material (epoxy, silicone, low melting "Wood's" metal, etc.) is drawn into the space between the inner support sleeve and the inner surface of the patterned cylinder.

[0083] Embodiments similar to that of FIG. 16B can be useful to eliminate/minimize air bubbles or pockets that could compromise the integrity of the bond. After curing, the outer shell is disassembled and the bonded pattern tool released. It should be noted that an advantage of the gap filling with low melting point liquid metal is that it offers the ability of re-melting (and reuse) of the metal in order to separate the drum tool from the inner sleeve.

[0084] A further advantage of such an approach shown in FIG. 16B is that during the bonding process, the pattern tool surface is protected by the outer fixture in which it was formed and is not directly handled until the tool is mounted on its inner support and released from the outer fixture.

Mounting Patterning Tool in Machine

[0085] For use in roll-to-roll embossing/imprinting equipment, the patterning cylinder may be mounted (with or without inner support member, depending on the mounting technique) by any of several means known to the art, including by tension mounting (expansion arbor or air-bladder), mechanical fastening (end-bells or inner core chuck), elastomeric compression arbor, adhesive bonding, soldering, welding,

magnetic clamping, etc. FIGS. 16A-16B depicts exemplary embodiments, as described previously.

Tool Performance Enhancements

[0086] It is a method of this disclosure to improve the embossing performance and durability of patterning tools described herein by the addition of certain overcoats and treatments.

[0087] To improve embossing performance and minimize tool clogging and contamination, release layers such as silicones, fluorocarbons and other low-surface energy materials may be applied to the surface of the tool. Certain metals, including chrome and gold, can be applied to the tool surface by vacuum deposition or electro-/electroless plating to impart improved release characteristics to the tool. For metal tools (particularly Ni), Ni and PTFE can be co-deposited to form a very effective release coating. Chemical and physical treatments, including passivation and surface conversion (in which a relatively thin layer is formed on the tool surface, such as an oxide or dichromate) are known to improve tool release characteristics.

[0088] Embodiments of the present disclosure can function to increase the durability and/or damage resistance of patterning tools in order to improve their longevity in manufacturing environments. For polymeric and photoresist tools (and intermediate patterns), post-exposure processing, such as cross-linking by e-beam, UV, thermal, chemical means, can increase hardness and chemical resistance, including solvent resistance.

[0089] The durability of metal tools made by electroplating, electroless deposition, chemical vapor deposition, etc. can be increased by metallurgical means such as annealing or by the use of additives in the deposition process. For example, it is well known that the hardness of electroformed Ni may be increased by the addition of small amounts of phosphorus, manganese, vanadium, etc. to the plating solutions.

[0090] FIG. 17 depicts apparatus 1700 and corresponding motion as used for forming an externally patterned drum 1702 with a minimal seam, in accordance with a further embodiment of the present disclosure. Larger diameter drum 1704 (which may have large seam) having complementary pattern to that of desired tool is pressed into outer surface of deformable (polymer, etc.) surface of smaller diameter drum 1702. The drums are separated after completion of one revolution of small drum. Post processing is used to further harden the drum tool.

Cylindrical Tool Replication/ Replication Tree

[0091] Thus as described herein, embodiments of the present disclosure can function to enable the production of multiple copies of a cylindrical tool made from an original pattern. This offers a number of advantages in the manufacturing of material using such patterning tools, including reduced costs (replicas being substantially less expensive than originals) and faster tool production (e.g., replica tools in accordance with the present disclosure) thus requiring less time to create than originals.

[0092] The flow diagram by which multiple replica patterning cylinders can be produced, whether using seamed or seamless tool elements, is given in FIG. 1B. The "family tree" propagation process can start with either an external ("negative") pattern (#1) or an internal ("positive") pattern (#3), where 'positive' arbitrarily refers to the relief pattern of the tool being that required to form the finished "product" (embossing), and "negative" being the opposite. The internal pattern (#3) can be formed by the shell fixture methods described above (e.g., for FIG. 11, 13, and 15), or can be formed as a result of replication of the external drum (#1). From this point it is irrelevant whether the starting point was an external or internal pattern.

[0093] While certain embodiments have been described herein, it will be understood by one skilled in the art that the methods, systems, and apparatus of the present disclosure may be embodied in other specific forms without departing from

the spirit thereof. The embodiments described herein are accordingly to be considered in all respects as illustrative of the present disclosure and not restrictive.

THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A relief pattern replication tool comprising:

One or more discrete elements having desired relief patterns configured with one common seam between adjacent pairs of the elements, wherein each discrete element is rectangular and has a length and width, wherein individual features of corresponding relief patterns on adjacent elements are aligned across a common seam that is linear and traverses the entire length or width, respectively, of each element of adjacent pairs of elements, and wherein the relief patterns are three-dimensional relief patterns having desired features and are configured to be co-planar across the seam and within a desired height offset, wherein the desired features are configured for embossing.

2. A tool according to claim 1, configured and arranged as a closed-form pattern replication tool.
3. A tool according to claim 2, wherein the one or more discrete elements are configured as (a) a belt; (b) a cylinder, or (c) a drum.
4. A tool according to claim 3, wherein all of the one or more discrete elements forming the closed-form pattern replication tool are configured and arranged with aligned patterns across the seams.
5. A tool according to any one of claims 1 to 4, wherein the tool is made from metal or plastic.
6. A tool according to any one of claims 1 to 5, wherein the relief patterns are on internal surface of the tool.
7. A tool according to any one of claims 1 to 5, wherein the relief patterns are on external surface of the tool.

100A




FIG 1a Metal or polymer copies can be made directly from original pattern or from one another


100B

FIG 1b "Process flow" for drum creation/duplication (Step 1 for external or Step 3 for internal master drum). Internal and external parts (2 & 4) are separated by differential thermal expansion or shell separation.

200B




FIG 2a Fixturing individual pattern elements to eliminate effects of thickness variation

200B

208




FIG 2b Bonding individual pattern elements into a cylindrical external pattern tool

300





FIG 3 Schematic process for making a continuous (polymer) tool by step-and-repeat method

400

404

continuous strip tool ("copy") made from "original"



continuous pattern strip ("original")

402

FIG 4 Schematic process for making one continuous tool from another continuous strip tool

Fixture #1 (used for cuts 1
& 2)

500




FIG 5 Preparing flat pattern element for assembly (step 1). Clamping fixture for making "reference" cut (protective mask over pattern surface not shown)

Fixture #2 (used for cuts 3
& 4) 600




FIG 6 Preparing flat pattern element for assembly (step 2). Clamping fixture used for making precision ("cross-web") cuts flush with support plate (protective mask over pattern surface not shown).

Fixture #2/end view

700




FIG 7 End view of Fixture #2, showing edge clamps and metal plating (or molding) stops.




FIG 8 "Dry fitting" fixture for aligning individual flat elements (after finish cuts)

900

Combined fixtures ready for
copying




FIG 9 Stop masks for metal deposition (plating) or molding

1000

continuous part with aligned
patterns




FIG 10 Continuous tool (plated metal or polymer) made from assembled fixtures.
Can be externally mounted to cylindrical sleeve or internally mounted (pattern
facing inward) for subsequent tool replication or used to make subsequent tools.

1100




FIG 11 Two-piece drum forming fixture (shell) with single strip pattern (1 seam)

1200




FIG 12 Curved pattern mounting fixture. Pattern is mounted facing inward (polymer mask used to protect pattern surface), held in place with clamp, and excess pattern material cut flush (2-part cylinder shown)

1300




FIG 13 Two-piece drum forming fixture (shell) with two pattern elements

Drum Copying Fixture/version 3
(shown open) 1400




FIG 14 Three-piece drum forming fixture (shell) with three pattern elements


1500

FIG 15 Three-part drum assembly (clamping bolts not shown)

1600A




FIG 16a Mounting patterned cylinder: “shrink fitting” to elastomer-coated inner support sleeve using differential thermal expansion


1600B

FIG 16b Mounting fixture for bonding external patterning tool to inner centralizing sleeve


1700

FIG 17 Formation of externally-patterned cylinder by embossing with external tool

100A

original pattern

102

copies

104

Ni replica

106

polymer replica

Metal or polymer copies can be made directly from original pattern or from one another

