



US009696684B2

(12) **United States Patent**
Maeshima et al.

(10) **Patent No.:** **US 9,696,684 B2**

(45) **Date of Patent:** **Jul. 4, 2017**

(54) **PROCESS CARTRIDGE AND IMAGE FORMING APPARATUS**

(71) Applicant: **CANON KABUSHIKI KAISHA**,
Tokyo (JP)

(72) Inventors: **Hideki Maeshima**, Mishima (JP);
Kuniaki Hirukawa, Yokohama (JP);
Shuichi Gofuku, Numazu (JP);
Yoshihiro Mitsui, Numazu (JP)

(73) Assignee: **Canon Kabushiki Kaisha**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/357,175**

(22) Filed: **Nov. 21, 2016**

(65) **Prior Publication Data**

US 2017/0068210 A1 Mar. 9, 2017

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/737,680, filed on Jun. 12, 2015, now Pat. No. 9,519,264, which (Continued)

(30) **Foreign Application Priority Data**

Dec. 14, 2012 (JP) 2012-273204

(51) **Int. Cl.**
G03G 21/18 (2006.01)

(52) **U.S. Cl.**
CPC **G03G 21/1803** (2013.01)

(58) **Field of Classification Search**
CPC G03G 21/1803; G03G 21/1825; G03G 21/185; G03G 21/1857

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,583,630 A 12/1996 Kimura et al.
6,947,686 B2 9/2005 Kawai et al.
(Continued)

FOREIGN PATENT DOCUMENTS

JP H09-325586 A 12/1997
JP H10-333409 A 12/1998
(Continued)

OTHER PUBLICATIONS

International Search Report for International Patent Application No. PCT/JP2013/084174.

(Continued)



Primary Examiner — Francis Gray

(74) *Attorney, Agent, or Firm* — Fitzpatrick, Cella, Harper & Scinto

(57) **ABSTRACT**

A process cartridge includes a photosensitive drum; a developing roller; a developer supplying roller, provided in contact with the developing roller; a driving force receiving portion provided at a shaft end of the supplying roller; a first driving force transmitting portion; a second driving force transmitting portion; flexible sheets provided adjacent to an engaging portion between the first portion and the second portion to intermittently contact the second portion with rotation of the second portion, wherein a rotational direction of the roller is opposite to that of the roller, and a peripheral speed of the roller is larger than that of the roller.

2 Claims, 24 Drawing Sheets



Related U.S. Application Data

is a continuation of application No. PCT/JP2013/084174, filed on Dec. 13, 2013.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,968,142	B2	11/2005	Arimitsu et al.	
6,980,758	B2	12/2005	Murayama et al.	
7,046,942	B2	5/2006	Arimitsu et al.	
7,072,594	B2	7/2006	Hoshi et al.	
7,072,603	B2	7/2006	Tsuzuki et al.	
7,088,939	B2	8/2006	Maeshima et al.	
7,127,194	B2	10/2006	Hoshi et al.	
7,158,735	B2	1/2007	Murayama et al.	
7,162,181	B2	1/2007	Maeshima et al.	
7,212,773	B2	5/2007	Sudo	
7,340,197	B2	3/2008	Murayama et al.	
7,349,649	B2	3/2008	Hoshi et al.	
7,813,671	B2	10/2010	Nittani et al.	
8,213,828	B2	7/2012	Murayama et al.	
8,369,743	B2	2/2013	Maeshima et al.	
8,565,639	B2	10/2013	Nittani et al.	
8,583,006	B2	11/2013	Murayama et al.	
8,688,003	B2	4/2014	Maeshima et al.	
9,063,501	B2	6/2015	Hirukawa et al.	
2003/0156848	A1*	8/2003	Kawai	G03G 21/1825 399/27
2003/0219276	A1*	11/2003	Sato	G03G 15/0815 399/103
2008/0247784	A1	10/2008	Kakuta et al.	
2008/0298847	A1	12/2008	Inoue et al.	
2009/0169255	A1*	7/2009	Sato	G03G 15/0808 399/119
2010/0303503	A1	12/2010	Woo	
2011/0158704	A1*	6/2011	Takagi	G03G 15/0808 399/279
2011/0222916	A1	9/2011	Sato	
2011/0280621	A1	11/2011	Suzuki et al.	
2012/0014730	A1	1/2012	Yoshizawa	

2012/0195634	A1*	8/2012	Kuriki	G03G 15/0818 399/281
2012/0237266	A1	9/2012	Miyazawa et al.	
2013/0108314	A1*	5/2013	Ito	G03G 15/0817 399/103
2013/0243498	A1	9/2013	Taniguchi et al.	
2013/0287450	A1*	10/2013	Hayashi	G03G 15/0808 399/281
2013/0308978	A1	11/2013	Nittani et al.	
2013/0330102	A1*	12/2013	Kato	G03G 15/0808 399/119
2014/0169829	A1	6/2014	Maeshima et al.	
2014/0178097	A1	6/2014	Maeshima et al.	
2015/0125166	A1	5/2015	Matsukawa et al.	
2015/0277370	A1	10/2015	Maeshima et al.	
2016/0018784	A1	1/2016	Maeshima et al.	

FOREIGN PATENT DOCUMENTS

JP	2003-084571	A	3/2003
JP	2005-114159	A	4/2005
JP	2006-208689	A	8/2006
JP	2008-170951	A	7/2008
JP	2009-162906	A	7/2009
JP	2010-197479	A	9/2010
JP	2011-232498	A	11/2011
JP	2011-257653	A	12/2011
RU	2 367 016	C2	9/2009

OTHER PUBLICATIONS

Examination Report in Canadian Patent Application No. 2,894,397, mailed May 25, 2016.
 Official Communication in European Patent Application No. 13862540.5, dated Jun. 17, 2016.
 Sep. 8, 2016 Notice of Allowance in Russian Patent Application No. 2015128304 (with English translation).
 Apr. 28, 2017 Office Action in Canadian Patent Application No. 2,894,397.

* cited by examiner




Fig. 1




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11





Fig. 12






Fig. 14




Fig. 15




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24

RANK
 A : GOOD
 B : TOLERABLE RANGE

	PERIPHERAL SPEED DIFFERENCE							
	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9
GHOST IMAGE DUE TO INSUFFICIENT PEELING	B	A	A	A	A	A	A	A
LATERAL STRIPE	A	A	A	A	A	A	A	B
POWER CONSUMPTION	S	←—————→						L

Fig. 25




Fig. 26




Fig. 27




Fig. 28

PROCESS CARTRIDGE AND IMAGE FORMING APPARATUS

TECHNICAL FIELD

The present invention relates to a process cartridge detachably mountable to an image forming apparatus and an image forming apparatus including the process cartridge. The image forming apparatus forms an image on a recording material using an image forming process. Examples of the image forming apparatus include a printer, a copying machine, a facsimile machine, or word processor and a multi-function machine of these machines.

BACKGROUND ART

Conventionally, in an image forming apparatus using an electrophotographic image forming process, a photosensitive drum and process parts actable on the photosensitive drum are unfixed into a cartridge. Further, a process cartridge type in which this cartridge is detachably mountable to an apparatus main assembly of the image forming apparatus is employed.

According to this process cartridge type, maintenance of the image forming apparatus can be performed by a user himself (herself). As a result, an operability can be improved remarkably and the process cartridge type is widely used in image forming apparatuses.

In a full-color electrophotographic image forming apparatus using a transfer belt (intermediary transfer belt), a constitution in which a plurality of process cartridges are arranged below the transfer belt is used. This is because in the case of a constitution in which a print is discharged onto an upper surface of the image forming apparatus, by disposing the process cartridges below the transfer belt, a first print time can be shortened. As a process cartridge corresponding to this constitution, a constitution in which a developing chamber is disposed at an upper portion close to the transfer belt and a developer is scooped up, to the developing chamber, from a developer accommodating chamber disposed below the developing chamber is used (Japanese Laid-Open Patent Application 2008-170951).

In this process cartridge, by providing a stirring member in the developing chamber, circulation of the developer in the developing chamber is improved, so that the developer is efficiently supplied to the developing roller above the developing chamber to reduce an amount of a residual developer.

However, in the constitution of Japanese Laid-Open Patent Application 2008-170951, there was a need to provide the stirring member in the developing chamber in a side below a contact portion between a developing roller and a developer supplying roller in the developing chamber. Therefore, the developer supplying roller for supplying the developer to the developing roller is rotated in a rotational direction opposite to rotational direction of the developing roller, so that circulation of the developer is made equivalent to or more than a conventional level without providing the stirring member in the developing chamber, and a supplying property of the developer from the developer supplying roller to the developing roller can be satisfied. According to this constitution, a space conventionally ensured for disposing the stirring member can be filled, and therefore a residual of the developer can be further suppressed.

The present invention is a further development of the prior art structure.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention is to provide a process cartridge and an image forming apparatus in which in a constitution that a developer is scooped up from a developer accommodating chamber, provided below a developing chamber, to the developing chamber above the developer accommodating chamber, it is possible to realize reduction of a residual developer while reducing the number of parts.

According to the present invention, there is provided process cartridge comprising: (i) a photosensitive drum; (ii) a rotatable developing roller for developing an electrostatic latent image formed on the photosensitive drum; (iii) a developer supplying roller, provided in contact with the developing roller, for supplying a developer to the developing roller; (iv) a driving force receiving portion for receiving a driving force, wherein the driving force receiving portion is provided at a shaft end portion of the developer supplying roller and is movable in a direction crossing a shaft of the developer supplying roller; (v) a first driving force transmitting portion for transmitting the driving force, received by the driving force receiving portion, to the developing roller, wherein the first driving force transmitting portion is provided on the developer supplying roller; and (vi) a second driving force transmitting portion, provided on the developing roller, for transmitting the driving force by engaging with the driving force transmitting portion. A rotational direction of the developing roller is an opposite direction to a rotational direction of the developer supplying roller, and a surface speed of the developer supplying roller is larger than a surface speed of the developing roller.

Further, according to the present invention, there is provided an image forming apparatus including a main assembly and a process cartridge, comprising: (i) the main assembly includes (i-i) a driving portion; and (ii) the process cartridge detachably mountable to the image forming apparatus includes: (ii-i) a photosensitive drum; (ii-ii) a developer supplying roller, provided in contact with a developing roller, for supplying a developer to the developing roller; (ii-iii) a developer supplying roller, provided in contact with the developing roller, for supplying the developer to the developing roller; (ii-iv) a driving force receiving portion for receiving a driving force by being connected with the driving portion, wherein the driving force receiving portion is provided at a shaft end portion of the developer supplying roller and is movable in a direction crossing a shaft of the developer supplying roller; (ii-v) a first driving force transmitting portion for transmitting the driving force, received by the driving force receiving portion, to the developing roller, wherein the first driving force transmitting portion is provided on the developer supplying roller; and (ii-vi) a second driving force transmitting portion, provided on the developing roller, for transmitting the driving force from the first driving force transmitting portion to the developing roller by engaging with the driving force transmitting portion. A rotational direction of the developing roller is an opposite direction to a rotational direction of the developer supplying roller, and a surface speed of the developer supplying roller is larger than a surface speed of the developing roller.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration showing a drive inputting portion and a driving system of a developing unit in an embodiment of the present invention.

3

FIG. 2 is a principal sectional view of an image forming apparatus in the embodiment of the present invention.

FIG. 3 is a principal sectional view of a process cartridge in the embodiment of the present invention.

FIG. 4 is a general perspective view of the process cartridge in the embodiment of the present invention.

FIG. 5 is a general perspective view of the developing unit in the embodiment of the present invention.

FIG. 6 is a schematic view of mounting of a process cartridge in the image forming apparatus in the embodiment of the present invention.

In FIG. 7, (a)-(d) are schematic views for illustrating an operation of mounting the process cartridge in an image forming apparatus main assembly in the embodiment of the present invention.

FIG. 8 is a perspective view showing a state in which the process cartridge is positioned to the image forming apparatus main assembly in the embodiment of the present invention.

FIG. 9 is a sectional view for illustrating a spacing operation of the developing unit in the embodiment of the present invention.

FIG. 10 is a sectional view for illustrating a contact operation of the developing unit in the embodiment of the present invention.

FIG. 11 is a perspective view before the process cartridge is mounted in the image forming apparatus main assembly in the embodiment of the present invention.

FIG. 12 is a perspective view of mounting of the process cartridge in the image forming apparatus main assembly in the embodiment of the present invention.

FIG. 13 includes schematic views in which an operation of mounting the process cartridge in the image forming apparatus main assembly is viewed from an apparatus main assembly front side in the embodiment of the present invention.

FIG. 14 includes schematic views in which the position of mounting the process cartridge in the image forming apparatus main assembly is viewed from an apparatus main assembly side surface side in the embodiment of the present invention.

FIG. 15 is a perspective view for illustrating a supporting constitution for a toner supplying roller and a developing roller in the embodiment of the present invention.

FIG. 16 is an exploded illustration of a shaft coupling member in the embodiment of the present invention.

FIG. 17 includes sectional illustrations of the shaft coupling member in the embodiment of the present invention.

FIG. 18 is a perspective view for illustrating the shaft coupling member in a developing unit state and a first main assembly driving member and a second main assembly driving member of the image forming apparatus main assembly in the embodiment of the present invention.

FIG. 19 is an illustration showing a constitution of a developing chamber in the embodiment of the present invention.

FIG. 20 is an illustration showing a driving gear train of the developing unit in the embodiment of the present invention.

FIG. 21 is an illustration showing minute deformation of a sponge portion in the embodiment of the present invention.

FIG. 22 is an illustration showing the case where a developing driving force is inputted onto a developing roller shaft.

FIG. 23 includes illustrations showing teeth of gears in a constitution in which the developing driving force is inputted onto the developing roller shaft.

4

FIG. 24 is an illustration showing the teeth of gears in the embodiment of the present invention.

FIG. 25 is a table showing a rank of a relationship between a peripheral speed difference and an image or the like in the embodiment of the present invention.

FIG. 26 is an illustration showing a comparison example in which a developing chamber toner feeding member is provided in a developing chamber.

FIG. 27 is an illustration showing flexible sheets adjacent to the developer roller gear in an embodiment of the present invention.

FIG. 28 is an illustration of a sectional view in which the gear portion of the developing idler gear is omitted.

EMBODIMENTS FOR CARRYING OUT THE PRESENT INVENTION

Hereinbelow, preferred embodiments of the present invention will be exemplarily and specifically described with reference to the drawings. However, dimensions, materials, shapes, relative arrangements and the like of constituent elements described in the following embodiments are appropriately changed depending on constitutions or various conditions of devices (apparatuses) to which the present invention is applied. Accordingly, the scope of the present invention is not limited thereto unless otherwise specified.

In the following, an image forming apparatus according to an embodiment of the present invention and a process cartridge used therein will be described in accordance with the drawings.

(General Structure of Image Forming Apparatus)

First, a general structure of an electrophotographic image forming apparatus (hereinafter referred to as an "image forming apparatus") 100 will be described using FIG. 2. As shown in FIG. 2, detachably mountable four process cartridges 70 (70Y, 70M, 70C, 70K) are detachably mounted by mounting members (unshown). Further, an upstream side of the process cartridge 70 with respect to a mounting direction to the image forming apparatus 100 is defined as a front (surface) side, and a downstream side of the process cartridge 70 with respect to the mounting direction is defined as a rear (surface) side. In FIG. 2, the respective process cartridges 70 are inclined and juxtaposed in an apparatus main assembly 100A with respect to a horizontal direction ht.

The process cartridge 70 includes electrophotographic photosensitive drums (hereinafter referred to as "photosensitive drums") 1 (1a, 1b, 1c, 1d), and at a periphery of the photosensitive drums 1, process means such as charging rollers 2 (2a, 2b, 2c, 2d), developing rollers 25 (25a, 25b, 25c, 25d), and cleaning members 6 (6a, 6b, 6c, 6d) are integrally provided.

The charging roller 2 electrically charges the surface of the photosensitive drum 1 uniformly, and the developing roller 25 develops a latent image, formed on the photosensitive drum 1, with a toner to visualize the latent image. The cleaning member 6 removes the toner remaining on the photosensitive drum 1 after a toner image formed on the photosensitive drum 1 is transferred onto a recording material (medium).

Further, below the process cartridges 70, a scanner unit 3 for forming the latent image on the photosensitive drums 1 by subjecting the photosensitive drums 1 to selective exposure to light on the basis of image information is provided.

At a lower portion of the apparatus main assembly 100A, a cassette 17 in which sheets of the recording material S are accommodated is mounted. Further, a recording material

5

feeding portion is provided so that the recording material S can be fed to an upper portion of the apparatus main assembly 100A by being passed through a secondary transfer roller 69 and a fixing portion 74. That is, a feeding roller 54 for separating and feeding the sheets of the recording material S in the cassette 17 in a one-by-one manner, a feeding roller pair 76 for feeding the fed recording material S, and a registration roller pair 55 for synchronizing the latent image formed on the photosensitive drum 1 with the recording material S are provided.

Further, above the process cartridges 70 (70Y, 70M, 70C, 70K), an intermediary transfer unit 5 as an intermediary transfer means onto which the toner image formed on each of the photosensitive drums 1 (1a, 1b, 1c, 1d) is to be transferred is provided. The intermediary transfer unit 5 includes a driving roller 56, a follower roller 57, primary transfer rollers 58 (58a, 58b, 58c, 58d) at positions opposing the photosensitive drums 1 for the respective colors, and an opposite roller 59 at a position opposing the secondary transfer roller 69 are provided. Around these rollers, a transfer belt (intermediary transfer belt) 9 is extended and stretched.

Further, the transfer belt 9 is circulated and moved so as to oppose and be contacted to all of the photosensitive drums 1, so that primary transfer (of the toner images) from the photosensitive drums 1 onto the transfer belt 9 is made by applying a voltage to the primary transfer rollers 58 (58a, 58b, 58c, 58d). Then, by voltage application to the secondary transfer roller 69 and the opposite roller 59 disposed inside the transfer belt 9, the toner images are transferred from the transfer belt 9 onto the recording material S.

During image formation, while rotating each of the photosensitive drums 1, the photosensitive drum 1 uniformly charged by the charging roller 2 is subjected to selective exposure to light emitted from the scanner unit 3. By this, an electrostatic latent image is formed on the photosensitive drum 1. The latent image is developed by the developing roller 25. By this, the toner images of the respective colors are formed on the photosensitive drums 1, respectively. In synchronism with this image formation, the registration roller pair 55 feeds the recording material S to a secondary transfer position where the secondary transfer roller 69 opposing the opposite roller 59 is contacted to the transfer belt 9.

Then, by applying a transfer bias voltage to the secondary transfer roller 69, the respective color toner images are secondary-transferred from the transfer belt 9 onto the recording material S. By this, a color image is formed on the recording material S. The recording material S on which the color image is formed is heated and pressed by the fixing portion 74, so that the toner images are fixed on the recording material S. Thereafter, the recording material S is discharged onto a discharge portion 75 by a (sheet-)discharging roller pair 72. The fixing portion 74 is disposed at an upper portion of the apparatus main assembly 100A. (Process Cartridge)

Next, the process cartridge 70 in this embodiment will be described with reference to FIGS. 3 to 5.

FIG. 3 is a principal sectional view of the process cartridge 70 in which the toner is accommodated. Incidentally, the process cartridge 70Y accommodating the toner of yellow, the process cartridge 70M accommodating the toner of magenta, the process cartridge 70C accommodating the toner of cyan, and the process cartridge 70K accommodating the toner of black have the same constitution.

The respective process cartridges 70 (70Y, 70M, 70C, 70K) include drum units 26 (26a, 26b, 26c, 26d) as a first

6

unit and developing units 4 (4a, 4b, 4c, 4d) as a second unit. The drum unit 26 includes the photosensitive drum 1 (1a, 1b, 1c, 1d), the charging roller 2 (2a, 2b, 2c, 2d) and the cleaning member 6 (6a, 6b, 6c, 6d). Further, the developing unit 4 includes the developing roller 25.

To a cleaning frame 27 of the drum unit 26, the photosensitive drum 1 is rotatably mounted via a front drum bearing 10 and a rear drum bearing 11. The photosensitive drum 1 is provided with a drum coupling 16 and a flange 19 at an end portion thereof.

On a circumferential surface of the photosensitive drum 1, as described above, the charging roller 2 and the cleaning member 6 are disposed. The cleaning member 6 is constituted by an elastic member formed with a rubber blade and a cleaning supporting member 8. A free end portion of the elastic member disposed in contact with the photosensitive drum 1 counter directionally to a rotational direction of the photosensitive drum 1. Further, a residual toner removed from the surface of the photosensitive drum 1 by the cleaning member 6 falls into a removed toner chamber 27a. Further, a receptor sheet 29 for preventing leakage of the removed toner in the removed toner chamber 27a is contacted to the photosensitive drum 1.

By transmitting a driving force of a main assembly driving motor (not shown) as a driving source to the drum unit 26, so that the photosensitive drum 1 is rotationally driven depending on an image forming operation. The charging roller 2 is rotatably mounted to the drum unit 26 via a charging roller bearing 28 and is urged against the photosensitive drum 1 by a charging roller urging member 46, thus being rotated by the rotation of the photosensitive drum 1.

The developing unit 4 includes the developing roller 26, rotating in contact with the photosensitive drum 1 in an arrow B direction, and a developing device frame 31 for supporting the developing roller 25. Further, the developing unit 4 is constituted by a developing chamber 31b in which the developing roller 25 is disposed and by a toner accommodating portion 31c, disposed below the developing chamber 31b with respect to the direction of gravity in a state in which the process cartridge is mounted in the image forming apparatus, as a developer accommodating container for accommodating the toner. These chambers (portions) are partitioned by a partition wall 31d. The toner accommodating portion 31 is positioned below the developing roller 25 and the developer supplying roller with respect to the direction of gravity. Further, the partition wall 31d is provided with an opening 31e through which the toner passes when the toner is fed from the toner accommodating portion 31c to the developing chamber 31b. The developing roller 25 is rotatably supported by the developing (device) frame 31 via a front developing (means) bearing 12 and a rear developing (means) bearing 13 provided in both sides of the developing device frame 31, respectively (FIG. 3).

Further, on a peripheral surface of the developing roller 25, a developer supplying roller 34 rotatable in contact with the developing roller 25 in an arrow E direction, and a developing blade 35 for regulating a toner layer on the developing roller 25 are provided.

The developer supplying roller 34 is constituted by a metal-made developer supplying roller shaft 34j and a sponge portion 34a which is an elastic portion for covering an outer peripheral surface of the shaft in an exposed state at end portions. The developer supplying roller 34 is disposed so that the sponge portion 34a is in contacted to the developing roller 25 with a predetermined penetration amount into the developing roller 25. Further, a leakage-out

preventing sheet **33** as a developing (means) contact sheet for preventing leakage-out of the toner from the developing frame **31** contacting the developing roller **25** is provided.

Further, in the toner accommodating portion **31c** in the developing frame **31**, a toner feeding member **36** which is a feeding means for feeding the toner into the developing chamber **31b** through the opening **31e** while stirring the toner accommodated in the toner accommodating chamber **31c** is provided.

As described above, the toner accommodating portion **31c** is provided below with respect to the direction of gravity, and therefore also the toner feeding member **36** is positioned below the developing chamber **31b** with respect to the direction of gravity. That is, the developing chamber **70** in this embodiment has a toner scooping-up constitution in which the toner is fed by the toner feeding member **36** against gravitation from the toner accommodating portion **31c** disposed at a lower portion with respect to the direction of gravity to the developing chamber **31b** disposed at an upper portion of the toner accommodating portion **31c** with respect to the direction of gravity.

FIG. **4** is a general perspective view of the process cartridge **70**. FIG. **5** is a general perspective view of the developing unit **4**. To the drum unit **26**, the developing unit **4** is rotatably mounted. A front supporting pin **14** and a rear supporting pin **15** which are press-fitted in the cleaning frame **27** are engaged with hang holes **12a** and **13a**, respectively, of the rear developing bearing **13**. As a result, the developing unit **4** is rotatably supported by the cleaning frame **27** with the front supporting pin **14** and the rear supporting pin **15** as rotation shafts.

Further, the cleaning frame **27** is provided with a front drum bearing **10** and a rear drum bearing **11** which rotatably support the photosensitive drum **1**. The rear drum bearing **11** supports a drum coupling **16** coupled to the photosensitive drum **1**. Further, the front drum bearing **10** supports the flange **19**. Here, the drum coupling **16** is a drum coupling member for transmitting a rotational driving force (first rotational driving force) from the apparatus main assembly **100A** to the photosensitive drum **1**.

The developing frame **31** is provided with the front and rear developing bearings **12** and **13** for rotatably supporting the developing roller **25**. Further, the developing unit **4** is constituted so as to be urged against the drum unit **26**, during image formation of the process cartridge **70**, by an urging spring **32** provided at each of ends of the developing frame **31**. By these urging spring **32**, an urging force for bringing the developing roller **25** into contact with the photosensitive drum **1** with, as rotation centers, the hang holes **12a** and **13a** of the front and rear developing bearings **12** and **13** is generated.

(Insertion and Mounting Constitution of Process Cartridge into Image Forming Apparatus Main Assembly)

In FIG. **6**, a constitution in which the process cartridge **70** is inserted into the image forming apparatus **100** will be described. In this embodiment, a constitution in which the process cartridges **70** (**70Y**, **70M**, **70C**, **70K**) are inserted through openings **101** (**101a**, **101b**, **101c**, **101d**) of the image forming apparatus **100** is a constitution in which the process cartridges **70** are inserted from the front side to the rear side in a direction (arrow F direction in the figure) parallel to an axial direction of the photosensitive drums **1** (**1a**, **1b**, **1c**, **1d**).

In this embodiment, with respect to an insertion direction of the process cartridge **70**, an upstream side is defined as a front side, and a downstream side is defined as a rear side. Further, in the image forming apparatus **100**, main assembly upper mounting guide portions **103** (**103a**, **103b**, **103c**,

103d) which are first main assembly guide portions are provided in an upper side. Further, in the image forming apparatus **100**, main assembly lower mounting guide portions **102** (**102a**, **102b**, **102c**, **102d**) which are second main assembly mounting guide portions are provided in a lower side. Each of the main assembly upper guide portions **103** and the main assembly lower guide portions **102** has a guide shape extending along an insertion direction F of each of the process cartridge **70**.

The process cartridge **70** is placed in a front side of the main assembly lower mounting guide portion **102** with respect to a mounting direction and then is moved in the insertion direction F along the main assembly upper and lower mounting guide portions **102** and **103**, thus being inserted into the image forming apparatus **100**.

An operation of mounting the process cartridge **70** into the apparatus main assembly **100A** will be described. FIG. **7(a)** is a schematic view for illustrating a state before mounting of the process cartridge **70** into the apparatus main assembly **100A**.

FIG. **7(b)** is a schematic view for illustrating a state during the mounting of the process cartridge **70** into the apparatus main assembly **100A**. The main assembly lower mounting guide portion **102** provided in the apparatus main assembly **100A** is provided with a main assembly(-side) pressing member **104** and a main assembly(-side) pressing spring **105** which press and position the process cartridge **70** against the apparatus main assembly. When the process cartridge **70** is mounted in the apparatus main assembly **100A**, a guide portion **27b** of the cleaning frame **27** runs on the main assembly pressing portion **104**, so that the process cartridge **70** moves in an upward direction. Then, the guide portion **27b** of the cleaning frame **27** is in a state in which the guide portion **27b** is spaced from a guide surface of the main assembly lower mounting guide portion **102**.

FIG. **7(c)** is a schematic view for illustrating a state in which the process cartridge **70** is mounted into the apparatus main assembly **100A** until the process cartridge **70** abuts against a rear(-side) plate **98**. In the state in which the guide portion **27b** of the cleaning frame **27** runs on the main assembly pressing member **104**, when the mounting of the process cartridge **70** is further continued, a longitudinal abutting portion provided on the rear drum bearing **11** contacts the rear plate **98** of the apparatus main assembly **100A**.

FIG. **7(d)** and FIG. **8** are schematic views for illustrating a state in which the process cartridge **70** is positioned relative to the apparatus main assembly **100A**. In a state of (c) of FIG. **7**, in interrelation with closing of a front door **96** of the apparatus main assembly **100A**, the main assembly lower mounting guide portion **102** including the main assembly pressing member **104** and the main assembly pressing spring **105** moves in the upward direction. With the movement, also the process cartridge **70** contacts a main assembly(-side) positioning portion **98a** of the rear plate **98** at a cartridge(-side) positioning portion **11a** provided at an upper portion of the rear drum bearing **11**.

Then, by the contact of the cartridge positioning portion **10a** provided at the upper portion of the rear drum bearing **10** with the main assembly positioning portion **97a** which is a main assembly(-side) positioning portion of a front plate **97**, the position of the process cartridge **70** relative to the apparatus main assembly **100A** is determined. Also in this state, the guide portion **27b** of the cleaning frame **27** is spaced from the guide surface of the main assembly lower mounting guide portion **102**, so that the process cartridge **70** is in a state in which the process cartridge **70** is pressed by

a spring force, of the main assembly pressing spring 105, received from the main assembly pressing member 104.

Further, the cleaning frame 27 is provided on a side surface thereof with a boss 27c as a rotation stopper for the process cartridge 70, and the boss 27c engages with a rotation preventing hole (portion) 98b provided in the rear plate 98. Thus, the process cartridge 70 is prevented from rotating in the apparatus main assembly 100A.

(Spacing Mechanism Between Photosensitive Drum and Developing Roller in Process Cartridge)

In the process cartridge 70 according to this embodiment, the photosensitive drum 1 and the developing roller 25 are capable of being contacted to and spaced from each other. Here, a spacing mechanism between the photosensitive drum 1 and the developing roller 25 will be described with reference to FIGS. 9 and 10.

In FIG. 9, the apparatus main assembly is provided with a spacing member 94 at a predetermined position with respect to a longitudinal direction of the process cartridge 70. In the developing unit 4 of the process cartridge 70, a spacing force receiving portion 31a of the developing frame 31 receives a force from the spacing member 94 moving in an arrow N direction, thus moving the developing roller 25 to a spaced position where the developing roller 25 is spaced from the photosensitive drum 1.

Further, as shown in FIG. 10, when the spacing member 94 moves in an arrow P direction away from the spacing force receiving portion 31a, the developing unit 4 is rotated in an arrow T direction about the holes 12a and 13a of the front and rear developing bearings 12 and 13 by the urging force of the urging springs 32 (FIG. 5) provided at the ends of the developing frame 31. Then, the developing unit 4 is moved to a contact position, so that the developing roller 25 and the photosensitive drum 1 are in contact with each other. At least during the image formation, the developing unit 4 is held at a contact position of FIG. 9. Then, at timing, set in advance, such as during stand-by other than during image formation, the developing unit 4 is held at the spaced position of FIG. 9. By that, an effect of suppressing the influence of deformation of the developing roller 25 on an image quality is obtained.

(Spacing Mechanism when Process Cartridge is Mounted)

A spacing mechanism when the process cartridge 70 is mounted in the apparatus main assembly 100A will be described using FIGS. 11 and 12.

When the process cartridge 70 is mounted in the apparatus main assembly 100A, the developing unit 4 is in the contact position, and the photosensitive drum 1 and the developing roller 25 are in contact with each other. At the time of completion of the mounting of the process cartridge 70 in the apparatus main assembly 100A and at the time of end of the image forming operation of the image forming apparatus 100, the developing unit 4 is in the spaced position, and the photosensitive drum 1 and the developing roller 25 are spaced from each other.

Therefore, when the process cartridge 70 is mounted in the apparatus main assembly 100A, there is a need to move the process cartridge 70 from the contact position to the spaced position, and a constitution thereof will be described using FIGS. 11-14. As shown in FIG. 11, the apparatus main assembly 100A is provided with an image forming apparatus opening 101 for permitting mounting of the process cartridge 70. Further, as shown in FIGS. 11 and 12, the apparatus main assembly 100A is provided with a spacing guide portion 93 contacting a spacing force receiving portion 31a provided on the developing unit 4 of the process cartridge 70.

As shown in (a) of FIG. 13 and (a) of FIG. 14, before the process cartridge 70 enters the apparatus main assembly 100A, the developing unit 4 is in the contact position, and the photosensitive drum 1 and the developing roller 25 are in contact with each other. Then, as shown in (b) of FIG. 13 and (b) of FIG. 14, when the process cartridge 70 is mounted into the apparatus main assembly 100A, first, the guide portion 27b provided integrally with the cleaning is mounted on the main assembly lower mounting guide portion 102 provided in the apparatus main assembly 100A. Then, the spacing force receiving portion 31a provided on the developing frame 31 contacts a chamfered portion 93a which is an inclined surface obliquely inclined relative to the spacing guide portion 93.

When the process cartridge 70 is caused to further enter the apparatus main assembly, as shown in (c) of FIG. 13 and (c) of FIG. 14, the developing unit 4 rotates in an arrow J direction about a rear supporting pin 15 as a rotation center. Then, the developing unit 4 moves in an arrow K direction to the spaced position. Then, when the process cartridge 70 is positioned in the apparatus main assembly 100A, as shown in (d) of FIG. 13 and (d) of FIG. 14, the spacing force receiving portion 31a is in a contact state with the spacing member 94 disposed downstream of the spacing guide portion 93 with respect to the mounting direction. At that time, the developing unit 4 is in the spaced position, so that the process cartridge 70 can be mounted in the apparatus main assembly 100A while keeping the developing roller 25 in the spaced state from the photosensitive drum 1.

(Constitution of Developer Supplying Roller Supporting and Developing (Means) Driving Force Inputting Portion in Process Cartridge)

Next, a constitution of a developing driving force inputting portion and a supporting constitution of the developer supplying roller 34 in the process cartridge 70 according to this embodiment will be described using FIGS. 15-18.

FIG. 15 is an illustration showing a longitudinal one end side (rear side) of a supporting portion for the developing roller 25 and the developer supplying roller 34. In FIG. 15, a developing roller shaft 25j of the developing roller 25 and a developer supplying roller shaft 34j of the developer supplying roller 34 are rotatably engaged with an inner peripheral surface of the rear developing bearing 13. Here, the supporting constitution in the longitudinal one end side of the developing roller 25 and the developer supplying roller 34 was described, but also in the other longitudinal one end side, similarly, the bearing portion is integrally provided with the bearing member, and the developing roller shaft 25j and the developer supplying roller shaft 34j are rotatably engaged in the other end side. Further, at the developing driving force inputting portion, an Oldham coupling 20 which is a shaft coupling member is used.

Using FIG. 16, a constitution of the Oldham coupling 20 will be described. Here, in order to describe the constitution of the Oldham coupling 20, the rear developing bearing 13 is not shown. As shown in FIG. 16, the Oldham coupling 20 is constituted by a follower-side engaging portion 21 which is a driven portion, an intermediary engaging portion which is an intermediary portion, and a driving-side engaging portion 23 which is a drive receiving portion.

The follower-side engaging portion 21 is fixed and mounted to an end portion (in one end side with respect to an axial direction) of the developer supplying roller shaft 34j. As a fixing method, there are a method in which connection is made by a spring pin or a parallel pin and a method in which as shown in FIG. 16, the developer supplying roller shaft 34j is provided with a cut portion 34k

11

at an end surface thereof and also a hole in the follower-side engaging portion 21 side is similarly shape and is engaged with the cut portion 34k.

The driving-side engaging portion 23 (first drive receiving portion) is a portion for receiving a driving force of a driving source of the main assembly. Further, in this embodiment, an H direction and an I direction are in a substantially perpendicular relationship. A shaft portion 23d of the driving-side engaging portion 23 is rotatably held in a hole 41d of a holding portion 41. Further, the driving-side engaging portion 23 is integrally formed with three projections 23c1, 23c2 and 23c3 engageable with a main assembly(-side) developing (means) coupling 91 (FIG. 18) which is a second main assembly(-side) drive transmitting member of the 100A described later.

This Oldham coupling 20 allows a deviation between an axis of the main assembly developing coupling 91 and an axis of the developer supplying roller 34, and transmits a rotational driving force (first rotational driving force) from the apparatus main assembly 100A to the developer supplying roller 34. Further, the Oldham coupling 20 is capable of transmitting a rotational driving force (second rotational driving force) from the apparatus main assembly 100A to the developer supplying roller 34 in a state in which the developing unit 4 is in the contact position and in the spaced position.

In FIG. 17, a constitution of the Oldham coupling 20 will be described in further detail using sectional views. FIG. 17(a) is a sectional view of the Oldham coupling 20 cut in an arrow H direction in FIG. 16, and FIG. 17(b) is a schematic view of the Oldham coupling 20 cut in an arrow I direction in FIG. 16. In (a) of FIG. 17, the follower-side engaging portion 21 is integrally provided with a rib 21a. The intermediary engaging portion 22 is provided with a groove 22a, and the rib 21a and the groove 22a are engaged with each other so as to be movable in the arrow H direction of FIG. 16. In (b) of FIG. 17, the driving-side engaging portion 23 is integrally provided with a rib 23b. The intermediary engaging portion 22 is provided with a groove 22b, and the rib 23b and the groove 22b are engaged with each other so as to be movable in the arrow I direction of FIG. 16. In this embodiment, the H direction and the I direction are in the substantially perpendicular relationship.

The intermediary engaging portion 22 engages with the follower-side engaging portion 21 and the driving-side engaging portion 23, and constitutes an intermediary portion for transmitting a driving force, inputted into the driving-side engaging portion 23, to the follower-side engaging portion 21, and is movable in a direction crossing the axial direction of the developer supplying roller 34 while maintaining engagement with each of the engaging portions 21 and 23.

FIG. 18 is an illustration showing a constitution including the coupling provided on the process cartridge 70 and the coupling provided in the apparatus main assembly 100A. At the end surface of the driving-side engaging portion 23 of the Oldham coupling 20 provided on the developing chamber 4, the three projections 23c1, 23c2 and 23c3 projecting in the axial direction are formed. Further, a centering boss 23a for being aligned with the axis (rotation center) of the main assembly developing coupling 91 projects in the axial direction from the end surface of the driving-side engaging portion 23.

The photosensitive drum 1 is provided, in one end side with respect to the axial direction, with a triangular prism drum coupling 16. A guide portion 41b of the holding portion 41 is movable, in a direction crossing the axial

12

direction of the developer supplying roller 34, along the groove 43a of the side cover 43 fixed on the developing unit with an unshown screw or the like. That is, the driving-side engaging portion 23 is movable in a direction (the direction crossing the axial direction of the developer supplying roller) crossing the developing unit 4.

In FIG. 18, the main assembly drum coupling 90 which is a first main assembly drive transmitting member for transmitting the drive of the apparatus main assembly 100A to the photosensitive drum 1 is provided with a hole 90a having a substantially triangular shape in cross section. The main assembly developing coupling 91 which is a second main assembly drive transmitting member for transmitting the rotational driving force (second rotational driving force) from the apparatus main assembly 100A to the developer supplying roller 34 is provided with three holes 91a1, 91a2 and 91a3.

The main assembly drum coupling 90 is urged in a direction of the process cartridge 70 by a drum pressing (urging) member 106 such as a compression spring. Further, the main assembly drum coupling 90 is movable in the axial direction of the photosensitive drum 1. Further, in the case where the drum coupling 16 and the hole 90a of the main assembly drum coupling 90 are out of phase and in contact with each other when the process cartridge 70 is mounted in the apparatus main assembly 100A, the main assembly drum coupling 90 is pushed by the drum coupling 16, thus being retracted. Then by rotation of the main assembly drum coupling 90, the drum coupling 16 and the hole 90a are engaged with each other, the rotational driving force is transmitted to the photosensitive drum 1.

Further, the main assembly developing coupling 91 is urged in the direction of the process cartridge 70 toward a direction parallel to the axial direction of the photosensitive drum 1 by a developing (means) pressing (urging) member 107 such as a compression spring. However, the main assembly developing coupling 91 has no play with respect to the direction crossing the axial direction and is provided in the apparatus main assembly 100A. That is, the main assembly developing coupling 91 not only rotates for transmitting the drive (driving force) but also in movable only in the axial direction.

When the driving-side engaging portion 23 and the main assembly developing coupling 91 are engaged with each other by causing the process cartridge 70 to enter the apparatus main assembly 100A, the projections 23c1-23c3 and the holes 91a1-91a3 are out of phase in some cases. In this case, free ends of the projections 23c1-23c3 contact portions other than the holes 91a1-91a3, so that the main assembly developing coupling 91 is retracted in the axial direction against an urging force of the developing pressing member 107. However, when the main assembly developing coupling 91 rotates and the projections 23c1-23c3 and the holes 91a1-91a3 are in phase, the main assembly developing coupling 91a advances by the urging force of the developing pressing member 107.

Then, the projections 23c1-23c3 and the holes 91a1-91a3 engage with each other, and also the centering boss 23a which is an engaging portion positioning portion and the centering hole 91b which is a transmitting member positioning portion engage with each other, so that the driving-side engaging portion 23 and the axis (rotation center) of the main assembly developing coupling 91 coincide with each other. Then, by rotation of the main assembly coupling 91, the projections 23c1-23c3 and the holes 91a1-91a3 engage with each other, respectively, so that the rotational driving force is transmitted to the developer supplying roller 34.

13

Next, rotation of the developing roller **25** will be described. The developer supplying roller **34** is provided with the driving-side engaging portion **23** in one end side and is provided with a gear in the other end side with respect to the longitudinal direction (the axial direction of the developer supplying roller). On the other hand, the developing roller **25** is provided with a gear engageable with the above gear. By this constitution, the rotational driving force is transmitted to the developing roller **25** drive-connected to the developer supplying roller **34** by the gears in the other end side with respect to the longitudinal direction.

Here, the drive transmission to the main assembly drum coupling **90** and the main assembly developing coupling **91** is made by a motor provided in the apparatus main assembly **100A**. By this, the photosensitive drum **1** and the developer supplying roller **34** receive the driving force from the image forming apparatus main assembly independently of each other. Incidentally, the motor may employ a constitution using a single motor per each of the process cartridges **70** for the respective colors and a constitution in which the drive is transmitted to some process cartridges by the single motor. (Constitution of Developing Frame and Rotational Directions of Developing Roller and Developer Supplying Roller)

Next, a constitution of the developing frame and the rotational directions of the developing roller and the developer supplying roller will be described using FIGS. **1**, **3**, **19** and **26**. FIG. **1** is an illustration showing a driving force inputting portion and a driving system of the developing unit in this embodiment. FIG. **3** is an illustration showing the cartridge mounted in the image forming apparatus. FIG. **19** is an illustration showing a constitution of the developing chamber in this embodiment. FIG. **26** is an illustration showing a comparison example in which the developing chamber toner feeding member is provided in the developing chamber.

As described above, the toner accommodating portion **31c** of the developing frame **31** is provided with the toner feeding member **36** (FIG. **3**) for not only stirring the accommodated toner but also feeding the toner to the developing chamber **31b** via the toner opening **31e**. Incidentally, in this embodiment, a constitution in which the developing roller **25** and the developer supplying roller **34** are provided in the developing chamber **31b** is employed. Further, the toner accommodating portion **31c** is provided below the developing chamber **31b** with respect to direction of gravity, and therefore the toner feeding member **36** is positioned below the developing chamber **31b** with respect to the direction of gravity. That is, the process cartridge **70** in this embodiment has a scooping-up constitution in which the toner is fed by the toner feeding member **36** against the gravity from the toner accommodating portion **31c** disposed below the developing chamber **31b** with respect to the direction of gravity to the developing chamber **31b** disposed above the toner accommodating portion **31c** with respect to the direction of gravity.

The developer fed from the toner accommodating portion **31c** to the developing chamber **31b** stagnates at a developing chamber bottom (portion) **31f** as shown in FIG. **19**. In order to feed the developer stagnating at the developing chamber bottom **31f** to the developer supplying roller, as the comparison example, as shown in FIG. **26**, a developing chamber toner feeding member **37** is provided at the developing chamber bottom **31f**, and the a developing chamber toner feeding member **37** is moved, so that the developer stagnating at the developing chamber **31f** was supplied to the developer supplying roller **34**.

14

In this embodiment, as shown in FIG. **19**, the developer supplying roller **34** is set so as to rotate in a direction (arrow E direction) opposite to the rotational direction (arrow B direction) of the developer supplying roller **34**. That is, at the contact portion between the developing roller **25** and the developer supplying roller **34**, the respective surfaces thereof are in a direction of movement in the same direction. Incidentally, as shown in FIG. **1**, the rotational direction of the photosensitive drum **1** is an opposite direction to the rotational direction of the developing roller. Further, the rotational direction of the photosensitive drum **1** is the same direction as the rotational direction of the developer supplying roller **34**.

In FIG. **19**, the developer supplying roller **34** has a constitution in which a sponge portion (elastic layer having an inner porous portion) **34a** is provided. Further, in FIG. **19**, the developing roller **25** has an elastic layer **25a**. A surface hardness of the developer supplying roller **34** is lower than a surface hardness of the developing roller **25**, and therefore when both rollers are in contact with each other, as shown in FIG. **19**, the developer supplying roller is dented (deformed). Here, as shown in FIG. **19**, the developer supplying roller **34** is in a state in which the surface of the sponge portion **34a** is deformed correspondingly to a penetration amount at the contact portion with the developing roller **25**. At this time, from the sponge portion **34a**, the toner contained in the sponge portion **34a** is discharged. Hereinafter, a portion where the toner is discharged by deformation of the sponge portion **34a** is referred to as a discharging portion **34b** and will be described. This discharging portion **34b** is a region in a side upstream of the contact portion between the developer supplying roller **34** and the developing roller **25** with respect to the rotational direction of the developer supplying roller **34**.

On the other hand, at a portion where the rotation of the developer supplying roller **34** advances and the state of the developer supplying roller **34** is restored from the deformed state, air pressure inside the sponge portion **34a** lowers with the restoration. For that reason, a flow of air for taking in the toner toward the inside of the sponge portion **34a** generates. Hereinafter, a portion where the state of the sponge portion **34a** is restored from the deformed state and the toner is taken in is referred to as a taking-in portion **34c** and will be described. This taken-in portion **34c** is a region in a side downstream of the contact portion between the developer supplying roller **34** and the developing roller **25** with respect to the rotational direction of the developer supplying roller **34**. The toner taken in this region is discharged again at the discharging portion **34b**.

In this way, during the rotational drive of the developer supplying roller **34**, the toner is circulated by continuously performing the above-described taking-in and discharging, and in this process, supply of the developer to the developing roller **25** is made. In order to effect stable supply of the developer to the developing roller **25**, it is important to stably supply the toner to the taking-in portion **34c**.

As shown in FIG. **26**, the rotational direction (arrow C direction) of the developer supplying roller **34** in the comparison example is set at the same direction as the rotational direction (arrow B direction) of the developing roller **25** in many cases. In this case, as in this embodiment, in the constitution in which the toner is fed from the lower toner accommodating portion **31c** to the upper developing chamber **31b**, the taking-in portion **34c** is positioned above the developing roller **25** and the developer supplying roller **34**. Accordingly, in order to stably supply the toner to the taking-in portion **34c**, there is a need to provide such an

15

arrangement relationship that the toner which passes through the toner opening 31e and which moves toward the taking-in portion 34c positioned above the developer supplying roller 34 is not blocked by the developer supplying roller 34 itself. Further, at the bottom 31f of the developing chamber 31c, a state in which the toner discharged from the discharging portion 34b, the toner fallen by regulation with a developing blade 35 and the toner fed from the toner accommodating portion 31c are accumulated is formed. In order to stir and circulate these toners, at the bottom 31f of the developing chamber 31b, the developing chamber toner feeding member 37 which is a stirring member is provided, and there was a need to supply the toner to the developer supplying roller 34 by the developing chamber toner feeding member 37.

On the other hand, in this embodiment, with respect to the direction of gravity as shown in FIG. 19, the taking in portion 34c is positioned below the developing roller 25 and the developer supplying roller 34 and is close to the bottom 31f of the developing chamber 31b. That is, the toner fed to the developing chamber 31b moves toward the rear portion by the airflow generated at the taking-in portion 31c, so that the taking-in portion is located at a position where the toner easily reaches the taking-in portion 31c naturally. Accordingly, constraint of an arrangement relationship between the toner opening 31e and the developer supplying roller 34 as in the conventional constitution is alleviated, and therefore a degree of flexibility in design of the arrangement of the toner opening 31e and the developer supplying roller 34 becomes high.

Here, with respect to the direction of gravity, when a lower end 31e2 of the toner opening 31e is disposed at a position higher than the bottom 31f of the developing chamber 31, the toner surface is raised to a position close to the taking-in portion 34c, and therefore such an arrangement is further desirable. Particularly, when the position of the lower end 31e2 of the toner opening 31e is set at a position higher than the taking-in portion 34c with respect to the direction of gravity, the toner surface in the developing chamber 31b always reaches a height of the taking-in portion 34c, and therefore a toner supplying property to the developing chamber 31c is further stabilized. In this embodiment, the height of the lower end 31e2 of the toner opening 31e is disposed at a position higher than a downstream end of the contact portion between the developer supplying roller 34 and the developing roller 25 with respect to the rotational direction of the developer supplying roller 34. Further, the taking-in portion 34c is positioned close to the bottom 31f of the developing chamber 31b, and therefore the toner accumulated at the bottom 31 is naturally taken in the developer supplying roller 34 and is gradually consumed.

Accordingly, as in the conventional constitution, the circulation of the toner is made even when the developing chamber toner feeding member 37 shown in FIG. 26 is not used, and therefore a space in which the developing chamber toner feeding member 37 has been conventionally disposed can be filled, so that it is possible to reduce the residual toner. (Surface Speeds and Roller Diameters of Developing Roller and Developer Supplying Roller)

Using FIG. 19, surface speeds of the developing roller 25 and the developer supplying roller 34 will be described. As shown in FIG. 19, the developing roller 25 and the developer supplying roller 34 rotates in opposite directions. Incidentally, at the contact portion, the respective surfaces move in the same direction. Here, the surface speed of the developer supplying roller 34 is set so as to be higher than the surface speed of the developing roller 25. This is because the toner

16

supplying property to the developing roller 25 and a property of peeling off the toner, on the developing roller 25, which is not used for development are taken into consideration. The surface speed of the developer supplying roller 34 is higher than the surface speed of the developing roller 25, so that a portion, where the toner is contained in a sufficient amount, of the sponge portion 34a always contacts the developing roller 25, and therefore stable toner supply to the developing roller 25 can be effected. Further, with respect to the toner peeling-off property, the surface speed of the developer supplying roller 34 is higher than the surface speed of the developing roller 25 and therefore a frictional force due to a peripheral speed driving force generates, so that the toner on the developing roller 25, which is not used for development, can be peeled off.

Incidentally, with respect to the toner supplying property and the toner peeling-off property, it has been known that an effect is larger when the peripheral speed difference is larger. However, the number of rotation of the developing roller 25 has a large influence on the toner supplying property to the photosensitive drum 1, and therefore from the viewpoint of a developing process, it is not desirable that the peripheral speed difference is provided by lowering the number of rotation of the developing roller 25.

Therefore, in order to increase the peripheral speed while maintaining the number of rotation of the developing roller 25, a method in which the number of rotation of the developer supplying roller 34 is increased relatively by changing a gear ratio between a developer supplying roller gear 38 and a developing roller gear 39 (FIG. 1) which are described later and a method in which a diameter 34r of the sponge portion 34a is increased are used. In the case where the number of rotation of the developer supplying roller 34 is increased relatively while maintaining the number of rotation of the developing roller 25, there is a need to increase an output from the main assembly driving motor (unshown) which is a driving source, and therefore much electric power is required. Accordingly, also in order to suppress electric power consumption, the diameter 34r of the sponge portion 34a may desirably be large, and in this embodiment, a diameter 25r of the developing roller 25 is set at 12 mm and the diameter 34r of the developer supplying roller 34 is set at 13.3 mm, so that a diameter ratio therebetween is about 1.11. However, it is not necessarily required that the diameter 34r of the sponge portion 34a is made larger than the diameter 25r of the developing roller 25, but a desired peripheral speed difference may also given by the gear ratio. Incidentally, although a driving system in this embodiment will be described later, with respect to the number of teeth of the developer supplying roller gear 38 and the developing roller gear 39 (FIG. 1) which are directly connected to each other, the number of teeth of the developer supplying roller gear 38 is set at 18 teeth, and the number of teeth of the developing roller gear 39 is set at 26 teeth, so that the gear ratio therebetween is about 1.44.

Here, with respect to a surface speed ratio between the developing roller 25 and the developer supplying roller 34 (i.e., (developer supplying roller surface speed)/(developing roller surface speed), hereinafter referred to as a "peripheral speed ratio"), it is desirable that the peripheral speed ratio is set in a range of 1.3 or more and 1.8 or less. This set range is such a range that necessary and sufficient toner supplying property and toner peeling off property can be maintained. When the peripheral speed ratio is below 1.3, there is a liability that a good toner peeling-off property cannot be maintained, so that there is a liability of the influence of a ghost or the like on an image quality. Further, when the

17

peripheral speed ratio is 1.8 or less, the toner supplying property and the toner peeling-off property can be sufficiently maintained. For that reason, when the peripheral speed ratio exceeds 1.8, friction becomes large and thus abrasion of the developer supplying roller and the developing roller is liable to generate, and therefore it is not desirable that the surface speed of the developer supplying roller **34** is excessively increased. Here, in this embodiment, by the above-described diameter ratio and gear ratio, the surface speed of the developing roller **25** is set at about 304 mm/s and the surface speed of the developer supplying roller **34** is set at about 487 mm/s, so that the peripheral speed ratio therebetween is about 1.60. In the setting, it has already been confirmed that a sufficient effect with respect to the toner supplying property and the toner peeling-off property can be obtained. Incidentally, the surface speed referred herein is a speed on the surface excluding the contact portion between the developing roller **25** and the developer supplying roller **34**, and this is similarly applicable to also the peripheral speed ratio.

(Drive Input and Driving System for Developing Unit)

Using FIGS. **1** and **20**, a drive input constitution and a constitution of the driving system for the developing unit **4** will be described. As described above, the driving force outputted from the main assembly driving motor (unshown) which is the driving source of the apparatus main assembly **100A** is inputted into the developing unit **4** by engagement of the main assembly developing coupling **91** of the apparatus main assembly **100A** with the driving-side engaging portion **23** of the Oldham coupling **20** provided at the end portion of the shaft portion **34j** of the developer supplying roller **34**.

Here, first, the drive input constitution of the developing unit **4** will be described using FIG. **1**. FIG. **1** is an illustration showing the driving system for the developing unit **4**, and for simplification of explanation, only the developing roller **25**, the developer supplying roller **34** and the driving system relating to these rollers are extracted and shown.

As shown in FIG. **1**, the shaft portion **34j** of the developer supplying roller **34** is provided with the developer supplying roller gear **38** which is an upstream drive transmitting member (first drive transmitting portion). Similarly, the shaft portion **34j** of the developing roller **25** is provided with the developing roller gear **39** which is a downstream drive transmitting member (second drive transmitting portion) provided so as to directly engage with the developer supplying roller gear **38**. Incidentally, in this embodiment, a gear train such as the developer supplying roller gear **38** is provided in a side (the other side) opposite from the driving force inputting portion of the developing unit **4** with respect to the axial direction from the viewpoint of the space or the like, but the gear train and the driving force inputting portion may also be provided in the same side. Here, the rotational directions of the developing roller **25** and the developer supplying roller **34** are opposite to each other, and therefore there is no need to provide an idler gear between the developer supplying roller gear **38** and the developing roller gear **39**, so that the number of parts can be reduce. The driving force inputted onto the shaft of the developer supplying roller **34** is transmitted from the developer supplying roller gear **38** to the developing roller **25** via the developing roller gear **39**. Incidentally, as described above, in this embodiment, the number of teeth of the developer supplying roller gear **38** is set at 18 teeth, and the number of teeth of the developing roller gear **39** is set at 26 teeth.

18

Using FIG. **20**, the driving system for the developing unit will be described. FIG. **20** is an illustration showing the driving system in a side downstream of the developing roller **25**.

As shown in FIG. **20**, in a side downstream of the developing roller gear **39**, a developing (means) idler gear **80**, a stirring idler gear **81** and a stirring gear **82** which are used for transmitting the drive to the toner feeding member **36** are provided in the listed order. The developing idler gear **80** and the stirring idler gear **81** are rotatably supported by the front developing bearing **12**, and the stirring gear **82** is rotatably supported by the developing frame **31** in a state in which the stirring gear **82** is connected to the toner feeding member **36** by an unshown connecting means such as snap-fit means and an engaging portion. The driving force inputted onto the shaft of the developer supplying roller **34** is transmitted in the order of the developer supplying roller gear **38**, the developing roller gear **39**, the developing idler gear **80**, the stirring idler gear **81** and the stirring gear **82** and is finally transmitted to the toner feeding member **36**.

As shown in FIG. **27**, the developing idler gear **80** is provided with flexible sheets **801** adjacent to the position where the developer supplying roller gear **38** and the developing roller gear **39** are engaged with each other. The flexible sheets **801** rotate in synchronism with the rotation of the developing idler gear **80**, so that they contact the developing roller gear **39** while rotating, by which wear chips which are produced by the sliding motion between the gear teeth in the case of long life and high speed process cartridge **70** are removed. By this, stabilized images can be produced stably throughout the life of the process cartridge **70**.

FIG. **28** is a sectional view illustrating the positions of the flexible sheet **801** and the developing roller gear, in which the gear portion of the developing idler gear **80** is omitted for better illustration.

(Small Deformation of Developer Supplying Roller)

Using FIGS. **21** and **22**, small deformation generating at the sponge portion **34a** of the developer supplying roller **34** will be described. The developer supplying roller **34** is always supported in the contact state with the developing roller **25**, but when the developer supplying roller **34** is left standing for a long time in a high-temperature environment or the like, at the contact portion with the developing roller **25**, small plastic deformation as shown in FIG. **21** generates in some cases. Hereinafter, with respect to the developer supplying roller **34**, a region where the small plastic deformation generates is referred to as a small deformation portion **34n** and will be described.

First, FIG. **22** is an illustration showing a constitution in which different from this embodiment, the driving force from the main assembly is not inputted into the developer supplying roller **34**, but is inputted into the developing roller **25**. In this constitution, the developing roller gear **39** drive the developer supplying roller gear **38**. Here, FIG. **23** is an illustration showing one tooth of each of the developer supplying roller gear and the developing roller gear at an engaging portion between a tooth **38a** of the developer supplying roller gear and a tooth **39a** of the developing roller gear. FIG. **23(a)** is an illustration showing a state in which the sponge portion **34a** which is not deformed reaches the contact position with the developing roller **25**, and FIG. **23(b)** is an illustration showing a state in which the small deformation portion **34n** reaches the contact position with the developing roller **25**. A broken line **39b** shown in (b) of FIG. **23** represents a behavior of the developing roller gear tooth **39a** in a state in which a load from the developer

supplying roller gear **38** is decreased. Using FIGS. **22** and **23**, the influence due to the small deformation of the developer supplying roller **34** will be described.

In the case where the sponge portion **34a** of the developer supplying roller **34** is not deformed, as shown in (a) of FIG. **23**, the developing roller gear tooth **39a** rotates in a state in which it receives a certain load from the developer supplying roller gear tooth **38a**. However, when the small deformation portion **34n** of the developer supplying roller **34** reaches the contact position with the developing roller **25**, a frictional force generating between the developing roller **25** and the developer supplying roller **34** decreases instantaneously. By this, the developer supplying roller **34** is in a state in which the developer supplying roller **34** easily rotates instantaneously, and therefore, as shown in (b) of FIG. **23**, the load received from the developer supplying roller gear tooth **38a** by the driven developing roller gear tooth **39a** decreases instantaneously. By this, the rotational speed of the developing roller **25** instantaneously increased. Therefore, the surface speed of the driving-side **25** instantaneously increases relative to the surface speed of the photosensitive drum **1**, and therefore there is a possibility that non-uniformity generates in toner supplying property from the developing roller **25** to the photosensitive drum **1** and thus a phenomenon such as a lateral stripe generates on the image. Incidentally, it is known that this phenomenon is liable to generate as the peripheral speed difference between the surface speed of the developing roller **25** and the surface speed of the developer supplying roller **34** becomes larger.

On the other hand, in this embodiment shown in FIG. **1**, the developer supplying roller **34** is in a state in which the developer supplying roller **34** readily rotates instantaneously by passing of the small deformation portion **34n** of the developer supplying roller **34** through the contact portion with the developing roller **25**. However, as shown in FIG. **24**, there is no large fluctuation in load for rotating the developing roller **25**, and therefore there is no generation of the influence on the behavior of the developing roller **25**. Accordingly, even when the small deformation generates at the sponge portion **34a** of the developer supplying roller **34**, the non-uniformity does not readily generate in toner supplying property from the developing roller **25** to the photosensitive drum **1**. For that reason, the constitution in which the driving force is inputted into the developer supplying roller **34** is capable of suppressing a lowering in image quality compared with a constitution in which the driving force is inputted into the developing roller **25**.

Here, when the toner peeling-off property, the electric power consumption and the influence of the small deformation of the sponge portion **34a** on the image are summarized from the viewpoint of the above-described roller peripheral speed difference, a tendency as shown in a Table of FIG. **25** is obtained from an experimental result. That is, the peripheral speed difference between the surface speed of the developing roller **25** and the surface speed of the developer supplying roller **34** may desirably be set at (developer supplying roller/developing roller)=1.3 or more and 1.8 or less also from the viewpoint of the influence of the small deformation of the sponge portion **34a** on the image.

As described above, according to this embodiment, in the developing device of the constitution in which the toner is scooped up from the toner accommodating chamber disposed below the developing chamber **31b** to the upper developing chamber **31b**, the rotational direction (arrow C direction) of the developer supplying roller **34** is made the opposite direction to the rotational direction (arrow B direction) of the developing roller. By this, it is possible to

suppress the stagnation of the toner without providing the stirring member in the developing chamber **31b**, and therefore it is possible to reduce the number of parts and to decrease the amount of the residual toner. Further, the surface speed of the developer supplying roller **34** is set so as to be higher than the surface speed of the developing roller, whereby it becomes possible to stably supply the toner to the developing roller. Further, the driving force from the image forming apparatus main assembly is inputted onto the shaft of the developer supplying roller **34**, whereby it is possible to reduce an image defect generating, e.g., when the developer supplying roller **34** is left standing in the high-temperature environment or the like. From the above, in the developing device having the scooping constitution including the toner accommodating chamber below the developing chamber **31c**, it is possible to provide a process cartridge and an image forming apparatus which are capable of improving the image quality while reducing the number of parts and decreasing the amount of the residual toner.

INDUSTRIAL APPLICABILITY

According to the present invention, there are provided a process cartridge and an image forming apparatus which are capable of realizing reduction of a residual developer while reducing the number of parts, in a constitution that a developer is scooped up from a developer accommodating chamber, provided below a developing chamber, to the developing chamber above the developer accommodating chamber.

The invention claimed is:

1. A process cartridge comprising:

- (i) a photosensitive drum;
 - (ii) a rotatable developing roller for developing an electrostatic latent image formed on said photosensitive drum;
 - (iii) a developer supplying roller, provided in contact with said developing roller, for supplying a developer to said developing roller;
 - (iv) a driving force receiving portion for receiving a driving force, wherein said driving force receiving portion is provided at a shaft end portion of said developer supplying roller and is movable in a direction crossing a shaft of said developer supplying roller;
 - (v) a first driving force transmitting portion configured to transmit the driving force received by said driving force receiving portion, to said developing roller, wherein said first driving force transmitting portion is provided on said developer supplying roller; and
 - (vi) a second driving force transmitting portion provided on said developing roller and configured to transmit the driving force by engaging with said driving force transmitting portion,
 - (v) flexible sheets provided adjacent to an engaging portion between said first driving force transmitting portion and second driving force transmitting portion and configured to intermittently contact said second driving force transmitting portion with rotation of said second driving force transmitting portion,
- wherein a peripheral movement direction of said developing roller is opposite to a peripheral movement direction of said developer supplying roller, and a peripheral speed of said developer supplying roller is larger than a peripheral speed of said developing roller.
- 2.** A process cartridge according to claim **1**, further comprising a third driving force transmitting portion for receiving a driving force from said second driving force

transmitting portion, wherein said flexible sheets are mounted on said third driving force transmitting portion.

* * * * *