



US007503213B2

(12) **United States Patent**
Campbell

(10) **Patent No.:** **US 7,503,213 B2**
(45) **Date of Patent:** **Mar. 17, 2009**

(54) **BIMETALLIC SENSOR MOUNT FOR AXLES**

(75) Inventor: **Rodney J. Campbell**, Grand Blanc, MI (US)

(73) Assignee: **American Axle & Manufacturing, Inc.**, Detroit, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 448 days.

(21) Appl. No.: **11/380,523**

(22) Filed: **Apr. 27, 2006**

(65) **Prior Publication Data**

US 2007/0251319 A1 Nov. 1, 2007

(51) **Int. Cl.**
G01P 15/00 (2006.01)

(52) **U.S. Cl.** **73/488; 73/494**

(58) **Field of Classification Search** **73/488, 73/494, 504.12, 504.18, 514.35, 528, 540; 301/124.1; 384/448, 544, 512, 589**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,063,345 A	11/1991	Akiyama	
5,091,022 A *	2/1992	Achikita et al.	148/104
5,122,740 A	6/1992	Cottam et al.	
5,486,757 A	1/1996	Easley	
5,486,758 A	1/1996	Hammerle	
5,640,087 A	6/1997	Alff	
5,967,473 A	10/1999	Singbartl	

5,997,182 A *	12/1999	Brown	384/448
6,019,086 A	2/2000	Schneider et al.	
6,081,111 A	6/2000	Herderich et al.	
6,127,819 A	10/2000	Ouchi et al.	
6,232,772 B1	5/2001	Liatard et al.	
6,400,135 B1	6/2002	Skoff et al.	
6,539,800 B2	4/2003	Yamashita	
6,650,412 B1 *	11/2003	Slater	356/328
6,766,820 B1 *	7/2004	Hoss	137/66
6,774,623 B2	8/2004	Palfenier et al.	
6,911,817 B2	6/2005	Clark	
2005/0006075 A1 *	1/2005	Wanni et al.	165/162
2005/0206222 A1 *	9/2005	Swanson	301/124.1

* cited by examiner

Primary Examiner—Hezron Williams


Assistant Examiner—Samir M Shah



(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

An axle assembly for a vehicle includes an axle housing having a tubular portion. A bimetallic sensor mount having a first region of corrosion resistant material and a second region of weldable material is welded to the tubular portion. A differential unit including a side gear is disposed in a central cavity of the axle housing. An axleshaft having a shaft portion and a target portion with a plurality of teeth is disposed in the tubular portion of the axle housing. The shaft portion is coupled to the side gear. A sensor is coupled to the sensor mount and extends through an aperture in the mount and the tubular portion to locate an end portion of the sensor a predetermined distance from the teeth of the target portion. A method of making an axle assembly having a sintered bimetallic sensor mount is also disclosed.

32 Claims, 3 Drawing Sheets








Fig-3




Fig-4

BIMETALLIC SENSOR MOUNT FOR AXLES**BACKGROUND OF THE INVENTION**

The present invention relates generally to speed sensor assemblies for use in motor vehicles and, more particularly, to a speed sensor assembly having a bimetallic sensor mount for mounting a speed sensor to a support structure.

As is well known, speed sensor assemblies are used in motor vehicle applications to detect the rotational speed of a rotary member (e.g., wheels, axleshafts, propshafts, etc.). The signal generated by the sensor is typically used to control actuation of vehicle systems such as, for example, anti-lock braking systems, four-wheel drive and all-wheel drive torque transfer systems, torque biasing or limited slip axle systems and electronic stability control systems.

Most speed sensor assemblies are equipped with a sensor that is operable to detect discontinuities, such as gear teeth, along a target surface. The target surface can be formed on the rotary member or can be formed on a target member, such as a tone wheel or exciter ring, that is mounted to the rotary member. In its environment of use, the speed sensor assembly requires a sensor mount for mounting the sensor to a stationary support structure. For example, one relatively common vehicular mounting arrangement for a speed sensor assembly utilizes a Hall-effect sensor which is mounted to the axle housing and an exciter ring that is secured to the axle shaft. The sensor mount for this arrangement typically employs a steel boss that is welded to the axle housing. Once the steel boss has been welded to the axle housing, it is machined to receive the sensor, as well as fasteners employed to both orient and secure the Hall-effect sensor to the axle housing. During prolonged vehicle operation, the steel boss on the axle housing tends to oxidize. If iron oxide forms at the mounting interface between the sensor and the boss, the position of the sensor may change relative to the exciter ring. Due to the operational characteristics of the Hall-effect sensor, a change in sensor position relative to the exciter ring can result in a loss of wheel speed sensing capability. Accordingly, a need exists for providing a speed sensor assembly having a sensor mount that is resistant to corrosion.

SUMMARY OF THE INVENTION

It is an object of the present invention to address the limitations of conventional speed sensor assemblies by providing a speed sensor assembly having a sensor mount capable of reducing corrosion between the sensor and the mounting structure.

As a related object, the speed sensor assembly of the present invention includes a bimetallic sensor mount having a first region of a first metallic material that is adapted to support the sensor and a second region of a second metallic material that is adapted for attachment to the mounting structure.

According to another related object, the bimetallic sensor mount associated with the speed sensor assembly of the present invention is a powdered metal component having its first region formed from a corrosion resistant material and its second region formed from a material capable of being welded to the mounting structure.

Pursuant to yet another object, the speed sensor assembly of the present invention is intended for use in association with power transmission assemblies of the type used in motor vehicles for detecting the rotational speed of a rotary component.

In accordance with these and other objects, the speed sensor assembly of the present invention is disclosed for use in cooperation with an axle assembly to detect the rotary speed of an axle shaft. The axle assembly includes an axle housing defining a central cavity and an axle tube attached to the axle housing within which the axle shaft is rotatably supported. A differential gearset is rotatably supported within the central cavity and includes an output side gear that is coupled to an end portion of the axle shaft. The sensor assembly includes a sensor device and a bimetallic sensor mount. The bimetallic sensor mount includes a first region of corrosion resistant material and a second region of weldable material. The sensor mount is arranged such that its second region is welded to the axle tube. The sensor extends through an aperture formed through the sensor mount and the axle tube such that its end portion is located a predetermined distance from a target surface formed on or secured to a target portion of the axle shaft.

The present invention is further directed to a method of making an axle assembly which includes the steps of providing an axle housing with a tubular portion and providing a sensor mount having a first region of non-corrosive metal and a second region of weldable metal. The method also includes the steps of welding the second region of the sensor mount to the tubular portion, forming a sensor aperture through the sensor mount and the tubular portion of the axle housing, and installing an axle shaft into the tubular portion. The axle shaft includes a target portion that is aligned with the sensor aperture. Further, the method includes the steps of inserting the sensor into the sensor aperture to position an end of the sensor a predetermined distance from the target portion and securing the sensor to the first region of the sensor mount.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred embodiment of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. 1 is a schematic illustration of an exemplary vehicle equipped with a powertrain assembly having a speed sensor assembly constructed in accordance with the teachings of the present disclosure;

FIG. 2 is a partially cut away perspective view of the powertrain assembly of FIG. 1 illustrating the components of a rear axle assembly and a propshaft in greater detail;

FIG. 3 is a fragmentary sectional view of a portion of the rear axle assembly illustrating the components of the speed sensor assembly constructed according to the present invention; and

FIG. 4 is an exploded perspective view of the speed sensor assembly shown in FIG. 3.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The following description of the preferred embodiment is merely exemplary in nature and is not intended to limit the invention, its application, or uses.

The present invention is directed to a speed sensor assembly adapted for use in a variety of speed sensing applications and which has a sensor operable to detect the rotational speed

of a rotary member. The sensor is mounted to a sensor mount that is rigidly fixed to a mounting structure such that an end portion of the sensor is positioned in close proximity to a target on the rotary member. The term "rotary member" is intended to define any component such as, for example, a wheel or a shaft, for which a rotational speed value is required. Likewise, the term "sensor" is intended to define any passive device such as, for example, a variable reluctance sensor or any active device such as, for example, a Hall-effect device or magneto-resistive element capable of generating a rotary speed signal. Finally, the term "target" is intended to define any component or surface having discontinuities extending from a target surface and may include, for example, a tone wheel, an exciter ring or a gear ring.

With reference to FIG. 1 of the drawings, a vehicle having an axle assembly that is constructed in accordance with the teachings of the present disclosure is generally indicated by reference numeral 10. Vehicle 10 includes a driveline 12 adapted to receive rotary power (i.e., drive torque) from a powertrain 14. Powertrain 14 includes an engine 16 and a transmission 18. Driveline 12 includes a propshaft assembly 20, a rear axle assembly 22 and a pair of rear wheels 24. Engine 16 is mounted in an in-line or longitudinal orientation along the axis of vehicle 10 and its output is selectively coupled via a conventional clutch (not shown) to the input of transmission 18 for rotation about a rotary axis. Transmission 18 also includes an output 18a and a geartrain (not shown). The geartrain is operable for coupling the transmission input to transmission output 18a at a predetermined gear speed ratio. Propshaft assembly 20 is coupled for rotation with transmission output 18a. Drive torque is transmitted through propshaft assembly 20 to rear axle assembly 22 where it is selectively apportioned to left and right rear wheels 24.

With additional reference to FIG. 2, rear axle assembly 22 is shown to include a carrier assembly 26, a left axleshaft 28 and a right axleshaft 30. Carrier assembly 26 includes a housing 32, a differential unit 34 and a pinion or input shaft 36. Housing 32 supports differential unit 34 for rotation about a first axis 38 and further supports pinion shaft 36 for rotation about a second axis 40 that is perpendicular to first axis 38. Housing 32 includes a wall member 42 that defines a central cavity 44 having a left axle aperture 46 and a right axle aperture 48 aligned with first axis 38 and an input shaft aperture 68 aligned with second axis 40. Housing 32 also includes a pair of axle tubes 52 that are fixedly mounted to wall member 42 so as to be aligned with axle apertures 46 and 48.

Differential unit 34 is disposed within central cavity 44 of housing 32 and includes a gearset 60. Gearset 60 includes first and second side gears 62 and 64, respectively, and a plurality of pinions 65. Pinions 65 are rotatably supported from a differential case 66 which, in turn, is rotatably supported within central cavity 44 of housing 32. Left and right axleshafts 28 and 30 extend through left and right axle apertures 46 and 48, respectively, where they are coupled for rotation about first axis 38 with first and second side gears 62 and 64, respectively.

Pinion shaft 36 extends through input shaft aperture 68 where it is supported in housing 32 for rotation about second axis 40. Pinion shaft 36 is coupled for rotation with propshaft assembly 20 and is operable for transmitting drive torque to differential unit 34. More specifically, the drive torque received by pinion shaft 36 is transmitted to differential case 66 of differential unit 34 such that drive torque is distributed through pinions 65 to first and second side gears 62 and 64, thereby causing left and right axleshafts 28 and 30 to rotate about first axis 38.

FIGS. 3 and 4 depict left axleshaft 28 and portions of axle assembly 22 in greater detail. As one of ordinary skill in the art would appreciate from this disclosure, the left side of axle assembly 22 is substantially similar to the right side. As such, a detailed discussion of the left side of axle assembly 22 will suffice for both. A bearing assembly 74 supports left axleshaft 28 for rotation relative to axle tube 52. As will be detailed, a sensor assembly 76 constructed in accordance with the present invention is coupled to axle tube 52 utilizing a method of the present invention.

Axleshaft 28 includes a drive flange 77, a bearing support portion 78, a target mount portion 80 and a shaft portion 82, the end of which is fixed for rotation with left side gear 62. In the particular example provided, bearing support portion 78 is formed with a first diameter, shaft portion 82 is formed with a second, relatively smaller diameter and target mount portion 80 is formed with a third diameter that is intermediate the diameters of bearing support portion 78 and shaft portion 82. Appropriately sized and contoured transition sections 86 are employed between bearing support portion 78, target mount portion 80 and shaft portion 82 so as to reduce stress concentrations.

As noted, bearing assembly 74 supports axleshaft 28 for rotation in axle tube 52. In this regard, bearing assembly 74 may be pressed into axle tube 52 such that elements (e.g., rollers 88) support bearing support portion 78 of axleshaft 28. A seal 90 is coupled to axle tube 52 in a conventional manner to retain lubricating fluids in axle tube 52 as well as to inhibit the transmission of dirt, debris and other contaminants to the interior of axle tube 52. Seal 90 may include one or more seal lips 92 that sealingly engage bearing support portion 78 of axleshaft 28.

Left axleshaft 28 also includes a target or exciter ring assembly 94 having a housing 96 axially positioning a tone wheel 98. A retainer 100 includes a case 102 and a nylon member 104. Case 102 is press-fit within housing 96 to mount retainer 100 to exciter ring assembly 94. Housing 96 may be pressed into axle tube 52 to retain and properly position exciter ring assembly 94. Once exciter ring assembly 94 is mounted to axle tube 52, nylon member 104 functions to maintain the axial position of tone wheel 98.

Tone wheel 98 includes a target portion having a plurality of discontinuity features, such as radially-extending and circumferentially spaced-apart teeth 106. Teeth 106 extend radially outwardly from a body portion 108 of tone wheel 98. A plurality of gripping portions 110 extend radially inwardly from body portion 108. Gripping portions 110 are circumferentially spaced-apart from one another. Each gripping portion 110 includes a surface 112 sized and positioned to engage exciter ring mount portion 80 of axleshaft 28. At initial assembly, a minor interference fit exists between gripping portions 110 and axleshaft 28. Gripping portions 110 are constructed from a material that swells when exposed to axle lubricant. Accordingly, when exposed to axle lubricant, gripping portions 110 swell to provide an increased amount of interference. It should be appreciated that an alternate embodiment axleshaft is contemplated where a target portion having teeth 106 is formed directly on axleshaft 28. As such, exciter ring assembly 94 need not be present within an axle assembly having a sensor assembly 76 as provided in this disclosure.

Referring primarily to FIGS. 3 and 4, sensor assembly 76 is shown to include a sensor mount 120, a sensor 124 and a mounting bolt 126. Mount 120 includes an arcuately shaped bottom surface 128 that is configured to complement an outer surface 130 of axle tube 52. Mount 120 is preferably welded to axle tube 52. Mount 120 includes a first throughbore 132

5

that is aligned with an axle tube throughbore **134** formed in axle tube **52**. First throughbore **132** and axle tube throughbore **134** may be simultaneously machined after mount **120** is welded to axle tube **52**. In this manner, consistent size and alignment of the throughbores is assured. A blind threaded bore **136** extends into mount **120** and is sized to threadingly receive mounting bolt **126**.

In accordance with the present invention, mount **120** is fabricated to include a first layer or region of material and a second layer or region of material. Preferably, mount **120** is constructed by sintering two different powdered metals to form a unitary, one-piece structure. Specifically, a first region **140** of mount **120** is constructed from a material that will resist corrosion during operation while a second region **142** of mount **120** is constructed from a material that is weldable to a mounting structure, such as surface **130** of axle tube **52**. One example of a material for first region **140** is SS304N1 modified powdered metal per MPIF standard 35. Another example of a material for first region **140** is 304 stainless steel. However, it should be appreciated that these powdered metal specifications are merely exemplary and any number of corrosion resistant materials may be used to form first region **140**.

First region **140** is constructed to be sufficiently thick such that a seal **144** associated with sensor **124** is positioned in contact with first region **140**. Seal **144** functions to inhibit fluid located within axle tube **52** from escaping through first throughbore **132**. Because seal **144** contacts a corrosion resistant surface of first region **140**, sensor **124** may be simply removed from mount **120** after long periods of use without interference from corrosion within first throughbore **132** at locations proximate to seal **144**. One exemplary material for second region **142** includes FY4500 modified sintered phosphorous iron alloy. This alloy is defined to include a maximum carbon content of 0.10%. Again, the material specification is merely exemplary and it should be appreciated that any number of weldable powdered metals may be specified as a suitable material for second region **142**.

Sensor **124** includes a body **146** and a sensor insert **148** coupled to body **146**. Body **146** includes a substantially planar elongated flange **149** having a bottom surface **150** adapted to be positioned substantially parallel to and spaced apart from an upper planar surface **152** of mount **120**. Sensor insert **148** is shaped as a substantially cylindrical tube having a first end face **154** and an opposite second end face **156**. An aperture **158** extends through sensor insert **148**. Aperture **158** is adapted to receive mounting bolt **126**. Once assembled, the head of bolt **126** engages first end face **154**. Second end face **156** engages planar surface **152**. Sensor **124**, sensor insert **148** and mount **120** are sized to accurately position an end **160** of sensor **124** a predetermined distance from teeth **106** of tone wheel **98**. Additionally, mounting bolt **126** and sensor insert **148** provide a convenient manner to removably secure sensor **124** to sensor mount **120** once sensor mount **120** is welded to axle tube **52**.

Sensor **124** may be any passive or active probe or device capable of generating a signal. Preferably, sensor **124** is a Hall-effect device operable to determine the presence and/or absence of a tooth **106** during rotation of axleshaft **28**. By accurately positioning end **160** in relation to tone wheel **98**, the rotational speed of axleshaft **28** may be determined. Through the use of bimetallic mount **120**, corrosion to surfaces affecting the position of end **160** will be greatly reduced. Therefore, the likelihood of obtaining accurate wheel speed data for extended periods of time should be increased. To further reduce corrosion between the components of sensor assembly **76**, sensor insert **148** and mounting bolt **126** may be

6

constructed from stainless steel materials to eliminate, or at least reduce, the tendency for galvanic corrosion to occur between the engaging surfaces of mounting bolt **126**, sensor insert **148** and mount **120**. As noted, it is contemplated that a similar sensor assembly and mounting arrangement would be provided on the right side of axle assembly **22** to detect the rotary speed of right axleshaft **30**.

Furthermore, the foregoing discussion discloses and describes merely exemplary embodiments of the present invention. One skilled in the art will readily recognize from such discussion, and from the accompanying drawings and claims, that various changes, modifications and variations may be made therein without departure from the spirit and scope of the invention as defined in the following claims. Likewise, those skilled in the art will readily recognize that the invention set forth in this disclosure can be used in a variety of other speed sensing applications.

What is claimed is:

1. An axle assembly for a vehicle, comprising:

an axle housing having a tubular portion with a through-bore;

a sensor mount having a first region of corrosion resistant material and a second region of weldable material, said second region being welded to said tubular portion of said axle housing;

an axleshaft rotatably supported in said tubular portion of said axle housing;

a target member coupled to said axleshaft, and having a target surface; and

a sensor coupled to said sensor mount, said sensor extending through an aperture in said sensor mount and said throughbore of said axle housing for locating an end portion of said sensor in proximity to said target surface of said target member.

2. The axle assembly of claim **1** wherein said sensor mount is a sintered powdered metal component.

3. The axle assembly of claim **2** wherein said first region of corrosion resistant material includes stainless steel.

4. The axle assembly of claim **2** wherein said first region of corrosion resistant material includes SS304N1 modified powdered metal.

5. The axle assembly of claim **2** wherein said first region of corrosion resistant material includes 304 stainless steel.

6. The axle assembly of claim **2** wherein said second region of weldable material includes FY4500 sintered phosphorous iron alloy.

7. The axle assembly of claim **1** wherein said second region includes a material having a maximum carbon content of 0.10 percent.

8. The axle assembly of claim **1** wherein said first region of material is shaped as a layer extending from a distal upper surface of said sensor mount.

9. The axle assembly of claim **8** wherein said second region of material is shaped as a layer extending from a proximal lower surface of said sensor mount.

10. The axle assembly of claim **1** further including a seal positioned between said sensor and said sensor mount, said seal being in engagement with said first region of material.

11. The axle assembly of claim **1** wherein said second region of material of said sensor mount includes a concave surface engaging said tubular portion of said axle housing.

12. The axle assembly of claim **1** further including a cylindrical sensor insert coupled to said sensor mount via a threaded fastener, said sensor insert being operable to restrict movement of said sensor relative to said sensor mount.

13. The axle assembly of claim **12** wherein said sensor insert includes stainless steel.

7

14. The axle assembly of claim **1** wherein said first region of material is adjacent to and in contact with said second region of material.

15. An axle assembly for a vehicle, comprising:

an axle housing defining a central cavity, said axle housing including a tubular portion with a hole extending there-through;

a bimetallic sensor mount having a first region of corrosion resistant material and a second region of weldable material, said second region being welded to said tubular portion of said axle housing;

a differential unit disposed in said central cavity, and including an output gear;

an axleshaft disposed in said tubular portion of said axle housing, said axleshaft having a shaft portion and a target portion, said shaft portion being coupled to said output gear, said target portion including a plurality of surface discontinuities; and

a sensor coupled to said sensor mount and extending through an aperture in said sensor mount and said hole in said tubular portion to thereby locate a portion of said sensor in proximity to said surface discontinuities on said target portion of said axleshaft.

16. The axle assembly of claim **15** wherein said target portion is a tone wheel fixed for rotation with said axleshaft.

17. The axle assembly of claim **15** further comprising a seal coupled to said tubular portion of said axle housing and sealingly engaging said axleshaft.

18. The axle assembly of claim **15** further including a sensor insert fixed to said sensor, said sensor insert being coupled to said sensor mount via a threaded fastener, said sensor insert and said fastener being operable to restrict movement of said sensor relative to said sensor mount.

19. The axle assembly of claim **15** wherein said sensor is a Hall-effect sensor.

20. The axle assembly of claim **15** wherein said sensor mount includes sintered powdered metal.

21. The axle assembly of claim **15** wherein said first region of corrosion resistant material includes stainless steel.

22. The axle assembly of claim **15** wherein said second region includes a material having a maximum carbon content of 0.10 percent.

8

23. The axle assembly of claim **15** wherein said sensor mount is a one-piece structure having said first region of material positioned adjacent to and in contact with said second region of material.

24. A method of making an axle assembly, the method comprising:

providing an axle housing with a tubular portion;

sintering a non-corrosive powdered metal and a weldable powdered metal to form a sensor mount having a first region of non-corrosive metal and a second region of weldable metal;

welding said second region to said tubular portion of said axle housing;

forming a sensor aperture through said sensor mount and said tubular portion;

inserting an axleshaft into said tubular portion, said axleshaft including a target portion that is aligned with said sensor aperture; and

inserting a sensor within said sensor aperture to position an end of said sensor in proximity to said target portion of said axleshaft.

25. The method of claim **24** further including fixing a sensor insert to said sensor and coupling said sensor insert to said sensor mount with a threaded fastener to restrict movement of said sensor relative to said tubular portion.

26. The method of claim **24** wherein said sensor is a Hall-effect sensor.

27. The method of claim **26** wherein said target portion includes a plurality of circumferentially spaced apart teeth.

28. The method of claim **24** further including mounting a bearing in said tubular portion proximate said sensor hole and supporting a portion of said axleshaft with said bearing.

29. The method of claim **28** wherein prior to inserting said axleshaft, the method further comprises installing a shaft seal to said tubular portion.

30. The method of claim **29** wherein said bearing is disposed between said shaft seal and said sensor aperture.

31. The method of claim **24** further including positioning a seal between said sensor and said sensor mount and engaging said seal with said first region.

32. The method of claim **24** wherein said first region is positioned adjacent to and in contact with said second region.

* * * * *