

(19) **DANMARK**



Patent- og
Varemærkestyrelsen

(12)

Oversættelse af europæisk patentskrift

(10) **DK/EP 3573671 T3**

-
- (51) Int.Cl.: **A 61 L 2/22 (2006.01)** **A 01 N 25/06 (2006.01)** **A 01 N 63/20 (2020.01)**
A 01 N 63/22 (2020.01) **A 47 L 11/00 (2006.01)** **B 08 B 7/00 (2006.01)**
B 08 B 9/00 (2006.01) **B 08 B 9/027 (2006.01)** **B 08 B 9/08 (2006.01)**
C 12 N 1/20 (2006.01)
- (45) Oversættelsen bekendtgjort den: **2022-07-11**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2022-04-13**
- (86) Europæisk ansøgning nr.: **18704600.8**
- (86) Europæisk indleveringsdag: **2018-01-24**
- (87) Den europæiske ansøgnings publiceringsdag: **2019-12-04**
- (86) International ansøgning nr.: **IB2018050424**
- (87) Internationalt publikationsnr.: **WO2018138645**
- (30) Prioritet: **2017-01-25 BE 201705044**
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Living Technologies, coöperatieve vennootschap met beperkte aansprakelijkheid, Klarstraat 104, 1745 Opwijk, Belgien**
- (72) Opfinder: **Willocx, Filip Willem Maria, Hoveniersdreef 27, 3001 Heverlee, Belgien**
DE KOSTER, Koen, Nanovestraat 157, 1745 Opwijk, Belgien
- (74) Fuldmægtig i Danmark: **AWA Norway AS, Hoffsvæien 1A, 0275 Oslo, Norge**
- (54) Benævnelse: **FREMGANGSMÅDE TIL RENGØRING AF OVERFLADER I INDRE RUM OG I TEKNISK Udstyr MED GODARTEDE BAKTERIER**
- (56) Fremdragne publikationer:
EP-A1- 2 329 893
WO-A1-2006/125283
BE-A5- 1 018 722

DESCRIPTION

[0001] The present invention relates to a method for cleaning surfaces in interior spaces and in technical equipments.

[0002] In particular, the invention is intended for the more efficient visual cleaning and slowing down of dust deposit for all types of surfaces in an interior space or in technical equipment.

[0003] It is known that cleaning surfaces in an interior space is a labour-intensive activity nowadays. In every house, building or production space, in every transport means and in all industrial and technical equipments all types of surfaces need to be cleaned periodically, and this both in case of normal use and after incidents such as fire or water damage.

[0004] Traditionally a cleaning company or the tenant or owner of a building establishes a regular cleaning programme whereby the surfaces in the interior spaces to be cleaned are described and whereby the frequency of cleaning and the cleaning products to be used are determined.

[0005] A specific cleaning programme is usually developed for all possible interior spaces of the building.

[0006] For residential buildings these are living rooms, bedrooms, bathrooms, kitchens, sanitary facilities such as showers and toilets, storage areas such as attics and cellars, stairwells and corridors, elevators and garages for vehicles and garden houses.

[0007] For industrial buildings or educational institutes these are reception areas, production halls, laboratories, training centres, classrooms, workplaces, dressing rooms, desks and offices, gym areas, sports centres, sanitary facilities such as showers and toilets, conference rooms, stairwells and corridors, elevators, storage areas, canteens, eating areas and restaurants, garages for company vehicles and the like.

[0008] For buildings intended for medical care or support to people in need such as hospitals, rehab centres, care homes or therapeutic institutions these are reception areas, waiting rooms, desks and offices, operating theatres, consultation rooms, spaces with diagnostic equipment, sanitary facilities for care, patient rooms, kitchens and canteens, eating areas and restaurants, garages for ambulances and patient transport, stairs, corridors and elevators, supply rooms, pharmacy rooms and the like.

[0009] Interior spaces of means of transport such as aircraft, cruise ships, cars, buses, trains and trams also need to be regularly cleaned.

[0010] In addition to the accommodation spaces, spaces that are difficult to access for manual cleaning also need to be regularly cleaned such as in technical equipments and air treatment

systems, air ducts, heating installations, elevator shafts and elevator cages, technical shafts and areas, pipes behind false ceilings or in cooling floors in data centres for computers and servers, cellars and crawl spaces, cinema and theatre auditoriums, high stairwells, inner courts, etc.

[0011] Each room has different types of surfaces which often need to be cleaned with a specific cleaning product and a specific technique: stone and wooden floors, carpets, walls, doors and ceilings, cupboards, glass and mirrors, windowsills, surfaces of a desk, chairs and tables, lamps, settees, beds, telephones, computers, televisions, books, paintings, art objects, plants, sunblinds and louvres, curtains - the list is pretty endless.

[0012] The frequency of cleaning is determined by the average level of soiling and the desired cleaning quality of the building as a function of the predetermined budget. Because of the many working hours required on a day-to-day basis to keep all kinds of surfaces in interior spaces clean, the cleaning activity becomes very expensive.

[0013] The following list (source: [https://osha.europa.eu/en/tools-and-publications/publications/literature_reviews/cleaning workers and OSH](https://osha.europa.eu/en/tools-and-publications/publications/literature_reviews/cleaning_workers_and_OSH)) indicates the biggest problems for the cleaning companies in a work environment:

1. i) Budgets and costs for cleaning are too high: the manual work covers at least 80% of the costs charged to the customer;
2. ii) bad or insufficient visual quality of the result;
3. iii) health problems in the building due to chemical pollution;
4. iv) odour nuisance in the building (toilets, perspiration, carpets);
5. v) non-sustainable cleaning, use of corrosive and toxic chemicals;
6. vi) health and safety problems for the cleaners: accidents, long-term absences;
7. vii) lack of organised communication between customer and cleaning company.

[0014] The cleaning sector has been going through a constant rationalisation since the eighties with the aim of improving productivity and reducing costs. A large number of companies, including many small and medium-sized enterprises is under constant competitive pressure.

[0015] As approximately 80% of the costs charged to the customers are labour costs, cost cuts often mean reducing personnel, increasing work load, such that health and safety standards slip. Some companies do not respect the labour laws and push the prices downwards. The pressure on the companies has a counterproductive effect on the quality of the services, which in the longer term may endanger the sector's income.

[0016] According to Dr. Herbert Sinner (Henkel, 1959, "Über das Waschen mit Haushaltwaschmaschinen", Haus + Heim-Verlag), the cleaning process is influenced by four factors that have an influence on each other:

1. a) a chemical reaction due to the operation of the cleaning product,
2. b) at a certain temperature,
3. c) during a certain contact time on the dirt, and
4. d) a mechanical treatment by means of a brush or microfibre cloth.

[0017] When one factor is reduced or removed it needs to be compensated by one or several of the other factors.

[0018] For instance, you can opt to use less strong chemicals, but then it needs to be compensated by a longer contact time or higher temperature.

[0019] Many solutions are offered to reduce the total time required for the cleaning: solutions to limit the preparation time, or the application of the cleaning product, shortening the contact time and the treatment time of the surface, rinsing and drying surfaces sooner and clearing up the tools more quickly.

[0020] Examples of solutions whereby less working hours are needed to clean surfaces comprise the use of microfibre cloths and mops, limiting the cleaning to the places where needed, not using too many different cleaning products, cleaning with two hands at the same time, not dosing the cleaning products manually, not using too much water such that limescale is avoided and the surfaces don't stay wet too long, and automated cleaning by scrubbing machines.

[0021] However, these solutions are limited because there is no universal method that can be used on all surfaces, because the cleaning products leave residues and too much water or because no solution is offered for surfaces that are difficult to reach manually. Ultimately, the cleaning frequency remains the same.

[0022] WO 2006/125283 A1 describes a method for keeping surfaces free from pathogenic bacteria by applying non-pathogenic bacteria including *Bacillus* varieties. The method involves spraying a solution of non-pathogenic bacteria strains over the surface, in order to prevent other, possibly dangerous bacteria multiplying quickly and exceeding a possible infection threshold.

[0023] BE 1018722 A5 describes a device to atomize non-pathogenic bacteria of the genus *Bacillus* on a pet and its surrounding to block pathogenic bacteria. The device is static and located on the cage or residence of the pet, and periodically emits non-pathogenic bacteria on the pet.

[0024] In EP 2329893 B1 of Metatecta a method is presented for the microbiological cleaning of an interior space. The method comprises a two-step technique in an enclosed space, whereby first a biocide is atomized and one hour later a mixture of spores of aerobic spore

forming *Bacillus* varieties. This method describes a method to sanitise an interior space biologically contaminated by viruses, bacteria, spores, yeasts or moulds. In this method no people or animals are permitted in the space during the treatment.

[0025] In EP 2863959 A2 of Living Technologies a method is presented for removing particulate matter smaller than 10 µm in indoor environments. The method comprises the atomization in an enclosed space of a mixture of spores of bacteria to metabolize the particles. In this method no people or animals are permitted in the space during the treatment either.

[0026] In both aforementioned methods non-targeted atomized droplets are used, with the aim of slowly letting the droplets descend through the air in the spaces to be cleaned, which raises the treatment duration per space.

[0027] The purpose of the present invention is to provide a solution to the aforementioned limitations and other disadvantages, by providing a method that allows surfaces in interior spaces to be cleaned more quickly, consisting of at least the following step:

- the targeted atomization on the surfaces of a liquid with spores of benign bacteria on all or certain types of surfaces by means of an electrical and/or pneumatically powered atomizer, while the space remains accessible to people and animals, with the purpose of speeding up the cleaning of interior spaces and of technical equipments, lowering the cleaning frequency, and lowering the dust deposit.

[0028] An advantage connected to the method of claim 1 is that it allows the surfaces to be cleaned to be moistened very quickly and in a targeted way whereby the surfaces that were sprayed don't feel wet, but are covered in benign bacteria.

[0029] An added advantage of this method is that no detergents or cleaning chemicals are required anymore and manipulations such as dissolving in water and pouring out buckets are no longer necessary.

[0030] The electrical and/or pneumatic atomizer atomizes the liquid with spores of benign bacteria to a droplet size that is smaller or equal to 80 µm, whereby the treated surfaces feel moist, but don't look wet.

[0031] Preferably the concentration of spores of benign bacteria in the liquid to be atomized amounts to between 10^6 KVE/ml and 50×10^7 KVE/ml, whereby sufficient benign bacteria are applied on the parts of the surface covered by the atomization.

[0032] Preferably the electrical or pneumatic atomizer is an ultra-low volume atomizer, which generates a straight jet with a reach up to 15 metres or less.

[0033] An example of such an atomizer is the targeted Vectornate atomizer type C20 or DC20. This straight jet allows to obtain a cleaning of the surface, also in spaces that are difficult to access for manual cleaning.

[0034] Preferably the electrical atomizer atomizes the liquid with spores of benign bacteria at a flow rate of maximum 300 ml per minute and at an air flow of 0.2 litre a minute on the surface at a pressure of maximum 18 KPa.

[0035] An advantage of such atomization is that a good distribution over the surface is obtained, without the surface feeling wet.

[0036] Optionally this step is followed by

- the manual or mechanical cleaning of the surfaces by means of a microfibre cloth.

[0037] An advantage of this manual cleaning with a microfibre cloth is that this step can also be done quickly, as the microfibre does not have to be moistened, and the treated surfaces do not have to be covered or treated with aqueous solutions with detergents for example.

[0038] Preferably the quantity of atomized liquid with spores of benign bacteria, applied per square metre of treated surface, amounts to maximum 10 grammes per m².

[0039] An advantage of these quantities is that they are much smaller than with a conventional wet cleaning of surfaces such as for floors, such that they are not only much quicker to apply, but also don't make the surface feel wet.

[0040] The atomized spores of bacteria in the atomized liquid are preferably chosen from the spores of benign bacteria of the genus *Bacillus* for applications at room temperature, and preferably comprise *Bacillus subtilis*, *Bacillus amyloliquefaciens*, *Bacillus pumilus*, *Bacillus licheniformis* or *Bacillus megaterium* or a combination of two or more of these strains.

[0041] For applications in cold environmental temperatures between 4 and 18 °C the spores of benign bacteria in the atomized liquid are preferably chosen from the spores of aerobic spore forming cold-tolerant bacteria of the genera *Sporosarcina*, *Paenisporosarcina*, or *Paenibacillus* or comprise a combination thereof and for the genus *Sporosarcina globispora*, *aquimarina*, or *psychrophila* or a combination of two or more of these strains.

[0042] For the genus *Paenisporosarcina* the atomized liquid preferably contains spores of *Paenisporosarcina macmoerdoensis*, and for the genus *Paenibacillus* preferably spores of *Paenibacillus glacialis*, *amylolyticus*, *pabuli*, *xylanexedens*, *castaneae*, or *macquariensis antarcticus* or a combination of two or more of these strains.

[0043] An advantage of these cold-tolerant bacteria is that they also thrive at lower temperatures.

[0044] When using an electrical and/or pneumatic atomizer a liquid with benign bacteria is atomized with a droplet size smaller than or equal to 80 μm . The amount of liquid can be restricted to maximum 10 grammes per m^2 such that the surface does not feel wet and there is no danger for slipping and no stripes or streaks are visible when people, animals or trolleys step or roll over the wet floors.

[0045] An advantage of this method is that the time of the cleaning of the surfaces can be reduced by 20 to 30%.

[0046] In a preferred embodiment a solution of spores of aerobic spore-forming *Bacillus* varieties dissolved in demineralised water with 1% isopropyl-alcohol or another suitable alcohol is atomized.

[0047] The aim of adding an alcohol is to degrease the surfaces in combination with the use of a microfibre.

[0048] During a test period of two months for the cleaning of sanitary facilities, this solution was atomized on all surfaces that needed to be cleaned. The atomization was done with a targeted Vectornate atomizer type C20.

[0049] The time savings with this method in relation to the traditional method for cleaning the sanitary facility amounted to 30%.

[0050] For the cleaning of stairwells and hotel rooms the time savings with this method in relation to the traditional method amounted to 20%.

[0051] For the cleaning of fitting rooms of shops this method in relation to the traditional method resulted in a substantially reduced amount of visual dust after a fixed time interval, such that the cleaning frequency could be lowered.

[0052] In the table I below a number of measurement data is provided whereby the required time and the dust load after cleaning was measured and a comparison was made between the conventional cleaning method with detergents and water versus the method according to the invention.

[0053] The table compares the method according to the invention with the conventional method and this for three different environments. The required time was measured every time and also the dust load of the surfaces before, during and after cleaning, and again one week later (after 7 days).

[0054] The table shows that the time for cleaning is significantly shorter with the method

according to the invention, and also that the obtained results strongly reduce the dust load afterwards.

Table I: Comparison of the method according to the invention with the conventional method for cleaning three different environments.

Method	steps	product	Time min	Dust load g/m ²		
				BEFORE	AFTER	AFTER 7d
1 - Showroom of 400 m ² with furniture						
Invention	Atomize + microfibre cloth	Spores- mixture	27	12.3	3.07	4.72
Conventional	Deterg. Mixture + cloth	detergent	39	12.3	8.78	10.45
2 - Air box section 42 m ² panels with insulating material						
Invention	Atomize + microfibre cloth	Spores- mixture	14	22.4	7.57	8.89
Conventional	Deterg. Mixture + cloth	detergent	19.4	22.4	8.78	14.59
3 - Computer room 84 m2 with tables, chairs and computers						
Invention	Atomize + micro fibre cloth	Spores- mixture	17	8.3	3.23	3.99
Conventional	Deterg. Mixture + cloth	detergent	25	8.3	5.67	6.81

[0055] In the first environment, the showroom of 400 m² with furniture, the method according to the invention results in time savings of 30% in relation to the conventional method. It is possible to work faster in large store areas, where many different objects are located closely against each other which in turn consist of separate components (textiles, glass, wood, metal) which conventionally are cleaned with specific means.

[0056] With the method according to the invention only one product is used for all types of objects, more specifically the atomized spore mixture of benign bacteria. The atomized jet of the electric atomizer has a greater reach than a human action and can also penetrate much easier under, between and above all objects.

[0057] In a second environment, an air box section with panels with insulating material, an air

box needs to be cleaned, in which outside air is sucked in, and is then heated and/or cooled and humidified, before being distributed in a building. Such an air box is characterised by a series of metal parts and insulating materials which are difficult to access manually, which collect a lot of dust and dirt. The fine atomized jet of the electrical atomizer allows the jet to be targeted on these components and to get to the dirty parts which before were not or barely accessible for cleaning.

[0058] With the method according to the invention the required time is less, and there is less dust accumulation in corners and sides.

[0059] In a third environment, a computer room with tables, chairs and computers as can be found in training centres, there were also considerable time savings when cleaning the room with the method according to the invention. The electric atomizer allows a fine atomized jet to be targeted on legs of chairs, computer screens, electric cables and computer screens, as well as in the areas between and under the computers, where a lot of dust particles tend to stick to.

[0060] Here too, the method according to the invention allows a reduction of dust accumulation and a lowering of the frequency of cleaning, without compromising the proper operation of the computers.

[0061] One of the technical solutions to control the climate in an indoor environment is the installation of a cooling ceiling or a climate ceiling. An important disadvantage of this technique is that on top of the climate ceiling the air has to circulate and an enormous amount of visual dirt occurs. At worst, entire dust clouds fall down in case of large air flows. The gap above the climate ceiling is very restricted, to a couple of centimetres, making it impossible to manually clean it directly.

[0062] A comparison was made between the cleaning of the gap above the climate ceiling with the conventional method, i.e. the use of a vacuum cleaner, and the method according to the invention, whereby a targeted jet of atomized spores of aerobic spore-forming *Bacillus* varieties in demineralised water was applied in the gap in a targeted way.

[0063] Not only was the required time reduced because the atomization could be done more quickly than vacuuming, but in addition an inspection 2 months later showed that the amount of accumulated dust in the gap was clearly lower in the part that had been cleaned with the method according to the invention, compared to the part that had been cleaned conventionally with a vacuum cleaner, such that this method according to the invention allows a lower and more effective cleaning frequency.

[0064] Another advantage of the method according to the invention is that it results in an electrostatic charge of the treated surface. In the known state of the art relating to the atomization of liquids a charge is formed on the droplets by the ballo-electrical effect (Thiago et al. J. Braz. Chem. Soc. Vol 27, No 2, AG 229-238, 2016). When aerosols are formed when atomizing a liquid with spores of bacteria, the droplets are given an equal electric charge and

they mutually repel. In the event of sedimentation of the aerosols on dust, the charge of the aerosols is maintained, such that all the dust obtains one and the same charge and will repel other charged dust particles. The atomizer keeps the opposite charge.

[0065] An added advantage of the method according to the invention is that it stimulates the taking up and metabolising of dust by the germinated spores because the surface charge of Bacillus spores favourably affects their germination speed (Nishihara T. et al. Microbiol. Immunol. 1981; 25(8): 763-71). Spores of Bacillus varieties have a negative charge (Didouh N. et al., Afr. J. Microbiol. Res., Vol.9 (2), AG 57-65, January 2015).

[0066] Bacillus subtilis spores survive being charged by electrospray treatment whereby the spores are desolvated and deagglomerated. (Pratt et al. J.Am. Soc. Mass Spectrom. 2014 May; 25(5):712-21, 2014 Feb 25).

[0067] The advantages of the method for cleaning surfaces in interior spaces according to the invention can be summarised as follows:

- significant time savings (20-30 %)
- lower cleaning frequency;
- significant reduction of visual dust deposit or dust burden by electrostatic repulsion;
- faster germination speed of the spores resulting in take-up and metabolising of dust;
- effective cleaning of all surfaces that are difficult to reach manually;
- elimination of the use of detergents and conventional cleaning products;
- minimising the amount of used water per surface unit when cleaning;
- increased safety (no danger of slipping);
- avoiding of shoe prints and streaks after cleaning;
- avoiding of finger prints with skin grease or deposits of cooking grease.

[0068] With the intention of better showing the characteristics of the invention, a preferred embodiment of the method to clean surfaces in interior spaces according to the invention is described hereinafter, by way of an example without any limiting nature, with reference to the accompanying drawings wherein:

figure 1 schematically shows a perspective view of an electric atomizer for use in the method for cleaning according to the invention;

figure 2 schematically shows the application of the targeted atomization of spores of benign bacteria on a surface of an interior space;

figure 3 schematically shows the optional take-up of the applied spores of benign bacteria by means of a microfibre;

figure 4 shows the application on a climate ceiling of the method for cleaning according to the invention;

figure 5 shows a Sinner circle with the four factors that influence the cleaning.

[0069] In figure 1 an atomizer 1 is shown for the targeted atomization of a liquid with spores of benign bacteria 2 on all or certain types of surfaces 3 in an interior space. The electric atomizer 1 consists of a fan 4 which can blow air through a solution of benign bacteria 2, and targets it via a nozzle 5 on a chosen surface.

[0070] Figure 2 schematically shows the application of the method for the cleaning of a surface in an interior space, consisting of a targeted atomization by means of an electric atomizer 1, in which a liquid with spores of benign bacteria 2 up to a droplet size of 80 μm is atomized, whereby in this case an aqueous solution of spores of benign bacteria of the genus *Bacillus* is dissolved.

[0071] In figure 3 the use of a microfibre 6 to take up an atomized bacteria film 7 on a surface 3 is illustrated. The microfibre 6 can be wiped over the surface 3 that was sprayed to clean the surface 3 without the need to make it wet first.

[0072] Figure 4 shows the use of the method for the cleaning of a surface according to the invention, whereby in this case the surface 3 to be cleaned is a climate ceiling 8, which results in the cooling of an interior space. The distance between ceiling and climate ceiling is restricted, but can be cleaned by the targeted atomization of a solution with spores of benign bacteria possibly with 1% isopropyl-alcohol.

[0073] Figure 5 shows a Sinner circle 9 in which the four factors are presented which influence the cleaning. It concerns chemical cleaning products 10, the temperature 11 at which they are active, the time 12 during which they are active, and the mechanical treatment 13 with brushes or cloths required to clean a surface. Reduction of one of these factors must be compensated by increasing other factors to achieve the same result. Use of less strong chemicals will have to be compensated by allowing them to work over a longer period of time or at a higher temperature for example.

[0074] The present invention is by no means limited to the embodiments described as an example and shown in the figures, but such a method for the cleaning of surfaces in interior spaces can be realised without departing from the scope of the invention, as described in the following claims.

REFERENCES CITED IN THE DESCRIPTION

Cited references

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- [WO2006125283A1](#) [0022]
- [BE1018722A5](#) [0023]
- [EP2329893B1](#) [0024]
- [EP2863959A2](#) [0025]

Non-patent literature cited in the description

- **THIAGO et al.**J. Braz. Chem. Soc., 2016, vol. 27, 2229-238 [0064]
- **NISHIHARA T. et al.**Microbiol. Immunol., 1981, vol. 25, 8763-71 [0065]
- **DIDOUH N. et al.**Afr. J. Microbiol. Res., 2015, vol. 9, 257-65 [0065]
- **PRATT et al.**J.Am. Soc. Mass Spectrom., 2014, vol. 25, 5712-21 [0066]

FREMGANGSMÅDE TIL RENGØRING AF OVERFLADER I INDRE RUM OG I TEKNISK UDSTYR MED GODARTEDE BAKTERIER



Patentkrav

- 5 1. Fremgangsmåde til at mindske støvaflejringen på indre rum eller teknisk udstyr,
hvorved rengøring gøres hurtigere og hyppigheden af rengøring af indre rum eller
teknisk udstyr mindskes, hvor nævnte fremgangsmåde omfatter mindst følgende trin:
- 10 - målrettet forstøvning på overfladerne af en væske med sporer af godartede bakterier
på alle eller visse typer af overflader med hjælp af en elektrisk og/eller
trykluftdrevet forstøver samtidig med, at rummet forbliver tilgængeligt for
mennesker og dyr;
- 15 **kendetegnet ved, at** i aerosolen dannet ved forstøvning af væsken er dråberne mindre end eller
lig med 80 mikrometer og opnår den samme elektriske ladning igennem den balloelektriske
effekt, hvor nævnte samme elektriske ladning bliver fastholdt efter aerosolens sedimentering på
støv.
- 20 2. Fremgangsmåde i overensstemmelse med krav 1 **kendetegnet ved, at** koncentrationen
af sporer af godartede bakterier i den væske, der skal forstøves, ligger mellem 10^6
KVE/ml og 50×10^7 KVE/ml.
- 25 3. Fremgangsmåde i overensstemmelse med krav 1 **kendetegnet ved, at** den elektriske
forstøver er en ultralav-rumfangs forstøver, som danner en ret stråle med en rækkevidde
på indtil 15 meter eller mindre.
- 30 4. Fremgangsmåde i overensstemmelse med krav 3 **kendetegnet ved, at** den elektriske
og/eller trykluftdrevne forstøver forstøver væsken med sporer af godartede bakterier
på overfladen med en strømningshastighed på højst 300 ml i minuttet og en luftstrøm
på 0,2 liter i minuttet ved et tryk på højst 18 KPa.
5. Fremgangsmåde i overensstemmelse med krav 1 **kendetegnet ved, at** den efterfølges af
- manuel eller mekanisk rengøring af overfladerne ved hjælp af mikrofiber.

- 5 6. Fremgangsmåde i overensstemmelse med krav 1 **kendetegnet ved, at** mængden af forstøvet væske med sporer af godartede bakterier, påført pr. kvadratmeter behandlet overflade, udgør højst 10 gram pr. m², med det formål, at overfladen ikke kommer til at føles våd.
- 10 7. Fremgangsmåde i overensstemmelse med krav 6 **kendetegnet ved, at** sporer af de godartede bakterier i den forstøvede væske er valgt fra slægten *Bacillus* til anvendelse ved stuetemperatur.
- 15 8. Fremgangsmåde i overensstemmelse med krav 7 **kendetegnet ved, at** de godartede bakterier i den forstøvede væske valgt fra slægten *Bacillus* består af *Bacillus subtilis*, *Bacillus amyloliquefaciens*, *Bacillus pumilus*, *Bacillus licheniformis* eller *Bacillus megaterium* eller en kombination deraf.
- 20 9. Fremgangsmåde i overensstemmelse med krav 6 **kendetegnet ved, at** sporer af de godartede bakterier i den forstøvede væske er valgt fra sporer af aerobiske sporedannende kuldetålende bakterier af slægterne *Sporosarcina*, *Paenisporosarcina* eller *Paenibacillus* eller en kombination deraf til anvendelse i kolde omgivelser med temperaturer mellem 4 og 18°C.
- 25 10. Fremgangsmåde i overensstemmelse med krav 9 **kendetegnet ved, at** sporer af de godartede bakterier i den forstøvede væske valgt fra slægten *Sporosarcina* består af *Sporosarcina globispora*, *aquimarina* eller *psychrophila* eller en kombination deraf.
- 30 11. Fremgangsmåde i overensstemmelse med krav 9 **kendetegnet ved, at** sporer af godartede bakterier i den forstøvede væske valgt fra slægten *Paenisporosarcina* består af sporer af *Paenisporosarcina macmoerdoensis*.
12. Fremgangsmåde i overensstemmelse med krav 9 **kendetegnet ved, at** sporer af godartede bakterier i den forstøvede væske valgt fra slægten *Paenibacillus* består af sporer af *Paenibacillus glacialis*, *amylolyticus*, *pabuli*, *xylanexedens*, *castaneae* eller *macquariensis antarcticus* eller en kombination deraf.

13. Fremgangsmåde i overensstemmelse med krav 7 **kendetegnet ved, at** den forstøvede væske består af en opløsning af sporer af aerobiske sporedannende *Bacillus*-varianter opløst i demineraliseret vand med 1 % isopropyl-alcohol.
- 5 14. Fremgangsmåde i overensstemmelse med krav 7 **kendetegnet ved, at** den stimulerer de spirede sporens optag og fordøjelse af støv, fordi overfladeladningen af *Bacillus*-sporer opnået ved den balloelektriske effekt påvirker deres spiringshastighed gunstigt.
- 10 15. Anvendelse af fremgangsmåden i overensstemmelse med et hvilket som helst af de foregående krav **kendetegnet ved, at** fremgangsmåden anvendes til at mindske støvaflejringen i rum, som er utilgængelige til at blive nået med hånden til manuel rengøring.

DRAWINGS

*Fig. 1**Fig. 2*




Fig. 3





Fig. 4

*Fig.5*