



US012108314B2

(12) **United States Patent**  
**Sharifi et al.**

(10) **Patent No.:** **US 12,108,314 B2**

(45) **Date of Patent:** **\*Oct. 1, 2024**

(54) **PERSONALIZED ENTITY REPOSITORY**

(71) Applicant: **GOOGLE LLC**, Mountain View, CA (US)

(72) Inventors: **Matthew Sharifi**, Kilchberg (CH); **Jorge Pereira**, Seattle, WA (US); **Dominik Roblek**, Meilen (CH); **Julian Odell**, Kirkland, WA (US); **Cong Li**, Mountain View, CA (US); **David Petrou**, Brooklyn, NY (US)

(73) Assignee: **GOOGLE LLC**, Mountain View, CA (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/227,751**

(22) Filed: **Jul. 28, 2023**

(65) **Prior Publication Data**

US 2023/0379678 A1 Nov. 23, 2023

**Related U.S. Application Data**

(63) Continuation of application No. 17/397,666, filed on Aug. 9, 2021, now Pat. No. 11,716,600, which is a (Continued)

(51) **Int. Cl.**  
**H04W 4/021** (2018.01)  
**G06F 16/23** (2019.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **H04W 4/60** (2018.02); **G06F 16/23** (2019.01); **G06F 16/235** (2019.01);

(Continued)

(58) **Field of Classification Search**

CPC ..... H04W 4/60; H04W 4/029; H04W 4/18; G06F 16/907; G06F 16/23; G06F 16/587; (Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,731,844 A 3/1998 Rauch et al.  
5,946,647 A 8/1999 Miller et al.  
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1476567 2/2004  
CN 101075236 11/2007  
(Continued)

OTHER PUBLICATIONS

China National Intellectual Property Administration: Notice of Grant issued for Application No. 201680061369.0; 4 pages; dated Jan. 18, 2022.

(Continued)


*Primary Examiner* — Dai Phuong

(74) *Attorney, Agent, or Firm* — Gray Ice Higdon

(57) **ABSTRACT**

Systems and methods are provided for a personalized entity repository. For example, a computing device comprises a personalized entity repository having fixed sets of entities from an entity repository stored at a server, a processor, and memory storing instructions that cause the computing device to identify fixed sets of entities that are relevant to a user based on context associated with the computing device, rank the fixed sets by relevancy, and update the personalized entity repository using selected sets determined based on the rank and on set usage parameters applicable to the user. In another example, a method includes generating fixed sets of entities from an entity repository, including location-based sets and topic-based sets, and providing a subset of the fixed sets to a client, the client requesting the subset based on the

(Continued)



client's location and on items identified in content generated for display on the client.

**14 Claims, 9 Drawing Sheets**

**Related U.S. Application Data**

continuation of application No. 16/241,704, filed on Jan. 7, 2019, now Pat. No. 11,089,457, which is a continuation of application No. 14/962,415, filed on Dec. 8, 2015, now Pat. No. 10,178,527.

(60) Provisional application No. 62/245,241, filed on Oct. 22, 2015.

(51) **Int. Cl.**

**G06F 16/2457** (2019.01)  
**G06F 16/248** (2019.01)  
**G06F 16/587** (2019.01)  
**G06F 16/907** (2019.01)  
**G06F 16/9535** (2019.01)  
**G06V 20/62** (2022.01)  
**H04L 67/50** (2022.01)  
**H04W 4/029** (2018.01)  
**H04W 4/18** (2009.01)  
**H04W 4/60** (2018.01)

(52) **U.S. Cl.**

CPC .... **G06F 16/2358** (2019.01); **G06F 16/24578** (2019.01); **G06F 16/248** (2019.01); **G06F 16/587** (2019.01); **G06F 16/907** (2019.01); **G06F 16/9535** (2019.01); **G06V 20/62** (2022.01); **H04L 67/535** (2022.05); **H04W 4/029** (2018.02); **H04W 4/18** (2013.01)

(58) **Field of Classification Search**

CPC ..... G06F 16/235; G06F 16/9535; G06F 16/2358; G06F 16/24578; G06F 16/248; G06V 20/62; H04L 67/535  
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,662,226 B1 12/2003 Wang et al.  
 7,054,917 B1 5/2006 Kirsch et al.  
 7,421,153 B1 9/2008 Ronca et al.  
 7,548,915 B2 6/2009 Ramer et al.  
 7,822,759 B2 10/2010 MacLaurin et al.  
 7,917,514 B2 3/2011 Lawler et al.  
 8,150,911 B2 4/2012 Bell et al.  
 8,204,966 B1 6/2012 Mendis et al.  
 8,255,386 B1 8/2012 Annau et al.  
 8,280,414 B1 10/2012 Nourse et al.  
 8,341,156 B1 12/2012 Westgate et al.  
 8,347,237 B2 1/2013 Bier et al.  
 8,418,055 B2 4/2013 King et al.  
 8,452,799 B2 5/2013 Zhou et al.  
 8,468,110 B1 6/2013 Podgorny et al.  
 8,571,319 B2 10/2013 Balasubramanian et al.  
 8,645,325 B2 2/2014 Anderson et al.  
 8,671,341 B1 3/2014 Hellwig et al.  
 8,700,604 B2 4/2014 Roseman et al.  
 8,713,004 B1\* 4/2014 Hands ..... G06F 16/9537  
 707/727  
 8,767,497 B2 7/2014 Marumoto et al.  
 8,832,116 B1 9/2014 Chu  
 8,954,836 B1 2/2015 Look et al.  
 8,977,639 B2 3/2015 Petrou et al.  
 9,165,406 B1 10/2015 Gray et al.

9,274,839 B2 3/2016 Schuessler et al.  
 9,354,778 B2 5/2016 Cornaby et al.  
 9,703,541 B2 7/2017 Sharifi et al.  
 9,715,553 B1\* 7/2017 Singleton ..... G06F 16/9537  
 9,762,651 B1 9/2017 Sharifi et al.  
 10,178,527 B2 1/2019 Sharifi et al.  
 11,089,457 B2 8/2021 Sharifi et al.  
 2004/0117750 A1 6/2004 Skoll et al.  
 2005/0083413 A1 4/2005 Reed et al.  
 2006/0047639 A1 3/2006 King et al.  
 2006/0080594 A1 4/2006 Chavoustie et al.  
 2006/0106844 A1 5/2006 Naick et al.  
 2006/0156222 A1 7/2006 Chi et al.  
 2006/0221409 A1 10/2006 Cohen et al.  
 2006/0253491 A1 11/2006 Gokturk et al.  
 2007/0008321 A1 1/2007 Gallagher et al.  
 2007/0047781 A1 3/2007 Hull et al.  
 2007/0143345 A1 6/2007 Jones et al.  
 2007/0168379 A1 7/2007 Patel et al.  
 2008/0010605 A1 1/2008 Frank  
 2008/0046175 A1\* 2/2008 Tengler ..... G01C 21/3647  
 701/414  
 2008/0176606 A1 7/2008 Kim  
 2008/0235018 A1 9/2008 Eggen et al.  
 2008/0275701 A1 11/2008 Wu et al.  
 2008/0281974 A1 11/2008 Slothouber et al.  
 2008/0301101 A1 12/2008 Baratto et al.  
 2009/0005003 A1 1/2009 Hartwell  
 2009/0006388 A1 1/2009 Ives et al.  
 2009/0036215 A1 2/2009 Saeki  
 2009/0063431 A1 3/2009 Erol et al.  
 2009/0228573 A1 9/2009 Asakawa et al.  
 2009/0282012 A1 11/2009 Konig et al.  
 2009/0319449 A1 12/2009 Gamon et al.  
 2010/0060655 A1 3/2010 Huang  
 2010/0088612 A1 4/2010 Jia et al.  
 2010/0250598 A1 9/2010 Brauer et al.  
 2010/0262928 A1 10/2010 Abbott  
 2010/0325127 A1 12/2010 Chaudhuri et al.  
 2011/0072455 A1 3/2011 Pickelsimer et al.  
 2011/0123115 A1 5/2011 Lee et al.  
 2011/0125735 A1 5/2011 Petrou  
 2011/0128288 A1 6/2011 Petrou et al.  
 2011/0131160 A1 6/2011 Canny et al.  
 2011/0131235 A1 6/2011 Petrou et al.  
 2011/0145692 A1 6/2011 Noyes et al.  
 2011/0225152 A1 9/2011 Beaudreau et al.  
 2011/0238768 A1 9/2011 Habets et al.  
 2011/0246471 A1 10/2011 Rakib  
 2011/0307478 A1 12/2011 Pinckney et al.  
 2011/0307483 A1 12/2011 Radlinski et al.  
 2011/0313657 A1\* 12/2011 Myllymaki ..... H04W 4/18  
 701/438  
 2012/0044137 A1 2/2012 Oddiraju et al.  
 2012/0083294 A1 4/2012 Bray et al.  
 2012/0117058 A1 5/2012 Rubinstein et al.  
 2012/0158751 A1 6/2012 Tseng  
 2012/0194519 A1 8/2012 Bissell et al.  
 2012/0239761 A1 9/2012 Linner et al.  
 2012/0303615 A1 11/2012 Goswami et al.  
 2013/0073988 A1 3/2013 Groten et al.  
 2013/0080447 A1 3/2013 Ramer et al.  
 2013/0091463 A1 4/2013 Nordstrom et al.  
 2013/0097507 A1 4/2013 Prewett  
 2013/0108161 A1 5/2013 Carr  
 2013/0111328 A1 5/2013 Khanna et al.  
 2013/0117252 A1 5/2013 Samaddar et al.  
 2013/0173604 A1 7/2013 Li et al.  
 2013/0254217 A1 9/2013 Xu  
 2013/0263098 A1 10/2013 Duda et al.  
 2013/0290110 A1 10/2013 LuVogt et al.  
 2013/0325329 A1 12/2013 Gupta  
 2013/0325844 A1 12/2013 Plaisant  
 2013/0346431 A1 12/2013 Erol et al.  
 2014/0029810 A1 1/2014 Barr et al.  
 2014/0040272 A1 2/2014 Houghton  
 2014/0082670 A1 3/2014 Papish  
 2014/0089626 A1 3/2014 Schuessler et al.  
 2014/0118597 A1 5/2014 Tabak et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0142922	A1	5/2014	Liang et al.	
2014/0146200	A1	5/2014	Scott et al.	
2014/0152655	A1	6/2014	Johnston et al.	
2014/0157210	A1	6/2014	Katz et al.	
2014/0188889	A1	7/2014	Martens et al.	
2014/0250147	A1	9/2014	Shapira et al.	
2014/0279013	A1	9/2014	Chelly et al.	
2014/0282660	A1	9/2014	Oztaskent et al.	
2014/0316890	A1	10/2014	Kagan	
2014/0317104	A1*	10/2014	Isaacs .....	G06F 16/332 707/728
2014/0366158	A1	12/2014	Han et al.	
2015/0016700	A1	1/2015	Drozdzal et al.	
2015/0019997	A1	1/2015	Kim et al.	
2015/0095855	A1	4/2015	Bai et al.	
2015/0100524	A1	4/2015	Pantel et al.	
2015/0169701	A1	6/2015	Stekkelpak et al.	
2015/0178786	A1	6/2015	Claessens	
2015/0212695	A1	7/2015	Nordstrom et al.	
2015/0285652	A1*	10/2015	Peri .....	G01C 21/3476 701/438
2015/0317649	A1	11/2015	Joshi et al.	
2016/0055246	A1	2/2016	Marcin et al.	
2016/0065628	A1	3/2016	Guo	
2016/0077526	A1	3/2016	Sisbot	
2016/0098640	A1	4/2016	Su	
2016/0140671	A1	5/2016	Hong	
2016/0321052	A1	11/2016	Sharifi et al.	
2016/0360382	A1*	12/2016	Gross .....	G06F 9/453
2017/0098159	A1	4/2017	Sharifi et al.	
2017/0139879	A1	5/2017	Sharifi et al.	
2017/0293950	A1	10/2017	Rathod	
2019/0028418	A1	1/2019	Ban	
2019/0220616	A1	7/2019	Lacey	
2021/0368313	A1	11/2021	Sharifi et al.	

FOREIGN PATENT DOCUMENTS

CN	101201827	6/2008
CN	101587495	11/2009
CN	101763357	6/2010
CN	103888455	6/2014
CN	104036002	9/2014
CN	104486350	4/2015
CN	104838413	8/2015
EP	2306290	4/2011
EP	2466921	6/2012
EP	2728481	5/2014
EP	2824558	1/2015
JP	201196173	5/2011
RU	2383921	3/2010
WO	03088080	10/2003
WO	2009054619	4/2009
WO	WO2010006241	1/2010

WO	WO2010091320	8/2010
WO	2012075315	6/2012
WO	2013172958	11/2013
WO	2013173940	11/2013
WO	WO2013173626	11/2013
WO	2014105922	7/2014
WO	2014146265	9/2014
WO	2016064857	4/2016

OTHER PUBLICATIONS

Intellectual Property India; Examination Report issued in Application No. IN202148009718; 7 pages; dated Feb. 17, 2022.

Great Britain Patent Office; Examination Report issued in Application No. 1806100.2; 7 pages; dated Jun. 25, 2021.

European Patent Office; Intention to Grant issued in Application No. 16858056.1; 53 pages; dated Jun. 10, 2021.

China National Intellectual Property Administration; Notification of First Office Action issued in Application No. 201680061369.0; 27 pages; dated Apr. 15, 2021.

Intellectual Property India; Examination Report issued for Application No. 201747044773 dated Aug. 26, 2020.

European Patent Office; Examination Report issued for Application No. 16858056.1 dated Jun. 8, 2020.

The Japanese Patent Office; Notice of Allowance issued in Application No. 2018-520605; 3 pages; dated Jan. 6, 2020.

The Korean Patent Office; Notice of Allowance issued in Application No. 10-2018-7014398 dated Nov. 13, 2019.

The European Patent Office; Extended European Search Report issued in Application No. 16858056.1 dated Apr. 1, 2019.

The Japanese Patent Office; Office Action issued in Application No. 2018-520605 dated Jun. 17, 2019.

The Russian Patent Office; Decision to Grant issued in Application No. 2018113725 dated May 20, 2019.

The Korean Patent Office; Office Action issued in Application No. 10-2018-7014398 dated Apr. 30, 2019.

Russian Patent Office; Office Action issued in Application No. 2018113725 dated Feb. 11, 2019.

Collobert, et al.; Natural Language Processing (almost) from Scratch; Journal of Machine Learning Research; vol. 12; pp. 2493-2537; dated Aug. 1, 2011.

Hsu, et al.; Snap2Read: Automatic Magazine Capturing and Analysis for Adaptive Mobile Reading; Lecture Notes in Computer Science; vol. 6524; 11 pages; dated 2011.

Minkov, et al.; Extracting Personal Names from Email: Applying Named Entity Recognition to Informal Text; Proceedings of Human Language Technology Conference and Conference on Empirical Methods in Natural Language Processing; 8 pages; dated Oct. 1, 2005.

Adistambha, et al.; Efficient multimedia query-by-content from mobile devices; Computers & Electrical Engineering, vol. 36, No. 4; 6 pages; dated 2010.

\* cited by examiner




FIG. 1




FIG. 3




FIG. 2




FIG. 5




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

**PERSONALIZED ENTITY REPOSITORY**

## BACKGROUND

The use of mobile devices, such as smart phones, wearable devices, tablets, laptops, etc., has been increasing. By understanding the content viewed by and actions taken by a user, the mobile device can build a much better user experience, for example by offering personalized predictions and assistance to the user. Part of understanding the content and actions involves identifying and classifying entities recognized in the content of the device screen. The entities may exist in an entity repository, such as a knowledge base or vision model, which stores facts and information about entities. Large, public entity repositories may include millions of such entities. Most computing devices, especially mobile computing devices, such as smart phones and tablets, have limited storage and use the entity repository via a connection with a server.

## SUMMARY

Implementations divide an entity repository into several fixed sets or slices. A set may be location-based, topic-based, action-based, or functional. The system may determine the sets at a server and provide only those sets to a client device that are relevant to that particular client. The sets downloaded to the client are a personalized entity repository that can be accessed without connection to the server. The client device may include a set identification engine. The set identification engine may include a prediction model that predicts one or more sets given some text, images, or other features. The prediction model may be used to determine which sets are most beneficial to the user. The set identification engine may also track a location of the user to determine which location sets may be most relevant.

Sets may be ranked for the user of the client device, e.g., based on the user's location, a user's search history, content the user has been viewing on the device, time of day, signals from other devices, etc. Thus, for example, if a user begins researching a trip to Hawaii, the system may determine that a set with entities related to Hawaii is particularly relevant to the user. If a user flies from New York to Los Angeles, the system may determine location sets for Los Angeles are relevant. The client device may use the rankings to determine which sets to retrieve and which to delete from memory. For example, if a set previously downloaded is no longer relevant, the system may remove that set to make room for another set. The system may employ set usage parameters to determine which sets to include in the personalized entity repository at any time. In some implementations, the user may establish and control the set usage parameters. Updating a set may include determining a delta for the set to reduce the data transferred to the client device. In some implementations, the sets may be versioned, e.g., so that a schema change does not break the applications using the model.

According to certain aspects of the disclosure, a mobile device comprises a display device, a personalized entity repository stored in memory, the personalized entity repository including a plurality of fixed sets of entities from an entity repository stored at a server, wherein each fixed set has a respective identifier and includes information about the entities in the set, at least one processor, and memory storing instructions that, when executed by the at least one processor, cause the mobile device to perform operations. The operation include identifying fixed sets of the entity repository

that are relevant to a user of the mobile device based on context associated with the mobile device, ranking the fixed sets by relevancy, determining selected sets from the identified fixed sets using the rank and set usage parameters applicable to the user, and updating the personalized entity repository using the selected sets.

According to certain aspects of the disclosure, a method includes receive a screen captured image configured to display content on a display of a mobile device, determining text in the image by performing text recognition on the image, providing the text to a set prediction model, wherein the set prediction model is trained to predict one or more fixed sets of entities, and storing at least one fixed set of entities of the predicted fixed sets of entities in a personalized entity repository in memory on the mobile device.

According to certain aspects of the disclosure, a method may include generating a plurality of fixed sets of entities from an entity repository. The fixed sets include location-based sets, each location-based set including entities from the entity repository that have a location inside a cell, the cell being associated with the set, and topic-based sets, at least some of the topic-based sets including entities from the entity repository that are related to each other via an embedding similarity. The method may also include providing a subset of the fixed sets of entities to a client device, the client device requesting the subset based on a location of the client device and on recognized items identified in content generated for display on the client device.

In one general aspect, a computer program product embodied on a computer-readable storage device includes instructions that, when executed by at least one processor formed in a substrate, cause a computing device to perform any of the disclosed methods, operations, or processes. Another general aspect includes a system and/or a method for generating fixed sets of entities in an entity repository and providing some of the fixed sets to a personal computing device as a personal entity repository, substantially as shown in and/or described in connection with at least one of the figures, and as set forth more completely in the claims.

One or more of the implementations of the subject matter described herein can be implemented so as to realize one or more of the following advantages. As one example, generating fixed sets of entities enables the system to provide personal or custom entity repositories in a scalable way. The customized entity repository can aid in on-device text analysis and image analysis to support user assistance capabilities even without connectivity to a network. The user may control the amount of resources dedicated to the personal entity repository and the system may automatically determine which sets best utilize the allocated resources. As another example, the system may predict which sets are most relevant to a user. The prediction may be based on a number of factors specific to the user and/or the personal computing device, such as location, time of day, signals from other computing devices associated with the user or known to the device, recent activity on the computing device, etc. As another example, implementations may support versioning of the sets, so that a change that restructures the information in the set does not break applications that use the set.

The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

## BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram illustrating an example system in accordance with the disclosed subject matter.

FIG. 2 illustrates an example display of a user interface for specifying set usage parameters for a personalized entity repository, in accordance with the disclosed subject matter.

FIG. 3 illustrates an example display of content that provides context for determining which sets are most relevant to a user of the computing device, in accordance with disclosed implementations.

FIG. 4 illustrates an example display of a user interface for suggesting additional sets for inclusion in a personalized entity repository, in accordance with disclosed implementations.

FIG. 5 illustrates another example display of a user interface for suggesting additional sets for inclusion in a personalized entity repository, in accordance with disclosed implementations.

FIG. 6 illustrates a flow diagram of an example process for generating and updating fixed sets of entities, in accordance with disclosed implementations.

FIG. 7 illustrates a flow diagram of an example process for building a personal entity repository using fixed sets of entities, in accordance with disclosed implementations.

FIG. 8 illustrates a flow diagram of an example process for identifying fixed sets of entities relevant to a user of a client device, in accordance with disclosed implementations.

FIG. 9 illustrates a flow diagram of an example process for selecting fixed sets of entities from fixed sets of entities relevant to a user of a client device based on set usage parameters, in accordance with disclosed implementations.

FIG. 10 shows an example of a computer device that can be used to implement the described techniques.

FIG. 11 shows an example of a distributed computer device that can be used to implement the described techniques.

Like reference symbols in the various drawings indicate like elements.

### DETAILED DESCRIPTION

FIG. 1 is a block diagram of a personal entity repository system in accordance with an example implementation. The system 100 may be used to build a personalized entity repository from selections of pre-computed or fixed sets of entities. The sets are fixed in the sense that they are computed ahead of any particular request for a set, or in other words are not generated in response to a request for a set. The system 100 may determine which sets are most useful at a particular point in time and may update the personalized entity repository to ensure entities in the personalized repository are relevant to the user. Updating the personalized entity repository includes deleting sets that are less relevant to the user now than before and adding new sets that have become relevant. The personalized entity repository may be used to determine entities in content generated for display on a computing device to personalize a user experience on the computing device. Personalizing the user experience can include predicting actions, topics, words, or phrases, etc. The system 100 in FIG. 1 is illustrated as a client-server system, with some data processing or data storage occurring at a server 110 and other data processing occurring at the client device 150. However, other configurations and applications may be used and implementations are not limited to the exact configurations illustrated.

The personalized entity repository system 100 may include a server 110, which may be a computing device or devices that take the form of a number of different devices, for example a standard server, a group of such servers, or a rack server system. For example, server 110 may be imple-

mented in a distributed manner across multiple computing devices. In addition, server 110 may be implemented in a personal computer, for example a laptop computer. The server 110 may be an example of computer device 900, as depicted in FIG. 9, or computer device 1100, as depicted in FIG. 11. Server 110 may include one or more processors formed in a substrate configured to execute one or more machine executable instructions or pieces of software, firmware, or a combination thereof. The processors can be semiconductor-based that is, the processors can include semiconductor material that can perform digital logic.

The server 110 may store or have access to entity repository 130. The entity repository 130 may store information about entities. An entity may be a person, place, item, idea, topic, word, phrase, abstract concept, concrete element, other suitable thing, or any combination of these. In some implementations, the entity repository 130 may be a knowledge base, which stores information about entities. In some implementations, a knowledge base stores information about entities in the form of relationships between entities. For example, entities in a knowledge base may be related to each other by labeled edges that represent relationships. The knowledge base may also store attributes of an entity. Some knowledge bases are large, sometimes including millions of entities. A knowledge base with a large number of entities and even a limited number of relationships may have billions of connections.

The entity repository 130 may also include image recognition entities that can be used to identify an entity in an image. For example, the entity repository 130 may include entities that represent known images of the entity and/or characteristics of the image and are used in image recognition processes (e.g., using image similarity techniques) to identify entities in images. For example, the characteristics may be features provided to an image recognition model (e.g., machine learning algorithm). The entity repository 130 may represent a single knowledge base, a combination of distinct knowledge bases, image recognition entities, and/or a combination of a knowledge base and image information. In some implementations, entity repository 130 may be stored in an external storage device accessible to server 110. In some implementations, the entity repository 130 may be distributed across multiple storage devices and/or multiple computing devices, for example multiple servers. The entities and relationships in a knowledge base may be searchable, e.g., via an index. For example, the index may include text by which an entity has been referred to. Thus, reference to the knowledge base may be understood to include an index that facilitates finding an entity using a text equivalent.

The server 110 can also include one or more computer memories. The memories, for example, a main memory, may be configured to store one or more pieces of data, either temporarily, permanently, semi-permanently, or a combination thereof. The memories may include any type of storage device that stores information in a format that can be read and/or executed by the one or more processors. The memories may include volatile memory, non-volatile memory, or a combination thereof, and store modules or engines that, when executed by the one or more processors, perform certain operations. In some implementations, the modules may be stored in an external storage device and loaded into the memory of server 110. In some implementations, the modules may include entity set generation engine 120. The entity set generation engine 120 may divide entities in an entity repository 130 into fixed entity sets 132. Each set in the fixed entity sets 132 may be thought of as a slice of the entity repository 130 that includes entities related by some

criteria. In some implementations a slice may contain meta-data about an entity (e.g., name, description, canonical image), relationships with other entities, and/or information used to detect the entity in text, such as common names, aliases, abbreviations, nicknames, and other signals. Each fixed set of entities in the fixed entity sets **132** may have an identifier so that a particular set can be tracked, identified, and requested by applications or client devices.

In some implementations, the entity set generation engine **120** may generate various types of sets, such as location-based sets, topic-based sets, or functional sets. A location-based set may include entities associated with a particular geographic cell. A geographic cell is an area of the surface of the earth defined by boundaries, for example two lines of latitude and two lines of longitude. Such cells are common for map applications, such as GOOGLE MAPS. A location-based fixed set of entities may include any entities known to be located within the cell. The entity repository **130** may include an attribute that specifies a location for an entity or may include metadata identifying the location. For example, a restaurant entity in entity repository **130** may have a location attribute specifying a particular geo cell or cells or latitude/longitude coordinates. While geo cells, i.e., cells used in a map application, are typically of similar size, location-based entity sets need not correspond to one geo cell but may be based, instead, on an area having a specified number of entities located within the area. Thus, for instance, a cell for a location-based set of entities in New York City may be quite small (e.g., ten square miles) because it is densely populated while a cell for a location-based set of entities in western Wyoming may be hundreds of square miles but have the same number of entities as the cell in New York City. Thus, for example, the entity set generation engine **120** may merge adjacent geo cells until the quantity of entities associated with the merged cell reaches a minimum quantity and fauns a location-based cell for a fixed set of entities.

The entity set generation engine **120** may also generate topic-based fixed sets of entities. In some implementations, the entity set generation engine **120** may generate topic-based sets by clustering the entities using conventional clustering techniques based on how related entities are. For example, the clustering may be based on characteristics of the entities, e.g., embeddings, trained on search records or on text such as text from documents indexed for a search engine. In some implementations, the entity set generation engine **120** may be given a seed entity and may form a cluster based on the seed entity. In some implementations, one or more topic-based sets may be based on collections identified in the entity repository. For instance, entities in the entity repository **130** may include an indication of one or more collections that the entity belongs to or the entity repository **130** may include a collection definition, or in other words requirements for inclusion in the collection, and entities may be evaluated against the requirements to determine membership in the collection. The entity set generation engine **120** may use entity membership in the collection to generate one or more of the topic-based sets. In some implementations, the entity set generation engine **120** may compute an embedding for each topic-related slice. The embedding may be used to compute similarity with a query embedding, e.g., generated by a set identification engine, to determine which sets are most similar to the query embedding. For example, the embedding may represent a cluster center.

The entity set generation engine **120** may also generate functional sets of entities. A functional set may include

entities that are deemed most popular, e.g., entities that are most frequently searched for or accessed, for example based on appearance in search queries. A functional set may also be based on a capability, for example the capability to translate from one language to another. As another example, a functional set may include entities likely to be encountered when using or requested by a particular application. Of course, these functional sets are provided as examples only and functional entity sets may include any collection of entities common to a particular purpose, characteristic, or function. In some implementations, the entity set generation engine **120** may generate fixed sets of entities that are combinations of the above. For example, the entity set generation engine **120** may generate a fixed set of entities for restaurants in San Jose California or another set for artwork recognition in Paris France. In some implementations, the entity set generation engine **120** may include a user interface that enables a user to curate one or more fixed sets of entities.

The entity set generation engine **120** may also update the fixed sets of entities **132** periodically. For example, as entities are added, deleted, or updated in the entity repository **130** the entity set generation engine **120** may determine changes to the fixed sets. In some implementations, the entity set generation engine **120** may determine deltas for each set, for example a list of entities to be deleted from the fixed set and a list of entities to be added to the fixed set. The entity set generation engine **120** may provide the deltas to the client device **150**, either as a push or a pull. The deltas reduce the amount of data transmitted between the server **110** and the client device **150** while still enabling the client device **150** to have the most current entity sets. This is especially useful when a particular fixed entity set changes often, such as a set of entities that represents movies. In some implementations, the entity set generation engine **120** may also version each of the fixed sets, also referred to as slices. For example, the entity set generation engine **120** may change the data format of the slices or may change the slices in another way that breaks the schema. When the schema is broken the applications that uses the slices may need a corresponding update to use the new slices. Accordingly the entity set generation engine **120** may version the fixed sets so that applications that have not been updated may continue to use older versions without malfunctioning. In some instances, the client device **150** may include two versions of the same fixed slice (e.g., a slice representing a particular location), until applications that use the old schema are updated.

In some implementations, the entity set generation engine **120** may also train and maintain a set prediction model **122**. A set prediction model, such as set prediction model **122**, may be any type of machine-learning algorithm, such as a long short-term memory (LSTM) neural network, feed-forward neural network, a support vector machine (SVM) classifier, etc., that can predict a fixed set of entities given a set of features or signals. The features may include a device location, text or images in content (e.g., documents, search records, etc.), applications typically used for various tasks, etc. As a machine-learning algorithm, the set prediction model has two modes, a training mode and an inference mode. For example, in the training mode the set prediction model **122** may use labeled search records **134** and labeled crawled documents **136** to predict one or more fixed sets of entities from fixed entity sets **132** given a set of signals. The labels may be created automatically or by human experts. The signals may be taken from content generated on a client device, such as device **150** or from search records, such as

search records **134** or user-specific records such as screen capture index **172**. In a training mode the set prediction model **122** may also take in a location as a signal (e.g., current geo cell location, coordinates, etc.) to predict a set of entities for the given location. During training the parameters of the model are updated to better reflect the labels assigned to text in the training documents. In an inference mode, the set prediction model **122** will predict one or more fixed entity sets from fixed entity sets **132** in response to a set of features that represents the signals. Each predicted set may have an associated confidence score or probability score indicating a level of certainty that the features provided predict the particular fixed set of entities. In some implementations, the confidence score may be based on a similarity measure which may differ depending on the type of set. For example, the confidence score for a location-based sets may be based on physical distance from a specified location, e.g., the current location of a computing device. The confidence score for a topic-based set may be based on an embedding distance with a query, such as an embedding generated based on signals from a client device. Such signals can include text recently seen on the screen, the state or proximity of external devices, content of recent searches, stated user interests, an application installed or executing on the client device, a time stamp, etc.,

Once trained, and then on a periodic basis to account for updates, the entity set generation engine **120** may provide the set prediction model **122** to the client device **150**. The client device **150** may store the model as set prediction model **164**. In some implementations, the client device **150** may personalize the set prediction model **164** by performing further training. The training may use information from search records associated with the user, for example from search records stored at client device **150** or screen capture index **172**. Thus the set prediction model **164** may be a copy of set prediction model **122** or a personalized copy of set prediction model **122**.

The server **110** may include search records **134** and crawled documents **136**. The search records **134** may include search logs, aggregated data gathered from queries, or any other data based on queries. In some implementations, the search records **134** may be generated by a search engine in the normal process of generating search results. In some implementations, the search records **134** may be stored on a different computing device that is accessible to server **110**. In some implementations, the search records may be distributed across a plurality of computing devices. The crawled documents **136** may be documents obtained using known or later developed web-crawling techniques, for example. In some implementations, the crawled documents **136** represent documents available over the Internet and may be an indexed form of the documents.

The personalized entity repository system **100** may include a computing device **150**. Computing device **150** may be any mobile computing device, such as a smartphone or other handheld computing device, a tablet, a wearable computing device, etc., that operates in a closed mobile environment rather than a conventional open web-based environment. Computing device **150** may also be other types of personal electronic computing devices, such as a laptop or net-based computer, a desktop computer, a television with a processor, etc. Computing device **150** may be an example of computer device **1000** or **1050**, as depicted in FIG. **10**. Computing device **150** may be a computing device used by a single user, or can be a computing device shared by multiple users.

Computing device **150** may include one or more processors formed in a substrate configured to execute one or more machine executable instructions or pieces of software, firmware, or a combination thereof. The processors can be semiconductor-based—that is, the processors can include semiconductor material that can perform digital logic. The computing device **150** may thus include one or more computer memories configured to store one or more pieces of data, either temporarily, permanently, semi-permanently, or a combination thereof. The computing device **150** may thus include applications **155**, which represent machine executable instructions in the form of software, firmware, or a combination thereof. The components identified in the applications **155** may be part of the operating system or may be applications developed to run using the operating system. In some implementations, applications **155** may be mobile applications. Conventionally, mobile applications operate in a closed environment, meaning that the user employs separate applications to perform activities conventionally performed in a web-based browser environment. For example, rather than going to bookit.com to book a hotel, a user of the computing device **150** can use a mobile application in applications **155** provided by bookit.com. Applications **155** may also include web applications, which may mirror the mobile application, e.g., providing the same or similar content as the mobile application. In some implementations, the applications **155** may include functions performed by an operating system of the computing device **150**.

The applications **155** may include a screen content agent **160** and a set identification engine **162**. In some implementations, one or more of these applications can be provided by the operating system (not shown) of the computing device **150**. In some implementations, one or more of these applications can be downloaded and installed by the user.

The screen content agent **160** can include various functionalities. In some implementations, the screen content agent **160** may be configured to get textual information represented on the screen of the computing device from an application program interface (API). In some implementations, the screen content agent **160** may be built into the operating system, which can determine the content of text fields displayed on the screen. The textual information may be considered screen captured content, and each call to the API or each time the content of text fields is determined may be considered a screen capture. In some implementations, the screen content agent **160** may be configured to capture the image displayed on the screen by copying or reading the contents of the device's frame buffer. Thus, the captured screen may be an image and may be referred to as a captured image. The screen content agent **160** may capture the screen at intervals. The interval can be small, for example every half second or every second. In some implementations, the screen content agent **160** may be configured to capture the screen every time a touch event occurs (e.g., every time the user touches the screen to scroll, zoom, click a link etc.), in response to an explicit user request or command, or when the device transitions from one mobile application to another mobile application. In some implementations, the screen content agent **160** may increase the interval at which a screen capture occurs when the screen does not change. In other words, when the screen is static, the screen content agent **160** may capture images less often.

The screen content agent **160** may provide the captured content or screen images and metadata to a recognition engine, which may be part of the screen content agent **160** and located on the computing device **150**. In some implementations, the recognition engine may be located at a

server, such as server **110**. When a screen capture image is provided to the recognition engine, the recognition engine may perform image and text recognition on the image to identify words, entities, logos, etc. in the content of the screen capture image. The recognition engine may be configured to perform various types of recognition, such as character recognition, image recognition, logo recognition, etc., using conventional or later developed techniques. Thus, the recognition engine may generate recognized content, which can be from words as well as from images.

The screen content agent **160** may also determine and use metadata about the screen capture image. The metadata may include the timestamp, the mobile device type, a mobile device identifier, the mobile application running when the content was captured, e.g., the application that rendered the content displayed on the screen, etc. In some implementations, the metadata may also include which applications are active, the location of the device, ambient light, motion of the device, etc. In some implementations, the metadata may include signals from other computing devices. For example, the screen content agent **160** may be provided or may obtain information from external devices such as appliances, televisions, personal assistants, music devices, alarm systems, etc., that are configured to communicate with the client device **150**. For instance, a voice-activated electronic list making device may store a list of grocery items to be purchased. This list may be transmitted to the client device **150** either directly from the electronic list making device or via user account information. As another example, a user may have a tablet and a smartphone that share information or a husband and a wife may have smartphones that share information. Thus, in some implementations, the information available to the client device **150** may include information that is provided by other devices. Some or all of this information can be included in metadata associated with a screen capture image.

The system may use the metadata and information obtained via the screen capture image to assist in on-device intelligence that analyzes the information to assist the user with tasks performed on the mobile device. For example, a user having a conversation with a friend may include the suggestion to see a movie. On-device intelligence may identify the suggestion and offer an action for viewing a movie review or for buying tickets. The screen content agent **160** may use an entity repository to determine whether recognized content includes known entities. While the screen content agent **160** may use a public entity repository, such as entity repository **130**, this requires a connection with server **110** and can slow down the recognition and action suggestion process. Accordingly, the client device **150** may have a personalized entity repository **176**, stored on the client device **150**. The personalized entity repository **176** may be a collection of fixed sets of entities, which are obtained from the server **110**, for example from fixed entity sets **132**. The personalized entity repository **176** may be generated and maintained by the set identification engine **162**.

In some implementations, the screen content agent **160** can include an indexing engine configured to index the captured content. The index may also associate a screen capture image with the text, entities, images, logos, etc. identified in the image. Thus, for example, the indexing engine may generate index entries (e.g., stored in screen capture index **172**) for a captured image and captured content. In some implementations the indexing engine may be on a server, such as server **110**, and the screen content agent **160** may provide the captured image and captured

content to the server. The index may be an inverted index, where a key value (e.g., word, phrase, entity, image, logo, etc.) is associated with a list of images (e.g., copies of the captured screen images) that include the key value. The index may include metadata (e.g., where on the captured image the key value occurs, a rank for the key value for the image, etc.) associated with each captured image in the list. In some implementations, the index may also include a list of captured images indexed by a timestamp. The indexing engine may store the index in memory, for example in screen capture index **172**. Of course, in some implementations the system may store the index in a user account on a server in addition to or instead of on the computing device **150**. The user of the computing device **150** may control when the screen content agent **160** is active. For example, the user may specify that the screen content agent **160** is active only when other specified applications **155** are running (e.g., only when in a social media mobile application). The user may also manually turn the screen content agent **160** on and off, for example via a settings application. In some implementations, the user may invoke the screen content agent **160** with a gesture or action. Disabling the screen content agent **160** may also disable the prediction and maintenance of the personalized entity repository described herein.

The computing device **150** may also include a set identification engine **162**. The set identification engine **162** may be configured to determine which sets of entities in the fixed entity sets **132** should be included in the personalized entity repository **176**. The set identification engine **162** may use information collected or generated by the screen content agent **160** as well as a set prediction model **164** and set usage parameters to determine which sets are potentially relevant to the user and obtain those sets from the server **110**. For example, the set identification engine **162** may collect signals as input for the set prediction model **164**. The signals can include information and metadata such as device location, a time of day, the state of various external devices in communication with the client device **150**, proximity to other devices, information from content in a screen capture image or a series of screen capture images, information from the screen capture index **172** or search records for the user, information in a user profile, etc. As explained above, external devices such as appliances, televisions, personal assistants, music devices, alarm systems, etc., may be configured to communicate with and provide status information to the client device **150** and the status information may be included in the signals generated by the identification engine **162**. The information used to generate signals may be stored as metadata in the screen capture index **172** or generated/collected at the time the set identification engine **162** determines the fixed sets of entities appropriate for the personalized entity repository **176**.

As discussed earlier, the set prediction model **164** may be a copy of set prediction model **122** or may be a personalized version of set prediction model **122**. When prediction model **164** is a personalized version, the set identification engine **162** may provide training examples from data stored on the client device **150** or from a user profile associated with the user of client device **150**. For example, the training examples may be generated using the screen capture index **172** or search records for the user **180**. In some implementations, the client device, with user permission, may provide updates to the set prediction model **122** on the server **110** so that the set prediction model can learn from predictions made over many client devices.

The set identification engine **162** may provide signals, for example as a set of features, to the set prediction model **164**

in an inference mode. In response, the set prediction model 164 may then provide the identifiers of one or more predicted fixed sets of entities to the set identification engine 162. The set identification engine 162 may then rank the predicted fixed sets of entities. The client device 150 may be a device with a small form factor, which limits storage space on the device. Accordingly, the set identification engine 162 may rank the predicted fixed sets of entities to determine which fixed sets to include in personalized entity repository 176. In some implementations, the set identification engine 162 may work within set usage parameters selected by the user of the client device. The set usage parameters may include a maximum quantity of fixed sets to store on the client device, a maximum amount of storage used by the personalized entity repository 176, a minimum rank, or a combination of these. If the quantity of predicted sets cannot be accommodated on the client device 150, the set identification engine 162 may select as many of the highest ranked sets as the set usage parameters accommodate.

In some implementations the ranking may be determined by the set prediction model 164. In some implementations, the set identification engine 162 may adjust rankings provided by the set prediction model 164. For example, if a particular fixed set is needed by a web application the user accesses often or has just installed, the set identification engine 162 may boost the ranking of that particular fixed set. The set identification engine 162 may also use metadata to adjust rank. For example, if Alice and Ted are travelling and have provided consent to share data, the client device for Alice may determine that the client device of Ted already has a particular fixed set included in the personalized entity repository on his device. Accordingly, when the Alice's client device detects Ted's device in close proximity, the set identification engine 162 on Alice's device may demote the ranking of that particular fixed set on her device.

In some implementations, the set identification engine 162 may generate the ranking of predicted fixed sets on a periodic basis or after some event, such as the install of a new application, the activation of an application that has not been used for a predetermined period of time, when the available space changes, e.g., the device becomes low on disk space (e.g., falls below a specified percentage) or some action that frees up a specified percentage of space, when the user changes location, etc. The set identification engine 162 may also update the personalized entity repository 176 in response to the ranking. For example, the set identification engine 162 may update the personalized entity repository 176 periodically, when an application using a particular fixed set of entities is installed, or when a rank for a fixed set of entities becomes more highly ranked than one of the sets currently in the personalized entity repository 176. For example, if Alice begins researching a trip to Hawaii, eventually the set prediction model 164 will predict a fixed slice related to Hawaii based on content (e.g., from screen capture index 172 or search records) Alice has been viewing. Because this set has previously never ranked high enough to be included in personalized entity repository 176, once the rank does exceed the rank of a set currently in the personalized entity repository 176 or when a change in rank exceeds some predetermined threshold, the set identification engine 162 may automatically update the personalized entity repository 176 or may obtain approval from Alice before including this particular set. Once Alice returns from Hawaii or if she does not go and does not access content on Hawaii for a period of time, the rank of the particular slice may fall, e.g., fall below another slice not in the personalized entity repository 176 or fall a predetermined percentage. This may

trigger execution of the set identification engine 162 so that another slice (i.e., another fixed set of entities) may take its place in the personalized entity repository 176.

Updating the personalized entity repository 176 may be accomplished in a variety of ways. In some implementations, the entire repository is deleted and replaced by fixed sets selected based on a rank and the set usage parameters. In some implementations, the set usage parameters may be set and controlled by the user. In some implementations the set identification engine 162 may determine whether a particular fixed set that should be in the personalized entity repository 176 already exists in the personalized entity repository 176. If it does the set identification engine 162 may either do nothing or determine if the set has changed, e.g., has been updated at server 110. If an update has occurred the set identification engine 162 may download the entire set or may download a delta to apply to the set. The set identification engine 162 may delete sets from the personalized entity repository 176 to make room for sets with a higher rank.

The computing device 150 may be in communication with the server 110 and with other mobile devices over network 140. Network 140 may be for example, the Internet, or the network 160 can be a wired or wireless local area network (LAN), wide area network (WAN), etc., implemented using, for example, gateway devices, bridges, switches, and/or so forth. Network 140 may also represent a cellular communications network. Via the network 140 the server 110 may communicate with and transmit data to/from computing device 140 and computing device 140 may communicate with other mobile devices (not shown).

The personalized entity repository system 100 represents one example configuration and implementations may incorporate other configurations. For example, some implementations may combine one or more of the components of the screen content agent 160, the set identification engine 162, or the set prediction model 164 into a single module or engine. Similarly, some implementations may combine one or more of the entity set generation engine 120 or the set prediction model 122 into a single module or application. As another example one or more of the data stores, such as the screen capture index 172, the personalized entity repository 176, or user profiles on client device 150 or entity repository 130, fixed entity sets 132, search records 134, or crawled document 136, may be combined into a single data store or may be distributed across multiple computing devices, or may be stored at another location.

To the extent that the personalized entity repository system 100 collects and stores user-specific data or may make use of personal information, the users may be provided with an opportunity to control collection of the user information (e.g., information about a user's social network, social actions or activities, a user's preferences, or a user's current location), or to control whether and/or how to store screen capture images and content. For example, the system may refrain from capturing content for certain applications, such as banking applications, health applications, or other similar applications or where capturing such content violates terms of service. In addition, the user may be provided with the opportunity to disable capturing screen content for specific applications or categories of applications. In addition, certain data may be treated in one or more ways before it is stored or used, so that personally identifiable information is removed. For example, a user's identity may be treated so that no personally identifiable information can be determined for the user, or a user's geographic location may be generalized where location information is obtained (such

13

as to a city, ZIP code, or state level), so that a particular location of a user cannot be determined. Thus, the user may have control over how information is collected about the user and used by a personalized entity repository system.

FIG. 2 illustrates an example display of a user interface **200** for specifying set usage parameters for a personalized entity repository, in accordance with the disclosed subject matter. The display may be a display of a mobile device or other personal computing device, such as client device **150** of FIG. 1. In some implementations, the user interface may be provided by the operating system of the client device or may be provided by a particular application, e.g., from applications **155** of FIG. 1. The user interface **200** includes controls **205** for a content agent, such as content agent **160** of FIG. 1. The controls **205** may regulate whether and how the content agent executes and what actions the content agent performs. The user interface **200** may also include set usage parameters for a personalized entity repository. The set usage parameters may include one or more of a maximum storage **210**, a maximum number of sets **215**, or a percent of storage **220**. The maximum storage **210** may set a limit on the amount of memory used by a personalized entity repository, such as personalized entity repository **176** of FIG. 1. The client device may download and store fixed sets of entities (slices) but not to exceed the maximum storage **210**.

The set usage parameters may also include maximum sets **215**. The maximum sets **215** limits the number of fixed sets of entities that the client device will include in the personalized entity repository. In other words, the client device may download and store only a specified number of sets. The percent of storage **220** may offer a flexible limit on the size of the personalized entity repository. For example, when the client device has more memory, the percent of storage **220** parameter may allow a larger personalized entity repository, but as space on the client device diminishes, the parameter may limit the sets stored in the personalized entity repository. The user interface **200** may also enable the user to select a combination of set usage parameters, e.g., via checkboxes, to turn on or off set usage parameters. Thus, the user may control the size of the personalized entity repository on their device, which in turn controls which slices are included in the repository. The user interface **200** may also include a control **225** that enables the user to specifically select one or more sets of entities for inclusion in the personalized entity model. When the user specifically uses the control **225** to select a slice of the entity repository, the system may rank the relevancy of that slice high, so that it is always included in the personalized entity model.

FIG. 3 illustrates an example display **300** of content that provides context for determining which sets are most relevant to a user of the computing device, in accordance with disclosed implementations. The display **300** may be a display of a mobile device or other computing device, such as client device **150** of FIG. 1. In the example of FIG. 3, the text "Alien Invaders" is selected. The selection may have been made by a user or may have been made automatically by the client device (e.g., a content agent or operation suggestion application running on the client device). The system has provided four suggested operations for the selection **305**, namely operation **340**, which may be for a mobile application that provides local movie times, a movie review operation **325**, and a movie database operation **320**. The user interface may have selected operation **340**, **325**, and **320** based on identification of selection **305** as an entity that exists in the personalized entity repository. Thus, the system

14

may provide display **300** even without connection to a server and to a server-based entity repository.

FIG. 4 illustrates an example display of a user interface **400** for suggesting additional slices for inclusion in a personalized entity repository, in accordance with disclosed implementations. The user interface **400** may be generated on a mobile device or other computing device, such as client device **150** of FIG. 1. In the example of FIG. 4, a user has entered text into a search interface **405**. Search interface **405** may be for a browser or a browser-like mobile application, but could be from any search bar in any application. The system may analyze the text provided to the search interface **405** and determine, e.g., via a set identification engine using a set prediction model, that the text is highly relevant to a topic-based fixed set of entities. The high relevancy may be determined based on a high confidence score or probability from the set prediction model. The high relevancy may be based not only on the content of the user interface **400** by also on previously presented content. For example, the user may have been looking at hotels in Hawaii in a booking application or may have been reading about things to see in Hawaii. While the client device may not have an entity for Hawaii in the current personalized entity repository, the set prediction model may recognize several words or images that predict the set. In some implementation, the set identification engine may be continuously analyzing text for relevant models. In some implementations, the set identification engine may be invoked during use of a search interface.

When the probability of the fixed set of entities indicates high relevancy, the system may automatically download and store the fixed set of entities for Hawaii, also referred to as the Hawaii slice. In some implementations, this may be a location-based set for all entities located in Hawaii, or a topic-based set, or a combination of these. In some implementations, the user interface may include confirmation window **410**. Confirmation window **410** may enable the user to accept or reject the suggestion. If the user rejects the suggestion, the system may not download the Hawaii slice. If the user accepts the suggestion, the system may download the Hawaii slice, and may remove one or more slices currently in the personalized entity repository to make room for the new slice, as explained in more detail with regard to FIG. 7.

FIG. 5 illustrates another example display of a user interface **500** for suggesting additional sets for inclusion in a personal entity repository, in accordance with disclosed implementations. The user interface **500** may be generated on a mobile device or other computing device, such as client device **150** of FIG. 1. In the example of FIG. 5, the user has just installed a dining reservation application **505**. In response to the installation process the set identification engine may determine that the application **505** has expressly requested a particular fixed set of entities or, e.g., using a set prediction engine, is likely to refer to the particular fixed set. Accordingly, the user may be presented with confirmation window **510**. Similar to confirmation window **410**, the confirmation window **510** may provide the opportunity for the user to elect to download the particular slice or to reject the download. In some implementations, the application **505** may generate window **510**. In some implementations (not shown) the application installation process or the set identification engine may automatically download the particular fixed set of entities.

FIG. 6 illustrates a flow diagram of an example process **600** for generating and updating fixed sets of entities, in accordance with disclosed implementations. Process **600**

may be performed by a personalized entity repository system, such as system **100** of FIG. **1**. Process **600** may be used to generate and maintain various slices of an entity repository, i.e., fixed sets of entities. The entity repository may be any large entity repository, for example entity repository **130** of FIG. **1**. Process **600** may begin by generating location-based sets of entities (**605**). A location-based set of entities may be any entities in an entity repository that are located in a particular cell. The cell may be defined by boundaries, for example by lines connecting three or more geographic coordinates. The cell may correspond to one or more geo cells (e.g., cells defined by a map application). The system may also generate topic-based fixed sets of entities (**610**). Topic-based sets may be formed by clustering, by similarity with or connection to a seed entity, by membership in a collection, etc. The system may also generate functional sets of entities (**615**). The functional sets may be combinations of location-based sets and topic sets, may be based on use by a particular application, may be based on popularity (i.e., the most commonly searched for entities and/or those appearing in the most crawled documents), may be based on a task or action, etc. Steps **605** to **615** may be performed at an initial time and to update sets. For example, at an initial time the system may perform steps **605** to **615** to generate initial sets of entities. Subsequently, the system may perform steps **605** to **615** to update the initial sets, add new sets, etc.

The system may version the fixed sets of entities. For example, when format changes to the set would cause an application that uses the sets to fail, the system may keep older versions and generate a new version after the schema change. In this manner, the system may handle schema changes in a manner that does not cause errors on client devices. Accordingly, the system may determine if the newly generated sets include a schema change (**620**). If so, the newly generated sets (e.g., from steps **605** to **615**), may be assigned a new version identifier (**625**). The version identifier will enable applications that use the sets to correctly download and use appropriate versions. No delta set is needed when the updates involve a schema change. If there is no schema change (**620**, No), the system may generate a delta for each set (**630**). The deltas are used when the client devices download just changes to fixed sets of entities rather than doing a delete of all fixed sets in the personalized entity model followed by storing the most recent sets of highest ranked fixed entity sets for that device. A delta may be a list of entities to remove and a list of entities to add. Thus, an update to an entity, e.g., name change, metadata or attribute change, etc., may be a delete of the entity followed by reading the entity. Deltas enable the system to transmit less data between the server where the sets are maintained and the client devices where the sets are used. However, step **630** is optional, and may not be performed for all sets or for even for any sets. For example, the client device, when updating the personalized entity repository, may delete all currently stored slices and fetch the desired slices (e.g., the predicted slices that fall within set usage parameters) and store those as the personalized entity model. Each fixed set of entities may have a unique identifier. In some implementations, the unique identifier may be a hash of the contents of the fixed set. Process **600** then ends. Process **600** may be repeated periodically to ensure the fixed sets of entities are current.

FIG. **7** illustrates a flow diagram of an example process **700** for building a personal entity repository using pre-computed sets of entities, in accordance with disclosed implementations. Process **700** may be performed by a personalized entity repository system, such as system **100** of FIG. **1**. Process **700** may be performed on a client device to

determine which fixed set of entities or slices are included in a personalized entity repository stored on the client device. The client device may perform process **700** continuously, on a periodic basis, upon network connectivity change, upon a triggering event, such as installation of a new application, an incoming phone call, addition of a new contact, etc., or user request of a synchronization. Process **700** may be performed by a set identification engine, such as set identification engine **162**.

Process **700** may begin by identifying fixed sets of entities relevant to a user of a client device (**705**). The sets may be fixed in the sense that the sets are determined prior to performance of step **705** and not as part of step **705**. In other words, the sets are determined independently of any particular user or query to the entity repository. The sets identified as part of step **705** are a much smaller subset than the total number of fixed sets. The identification of the fixed sets may be based, for example, on context associated with the client device. For example a set prediction model may be provided a set of features generated from a variety of signals (i.e., context) that can include metadata and information collected from content generated on the client device, for example via a content agent, search history, user profiles, etc. In some implementations the information used as a signal may include information from devices in proximity to the client device, e.g., from appliances or other computing devices in an Internet of Things home, from other personal computing devices associated with the user or the user's household, etc. Although such signals originate from another device, the proximity is context associated with the client device. In some implementations, the information may include the location of the computing device, a timestamp, content in a search history for the user, content in a screen capture index, content associated with a user profile, the applications installed on the client device, an activity performed by the user (e.g., changing device settings, installing an application), etc. The signals may be provided to the set prediction model, such as set prediction model **122** or set prediction model **164**, which may in turn provide one or more predicted fixed sets of entities. The fixed sets of entities identified in step **705** may also be based on a location of the device, applications installed on the device, tasks or activities commonly performed on the device, etc.

The system may then rank the identified fixed sets of entities by relevancy (**710**). The relevancy may be based on the probability score provided by the set prediction model. In some implementations, the system may adjust that probability based on other information, such as location of the device, time of day, other devices in proximity, etc. For example, if two traveling companions have linked their devices, the device of the first companion may determine, e.g., via device to device signaling, that the device of the second companion has a particular slice of the entity repository stored and the device of the first companion may demote the relevancy of that slice, e.g., because one of the two devices already has that slice of the entity repository stored in the personalized entity repository. As another example, the user's device may have a particular application that requires a particular slice of the entity repository and the system may boost the relevancy of that particular slice. As another example, the system may boost the relevancy of a slice that is specified by the user, e.g., via control **225** of FIG. **2**. For location-based fixed sets of entities, the system may set a relevancy score for the set based on the distance of the client device from the cell represented by the set. For example, when a client device is located within the cell, the relevancy may be very high. The relevancy of other cells

may be based on the distance between a center of the cell and the current location of the client device, so that longer distances produce lower relevancy.

The system may determine selected sets for the personalized entity repository based on the set usage parameters and the ranks (715). In some implementations, the system may determine a relevancy threshold based on the set usage parameters and the ranks of the fixed entity sets identified as relevant to the user. Any sets with a relevancy score that meets the threshold may be included in the sets selected for the personalized entity repository. FIG. 9 is another example of the selection of the sets based on the set usage parameters and rank. The system may then determine whether the personalized entity repository needs to be updated (720). For example, if the selected fixed sets of entities are the same as the sets currently included in the personalized entity repository, but the system has not recently checked for updates, then the system may update the repository (720, Yes). As another example, if the system has been notified of an update to one of the fixed sets in the selected sets, the system may update the repository (720, Yes). If a fixed set of entities is in the selected sets but not currently in the personalized entity repository, the system may update the repository (720, Yes). If the system does not need to update the repository (720, No), process 700 ends.

If the system does update the repository (720, Yes), the system may select a highest ranked set of the selected sets (725). For ease of explanation this highest ranked set may be referred to as the first set. The system may determine if this first set is already in the personalized entity repository (730). If it is in the repository (730, Yes), the system may update the first set on the client device, if an update is needed (735). The system may determine if an update is needed by either pulling the first set from the server or by notification from the server that an update exists. The update may be in the form of a delta, e.g., a list of entities to delete and a list of entities to add to the fixed set. If the first set is not in the personalized entity repository (730, No), the system may determine if the personal entity repository has room for the first set (740). For example, the personal entity repository may have a limit on the number of sets in the repository or the memory used by the repository, or both. If the addition of the first set would exceed the limits (740, No), the system may determine whether there is a fixed set currently in the personalized entity repository that can be deleted (745). A set that is currently in the personalized entity repository can be deleted if it is not in the selected fixed sets of entities, i.e., those identified in step 715. A set can also be deleted if it has a lower rank than the first set. If there is a set to delete (745, Yes), the system may delete the set from the personalized entity repository (750) and return to step 740. If no sets can be deleted (745, No), process 700 may end.

When there is room for the first set in the personalized entity repository (740, yes), the system may add the first set to the personalized entity repository on the mobile device (755). The system may then determine whether there is a next highest ranked set in the selected sets (760). If there is a next highest set (760, Yes), the system may perform steps 725 to 760 for the next set. This next set then becomes the first set for the ease of explanation. Thus, for example, the system may determine if the next set, i.e., now the first set, is already in the personalized entity repository (730), etc. When all sets in the selected sets have been processed via steps 730 to 760 (760, No), the system has updated the personalized entity repository and process 700 ends.

FIG. 8 illustrates a flow diagram of an example process 800 for identifying fixed sets of entities relevant to a user of

a client device, in accordance with disclosed implementations. Process 800 may be performed by a personalized entity repository system, such as system 100 of FIG. 1. Process 800 may be performed on a client device as part of step 705 of FIG. 7 to determine which fixed set of entities or slices are relevant to a user. Process 800 begins by determining a location of the client device (805). The location may be expressed as coordinates, e.g., Global Positioning System (GPS) coordinates, or as the identifier of a geo cell, or some other methods of expressing a location on the Earth. The system may assign the relevancy of a location-based fixed set of entities based on the distance from the client device to the cell represented by the location-based fixed set (810). The distance may be measured from the location of the client device to a center of the cell. The relevancy may also have an inverse relationship to the distance, so that a shorter distance has a higher relevancy. When the client device is located in a cell for a particular fixed set of entities, the particular fixed set of entities may receive a highest relevancy score.

The system may also determine topic-based fixed sets of entities that are relevant to the user (815). The topic-based sets may be determined with a set prediction model, such as set prediction model 164 or set prediction model 122, that provides one or more identifiers for fixed sets of entities that are predicted based on features. The features may be based on a number of information items, such as the location of the device, content in search records, a user profile, or screen capture content, data from devices in proximity to the client device, e.g., exchanging data with the client device, a timestamp, applications installed or executing at the time, etc. The system may set the relevancy score of each topic-based fixed set of entities to a similarity with an embedding for the user of the client device (820). In some implementations, the similarity may be the probability associated with the fixed set provided by the set prediction model. The system may also determine functional fixed sets of entities (825). The functional sets may be entities deemed most popular, e.g., most commonly searched for entities, most commonly accessed entities, entities found most often in crawled documents, etc. The functional sets may also include entities used for a particular task, action, or application. For example, a functional set may include entities that enable the device to perform OCR in a particular language, or that are used by an art appreciation application, etc. Functional sets may also include combinations of location-based and topic-based sets, for example, movie theaters in Portland Oregon or national monuments in Washington D.C. In some implementations, the system may use entity popularity as a relevancy score for a functional fixed set of entities. In some implementations, a fixed set may be ranked high based on an application that the user has installed. Process 800 then ends, having identified fixed sets of entities relevant to the user of the computing device and assigning a relevance score to each set.

FIG. 9 illustrates a flow diagram of an example process 900 for selecting fixed sets of entities from fixed sets of entities relevant to a user of a client device based on set usage parameters, in accordance with disclosed implementations. Process 900 may be performed by a personalized entity repository system, such as system 100 of FIG. 1. Process 900 may be performed on a client device as part of step 715 of FIG. 7 to determine which fixed set of entities or slices that are relevant to the user are selected for inclusion in a personal entity repository based on set usage parameters and rank. Process 900 begins by initializing set count and model size variables. The set count may be set to

zero and the repository size may also be set to zero. The system may then select from the fixed sets identified as relevant the fixed set with the highest rank (910). The system may determine whether the set usage parameters include a quantity parameter (915). The quantity parameter is the maximum sets 215 of FIG. 2 and represents a limit on the number of fixed sets that can be in the personalized entity repository. If there is a quantity parameter (915, Yes), the system may increase the set count (920) by one. The system may then determine if the set count is greater than the quantity parameter (925). If it is, process 900 may end because the fixed set would go beyond the limits represented by the set usage parameters. However, for the highest ranked set, the set count is not greater than the quantity parameter (925, No), so the system continues with step 930.

The system determines if the set usage parameters include a space parameter (930). The space parameter may be expressed as a specified amount of memory (e.g., maximum storage 210 of FIG. 2) or a percentage of available memory (e.g., percentage of storage 220 of FIG. 2), or a combination of these. If the set usage parameters do include a space parameter (930, Yes), the system may add the size of the fixed set being examined to the repository size (953). The size may be known or may be estimated, for example, based on an average size of fixed sets of entities. The system may determine whether the repository size is greater than the space parameter (940). If it is (940, Yes), process 900 ends because the fixed set would violate a limit established by the set usage parameters. Otherwise (940, No), the system adds the set to the selected sets (945). The selected sets are the highest ranked fixed sets identified as relevant to the user that also meet limits established by the set usage parameters. If there is another set in the identified sets (e.g., the fixed sets identified as relevant to the user), 950, Yes, the system may select the next highest ranked set (955) and continue with steps 915 to 950 as described above. If no other sets exist in the identified sets (950, No), process 900 ends, having identified sets to be included in the repository based on the set usage parameters.

FIG. 10 shows an example of a generic computer device 1000, which may be operated as server 110, and/or client device 150 of FIG. 1, which may be used with the techniques described here. Computing device 1000 is intended to represent various example forms of computing devices, such as laptops, desktops, workstations, personal digital assistants, cellular telephones, smartphones, tablets, servers, and other computing devices, including wearable devices. The components shown here, their connections and relationships, and their functions, are meant to be examples only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

Computing device 1000 includes a processor 1002, memory 1004, a storage device 1006, and expansion ports 1010 connected via an interface 1008. In some implementations, computing device 1000 may include transceiver 1046, communication interface 1044, and a GPS (Global Positioning System) receiver module 1048, among other components, connected via interface 1008. Device 1000 may communicate wirelessly through communication interface 1044, which may include digital signal processing circuitry where necessary. Each of the components 1002, 1004, 1006, 1008, 1010, 1040, 1044, 1046, and 1048 may be mounted on a common motherboard or in other manners as appropriate.

The processor 1002 can process instructions for execution within the computing device 1000, including instructions stored in the memory 1004 or on the storage device 1006 to

display graphical information for a GUI on an external input/output device, such as display 1016. Display 1016 may be a monitor or a flat touchscreen display. In some implementations, multiple processors and/or multiple buses may be used, as appropriate, along with multiple memories and types of memory. Also, multiple computing devices 1000 may be connected, with each device providing portions of the necessary operations (e.g., as a server bank, a group of blade servers, or a multi-processor system).

The memory 1004 stores information within the computing device 1000. In one implementation, the memory 1004 is a volatile memory unit or units. In another implementation, the memory 1004 is a non-volatile memory unit or units. The memory 1004 may also be another form of computer-readable medium, such as a magnetic or optical disk. In some implementations, the memory 1004 may include expansion memory provided through an expansion interface.

The storage device 1006 is capable of providing mass storage for the computing device 1000. In one implementation, the storage device 1006 may be or include a computer-readable medium, such as a floppy disk device, a hard disk device, an optical disk device, or a tape device, a flash memory or other similar solid state memory device, or an array of devices, including devices in a storage area network or other configurations. A computer program product can be tangibly embodied in such a computer-readable medium. The computer program product may also include instructions that, when executed, perform one or more methods, such as those described above. The computer- or machine-readable medium is a storage device such as the memory 1004, the storage device 1006, or memory on processor 1002.

The interface 1008 may be a high speed controller that manages bandwidth-intensive operations for the computing device 1000 or a low speed controller that manages lower bandwidth-intensive operations, or a combination of such controllers. An external interface 1040 may be provided so as to enable near area communication of device 1000 with other devices. In some implementations, controller 1008 may be coupled to storage device 1006 and expansion port 1014. The expansion port, which may include various communication ports (e.g., USB, Bluetooth, Ethernet, wireless Ethernet) may be coupled to one or more input/output devices, such as a keyboard, a pointing device, a scanner, or a networking device such as a switch or router, e.g., through a network adapter.

The computing device 1000 may be implemented in a number of different forms, as shown in the figure. For example, it may be implemented as a standard server 1030, or multiple times in a group of such servers. It may also be implemented as part of a rack server system. In addition, it may be implemented in a computing device, such as a laptop computer 1032, personal computer 1034, or tablet/smart phone 1036. An entire system may be made up of multiple computing devices 1000 communicating with each other. Other configurations are possible.

FIG. 11 shows an example of a generic computer device 1100, which may be server 110 of FIG. 1, which may be used with the techniques described here. Computing device 1100 is intended to represent various example forms of large-scale data processing devices, such as servers, blade servers, datacenters, mainframes, and other large-scale computing devices. Computing device 1100 may be a distributed system having multiple processors, possibly including network attached storage nodes, that are interconnected by one or more communication networks. The components shown

here, their connections and relationships, and their functions, are meant to be examples only, and are not meant to limit implementations of the inventions described and/or claimed in this document.

Distributed computing system **1100** may include any number of computing devices **1180**. Computing devices **1180** may include a server or rack servers, mainframes, etc. communicating over a local or wide-area network, dedicated optical links, modems, bridges, routers, switches, wired or wireless networks, etc.

In some implementations, each computing device may include multiple racks. For example, computing device **1180a** includes multiple racks **1158a-1158n**. Each rack may include one or more processors, such as processors **1152a-1152n** and **1162a-1162n**. The processors may include data processors, network attached storage devices, and other computer controlled devices. In some implementations, one processor may operate as a master processor and control the scheduling and data distribution tasks. Processors may be interconnected through one or more rack switches **1158**, and one or more racks may be connected through switch **1178**. Switch **1178** may handle communications between multiple connected computing devices **1100**.

Each rack may include memory, such as memory **1154** and memory **1164**, and storage, such as **1156** and **1166**. Storage **1156** and **1166** may provide mass storage and may include volatile or non-volatile storage, such as network-attached disks, floppy disks, hard disks, optical disks, tapes, flash memory or other similar solid state memory devices, or an array of devices, including devices in a storage area network or other configurations. Storage **1156** or **1166** may be shared between multiple processors, multiple racks, or multiple computing devices and may include a computer-readable medium storing instructions executable by one or more of the processors. Memory **1154** and **1164** may include, e.g., volatile memory unit or units, a non-volatile memory unit or units, and/or other forms of computer-readable media, such as a magnetic or optical disks, flash memory, cache, Random Access Memory (RAM), Read Only Memory (ROM), and combinations thereof. Memory, such as memory **1154** may also be shared between processors **1152a-1152n**. Data structures, such as an index, may be stored, for example, across storage **1156** and memory **1154**. Computing device **1100** may include other components not shown, such as controllers, buses, input/output devices, communications modules, etc.

An entire system, such as server **110**, may be made up of multiple computing devices **1100** communicating with each other. For example, device **1180a** may communicate with devices **1180b**, **1180c**, and **1180d**, and these may collectively be known as server **110**. As another example, system **100** of FIG. **1** may include one or more computing devices **1100**. Some of the computing devices may be located geographically close to each other, and others may be located geographically distant. The layout of system **1100** is an example only and the system may take on other layouts or configurations.

According to certain aspects of the disclosure, a mobile device comprises a display device, a personalized entity repository stored in memory, the personalized entity repository including a plurality of fixed sets of entities from an entity repository stored at a server, wherein each fixed set has a respective identifier and includes information about the entities in the set, at least one processor, and memory storing instructions that, when executed by the at least one processor, cause the mobile device to perform operations. The operation include identifying fixed sets of the entity repository

that are relevant to a user of the mobile device based on context associated with the mobile device, ranking the fixed sets by relevancy, determining selected sets from the identified fixed sets using the rank and set usage parameters applicable to the user, and updating the personalized entity repository using the selected sets.

This and other aspects can include one or more of the following features. For example, updating the personalized entity repository may occur responsive to determining that a first fixed set of the identified fixed sets does not exist in the personalized entity repository. As another example, updating the personalized entity repository can include removing a set in the personalized entity repository that is not a selected set. As another example, the set usage parameters can include a quantity of fixed sets and/or an amount of memory allocated to the personalized entity repository, the amount being set by the user. As another example, the plurality of fixed sets stored in the personalized entity repository can include location sets, wherein entities in a location set are located in a same cell. As another example, the plurality of fixed sets stored in the personalized entity repository includes topic sets, wherein entities in a topic set are entities clustered together based on entity characteristics. In some implementations, the rank of a first topic set is a rank assigned by a prediction model based on items recognized in content generated for display on the display device. As another example, updating the personalized entity repository can include adding a fixed set that does not currently exist in the personalized entity repository and using a delta of a fixed set that exists in the personalized entity repository.

As another example, the operations may also include identifying an entity in content generated for display on the display device using the personalized entity repository. As another example, each of the plurality of sets has a version identifier, the version identifier changing when an update to a particular set breaks a schema of the personalized entity repository. As another example, the operations may also include initiate display of information that identifies a first fixed set from the selected sets and a control configured to enable the user to accept instillation of the first fixed set and download the first fixed set and add it to the personalized entity repository when the user accepts installation. As another example, identifying fixed sets of the entity repository that are relevant to the user based on the context can include determining a location of the mobile device and using the location to determine location-based fixed sets relevant to the user, using a set prediction model to identify topic-based sets relevant to the user, and determining sets identified by at least one application installed on the mobile device. As another example, identifying fixed sets of the entity repository that are relevant to the user based on the context can include determining content previously viewed on the mobile device and providing the content previously viewed to a set prediction model configured to predict at least one topic-based set from the content previously viewed and/or determining recent searches conducted on the mobile device and providing the content from the recent searches to a set prediction model configured to predict at least one topic-based set from the content. As another example, identifying fixed sets of the entity repository that are relevant to the user based on the context can include determining an activity performed by the user of the mobile device and predicting a fixed set of entities based on the activity.

According to certain aspects of the disclosure, a method includes receive a screen captured image configured to display content on a display of a mobile device, determining text in the image by performing text recognition on the

image, providing the text to a set prediction model, wherein the set prediction model is trained to predict one or more fixed sets of entities, and storing at least one fixed set of entities of the predicted fixed sets of entities in a personalized entity repository in memory on the mobile device.

These and other aspects can include one or more of the following features. For example, the method may also include identifying entities in screen capture images using the personalized entity repository. The method may also include determining a location associated with content recognized in a screen capture image, provide the location to the set prediction model, the set prediction model predicting at least one location-based fixed set of entities based on the location, and storing the location-based fixed set of entities in the personalized entity repository. As another example, the prediction model may predict a plurality of predicted fixed sets of entities and the method also includes ranking each of the predicted fixed sets of entities, using set usage parameters and the rankings to determine selected fixed sets of entities from the predicted fixed sets of entities and storing the selected fixed sets of entities in the personalized entity repository.

According to certain aspects of the disclosure, a method may include generating a plurality of fixed sets of entities from an entity repository. The fixed sets include location-based sets, each location-based set including entities from the entity repository that have a location inside a cell, the cell being associated with the set, and topic-based sets, at least some of the topic-based sets including entities from the entity repository that are related to each other via an embedding similarity. The method may also include providing a subset of the fixed sets of entities to a client device, the client device requesting the subset based on a location of the client device and on recognized items identified in content generated for display on the client device.

These and other aspects can include one or more of the following features. For example, the method may also include identifying at least one entity added to the entity repository, determining at least one fixed set that the added entity belongs to, and generating a delta for the at least one fixed set that includes the added entity. As another example, the method may also include identifying at least one entity added to the entity repository, determining at least one fixed set that the added entity belongs to, determining that a schema of the fixed sets has changed, and generating a new version of the at least one fixed set, the new version including the added entity and having a new version identifier. As another example, at least some of the topic-based sets may include entities similar to a seed entity and/or the fixed sets may also include functional sets, at least one of the functional sets including entities deemed most popular.

Various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor, and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms “machine-readable medium” “computer-readable medium” refers to any non-transitory computer program product, apparatus and/or

device (e.g., magnetic discs, optical disks, memory (including Read Access Memory), Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor.

The systems and techniques described here can be implemented in a computing system that includes a back end component (e.g., as a data server), or that includes a middleware component (e.g., an application server), or that includes a front end component (e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the systems and techniques described here), or any combination of such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication (e.g., a communication network). Examples of communication networks include a local area network (“LAN”), a wide area network (“WAN”), and the Internet.

The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other.

A number of implementations have been described. Nevertheless, various modifications may be made without departing from the spirit and scope of the invention. In addition, the logic flows depicted in the figures do not require the particular order shown, or sequential order, to achieve desirable results. In addition, other steps may be provided, or steps may be eliminated, from the described flows, and other components may be added to, or removed from, the described systems. Accordingly, other implementations are within the scope of the following claims.

What is claimed is:

1. A method implemented by one or more processors, the method comprising:

determining that each of multiple user interactions via a user device relate to a particular topic;

determining, based on the multiple user interactions that each relate to the particular topic, a confidence score for a topic-based set of entities for the particular topic;

in response to the confidence score for the topic-based set of entities satisfying a threshold:

causing an interactive prompt, related to the topic-based set of entities, to be rendered at the user device;

in response to an acceptance user interaction with the interactive prompt at the user device:

causing the user device to download the topic-based set of entities; and

subsequent to causing the user device to download the topic-based set of entities:

identifying an additional user interaction via the user device related to an application that is currently running on the user device;

determining that the additional user interaction is associated with at least one entity from the topic-based set of entities;

selecting, based on determining that the additional user interaction is associated with at least one entity from the topic-based set of entities, one or more actions to suggest to a user of the user device; and

causing the user device to display one or more suggested actions based on the one or more selected actions; and

25

in response to a rejection user interaction with the interactive prompt at the user device:

refraining from causing the user device to download the topic-based set of entities.

2. The method of claim 1, wherein the one or more suggested actions that are displayed are each associated with a corresponding different application that is different from the application related to the additional user interaction.

3. The method of claim 1, wherein each of the one or more suggested actions is associated with at least one additional corresponding entity from the topic-based set of entities.

4. The method of claim 1, wherein determining that each of the multiple user interactions via the user device relate to the particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being generated based on one or more of:

an application currently in use by the user during a respective one of the multiple user interactions,

screen metadata indicating content displayed on a screen of the user device during the respective one of the multiple user interactions, and/or

content associated with recent search queries submitted by the user as indicated by a search log;

comparing the multiple embeddings to a plurality of topic embeddings; and

determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

5. The method of claim 1, wherein determining that each of the multiple user interactions via the user device relate to the particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being generated based on content associated with recent search queries submitted by the user as indicated by a search log;

comparing the multiple embeddings to a plurality of topic embeddings; and

determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

6. The method of claim 1, wherein determining that each of the multiple user interactions via the user device relate to the particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being generated based on screen metadata indicating content displayed on a screen of the user device during the respective one of the multiple user interactions;

comparing the multiple embeddings to a plurality of topic embeddings; and

determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

7. The method of claim 1, wherein determining the confidence score for the topic-based set of entities for the particular topic comprises:

determining the confidence score using a trained set prediction model and features related to one or more of the multiple user interactions.

8. A system comprising:

one or more computing devices and more or more storage devices storing instructions that are operable, when executed by the one or more computing devices, to cause the one or more computing devices to perform operations comprising:

26

determining that each of multiple user interactions via a user device relate to a particular topic;

determining, based on the multiple user interactions that each relate to the particular topic, a confidence score for a topic-based set of entities for the particular topic;

in response to the confidence score for the topic-based set of entities satisfying a threshold:

causing an interactive prompt, related to the topic-based set of entities, to be rendered at the user device;

in response to an acceptance user interaction with the interactive prompt at the user device:

causing the user device to download the topic-based set of entities; and

subsequent to causing the user device to download the topic-based set of entities:

identifying an additional user interaction via the user device related to an application that is currently running on the user device;

determining that the additional user interaction is associated with at least one entity from the topic-based set of entities;

selecting, based on determining that the additional user interaction is associated with at least one entity from the topic-based set of entities, one or more actions to suggest to a user of the user device; and

causing the user device to display one or more suggested actions based on the one or more selected actions; and

in response to a rejection user interaction with the interactive prompt at the user device:

refraining from causing the user device to download the topic-based set of entities.

9. The system of claim 8, wherein the one or more suggested actions displayed are each associated with a corresponding different application that is different from the application related to the additional user interaction.

10. The system of claim 8, wherein each of the one or more suggested actions is associated with at least one additional corresponding entity from the topic-based set of entities.

11. The system of claim 8, wherein determining that each of multiple user interactions via a user device relate to a particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being generated based on one or more of:

an application currently in use by the user during a respective one of the multiple user interactions,

screen metadata indicating content displayed on a screen of the user device during the respective one of the multiple user interactions, and/or

content associated with recent search queries submitted by the user as indicated by a search log;

comparing the multiple embeddings to a plurality of topic embeddings; and

determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

12. The system of claim 8, wherein determining that each of multiple user interactions via a user device relate to a particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being

generated based on content associated with recent search queries submitted by the user as indicated by a search log;  
 comparing the multiple embeddings to a plurality of topic embeddings; and  
 determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

13. The system of claim 8, wherein determining that each of multiple user interactions via a user device relate to a particular topic comprises:

generating multiple embeddings for the multiple user interactions, each of the multiple embeddings being generated based on an application currently in use by the user during a respective one of the multiple user interactions;  
 comparing the multiple embeddings to a plurality of topic embeddings; and  
 determining, based on the comparing, that each of the multiple user interactions via the user device relate to the particular topic.

14. The system of claim 8, wherein determining the confidence score for the topic-based set of entities for the particular topic comprises:

determining the confidence score using a trained set prediction model and features related to one or more of the multiple user interactions.

\* \* \* \* \*