



(43) International Publication Date  
28 August 2014 (28.08.2014)

- (51) International Patent Classification:  
B62J 27/00 (2006.01) B60R 21/16 (2006.01)  
A41D 13/018 (2006.01)
- (21) International Application Number:  
PCT/US2014/013530
- (22) International Filing Date:  
29 January 2014 (29.01.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
61/767,412 21 February 2013 (21.02.2013) US
- (72) Inventor; and
- (71) Applicant : FENYVES, Andras [US/US]; 381 5th Street,  
Brooklyn, New York 11215 (US).
- (74) Agent: FROEBRICH, Alfred W.; Lucas & Mercanti,  
LLP, 475 Park Avenue South, 15th Floor, New York, NY  
10016 (US).
- (81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report (Art. 21(3))

(54) Title: CRASH PROTECTION SYSTEM




FIG. 1

(57) Abstract: A crash protection system includes a base connectable to a support on an open vehicle or an animal. The base includes a front airbag module arranged proximate a front end of the base and a rear airbag module arranged proximate a rear end of the base. The front airbag module has a front airbag, and the rear airbag module has a rear airbag. The system further includes a belt system having a first belt connectable around a waist of a rider and at least one strap connecting the first belt to the base. A control system includes sensors that are monitored to determine whether a crash situation is present and the control system actuates the front airbag module and the rear airbag module and releases the base from the support when the crash situation is present.

WO 2014/130219 A1

## CRASH PROTECTION SYSTEM

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The present invention relates to a protection device for a rider of an open vehicle, such as a motorcycle or snowmobile, or an animal, such as a horse, the protection device cushioning an impact of the rider after ejection from the open vehicle or animal.

#### Description of Prior Art

Air bag devices are used extensively in automobiles to cushion the impact of a driver or rider in the event that the automobile is involved in a collision. For automobiles, the airbag prevents impacts within the structure of the vehicle. However, a different type of device for cushioning the impact of motorcycle riders during accidents is required because motorcycle riders are easily thrown from or otherwise separated from their vehicles.

US 4,685,151 discloses apparel in the form of a jacket that is inflatable in the event of an accident to protect a motorcycle rider from an impact. Here, the rider is required to wear the jacket to obtain protection.

US 6,007,090 discloses another type of air bag device for a motorcycle in which the air bag is incorporated on the motorcycle. Here the air bag device protects the rider under circumstances limited to a frontal collision. Furthermore, the protection is limited to a limited range of forward thrust of the rider. It is still possible for rider to be thrown from the motorcycle, in which case this prior art air bag device fails to provide adequate protection.

### SUMMARY OF THE INVENTION

An object of the present invention is provide an improved system for protecting a rider of an open vehicle or an animal.

The object is met by a crash protection system including a base connectable to a support on an open vehicle or an animal, a front airbag module arranged proximate a front end of the base and comprising a front airbag, a rear airbag module arranged proximate a rear end of the base and comprising a rear airbag, and a belt system including a first belt connectable around a waist of a rider and at least one strap connecting said first belt to said base. The crash protection system further includes a control

system including sensors. The control system monitors the sensors to determine whether a crash situation is present and the control system actuates the front airbag module and the rear airbag module and releases the base from the support when the crash situation is present.

Thus, according to the present invention, the base is connected to the rider and the base is released from the open vehicle or animal when a crash situation is detected. The base includes the airbags that are deployed to protect the rider.

According to an embodiment of the invention, the front airbag is deployed upward from the base and in front of the rider when the front airbag module is actuated, and the rear airbag is deployed upward from said base and in back of the rider when the front airbag is actuated.

According to a further embodiment, the front airbag is deployed downward from said base and in front of the rider when the front airbag module is actuated, and said rear airbag is deployed downward from said base and in back of the rider when the rear airbag module is actuated.

According to another embodiment of the present invention, the first belt includes a front first belt portion and a rear first belt portion that are connectable by a right fastener and a left fastener, which the rider fastens once the rider is in position on the base. The front first belt portion is connected to the base by a right front strap and a left front strap, and the rear first belt portion is connected to the base by a right rear strap and a left rear strap. The right fastener is arranged between the right front strap and the right rear strap on the right side of the base and the left fastener is arranged between the left front strap and the left rear strap on the left side of the base.

The crash protection system may further include an upper outer belt comprising a front left upper outer belt connected to a left side of the front airbag and the left fastener, a front right upper outer belt connected to a right side of the front airbag and the right fastener, a rear left upper outer belt connected to a left side of the rear airbag and the left fastener, and a rear right upper outer belt connected to a right side of the rear airbag and the right fastener.

The upper outer belt is separable from the first belt at the right fastener and the left fastener during deployment of the front airbag and the rear airbag while maintaining an integrity of the upper outer belt and the first belt. For this purpose, each of the right fastener and the left fastener includes a first portion connecting the inner belt and a second portion connecting the upper outer belt, the first portion

being connected to the second portion by a frangible connection that breaks away in response to a deployment force of the airbags.

According to another embodiment of the present invention, the crash protection system further includes an upper outer belt comprising a left upper outer belt connected between a left side of the front airbag and a left side of the rear airbag, and a right upper outer belt connected between a right side of the front airbag and a left side of the rear airbag. The upper outer belt retains the front airbag and rear airbag proximate a front and rear of the rider when the airbags are deployed.

According to yet another embodiment of the present invention, the front airbag module is an upper front airbag module with an upper airbag and the rear airbag module is an upper rear airbag module with an upper rear airbag, and the crash protection system further includes a lower front airbag module arranged proximate a front end of the base and having a lower front airbag, and a lower rear airbag module arranged proximate a rear end of the base and having a lower rear airbag. The upper front airbag is deployed upward from the base and in front of the rider when the upper front airbag module is actuated, the upper rear airbag is deployed upward from said base and in back of the rider when the upper rear airbag module is actuated, the lower front airbag is deployed downward from the base and in front of the rider when the lower front airbag module is actuated, and the lower rear airbag is deployed downward from the base and in back of the rider when the lower rear airbag module is actuated.

According to a specific embodiment of the present invention, the base is a motorcycle seat. Alternatively, the base comprises a portion of the motorcycle seat and is released from another portion of the seat upon determination of a crash situation. The present invention is not limited to motorcycles. The seat may also be used on snowmobiles or any other open vehicles from which a rider may be thrown or otherwise separated. Moreover, the present invention may also be used for riders of animals such as horses. In one example, the base is part of a saddle and is separable from the saddle. Accordingly, the invention protects a rider that is thrown from a horse or other animal.

In an additional embodiment, the crash protection device includes an ejector that pushes the base away from the support upon release of the base from the support.

In a particular embodiment of the present invention, the belt system includes a front right strap connected to a front right side of the base, a rear right strap connected to a rear right side of the base, a front left strap connected to a front left side of the base, and a rear left strap connected to a rear left side

of the base. The front right strap is reeved through a front right pulley and connected to a portion of a right fastener, the rear right strap is reeved through a rear right pulley and connected to another portion of the right fastener, the front left strap is reeved through a front left pulley and connected to a portion of a left fastener, and the rear left strap is reeved through a rear left pulley and connected to another portion of the left fastener. The front right pulley is connected to the front left pulley by a front portion of the first belt, and the rear right pulley is connected to the rear left pulley by a rear portion of the first belt. When the rider moves off of or away from the base, such as in a crash situation, the first belt tightens around the rider's body.

At least one of the front right strap, the front left strap, the rear right strap, and the rear left strap is connected to the base by a retractor mechanism. This retractor mechanism may be any known or hereafter developed retractor mechanism that is used with automotive seat belts.

The sensors of the control system include a tension sensor on the at least one of the front right strap, the front left strap, the rear right strap, and the rear left strap.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, wherein like reference characters denote similar elements throughout the several views:

Fig. 1 is a side view of a rider on a motorcycle with a protection system according to an embodiment of the present invention;

Fig. 2 is a schematic diagram showing a seat of the motorcycle according to an embodiment of the present invention;

Fig. 2A is a schematic diagram of the seat of Fig. 2 with the belt unbuckled;

Fig. 3 is a schematic diagram of an inner belt according to an embodiment of the present invention;

Fig. 4 is a schematic diagram of an inner belt and two outer belts according to an embodiment of the present invention;

Fig. 4A is a schematic sectional diagram of the buckle according to an embodiment of the present invention;

Fig. 5 is a schematic diagram of the protection system showing a deployed position of the upper airbags;

Fig. 6 is a block diagram of the control system according to an embodiment of the present invention;

Fig. 7 is a side view of the motorcycle and driver with an ejector actuated;

Fig. 8 is a side view of the motorcycle with the upper air bags deployed;

Fig. 9 is a side view of the motorcycle with the upper air bags and the lower air bags deployed;

Fig. 10 is a schematic diagram showing internal features of the upper airbags;

Fig. 11 is a schematic top view of the deployed upper air bags; and

Figs. 12A and 12B are schematic top view diagrams of two stages of deployment of the upper air bags.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 shows a rider 20 on a motorcycle 10 equipped with a protection system 100 according to an embodiment of the present invention. Further details of the protection system 100 are shown in Figs. 2A and 2B, which show that a seat 128 of the motorcycle includes front airbag modules 130, 134 and rear airbag modules 132, 136 disposed within the seat. Each of the airbag modules 130, 132, 134, 136 is connected to a controller 138, which is depicted in the seat 128. Although, the controller 138 is depicted as being disposed in the seat, the controller 138 can be located at any convenient location on the motorcycle. The controller 138 is described in more detail below.

Furthermore, the seat 128 is attached to the rider 20 by straps 112, 114, 116, 118 and inner belt 110. The inner belt 110 includes an inner belt front portion 120 and an inner belt rear portion 122, which are connected to each other by buckles 124 and 126 or other known or hereafter developed releasable fasteners. As shown in Fig. 2A, before a rider 20 mounts the motorcycle 10, the buckles 124, 126 are opened. The rider sits on the seat so that the rider's right leg is between the front right strap 118 and rear right strap 114, and the rider's left leg is between the front left strap 116 and the rear left strap 112. The rider pulls the inner belt front portion 120 and inner belt rear portion 122 up around the rider's waist and attaches the buckles 124, 126. The straps 112, 114, 116, 118 may be connected to the seat by conventional methods such as sewing. One or more of the straps 112, 114, 116, 118 may be connected to the seat 128 by a retractor mechanism and/or a pretensioner that are currently used with automotive seatbelts.

Fig. 3 shows another embodiment of the present invention in which the inner belt 110 is connected to the straps 114 and 118 via pulleys 140, 142. In this embodiment, a belt forming the strap 114 is reeved through pulley 140 and is connected to the fastener 124. Likewise, the belt forming strap 118 is reeved through pulley 142 and connected to the fastener 124. The front and back portions of the inner belt are connected to the axles of the pulleys 140, 142. A similar configuration is disposed on the left side of the seat 128. Accordingly, as the rider lifts up from the seat, the straps 114, 118 lengthen and the inner belt 110 shortens. Figure 3 further shows that the straps 114, 118 are each connected to the seat 128 by a retractor mechanism 141, 143. Similarly, the straps 112 and 116 may also be connected to the seat by retractor mechanisms.

Fig. 4 shows another feature of the present invention. An upper right outer belt 144 has an outer belt front portion 146 connected on the right side of an airbag 130a in airbag module 130 and an outer belt rear portion 148 right side of an airbag 132a in airbag module 130. The outer belt front portion 146 is connected to the outer belt rear portion 148 by an outer belt fastener 150. A left outer belt 154 (not shown in Fig. 4) with a similar construction is connected to the left side of the air bag 130a and left side of airbag 132a in the seat 128. The outer belt 144 facilitates keeping the air bags 130a and 132a proximate the rider during deployment of the air bags. As shown schematically in Fig. 5, the deployed air bags 130a and 132a remain connected to each other by the outer belts 144 and 154 when they are deployed. This connection keeps the airbags 130, 132 proximate the rider during deployment for maximum protection. Similarly, a lower outer belt 244 having front and rear portions 244a, 244b and a buckle 151 is connected to the right side of airbags 134a, 136a in airbag modules 134, 136. The right lower outer belt 244 and left lower outer belt (not shown in Fig. 4) facilitate keeping the air bags 134a, 136a proximate the rider's legs during deployment.

Connections of the belts 144, 154 to the airbags may be accomplished by both adhesives and/or stitching. In one embodiment, the belt ends overlap and/or meet at the front or back so that a continuous loop is formed around the airbags for increased strength and thereby minimizing strain on the airbag fabric.

Fig. 4A shows a sectional schematic view of the buckles 124, 150 and 151. Each of the buckles includes a male part 124b, 150b, 151b and a female part 124a, 150a, 151a. Each female part includes a releasable latch 124c, 150c, 151c for releasably engaging the respective male part, as in any conventional buckle. The male parts 124b, 150b, 151b are connected by frangible connections 250. Similarly, the female parts 124a, 150a, 151a are connected by frangible connections 260. The buckles can be operated simultaneously via pushbutton 246 and connectors 248. However, during deployment, the inner belt 110 and the two outer belts 144, 244 are required to separate from each other, while the buckles remain closed. The frangible connections allow the separation of the belts from each other. In general, the frangible connections 250, 260 should be strong enough to maintain the connection of the buckles during normal handling and weak enough to separate in response to the deployment of the airbags. If the portions of the buckles that are connected are plastic, the frangible connection may comprise small connection areas. If the portions of the buckles that are connected are metal, the

frangible connection may be a spot weld. Alternatively, the frangible connections 250, 260 may comprise hook and loop fasteners such as VELCRO<sup>™</sup>. As a further alternative, a releasable magnetic lock 251, 261 may be used instead of the frangible connections 250, 260. The magnetic lock may work on the principle of magnetic door lock devices known, for example, from U.S. Patent No. 4,826,223, the entire contents of which are incorporated herein by reference. Each magnetic lock includes an electromagnet 166 controlled by the controller (see Fig. 6) and an armature 167. In a preferred embodiment, the magnetic lock is fail-secure so that the magnetic lock does not accidentally release when no power is provided, such as in a low battery condition.

According to Fig. 6, the controller 138 includes a central controller 158 connected to accelerometers 160, seatbelt tension sensors 162, and other crash sensors 164 such as speed sensors and/or 3D position sensors. The accelerometers 160 may comprise 1D, 2D, and/or 3D accelerometers, depending on the particular requirements. The present invention may also employ any known or hereafter developed safing sensors to ensure operational reliability.

Specific combinations of sensor signals will be recognized by the central controller 158 as a crash situation requiring actuation of the airbag modules 130, 132, 134, and 136. In one example, a crash situation occurs when at least one of the sensors 160, 162, 164 indicates a front collision at greater than a predetermined speed. Other crash situations may include when the vehicle is tilting and a rider is falling off of the vehicle, when the vehicle is hit from behind, and when the vehicle is hit from the side. In the first scenario, the sensors would sense a speed of the vehicle and the accelerometers would sense that the vehicle is tilting. If the tilt occurs to a degree that is outside of a normal operation at the sensed speed, deceleration or acceleration by a predetermined amount, the airbag modules 130, 132, 134, and 136 would deploy. For the rear and side impacts, the accelerometers would sense that which is considered to be unusual accelerations.

Once a crash situation is recognized, the central controller 158 actuates a seat ejector 156, which releases the seat 128, or at least a portion of the seat 128 from the motorcycle 10 (see Fig. 7). The seat ejector 156 may simply comprise a latch that is released upon detection of a crash situation so that the seat is released from the motorcycle. Alternatively, the ejector may further include an energy storage unit such as a spring that urges the seat 128 away from the motorcycle after the latch is released. As a further alternative, the seat ejector may have a variable force that takes into account anticipated impact and

weight of rider upon detection of a crash situation. Here, the ejector 156 may comprise an explosive cartridge, similar to the explosive cartridges used for ejection seats in aircraft. To achieve a variable force, two or more explosive cartridges of different charges, i.e., a first charge 156a and a second charge 156b may be used.

Simultaneously with the actuation of the seat ejector 156, or with a nominal delay, the central controller 158 actuates the air bag modules 130, 132, 134, and 136. According to one embodiment of the invention, the upper air bags 130a, 132a are deployed first as shown in Fig. 8. After a small delay, the lower airbags 134a, 136a are deployed as shown in Fig. 9. As an alternative, all of the airbags 130a, 132a, 134a, 136a may be deployed simultaneously. Each of the air bags 130a, 132a, 134a, 136a is deployed with a respective conventional airbag inflator (not shown) as is used for automotive airbags.

As shown in Fig. 10, the airbags 130a, 132a have internal webs or strings connecting the walls of the respective air bags 130a, 132a so that the air bags are deployed in the proper shape. The upper front airbag is shaped so that it has a height that extends over a top of a head of a typical rider and will arch back over the top of the rider's head. The depth of the inflated airbag 130a from front to back is large enough so that it is greater than a length of the rider's arms.

The upper rear airbag 132a also has a height that extends over a top of a head of a typical rider and will arch over the rider's head and meet the top of the upper front airbag 130a. Further, the upper rear airbag designed to curve around a back of the rider toward the front and cover sides of the rider (see, e.g., Fig. 11). The outer belt 144 will facilitate maintaining the airbags 130a, 132a in place around the rider.

Similarly, the lower front and rear airbags 134a, 136a are shaped to cover the rider's legs. More specifically, the lower airbags are shaped and deployed to cover the typical riding position of the legs.

Furthermore, the air bags 130a, 132a may include a number of different internal chambers that are separated by valves. For example, Fig. 10 shows portions 166, 168 in the areas facing the riders head. These portions 166, 168 are separated from the remainder of the airbag volume by respective valves 166a, 168a, which are dimensioned so that portions remain softer than the remainder of the air bags during a predetermined time period after deployment. As an alternative, separate inflators may be used for each separate internal chamber. Accordingly, the initial impact of the drivers head is further cushioned during this time period.

Fig. 11 shows how the upper outer belts 144, 154 are secured to the airbags 130, 132. According to an embodiment of the invention shown in Figs. 12A and 12B, the rear upper air bag 132 includes an inner chamber 132' and an outer chamber 132". The inner chamber 132' inflates first so that the outer belts 144, 154 can easily move upward as the airbags are deployed, then the outer chamber 132" inflates to tighten the outer belts, which causes the airbags 130, 132 to be urged toward or held close to the rider.

Thus, while there have shown and described and pointed out fundamental novel features of the invention as applied to a preferred embodiment thereof, it will be understood that various omissions and substitutions and changes in the form and details of the devices illustrated, and in their operation, may be made by those skilled in the art without departing from the spirit of the invention. For example, it is expressly intended that all combinations of those elements, which perform substantially the same function in substantially the same way to achieve the same results, are within the scope of the invention. Moreover, it should be recognized that structures and/or elements shown and/or described in connection with any disclosed form or embodiment of the invention may be incorporated in any other disclosed or described or suggested form or embodiment as a general matter of design choice. It is the intention, therefore, to be limited only as indicated by the scope of the claims appended hereto.

## CLAIMS

What is claimed is:

1. A crash protection system, comprising:
  - a base connectable to a support;
  - a front airbag module arranged proximate a front end of said base and comprising a front airbag;
  - a rear airbag module arranged proximate a rear end of said base and comprising a rear airbag;
  - a belt system including a first belt connectable around a waist of a rider and at least one strap connecting said first belt to said base;
  - a control system including sensors, said control system monitoring said sensors to determine whether a crash situation is present and said control system actuating said front airbag module and said rear airbag module and releasing said base from said support when the crash situation is present.
2. The crash protection system of claim 1, wherein said front airbag is deployed upward from said base and in front of the rider when said front airbag module is actuated, and said rear airbag is deployed upward from said base and in back of the rider when said front airbag is actuated.
3. The crash protection system of claim 1, wherein said first belt includes a front first belt portion and a rear first belt portion that are connectable by a right fastener and a left fastener, wherein said front first belt portion is connected to said base by a right front strap and a left front strap, and said rear portion is connected to said base by a right rear strap and a left rear strap, said right fastener arranged between said right front strap and said right rear strap on the right side of said base and said left fastener arranged between said left front strap and said left rear strap on the left side of said base.
4. The crash protection system of claim 3, further comprising an upper outer belt comprising a front left upper outer belt connected to a left side of said front airbag and said left fastener, a front right upper outer belt connected to a right side of said front airbag and said right fastener, a rear left upper

outer belt connected to a left side of said rear airbag and said left fastener, and a rear right upper outer belt connected to a right side of said rear airbag and said right fastener.

5. The crash protection system of claim 4, wherein said upper outer belt is separable from said first belt at said right fastener and said left fastener during deployment of said front airbag and said rear airbag while maintaining an integrity of said upper outer belt and said first belt.

6. The crash protection system of claim 4, wherein each of said right fastener and said left fastener each include a first portion connecting said inner belt and a second portion connecting said upper outer belt, said first portion being connected to said second portion by a frangible connection that breaks away in response to a deployment force of said airbags.

7. The crash protection system of claim 2, further comprising an upper outer belt comprising a left upper outer belt connected between a left side of said front airbag and a left side of said rear airbag, and a right upper outer belt connected between a right side of said front airbag and a left side of said rear airbag, said upper outer belt retaining said front airbag and rear airbag proximate a front and rear of the rider.

8. The crash protection system of claim 1, wherein said front airbag module is an upper front airbag module with an upper airbag and said rear airbag module is an upper rear airbag module with an upper rear airbag, said crash protection system further comprising:

a lower front airbag module arranged proximate a front end of said base and comprising a lower front airbag; and

a lower rear airbag module arranged proximate a rear end of said base and comprising a lower rear airbag.

9. The crash protection system of claim 8, wherein said upper front airbag is deployed upward from said base and in front of the rider when said upper front airbag module is actuated, said upper rear airbag is deployed upward from said base and in back of the rider when said upper rear airbag

module is actuated, said lower front airbag is deployed downward from said base and in front of said rider when said lower front airbag module is actuated, and said lower rear airbag is deployed downward from said base and in back of the rider when said lower rear airbag module is actuated.

10. The crash protection system of claim 1, wherein said front airbag is deployed downward from said base and in front of the rider when said front airbag module is actuated, and said rear airbag is deployed downward from said base and in back of the rider when said rear airbag module is actuated.

11. The crash protection system of claim 1, wherein said base comprises at least a portion of a motorcycle seat.

12. The crash protection system of claim 1, further comprising an ejector that pushes said base away from the support upon release of said base from the support.

13. The crash protection system of claim 1, wherein said belt system includes a front right strap connected to a front right side of said base, a rear right strap connected to a rear right side of said base, a front left strap connected to a front left side of said base, and a rear left strap connected to a rear left side of said base.

14. The crash protection system of claim 13, wherein said front right strap is reeved through a front right pulley and connected to a portion of a right fastener, said rear right strap is reeved through a rear right pulley and connected to another portion of said right fastener, said front left strap is reeved through a front left pulley and connected to a portion of a left fastener, and said rear left strap is reeved through a rear left pulley and connected to another portion of said left fastener;

said front right pulley is connected to said front left pulley by a front portion of said first belt; and

said rear right pulley is connected to said rear left pulley by a rear portion of said first belt.

15. The crash protection system of claim 13, wherein at least one of said front right strap, said front left strap, said rear right strap, and said rear left strap is connected to said base by a retractor mechanism.

16. The crash protection system of claim 13, wherein said sensors of said control system include a tension sensor on said at least one of said front right strap, said front left strap, said rear right strap, and said rear left strap.




FIG. 1




FIG. 2B




FIG. 2A

3/13




FIG. 3




FIG. 4






FIG. 5




FIG. 6

8/13




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

13/13




FIG. 12B




FIG. 12A

## INTERNATIONAL SEARCH REPORT

International application No.  
**PCT/US2014/013530****A. CLASSIFICATION OF SUBJECT MATTER****B62J 27/00(2006.01)i, A41D 13/018(2006.01)i, B60R 21/16(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

B62J 27/00; B60K 28/00; A41D 13/00; A41D 13/018; B60R 21/16

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) &amp; Keywords: crash, protection, airbag, belt, control, sensor, and strap

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 98-11793 A1 (ALALOOF, JACOB) 26 March 1998 See pages 8-9,12-15 and figures 2A,2C,6C,8A.	1-10
A		11-16
Y	US 2009-0019623 A1 (UCHIDA et al.) 22 January 2009 See paragraphs [0029]-[0048] and figures 1,7.	1-10
A	JP 2010-125992 A (HONDA MOTOR CO., LTD. et al.) 10 June 2010 See paragraphs [0016]-[0020] and figures 1-2.	1-16
A	US 2009-0127835 A1 (LIN, HSIU-PING) 21 May 2009 See paragraphs [0051]-[0053],[0075] and figures 6-8,23A.	1-16
A	US 2006-0125206 A1 (GOTO et al.) 15 June 2006 See paragraphs [0016]-[0023] and figures 1-3.	1-16

 Further documents are listed in the continuation of Box C. See patent family annex.

\* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search

15 April 2014 (15.04.2014)

Date of mailing of the international search report

**07 May 2014 (07.05.2014)**

Name and mailing address of the ISA/KR


International Application Division  
Korean Intellectual Property Office  
189 Cheongsu-ro, Seo-gu, Daejeon Metropolitan City, 302-701,  
Republic of Korea

Facsimile No. +82-42-472-7140

Authorized officer

CHOI, Hyun Goo

Telephone No. +82-42-481-8288



**INTERNATIONAL SEARCH REPORT**

Information on patent family members

International application No.

**PCT/US2014/013530**

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 98-11793 A1	26/03/1998	EP 1014814 A1 IL 113081 A IL 113081 D0 JP 2001-502383 A WO 98-11793 A1	05/07/2000 05/12/1996 29/06/1995 20/02/2001 26/03/1998
US 2009-0019623 A1	22/01/2009	CN 101151070 A CN 101151070 B EP 1857147 A1 EP 1857147 A4 HK 1118746 A1 KR 10-2007-0115990 A US 7690051 B2 WO 2006-095440 A1	26/03/2008 03/08/2011 21/11/2007 29/04/2009 01/06/2012 06/12/2007 06/04/2010 14/09/2006
JP 2010-125992 A	10/06/2010	JP 05113731 B2	09/01/2013
US 2009-0127835 A1	21/05/2009	TW 200918371 A	01/05/2009
US 2006-0125206 A1	15/06/2006	DE 602005004727 D1 DE 602005004727 T2 EP 1668999 A1 EP 1668999 B1 JP 2006-160171 A US 7401364 B2	27/03/2008 05/03/2009 14/06/2006 13/02/2008 22/06/2006 22/07/2008