

(51) International Patent Classification:
H04W 36/00 (2009.01)(21) International Application Number:
PCT/CN2015/073373(22) International Filing Date:
27 February 2015 (27.02.2015)


(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61946418 28 February 2014 (28.02.2014) US
14630233 24 February 2015 (24.02.2015) US(71) Applicant: **HUAWEI TECHNOLOGIES CO., LTD.**
[CN/CN]; Huawei Administration Building, Bantian, Long-
gang District, Shenzhen, Guangdong 518129 (CN).(72) Inventors: **KAIPPALLIMALIL, John;** 3260
Heatherbrook Ln., Richardson, TX Texas 75082 (US).
MCCANN, Peter J.; 1030 Crim Rd, Bridgewater, NJ New
Jersey 08807 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR CONNECTION REHOMING

**Fig. 2**(57) Abstract: A method for connection rehomming by a user
equipment includes attaching to a first network attachment
point (AP) and establishing a first connection to a first packet
data network (PDN) interface, and moving from the first net-
work AP to a second network AP. The method includes dis-
covering a first cost associated with the first connection is
high, and rehomming the first connection, thereby establishing
a second connection coupling the UE to a second network
AP and to a second PDN interface, wherein a second cost as-
sociated with the second connection is low.



Declarations under Rule 4.17:

Published:

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))* — *with international search report (Art. 21(3))*

System and Method for Connection Rehoming

[0001] This application claims the benefit of U.S. Provisional Application No. 61/946,418, filed on February 28, 2014 and entitled “System and Method for Packet Data Network Connection Rehoming,” and U.S. Non-Provisional Application No. 14/630,233, filed on February 24, 2015 and entitled “System and Method for Connection Rehoming”. Each of these applications is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates generally to digital communications, and more particularly to a system and method for connection reforming in communications networks.

BACKGROUND

[0003] Denser radio networks, localized patterns of mobility, virtualization and other technological/business drivers are causing the 3GPP evolved packet core (EPC) to become more distributed. Distributed gateways (internet protocol (IP) anchor points) of such EPC networks are much closer to the user. As a user moves from one radio access network (RAN) node/evolved Node B (eNB) to the next, it is likely that the point of initial attachment (initial packet data network gateway (PGW)) is not the best or closest.

SUMMARY OF THE DISCLOSURE

[0004] Example embodiments of the present disclosure which provide a system and method for connection rehomings in communications networks.

[0005] In accordance with an example embodiment of the present disclosure, a method for connection rehomings is provided. The method includes attaching, by a user equipment (UE), to a first network attachment point (AP) and establishing a first connection to a first packet data network (PDN) interface, and moving, by the UE, from the first network AP to a second network AP. The method includes discovering, by the UE, a first cost associated with the first connection is high, and rehomings, by the UE, the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.

[0006] In accordance with another example embodiment of the present disclosure, a method for connection rehomings is provided. The method includes receiving, by a network entity, a first control message from a user equipment (UE) initiating a rehomings for a first connection coupling the UE to a first network AP and to a first packet data network (PDN) interface, wherein a first cost associated with the first connection is high, and sending, by the network entity, a second control message to the UE, the second control message completing the rehomings of the first connection.

[0007] In accordance with another example embodiment of the present disclosure, a user equipment (UE) adapted to perform connection rehomings is provided. The UE includes a processor, and a computer readable storage medium storing programming for execution by the processor. The programming including instructions to attach to a first network attachment point (AP) and establish a first connection to a first packet data network (PDN) interface, move from the first network AP to a second network AP, discover a first cost associated with the first connection is high, and rehome the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.

[0008] One advantage of an embodiment is that rehomeing leads to the replacement of high cost (overhead, resources, and the like) connections with low cost connections, thereby reducing communications costs.

[0009] A further advantage of an embodiment is that the user equipments initiate the rehomeing since the user equipments have knowledge of the communications needs of applications that they are executing.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] For a more complete understanding of the present disclosure, and the advantages thereof, reference is now made to the following descriptions taken in conjunction with the accompanying drawing, in which:

[0011] Figure 1 illustrates an example communications system according to example embodiments described herein;

[0012] Figure 2 illustrates flow diagram of example operations occurring in a UE as the UE participates in connection rehomeing according to example embodiments described herein;

[0013] Figure 3 illustrates an example communications system providing a high-level view of PDN connections and UE mobility according to example embodiments described herein;

[0014] Figure 4 illustrates an example message exchange and processing diagram highlighting case A with dynamic mobility management (DMM) based PDN rehomeing in 3GPP compliant networks according to example embodiments described herein;

[0015] Figure 5 illustrates an example message exchange and processing diagram highlighting case B with MME based PDN rehomeing in 3GPP compliant networks according to example embodiments described herein;

[0016] Figure 6 illustrates an example communications system providing a high-level view of PDN connections of a UE before and after rehomeing in trusted non-3GPP (N3GPP) networks according to example embodiments described herein;

[0017] Figure 7 illustrates an example message exchange and processing diagram highlighting case C with DMM based PDN rehomeing in trusted N3GPP networks according to example embodiments described herein;

[0018] Figure 8 illustrates an example message exchange and processing diagram highlighting case D with TWAG based PDN rehomeing in trusted N3GPP networks according to example embodiments described herein;

[0019] Figure 9 illustrates a flow diagram of example operations occurring in a network entity participating in connection rehomeing according to example embodiments described herein;

[0020] Figure 10 is a block diagram of a processing system that may be used for implementing the devices and methods disclosed herein; and

[0021] Figure 11 is a block diagram of a user equipment that may be used for implementing the devices and methods disclosed herein.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

[0022] The operating of the current example embodiments and the structure thereof are discussed in detail below. It should be appreciated, however, that the present disclosure provides many applicable inventive concepts that can be embodied in a wide variety of specific contexts. The specific embodiments discussed are merely illustrative of specific structures of the disclosure and ways to operate the disclosure, and do not limit the scope of the disclosure.

[0023] One embodiment of the disclosure relates to connection rehomeing in communications networks. For example, a user equipment (UE) attaches to a first network attachment point (AP) and establishing a first connection to a first packet data network (PDN) interface, and moves from the first network AP to a second network AP. The UE discovers a first cost associated with the first connection is high, and rehomes the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.

[0024] The present disclosure will be described with respect to example embodiments in a specific context, namely communications systems that support user equipment (UE) mobility and UE initiated rehomeing. The disclosure may be applied to standards compliant communications systems, such as those that are compliant with Third Generation Partnership Project (3GPP), IEEE 802.11, IETF, and the like, technical standards, and non-standards compliant communications systems, that support UE mobility and UE initiated rehomeing.

[0025] Figure 1 illustrates an example communications system 100. Communications system 100 includes an Evolved Packet Core (EPC) 112, a macro EPC 105 (shown in Figure 1 as "MACRO-CELL"), and a micro EPC 110 (shown in Figure 1 as "MICRO-CELL NET-1"). Macro EPC 105 and micro EPC 110 may be components of EPC 112. EPC 112 may also include a mobility management entity (MME) 113 and an authentication authorization accounting proxy (AAA-P) 114. MME 113 may handle signaling related to mobility and security for network access, while AAA-P 114 may provide authentication, authorization, and/or accounting services for communications system 100. EPC 112 may be a stand-alone network or may be coupled to another packet data network (PDN) 116. A UE may move between radio nodes and/or cells in the networks. As an illustrative example, UE 115 that is

attached to evolved Node B (eNB) 120 of macro EPC 105 may move to a coverage area served by access point (AP) ("AP-1") 122, where it is shown as UE 117 to avoid confusion. AP 122 may be an eNB, a micro cell, a femto cell, a pico cell, or a low power node (LPN). Macro EPC 105 is depicted as an eNB, but could be any manner of AP, including a cell, a micro cell, a femto cell, a pico cell, or a LPN.

[0026] When UE 115 is connected to eNB 120 of the macro EPC 105, packet data network (PDN) connections of UE 115 are established to a serving gateway (SGW) 125 (shown as SGW1 of the EPC 112) and a packet data network gateway (PGW) 127 (shown as PGW1). The term PGW1 127 is used herein, although it should be understood that the PGW1 127 element can comprise any PDN interface. As UE 115 moves from the macro EPC 105 to AP-1 122 of the micro EPC 110, UE 117 (formerly UE 115) may establish an S1 connection to SGWx 130 while maintaining an S5 connection to PGW1 127. The establishment of the S1 and S5 connections may help to ensure that the Internet Protocol (IP) session is not suddenly lost. Communications system 100 may be able to signal (to the UEs) that the IP attachment is not optimal and have the UEs set up PDN connections to a more optimal PDN interface, such as PGWx 132 in this situation. The term PGWx 132 is used herein, although it should be understood that the PGWx 132 element can comprise any PDN interface. Typically, a PDN interface may be any of a SGW, a PGW, a router, a gateway, and the like.

[0027] While it is understood that communications systems may employ multiple eNBs/nodes capable of communicating with a number of UEs, only one eNB, two APs, a number of nodes, and a number of UEs are illustrated for simplicity.

[0028] The IP connections and PDN transfer capabilities are valuable for transmission control protocol (TCP) and/or user datagram protocol (UDP), even when new transports such as multipath TCP (MPTCP) are utilized. They provide UEs the ability to select a time at which it is optimal to transfer the connection, as well as packets in transit.

[0029] In Third Generation Partnership Project (3GPP) compliant networks, the SGW anchors the mobility of a UE between eNBs while the PGW serves as an anchor for the IP address. Mobility mechanisms in S1 and X2 interfaces address how the network can maintain the session during handover between different eNBs (and SGWs). On the other hand, IP

session mobility is not addressed in current networks because the PGW is highly centralized and the IP address remains anchored as the user moves within the radio access networks.

[0030] In future mobile networks with highly distributed gateways, IP session mobility may become an issue. As a UE moves from one radio access network (RAN) eNB and/or node to the next, it is likely that the point of initial attachment (initial PGW) is not the best or closest. The UE may need to be notified of its distance from the first PGW. The distance between UE and first PGW may be quantified in terms of cost, for example. The cost may be characterized as overhead, network resources, and the like, dedicated to the connection(s) between the UE and the first PGW. The established PDN connections need to be moved so as not to adversely impact packets in transit during these events. An example embodiment addresses this by moving PDN connections to the closer IP access point (i.e., PGW).

[0031] Since 3GPP compliant networks use bearers and PDN connections, which are Layer 2 constructs, over which IP services are transported, example embodiments are also applicable to 3GPP PDN connection handling. Each UE may have multiple PDN connections. Current systems may need extensions to provide fully optimal selection of gateways or routers.

[0032] While future mobile and/or 3GPP compliant networks are expected to have much more distributed gateways, it may also be the case that transports (such as MPTCP) can alleviate the need for extensive IP layer mobility support. Example embodiments may also work with MPTCP to provide IP session continuity for a short duration, and to transfer the connection to a more optimally routed one. Therefore, example embodiments should be applicable regardless of the transport layer of the IP packet, e.g., UDP, TCP, MPTCP, and the like.

[0033] According to an example embodiment, mobility support is provided in networks in which IP gateways are distributed. In such a situation, a UE discovers the cost of connections to the PDN interfaces is high and determines to rehome the connections. The UE may discover the status of its IP attachments, and, if it is not optimally attached, it may be able to reattach to a better PDN interface (e.g., a PGW, a SGW, a router, a gateway, and the like). As a result of the high costs, the UE may trigger a setup to rehome the PDN connection(s). The UE may indicate to the network at an appropriate time (based on application status, transport, and the like) to transition to the new PDN interface. The UE may be able to trigger the tear

down of old and/or suboptimal PDN connections and establish new PDN connections. The network may facilitate the change from the old PDN connections to the new PDN connections.

[0034] According to an example embodiment, 3GPP and IEEE 802.11 WiFi networks attached to the EPC are supported. Solutions for each of the cases are provided. A first solution temporarily relocates the IP address while the connection(s) is rehommed, while a second solution maintains a tunnel while the connection(s) is rehommed.

[0035] According to an example embodiment, the transition to a new PDN interface and/or connection occurs while a session is in progress, which becomes more valuable as gateways become distributed. The example embodiments may be implemented in PGWs, SGWs, mobility management entities (MMEs), trusted wireless access gateways (TWAGs), and other nodes of networks, such as 3GPP EPCs, and the like.

[0036] According to an example embodiment, networks, such as 3GPP EPCs, establish a new PDN connection following a mobility event between radio access clusters, retains an old IP prefix, advertises both the old IP prefix (presumably a high cost prefix) and a new IP prefix (typically a low cost prefix), and reclaims the high cost prefix after the UE switches to the low cost prefix.

[0037] According to an example embodiment, a MME indicates rout distance (e.g., connection cost) and enables the rehomming of PDN connection(s).

[0038] According to an example embodiment, a 3GPP TWAG establishes a PDN connection following a mobility event between clusters, retains an old IP prefix, advertises both the old IP prefix (presumably a high cost prefix) and a new IP prefix (typically a low cost prefix) from a local IP prefix pool, and reclaims the high cost prefix after the UE switches to the low cost prefix. According to another example embodiment, the TWAG indicates the high cost prefix and rehomes the PDN connection and IP prefix to a low cost PDN interface when the UE indicates.

[0039] According to an example embodiment, the UE discovers high cost connections in router advertisements including a measure of cost associated with the connections, as well as MME indications.

[0040] Figure 2 illustrates a flow diagram of example operations 200 occurring in a UE as the UE participates in connection rehomings. Operations 200 may be indicative of operations occurring in a UE, such as UE 117, as the UE participates in connection rehomings.

[0041] Operations 200 may begin with the UE attaching to an initial EPC of a communications system (block 205). Part of the initial attach may include the assigning to PGW and SGW to serve the UE (referred to herein as initial PGW and SGW), setting up PDN connection(s), obtaining an IP prefix (through IP version 6 (IPv6) stateless autoconfiguration, dynamic host configuration protocol (DHCP), and the like), and the like. The UE may exchange packets with services over the PDN connection(s). The UE may also move about.

[0042] As the UE moves, it may participate in a mobility event (block 210). Examples of mobility events may include a handover, a detach-attach operation, and the like. A result of the mobility event may be a change in SGW and/or PGW serving the UE (referred to herein as new SGW and PGW). Along with the change in SGW and/or PGW, the UE may receive a new IP prefix. The change(s) may result in increased communications costs (or increased routing distance) for packets exchanged between the UE and the services to which it is connected.

[0043] The UE may discover IP attachment information from the communications system (block 215). The IP attachment information may include IP prefixes servable by the new SGW and PGW, as well as measures of cost for the servable IP prefixes. As discussed previously, the measures of cost for the servable IP prefixes may be reflective of the routing distances of, resources utilized by, latency incurred by, and the like, packets exchanged between the UE and the services to which it is connected.

[0044] Based on the IP attachment information, the UE may initiate a transition to a new PDN interface (block 220). The UE may evaluate the servable IP prefixes in accordance with the measures of cost, as well as application usage, application capability, and the like, to determine if it can transition to the new PDN interface. As an illustrative example, the UE determines which of the servable IP prefixes can be released. Additionally, the UE determines how to handle IP prefixes that it is to continue using, but are not servable by the new SGW and PGW.

[0045] The UE may rehome connections (block 225). The UE may rehome connections by replacing the IP prefixes released with replacement connections established through the new SGW and PGW. Furthermore, for those IP prefixes that are not servable by the new SGW and PGW but that are still used by the UE, the UE may establish mobile IP sessions to continue using those IP prefixes.

[0046] In many networks that support mobility, such as 3GPP compliant networks, bearers and PDN connections (Layer 2 constructs) are used. The bearers and PDN connections are used to transport IP services. Each UE may have multiple PDN connections. Current networks may need extensions to provide fully optimal selection of gateways and/or routers.

[0047] Figure 3 illustrates an example communications system 300 providing a high-level view of PDN connections and UE mobility. As shown in Figure 3, a UE 305 is attached to an eNB 307 (eNB-a) of a cluster 309 (Cluster A). UE 305 is also connected to SGW 320 and PGW 322 of 3GPP EPC 324. The term PGW 322 is used herein, although it should be understood that the PGW 322 element can comprise any PDN interface. As UE 305 moves, it becomes attached to an eNB 310 (eNB-b) of a cluster 312 (Cluster B) after a mobility event. UE 305 is relabeled UE 314 to avoid confusion. 3GPP EPC 324 may maintain IP connectivity by attaching to SGW 325 while maintaining the initial IP prefix (IP-1). The initial IP prefix (IP-1) may be maintained by either relocating the IP prefix to PGW 327 of 3GPP EPC 329 using DMM (referred to herein as case A which may be referred to as maintaining connectivity through DMM) or by establishing a tunnel to PGW 322 of 3GPP EPC 324 (referred to herein as case B which may be referred to as maintaining connectivity through tunneling). The term PGW 327 is used herein, although it should be understood that the PGW 327 element can comprise any PDN interface.

[0048] Both PGW 322 and MME 330 may be aware that the connection to a PDN 340 through the currently used PDN interface (i.e., PGW 322) is more costly (i.e., more distant in network terms from UE 314). As an illustrative example, PGW 322 determines that SGW 325 is in another IP subnet through configuration information, autonomous system (AS) information, and the like. MME 330 may similarly know through PDN connection setup that PGW 322 is distant from UE 314. Either of these entities (PGW 322 and/or MME 330) may be capable of informing UE 314 regarding connection cost or router distance. It is noted that

3GPP EPC 329 also includes a MME 332 and that while MME 330 and MME 332 may be implemented in a disjoint manner, they may be operatively coupled together and share common information and state.

[0049] When UE 314 receives information regarding connection cost or router distance and when it is ready to transfer the PDN connection(s) to a more optimal router (i.e., PGW 327), UE 314 may trigger a process to rehome the PDN connection(s) and bearers for an access point name (APN). Several different rehome processes are possible, as is shown in Figure 3.

[0050] Figure 4 illustrates an example message exchange and processing diagram 400 highlighting case A with dynamic mobility management (DMM) based PDN rehome in 3GPP compliant networks. Diagram 400 includes messages exchanged and processing occurring in a UE 405, a MME 407, a first SGW ("SGW-a") 409, a first PGW ("PGW-a") 411, a second SGW ("SGW-b") 413, and a second PGW ("PGW-b") 415. Diagram 400 refers to case A as shown in Figure 3.

[0051] UE 405 attaches to an eNB, e.g., eNB-a, in cluster A and MME 407 may assign it to be served by first SGW 409 and first PGW 411 (shown as block 420). MME 407 may select first PGW 411 and initiate signaling to setup PDN connection(s). UE 405 may obtain an IP prefix from first PGW 411 (e.g., IP-1), such as by using IPv6 stateless autoconfig or DHCP, for example. As part of obtaining the IP prefix, UE 405 may receive a router advertisement from first PGW 411 including IP-1 and an associated measure of cost for IP-1, low (shown as event 422).

[0052] As UE 405 moves, it may participate in a mobility event, e.g., move from eNB-a to an eNB, e.g., eNB-b in cluster B (shown as block 424). As part of the mobility event, MME 407 changes the SGW serving UE 405 from first SGW 409 to second SGW 413. MME 407 may also select second PGW 415 to replace first PGW 411. MME 407 may also generate a new session, as well as indicate to second PGW 415 to obtain IP-1 from first PGW 411. It is noted that the indication (the indication for second PGW 415 to obtain IP-1 from first PGW 411) is a new indication.

[0053] Second PGW 415 may acquire IP-1 from first PGW 411 and set up S5 bearer sessions (shown as block 426). MME 407 may complete signaling to establish and link S1 and radio

bearers. Second PGW 415 may advertise to other routers that it owns IP-1. First PGW 411 may exclude IP-1 from its advertisements (e.g., border gateway protocol (BGP)).

[0054] Second PGW 415 may send a first router advertisement for IP-1 with associated measure of cost to high (shown as event 428), and a second router advertisement for IP-2 (an IP prefix within its own IP prefix pool) with associated measure of cost to low (shown as event 430). The sending of the router advertisements for IP-1 and IP-2 may constitute a discovery process for UE 405 (event 432), where it discovers available IP prefixes and costs associated therewith.

[0055] UE 405 may evaluate the information received during discovery process 432. UE 405 may determine to continue using its current IP prefix. Alternatively, UE 405 may determine to transition to new, low cost IP prefix. When UE 405 determines that it is to transition to the new, low cost IP prefix, it may generate an address associated with the IP-2 IP prefix and send a neighbor solicitation (NS) duplicate address detection (DAD) message with the address associated with the IP-2 IP prefix (shown as event 434). In other words, UE 405 is checking to determine if it is using a duplicate address (the address associated with the IP-2 IP prefix). If the address is not a duplicate, which UE 405 may be able to determine if it does not receive a DAD response message within a specified time duration, UE 405 may use the address associated with the IP-2 IP prefix. Second PGW 415 may interpret the use of the address associated with the IP-2 IP prefix by UE 405 as a trigger for it to send one or more neighbor unreachability detection messages (NUDs) for IP-1 IP prefix (shown as event 436). Collectively, events 434 and 436 may be referred to as the connection rehomeing process 438.

[0056] Second PGW 415 may release the IP-1 IP prefix to first PGW 411 after transmitting the NUDs in event 436 and determining that the IP-1 IP prefix is not in use (shown as event 440). With the release of the IP-1 IP prefix, second PGW 415 may no longer advertise IP-1, while first PGW 411 may resume advertising IP-1 since it has been released. The PDN connection and the IP prefix for UE 405 have been rehomeed.

[0057] Figure 5 illustrates an example message exchange and processing diagram 500 highlighting case B with MME based PDN rehomeing in 3GPP compliant networks. Diagram 500 includes messages exchanged and processing occurring in a UE 505, a MME 507, a first

SGW ("SGW-a") 509, a first PGW ("PGW-a") 511, a second SGW ("SGW-b") 513, and a second PGW ("PGW-b") 515.

[0058] UE 505 attaches to an eNB, e.g., eNB-a, in cluster A and MME 507 may assign it to be served by first SGW 509 and first PGW 511 (shown as block 520). MME 507 may select first PGW 511 and initiate signaling to setup PDN connection(s). UE 505 may obtain an IP prefix from first PGW 511 (e.g., IP-1), such as by using IPv6 stateless autoconfig or DHCP, for example. As part of obtaining the IP prefix, UE 505 may receive a router advertisement from first PGW 511 including IP-1 and an associated measure of cost for IP-1, low (shown as event 522).

[0059] As UE 505 moves, it may participate in a mobility event, e.g., move from eNB-a to an eNB, e.g., eNB-b in cluster B (shown as block 524). As part of the mobility event, MME 507 changes the SGW serving UE 505 from first SGW 509 to second SGW 513, but first PGW 511 is retained so that IP session continuity is maintained.

[0060] UE 505 may participate in a discovery process 526 to determine costs associated with packet routing. Discovery process 526 may include a router cost metric provided by first PGW 511 in a router advertisement with IP-1 and a measure of cost for IP-1 (shown as event 528). The measure of cost may serve as an indication to UE 505 of costs of the current connection. UE 505 may use the measure of cost to determine if it should rehome the current connection. Alternatively, discovery process 526 may include information provided by MME 507. MME 507 may send a notification message to UE 505, where the notification message includes an indication of cost for the current connection and/or advice for UE 505 to rehome the current connection (shown as event 530). Discovery process 526 may include one or both of the alternatives.

[0061] UE 505 may send to MME 507 a rehome request message (shown as event 532) with PDN and/or access point name (APN) information. Alternatively, an attach request message may be sent with a parameter indicating a rehome mode, e.g., parameter: "mode = rehome". MME 507 may send a delete session request to delete the current connection and bearer resources at first PGW 511 and second SGW 513 (shown as event 534). MME 507 may send a create session request to create a PDN connection and bearer resources to second PGW 515 and second SGW 513 (shown as event 536). MME 507 may link the new PDN connection to

existing radio access bearers at eNB-b, as well as send a rehome response message to UE 505 (shown as event 538). Collectively, events 532-538 may be referred to as connection rehome process 540. The PDN connection and IP prefix of UE 505 have been rehomed. Second PGW 515 may send a router advertisement to UE 505 for IP-2 with the measure of cost set to low (shown as event 542).

[0062] With respect to mobility in trusted non-3GPP (N3GPP) compliant networks, 3GPP uses bearers and PDN connections (Layer 2 constructs) over which IP services are transported. Each UE may have multiple PDN connections. Extensions are used to provide fully optimal selection of gateways or routers.

[0063] Figure 6 illustrates an example communications system 600 providing a high-level view of PDN connections of a UE before and after rehome in trusted N3GPP networks. The trusted N3GPP networks shown in Figure 6 are IEEE 802.11 WiFi networks, but other trusted N3GPP networks may operate in a similar manner. As shown in Figure 6, a UE 605 may be initially attached to AP-x 607 in cluster A 609. UE 605 may be attached to a first TWAG (TWAG-a) 615 and first PGW (PGW-a) 617 of 3GPP EPC 619. The term PGW-a 617 is used herein, although it should be understood that the PGW-a 617 element can comprise any PDN interface. As UE 605 moves, it participates in a mobility event and attaches to AP-y 611 in cluster B 613, where it is relabeled UE 613 to avoid confusion. As UE 613 becomes attached to AP-y 611, 3GPP EPC 619 maintains IP session continuity by attaching to second TWAG (TWAG-b) 621 while maintaining IP anchor at first PGW 617 and retaining the initially assigned IP prefix, IP-1. The initially assigned IP prefix may be maintained by relocating the IP prefix to second PGW 623 using DMM (shown as case C which may be referred to as maintaining connectivity through DMM) or by managing a tunnel(s) between first PGW 617 and second TWAG 621 (shown as case D which may be referred to as maintaining connectivity through tunneling). The term PGW 623 is used herein, although it should be understood that the PGW 623 element can comprise any PDN interface. First PGW 617 may be aware that routing packets to and from UE 613 is now more costly (due to increased distance or latency, for example). As an example, first PGW 617 determines that second TWAG 621 is in another IP subnet using configuration information, autonomous system (AS) information, and the like. When UE 613 acquires knowledge of the costs of staying with first PGW 617 and is ready to transfer the PDN connection(s) to a more

optimal router (e.g., second PGW 623), UE 613 may trigger a process to rehome the PDN connection(s) and bearers for the APN. Several different rehome processes are possible, as is shown in Figure 6.

[0064] Figure 7 illustrates an example message exchange and processing diagram 700 highlighting case C with DMM based PDN rehome in trusted N3GPP networks. Diagram 700 includes messages exchanged and processing occurring in a UE 705, a first TWAG ("TWAG-a") 707, a first PGW ("PGW-a") 709, a second TWAG ("TWAG-b") 711, and a second PGW ("PGW-b") 713). Diagram 700 refers to case C as shown in Figure 6.

[0065] UE 705 attaches to AP-x in cluster A and first TWAG 707 may set up general packet radio service (GPRS) tunneling protocol (GTP) bearers and/or PDN connection(s) to first PGW 709 (shown as event 715). UE 705 may obtain an initial IP prefix IP-1 from first PGW 709, such as by using IPv6 stateless autoconfig or DHCP, for example. As part of obtaining the IP prefix, UE 705 may receive a router advertisement sent by first PGW 709, the router advertisement including IP-1 and an associated measure of cost for IP-1, low (shown as event 717).

[0066] As UE 705 moves, it may participate in a mobility event, e.g., move from AP-x to another AP, e.g., AP-y in cluster B and attaches to second TWAG 711 (shown as block 719). As part of attaching to second TWAG 711, UE 705 may download authorization profiles to second TWAG 711. As an illustrative example, the authorization profiles may include the previous address of UE 705 (IP-1), gateway (first PGW 709), as well as an indication of IP address relocation support. It is noted that the indication of the IP address relocation support may be a new indication.

[0067] Since IP address relocation is supported, second TWAG 711 may create a session to second PGW 713 (shown as event 721). Second TWAG 711 may provide to second PGW 713 the IP prefix of UE 705 (IP-1) and/or a gateway address (address of first PGW 709). Second TWAG 711 may alternatively provide a fully qualified domain name (FQDN), which may comprise IP-1 and the address of first PGW 709. Second TWAG 711 may send a router advertisement including IP-1 and a measure of cost set to high (shown as event 723). Second PGW 713 may obtain IP-1 from first PGW 709 using any of a variety of widely known techniques (shown as event 725).

[0068] Second TWAG 711 may send a router advertisement including IP-1 and a measure of cost set to high (shown as event 727). Second TWAG 711 may send a router advertisement including IP-2 (an IP prefix from its IP pool) and a measure of cost set to low (shown as event 729). Events 725-729 may be collectively referred to as discovery 731.

[0069] When UE 705 is ready to transition to the new, low cost IP prefix (IP-2), UE 705 may generate an address associated with the IP-2 IP prefix and send a NS DAD message with the address associated with IP-2 (shown as event 733). If the address is not a duplicate, which UE 705 may be able to determine if it does not receive a DAD response message within a specified time duration, UE 705 may use the address associated with IP-2 IP. Second TWAG 711 may interpret the use of the address associated with IP-2 by UE 705 as a trigger to send one or more NUD messages with IP-1 (shown as event 735). Events 733-735 may be collectively referred to as the connection rehomeing process 737. Second TWAG 711 may release IP-1 and PDN connection segment S5 by sending a delete session request message to first PGW 709 (shown as event 739). Second TWAG 711 may also stop advertising IP-1. The PDN connection and the IP prefix for UE 705 have been rehomed.

[0070] Figure 8 illustrates an example message exchange and processing diagram 800 highlighting case D with TWAG based PDN rehomeing in trusted N3GPP networks. Diagram 800 includes messages exchanged and processing occurring in a UE 805, a first TWAG ("TWAG-a") 807, a first PGW ("PGW-a") 809, a second TWAG ("TWAG-b") 811, and a second PGW ("PGW-b") 813). Diagram 800 refers to case D as shown in Figure 6.

[0071] UE 805 attaches to AP-x in cluster A and first TWAG 807 may set up general packet radio service (GPRS) tunneling protocol (GTP) bearers and/or PDN connection(s) to first PGW 809 (shown as event 815). UE 805 may obtain an initial IP prefix IP-1 from first PGW 809, such as by using IPv6 stateless autoconfig or DHCP, for example. As part of obtaining the IP prefix, UE 805 may receive a router advertisement sent by first PGW 809, the router advertisement including IP-1 and an associated measure of cost for IP-1, low (shown as event 817).

[0072] As UE 805 moves, it may participate in a mobility event, e.g., move from AP-x to another AP, e.g., AP-y in cluster B and attaches to second TWAG 811 (shown as block 819). Second TWAG 811 may set up PDN connections and/or bearer sessions to first PGW 809 so

that IP session continuity is maintained. Second TWAG 811 may send a router advertisement with IP-1 and a measure of cost equal to high (shown as event 821). The router advertisement may serve as an indication to UE 805 that second TWAG 811 may route IP-1 but that the cost for such routing is high. Event 821 may be referred to as discovery 823.

[0073] When UE 805 is ready to transition to a new, low cost IP prefix, UE 805 may send a rehome request message to second TWAG 811 (shown as event 825). The rehome request message may be a newly defined message. Second TWAG 811 may send a delete session request message to delete PDN connection(s) and/or bearer(s) at first PGW 809 (shown as event 827). Second TWAG 811 may send a create session request message to establish PDN connection(s) and/or bearer(s) at second PGW 813 (shown as event 829). It is noted that the delete session request and the create session request and attendant response messages may occur sequentially or in parallel with one another. In other words, second TWAG 811 may send the delete session request and the create session request sequentially or in parallel. With the PDN connection(s) and/or bearer(s) established, second TWAG 811 may send a rehome response message to UE 805 (shown as event 831). Events 825-831 may be referred to as the connection rehome process 835. The PDN connection and the IP prefix for UE 805 have been rehomed. Second TWAG 811 may send a router advertisement with IP-2 and a measure of cost equal to low (shown as event 837). It is noted that the rehomed S5 sessions may be treated as continuations of initial S5 sessions.

[0074] Figure 9 illustrates a flow diagram of example operations 900 occurring in a network entity participating in connection rehomeing. Operations 900 may be indicative of operations occurring in a network entity, such as a second PGW (such as second PGW 415), a MME (such as MME 507), a second TWAG (such as second TWAG 711 and 811), and the like, as the network entity participates in connection rehomeing.

[0075] Operations 900 may begin with the network entity participating in a mobility event (block 905). The network entity may participate in a mobility event where a UE changes from a first SGW to a second SGW or from a first TWAG to a second TWAG, for example. When the UE participates in discovery and when the UE is ready to participate in the connection rehomeing, the UE may initiate the connection rehomeing by sending a first control message to the network entity (block 910). The first control message may differ depending

on the mechanism used for connection rehomeing. As an illustrative example, if DMM is used for connection rehomeing, the first control message may be a DAD message sent by the UE to the network entity (the second PGW). If MME based connection rehomeing is being implemented, the first control message may be a rehome request message sent to the network entity (the MME). In the situation when trusted N3GPP compliant networks are involved in connection rehomeing, the first control message may be a DAD message sent to the second TWAG when DMM is used and a rehome request message sent by the UE when TWAG based connection rehomeing is used. The network entity may send a second control message to the UE to finalize the connection rehomeing (block 915). The second control message may differ depending on the mechanism used for connection rehomeing. As an illustrative example, if DMM is used for connection rehomeing, the second control message may be a NUD message sent by the network entity to the UE. If MME based connection rehomeing is being implemented, the second control message may be a rehome response message sent by the MME to the UE. In the situation when trusted N3GPP compliant networks are involved in connection rehomeing, the second control message may be a NUD message sent by the second TWAG when DMM is used and a rehome response message sent by the second TWAG when TWAG based connection rehomeing is used.

[0076] Figure 10 is a block diagram of a processing system 1000 that may be used for implementing the devices and methods disclosed herein. Specific devices may utilize all of the components shown, or only a subset of the components, and levels of integration may vary from device to device. Furthermore, a device may contain multiple instances of a component, such as multiple processing units, processors, memories, transmitters, receivers, etc. The processing system may comprise a processing unit equipped with one or more input/output devices, such as a speaker, microphone, mouse, touchscreen, keypad, keyboard, printer, display, and the like. The processing unit may include a central processing unit (CPU), memory, a mass storage device, a video adapter, and an I/O interface connected to a bus.

[0077] The bus may be one or more of any type of several bus architectures including a memory bus or memory controller, a peripheral bus, video bus, or the like. The CPU may comprise any type of electronic data processor. The memory may comprise any type of non-transitory system memory such as static random access memory (SRAM), dynamic random

access memory (DRAM), synchronous DRAM (SDRAM), read-only memory (ROM), a combination thereof, or the like. In an embodiment, the memory may include ROM for use at boot-up, and DRAM for program and data storage for use while executing programs.

[0078] The mass storage device may comprise any type of non-transitory storage device configured to store data, programs, and other information and to make the data, programs, and other information accessible via the bus. The mass storage device may comprise, for example, one or more of a solid state drive, hard disk drive, a magnetic disk drive, an optical disk drive, or the like.

[0079] The video adapter and the I/O interface provide interfaces to couple external input and output devices to the processing unit. As illustrated, examples of input and output devices include the display coupled to the video adapter and the mouse/keyboard/printer coupled to the I/O interface. Other devices may be coupled to the processing unit, and additional or fewer interface cards may be utilized. For example, a serial interface such as Universal Serial Bus (USB) (not shown) may be used to provide an interface for a printer.

[0080] The processing unit also includes one or more network interfaces, which may comprise wired links, such as an Ethernet cable or the like, and/or wireless links to access nodes or different networks. The network interface allows the processing unit to communicate with remote units via the networks. For example, the network interface may provide wireless communication via one or more transmitters/transmit antennas and one or more receivers/receive antennas. In an embodiment, the processing unit is coupled to a local-area network or a wide-area network for data processing and communications with remote devices, such as other processing units, the Internet, remote storage facilities, or the like.

[0081] One embodiment of the disclosure relates to a user equipment (UE) that may be used for implementing the devices and methods disclosed herein. For example, Figure 11 is a block diagram of the user equipment that may be used for implementing the devices and methods disclosed herein. Preferably, the UE 1100 may include an attaching unit 1105, a moving unit 1110, a discovering unit 1115 and a rehomeing unit 1120. The attaching unit 1105 is configured to attach to a first network attachment point (AP) and establish a first connection to a first packet data network (PDN) interface. The moving unit 1110 is configured to move from the first network AP to a second network AP. The discovering unit

1115 is configured to discover a first cost associated with the first connection is high. The rehome unit 1120 is configured to rehome the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.

[0082] According to an example embodiment, the discovering unit 1115 may include a first sub-unit. The first sub-unit is configured to receive a first router advertisement including a first Internet Protocol (IP) prefix associated with the first connection and a first measure of cost associated with the first connection, wherein the first measure of cost is high. The first router advertisement, for example, may be received from one of the first network AP and the second network AP.

[0083] According to an example embodiment, the discovering unit 1115 may include a second sub-unit. The second sub-unit is configured to receive a notification message including a measure of cost associated with the first connection, wherein the measure of cost is high. The notification message, for example, may be received from one of a mobility management entity (MME) and a PDN gateway (PGW).

[0084] According to an example embodiment, the UE may further include a duplicate address detection unit. The duplicate address detection unit is configured to receive a second router advertisement including a second IP prefix associated with the second network AP and a second measure of cost associated with the second IP prefix, wherein the second measure of cost is low. Then the rehome unit may be further configured to generate an IP address associated with the second IP prefix; send a duplicate address detection (DAD) message for the IP address; and commence using the second connection with the IP address in response to determining that a DAD response is not received within a specified time duration. Optionally, the rehome unit may be further configured to receive at least one neighbor unreachability detection (NUD) message for a first IP prefix associated with the first connection.

[0085] According to an example embodiment, the rehome unit 1120 may be further configured to send a rehome request message including information associated with the first connection; and receive a rehome response message. The rehome request message, for example, may be sent to one of the second network AP and a mobility management entity (MME).

[0086] According to an example embodiment, the first connection and the second connection are PDN connections.

[0087] As used herein and without limitation, the term “unit” as employed herein is not necessarily confined to a processor which executes programmed instructions, but extends to any type of hardwired device, hardwired circuit, integrated circuit or circuit implemented device which performs a corresponding function. Furthermore, a function of one unit may be provided by two or more physical units, circuits or devices. Functions of two or more units may be provided by one physical unit, circuit or device.

[0088] Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims.

CLAIMS

1. A method for connection rehomeing, the method comprising:
attaching, by a user equipment (UE), to a first network attachment point (AP) and establishing a first connection to a first packet data network (PDN) interface;
moving, by the UE, from the first network AP to a second network AP;
discovering, by the UE, a first cost associated with the first connection is high; and
rehomeing, by the UE, the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.
2. The method of claim 1, wherein discovering the first cost comprises receiving a first router advertisement comprising a first Internet Protocol (IP) prefix associated with the first connection and a first measure of cost associated with the first connection, wherein the first measure of cost is high.
3. The method of claim 2, wherein the first router advertisement is received from one of the first network AP and the second network AP.
4. The method of claim 1, wherein discovering the first cost comprises receiving a notification message including a measure of cost associated with the first connection, wherein the measure of cost is high.
5. The method of claim 4, wherein the notification message is received from one of a mobility management entity (MME) and a PDN gateway (PGW).
6. The method of claim 1, further comprising receiving a second router advertisement including a second IP prefix associated with the second network AP and a second measure of cost associated with the second IP prefix, wherein the second measure of cost is low, and wherein rehomeing the first connection comprises:
generating an IP address associated with the second IP prefix;
sending a duplicate address detection (DAD) message for the IP address; and

commencing using the second connection with the IP address in response to determining that a DAD response is not received within a specified time duration.

7. The method of claim 6, wherein rehomeing the first connection further comprises receiving at least one neighbor unreachability detection (NUD) message for a first IP prefix associated with the first connection.

8. The method of claim 1, wherein rehomeing the first connection comprises:
sending a rehomeing request message including information associated with the first connection; and
receiving a rehomeing response message.

9. The method of claim 8, wherein the rehomeing request message is sent to one of the second network AP and a mobility management entity (MME).

10. The method of any one of claims 1-9, wherein the first connection and the second connection are PDN connections.

11. A method for connection rehomeing, the method comprising:
receiving, by a network entity, a first control message from a user equipment (UE)
initiating a rehomeing for a first connection coupling the UE to a first network AP and to a first packet data network (PDN) interface, wherein a first cost associated with the first connection is high; and
sending, by the network entity, a second control message to the UE, the second control message completing the rehomeing of the first connection.
12. The method of claim 11, wherein the first control message comprises a duplicate address detection (DAD) message for a second Internet Protocol (IP) prefix associated with a second network AP, wherein the second IP prefix identifies a second connection coupling the UE to the second network AP and to a second PDN interface.
13. The method of claim 11, wherein the second control message comprises a neighbor unreachability detection (NUD) message for a first IP prefix identifying the first connection.
14. The method of claim 11, wherein the first control message comprise a rehome request message including information associated with the first connection, and wherein the second control message comprises a rehome response message.
15. The method of claim 14, further comprising:
deleting the first connection; and
generating a second connection coupling the UE to a second network attachment point and to a second router.

16. A user equipment (UE) adapted to perform connection rehomming, the UE comprising:
a processor; and
a computer readable storage medium storing programming for execution by the processor,
the programming including instructions to:
attach to a first network attachment point (AP) and establish a first connection to a
first packet data network (PDN) interface,
move from the first network AP to a second network AP,
discover a first cost associated with the first connection is high, and
rehome the first connection, thereby establishing a second connection coupling
the UE to a second network AP and to a second PDN interface, wherein a second cost associated
with the second connection is low.
17. The UE of claim 16, wherein the programming includes instructions to receive a first
router advertisement comprising a first Internet Protocol (IP) prefix associated with the first
connection and a first measure of cost associated with the first connection, wherein the first
measure of cost is high.
18. The UE of claim 17, wherein the programming includes instructions to receive the first
router advertisement from one of the first network AP and the second network AP.
19. The UE of claim 16, wherein the programming includes instructions to receive a
notification message including a measure of cost associated with the first connection.
20. The UE of claim 16, wherein the programming includes instructions to:
receive a second router advertisement including a second IP prefix associated with the
second network AP and a second measure of cost associated with the second IP prefix, wherein
the second measure of cost is low;
generate an IP address associated with the second IP prefix;
send a duplicate address detection (DAD) message for the IP address; and
commence use of the second connection with the IP address in response to determining
that a DAD response is not received within a specified time duration..

21. The UE of claim 16, wherein the programming includes instructions to:
send a rehomings request message including information associated with the first connection; and
receive a rehomings response message.
22. The UE of claims 21, wherein the programming includes instructions to send the rehomings request message to one of the second network AP and a mobility management entity (MME).
23. A user equipment (UE) adapted to perform connection rehomings, the UE comprising:
an attaching unit, configured to attach to a first network attachment point (AP) and establish a first connection to a first packet data network (PDN) interface;
a moving unit, configured to move from the first network AP to a second network AP;
a discovering unit, configured to discover a first cost associated with the first connection is high; and
a rehomings unit, configured to rehome the first connection, thereby establishing a second connection coupling the UE to a second network AP and to a second PDN interface, wherein a second cost associated with the second connection is low.
24. The UE of claim 23, wherein the discovering unit comprises a first sub-unit and the first sub-unit is configured to receive a first router advertisement comprising a first Internet Protocol (IP) prefix associated with the first connection and a first measure of cost associated with the first connection, wherein the first measure of cost is high.
25. The UE of claim 24, wherein the first router advertisement is received from one of the first network AP and the second network AP.
26. The UE of claim 23, wherein the discovering unit comprises a second sub-unit and the second sub-unit is configured to receive a notification message including a measure of cost associated with the first connection, wherein the measure of cost is high.

27. The UE of claim 26, wherein the notification message is received from one of a mobility management entity (MME) and a PDN gateway (PGW).

28. The UE of claim 23, the UE further comprising a duplicate address detection unit, configured to receive a second router advertisement including a second IP prefix associated with the second network AP and a second measure of cost associated with the second IP prefix, wherein the second measure of cost is low, and wherein the rehomeing unit is further configured to:

- generate an IP address associated with the second IP prefix;
- send a duplicate address detection (DAD) message for the IP address; and
- commence using the second connection with the IP address in response to determining that a DAD response is not received within a specified time duration.

29. The UE of claim 28, wherein the rehomeing unit is further configured to receive at least one neighbor unreachability detection (NUD) message for a first IP prefix associated with the first connection.

30. The UE of claim 23, wherein the rehomeing unit is further configured to:

- send a rehomeing request message including information associated with the first connection; and
- receive a rehomeing response message.

31. The UE of claim 30, wherein the rehomeing request message is sent to one of the second network AP and a mobility management entity (MME).

32. The UE of any one of claims 23-31, wherein the first connection and the second connection are PDN connections.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

1000





Fig. 10

**Fig. 11**

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2015/073373

A. CLASSIFICATION OF SUBJECT MATTER

H04W 36/00(2009.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H04W; H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI,EPODOC:rehoming, rehome, connection, two, multi, link, ip, AP, pdn, packet data network, access, gateway, relocation, switch, handoff, cost, band, frequency, load, point, prefix, time, interface

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2009080382 A1 (MOTOROLA INC.) 26 March 2009 (2009-03-26) description paragraphs [0017]-[0063], figure 1	1-32
X	US 2004030791 A1 (MOTOROLA INC.) 12 February 2004 (2004-02-12) description paragraphs [0015]-[0043], figures 1-9	1-32
A	US 8432871 B1 (JUNIPER NETWORKS INC.) 30 April 2013 (2013-04-30) the whole document	1-32



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search

14 May 2015

Date of mailing of the international search report

02 June 2015

Name and mailing address of the ISA/CN

STATE INTELLECTUAL PROPERTY OFFICE OF THE
P.R.CHINA
6, Xitucheng Rd., Jimen Bridge, Haidian District, Beijing
100088, China

Facsimile No. (86-10)62019451

Authorized officer

WANG,Xinyue

Telephone No. (86-10)82245268

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2015/073373

Patent document cited in search report			Publication date (day/month/year)	Patent family member(s)			Publication date (day/month/year)
US	2009080382	A1	26 March 2009	WO	2008157461	A1	24 December 2008
				IN	KOLNP200904383	E	23 April 2010
				CN	101743769	A	16 June 2010
US	2004030791	A1	12 February 2004	EP	1529361	A2	11 May 2005
				AU	2003254240	A1	23 February 2004
				CN	1692346	A	02 November 2005
				JP	2006501702	A	12 January 2006
				WO	2004013998	A2	12 February 2004
				KR	20050040917	A	03 May 2005
				INDE	LNP200500122	E	30 January 2009
				IN	244934	B	31 December 2010
US	8432871	B1	30 April 2013	US	8934453	B1	13 January 2015