



(11)

EP 3 907 148 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:

28.08.2024 Bulletin 2024/35

(51) International Patent Classification (IPC):
B65C 9/18 (2006.01) **B65C 3/14 (2006.01)**

(21) Application number: **21175637.4**

(52) Cooperative Patent Classification (CPC):
B65C 3/14; B65C 9/1865; B65C 9/1869

(22) Date of filing: **20.04.2018**

(54) **LABEL APPLICATION SYSTEMS**

ETIKETTENAPPLIKATIONSSYSTEME

SYSTÈMES D'APPLICATION D'ÉTIQUETTES

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

- **Woods, Michael Clarke**
Rumford RI, 02916 (US)
- **Meek, Jason A.**
Pawtucket RI, 02860 (US)
- **Marsella, Andrew W.**
Providence RI, 02906 (US)
- **Voicechovski, Nikolai A.**
Westerly RI, 02891 (US)
- **Lux, Benjamin David**
Providence RI, 0209 (US)
- **Medeiros, Michael**
Plainville MA, 02762 (US)
- **Grauds, Juris Alex**
Canton MA, 02021 (US)

(30) Priority: **20.04.2017 US 201762487520 P**

(74) Representative: **Hoffmann Eitle**
Patent- und Rechtsanwälte PartmbB
Arabellastraße 30
81925 München (DE)

(43) Date of publication of application:

10.11.2021 Bulletin 2021/45

(60) Divisional application:

24187462.7

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:

18723226.9 / 3 612 452

(56) References cited:
WO-A1-00/73152 **WO-A1-2016/191663**
DE-A1- 19 621 857 **DE-U1- 20 006 315**

(73) Proprietor: **Actega North America Technologies, Inc.**

Cinnaminson, NJ 08077 (US)

(72) Inventors:

- **Munnelly, Heidi M.**
Cumberland RI, 02864 (US)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND

[0001] Adhesive labels are widely used, such as for providing information and/or decoration on substrates such as bottles and other containers, on packages for shipment, on products for sale, and so on. In some applications, labels are provided on a continuous web, which may be rolled onto a spool. During a labeling process, the web is unwound from the spool guided through a pre-defined path to a location at which the labels are removed from the web and applied to the substrate. Frequently, such webs are controlled by features such as rollers which contact the front and back surfaces of the web to guide the web, maintain a desired web tension, and otherwise control the positioning and/or velocity of the web such that the labels may be accurately positioned when applied to the substrate.

[0002] The labels typically have an adhesive side, whether formed by a pressure-sensitive adhesive (PSA), a glue applied to the label or a thermally-activated or fluid-activated adhesive, that serves to secure the label to a box, product or other substrate. When the label is applied to the substrate, the adhesive side may be exposed, e.g., by peeling the label off of the web or by removing a liner from the adhesive side. In certain applications, the adhesive side may be non-tacky until just prior to applying the label, at which time the adhesive is activated (e.g., by applying heat or an activation fluid) and the label is applied to the substrate.

[0003] DE 19621857 A1 discloses a decorating machine for decorating and labelling of containers, specifically bottle crates, with printed images which are detachably fixed to a flexible carrier band whilst the self-adhesive rear side is exposed. The decorating machine comprises a base frame, on the upper side of which a container conveyor and a dispensing unit for the printed images are arranged side by side. The horizontal, linear container conveyor has two parallel conveyor belts which are continuously driven by a motor. Furthermore, the container conveyor comprises two parallel lateral guide railings through which the bottle crates positioned on the container belts are guided along an exact linear path. The dispensing unit has a horizontal base plate which is arranged on the base frame so that it can be adjusted in height and laterally. On the upper side of the base plate there is a first receptacle for the carrier band and, and positioned at a distance from it, a second receptacle for the empty carrier band with a drive motor. Between the two receptacles, there is a guide comprising a plurality of guide rollers and guide rails which guides the carrier band in a V-shape from the first receptacle to the path of movement of the bottle crates on the container conveyor and away to the second receptacle. A printed image sensor is positioned between first receptacle and the path of movement of the bottle crates. A container sensor is positioned at the container conveyor. A cylindrical roller

is positioned between the first receptacle and the second receptacle and configured to rotate and press the self adhesive rear side of the printed images onto the bottle crates. The carrier band is operated in a start-stop manner between the first and second receptacle. During the transfer of the printed images from the carrier band to the bottle crates, the speed of the carrier band is matched to the speed of the container conveyor.

[0004] WO 2016/191663 A1 discloses a pressure sensitive label and a method for preparing the same.

[0005] WO 00/73152 discloses a device and method for applying labels to products.

[0006] DE 200 06 315 U1 discloses a label application system.

15

SUMMARY

[0007] In a first aspect of the present invention, there is provided a system according to claim 1.

[0008] In a second aspect of the present invention, there is provided a method according to claim 9.

[0009] Aspects described herein relate to systems and methods for applying decorations (e.g. labels) from a continuous web onto substrates. The web may include a carrier film with a plurality of decorations provided on one side of the carrier film (e.g., a front side of the web.). The decorations may have a tacky adhesive layer, such as a pressure sensitive adhesive (PSA) layer or other suitable viscoelastic adhesive layer, provided on a side of the decoration opposite the carrier film for adhering the decorations to the substrates. Accordingly, the tacky adhesive layer may be exposed one side of the web (i.e., the side of the web on which the decorations are provided). However, the inventors have appreciated that when using such decorations, conventional web control systems may not be suitable, as contact between the adhesive layer and rollers or other components of a web control system may damage the decoration or web and/or foul the web control system. Similarly, in some applications, a web may include decorations having small and/or delicate portions (e.g., decorative elements), and thus it may be desirable to avoid contacting those portions of the decorations while controlling or guiding the web prior to application of the decorations onto the substrates.

[0010] Depending on the embodiment, each decoration on a web may include a single element that may be transferred to a substrate, or each decoration can include multiple elements that are separate from each other though initially supported on a common web and transferred to the same substrate. In some instances, the term "label" may be used to refer to a decoration; accordingly, as used herein, the terms "decoration" and "label" have the same meaning and may be used interchangeably.

Thus, in some cases, a label may include a single element or multiple elements that are transferred together to substrate.

[0011] Moreover, it should be understood that the term decoration does not necessarily refer to "decorating" an

item in any particular aesthetic sense. For example, a decoration may provide visible graphics, text, colors, optical effects (like diffraction that gives a rainbow effect), and so on.

[0012] In one embodiment, a system for transferring decorations to substrates may include a continuous web including a plurality of decorations provided on a first side of the web, with each decoration having a pressure sensitive adhesive exposed on a surface of the decoration facing outwardly from the first side of the web. The system may include an application station at which the decorations are transferred from the web to substrates, a web path along which the web travels to transport the decorations to the application station, and a substrate transport configured to move the substrates to the label application station, and a web control system including at least one web controller configured to move the web at the application station to position a decoration on the web for transfer to a substrate. Moreover, the application station may be configured to transfer a decoration from the web directly to a substrate based on contact of the substrate with the pressure sensitive adhesive of a portion of the decoration while the portion of the decoration is attached to the web.

[0013] It should be understood that transfer of a decoration from a web to a substrate may be accomplished via any number of suitable mechanisms, and that the current disclosure is not limited to any particular mechanism. For example, in some instances, contact between an adhesive surface of a decoration and a substrate may cause the decoration to adhere to the substrate and release or separate from the web, thereby resulting in the decoration being transferred directly to the substrate from the web.

[0014] As noted above, in some instances, a decoration or label may include multiple separate elements or decoration components. These decoration components may be physically separated from one another on the web, and the decoration components may be transferred together onto a substrate in register with one another, thereby maintaining the relative spacing and arrangement and orientation of the decoration components after being transferred to the substrate. The decoration components may work together to form a single decoration. For example, the decoration components may comprise different graphical elements that work together to form the decoration. In some instances, separate decoration components may include text characters that form a word, phrase, number, and so on.

[0015] According to some aspects, systems and methods described herein may be used to apply decorations and/or labels to substrates. In some instances, applying a decoration to a substrate may involve directly transferring the decoration to the substrate from the web. In such embodiments, the decoration is always supported by either the web. In other instances, a decoration may be partially or completely separated from the web prior to being applied to the substrate.

[0016] In one embodiment, a method for applying a decoration to a substrate includes moving a continuous web along a web path to transport a plurality of decorations provided on a first side of the web to an application station. Each decoration comprises two or more physically separate decoration components and each decoration component has an adhesive exposed on a surface of the decoration component facing outwardly from the first side of the web. The method further includes applying

5 the two or more decoration components in register with one another onto the surface of a substrate at the application station.

[0017] In another embodiment, a system for applying decorations to substrates may include a continuous web including a plurality of decorations provided on a first side of the web, with each decoration having an adhesive exposed on a surface of the decoration facing outwardly from the first side of the web. The system may further include an application station at which the decorations

10 are applied from the web to substrates, a web path along which the web travels to transport the decorations to the application station, a substrate transport configured to move the substrates through the application station, and a web control system including at least one web controller.

15 The web control system may be configured to move the web at the application station along a direction of travel of the substrates through the application station.

[0018] In yet another embodiment, a method for applying a decoration to a substrate includes moving a continuous web along a web path to transport a plurality of decorations provided on a first side of the web to an application station. Each decoration has an adhesive exposed on a surface of the decoration facing outwardly from the first side of the web. The method further comprises moving a substrate through the application station to apply a decoration to the substrate and moving the web at the application station along a direction of travel of the substrate through the label application station.

[0019] According to some aspects, relative movement 20 of a decoration on a web and a substrate may be controlled, such as, during application of the decoration to the substrate. For example, such relative motion between the decoration and the substrate may aid in releasing the decoration from the web when transferring a decoration

25 from the web to a substrate.

[0020] According to the invention, a system for applying decorations to substrates includes a continuous web including a plurality of decorations provided on a first side of the web, with each decoration having an adhesive exposed on a surface of the decoration facing outwardly from the first side of the web. The system further includes an application station at which the decorations are applied from the web to substrates, a web path along which the web travels to transport the decorations to the application station, and a web control system including at least one web controller. The web control system is configured to stop movement of the web when a decoration is positioned at the application station. The system further in-

cludes a substrate transport configured to move a substrate through the application station while the web is stopped to move the substrate relative to the decoration positioned at the application station and apply the decoration to the substrate.

[0021] According to the invention, a method for applying a decoration to a substrate includes moving a continuous web along a web path to transport a plurality of decorations provided on a first side of the web to an application station. Each decoration has an adhesive exposed on a surface of the decoration facing outwardly from the first side of the web. The method further includes stopping movement of the web when a decoration is positioned at the application station, and moving a substrate through the application station while the web is stopped to apply the decoration positioned at the application station to the substrate.

[0022] According to some aspects, decorations provided on a web may have an exposed adhesive surface, and as noted previously, the inventors have appreciated that conventional web control systems may not be suitable, as contact between the exposed adhesive and rollers or other components of a web control system may damage the decoration or web and/or foul the web control system.

[0023] In one embodiment, a system for applying labels to substrates may include an application station at which decorations are applied to substrates from a web. The web may include a first side and a second side opposite the first side, and the decorations may be provided on the first side. The system may include a web path along which the web travels to transport the decorations to the application station, and the web path may include a first path portion positioned before the application station and a second path portion positioned after the application station. A web control system including at least one web controller may be provided, and the web control system may be configured to control at least one web characteristic without physically contacting at least a portion of the first side of the web and the decorations along the first path portion.

[0024] For example, the decorations may be carried on the web through the first path portion and to the application station where the decorations are applied to the substrate, and when in the second path portion, the web may be devoid of decorations. In some embodiments, the system may be arranged to control the web characteristics without physically contacting the portions of the web where an adhesive surface of the decorations is exposed as the decorations are transported through the first web path portion. The web characteristics may include, without limitation, a web tension, a direction of travel of the web, a velocity of the web, a position of the web, and an alignment of the web, and controlling one or more of these web characteristics may allow for accurate application of the labels onto the substrate.

[0025] In some embodiments, the web control system may include at least one web controller to control the one

or more web characteristics in the first path portion without physically contacting one side of the web (e.g., a front side on which the decorations are provided). Along the second path portion, additional web controllers (e.g., rollers, idlers, brakes, and the like) may be provided which may contact the entire web, including both the front and back sides of the web, to control and/or guide the web as desired.

[0026] The web control system described herein may include any number of sensors, detectors, controllers, relays, etc., arranged to detect and/or control any number of web characteristics. For example, sensors may be provided to determine the web tension, the web velocity, the direction of the web, an angular alignment of the web, a position of the web along a direction transverse to the web path, and so on. One or more controllers may be provided to adjust the web (e.g., the web tension, velocity, direction, position, etc.) based on the sensed web characteristics. In some cases, sensors and/or controllers may be provided at multiple locations along the web path to control the web as desired.

[0027] In some embodiments, the web control system may include one or more web controllers arranged to apply a force to one side of the web without physically contacting the web. Such web control elements may be employed to control the web characteristics (e.g., to guide the web along a desired direction, to control the web tension, etc.). In one embodiment, a non-contact guide may be provided along the first path portion and may employ pressurized air to apply a force against the front side of the web, thereby allowing for non-contact web guidance and/or tension control along the first path portion. In another embodiment, a vacuum belt may be provided along the first path portion and arranged to apply vacuum to the back side of the label. In this manner, the vacuum belt may guide and/or control the web without contacting the front surface of the web.

[0028] In some embodiments, one or more web controllers may be configured to contact the front side of web at positions where the decorations are not provided. For example, the decorations may be located only in a central portion of the web and spaced from the top and bottom edges of the web, and one or more rollers may be arranged to contact the front side of the web only along top and/or bottom portions of the web adjacent the edges of the web. In some embodiments, one or more web controllers may be arranged to contact the front side of the web at spaces between decorations on the web.

[0029] In another embodiment, a method for applying a decoration to a substrate includes transporting a decoration along a web path to an application station. The decoration is provided on a first side of a web opposite a second side of the web, and the web path includes a first path portion positioned before the application station and a second path portion positioned after the application station. The method further includes controlling at least one web characteristic without physically contacting at least a portion of the first side of the web and the deco-

rations along the first path portion, and applying the label to a substrate at the application station.

[0030] According to some aspects, an application station may include one or more features to assist with applying a decoration from a web to a substrate. For instance, in some systems, an adhering force between the decorations and the web may be similar in strength to an adhering force between the adhesive layer of the decorations and the substrate. Therefore, it may be advantageous to assist with releasing the decorations from the web at the application station to ensure proper application of the decoration to the substrate.

[0031] In some embodiments, an actuator may be provided at the application station to forcibly press the decorations into contact with the substrate, which may increase the adhesion force between the adhesive layer of the decoration and the substrate. For example, in some embodiments, an actuator may be provided to press the substrate against the decoration (and against the web) as the decoration is moved through the application station. The actuator may be configured to provide an application force to any suitable portion of the decoration, including, but not limited to, a central portion of the decoration or an edge of the label. Alternatively, or in addition, in some embodiments, an actuator may be provided to apply an application force to the web to press the web (and the decoration) against the substrate. In some embodiments, the web may be perforated or gas permeable, and a pressurized gas (e.g., pressurized air) may be applied through the web to apply a force to the decorations to assist with separating the decorations from the web and applying the decorations to the substrates.

[0032] In some embodiments, the application station may include one or more features to assist with physically separating labels from a web prior to application onto the substrate. For example, a label separator may be provided to at an entrance to the application station and arranged to apply a force to an interface between the labels and the web. In one embodiment, the separator may include a wire or other suitable structure positioned at the interface of the labels and the web. In another embodiment, a label separator may apply a force to the interface without physically contacting the interface. For instance, the separator may employ pressurized air to apply a separating force to the label-web interface.

[0033] In some embodiments, labels may include an activatable release layer provided between a web and the labels. At the application station, the release layer may be activated (e.g., by application of heat, radiation such as UV light, an activation fluid, etc.) to aid in release of the label from the web.

[0034] In some embodiments, the application system may include one or more features to enhance an attractive force between the labels and the substrates to assist with application of the labels. For example, in one embodiment, the substrates may be treated prior to entering the label application station. The treatment may include, without limitation, a thermal treatment, exposure to radia-

tion (e.g., UV light), and/or application of a fluid to enhance label application at the label application station. In another embodiment, the labels and/or substrates may be electrostatically charged prior to passing through the label application station to create an electrostatic attraction between the labels and the substrates to further assist with application of the label.

[0035] According to some aspects, a label application system may employ a temporary liner to protect the front side of the web (including the decorations provided thereon) as the web is guided through at least a portion of the first web path portion prior to label application. The temporary liner may be configured to easily release from the front side of the web, and the temporary liner may be provided along the portion of the first web path portion to allow for control of the web as desired. In particular, one or more web controllers may be provided to apply a force to the front side of the web through the temporary liner, and therefore the web controllers may control one or more characteristics of the web while not directly contacting the front side of the web. Thereafter, and prior to application of the decorations, the temporary liner may be removed from the front side of the web.

[0036] In one embodiment, a system for applying decorations to substrates includes an application station at which decorations are applied to a substrate from a web. The web includes a first side and a second side opposite the first side, and the decorations are provided on the first side. The system further includes a web path along which the web travels to transport the decorations from a to the application station, and the web path includes a first path portion positioned before the application station and a second path portion positioned after the label application station. A liner is arranged to contact the first side of the web only along a contact length of the of the first web path portion, and the contact length is shorter than a total path length of the first web path portion.

[0037] In another embodiment, a method for applying a decoration to a substrate includes transporting a decoration along a web path to an application station. The decoration is provided on a first side of a web opposite a second side of the web, and the web path includes a first path portion positioned before the label application station and a second path portion positioned after the label application station. The method further includes moving a liner into contact with the first side of the web only along a contact length of the first web path portion. The contact length is shorter than a length of the first web path portion. The decoration is applied to a substrate at the application station.

[0038] In some embodiments, the liner may be provided on a liner supply reel and may be transported along a liner path to a liner take-up reel. The liner may be arranged to contact the first side of the web along a portion of the liner path to define the contact length of the first web path portion.

[0039] In some embodiments, the liner may be provided as a continuous closed loop defining a liner loop path,

and the liner may be arranged to contact the first side of the web along a portion of the liner loop path to define the contact length of the first web path portion.

[0040] In some embodiments, a portion of the web in the second web path portion may be used as the liner. For example, after the label is removed from the web and applied to the substrate, the web in the second web path portion may be configured to contact the front side of the web in the first path portion to define the contact length of the first path portion. 5

[0041] According to some aspects, a decoration application system may be arranged to maintain contact between decorations on a web and the substrates over an extended contact length prior to final application of the decorations to the substrates. For example, such arrangements may provide for an increased contact time between the decorations and the substrates during decoration application, which may promote the adhesion between the decorations and the substrates. In some cases, such increased adhesion may aid in releasing the decorations from the web during application and/or may improve the quality of the decoration application. 15

[0042] In one embodiment, a system for applying decorations to substrates may include an application station at which decorations are applied to substrates from a web. The web may include a first side and a second side opposite the first side, and the decorations may be provided on the first side. The system may include a web path along which the web travels to transport the decorations to the application station, and a web control system including at least one web controller may be provided to control at least one web characteristic. The decorations and the substrates may be held in contact along an extended contact length at the label application station before the decorations are applied to the substrates. 20 25

[0043] Other features and advantages are apparent from the following description and from the claims. 30 35

BRIEF DESCRIPTION OF DRAWINGS

[0044] The accompanying drawings are not intended to be drawn to scale. In the drawings, each identical or nearly identical component that is illustrated in various figures may be represented by a like numeral. For purposes of clarity, not every component may be labeled in every drawing. In the drawings: 40 45

Fig. 1 is a top view of a label application system including an air roller, according to one embodiment; Fig. 2 is a perspective view of the air roller of Fig. 1; Fig. 3 is a top view of a label application system including a vacuum belt, according to one embodiment; Fig. 4 is a top view of a label application system in which labels are applied directly after unwinding a web from a roll, according to one embodiment; Fig. 5 is a top view of a label application system including a roller which contacts only a portion of a 50 55

web, according to one embodiment;

Fig. 6 is a front view of the roller and web of the Fig. 5 embodiment;

Fig. 7 is a top view of a label application system including a web controller which contacts only a portion of the web with the web controller in a first position, according to one embodiment;

Fig. 8 is a top view of the label application system of Fig. 7 with the web controller in a second position; Fig. 9 is a top view of a label application system including an adhesive application station, according to one embodiment;

Fig. 10 is a top view of a label application system including an actuator to press a container against a web, according to one embodiment;

Fig. 11 shows the Fig. 10 embodiment with the actuator pressing the container against the web;

Fig. 12 is a top view of a label application system including an actuator to press a container against a web, according to one embodiment;

Fig. 13 shows the Fig. 12 embodiment with the actuator pressing the container against the web;

Fig. 14 is a top view of a label application system including an actuator to press a web against a container, according to one embodiment;

Fig. 15 shows the Fig. 14 embodiment with the actuator pressing the web against a container;

Fig. 16 is a top view of a label application system including a pressurized gas source for separating the labels from the web, according to one embodiment;

Fig. 17 is a front perspective view of a portion of the Fig. 16 embodiment;

Fig. 18 is a top view of a label application system including a label separator, according to one embodiment;

Fig. 19 is a front perspective view of a portion of the Fig. 18 embodiment;

Fig. 20 is a top view of a label application system including a non-contact label separator according to one embodiment;

Fig. 21 is a front perspective view of a portion of the Fig. 20 embodiment;

Fig. 22 is a top view of a label application system including an activation station for activating a release layer, according to one embodiment;

Fig. 23 is a top view of a label application system including an electrostatic charging station, according to one embodiment;

Fig. 24 is a top view of a label application system including a container treatment station, according to one embodiment;

Fig. 25 is a top view of a label application system including a temporary liner, according to one embodiment;

Fig. 26 is a top view of a label application system including a temporary liner loop, according to one embodiment;

Fig. 27 is a top view of a label application system including a temporary liner, according to one embodiment;

Fig. 28 is a top view of a label application system in which a portion of the web is used as a temporary liner, according to one embodiment; and

Fig. 29 is a schematic representation of a decoration including multiple separate decoration components, according to one embodiment.

DETAILED DESCRIPTION

[0045] It should be understood that aspects of the invention are described herein with reference to the figures, which show illustrative embodiments. The illustrative embodiments described herein are not necessarily intended to show all embodiments in accordance with the invention, but rather are used to describe a few illustrative embodiments. Thus, aspects of the invention are not intended to be construed narrowly in view of the illustrative embodiments. In addition, it should be understood that aspects of the invention may be used alone or in any suitable combination with other aspects of the invention.

[0046] In some embodiments, a web may include a plurality of labels provided on a first side of the web opposite a second side of the web. Each label may include an adhesive layer (such as a layer of a PSA), and the adhesive layer may be exposed on the first side of the web. In some embodiments, the web may be a carrier film, and the labels may be provided on and/or formed on the carrier film using a suitable printing or other method. For example, the labels may include a first label layer formed on the carrier film, and the first label layer may form the outer surface of the label when the label is applied to a substrate. One or more indicia layers may be provided on the first label layer, followed by an adhesive layer formed on the indicia layer(s). In this manner, the labels may be reverse printed and may feature an exposed adhesive layer which may be located between the substrate and the indicia and first label layers when the label is applied to the substrate. In some cases, the carrier film and the labels provided thereon may be rolled prior to application. In such cases, the adhesive layer and the carrier film may be configured such that the adhesive layer does not adhere strongly to the adhesive layer so that the carrier film web may be easily unrolled during application without disturbing the labels. In some instances, a release layer may be provided between the carrier film and the first label layer to facilitate release of the labels from the carrier film. For example, labels and webs which may be used with the systems provided herein are described in US Patent Application Pub. No. 2016/0335927. However, it should be understood that the current disclosure is not limited to any particular types of labels or web arrangements.

[0047] Depending on the particular embodiment, the labels may bear any suitable visible or non-visible information, such as text, graphics, electronic circuitry (such

as an RFID device), etc. Moreover, a label may be provided as a single, continuous piece of material applied to a substrate, or alternatively, the label may be formed as a plurality of separate label components which collectively form the label. Additionally, it should be understood that the systems described herein may be suitable for applying labels to any suitable substrates, such as bottles or other containers (including irregularly shaped containers), boxes, envelopes, or other packaging materials, products for sale, etc.

[0048] Fig. 1 depicts an illustrative embodiment of a label application system 50 for applying a label to substrates, such as bottles 10, from a web 102. The bottles 10 may be transported to an application station 108 where the labels are applied to the bottles. In some instances, the labels may be transferred directly from the web 102 to the substrates at the application station 108, such that the labels are always supported by either the web or the substrate.

[0049] The bottles (or other suitable substrates) may be provided on a substrate transport such as a belt 12 to move the bottles towards and through the application station 108. As illustrated, the web 102 may move along a direction of travel of the bottles through the application station 108, e.g., along the same direction as the direction of travel of the belt 12. Although a linear belt is depicted, other configurations are contemplated, such as rotary labeling systems which transport bottles along a generally circular path. In some embodiments, a timing screw 14 may be used to achieve a desired spacing of the bottles 10 along the belt 12. While a screw 14 is shown in the figures, it should be understood that other arrangements may be suitable to control a rate at which bottles (or other substrates) move to and through the application station.

[0050] Additionally, one or more belts 16 may be provided to contact sides of the bottles while the bottles are moved through the label applications station, and/or before or after the bottles arrive at the label application station. In some cases, the belt(s) 16 may be driven by an associated drive (not depicted), and the belt(s) may impart a desired rotation to the bottles before, during, and/or after the bottles are labeled. Alternatively, the belts may not be driven and may be stationary, or the belt(s) may be provided on freely rotating rollers or bearings. Accordingly, it should be understood that the label application systems described herein are not limited to any particular arrangements for transporting bottles or other substrates to be labeled.

[0051] The web 102 may be provided as a web roll 104, and the web may be guided along a web path through the application system 50 to a web take-up roll 106. The application system may use the web to transport the labels to the label application station 108, where the labels are applied to the bottles 10. The web path includes a first web path portion 110 along which the web is guided from the roll 104 to the label application station 108, and a second web path portion 112 along which the web is

guided from the label application station to the web take-up reel 106.

[0052] The web 102 includes a first side 114 and a second side 116 opposite the first side. A plurality of labels (not depicted) may be provided on the first side and the labels may be transported on the web to the label application station 108 for application to the bottles 10. As discussed previously, the labels may include an adhesive layer that is exposed on the first side 114 of the web. At the label application station 108, the adhesive layer of the labels may be brought into contact with bottles 10, and the adhesion between the adhesive layer and the bottles may cause the labels to release from the web 102 and stick to the bottles. For example, the adhesive force between the adhesive layer and the bottles 10 may be tuned to be larger than an adhesive force between the labels and the web, thereby allowing the contact with the bottles to pull the labels off of the web.

[0053] The label application system 50 may include a web control system arranged to control one or more characteristics of the web. For example the web control system may include one or more web controllers 118 arranged to contact the second side 116 of the web 102 along the first web path portion 110. Along the second web path portion 112 (i.e., after the labels have been applied to the containers 110), the web controllers 118 may be arranged to contact both the first and second sides 114, 116 of the web 102.

[0054] Depending on the particular embodiment, the web control system may include web controllers such as rollers (e.g., drive, idle, or tension rollers), or other web control features such as web guides as are known in the art for controlling various aspects or characteristics of the web 102. These characteristics may include a direction or velocity of the web, a web tension, a web alignment, and/or a position of the web along a direction transverse to a direction along which the web travels (e.g., to adjust the vertical alignment of the web and labels relative to the bottles). As noted previously, the web control system may include one or more sensors (not depicted), such as web tension sensors, web velocity sensors, web position sensors, etc., to detect the web characteristics. Moreover, the system may include any suitable number and/or arrangement of web controllers and/or sensors to guide and/or control a web as desired (e.g., to define a desired web path) as the current disclosure is not limited in this regard.

[0055] According to the invention, the web control system controls movement of the web 102 through the application station 108. The web control system is configured to stop movement of the web when a label (or other suitable decoration) is positioned at the application station. While the web is stopped, the movement of the bottles along the belt 12 imparts relative motion between the label positioned at the application station and a bottle moving through the application station. The bottle and label are brought into contact at the application station, and this relative movement results in the label being ap-

plied to the bottle, (e.g., by transferring directly from the web to the substrate). After application of the label from the web to the bottle, the web controller may subsequently move the web to move another label to the application station.

[0056] In some applications, it may be desirable to provide additional web control along the first web path portion 110. However, since the labels are provided on the first side 114 of the web 102 along the first path portion, it may be desirable to avoid contact with the first side of the web (e.g., to avoid contacting an exposed adhesive layer of the labels). In the illustrative embodiment of Figs. 1-2, the web control system includes a non-contact guide 120 arranged to apply pressurized air 122 to the first side 116 of the web. In this manner, the non-contact guide may act as an additional web controller (similar to the web controllers 118) and may use the pressurized air to apply a force to the first side of the web for controlling and/or guiding the web, as desired, without physically contacting the first side of the web. While a single non-contact guide 120 has been depicted, it should be appreciated that any suitable number of non-contact guides may be provided as desired for controlling the web 102 along the first web path portion 110.

[0057] Fig. 2 depicts a perspective view of the non-contact guide 120 of Fig. 1. As illustrated, the non-contact guide includes a generally cylindrically body 124 provided on a shaft 126. In some embodiments, the non-contact guide may be rotatable relative to the web 102. For example, in some embodiments the body may be rotatable relative to the shaft 124, or alternatively, the body may be fixed relative to the shaft and the shaft may be rotatably mounted in the application system 50. In other embodiments, though, the non-contact guide 120 may not be rotatable relative to the web, as the disclosure is not limited in this regard. The non-contact guide may be coupled to a pressurized air source (not depicted), and the pressurized air 122 may exit the non-contact guide through a plurality of apertures 128 formed in the body 124. Although a uniform array of apertures is depicted in Fig. 2, it should be understood that the non-contact guide may include any suitable arrangement of apertures to deliver airflow 122.

[0058] In some embodiments, airflow through the apertures 128 may adjustable and may be controlled to apply a desired force to the web 102 for controlling the web along the first web path portion 110. For instance, a controller (not depicted) may be provided and coupled to the non-contact guide and one or more sensors which may detect various web characteristics (e.g., web tension, web position, velocity, etc.); the controller may adjust the airflow from the non-contact guide to control the web as desired. Alternatively, the airflow may not be adjustable or controllable, and the airflow may be determined by the air pressure and the size, number, and arrangement of apertures 128.

[0059] While a non-contact guide 120 is described above in connection with Fig. 1, other arrangements in

which contact may occur between the guide roller and the first side of the web may be suitable. For example in some embodiments, the guide 120 may include a coating selected such that the exposed adhesive of the labels/decorations does not adhere to the guide roller. In other embodiments, the guide 120 may be cooled or chilled to reduce adhesion between the guide roller and the exposed adhesive of the decorations.

[0060] As will be appreciated in view of the Figures, the various features described above in connection with Fig. 1, including the bottles 10, belt 12, timing screw 14, belt(s) 16, web 102, web roll 104, web take-up roll 106, label application station 108, first and second web path portions 110 and 112, first and second sides of the web 114 and 116, and web controllers 118 may be seen in embodiments depicted in Figs. 3-28. It should be understood that these features may be arranged in any number of ways as would be apparent to one of skill in the art.

[0061] Fig. 3 depicts an illustrative embodiment of a label application system 52 including a vacuum belt system 200 for controlling and/or guiding the web 102 along the first web path portion 110 without contacting the first side 114 of the web. As illustrated, the vacuum belt system may include a belt 202 extending around a plurality of rollers 204 provided on a housing 206. A vacuum may be created within the housing, e.g., via a plurality of fans 208 arranged to blow air out of the housing. The housing 206 and belt 202 may include perforations arranged to communicate vacuum to a contact length 210 of the vacuum belt system. In this manner, the vacuum may pull the second side 116 of the web 102 against the vacuum belt along the contact length to facilitate web control and/or guidance. For example, in some applications, the rollers 204 may be arranged to drive the vacuum belt 202 at a different velocity than a velocity of the web, thereby providing control of the web tension and/or web velocity as the labels are transported through the label application station 108. In some embodiments, the vacuum belt system 200 may be movable relative to the web 102 to allow for a vertical adjustment of the web relative to the bottle (i.e., an adjustment to the web along a direction transverse to the direction of the web along the web path).

[0062] In some embodiments, web control may not be required prior to application of the labels to a substrate. For example, as depicted in Fig. 4, a label application system 54 may be arranged to apply labels from the web 102 the bottles immediately after unwinding the labels from the web roll 104, and web control may be accommodated by one or more web controllers 118 provided only along the second web path portion 112. Accordingly, the labels may be transported on the web directly from the web roll to the label application station 108. As illustrated, the label application station may include an applicator pad 300 arranged to contact the second side 116 of the web at the label application station. The applicator pad may be shaped and/or structured to apply a desired application force against the bottles as the web and bottles are moved through the label application station 108.

[0063] In some embodiments, a label application system may include one or more web control controllers along the first web path portion 110 which are configured to contact only a portion of the first side 114 of the web 102. For example, Figs. 5-8 depict illustrative embodiments in which web controllers are configured to contact portions of the first side 114 of the web where the labels are not provided. In particular, Figs. 5-6 depict an embodiment of a label application system 56 including a contoured web control roller 400 arranged to contact only the top and bottom edges of the first side 114 of the web. As illustrated, a label 18 is provided on the first side of the web, and is provided only in a central portion of the web, spaced from the edges of the web. The roller 400 is generally cylindrical in shape and includes end portions 402 which have a larger diameter than a central portion 404. Accordingly, the roller may contact the front side 114 of the web along the end portions, but the roller may be spaced from the front side along the central portion 404. In this manner, contact between the label 18 (including an adhesive surface 20 of the label) and the roller may be avoided while the roller controls the web as desired. In some embodiments, protrusions 406 may be provided on the end portions 402 and arranged to engage with corresponding openings 408 formed in the web 102. The protrusions and openings may provide a registration between the roller 400 and the web 102 to assist with web control and/or guidance, including driving the web. However, it should be understood that the protrusions and openings may not be provided in some embodiments, and that the roller may still suitably control or guide the web. For instance, in one embodiment the end portions 402 may include a rubber or other suitable material to increase friction at the interface between the end portions and the web.

[0064] Figs. 7-8 depict another illustrative embodiment of a label application system 58 in which labels 18 are spaced along the first side 114 of the web 102, and a web controller 500 is arranged to contact the portions of the first side of the web between the labels. As illustrated, the web controller includes two rollers 502 provided on an arm 504, which is rotatably mounted on a shaft 506. The arm 504 and shaft 506 may be mounted below the web, and the rollers 502 may extend upwardly to contact portions of the first side 114 of the web between labels 18. In particular, Fig. 7 depicts the web controller 500 in a first configuration in which both rollers 502 are in contact with the first side 114 of the web, and Fig. 8 depicts the web controller in a second configuration in which only one of the rollers 502 is in contact with the web. Accordingly, rotation of the web controller 500 causes the rollers to walk along the first side of the web and contact successive portions of the first side between the labels 18. Although a web controller with two rollers is depicted, it should be understood that other arrangements including more than two rollers are also contemplated. For instance, the web controller may include any number of rollers arranged to contact successive spaces between

labels on the first side of the web. For example, the arm 504 may be arranged as a circular plate with multiple rollers 502 arranged at the periphery of the plate. Rotation of the plate may allow each roller 502 to contact a portion of the web 102 between labels 18 and move with the web 102. Additionally, although a configuration including rollers extending from below the web is depicted and described above, it should be understood that other configurations may be suitable. For instance, in one embodiment, the web controller may include a hub or drum with a plurality of protrusions extending radially outwardly from the hub (e.g., similar to a sprocket shape), and the protrusions may be arranged to contact the spaces between labels on the first side of the web.

[0065] As discussed previously, in some applications it may be desirable to avoid contact with an adhesive layer of a label prior to applying the label to a substrate. In one illustrative embodiment shown in Fig. 9, a label application system 60 includes an adhesive applicator 600 located along the first web path portion 110 adjacent the label application station. In this embodiment, the labels may be provided on the first side 114 of the web 102, but may not include an adhesive layer. Thus, the web may be controlled as desired along the first web path portion with web controllers 118 arranged to contact both the first and second sides 114, 116 of the web 102. Prior to label application at the label application station 108, the adhesive applicator 600 may apply an adhesive layer (e.g., a PSA or other suitable viscoelastic adhesive) to the labels. In some embodiments, the adhesive applicator 600 may be configured to print or otherwise apply the adhesive layer in registration with a pattern of the label provided on the web.

[0066] As noted above, in some label systems, an adhering force between the labels and the web may be similar in strength to an adhering force between the adhesive layer of the labels and the substrate when the label is applied to the substrate. Therefore, in some embodiments, a labeling system may include one or more features to provide an increased application force at a label application station, thereby enhancing the adhesion between the adhesive label and the substrate. For example, Figs. 10-11 depict an illustrative embodiment of a labeling system 62 including an actuator 700 arranged to apply an enhanced application force between the bottles 10 and the labels provided on the web. In this embodiment, the actuator includes a bottle engaging member 702 located at the label application station 108 and movable from a retracted position to an extended position. Fig. 10 depicts the bottle engaging member 702 in the retracted position, in which a bottle 10 may be transported along the belt 12 into a position in which the bottle engaging member may align with and engage the bottle. As illustrated in Fig. 11, when the bottle is engaged with the bottle engaging member, the actuator 700 is activated to move the bottle engaging member to the extended position and forcibly press the bottle into contact with a label provided on the web 102. In some embodiments, the web

102 may be supported by a flexible web support belt 130 while the web moves through the label application station 108, and the web support belt may deform as the actuator presses the bottle against the web. However, it should be understood that other web support arrangements are contemplated for supporting the web during label application, such as a compliant pad or a rigid support.

[0067] Figs. 12-13 show another illustrative embodiment of a label application system 64 including an actuator 800 arranged to apply an enhanced application force between the bottles 10 and the labels provided on the web. In this embodiment, a label engaging member includes rollers 806 for contacting the bottle at the label application station.

[0068] Depending on the particular embodiment, a label application system including an actuator arranged to apply an enhanced application force may be configured to apply the application force to any suitable portion of the label. For instance, in the embodiment shown in Figs. 10-11, the actuator 700 may be configured to apply an application force beginning generally at central portion of the label, e.g., along a midline of the label. In contrast, the actuator 800 shown in Figs. 12-13 may be configured to apply an application force beginning at an edge of the label, e.g., to roll the label from the web 102 onto the bottle.

[0069] In some embodiments, a label application system may be arranged to actuate an actuator and apply a label from the web 102 onto the bottle while the web and/or belt 12 is continuously moving. Alternatively, in some applications, the web and/or belt may be operated intermittently to move a bottle 10 into the label application station 108, after which the web and/or belt may be paused while the actuator is activated to apply the label to the bottle. In some embodiments, a bottle timing cam (depicted as cam 704 in Figs. 10-11 and cam 804 in Figs. 12-13) may be provided on the belt 12 to selectively allow a bottle to move into the label application position. For instance, the belt 12 may be operated continuously, and the cams 704, 804 may selectively retain bottles from moving into the label application station, and subsequently allow one or more bottles to move into the label application station when desired.

[0070] Figs. 14-15 depict yet another illustrative embodiment of a label application system 66 including an actuator 900 provided at the label application station 108 to provide an enhanced label application force. In this embodiment, the actuator 900 is arranged to move a protrusion 902 into or out of engagement with the web support belt 130. In particular, Fig. 14 illustrates the actuator 900 in a first position in which the protrusion 902 is not engaged with the web support belt, such that a bottle 10 may be moved by the belt 12 into the label application station 108. When the bottle is in the desired position for label application, the actuator may cause the protrusion to rotate into engagement with the web support belt 130, thereby pressing the web support belt and the web 102 against the bottle to apply a label from the web onto the

bottle (Fig. 15). In some embodiments, a bottle support (not depicted) may be provided on the other side of the bottles opposite the web support belt 130 to support the bottles during label application as the protrusion 902 presses the web against the bottle.

[0071] As discussed previously, in some applications it may be desirable to assist with releasing the labels from the web at the label application station to ensure proper application of the label to the substrate. In one illustrative embodiment shown in Figs. 16-17, the web 102 may be formed of a perforated or gas permeable material such that the web may allow a pressurized gas to flow through the web. An air box 1000 or other suitable pressurized gas source may be provided at the label application station 108 to provide an air flow 1002 (or a flow of another suitable gas) through the web. As illustrated in Fig. 17, the air flow may apply a force to the label 18 to assist with releasing the labels from the first side 114 of the web 102 prior to applying the label to a bottle. In some embodiments, the air flow 1002 may direct the label directly onto a bottle, and thus the airflow may assist with applying the label in addition to assisting with releasing the label from the web.

[0072] Figs. 18-19 show an illustrative embodiment of a label application system 70 including a label separator 1100 provided at the label application station to assist with releasing the labels 18 from the web 102. In this embodiment, the separator 1100 includes a wire 1104 mounted on a housing 1102. The wire is arranged to extend across the web 102 and apply a force (e.g., a peeling force) at an interface between the labels 18 and the front side 114 of the web. In this manner, the separator may assist with releasing a first side 22 of a label from the web such that the label may be more easily applied to a bottle 10 (or other suitable substrate) when the adhesive surface 20 of the label is brought into contact with the bottle. Although a wire is depicted in Figs. 18-19, it should be understood that other separator structures may be suitable, such as a blade or razor arranged to apply a force to the interface of the label and the liner.

[0073] In some embodiments, a label separator may be arranged to facilitate separation of a label from a web without physically contacting the label or the web. For example, in one embodiment shown in Figs. 20-21, a label application system 72 includes a label separator 1200 provided at the label application station 108. In this embodiment, the label separator 1200 may be an air blade arranged to direct a pressurized air flow 1204 (or flow of other suitable gas) towards the interface of the label 18 and the front side 114 of the web 102. The label separator 1200 may include an aperture 1202 coupled to an air supply 1206, and the aperture may be configured to shape the air flow 1204 to apply a desired force to release the label. Although the air flow 1204 is depicted as being applied in a direction generally along the first surface 114 of the web, it should be understood that other arrangements may be suitable. For instance, the label separator may be arranged to provide an air flow directed

at an angle either toward or away from the web to provide a desired force at the label-web interface.

[0074] In some embodiments, a label application system may include one or more features to enhance the strength of the adhesive force between the adhesive layer on a label and the substrate relative to that between the label and the web. For example, in one illustrative embodiment shown in Fig. 22, a label application system 74 may include one or more activation stations 1300 arranged to activate a release layer provided at an interface between the labels and the web 102, thereby reducing the adhesive force holding the labels to the web. In some instances, activation of the release layer may completely release the label from the web and allow the label to be freely applied to the bottles 10 or other suitable substrates. In other embodiments, activation of the release layer may only partially release the label, but may decrease the adhesive force between the label and the web such that the label may be more easily pulled off of the web 102 when pressed against the bottle 10.

[0075] Depending on the embodiment, the release layer may be activatable by exposure to heat, radiation such as UV light, an activation fluid, etc. When activated, the release layer may melt, decompose, or otherwise change phase or form to aid in releasing the label from the web. As illustrated in Fig. 22, some systems may include more than one activation station 1300, and the activation stations may be located at the label application station 108 and/or along the first web path portion 110 for activation prior to application to the bottles 10.

[0076] In another embodiment shown in Fig. 23, a label application system 76 may include one or more electrostatic charging stations 1400 arranged to apply an electrostatic charge on the labels provided on the web 102 and the bottles 10, prior to application of the labels to the bottles at the label application station 108. For example, the labels and the bottles may have opposite charges applied to their surfaces to create an electrostatic attractive force between the bottles and the labels. In some embodiments, the electrostatic attractive force may augment the adhesive force formed between the labels and the bottles during label application, thereby aiding in the release of the labels from the web 102 and/or proper application of the labels. In certain embodiments, such as those employing a separator to separate the labels from the web prior to application, the electrostatic attractive force created by the charging stations 1400 may be used to provide a provisional attachment between the labels and the bottles 10 until the labels are pressed against the bottles, e.g., with an actuator or other suitable arrangement provided at the label application station 108.

[0077] In some embodiments, the bottles (or other suitable containers) may be treated prior to being transported to the label application to promote adhesion between the bottles and the labels. For example, Fig. 24 shows one embodiment of a label application system 78 including bottle treatment stations 1500 arranged to apply a treat-

ment to the surface of the bottles prior to application of the labels at the label application station 108. In some embodiments, the bottle treatment may include, without limitation, a thermal treatment (e.g., the bottles may be passed through one or more heaters), exposure to radiation such as UV light, and/or application of a suitable fluid.

[0078] In some embodiments, the label application station 108 may be arranged to hold the web 102 in contact with the bottles 10 over an extended contact length. Fig. 24 illustrates one such embodiment in which the extended contact length corresponds to a length of the web support belt 130 along which the web travels. In some instances, the bottles (or other suitable substrates) may be supported along the contact length, e.g., with a suitable bottle support such as belt 16. As the bottles travel through the label application station 108, the labels are held in contact against the bottles 10 while the labels are still on the web 102. In this manner the adhesive layer on the labels may have adequate time to form an adhesive bond with the bottles, which, in some cases, may aid in releasing the labels from the web 102.

[0079] As discussed previously, according to some aspects, a label application system may employ a temporary liner to protect the front side of the web (including the labels provided thereon) as the web is guided through at least a portion of the first web path portion prior to label application. For example, Fig. 25 shows an illustrative embodiment of a label application system 80 in which a liner 1602 is provided to contact the first side 114 of the web 102 along a contact length 1604 located along the first web path portion 110. The liner may protect first side 114 of the web 102, including an adhesive layer of the labels provided on the web, of as the web is guided through the contact portion is guided through the contact length. In this manner, the liner may allow for the use of one or more web controllers, such as the web controllers 118 described above, along the contact length of the first web path portion for controlling the web prior to label application. In this embodiment, the liner 1602 may a web similar to web 102, and may be transported on a liner path (including the contact length 1604) from a liner roll 1606 to a liner take-up reel 1608.

[0080] In another illustrative embodiment shown in Fig. 26, a label application system 82 includes a liner 1702 provided as a continuous loop. The liner is guided continuously along a liner path including a contact length 1704 where the liner 1702 contacts a first side 114 of the web. Similar to the embodiment described above in connection with Fig. 25, the liner may protect the first side of the web along the contact length and allow one or more web controllers to be provided along the contact length to control the web 102 as desired prior to label application. As shown in Fig. 26, one or more liner controllers 1706, such as rollers or other suitable features to drive and/or otherwise control the liner may be provided, and the liner controllers may be arranged in any suitable configuration. For example, in Fig. 26 the liner controllers

are arranged to define a generally triangular liner path, though it should be understood that additional liner controllers may be provided to define other shapes, including non-triangular shapes, as desired. Moreover, as illustrated in Fig. 26, one or more liner controllers may be provided along the contact length 1704 and may be used as web controllers to control one or more characteristics of the web 102 along the first web path portion 110.

[0081] In some embodiments, a liner may be provided to protect the first side 114 of the web 102 during the manufacturing process and prior to rolling the web into a web roll 104. For example, as illustrated in Fig. 27, the web roll 104 includes a web 102 have a liner 1802 provided thereon. When the web is unwound from the web roll 104 and guided through the first web path portion the liner may protect the first side 114 of the web, and allow one or more web controllers 118 to be provided along the first path portion to control one or more characteristics of the web, as desired. Prior to application of the labels at the label application station 108, the liner may be removed from the web 102 and wound onto a liner take-up roll 1804. In some instances, the liner 1802 may be reusable, such that the liner may be unwound from the take-up roll 1804 and applied to a new web during a subsequent manufacturing process.

[0082] In some embodiments, a separate liner may not be provided, and instead, a portion of the web in the second web path portion may be used as the liner to protect the first side of the web along the first path portion. For example, Fig. 28 depicts an illustrative embodiment in which the second web path portion 112 is arranged to guide the web such that the second side 116 of the web is brought into contact with the first side 114 of the web along a contact length 1904 in the first web path portion 110. In this manner, the web 102 in the second path portion 112 acts as the liner to protect the first side 114 of the web along the first web path portion 110, and allow for the web to be controlled as desired along the first web path portion. For instance, a liner controller 1906 may be provided along the contact length 1904, and the liner controller may be used to control one or more web characteristics along the first path portion 110. As illustrated, in some embodiments, the liner controller 1906 may be movable to adjust the web path along the first web path portion 110 and/or to adjust the tension or other characteristics of the web prior to application of the labels from the web. After the web 102 is guided through the second web path portion, including through the contact length 1904, the web may be guided to the web take-up roll 106.

[0083] Depending on the embodiment, a liner a may be configured to easily release from the first side of the web. For example the liner may include a surface which has a low adhesion strength to the adhesive layer of the labels such that the liner may contact the adhesive layer along a contact length, and subsequently easily be released from the adhesive layer without disturbing labels on the web.

[0084] As discussed above, in some instances, a dec-

oration may include two or more physically separate components that together make up a single decoration. For example, Fig. 29 depicts a portion of a decoration transfer system 1600 including a continuous web 1602 on which a plurality of decorations 1604 are provided. Each decoration 1604 includes multiple separate decoration elements 1606. When the decoration 1604 is applied to a substrate, the decoration components 1606 are applied together in register with one another and work together to form a single decoration on the substrate. Depending on the particular embodiment, the decoration 1604 may include any suitable number of separate decoration components 1606, and each decoration component may have any suitable shape, orientation, color, pattern, and so on. For example each decoration component could be graphic design composed of two or more separate features. In other instances, each decoration may be a text string (e.g., a word, phrase or number), and the decoration components may include individual text characters that together form the text string. Moreover, combinations of different types of decoration components (e.g., graphical, text, or other types of decoration elements) may be included within a single decoration.

[0085] Having thus described several aspects of at least one embodiment of this invention, it is to be appreciated that various alterations, modifications, and improvements will readily occur to those skilled in the art. Accordingly, the foregoing description and drawings are by way of example only, the invention being defined by the appended claims.

Claims

1. A system for applying decorations to substrates, comprising:
a continuous web (102) including a plurality of decorations (18, 1604) provided on a first side (114) of the web, each decoration having an adhesive (20) exposed on a surface of the decoration facing outwardly from the first side of the web;
an application station (108) at which the decorations are applied to substrates (10);
a web path along which the web travels to transport the decorations to the application station;
a web control system including at least one web controller (118), wherein the web control system is configured to stop movement of the web when a decoration is positioned at the application station; and
a substrate transport (12) configured to move a substrate through the application station while the web is stopped to move the substrate relative to the decoration positioned at the application station and apply the decoration to the substrate. 35
2. The system of claim 1, wherein the adhesive (20) is 40
3. The system of claim 1 or 2, wherein the substrates (10) move continuously at the application station (108). 5
4. The system of any of claims 1 to 3, wherein the substrates (10) are rotated while moving through the application station (108). 10
5. The system of any preceding claim, the web control system is configured to move the web (102) to transport a second decoration of the plurality of decorations (18, 1604) to the application station (108) after application of the decoration to the substrate. 15
6. The system of any preceding claim, wherein each decoration of the plurality of decorations (18, 1604) comprises two or more physically separate decoration components (1606), and the adhesive is exposed on a surface of each decoration component facing outwardly from the first side (114) of the web. 20
7. The system of claim 6, wherein the two or more decoration components (1606) are applied in register with one another to the substrate (10) at the application station (108). 25
8. The system of any preceding claim, wherein the decorations (18, 1604) are transferred directly from the web (102) to the substrate (10) when applied to the substrates at the application station (108). 30
9. A method for applying a decoration (18, 1604) to a substrate (10), comprising:
moving a continuous web (102) along a web path to transport a plurality of decorations provided on a first side (114) of the web to an application station (108), wherein each decoration has an adhesive (20) exposed on a surface of the decoration facing outwardly from the first side of the web;
stopping movement of the web (102) when a decoration is positioned at the application station (108); and
moving a substrate (10) through the application station (108) while the web (102) is stopped to apply the decoration positioned at the application station to the substrate. 50
10. The method of claim 9, wherein the adhesive (20) is a pressure sensitive adhesive. 55
11. The method of claim 9 or 10, wherein the substrate (10) moves continuously through the application station (108) while the web is stopped. 60

a pressure sensitive adhesive.

3. The system of claim 1 or 2, wherein the substrates (10) move continuously at the application station (108). 5
4. The system of any of claims 1 to 3, wherein the substrates (10) are rotated while moving through the application station (108). 10
5. The system of any preceding claim, the web control system is configured to move the web (102) to transport a second decoration of the plurality of decorations (18, 1604) to the application station (108) after application of the decoration to the substrate. 15
6. The system of any preceding claim, wherein each decoration of the plurality of decorations (18, 1604) comprises two or more physically separate decoration components (1606), and the adhesive is exposed on a surface of each decoration component facing outwardly from the first side (114) of the web. 20
7. The system of claim 6, wherein the two or more decoration components (1606) are applied in register with one another to the substrate (10) at the application station (108). 25
8. The system of any preceding claim, wherein the decorations (18, 1604) are transferred directly from the web (102) to the substrate (10) when applied to the substrates at the application station (108). 30
9. A method for applying a decoration (18, 1604) to a substrate (10), comprising:
moving a continuous web (102) along a web path to transport a plurality of decorations provided on a first side (114) of the web to an application station (108), wherein each decoration has an adhesive (20) exposed on a surface of the decoration facing outwardly from the first side of the web;
stopping movement of the web (102) when a decoration is positioned at the application station (108); and
moving a substrate (10) through the application station (108) while the web (102) is stopped to apply the decoration positioned at the application station to the substrate. 50
10. The method of claim 9, wherein the adhesive (20) is a pressure sensitive adhesive. 55
11. The method of claim 9 or 10, wherein the substrate (10) moves continuously through the application station (108) while the web is stopped. 60

12. The method of any of claims 9 to 11, further comprising rotating the substrate (10) while moving the substrate through the application station (108).
10

13. The method of any of claims 9 to 12, further comprising moving the web (102) after transferring the decoration to transport a second decoration of the plurality of decorations to the application station (108).
15

14. The method of any of claims 9 to 13, wherein each decoration of the plurality of decorations (18, 1604) comprises two or more physically separate decoration components (1606), and the adhesive (20) is exposed on a surface of each decoration component facing outwardly from the first side (114) of the web.
20

15. The method of claim 14, further comprising applying the two or more decoration components (1606) in register with one another to the substrate (10) at the application station (108).
25

16. The method of any of claims 9 to 15, wherein the decoration is transferred directly from the web (102) to the substrate (10) when the decoration is applied to the substrate.
30

Patentansprüche

1. System zum Applizieren von Dekorationen auf Substrate, umfassend:
35

eine durchgehende Bahn (102) einschließlich einer Vielzahl von Dekorationen (18, 1604), die auf einer ersten Seite (114) der Bahn bereitgestellt sind, wobei jede Dekoration einen Klebstoff (20) aufweist, der auf einer Oberfläche der Dekoration, die von der ersten Seite der Bahn nach außen weist, freiliegt;
40

eine Applizierstation (108), in der die Dekorationen auf Substrate (10) appliziert werden; einen Bahnweg, den die Bahn sich entlang bewegt, um die Dekoration zur Applizierstation zu transportieren;
45

ein Bahnsteuersystem einschließlich zumindest einer Bahnsteuerung (118), wobei das Bahnsteuersystem konfiguriert ist, um eine Bewegung der Bahn anzuhalten, wenn eine Dekoration an der Applizierstation positioniert ist; und einen Substrattransport (12), der konfiguriert ist, um ein Substrat durch die Applizierstation zu bewegen, während die Bahn angehalten wird, um das Substrat relativ zu der an der Applizierstation positionierten Dekoration zu bewegen und die Dekoration auf das Substrat zu applizieren.
50

2. System nach Anspruch 1, wobei der Klebstoff (20) ein druckempfindlicher Klebstoff ist.
55

3. System nach Anspruch 1 oder 2, wobei das Substrat (10) sich kontinuierlich an der Applizierstation (108) bewegt.
60

4. System nach einem der Ansprüche 1 bis 3, wobei die Substrate (10) gedreht werden, während sie sich durch die Applizierstation (108) bewegen.
65

5. System nach einem vorstehenden Anspruch, wobei das Bahnsteuersystem konfiguriert ist, um die Bahn (102) zu bewegen, um eine zweite Dekoration aus der Vielzahl von Dekorationen (18, 1604) nach dem Applizieren der Dekoration auf das Substrat zu der Applizierstation (108) zu transportieren.
70

6. System nach einem vorstehenden Anspruch, wobei jede Dekoration der Vielzahl von Dekorationen (18, 1604) zwei oder mehr physisch getrennte Dekorationskomponenten (1606) umfasst und der Klebstoff auf einer Oberfläche jeder Dekorationskomponente, die von der ersten Seite (114) der Bahn nach außen weist, freiliegt.
75

7. System nach Anspruch 6, wobei die zwei oder mehr Dekorationskomponenten (1606) in der Applizierstation (108) aufeinander ausgerichtet auf das Substrat (10) appliziert werden.
80

8. System nach einem vorstehenden Anspruch, wobei die Dekorationen (18, 1604) direkt von der Bahn (102) auf das Substrat (10) übertragen werden, wenn sie in der Applizierstation (108) auf die Substrate appliziert werden.
85

9. Verfahren zum Applizieren einer Dekoration (18, 1604) auf ein Substrat (10), umfassend:
90

Bewegen einer kontinuierlichen Bahn (102) entlang eines Bahnweges, um eine Vielzahl von Dekorationen, die auf einer ersten Seite (114) der Bahn bereitgestellt sind, zu einer Applizierstation (108) zu transportieren, wobei jede Dekoration einen Klebstoff (20) aufweist, der auf einer Oberfläche der Dekoration, die von der ersten Seite der Bahn nach außen weist, freiliegt;
95

Anhalten der Bewegung der Bahn (102), wenn eine Dekoration an der Applizierstation (108) positioniert ist; und Bewegen eines Substrats (10) durch die Applizierstation (108), während die Bahn (102) angehalten wird, um die an der Applizierstation positionierte Dekoration auf das Substrat zu applizieren.
100

10. Verfahren nach Anspruch 9, wobei der Klebstoff (20)

ein druckempfindlicher Klebstoff ist.

11. Verfahren nach Anspruch 9 oder 10, wobei sich das Substrat (10) kontinuierlich durch die Applizerstation (108) bewegt, während die Bahn angehalten wird.

5

12. Verfahren nach einem der Ansprüche 9 bis 11, weiter umfassend, Drehen des Substrats (10), während das Substrat durch die Applizerstation (108) bewegt wird.

10

13. Verfahren nach einem der Ansprüche 9 bis 12, weiter umfassend, Bewegen der Bahn (102) nach dem Übertragen der Dekoration, um eine zweite Dekoration aus der Vielzahl von Dekorationen zur Applizerstation (108) zu transportieren.

15

14. Verfahren nach einem der Ansprüche 9 bis 13, wobei jede Dekoration der Vielzahl von Dekorationen (18, 1604) zwei oder mehr physisch getrennte Dekorationskomponenten (1606) umfasst und der Klebstoff (20) auf einer Oberfläche jeder Dekorationskomponente, die von der ersten Seite (114) der Bahn nach außen weist, freiliegt.

20

15. Verfahren nach Anspruch 14, weiter umfassend, applizieren der zwei oder mehr Dekorationskomponenten (1606) aufeinander ausgerichtet auf das Substrat (10) an der Applizerstation (108).

25

16. Verfahren nach einem der Ansprüche 9 bis 15, wobei die Dekoration direkt von der Bahn (102) auf das Substrat (10) übertragen wird, wenn die Dekoration auf das Substrat appliziert wird.

30

Revendications

1. Système d'application de décos sur des substrats, comprenant :

40

une bande (102) continue comprenant une pluralité de décos (18, 1604) disposées sur un premier côté (114) de la bande, chaque décoration comportant un adhésif (20) exposé sur une surface de la décoration tournée vers l'extérieur du premier côté de la bande ;

45

une station (108) d'application au niveau de laquelle les décos sont appliquées sur des substrats (10) ;

50

un trajet de bande, le long duquel la bande se déplace pour transporter les décos jusqu'à la station d'application ;

55

un système de commande de bande comprenant au moins un dispositif (118) de commande de bande, dans lequel le système de commande de bande est conçu pour arrêter le déplacement de la bande lorsqu'une décoration est position-

née au niveau de la station d'application ; et un transport (12) de substrat conçu pour déplacer un substrat à travers la station d'application tandis que la bande est arrêtée pour déplacer le substrat par rapport à la décoration positionnée au niveau de la station d'application et appliquer la décoration sur le substrat.

2. Système selon la revendication 1, dans lequel l'adhésif (20) est un adhésif sensible à la pression.

3. Système selon la revendication 1 ou la revendication 2, dans lequel les substrats (10) se déplacent en continu au niveau de la station (108) d'application.

4. Système selon l'une quelconque des revendications 1 à 3, dans lequel les substrats (10) sont mis en rotation tout en se déplaçant à travers la station (108) d'application.

5. Système selon une quelconque revendication précédente, dans lequel le système de commande de bande est conçu pour déplacer la bande (102) pour transporter une seconde décoration de la pluralité de décos (18, 1604) jusqu'à la station (108) d'application après l'application de la décoration sur le substrat.

6. Système selon une quelconque revendication précédente, dans lequel chaque décoration de la pluralité de décos (18, 1604) comprend au moins deux composants (1606) de décoration physiquement séparés, et l'adhésif est exposé sur une surface de chaque composant de décoration tournée vers l'extérieur du premier côté (114) de la bande.

7. Système selon la revendication 6, dans lequel les au moins deux composants (1606) de décoration sont appliqués en alignement l'un avec l'autre sur le substrat (10) au niveau de la station (108) d'application.

8. Système selon une quelconque revendication précédente, dans lequel les décos (18, 1604) sont transférées directement de la bande (102) sur le substrat (10) lorsqu'appliquées sur les substrats au niveau de la station (108) d'application.

9. Procédé d'application d'une décoration (18, 1604) sur un substrat (10), comprenant : le déplacement d'une bande (102) continue le long d'un trajet de bande pour transporter une pluralité de décos disposées sur un premier côté (114) de la bande jusqu'à une station (108) d'application, dans lequel chaque décoration comporte un adhésif (20) exposé sur une surface de la décoration tournée vers l'extérieur du premier côté de la bande ;

l'arrêt du déplacement de la bande (102) lors-
qu'une décoration est positionnée au niveau de
la station (108) d'application ; et
le déplacement d'un substrat (10) à travers la
station (108) d'application tandis que la bande 5
(102) est arrêtée pour appliquer la décoration
positionnée au niveau de la station d'application
sur le substrat.

10. Procédé selon la revendication 9, dans lequel l'ad- 10
hésif (20) est un adhésif sensible à la pression.

11. Procédé selon la revendication 9 ou la revendication
10, dans lequel le substrat (10) se déplace en continu
à travers la station (108) d'application tandis que la 15
bande est arrêtée.

12. Procédé selon l'une quelconque des revendications
9 à 11, comprenant en outre la mise en rotation du
substrat (10) tout en déplaçant le substrat à travers 20
la station (108) d'application.

13. Procédé selon l'une quelconque des revendications
9 à 12, comprenant en outre le déplacement la bande 25
(102) après le transfert de la décoration pour trans-
porter une seconde décoration de la pluralité de dé-
corations jusqu'à la station (108) d'application.

14. Procédé selon l'une quelconque des revendications
9 à 13, dans lequel chaque décoration de la pluralité 30
de décorations (18, 1604) comprend au moins deux
composants (1606) de décoration physiquement sé-
parés, et l'adhésif (20) est exposé sur une surface
de chaque composant de décoration tournée vers
l'extérieur du premier côté (114) de la bande. 35

15. Procédé selon la revendication 14, comprenant en
outre l'application des au moins deux composants
(1606) de décoration en alignement l'un avec l'autre
sur le substrat (10) au niveau de la station (108) d'ap- 40
plication.

16. Procédé selon l'une quelconque des revendications
9 à 15, dans lequel la décoration est transférée di-
rectement de la bande (102) sur le substrat (10) lors- 45
que la décoration est appliquée sur le substrat.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- DE 19621857 A1 [0003]
- WO 2016191663 A1 [0004]
- WO 0073152 A [0005]
- DE 20006315 U1 [0006]
- US 20160335927 [0046]