

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property

Organization

International Bureau

(43) International Publication Date

03 December 2020 (03.12.2020)



(10) International Publication Number

WO 2020/239729 A1

(51) International Patent Classification:

C10G 1/00 (2006.01) C10G 19/02 (2006.01)

C10G 1/10 (2006.01) C10G 31/08 (2006.01)

C10G 3/00 (2006.01) C10G 67/10 (2006.01)

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(21) International Application Number:

PCT/EP2020/064512

(22) International Filing Date:

26 May 2020 (26.05.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

20195446 28 May 2019 (28.05.2019) FI

(71) Applicant: NESTE OYJ [FI/FI]; Keilaranta 21, 02150 Espoo (FI).

(72) Inventors: PAASIKALLIO, Ville; c/o Neste Oyj / IPR, POB 310, 06101 PORVOO (FI). TOUKONHITTY, Blanka; c/o Neste Oyj / IPR, POB 310, 06101 PORVOO (FI). PASANEN, Jukka-Pekka; c/o Neste Oyj / IPR, POB 310, 06101 PORVOO (FI).

(74) Agent: ZACCO DENMARK A/S; Arne Jacobsens Allé 15, 2300 København S (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: ALKALI-ENHANCED HYDROTHERMAL PURIFICATION OF PLASTIC PYROLYSIS OILS

(57) Abstract: The invention provides a method for preparing fuel components from waste pyrolysis oil, comprising: a) providing a waste pyrolysis oil, comprising as the major part plastic pyrolysis oil and/or tyre pyrolysis oil, and comprising impurities in the form of chlorine, nitrogen, sulphur, and optionally silicone or bromide; b) purifying the waste pyrolysis oil by subjecting it to a hydrothermal treatment with water or alkaline water; c) separating the hydrothermally treated waste pyrolysis oil from the aqueous phase; d) preparing a hydroprocessing feed from the hydrothermally treated waste pyrolysis oil, optionally in mixture with one or more feed(s) of oxygen-containing biological oils having impurities of chlorine and silicon; e) hydroprocessing the hydroprocessing feed catalytically with hydrogen to cause hydrogenation, and optionally one or more of hydrodeoxygenation, hydrodesulfurisation, hydrodenitrification, hydrodechlorination, hydrodearomatization, and hydroisomerisation; f) recovering a hydrocarbon fraction boiling in the liquid fuel range.



WO 2020/239729 A1

Alkali-enhanced hydrothermal purification of plastic pyrolysis oils

Field of the invention

- 5 The present invention relates to a method for preparing fuel components from waste pyrolysis oil (WPO).

Background of the invention

- 10 There is an increasing demand to find more sustainable refinery feedstocks. Co-processing renewable or recycled-type raw materials in existing refinery units along with traditional fossil feeds or even retro-fitting existing units to process solely these new raw materials is therefore gaining increasing attention.

- 15 Recycled-type raw materials or reduced-carbon feedstocks are feeds created by the processing of fossil-based wastes, like waste plastics or end-of-life tires. The attractive feature of these raw materials from the viewpoint of the refinery is that they largely represent the traditional refinery feeds in that they contain only small amount of oxygen and are composed of hydrocarbons.

- 20 Waste pyrolysis oil (WPO) is not a common feedstock as refinery stream in a hydrotreatment process. It is substantially different in composition from a feedstock based on oils and fatty acids components of plant origin, and hydrotreatment reactors in prior art in general do not have capacity to handle a feedstock having the properties of waste pyrolysis oil. Waste pyrolysis oils, such as plastic pyrolysis oils, contain different elemental
25 impurities dependent mostly on the original raw material, but also on the pyrolysis technology employed. The three most relevant impurities in waste pyrolysis oils are nitrogen, sulphur, and chlorine, which have a detrimental effect on the utilization of the pyrolysis oil. These impurities are primarily present in organic form, which means that they are structurally associated with hydrocarbon chains of varying size and complexity. Efficient
30 removal of organic impurities like chlorinated hydrocarbons is not possible using simple means like water washing or adsorption. Removal of compounds such as these necessitates the use of a reactive approach that liberates chlorine in a form that readily separates from the pyrolysis oil. One such form is hydrogen chloride (HCl), which is generated when chlorinated hydrocarbons are catalytically hydrotreated. This sort of catalytic processing
35 requires otherwise low elemental impurities in order to avoid catalyst deactivation, which can be problematic for processing complex materials such as plastic pyrolysis oils.

- Specifically, the hydrotreatment of the hydrocarbon chains comprising nitrogen, sulphur, and chlorine will result in the production of HCl, NH₃, and H₂S. After cooling of the
40 hydrotreated product, the HCl produced may be corrosive for the inlet pipe for the hydrotreatment reaction if it meets contact with water. The HCl may also react with the

NH₃ and produce NH₄Cl, which may plug the catalyst bed. NH₄Cl can also lead to fouling of heat exchangers.

Consequently, a different technology is required to prepare WPO as feedstock for refinery, and there is a pressing need to develop efficient and robust purification methods that can eliminate contaminants such as chlorinated hydrocarbons prior to subjecting a feedstock to hydrotreatment.

The prior art teaches, in general, four different concepts for processing plastic pyrolysis oil in a refinery setting which each of them aims at solving the challenge of removing harmful element impurities, in particular halogens, such as chlorine and bromine, but sometimes also nitrogen and sulphur, prior to the hydrotreatment:

- ✓ Removal of the harmful impurities through sorting of the solid plastic raw material;
- ✓ Removal of the harmful impurities during the pyrolysis most often using the so-called pre-cracking;
- ✓ Removal of the harmful impurities in a dedicated hydrotreatment unit;
- ✓ Removal of the harmful impurities using a pre-treatment step for the liquid pyrolysis oil prior to conventional refinery hydrotreatment.

The present invention is based on the principles of the last-mentioned of these concepts, but the solution according to the invention is different from the teaching of that concept in prior art. In particular, the literature disclosing removal of impurities from plastic pyrolysis oil is sparse, and it does not discuss plastic pyrolysis oil pre-treatment prior to refinery units for hydrotreatment.

WO 2017088015 A1 discloses a liquid-liquid extraction, a purification methods that are specified to be used for plastic pyrolysis oils.

US 2016/0264874 A1 discloses catalytic hydrotreatment of plastic pyrolysis oils.

US 7,955,498 B2 discloses a method for reducing halide concentration in a hydrocarbon product having an organic halide content that is made by a hydrocarbon conversion process using a halogen containing acidic ionic liquid catalyst

The object of the invention is to provide a method for removal of harmful impurities, in particular chlorine and nitrogen, in waste pyrolysis oil prior to conventional refinery hydrotreatment.

Another object is to provide a less complex pre-treatment step that removes the impurities prior to the refinery hydrotreatment without the use of heterogeneous catalysts and external hydrogen.

- 5 Yet another object is to provide a waste pyrolysis oil that can be used in existing hydrotreatment units for preparing fuel components.

These objects are fulfilled with the method of the present invention.

10 Summary of the Invention

Accordingly, the present invention provides a method for preparing fuel components from waste pyrolysis oil (WPO), comprising:

- a) providing a waste pyrolysis oil, comprising as the major part, such as at least 75 wt%, plastic pyrolysis oil (PPO) and/or tyre pyrolysis oil (TPO), the waste pyrolysis oil comprising as the major part hydrocarbons, and comprising impurities in the form of:
 - chlorine compounds, comprising at least 20 mg/kg chlorine of the WPO and optionally up to 3500 mg/kg,
 - nitrogen compounds, comprising at least 50 mg/kg nitrogen of the WPO and optionally up to 10,000 mg/kg,
 - sulphur compounds, comprising at least 10 mg/kg sulphur of the WPO and optionally up to 15,000 mg/kg;
- b) purifying the waste pyrolysis oil by subjecting it to a hydrothermal treatment with water or with water having a pH above 7 at 150-450 °C, where the oil to water ratio is from 9:1 to 1:9 (weight/weight), such as from 4:1 to 1:1;
- c) separating the hydrothermally treated waste pyrolysis oil from the aqueous phase;
- d) preparing a hydroprocessing feed
 - consisting essentially of the hydrothermally treated waste pyrolysis oil; or
 - consisting essentially of a mixture of the hydrothermally treated waste pyrolysis oil and one or more feed(s) selected from the list consisting of oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon and hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon;
- e) hydroprocessing the hydroprocessing feed catalytically with hydrogen to cause hydrogenation, and optionally one or more of hydrodeoxygenation (HDO), hydrodesulfurisation (HDS), hydrodenitrification (HDN), hydrodechlorination (HDCI), hydrodearomatization (HDAr), and hydroisomerisation (HI), at a temperature between 200 and 450 °C, and at a pressure between 1MPa and 25 MPa;

- f) recovering from the hydroprocessed product at least one hydrocarbon fraction boiling in the liquid fuel range.

Thus, the present invention combines a hydrolysis step prior to hydrotreatment and a hydrotreatment step in existing hydrotreatment equipment. According to the invention, waste pyrolysis oil is pre-treated by heating to temperatures of 150 to 450 °C in the presence of water or an aqueous solution having a pH of more than 7. By the present invention, it is possible to at least partially remove organic chlorine and other elemental impurities from the waste pyrolysis oils without using heterogeneous catalysts and external hydrogen. Although this purified waste pyrolysis oil is not yet a ready fuel component, there are less impurities left that would need to be removed using other means. Thus, this purification method essentially improves the usability of waste pyrolysis oils, such as plastic pyrolysis oil (PPO) and tyre pyrolysis oil (TPO), for e.g. existing refinery hydrotreatment units. In theory, waste pyrolysis oils which prior to hydrotreatment have been purified using the method according to the invention could be fed into refinery hydrotreatment units utilizing higher blends than what would be possible if the purification had not been carried out prior to feeding the feedstock to the hydrotreatment reactor.

5 The reaction may be carried out in a pressurized system that includes mixing. After a certain reaction time, the mixture may be cooled, and the oil and aqueous phases separated by for example centrifugation. It is presumed that chlorine is released in the form of HCl, which is subsequently neutralized by the basic component, e.g. NaOH, if present in the aqueous solution. Consequently, the pH of the aqueous solution decreases during the reaction. Compared to the original plastic pyrolysis oil, the pyrolysis, which has been treated in this manner, has lower contents of chlorine, nitrogen, and sulphur, and in some embodiments
10 it may also have lower contents of bromine and silicon. In some embodiments, a solid precipitate is also formed. It is therefore plausible that impurities that are removed from the pyrolysis oil are transferred to both the aqueous phase and the precipitate.

15 Compared to the hydrotreatment approach in prior art, the process of the invention is much less complex as it requires no hydrogen or catalyst, and besides removing chlorine, nitrogen, and sulphur, it may also remove bromine and silicon in some embodiments.

Thus, in one preferred embodiment of the method of the invention, the WPO may further comprise impurities in the form of silicon compounds, comprising at least 20 mg/kg silicon of the WPO, and/or impurities in the form of bromine compounds, comprising at least 10 mg/kg bromine of the WPO. In particular, it is surprising that silicon can also be removed by the present method, and this broadens the application field of the waste pyrolysis oil.

Some definitions**Hydroprocessing feed**

In the context of the present invention, the hydroprocessing feed may comprise oxygen-containing biological oils in mixture with the hydrothermally treated waste pyrolysis oil deriving from plastic pyrolysis oil (PPO) and/or tyre pyrolysis oil (TPO) as defined in the claims. Oxygen-containing biological oils are typically free fatty acids and fatty acid derivatives, such as esters, e.g. glycerides, amides, alcohols, anhydrides, metal salts, or mixtures thereof, the fatty acids having 4 or more carbon atoms, such as from 4 to 24 carbon atoms, and the fatty acid may be saturated or unsaturated.

Hydroprocessing

In the context of the present invention, hydroprocessing is a catalytic treatment causing hydrogenation of the hydrocarbons in the feed and, optionally, one more of the processes as defined in the claims, and which adds hydrogen to and/or remove oxygen, sulphur, nitrogen, chlorine, and/or aromatics from the hydrocarbons in the feed, and/or causes hydroisomerisation thereof.

Detailed description of the invention

In describing the embodiments of the invention, specific terminology will be resorted to for the sake of clarity. However, the invention is not intended to be limited to the specific terms so selected, and it is understood that each specific term includes all technical equivalents that operate in a similar manner to accomplish a similar purpose.

When describing the embodiments of the present invention, the combinations and permutations of all possible embodiments have not been explicitly described. Nevertheless, the mere fact that certain measures are recited in mutually different dependent claims or described in different embodiments does not indicate that a combination of these measures cannot be used to advantage. The present invention envisages all possible combinations and permutations of the described embodiments.

The terms “comprising”, “comprise” and comprises herein are intended by the inventors to be optionally substitutable with the terms “consisting of”, “consist of” and “consists of”, respectively, in every instance.

According to the method of the invention, the WPO comprises as a major part PPO and/or TPO that comprises hydrocarbons as their major part. The major part constitutes for example at least 75 wt% PPO and/or TPO in the WPO, such as at least 80 wt%, e.g. at least 85wt%, at least 90 wt%, at least 95wt%, or at least 98 wt%. The hydrocarbons constitute for example at least 75 wt% of the WPO, such as at least 80 wt%, e.g. at least 85wt%, at least 90 wt%, at least 95wt%, or at least 98 wt% of the WPO.

The impurities in the WPO in the form of chlorine compounds constitute at least 20 mg/kg chlorine of the WPO, such as at least 50 mg/kg, e.g. at least 100 mg/kg, at least 200 mg/kg, at least 300 mg/kg, at least 400 mg/kg, at least 500 mg/kg, at least 1000 mg/kg, at least 1500 mg/kg, at least 2000 mg/kg, at least 2500 mg/kg, at least 3000 mg/kg, and up to 3500 mg/kg.

The impurities in the WPO in the form of nitrogen compounds constitute at least 50 mg/kg nitrogen of the WPO, e.g. at least 100 mg/kg, at least 200 mg/kg, at least 300 mg/kg, at least 400 mg/kg, at least 500 mg/kg, at least 1000 mg/kg, at least 2000 mg/kg, at least 3000 mg/kg, at least 5000 mg/kg, at least 7000 mg/kg, and up to 10,000 mg/kg.

The impurities in the WPO in the form of sulphur compounds constitute at least 10 mg/kg sulphur of the WPO, such as at least 20 mg/kg, e.g. at least 50 mg/kg, at least 100 mg/kg, at least 200 mg/kg, at least 300 mg/kg, at least 400 mg/kg, at least 500 mg/kg, at least 1000 mg/kg, at least 2000 mg/kg, at least 3000 mg/kg, at least 5000 mg/kg, at least 7000 mg/kg, at least 10,000 mg/kg, and up to 15,000 mg/kg.

During the hydrothermal treatment, the pH in the water may be adjusted to above 7 by adding any convenient base, such as NaOH, KOH, LiOH, Ca(OH)₂, Mg(OH)₂, Ba(OH)₂, preferably NaOH.

During the hydrothermal treatment, the temperature is from 150 to 450 °C, such as from 175 to 425 °C, e.g. from 200 to 400 °C, from 225 to 375 °C, from 250 to 350 °C, from 275 to 325 °C, or from 250 to 300 °C.

During the hydrothermal treatment, the oil to water ratio (weight/weight) is from 9:1 to 1:9, such as from 4:1 to 1:1, e.g. 2:1.

In a first embodiment of the method of the invention, the WPO may further comprise impurities in the form of silicon compounds, comprising at least 20 mg/kg silicon of the WPO, such as at least 30 mg/kg, at least 40 mg/kg, at least 50 mg/kg, at least 60 mg/kg, at least 70 mg/kg, at least 80 mg/kg, at least 90 mg/kg, at least 100 mg/kg, at least 150 mg/kg, at least 200 mg/kg, at least 300 mg/kg, at least 400 mg/kg, at least 500 mg/kg, at least 600 mg/kg, at least 700 mg/kg, at least 800 mg/kg, at least 900 mg/kg, at least 1000 mg/kg, at least 1500 mg/kg, and up to 2000 mg/kg; and/or impurities in the form of bromine compounds, comprising at least 10 mg/kg bromine of the WPO, such as at least 20 mg/kg, at least 30 mg/kg, at least 40 mg/kg, at least 50 mg/kg, at least 60 mg/kg, at least 70 mg/kg, at least 80 mg/kg, at least 90 mg/kg, at least 100 mg/kg, at least 150 mg/kg, at least 200 mg/kg, at least 300 mg/kg, at least 400 mg/kg, at least 500 mg/kg, at least 600 mg/kg, at least 700 mg/kg, at least 800 mg/kg, at least 900 mg/kg, at least 1000 mg/kg, at least 1500 mg/kg, and up to 2000 mg/kg.

In any of the embodiments of the invention, the WPO may further comprise impurities in the form of silicon compounds, comprising at least 20 mg/kg silicon and up to 2000 mg/kg, and the hydrothermal treatment in step b) may be conducted so as to cause at least a 50% reduction of silicon compounds of the waste pyrolysis oil and/or at least a 50% reduction of chlorine compounds, optionally whereby the silicon in the hydrothermally treated waste pyrolysis oil are below 20 mg/kg, and/or whereby the oxygen in the hydrothermally treated waste pyrolysis oil are above 20 mg/kg.

In any of the embodiments of the invention, the water used in step b) having a pH above 7 may contain one or more cations selected from the list consisting of: alkali metals, such as Li, Na, K, Rb, Cs, and alkaline earth metals, such as Mg, Ca, Sr, and Ba.

In any of the embodiments of the invention, the hydroprocessing feed may consist essentially of a mixture of the hydrothermally treated waste pyrolysis oil and one or more of the list consisting of: oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon and hydrocarbons having less than 5 mg/kg chlorine and less than 1 mg/kg silicon.

In any of the embodiments of the invention, the hydroprocessing feed may consist essentially of a mixture of the hydrothermally treated waste pyrolysis oil, oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon, and hydrocarbons having less than 5 mg/kg chlorine and less than 1 mg/kg silicon.

In any of the embodiments of the invention, the hydroprocessing feed may consist essentially of a mixture of:

- 1-100 wt% of the hydrothermally treated waste pyrolysis oil, such as 5, 10, 20, 30, 40, 50, 60, 70, 80, 90, or 95 wt%;
- 0-40 wt% of the oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon, such as 1-30 wt%, e.g. 5-25 wt%, or 10-20 wt%; and
- 0-99 wt% of the hydrocarbons, such as 2, 5, 10, 15, 20, 25, 30, 35, 40, 50, 60, 70, 80, 90, or 95 wt%, having less than 5 mg/kg chlorine and less than 1 mg/kg silicon.

In any of the embodiments of the invention, the hydroprocessing feed may consist essentially of a mixture of:

- 1-10 wt% of the hydrothermally treated waste pyrolysis oil, such as 2, 3, 4, 5, 6, 7, 8, 9, or 10 wt%;
- 1-40 wt% of the oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon, such as 5-30 wt%, e.g. 10-25 wt%, or 15-20 wt%; and
- 50-98 wt% of the hydrocarbons, such as 55-95 wt%, e.g. 60-90 wt%, or 70-80wt%, having less than 5 mg/kg chlorine and less than 1 mg/kg silicon.

In any of the embodiments of the invention, in step d) at least 80 wt% of the hydrocarbons having less than 5 mg/kg chlorine and less than 1 mg/kg silicon, such as at least 85 wt%, e.g. at least 90 wt% or at least 95wt%, may be recycled product obtained from step f).

In any of the embodiments of the invention, in step d) the hydrocarbons having less than 5 mg/kg chlorine and less than 1 mg/kg silicon may further also have less than 1 wt% olefins.

In any of the embodiments of the invention, in step f) the at least one hydrocarbon fraction boiling in the liquid fuel range may be diesel and/or gasoline and/or naphtha.

In any of the embodiments of the invention, in step e) the hydroprocessing may be conducted in a fixed bed reactor.

In any of the embodiments of the invention, the hydroprocessing reaction conditions may comprise a temperature in the range from 270 to 390 °C, such as 280 °C, 290 °C, 300 °C, 310 °C, 320 °C, 330 °C, 340 °C, 350 °C, 360 °C, 370 °C, or 380 °C, depending of the nature of the hydrocarbon and the biological oil in the mixture, a pressure in the range from 2 to 8 MPa, and a WHSV in the range from 0.1 – 10 h⁻¹, preferably from 0.5 to 5 h⁻¹, and a H₂ flow of 50 to 2000 nl H₂/l feed, preferably from 100 to 900 nl H₂/l feed, in the presence of a hydrodeoxygenation catalyst, such as NiMo on an alumina support.

In any of the embodiments of the invention, the hydroprocessing reaction conditions may comprise conditions suitable for isomerisation, which reaction conditions comprise a temperature in the range from 250 to 450 °C, such as 300 to 400 °C, a pressure in the range from 1 to 6 MPa, such as 2 to 5 MPa, and a WHSV in the range from 0.1 to 10 h⁻¹, preferably from 0.5 to 5 h⁻¹, more preferably from 0.5 to 3 h⁻¹, and a H₂ flow of from 50 to 2000 nl H₂/l feed, preferably from 100 to 900 nl H₂/l feed, more preferably from 100 to 800 nl H₂/l feed, in the presence of an isomerisation catalyst, such as a catalyst comprising a Group VIII metal and a molecular sieve, optionally on an alumina and/or silica support.

Examples

Example 1

High temperature NaOH treatment of waste plastic pyrolysis oil naphtha fraction

5 The following experiment was carried out in a 1-litre batch autoclave reactor. A distilled naphtha fraction (5-95 wt% distillation range 85-174 °C) derived from waste plastic pyrolysis oil (340 g) and the 2 wt% aqueous NaOH (227 g) were weighed together into the reactor vessel. After sealing and pressure testing, the reactor that was stirred at 500 rpm was heated to the desired reaction temperature of 240 °C, which was then maintained for 10 30 min. The reactor was subsequently cooled down to room temperature before recovery of products. The contents were decanted from the reactor vessel into centrifugation tubes, and the liquids were centrifuged at 20 °C and 4300 rpm for 30 minutes. After the centrifugation, the purified pyrolysis oil was recovered as a separate layer, and analysed for its Cl, Br, S, and N content. Cl, Br, and S content was determined using X-ray fluorescence spectroscopy, and N content was determined according to standard ASTM D 5762. The 15 results, which are presented in Table 1, show that the content of both Cl and Br is reduced by more than 90 %.

20 *Table 1. Impurity content of waste plastic pyrolysis oil naphtha fraction before and after 30 min treatment with 2 wt-% aqueous sodium hydroxide at 240 °C.*

	Original waste plastic pyrolysis oil naphtha fraction	Purified waste plastic pyrolysis oil naphtha fraction	Decrease (%)
N (mg/kg)	500	25	95
Cl (mg/kg)	590	36	94
Br (mg/kg)	213	7	97
S (mg/kg)	89	80	10

Example 2

High temperature NaOH treatment of waste plastic pyrolysis oil naphtha fraction

25 The following experiment was carried out in a 1-litre batch autoclave reactor. A distilled naphtha fraction (5-95 wt% distillation range 85-174 °C) derived from waste plastic pyrolysis oil (340 g) (obtained commercially from Ecomation) and the 2 wt% aqueous NaOH (227 g) were weighed together into the reactor vessel. After sealing and pressure testing, the reactor that was stirred at 500 rpm was heated to the desired reaction temperature of 30 240 °C, which was then maintained for 30 min. The reactor was subsequently cooled down to room temperature before recovery of products. The contents were decanted from the reactor vessel into centrifugation tubes, and the liquids were centrifuged at 20 °C and 4300 rpm for 30 minutes. After the centrifugation, the purified pyrolysis oil was recovered as a

separate layer, and analysed for its Cl, Br, S, N and Si content. Cl, Br, and S content was determined using X-ray fluorescence spectroscopy, and N content was determined according to standard ASTM D5762. The silicon content was analysed using inductively coupled plasma mass spectrometry. The results, which are presented in Table 2, clearly show that the content of Cl, Br and Si decreased by more than 90%.

Table 2. Impurity content of waste plastic pyrolysis oil naphtha fraction before and after 30 min treatment with 2 wt-% aqueous sodium hydroxide at 240 °C.

	Original waste plastic pyrolysis oil naphtha fraction	Purified waste plastic pyrolysis oil naphtha fraction	Decrease (%)
N (mg/kg)	500	65	87
Cl (mg/kg)	590	28	95
Br (mg/kg)	213	7	97
S (mg/kg)	89	87	2
Si (mg/kg)	230	2	99

Example 3

Solvent extraction of waste plastic pyrolysis oil middle distillate fraction

In this example, impurities were removed from a waste plastic pyrolysis oil middle distillate fraction (5-95 wt% distillation range 172-342 °C) using solvent extraction with *N*-methyl-2-pyrrolidone (NMP). The waste plastic pyrolysis oil (100 g) was first mixed with NMP containing 2 wt% water (196 g NMP, 4 g water) in a glass separation funnel at ambient temperature. After mixing, the raffinate and extract were allowed to separate. The raffinate, which in this case represents the purified waste plastic pyrolysis oil, was subjected to the same extraction treatment two more times (3 extraction steps in total). After the third extraction step, the raffinate was washed with water at ambient temperature in a glass separation funnel using a water-to-oil ratio of 2:1 (w/w). The water-washed raffinate, *i.e.* the purified pyrolysis oil middle distillate fraction, was analysed for its Cl, Br, S and N content. Cl, Br and S content was determined using X-ray fluorescence spectroscopy, and N content was determined according to standard ASTM D 5762. The results in Table 3 show Cl and Br content were both reduced by more than 90 % as a result of the solvent extraction treatment.

Table 3. Impurity content of waste plastic pyrolysis oil middle distillate fraction before and after solvent extraction with N-methyl-2-pyrrolidone and water washing.

	Original waste plastic pyrolysis oil middle distillate fraction	Purified waste plastic pyrolysis oil middle distillate fraction	Decrease (%)
N (mg/kg)	810	24	97
Cl (mg/kg)	590	40	93
Br (mg/kg)	325	14	96
S (mg/kg)	695	35	95

Claims

1. A method for preparing fuel components from waste pyrolysis oil (WPO), comprising:
 - a) providing a waste pyrolysis oil, comprising as the major part, such as at least 75 wt%, plastic pyrolysis oil (PPO) and/or tyre pyrolysis oil (TPO), the waste pyrolysis oil comprising as the major part hydrocarbons, and comprising impurities in the form of:
 - chlorine compounds, comprising at least 20 mg/kg chlorine of the WPO and optionally up to 3500 mg/kg,
 - nitrogen compounds, comprising at least 50 mg/kg nitrogen of the WPO and optionally up to 10,000 mg/kg,
 - sulphur compounds, comprising at least 10 mg/kg sulphur of the WPO and optionally up to 15,000 mg/kg;
 - b) purifying the waste pyrolysis oil by subjecting it to a hydrothermal treatment with water or with water having a pH above 7 at 150-450 °C, where the oil to water ratio is from 9:1 to 1:9 (weight/weight), such as from 4:1 to 1:1;
 - c) separating the hydrothermally treated waste pyrolysis oil from the aqueous phase;
 - d) preparing a hydroprocessing feed
 - consisting essentially of the hydrothermally treated waste pyrolysis oil; or
 - consisting essentially of a mixture of the hydrothermally treated waste pyrolysis oil and one or more feed(s) selected from the list consisting of oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon and hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon;
 - e) hydroprocessing the hydroprocessing feed catalytically with hydrogen to cause hydrogenation, and optionally one or more of hydrodeoxygenation (HDO), hydrodesulfurisation (HDS), hydrodenitrification (HDN), hydrodechlorination (HDCI), hydrodearomatization (HDAr), and hydroisomerisation (HI), at a temperature between 200 and 450 °C and at a pressure between 1MPa and 25 MPa;
 - f) recovering from the hydroprocessed product at least one hydrocarbon fraction boiling in the liquid fuel range.
2. The method according to claim 1, wherein the WPO further comprises impurities in the form of silicon compounds, comprising at least 20 mg/kg silicon of the WPO and optionally up to 2000 mg/kg, and/or impurities in the form of bromine compounds, comprising at least 10 mg/kg bromine of the WPO and optionally up to 2000 mg/kg.

3. The method according to any of the claims 1 and 2, wherein the WPO further comprises impurities in the form of silicon compounds, comprising at least 20 mg/kg silicon of the WPO and optionally up to 2000 mg/kg, wherein in step b) the hydrothermal treatment is conducted so as to cause at least a 50% reduction of silicon compounds of the WPO; or at least a 50% reduction of chlorine compounds of the WPO; or at least a 50% reduction of silicon compounds of the WPO, and at least a 50% reduction of chlorine compounds of the WPO, optionally where the silicon in the hydrothermally treated WPO are below 20 mg/kg, and/or where the oxygen in the hydrothermally treated WPO are above 20 mg/kg.
4. The method according to any one of claims 1 - 3, wherein in step b) the water having a pH above 7 contain one or more cations selected from the list consisting of: alkali metals, such as Li, Na, K, Rb, Cs, alkaline earth metals, such as Mg, Ca, Sr, Ba.
5. The method according to any one of claims 1 – 4, wherein the hydroprocessing feed consists essentially of a mixture of the hydrothermally treated waste pyrolysis oil and one or more feed(s) selected from the list consisting of oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon and hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon.
6. The method according to any one of claims 1 – 5, wherein the hydroprocessing feed consists essentially of a mixture of the hydrothermally treated waste pyrolysis oil, oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon, and hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon.
7. The method according to any one of claims 1 – 6, wherein the hydroprocessing feed consists essentially of a mixture of:
 - 1-100 wt% of the hydrothermally treated waste pyrolysis oil,
 - 0-40 wt% of the oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon; and
 - 0-99 wt% of the hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon.
8. The method according to any one of claims 1 – 7, wherein the hydroprocessing feed consists essentially of a mixture of:
 - 1-10 wt% of the hydrothermally treated waste pyrolysis oil,
 - 1-40 wt% of the oxygen-containing biological oils having less than 50 mg/kg chlorine and less than 1 mg/kg silicon; and
 - 50-98 wt% of the hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon.

9. The method according to any one of claims 1 – 8, wherein in step d) at least 80 wt% of the hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon are recycled product obtained from step f).
10. The method according to any one of claims 1 – 9, wherein in step d) the hydrocarbons having less than 50 mg/kg chlorine and less than 1 mg/kg silicon further also have less than 1 wt% olefins.
11. The method according to any one of claims 1 – 10, wherein in step f) the at least one hydrocarbon fraction boiling in the liquid fuel range is diesel and/or gasoline and/or naphtha.
12. The method according to any one of claims 1 – 11, wherein in step e) the hydroprocessing is conducted in a fixed bed reactor.
13. The method according to any one of claims 1 – 12, wherein the hydroprocessing reaction conditions comprise a temperature in the range from 270 to 390 °C, a pressure in the range from 2 MPa to 8 MPa, a WHSV in the range from 0.1 – 10 h⁻¹, and a H₂ flow of 50-2000 nl H₂/l feed.
14. The method according to claim 13, wherein the reaction conditions comprise the presence of a hydrodeoxygenation catalyst, such as NiMo on an alumina support.
15. The method according to any one of claims 1 – 14, wherein the hydroprocessing reaction conditions comprise conditions suitable for isomerisation, which reaction conditions comprise a temperature in the range from 250 to 450 °C, a pressure in the range from 1 MPa to 6 MPa, a WHSV in the range from 0.1 to 10 h⁻¹, and a H₂ flow of 50 to 2000 nl H₂/l feed, in the presence of an isomerisation catalyst, such as a catalyst comprising a Group VIII metal and a molecular sieve, optionally on an alumina and/or silica support.

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2020/064512

A. CLASSIFICATION OF SUBJECT MATTER

INV. C10G1/00 C10G1/10 C10G3/00 C10G19/02 C10G31/08
C10G67/10

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2009/062581 A1 (APPEL BRIAN S [US] ET AL) 5 March 2009 (2009-03-05) figure 1 claims 37, 43-46, 52, 53 paragraphs [0051], [0076] -----	1-15
X	WO 2014/001632 A1 (UPM KYMMENE CORP [FI]) 3 January 2014 (2014-01-03) claims 1, 4, 6, 9-13 figure 1 page 16, lines 23-25 -----	1-15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 July 2020

Date of mailing of the international search report

22/07/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Pardo Torre, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2020/064512

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009062581	A1	05-03-2009	
		AU 2009219278 A1	03-09-2009
		BR PI0907920 A2	28-07-2015
		CA 2753534 A1	03-09-2009
		CN 102015583 A	13-04-2011
		EP 2257510 A1	08-12-2010
		JP 2011515509 A	19-05-2011
		KR 20100122103 A	19-11-2010
		NZ 588214 A	26-10-2012
		US 2009062581 A1	05-03-2009
		WO 2009108761 A1	03-09-2009
		ZA 201006788 B	25-01-2012

WO 2014001632	A1	03-01-2014	
		FI 126813 B	31-05-2017
		WO 2014001632 A1	03-01-2014
