

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
10 September 2004 (10.09.2004)

PCT

(10) International Publication Number  
WO 2004/077204 A2

(51) International Patent Classification<sup>7</sup>: G06F

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/IB2004/001091

(22) International Filing Date: 27 February 2004 (27.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/450,576 27 February 2003 (27.02.2003) US

(71) Applicant (for all designated States except US): THOM-SON LICENSING S.A. [FR/FR]; 46, Quai A. Le Galo, F-92648 Boulogne Cedex (FR).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BICHOT, Guillaume [FR/FR]; 26, rue de Mont Muran, F-35630 La Chapelle Chaussee (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,



(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: WLAN TIGHT COUPLING SOLUTION



WO 2004/077204 A2

(57) Abstract: A method for communicating between a cellular system and a mobile terminal by way of a standard wireless LAN and the Internet allows data communications to traverse the core of the cellular network, thereby allowing monitoring of the time and volume usage by the subscriber for billing purposes. The user terminal has a communication protocol for communicating with the wireless LAN, over which is a EAP/EAPOL protocol. A Radio Adaptation Layer (RAL) protocol overlies the EAP/EAPOL protocol. At the cellular system, a Serving GPRS Support Node has a RAL/EAP/TCP-IP protocol for providing communications between the wireless LAN and the cellular system by way of the Internet.

WLAN TIGHT COUPLING SOLUTIONField of the Invention

5 [0001] The invention relates to communications between a user terminal and a cellular communication system by means of a wireless LAN. The wireless LAN communicates with the cellular system by means of the Internet. The user terminal is attached to the cellular communication system through the wireless LAN access point.

10

Background of the Invention

15 [0002] Public Wireless Local Area Networks (WLAN) systems are becoming more common, but the WLAN systems are for the most part independently operated and controlled. Thus, there are many separate owner/operators of WLAN systems. Each separately controlled system is termed a "domain." Because of the large number of owner/operators or domains, it is difficult or impossible for a user to subscribe to all the different WLAN systems to which connection may be made, especially in view of 20 the fact that the potential user may become aware of the existence of a wireless local area system in a particular area only when his portable communication device announces its availability. In order to ameliorate this situation and to provide improved service, some service providers aggregate, in 25 some way, two or more separate WLAN systems by entering into agreements with other providers.

30 [0003] A communications service provider may provide various different kinds of service. In those cases in which the communications service provider is a cellular communications network (3GPP or cellphone service) provider, the provider may make available Internet access, with the user authenticated by the cellular network but Internet access by way of the Wireless Local Area Network (WLAN). In such

Internet-only WLAN service, the Internet data never traverses or moves over the cellular system. However, the authentication, authorization, and accounting control data relating to the Internet service may traverse the cellular 5 system. The term "loose coupling" is applied to communications in which control data for establishing a connection, and authenticating, authorizing, and accounting information of the user is routed through the WLAN to the cellular system, but once the connection is set up, the user data is routed to the 10 internet, or other network, through only the WLAN. The loose coupling arrangement has the disadvantage that the cellular and WLAN systems are substantially independent, and the cellular system operator therefore does not have any ready access to information about the time usage of the WLAN system, or the 15 volume of data, either or both of which may be useful in customer billing. Moreover the user cannot access certain cellular network specific services like SMS.

[0004] Another possible type of communication service is full cellular network based access, in which the user data 20 and the control information both traverse the cellular network. In such service, the WLAN acts as a radio network portion of the cellular network and the user has access to the full cellular network service set, including Internet access and specific services like SMS. This type of communication is 25 known as "tight" coupling. While theoretically appealing and potentially advantageous to the user and service provider, tight coupling has been considered by the various standardization groups to be too complex, as the protocols and requisite infrastructure would adversely affect the WLAN.

30 Currently, certain standards bodies, such as the European Telecommunication Standard Institute (ETSI), Institute of Electrical and Electronic Engineers (IEEE), and 3<sup>rd</sup> Generation Partnership Project (3GPP) are focusing on the loose coupling

model due to its relative simplicity.

**[0005]** FIGURE 1 is a simplified block diagram of a prior art GPRS 3GPP digital cellular telecommunications system designated generally as 10. In general, such a system adheres 5 to standards for digital cellular telecommunication system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); General Packet Radio Service (GRPS); Service description; Stage 2 (3GPP TS 23.060 version 3.7.0 Release 1999. The system 10 of FIGURE 1 includes a radio access 10 network (RN or RAN) 12 and a core network (CN) 14. The radio access network 12 includes a set 16 of Radio Network Controllers (RNC), some of which are illustrated as 16a and 16b. Each radio network controller (RNC) of set 16, such as RNC 16b, controls at least one "base station" or "Node B." In 15 FIGURE 1, RNC 16b controls a set 18 including node B base stations 18a and 18b. Each node B base station corresponds to a cell of the cellular system. Each node B base station or cell communicates by wireless (radio) means with one or more mobile users (UE), one of which is designated 20, located in the zone 20 of the corresponding cell, as suggested by symbol 22.

**[0006]** The core network (CN) 14 of the telecommunications system 10 of FIGURE 1 includes a set 30 of Serving GPRS Support Nodes (SGSN), two of which are designated 30a and 30b. Each SGSN of set 30 provides services for 25 managing the connection between the core network 13 and the user 20, by way of the radio network controller 12. In this context, management of the connection refers to management of connection, authentication, and mobility. In this context, connection management relies on the process to provision 30 network resources such as radio resources, memory, and priority in order to be able to transmit data. Mobility is the set of protocols/processes which allow the user to move among several cells, and is also known as handover. Each SGSN also serves as

a "front end," providing the user 20 with access to other 3G services such as Short Messaging System (SMS).

5 [0007]. The Serving GPRS Support Nodes (SGSN) of set 30 of SGSNs of core network 14 communicate with a Home Location Register (HLR) which is illustrated as an external memory 40. The HLR 40 is the database that includes all relevant information relating to each subscriber to the network 10. The SGSN of set 30, as for example SGSN 30a, identifies and authenticates a user by reference to the HLR 40.

10 [0008] The Gateway GPRS Support Node (GGSN) 32 of core network 14 provides interconnection between core network 14 and an external Internet-Protocol (IP) based Packet Data Network (PDN) 110, such as the Internet.

15 [0009] The system 10 also includes a Border Gateway (BG) 34 in core network 14. Border gateway 34 is a function, which allows the user to roam between or among GPRS networks belonging to different domains (operators). Border Gateway 34 is connected to an external Public Land Mobile Network (PLMN) 134.

20 [0010] In operation of system 10, the RNCs 16a, 16b of set 16 implement or realize the interface between the core network 14 and the radio network.

25 [0011] FIGURE 2a is a simplified illustration of the control protocol stacks of the mobile terminal (UE) 20, the node B of set 18, the Radio Network Controllers (RNC) of set 16, and the Serving GPRS Support Nodes (SGSN) of set 30, and FIGURE 2b illustrates a sequence of the successive protocol operations for opening a user data channel between the UE 20 and SGSN 30 of FIGURE 2a. In FIGURE 2a, protocols associated 30 with the mobile terminal UE are designated generally as 220, protocols associated with the Node B are designated generally as 250, protocols associated with the RNC are designated generally as 216, and those associated with SGSNs are

designated generally as 230. The radio interface between the mobile node UE and the Node B corresponds to one of the standardized 3G cellular radio interface, such as WCDMA. In the mobile terminal UE, the MAC (Medium Access Control) protocol in conjunction with the RLC (Radio Link Control) protocol allows the transport of information, whatever its nature (i.e. user data or control). The RRC (Radio Resource Control) protocol is used between the UE and the RNC for radio connection control (creation, removal, and/or modification of the connection). The GMM (GPRS Mobility Management) protocol and CM (Connection Management) protocols are used between the mobile terminal and the SGSN for respectively mobility management (authentication and handover) and user data connection management. The Node B (or base station) is under the control of an RNC through the usage of a set of protocols, which are not represented in FIGURE 2a. The RNC is controlled by the SGSN by means of the RANAP (Radio Network Application Protocol) protocol that is carried by a protocol stack based on ATM (Asynchronous Transfer Mode) not depicted. The SGSN communicates with the GGSN 32 of FIGURE 1 for control purposes by means of the GTP-C (GPRS Tunneling Protocol- Control) that is carried by a protocol stack based on the TCP/IP protocol stack. Figure 2b represents a sequence diagram of the successive protocol operations in order to open a data user channel between the mobile terminal and the SGSN.

[0012] Initially, a mobile terminal UE such as terminal 20, once switched on, catches or captures broadcast downlink information, thereby allowing the UE to send an attachment request to the SGSN through a physical transmission opportunity. The SGSN immediately opens a signaling channel used only for control purposes. This process is not depicted in

FIGURE 1B and is represented as a first step by a numeral 1 within a circle. Once the basic signaling (or control) channel is set up, the mobile terminal UE requests a user data connection characterized by means of QOS (Quality Of Service) 5 parameters through or by means of a Connection Management (CM) protocol (step 2 in Figure 2B). The appropriate SGSN, such as SGSN 30a of FIGURE 1, verifies the request (determines if the mobile terminal is authorized for the requested service) and requests through or by means of the Radio Access Network 10 Protocol (RANAP) that an associated RNC, which in this case could be RNC 16b, establish the radio connection associated with the QOS parameters (circled step "3" in Figure 2b). The RNC (16b in this case) translates the QOS parameters into 15 parameters which are used to establish the corresponding radio connection, and commands such a radio connection in both the base station (Node B 18a in this case) and the mobile terminal UE, corresponding to circled step 4 in Figure 2b). The RNC controls the terminal by means of the Radio Resource Control (RRC) protocol. The UE 20 and the Node B 18a use the 20 parameters transmitted by the RNC (carry them without change) to configure their respective radio protocol layers, including Radio Link Control (RLC), Medium Access Control (MAC), and physical layers. The radio channel is then established (circled step 5 in Figure 2b). Both the Node B 18a and the 25 mobile terminal UE confirm the operation, and the RNC acknowledges the operation to the SGSN (circled step 6 in Figure 2b). Last, the SGSN acknowledge the success of the operation to the mobile terminal using the CM protocol (circled step 7 in Figure 2b).

30 [0013] FIGURE 3 is a simplified representation of 3G GPRS user data protocol stack. User data (not illustrated) originating at the user terminal UE, which may, for example, be in Internet-Protocol (IP) form, is transported between the user

terminal UE and the SGSN using the Packet Data Compression Protocol (PDCP), which compresses the IP header in order to conserve some bandwidth. Between the RNC stack and the SGSN stack 330, and within the remainder of the core network 14 of FIGURE 1 up to the stack (not illustrated in FIGURE 3) of the GGSN of FIGURE 1, the user data is carried by GPRS Tunnel Protocol (GTP) that is implemented over UDP/IP represented in FIGURE 3.

[0014] FIGURE 4 is a conceptual representation of the 3G-WLAN loose coupling arrangement. In FIGURE 4, the Internet is illustrated as a cloud or circle 410, the public WLAN system as a cloud or circle 412, and the 3G core network, corresponding to 14 of FIGURE 1, is designated 414. Additionally, FIGURE 416 shows a representative web server 416 and a mobile user 420, corresponding to user 20 of FIGURE 1. In the prior-art scenario represented by FIGURE 4, user 420 is within the coverage region of public WLAN 412.

[0015] When the mobile user 420 of FIGURE 4 turns ON or energizes his mobile terminal so as to make a connection request illustrated as 430, the WLAN 412 detects this fact, and directs or redirects the connection request by way of a control path 428 through the Internet 410 toward an Authentication, Authorization, and Accounting (AAA) portion 424 of the core network 414. AAA 424 consults its Home Location Register 40 to determine if the user's data corresponds with that of an authorized user. After being authenticated, the AAA 424 authorizes the WLAN 412, to let the user data traffic through the access point. The user is then able to use the Internet, as by browsing, by way of a data path 426 communicating with web server 416.

[0016] In the communication domain, the protocols are split among three different planes, namely Management, Control and User. The Management protocols provide a way to configure

the equipments. The Control protocols provide a way to control/command dynamically the equipments (e.g. connection establishment). The user plane protocols provide a way to carry user data. The three protocol stacks may include common 5 protocols especially those relative to the transport of information. Figure 5 shows the Control plane protocol stack in case of the loose coupling model. The corresponding User plane protocol stack based on TCP/IP/Ethernet corresponds with the prior art and is not represented, but is simply IP over 10 Ethernet over the WLAN MAC (IEEE 802.11 in our example).

[0017] The control protocol stacks associated with the mobile terminal 420, the Access Point (AP) 412, and the AAA server 424 of FIGURE 4 are represented in FIGURE 5 as 520, 516, and 530, respectively. FIGURE 5 assumes IEEE 802.11 as the 15 radio interface between the mobile terminal 520 and the AP 516, but it can be also other WLAN protocols, such as the ETSI Hiperlan2 protocol. As illustrated in FIGURE 5, EAPOL information is transmitted between the mobile terminal 520 and the access point 516. EAPOL refers to EAP Over LAN, where the 20 LAN is the public WLAN. EAPOL is a standardized (IEEE 802.1X) protocol that is used to carry EAP packets within Ethernet frames. "EAP" stands for Extended Authentication Protocol, which is a protocol that can be used to carry any kind of authentication protocol. The authentication protocol may be, 25 for instance, the EAP AKA and EAP SIM that might be chosen by the 3GPP standard body. The DIAMETER protocol is a well-known IETF protocol (RFC 3588) used to control the authorization of the user by the AAA. It could be replaced by other equivalent protocols, such as the RADIUS protocol (RFC 2138). Once the 30 user 520 is authenticated, meaning that the AAA server 424 of FIGURE 4 retrieved a corresponding entry in its Home Location Register or subscription database 40 and the authentication protocol succeeded, the AAA server 424 (530 of FIGURE 5) sends

a DIAMETER message to the AP 412 (516 of FIGURE 5) in order to unblock the Ethernet traffic corresponding to the authenticated user 420 (520 of FIGURE 5).

5

### Summary of the Invention

**[0018]** The invention provides a method for implementing a tight coupling arrangement for allowing a mobile terminal to communicate with a communications network through first and second networks, wherein the first network comprises 10 a wireless local area network (WLAN) and the second network comprises a cellular network. The invention places certain radio network control protocols within the mobile terminal to advantageously allow a tight coupling arrangement to be implemented using a WLAN access point that has been configured 15 for a loose coupling arrangement. Specifically, the invention provides a method for implementing a tight coupling arrangement between first and second communications networks for allowing a mobile terminal to communicate with a third communications network through the first and second communications networks, 20 comprising the steps of: (a) providing, in the first communications network, an access point having protocol stacks adapted for operation within a loose coupling arrangement that allows the mobile terminal to communicate with the third communications network through the first communications network 25 without traversing through the second communications network; (b) providing, in the mobile terminal, radio network controller protocol stacks that directly interface with corresponding radio network controller protocol stacks in an access device of the second communications network; and (c) providing, in the 30 access device of the second communications network, the corresponding radio network controller protocol stacks for interfacing with the mobile terminal radio network controller protocol stacks, whereby the mobile terminal communicates

directly with the access device to traverse the second communications network to thereby communicate with the third communications network in a tight coupling arrangement.

5 [0019] In a particular mode of this aspect of the method of the invention, the step of communicating particular data includes the further step of communicating the particular data between the Serving GPRS Support Node and a server associated with the Internet. As a result, the user terminal can access or browse the Internet.

10 [0020] According to another aspect of the invention, a method for communicating between a mobile user terminal and a cellular network by way of a wireless LAN comprises the steps of providing at the user terminal a communication protocol for communicating with the wireless LAN, and providing at the user 15 terminal, and over the communication protocol, a standardized EAPOL protocol for packet frame communication. In addition, the method includes the provision, at the user terminal, and over the EAPOL protocol, of a standardized EAP protocol for communicating authorization control information, and further 20 providing, at the user terminal, and over the EAP protocol, a Radio Adaptation Layer protocol, which Radio Adaptation Layer protocol provides control of the radio communications. At the cellular network, a Serving GPRS Support Node is provided. An Internet protocol stack suited for communication over the 25 Internet is associated with the Serving GPRS Support Node. A standardized EAP protocol for communicating authorization control information over the Internet is provided over the Internet protocol stack. A Radio Adaptation Layer protocol, which Radio Adaptation Layer protocol provides control of the 30 radio communications, is provided over the EAP protocol at the Serving GPRS Support Node. Communications are between the wireless LAN and the cellular system by way of the Internet. Finally, communications are provided between the user terminal

and the wireless LAN by use of the Radio Adaptation Layer.

**[0021]** In a particular mode of this other method, the step of providing, at the cellular network, a Serving GPRS Support Node, and associating with the Serving GPRS Support Node an Internet protocol stack suited for communication over the Internet, includes the step of providing at least TCP/IP protocol over a physical layer, and providing Diameter protocol over the TCP/IP protocol.

10 Brief Description of the Drawing

**[0022]** FIGURE 1 is a simplified functional block diagram or architecture of a prior art 3G GPRS digital cellular telecommunications system;

15 FIGURE 2a is a simplified representation of 3G GPRS protocol stacks of various portions of the system of FIGURE 1, and FIGURE 2b illustrates a sequence of the successive protocol operations for opening a user data channel between the various portions of FIGURE 1;

20 FIGURE 3 is a simplified representation of 3G GPRS user data protocol stack;

FIGURE 4 FIGURE 4 is a conceptual representation of prior-art 3G-WLAN loose coupling;

25 FIGURE 5 represents the control protocol stacks associated with the mobile terminal, the Access Point (AP), and the AAA server of FIGURE 4;

FIGURE 6 is a simplified representation of the flow of control information and data according to an aspect of the invention; and

30 FIGURES 7 and 8 illustrate the control and data protocol stacks according to an embodiment of the invention, for enabling the connectivity functions expressed in FIGURE 6.

Description of the Invention

**[0023]** The prior art presented above shows that for WLAN -cellular network inter-connection, the loose coupling model is simple, but the relative simplicity is associated with some undesirable limitations or problems. These include the fact that the authentication protocol is new (IEEE 802.1x, EAP, ...) and consequently requires a new equipment (AAA server 424 in figure 4) inside the cellular network, and new interfaces with legacy equipments (HLR 40 in figure 4), all compliant with the new paradigm. In addition, a mobile terminal equipment like a cellular phone must include two different protocol stacks, depending upon whether the attachment is done through the conventional cellular radio interface (22 in FIGURE 1) or through the WLAN radio interface (FIGURE 7). Further, the Loose coupling model prevents the access of cellular network specific services like SMS (Short Messaging System).

**[0024]** The invention implements a tight coupling model in which, as in the loose coupling model, the mobile terminal UE is attached or communicates through a WLAN as an access point. In the exemplary embodiment, the WLAN communicates with the cellular network through the Internet, however, it is to be understood that the WLAN may also communicate with the cellular network through other suitable communication networks. The protocol stack in a WLAN used in a system according to an aspect of the invention has a protocol stack which is (or at least can be) identical to that used in the case of loose coupling, and therefore a WLAN which is (or can be) used for the loose coupling model can also handle tight coupling traffic without any modification. A further advantage which can be achieved in the invention, but which is not found in the prior art loose coupling model, is that the signaling protocols in the user terminal and the SGSN, which are used to

manage user data connections and to manage mobility (including authorization), are those already standardized by cellular network specifications such as the CM (Connection Management) and the GMM (GPRS Mobility Management) protocol. According to 5 a further aspect of the invention, in order to avoid the complexity of the radio control protocols (RRC in figure 2a) linked with the cellular network radio interface (22 in figure 1) technology and its complete redesign, a new simplified protocol called RAL (Radio Adaptation Layer) is defined. The 10 RAL layer is a subset of the known RANAP protocol and includes the commands for establishing and managing, i.e., setting up, a connection. This new protocol is very similar to the RANAP (figure 2a) protocol, and thus is readily implemented. The RAL protocol layer is also similarly implemented in the SGSN.

15 According to one aspect of the invention, and in contradistinction to the loose coupling scenario set forth in conjunction with FIGURES 1, 2a, 2b, 3, 4, and 5, connection requests from the SGSN to the mobile terminal UE by mean of this RAL protocol directly provide QOS parameters to the mobile 20 terminal, and the mobile terminal translates these parameters into radio dependent parameters. Also, as described below in conjunction with FIGURE 8, the transport of user data is compliant with the conventional model, described above in conjunction with FIGURE 3, in which the transport protocol GTP- 25 U is used between the SGSN and the mobile terminal UE, thereby implying no change in the SGSN.

[0025] FIGURE 6 is a simplified representation of the flow of control information and data according to an aspect of the invention. In FIGURE 6, elements corresponding to those of 30 FIGURE 4 are designated by like reference alphanumerics. As illustrated in FIGURE 6, the control information, including the request for access by the mobile terminal 620, flows between the mobile terminal 620 and the core network 630 of a cellular

communications system 600 by means of a control path 628, which passes through the public WLAN 412 and the Internet 410. User Data flowing between mobile terminal 620 and a remote web server illustrated as 416 flows by a data path 626a through the 5 WLAN 412, Internet 410, and core network 630, and then by a further path 626b between core network 630 and web server 416, again by way of Internet 410.

**[0026]** FIGURES 7 and 8 illustrate the control and data protocol stacks, respectively, according to an embodiment 10 of the invention, for enabling the connectivity functions expressed in FIGURE 6. In FIGURE 7, 720 designates the control protocol stack for the mobile user UE (620 of FIGURE 6), 730 the control protocol stack for the SGSN (630 of FIGURE 6), and 760 the control stack for the access point (AP). The protocol 15 stack of access point AP of FIGURE 7 is exactly the same as that of a prior-art wireless LAN used in the loose coupling model. Comparison of the stacks of FIGURE 7 with those of the loose coupling solution, as illustrated in FIGURE 2a, shows that all the protocols related to the radio link, namely stacks 20 250 and 252, have disappeared. The 3GPP UMTS Radio Access Network Adaptation Protocol (RANAP) used in the arrangement of FIGURE 2a is replaced in FIGURE 7 by Radio Adaptation Layer Protocol (RALP), which is a subset of RANAP and implemented in the mobile terminal and SGSN, plus some extra commands related 25 to encryption.

**[0027]** Most of the RALP messages are based on RANALP. Therefore, the RALP header contains a value that indicates the format of the message. The general RALP message format includes (a) version number, (b) integrity check information 30 (only when integrity protection is required), and (c) remaining information elements (IE).

**[0028]** Thus, the Radio Adaptation Layer (RAL) entity of UE 720 and SGSN 730 performs the functions of the RANAP. The

RALP control information is transmitted between user terminal UE 720 of FIGURE 7 and SGSN 730 of FIGURE 7 by way of access point (AP) 760, but the RALP control information is not processed by the access point, so essentially flows directly 5 between the UE and the SGSN, as suggested by path 761.

[0029] In FIGURE 7, note that the access point (AP) 760 is configured, or has protocol stacks, exactly as set forth in conjunction with the "loose coupling" solution of FIGURE 5. More particularly, the access point (AP) 516 of FIGURE 5 10 communicates with the mobile terminal with physical radio equipment and the EAPOL/WLAN protocol, corresponding to the left portion of AP stack 760 of FIGURE 7. Similarly, access point 516 of FIGURE 5 communicates with the Authentication, Authorization, and Accounting (AAA) portion 530 of the core 15 network 414 of FIGURE 4 by means of a physical level (not expressly illustrated) together with Diameter/TCP-IP protocols, which is identical to the protocol stack represented on the right side of the AP stack 760 of FIGURE 7. Also note that the authentication protocol and the other control protocols set 20 forth in FIGURE 7 are those already specified by the 3G cellular specification document, and more particularly by the 3GPP UMTS: connection management SM and SMS specifications and GMM as introduced in the first section of that document. Consequently, a wireless LAN access point can operate in the 25 inventive arrangement without any substantive modification necessary for implementing a tight coupling arrangement, which is a major advantage.

[0030] When a mobile terminal UE moves into the coverage area of a wireless LAN, or is initially switched ON in 30 such a coverage area, it first establishes an EAP connection with a remote server (SGSN in this case) in conformance with the procedure discussed in relation to the loose coupling scenarios. The access point authorizes or carries only the

control or EAP traffic. When the UE is authenticated according to the relevant protocol, such as 3G GPRS protocol (GMM), the SGSN 730 authorizes the user's traffic by sending a DIAMETER message, known in the art, to the access point (AP) 760, using 5 the procedure followed by the AAA server 424 in the loose coupling scenario.

[0031] When the user terminal UE 720 requests connection by means of the connection management (CM) protocol, the SGSN 730 processes the request and, using the RALP protocol, 10 requests that the mobile unit establish the radio part of the connection, by which data can be communicated. In response to the request, the user terminal UE 720 translates the request into parameters which are used to establish the corresponding radio connection, ultimately completed by way of 15 the WLAN protocol.

[0032] FIGURE 8 illustrates the data protocol stacks for the user plane for implementing the tight coupling arrangement according to the present invention. Comparing the stacks of FIGURE 8 with the 3G GPRS stacks of FIGURE 3, it can 20 be seen that all the protocols relating to the GPRS radio network are absent. The illustrated data stacks for the user terminal, the access point, and the SGSN are designated 820, 860, and 830, respectively. A notable feature of the present invention is that the radio control functions of the RNC are 25 embedded in the control stack of the mobile terminal by virtue of the abovedescribed protocol structure.

[0033] In the data stack arrangement of FIGURE 8, the GPRS Tunneling Protocol (GTP) is "directly" connected between the user terminal UE 820 and the SGSN 830 as indicated by line 30 865. The GTP protocol is carried over UDP/IP as specified by the 3GPP standard. GTP encapsulates user data packets, such as, for example, IP datagrams. The user data packets are carried transparently by the access point AP 860, and by the

SGSN up to GGSN (FIGURE 1) that performs the function of an IP router.

5 [0034] The "tight" communication system according to the invention provides mobility for the user terminal, which is inherent in the GMM protocol. It is also inherently capable of full 3G GPRS service, full accounting, and security, all inherent in the GMM protocol.

10 [0035] Among the advantages of various embodiments of the invention are that the coupling is realized or accomplished through an Internet Protocol (IP) based network, which may be the Internet, and that the solution is compatible, at least as to the WLAN, with the loose coupling solution as currently envisaged by 3GPP SA2, IEEE 802.11i or ETSI/BRAN.

15 [0036] Thus, a method according to an aspect of the invention is for communicating data between a mobile terminal (620) and a server (630; 416). The method comprises the steps of communicating from the mobile terminal (620) to a wireless LAN access point (412) a request for data channel access to the Internet (410), and routing the request (628) for a data channel from the wireless LAN access point (412), by way of the Internet (410), to a Serving GPRS Support Node (630) of a cellular communication system (600). The method also includes the step of communicating authorization (628) for the data channel from the Serving GPRS Support Node (630) of the cellular communications system (600) to the wireless LAN access point (412) by way of the Internet (410). In response to the authorization, a data channel is opened (627, 626a) between the user terminal (620) and the Serving GPRS Support Node (630) by way of the wireless LAN (412) and the Internet (410).  
20  
25  
30 Particular data is communicated between the user terminal (620) and the Serving GPRS Support Node (630) of the cellular communication system by way of the data channel wireless LAN access point (412) and the Internet (410).

[0037] In a particular mode of this aspect of the method of the invention, the step of communicating particular data includes the further step of communicating the particular data between the Serving GPRS Support Node (630) and a server 5 (416) associated with the Internet. As a result, the user terminal can access or browse the Internet.

[0038] According to another aspect of the invention, a method for communicating between a mobile user terminal (620) and a cellular network (600) by way of a wireless LAN (412) 10 comprises the steps of providing at the user terminal (620) a communication protocol (WLANMAC and Radio) for communicating with the wireless LAN (412), and providing at the user terminal (620), and over the communication protocol (WLANMAC and Radio), a standardized EAPOL protocol for packet frame communication. 15 In addition, the method includes the provision, at the user terminal, and over the EAPOL protocol, of a standardized EAP protocol for communicating authorization control information, and further providing, at the user terminal, and over the EAP protocol, a Radio Adaptation Layer protocol, which Radio 20 Adaptation Layer protocol provides control of the radio communications. At the cellular network (600), a Serving GPRS Support Node (630) is provided. An Internet protocol stack (730, TCP/IP) suited for communication over the Internet (410) is associated with the Serving GPRS Support Node (630). A 25 standardized EAP protocol for communicating authorization control information over the Internet (410) is provided over the Internet protocol stack (730, TCP/IP). A Radio Adaptation Layer protocol (RAL), which Radio Adaptation Layer protocol provides control of the radio communications, is provided over 30 the EAP protocol at the Serving GPRS Support Node (630). Communications are between the wireless LAN (412) and the cellular system (600) by way of the Internet (410). Finally, communications are provided between the user terminal (620) and

the wireless LAN (412) by use of the Radio Adaptation Layer (RAL).

[0039] In a particular mode of this other method, the step of providing, at the cellular network (600), a Serving GPRS Support Node (630), and associating with the Serving GPRS Support Node (630) an Internet protocol stack (Diameter, TCP/IP) suited for communication over the Internet (410), includes the step of providing at least TCP/IP protocol over a physical layer, and providing Diameter protocol over the TCP/IP protocol.

## CLAIMS

1. A method for implementing a tight coupling arrangement between first and second communications networks for allowing a mobile terminal to communicate with a third communications network through the first and second communications networks, said method comprising the steps of:

(a) providing, in the first communications network, an access point having protocol stacks adapted for operation within a loose coupling arrangement that allows the mobile terminal to communicate with the third communications network through the first communications network without traversing through the second communications network;

(b) providing, in the mobile terminal, radio network controller protocol stacks that directly interface with corresponding radio network controller protocol stacks in an access device of the second communications network; and

(c) providing, in the access device of the second communications network, the corresponding radio network controller protocol stacks for interfacing with the mobile terminal radio network controller protocol stacks, whereby the mobile terminal is able to interface with the access device to traverse the second communications network to thereby communicate with the third communications network in a tight coupling arrangement.

2. The method according to claim 1, wherein the first communications network comprises a wireless local area network in accordance with IEEE 802 standards, and the second communications network comprises a cellular network.

3. The method according to claim 2, wherein the access device of the second communications network comprises a serving GPRS support node (SGSN).

5

4. The method according to claim 3, wherein step (b) includes the step of providing, in the access point, a control data protocol stack that includes a subset of the RANAP protocol for establishing and setting up a connection.

10

5. The method according to claim 4, wherein step (a) includes the step of providing in the access point a protocol stack comprising Radio/WLAN MAC/EAPOL/Diameter/TCP protocols.

15

6. The method according to claim 4, wherein step (c) includes the step of providing in the access device of the second communications network a control data protocol stack that includes the subset of the RANAP protocol for establishing and setting up the connection.

20

7. The method according to claim 3, wherein step (b) includes the step of providing, in the mobile terminal, a user data protocol stack that includes GTP-U/UDP/IP/WLAN MAC protocols.

25

8. The method according to claim 7, wherein step (a) includes the step of providing, in the access point, a user data protocol stack that includes Radio/WLAN MAC/Link/Physical Layer protocols.

30

9. The method according to claim 7, wherein step (c) includes the step of providing, in the access device of the second communications network, a user data protocol stack that 5 includes GTU-U/UDP/IP/Link/Physical layer protocols.

10. A mobile terminal for communicating with a wireless local area network (WLAN) for accessing a communications network through the WLAN and a cellular network, 10 said mobile terminal comprising:

means for communicating control data and user data with a WLAN access point configured for loose coupling between the WLAN and the cellular network; and

15 radio network controller protocol stacks for enabling the mobile terminal to communicate with the communications network through the WLAN and the cellular network in a tight coupling arrangement.

11. The mobile terminal according to claim 10, 20 wherein the radio network controller protocol stack includes a control data protocol stack that includes RAL/EAP/EAPOL/WLANMAC protocol stack for establishing a connection between the mobile terminal and the WLAN and the cellular network.

25 12. The mobile terminal according to claim 11, wherein the RAL protocol comprises a subset of the RANAP protocol for establishing the connection.

13. The mobile terminal according to claim 11, 30 wherein the radio network controller protocol stack includes a user data protocol stack that includes GTPU/UDPIP/WLANMAC protocols.

1/7





FIG. 1  
PRIOR ART

10



**FIG. 2a**  
PRIOR ART

3/7





FIG. 2b  
PRIOR ART



**FIG. 3**  
PRIOR ART

5/7




FIG. 4  
PRIOR ART





FIG. 5



6/7




FIG. 7

7/7




FIG. 8