

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

(43) International Publication Date 24 June 2010 (24.06.2010)

(10) International Publication Number
WO 2010/070325 A1

(51) International Patent Classification: C07C 67/60 (2006.01) C07C 69/54 (2006.01)

(21) International Application Number: PCT/GB2009/051693

(22) International Filing Date: 11 December 2009 (11.12.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0823075.7	18 December 2008 (18.12.2008)	GB
0910498.5	18 June 2009 (18.06.2009)	GB

(71) Applicant (for all designated States except US): LUCITE INTERNATIONAL UK LIMITED [GB/GB]; Queens Gate, 15-17 Queens Terrace, Southampton, Hampshire SO14 3BP (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JOHNSON, David, William [GB/GB]; Wilton Centre, Wilton, Redcar TS10 4RF (GB). MORRIS, Trevor, Huw [GB/GB]; Wilton Centre, Wilton, Redcar TS10 4RF (GB).

(74) Agent: APPLEYARD LEES; 15 Clare Road, Halifax, Yorkshire HX1 2HY (GB).

(54) Title: METHYL METHACRYLATE PURIFICATION PROCESS

Figure 1

$$\text{R}^5\text{X} \text{---} \left(\text{C}_2\text{H}_4 \right)_m \text{---} \text{X} \text{---} \text{R}^6 \quad (\text{I})$$

(57) Abstract: A process for purifying methyl methacrylate (MMA) is described. The process involves contacting liquid MMA having impurities therein with a sulphonic acid resin, in the presence of formaldehyde or a suitable source of methylene or ethylene of formula I. R⁵ and R⁶ are independently selected from C₁-C₁₂ hydrocarbons or H; X is either O or S; n is an integer from, 1 to 100; and m is 1 or 2: The compound of formula I may be suitable source of formaldehyde.

METHYL METHACRYLATE PURIFICATION PROCESS

The present invention relates to a purification process, particularly to a process for purifying methyl 5 methacrylate (MMA).

MMA is a well known chemical substance and has many uses, but largely it is used as a monomer in the production of poly-methylmethacrylate (PMMA). PMMA is often formed in 10 thin sheets which can be moulded into a variety of shapes as required by a particular use.

It is important when preparing PMMA, that the MMA used is of the highest purity because even low levels of impurity 15 can lead to a PMMA product which has a cloudy or dull appearance or is discoloured. Also, low levels of impurity in the MMA can lead to a change in the structural properties of the PMMA product which can have undesired effects. It is therefore important to be able to provide 20 MMA, the monomer for PMMA, with a high degree of purity to try and reduce the occurrence of these problems.

MMA may be produced in many ways. For example, reaction of acetone cyanohydrin, methanol and concentrated 25 sulphuric acid; oxidation of tertiary butyl alcohol to methacrolein and then to methacrylic acid followed by esterification with methanol; alternatively catalysed reactions as disclosed in EP 1,073,517. Such reactions and many others known in the art provide a stream of MMA 30 that commonly contains impurities therein which can cause problems such as those discussed above when the MMA is polymerised to form PMMA. Consequently, it is usual to attempt to purify the MMA stream before polymerisation.

It is known to separate impurities having boiling points which are significantly different to the MMA by distillation. However, such a separation method is 5 difficult to achieve where the impurities have a similar boiling point to the MMA.

Japanese patent 58-183641 discloses the use of an acid catalyst to treat impurities in crude methyl methacrylate.

10

Japanese patent application 63-127952 teaches the use of sulfonic acid group containing compounds to treat high purity methyl methacrylate.

15

US Patent 4,625,059, to Mitsubishi Petrochemical shows the use of acid ion exchange resin fixed beds to remove impurities from crude MMA.

20


Therefore, crude MMA made by a number of process routes contains a wide range of impurities which are difficult to remove by distillation. MMA produced by the condensation of formaldehyde with methyl propionate contains additionally other as yet undefined impurities such as colour forming compounds which are not disclosed in prior 25 art MMA production processes.

It is an object of aspects of the present invention to provide a solution to the removal of these or other impurities by purification of MMA.

30

According to a first aspect of the present invention there is provided a process for purifying methyl methacrylate (MMA) comprising contacting liquid MMA having impurities

therein with a sulphonic acid resin, in the presence of formaldehyde or a suitable source of methylene or ethylene of formula I as defined below:



5 where R^5 and R^6 are independently selected from $\text{C}_1\text{-C}_{12}$ hydrocarbons, preferably, $\text{C}_1\text{-C}_{12}$ alkyl, alkenyl or aryl as defined herein, or H, more preferably, $\text{C}_1\text{-C}_{10}$ alkyl, or H, most preferably, $\text{C}_1\text{-C}_6$ alkyl or H, especially, methyl or H;

10 X is either O or S, preferably, O;

n is an integer from 1 to 100, preferably, 1 to 10, more preferably 1 to 5, especially, 1-3;

and m is 1 or 2, preferably 1.

15 In a particularly preferred embodiment the compound of formula I is derived from formaldehyde in the presence of methanol and/or water. In such a case, the compound of formula I may be defined as a suitable source of formaldehyde.

20 For the avoidance of doubt, a suitable source of formaldehyde includes any equilibrium composition which may provide a source of formaldehyde. Examples of such include but are not restricted to methylal (1,1 dimethoxymethane), polyoxymethylenes $-\text{(CH}_2\text{-O)}_i-$ wherein i=1 to 100 formalin (formaldehyde, methanol, water) and other equilibrium compositions such as a mixture of formaldehyde, methanol and methyl propionate.

Typically, the polyoxymethylenes are higher formals of formaldehyde and methanol $\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_i\text{-CH}_3$ ("formal-i"), wherein $i=1$ to 100, preferably, 1-5, especially 1-3, or other polyoxymethylenes with at least one non methyl terminal group. Therefore, the source of formaldehyde may also be a polyoxymethylene of formula $\text{R}_1\text{-O-}(\text{CH}_2\text{-O})_i\text{R}_2$, where R_1 and R_2 may be the same or different groups and at least one is selected from a $\text{C}_2\text{-C}_{10}$ alkyl group, for instance R_1 = isobutyl and R_2 = methyl.

Preferably, the formaldehyde or the amount of formaldehyde that can be liberated from a suitable source of formaldehyde is present in an amount between 0.01 and 0.1 weight percent relative to the weight of liquid MMA.

Preferably, the suitable source of formaldehyde is selected from 1,1 dimethoxymethane, higher formals of formaldehyde and methanol for example $\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_i\text{-CH}_3$ where $i=2$ or more as set out above, formalin or a mixture comprising formaldehyde, methanol and methyl propionate.

Preferably, by the term formalin is meant a mixture of formaldehyde:methanol:water in the ratio 25 to 65%: 0.01 to 25%: 25 to 70% by weight. More preferably, by the term formalin is meant a mixture of formaldehyde:methanol:water in the ratio 30 to 60%: 0.03 to 20%: 35 to 60% by weight. Most preferably, by the term formalin is meant a mixture of formaldehyde:methanol:water in the ratio 35 to 55%: 0.05 to 18%: 42 to 53% by weight.

Preferably, the mixture comprising formaldehyde, methanol and methyl propionate contains less than 5% water by weight. More preferably, the mixture comprising formaldehyde, methanol and methyl propionate contains less than 1% water by weight. Most preferably, the mixture comprising formaldehyde, methanol and methyl propionate contains 0.1 to 0.5% water by weight.

Preferably, the suitable source of formaldehyde has a boiling point in the range of 69 to 73°C at 0.75 bar absolute.

Preferably, the formaldehyde or source thereof is mixed with the impure liquid MMA prior to contact with the sulphonic acid resin. Typically, in a continuous or semi-continuous process, an impure liquid MMA stream is mixed with a stream containing the formaldehyde or source thereof to form a combined liquid stream prior to contact with the sulphonic acid resin. The formaldehyde is therefore present in an amount between 0.01 and 0.1 weight percent in the combined liquid stream.

Alternatively, or additionally the formaldehyde source may be present as an impurity in the MMA, preferably as a close boiling impurity prior to contact with the sulphonic acid resin. In such cases the passing of the impure MMA over the ion exchange resin bed acts to remove or reduce the concentration of the formaldehyde source and or change its composition to a heavy or a light component which can be readily separated from MMA by distillation.

Preferably the close boiling impurity present as an impurity in the MMA is formal-2 ($\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_2\text{-CH}_3$).

Preferably the light component with respect to separation from MMA is dimethoxymethane. Preferably the dimethoxymethane is separated from the MMA by 5 distillation.

Preferably, the purification process of the invention is performed at a temperature between 25 and 100°C. More preferably, the process is carried out at a temperature 10 between 40 and 90°C. More preferably, the process is carried out at a temperature between 50 and 80°C. Most preferably, the process is carried out at a temperature between 50 and 70°C.

15 Preferably, the sulphonic acid resin comprises a packed bed. Preferably, the sulphonic acid resin comprises a strongly acidic, macroporous, polymer based resin. Most preferably, the sulphonic acid resin comprises a crosslinked polystyrene resin in spherical bead form with 20 bead size 0.4 to 1.64mm, with between 0.5 and 3.0 equivalents per litre of sulphonic acid groups (preferably between 0.7 and 2.5) with a large pore structure with mean pore diameter between 15nm and 90nm (preferably between 20nm and 70nm), surface area between 15m²g⁻¹ and 100 m²g⁻¹ 25 (preferably between 20m²g⁻¹ 80m²g⁻¹) and a pore volume measured by the extent of water retention per unit of wet resin of between 30 and 80% (preferably 40-70%). Preferably the acidic ion exchange resin is a macroreticular resin.

30

Preferably, at least one carboxylic acid ester is also present in the purification process. Preferably, the or each carboxylic acid ester is selected from the methyl,

ethyl or propyl ester of any straight or branched C₂ to C₆ carboxylic acid. More preferably, the or each at least one carboxylic acid is selected from the methyl or ethyl ester of any branched or unbranched C₂ to C₄ carboxylic acid. Examples of suitable carboxylic acid esters include but are not restricted to methyl propionate, ethyl propionate, propyl propionate, methyl butanoate, methyl isobutyrate, ethyl butanoate, propyl butanoate, butyl butanoate. In a preferred embodiment, methyl propionate or methyl isobutyrate are also present in the purification process.

Typically, in a continuous or semi-continuous process the at least one carboxylic acid ester is already present in the impure liquid MMA stream prior to contact with the sulphonic acid resin. Typically, therefore, in such embodiments, the at least one carboxylic acid ester forms part of the combined liquid stream.

Typically, the impurities have a boiling point which renders separation by distillation ineffective. Typically, the impurities have a boiling point within 15°C of MMA. More typically, the impurities have a boiling point within 10°C of MMA. Most typically, the impurities have a boiling point within 5°C of MMA. Generally, the impurities have a boiling point which is approximately the same as MMA i.e. within 1 or 2°C. Impurities may have boiling points as pure components which are more than 15°C of MMA if they exhibit non ideal distillation behaviour, in combination with either MMA or with one or more impurities or with MMA and another impurity such physical effects making the impurity very difficult to separate from MMA by distillation. Examples of such physical

effects are the formation of high or low boiling azeotropes.

The invention has been found to be particularly useful in
5 the removal of several impurities in the impure MMA liquid. It has been found that the impurities may comprise isobutyraldehyde either as isobutyraldehyde or in a compound which regenerates isobutyraldehyde when exposed to the sulphonic acid ion exchange resin. Examples of
10 such compounds include the mono or di-acetals of isobutyraldehyde with a C₁ to C₆ branched or non-branched alcohol, in particular 2,2-dimethoxypropane, and methallyl alcohol.

15 Removal of isobutyraldehyde using the formaldehyde/resin combination is advantageous even though isobutyraldehyde would separate from the MMA as a lower boiling impurity. Removing isobutyraldehyde in the low boiling impurity (lights) column runs the risk of polymerisation initiation
20 by isobutyraldehyde/oxygen in the lights column overheads which are predominantly MMA and have to be fed with oxygen for the polymerisation stabilisers to be effective.

In addition, recycling of isobutyraldehyde causes slow
25 conversion to isobutanol over the catalyst. Isobutanol escapes into the MMA pure product both reducing the specification and also providing a problem with thick sheet as it reacts with polymerisation initiators, thereby increasing the demand for such initiators which are
30 invariably coloured in both their unreacted and reacted (with isobutanol) forms. This is an issue with aquarium grades and some others where very low levels of initiators are demanded.

Further impurities that have been advantageously removed include optionally substituted C₄-C₂₀ dienes. The invention has been found to be particularly useful for such dienes.

5 Useful substituted dienes that can be removed are C₁-₆ mono-tetra alkyl C₄-C₂₀ dienes, such as C₄-C₈ dienes, for example, mono or dialkyl hexadienes. Examples of dienes have been found to include but are not restricted to any of the following: 2,5-dimethyl-2,4-hexadiene; 2,5-dimethyl-1,5-hexadiene, 2-methyl-1,5-hexadiene; trans 2-methyl-2,4-hexadiene; cis 2-methyl-2,4-hexadiene; 2-methyl-3,5-hexadiene; 2-methyl-1,3-hexadiene; 2,5-dimethyl-1,3-hexadiene and 1,6-heptadiene.

15 In addition, the impurities may also typically comprise optionally substituted C₆-C₂₀ trienes. Examples of trienes include but are not restricted to any of the following: heptatriene, cycloheptatriene.

20 The invention has been found to be especially efficient for C₄-C₂₀ dienes or C₆-C₂₀ trienes with one or more substituted, preferably, alkyl, more preferably, C₁-₆ alkyl substituted, internal enyl carbons or di-substituted, preferably, alkyl, more preferably, C₁-₆ alkyl substituted, 25 terminal enyl carbons which enyl carbons are thereby capable of forming tertiary carbocations. Most preferably, the invention is for the removal of C₄-C₂₀ dienes, optionally, substituted as defined above. Particularly preferred dienes for removal by the present invention are: 30 trans 2-methyl-2,4-hexadiene; cis 2-methyl-2,4-hexadiene; 2-methyl-3,5-hexadiene; 2-methyl-1,3-hexadiene; 2,5-dimethyl-1,3-hexadiene and 1,6-heptadiene, in particular

trans 2-methyl-2,4-hexadiene and cis 2-methyl-2,4-hexadiene.

Other impurities that may be removed by the practice of
5 the present invention also typically comprise optionally
substituted unsaturated aldehydes and ketones. Examples of
such aldehyde or ketone compounds include $R'C=OR''$ wherein
R' can be hydrogen, optionally substituted alkyl, alkenyl
or aryl more preferably, C_{1-6} alkyl, C_{1-6} alkenyl or aryl
10 and R'' can be optionally substituted alkyl, alkenyl or
aryl, more preferably, C_{1-6} alkyl, C_{1-6} alkenyl or phenyl.

In addition, 2-methylene-3-buten-al may also be present
and removed by the process of the invention.
15 Advantageously, this impurity may otherwise be colour
forming in the MMA.

Suitable further impurities include: divinyl ketone, ethyl
vinyl ketone, diethyl ketone, ethyl isopropenyl ketone, 3-
20 methylene 1-hexen-4-one, methacrolein, isobutanol,
toluene, and pentenals such as 3-pentenal. Preferred
further impurities which can be removed by the practice of
the present invention are ethyl vinyl ketone and divinyl
ketone.


25

Accordingly, the present invention is particularly
beneficial for the removal of trans 2-methyl-2,4-
hexadiene; cis 2-methyl-2,4-hexadiene; ethyl vinyl ketone
and divinyl ketone.

30

A suitable process for preparing the MMA prior to
purification by contact with formaldehyde or a source of
methylenes or ethylenes comprises contacting methyl

propionate with a suitable source of methylene of formula I as defined below:



5 where R^5 and R^6 are independently selected from $\text{C}_1\text{-C}_{12}$ hydrocarbons, preferably, $\text{C}_1\text{-C}_{12}$ alkyl, alkenyl or aryl as defined herein, or H, more preferably, $\text{C}_1\text{-C}_{10}$ alkyl, or H, most preferably, $\text{C}_1\text{-C}_6$ alkyl or H, especially, methyl or H;

10 X is either O or S, preferably, O;

n is an integer from 1 to 100, preferably, 1 to 10, more preferably 1 to 5, especially, 1-3;

and m is 1;

15 in the presence of a suitable catalyst, and optionally in the presence of an alcohol.

The process may be carried out in the presence of at least one suitable stabiliser. Preferably, the at least one stabiliser may be selected from hydroquinone, p-methoxyphenol, Topanol-A (2-t-butyl-4,6-dimethylphenol) or 20 phenothiazine.

The term "alkyl" when used herein, means unless otherwise indicated, C_1 to C_{10} alkyl and alkyl includes methyl, ethyl, propyl, butyl, pentyl, hexyl, and heptyl groups.

25 Unless otherwise specified, alkyl groups may, when there is a sufficient number of carbon atoms, be linear or branched (particularly preferred branched groups include

t-butyl and isopropyl), be saturated, be cyclic, acyclic or part cyclic/acyclic, be unsubstituted, substituted or terminated by one or more substituents selected from halo, cyano, nitro, OR¹⁹, OC(O)R²⁰, C(O)R²¹, C(O)OR²², NR²³R²⁴, 5 C(O)NR²⁵R²⁶, SR²⁹, C(O)SR³⁰, C(S)NR²⁷R²⁸, unsubstituted or substituted aryl, or unsubstituted or substituted Het, wherein R¹⁹ to R³⁰ each independently represent hydrogen, halo, unsubstituted or substituted aryl or unsubstituted or substituted alkyl, or, in the case of R²¹, halo, nitro, 10 cyano and amino and/or be interrupted by one or more (preferably less than 4) oxygen, sulphur, silicon atoms, or by silano or dialkylsilicon groups, or mixtures thereof.

15 The term "Ar" or "aryl" when used herein, includes five-to-ten-membered, preferably five to eight membered, carbocyclic aromatic or pseudo aromatic groups, such as phenyl, cyclopentadienyl and indenyl anions and naphthyl, which groups may be unsubstituted or substituted with one 20 or more substituents selected from unsubstituted or substituted aryl, alkyl (which group may itself be unsubstituted or substituted or terminated as defined herein), Het (which group may itself be unsubstituted or substituted or terminated as defined herein), halo, cyano, 25 nitro, OR¹⁹, OC(O)R²⁰, C(O)R²¹, C(O)OR²², NR²³R²⁴, C(O)NR²⁵R²⁶, SR²⁹, C(O)SR³⁰ or C(S)NR²⁷R²⁸ wherein R¹⁹ to R³⁰ each independently represent hydrogen, unsubstituted or substituted aryl or alkyl (which alkyl group may itself be unsubstituted or substituted or terminated as defined 30 herein), or, in the case of R²¹, halo, nitro, cyano or amino.

The term "alkenyl" when used herein, means C₂ to C₁₀ alkenyl and includes ethenyl, propenyl, butenyl, pentenyl, and hexenyl groups. Unless otherwise specified, alkenyl groups may, when there is a sufficient number of carbon atoms, be linear or branched, be cyclic, acyclic or part cyclic/acyclic, be unsubstituted, substituted or terminated by one or more substituents selected from halo, cyano, nitro, OR¹⁹, OC(O)R²⁰, C(O)R²¹, C(O)OR²², NR²³R²⁴, C(O)NR²⁵R²⁶, SR²⁹, C(O)SR³⁰, C(S)NR²⁷R²⁸, unsubstituted or substituted aryl, or unsubstituted or substituted Het, wherein R¹⁹ to R³⁰ are defined as for alkyl above and/or be interrupted by one or more (preferably less than 4) oxygen, sulphur, silicon atoms, or by silano or dialkylsilicon groups, or mixtures thereof.

15

Halo groups with which the above-mentioned groups may be substituted or terminated include fluoro, chloro, bromo and iodo.

20

The term "Het", when used herein, includes four- to twelve-membered, preferably four- to ten-membered ring systems, which rings contain one or more heteroatoms selected from nitrogen, oxygen, sulfur and mixtures thereof, and which rings contain no, one or more double bonds or may be non-aromatic, partly aromatic or wholly aromatic in character. The ring systems may be monocyclic, bicyclic or fused. Each "Het" group identified herein may be unsubstituted or substituted by one or more substituents selected from halo, cyano, nitro, oxo, alkyl (which alkyl group may itself be unsubstituted or substituted or terminated as defined herein) -OR¹⁹, -

OC(O)R²⁰, -C(O)R²¹, -C(O)OR²², -N(R²³)R²⁴, -C(O)N(R²⁵)R²⁶, -SR²⁹, -C(O)SR³⁰ or -C(S)N(R²⁷)R²⁸ wherein R¹⁹ to R³⁰ each independently represent hydrogen, unsubstituted or substituted aryl or alkyl (which alkyl group itself may be unsubstituted or substituted or terminated as defined herein) or, in the case of R²¹, halo, nitro, amino or cyano. The term "Het" thus includes groups such as optionally substituted azetidinyl, pyrrolidinyl, imidazolyl, indolyl, furanyl, oxazolyl, isoxazolyl, 10 oxadiazolyl, thiazolyl, thiadiazolyl, triazolyl, oxatriazolyl, thiatriazolyl, pyridazinyl, morpholinyl, pyrimidinyl, pyrazinyl, quinolinyl, isoquinolinyl, piperidinyl, pyrazolyl and piperazinyl. Substitution at Het may be at a carbon atom of the Het ring or, where appropriate, at one or more of the heteroatoms.

"Het" groups may also be in the form of an N oxide.


The term "hetero" as mentioned herein means nitrogen, 20 oxygen, sulfur or mixtures thereof.

In a continuous process, after a period of, say, a few months, the efficacy of a sulphonic acid resin may have reduced to about 20% of its efficacy when fresh. This is often referred to as a "deactivated" resin. However, it has further been surprisingly found that the presence of a suitable source of formaldehyde in the present invention on a "deactivated" resin causes the removal of impurities 30 at a rate similar to that of fresh resin.

Therefore, according to a second aspect of the present invention there is provided a process for purifying methyl

methacrylate (MMA) comprising contacting liquid MMA having impurities therein with a sulphonic acid resin, in the presence of formaldehyde or a suitable source of methylene or ethylene of formula I as defined below:

5



where R^5 and R^6 are independently selected from $\text{C}_1\text{-C}_{12}$ hydrocarbons, preferably, $\text{C}_1\text{-C}_{12}$ alkyl, alkenyl or aryl as defined herein, or H , more preferably, $\text{C}_1\text{-C}_{10}$ alkyl, or H , most preferably, $\text{C}_1\text{-C}_6$ alkyl or H , especially, methyl or H ;

X is either O or S , preferably, O ;

n is an integer from 1 to 100, preferably, 1 to 10, more preferably 1 to 5, especially, 1-3;

15 and m is 1 or 2, preferably 1, wherein the sulphonic acid resin is at least partially deactivated.


In a particularly preferred embodiment the compound of formula I is derived from formaldehyde in the presence of methanol and/or water. In such a case, the compound of 20 formula I may be defined as a suitable source of formaldehyde. By the term "the sulphonic acid resin is at least partially deactivated", it is meant that the efficacy of the sulphonic acid resin has become reduced (as compared to a fresh resin) due to its prior exposure 25 to resin contaminants such as those present in a feed stream being purified such as an impure liquid MMA stream.

Preferably, the at least partially deactivated sulphonic acid resin has less than 99.9% efficacy as compared to its efficacy when unused. Preferably, the at least partially deactivated sulphonic acid resin has less than 99% efficacy as compared to its efficacy when unused, more typically, less than 95% efficacy, most typically, less than 75% efficacy, especially, less than 50% efficacy.

Preferably, the at least partial deactivation refers to the sulphonic acid resins ability to react with at least one diene. For example, preferably the at least partially deactivated sulphonic acid resin has less than 50% efficacy in reacting with at least one diene as compared to its efficacy when unused.

15

According to a third aspect of the present invention there is provided methyl methacrylate such as liquid MMA having one or more of the impurities indicated herein which has contacted a sulphonic acid resin in the presence of formaldehyde or a suitable source of methylene or ethylene of formula I as defined below:




where R^5 and R^6 are independently selected from C_1-C_{12} hydrocarbons, preferably, C_1-C_{12} alkyl, alkenyl or aryl as defined herein, or H, more preferably, C_1-C_{10} alkyl, or H, most preferably, C_1-C_6 alkyl or H, especially, methyl or H;

X is either O or S, preferably, O;

n is an integer from 1 to 100, preferably, 1 to 10, more preferably 1 to 5, especially, 1-3;

and m is 1 or 2, preferably 1, when in the liquid phase.

5 According to a fourth aspect of the present invention there is provided a polymer comprising methyl methacrylate residues, which methyl methacrylate residues have contacted a sulphonic acid resin in the presence of formaldehyde or a suitable source of methylene or ethylene
10 of formula I as defined below:



where R⁵ and R⁶ are independently selected from C₁-C₁₂ hydrocarbons, preferably, C₁-C₁₂ alkyl, alkenyl or aryl as defined herein, or H, more preferably, C₁-C₁₀ alkyl, or H, most preferably, C₁-C₆ alkyl or H, especially, methyl or H;

X is either O or S, preferably, O;

n is an integer from 1 to 100, preferably, 1 to 10, more preferably 1 to 5, especially, 1-3;

and m is 1 or 2, preferably 1, when in the liquid monomer phase.

25 Preferably, the impure MMA of the present invention is produced by the condensation of formaldehyde with methyl propionate. It has been found that the present invention is particularly advantageous in the removal of impurities from liquid MMA produced by such a process. Typically, the

impure MMA for purification by the practice of the present invention is produced by the condensation of formaldehyde with methyl propionate in the presence of a suitable basic catalyst and, optionally, methanol, to prevent acid 5 formation. A suitable basic catalyst for the condensation reaction is an alkali metal doped silica such as Caesium on silica(Cs^+/SiO_2). In such cases, the silicas that may be employed are preferably porous high surface area silicas such as gel silicas, precipitated gel silicas and 10 agglomerated pyrogenic silicas. Preferably, the alkali metal is present in the silica catalyst in the range 1-10%w/w (expressed as metal).

15 All of the features contained herein may be combined with any of the above aspects and in any combination.

The invention will now be illustrated by the following examples and with reference to the figure in which:-

20 Figure 1 is a graph of divinylketone removal with respect to formaldehyde feed.

Examples

25 Example 1

100g of water wet Lewatit 2314 strong sulphonic acid ion exchange resin supplied by Lanxess was washed by allowing methanol to flow down a glass column packed with the resin 30 at a rate of 1 bed volume per hour until the eluent, initially brown, became colourless to the eye. It was then washed with pure MMA until the concentration of methanol fell to 100 ppm. 20g of such resin was placed in

a 3 necked round bottomed flask equipped with a magnetic stirrer follower, a thermometer and a water cooled reflux condenser. 50 ml of a sample of pure MMA to which 100ppm of 2-methyl-1,5-hexadiene had been added was placed in the 5 flask. The flask was placed in a preheated oil bath and samples taken by pipette from the flask at defined intervals. The same batch of resin was used for each experiment. Samples were analysed on a Varian GC equipped with a CPSil 1701 capillary column. The 2-methyl-1,5-10 hexadiene isomerised rapidly to form 2-methyl-2,5-hexadiene. This component then disappeared very slowly to form 2-methyl-2,4-hexadiene. The experiment was run three times, at 70°C, 50°C and 30°C. The wt% of each component are shown in tables 1, 3 and 5.

15

Example 2

Example 1 was repeated, but in this case 1000 or 7000ppm of 1,1-dimethoxymethane was added to the MMA solution 20 before heating. The wt% of each component are shown in tables 2, 4 and 6.

Example 3

25

Example 1 was repeated except that a mixture of 100 ppm each of 2,5-dimethyl-1,5-hexadiene and 2,5-dimethyl-2,4-hexadiene were used instead of 100 ppm 2-methyl-1,5 hexadiene. The wt% of each component at three different 30 temperatures is shown in table 7, 9 and 11.

Example 4

Example 3 was repeated except that 1000 or 7000ppm of 1,1-dimethoxymethane was added to the MMA solution before heating.

5 The wt% of each component at each heating temperature is shown in tables 8, 10 and 12.

Tables 7-12 show the amount of 2,5-dimethyl-2,4-hexadiene present at different time intervals and different temperatures both with and without 1,1-dimethoxymethane 10 present.

Table 1 70°C, 0ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0109%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
2Me-2,5-hexadiene	0.0000%	0.0083%	0.0072%	0.0052%	0.0031%	0.0014%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0005%	0.0019%	0.0022%	0.0027%	0.0025%
Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%

Table 2 70°C, 1000ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0117%	0.0007%	0.0004%	0.0005%	0.0005%	0.0006%
2Me-2,5-hexadiene	0.0000%	0.0054%	0.0027%	0.0011%	0.0009%	0.0006%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%

Table 3 50°C, 0 ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0109%	0.0003%	0.0004%	0.0005%	0.0000%	0.0000%
2Me-2,5-hexadiene	0.0000%	0.0076%	0.0072%	0.0068%	0.0065%	0.0049%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0001%	0.0003%	0.0007%

Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
------------------------	---------	---------	---------	---------	---------	---------

Table 4 50°C, 1000ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0111%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
2Me-2,5-hexadiene	0.0000%	0.0062%	0.0047%	0.0031%	0.0014%	0.0008%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%

5 Table 5 30°C, 0 ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0132%	0.0002%	0.0002%	0.0002%	0.0002%	0.0001%
2Me-2,5-hexadiene	0.0000%	0.0067%	0.0070%	0.0065%	0.0065%	0.0063%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%

Table 6 30°C, 7000ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2Me-1,5-hexadiene	0.0121%	0.0007%	0.0002%	0.0002%	0.0000%	0.0000%
2Me-2,5-hexadiene	0.0000%	0.0064%	0.0052%	0.0031%	0.0009%	0.0000%
Trans-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%
Cis-2-Me-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%	0.0000%

10

In the absence of 1,1-dimethoxymethane the 2-methyl-1,5-dimethylhexadiene rapidly isomerises to 2-methyl-2,5-hexadiene and then slowly converts in part to 2-methyl-2,4-hexadiene. In the presence of 1,1-dimethoxymethane, there is a rapid removal of 2-methyl-2,5-hexadiene following the isomerisation process, without 2-methyl-2,4-hexadiene being detected in the flask.

Table 7 30°C, 0ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2,5-Dimethyl-1,5-hexadiene	0.0034%	0.0000%	0.0049%	0.0027%	0.0035%	0.0034%
2,5-Dimethyl-2,4-hexadiene	0.0000%	0.0000%	0.0000%	0.0060%	0.0054%	0.0044%

5 Table 8 30°C, 7000ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2,5-dimethyl-1,5-hexadiene	0.0069%	0.0023%	0.0024%	0.0027%	0.0023%	0.0025%
2,5-Dimethyl-2,4-hexadiene	0.0082%	0.0068%	0.0039%	0.0018%	0.0000%	0.0000%

Table 9 50°C, 0ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2,5-dimethyl-1,5-hexadiene	0.0082%	0.0006%	0.0009%	0.0008%	0.0008%	0.0011%
2,5-Dimethyl-2,4-hexadiene	0.0088%	0.0111%	0.0119%	0.0118%	0.0120%	0.0117%

10

15 Table 10 50°C 1000ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2,5-dimethyl-1,5-hexadiene	0.0057%	0.0013%	0.0016%	0.0015%	0.0017%	0.0016%
2,5-Dimethyl-2,4-hexadiene	0.0064%	0.0090%	0.0071%	0.0047%	0.0018%	0.0013%

Table 11 70°C 0ppm 1,1-dimethoxymethane

Component	Time/min					
	0	5	10	20	40	60
2,5-dimethyl-1,5-hexadiene	0.0024%	0.0005%	0.0006%	0.0006%	0.0010%	0.0012%
2,5-Dimethyl-2,4-hexadiene	0.0042%	0.0133%	0.0131%	0.0124%	0.0104%	0.0096%

Table 12 70°C 1000ppm 1,1-dimethoxymethane

Component	Time/min					
		0	5	10	20	40
2,5-dimethyl-1,5-hexadiene	0.0027%	0.0013%	0.0010%	0.0008%	0.0007%	0.0003%
2,5-Dimethyl-2,4-hexadiene	0.0049%	0.0050%	0.0027%	0.0014%	0.0009%	0.0006%

5 In the absence of 1,1-dimethoxymethane the rapid isomerisation of 2,5-dimethyl-2,5-hexadiene to 2,5-dimethyl-2,4-hexadiene is followed by a very slow decay of the latter. When 1,1-dimethoxymethane is present in the solution there is a rapid decay of 2,5-dimethyl-2,4-hexadiene to a different product.

The first order rate constants for decay of 2-methyl-2,5-hexadiene and 2,5-dimethyl-2,4-hexadiene are listed in the table 13 for each of the conditions.

Table 13

		First Order Rate Constant s ⁻¹		
	[1,1-dimethoxymethane]/ppm	30°C	50°C	70°C
rate constants for decay of 2-methyl-2,5-hexadiene	0	0.0015	0.007	0.0325
	1000		0.0367	0.1147
	7000	0.0581		
rate constants for decay of 2,5-dimethyl-2,4-hexadiene	0	0.0003	0.0063	0.0003
	1000		0.0365	0.0812
	7000	0.0878		

5 Therefore, the addition of 1,1-dimethoxymethane has a large impact on the rate of decay both for the 2-methyl 2,5-hexadiene and 2,5-dimethyl-2,4-hexadiene.

Example 5

10

Two Lewatit 2431 resin samples were used:

A Fresh Resin

15 This was prepared by washing the resin with methanol containing 200 ppm hydroquinone (HQ) and then pure MMA containing 100 ppm HQ.

B Used Resin

20

A sample which had been exposed to a continuous flow of impure MMA over a period of 12 days was used. The impure MMA was derived from a process generating MMA by a

condensation reaction between methyl propionate and formaldehyde.

The two samples were tested with a reaction mixture of 5 impure MMA and containing the levels of cis and trans-2-methyl-2,4-hexadiene shown in the table and 100 ppm HQ, using the method of example 1 and at 50°C:

10 The concentrations of each species are shown in table 14 below.

Table 14

		Time of Exposure/minutes					
		0	2	5	10	20	30
Fresh Resin	0ppm 1,1-Dimethoxymethane	t-2-Me-2,4-hexadiene c-2-Me-2,4-hexadiene	0.0035% 0.0040%	0.0011% 0.0003%	0.0004% 0.0001%	0.0002% 0.0001%	0.0000% 0.0000%
	Used 0ppm 1,1-Dimethoxymethane	t-2-Me-2,4-hexadiene c-2-Me-2,4-hexadiene	0.0035% 0.0040%	0.0022% 0.0014%	0.0021% 0.0008%	0.0016% 0.0007%	0.0007% 0.0002%
Fresh Resin	+1000ppm 1,1-Dimethoxymethane	t-2-Me-2,4-hexadiene c-2-Me-2,4-hexadiene	0.0041% 0.0015%	0.0008% 0.0004%	0.0000% 0.0000%	0.0000% 0.0000%	0.0000% 0.0000%
	Used +1000ppm 1,1-Dimethoxymethane	t-2-Me-2,4-hexadiene c-2-Me-2,4-hexadiene	0.0041% 0.0015%	0.0001% 0.0000%	0.0000% 0.0000%	0.0000% 0.0000%	0.0000% 0.0000%

The change in concentration of the 2-methyl hexadienes with time is complicated by their being in equilibrium in the presence of the acidic ion exchange resin. Therefore, the concentrations of the dienes were added to examine the 5 decay kinetics. It was found that their combined concentrations fell approximately exponentially with time. The first order rate constants derived from the two resins, with and without added formaldehyde containing species are shown in table 15 below:

10

Table 15

Kinetic Comparison	Fresh Resin	Used Resin
No 1,1-dimethoxymethane	0.5	0.09
Added 1,1-dimethoxymethane	0.8	0.9

Over the fresh resin, there was an approximately 50% increase in rate of removal on addition of 1,1-dimethoxymethane. Over the resin that had been used previously, the rate of removal in the absence of 1,1-dimethoxymethane was very low, only 17% of that on the fresh resin. However, there was a ten fold increase in activity on the used resin in the presence of 1,1-dimethoxymethane, such that the activity was as good as that on the fresh resin.

This experiment demonstrates that addition of formaldehyde is particularly effective on partially deactivated acidic 25 ion exchange resins.

Example 6

A sample of MMA containing cis and trans 2-methyl-2,4-hexadiene and other impurities and 100ppm HQ was passed as a liquid over a fixed bed of 16g resin in a 0.5 inch OD stainless steel reactor at atmospheric pressure and 70°C.

5 The flow rate was adjusted to give a residence time of 31.7 minutes. After the feed was introduced, the samples were left for 2 residence times before samples were collected and analysed. The analysis of the combined levels of cis and trans 2-methyl-2,4-dimethylhexadiene is
10 compared with the untreated MMA containing stream in table 16.

Table 16

		Fresh Resin		
		start	80ppm HCHO	200 ppm HCHO
Formalin Source				320 ppm HCHO
1,1-dimethoxymethane	0.0061%	0.0005%	0.0005%	0.0000%
37% formalin	0.0061%	0.0012%	0.0000%	0.0000%
Process stream containing 81.5% MeP, 10%HCHO, 6.5%methanol, 2% others	0.0061%	0.0007%	0.0006%	0.0000%
		Used Resin		
Formalin Source		start	80ppm HCHO	200 ppm HCHO
1,1-dimethoxymethane	0.0061%	0.0018%	0.0017%	0.0000%
37% formalin	0.0061%	0.0026%	0.0004%	0.0004%
Process stream containing 81.5% MeP, 10%HCHO, 6.5%methanol, 2% others	0.0061%	0.0014%	0.0015%	0.0006%

This experiment demonstrates that there is no difference between whether the formaldehyde is added as 1,1-dimethoxymethane, as formalin or as a methanolic non-aqueous formaldehyde stream.

5

Example 7

A bed of 750ml of Lewatit 2431 Acidic Ion Exchange Resin was used for treating impure MMA containing various 10 impurities and 100ppm hydroquinone as stabiliser at a flow rate of 600g/hour. The flow was maintained for 62 days. During the first 62 days, the average feed and exit compositions in ppm for various impurities and fractional conversions are shown in table 17 for a formaldehyde feed 15 of 17.5ppm:

Table 17

	Feed	Exit	Conversion
Isobutyraldehyde	96.1	37.4	61.1%
Methacrolein	3.2	0.1	96.4%
Isobutanol	50.7	27.7	45.3%
Pentenal	8.9	0.2	97.4%
Toluene	18.9	17.6	7.1%

Further impurities were analysed after longer flow periods 20 as shown in table 18.

Table 18

	Feed	Exit	Average Conversion
Day 120-126			
Ethylisopropenylketone	2.7	0.0	100.0%

Several other components require formaldehyde for their removal when the resin bed has been operating for a long time. Figure 1 and table 19 show that divinyl ketone 5 (DVK) containing MMA requires over 60ppm of formaldehyde before it is completely removed.

Table 19

Time on Line/ days	Contained Formaldehyd e/ppm	Fractional conversion of Divinyl ketone/%	Time on Line/ days	Contained Formaldehy de/ppm	Fractional Conversion of Divinyl Ketone/%
115	32	67%	121	204	100%
116	32	72%	121	173	100%
116	39	71%	122	162	100%
117	40	82%	122	143	100%
117	44	67%	123	141	100%
118	48	25%	123	144	100%
118	48	59%	124	143	100%
119	53	63%	124	153	100%
119	111	100%	125	147	100%
120	200	100%	125	152	100%
120	207	100%	126	161	100%

10 Example 8

A fresh ion exchange resin (800ml aliquot) was washed with methanol to remove water at a flow rate of 0.15 g/ml/h, until the water content fell to below 0.2 wt%. It was 15 then drained to remove excess methanol and washed with MMA at the same flow rate until the methanol level dropped below 0.2 wt%. Two volumes of impure MMA containing 111ppm diethylketone and 320ppm formal-2 ($\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_2\text{-}$

CH₃), (equivalent to 180 ppm contained formaldehyde) to be used for the experiment were then flushed through the resin sample at 2 ml/min for 80 min to replace the pure MMA with the desired component. The resin was transferred 5 into a bottle, the bottle was topped up with the impure MMA sample and the sample was sparged with air through a cannula to saturate it. The bottle was sealed and then placed in an oil bath at 55°C. Periodically, samples were collected for analysis. The analysis is shown in table 10 20:

Table 20

Time exposed to Resin in hours	[Diethylketone]/ppm
0.0	111
0.7	103.5
2.5	102.5
3.8	95
4.8	91
5.8	110
6.3	70
8.0	66
9.5	55
11.7	31
14.75	37
15.5	38

Clearly, the process of the invention results in a 15 dramatic reduction in the level of diethyl ketone.

Attention is directed to all papers and documents which are filed concurrently with or previous to this specification in connection with this application and 20 which are open to public inspection with this specification, and the contents of all such papers and documents are incorporated herein by reference.

All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, 5 except combinations where at least some of such features and/or steps are mutually exclusive.


Each feature disclosed in this specification (including any accompanying claims, abstract and drawings) may be 10 replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example only of a generic series of equivalent or similar features.

15

The invention is not restricted to the details of the foregoing embodiment(s). The invention extends to any novel one, or any novel combination, of the features disclosed in this specification (including any 20 accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

CLAIMS

1 A process for purifying methyl methacrylate (MMA)
5 comprising contacting liquid MMA having impurities
therein with a sulphonic acid resin, in the presence
of formaldehyde or a suitable source of methylene or
ethylene of formula I as defined below:



where R^5 and R^6 are independently selected from C_1-C_{12} hydrocarbons or H;

X is either O or S;

n is an integer from 1 to 100;

15 and m is 1 or 2.

2 A process for purifying methyl methacrylate (MMA)
according to claim 1, wherein the compound of formula
I is a suitable source of formaldehyde.


20

3. A process for purifying methyl methacrylate according
to claim 2, wherein formaldehyde or the amount of
formaldehyde that can be liberated from a suitable
source of formaldehyde is present in an amount between
25 0.01 and 0.1 weight percent relative to the weight of
liquid MMA.

4. A process for purifying methyl methacrylate according to claim 2 or 3, wherein the suitable source of formaldehyde is selected from 1,1 dimethoxymethane, higher formals of formula $\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_i\text{-CH}_3$ where $i=2$ or more, formalin or a mixture comprising formaldehyde, methanol and methyl propionate.
5. A process for purifying methyl methacrylate according to any preceding claim, wherein the formaldehyde or source thereof is mixed with the impure liquid MMA prior to contact with the sulphonic acid resin.
10. A process for purifying methyl methacrylate according to claim 5, wherein in a continuous or semi-continuous process, an impure liquid MMA stream is mixed with a stream containing the formaldehyde or source thereof to form a combined liquid stream prior to contact with the sulphonic acid resin.
15. A process for purifying methyl methacrylate according to claim 6, wherein the formaldehyde is therefore present in an amount between 0.01 and 0.1 weight percent in the combined liquid stream.
20. A process for purifying methyl methacrylate according to any preceding claim, wherein the formaldehyde source is alternatively or additionally present as an impurity in the MMA.
25. 9. A process for purifying methyl methacrylate according to claim 8, wherein the impurity in the MMA is formal-2 ($\text{CH}_3\text{-O-}(\text{CH}_2\text{-O})_2\text{-CH}_3$).
10. A process for purifying methyl methacrylate according to any preceding claim, wherein the purification process of the invention is performed at a temperature between 25 and 100°C.
30. 11. A process for purifying methyl methacrylate according to any preceding claim, wherein at least one

carboxylic acid ester is also present in the purification process.

12. A process for purifying methyl methacrylate according to claim 11, wherein in a continuous or semi-
5 continuous process the at least one carboxylic acid ester is already present in the impure liquid MMA stream prior to contact with the sulphonic acid resin.
13. A process for purifying methyl methacrylate according to any preceding claim, wherein the impurities have a
10 boiling point within 15°C of MMA.
14. A process for purifying methyl methacrylate according to any preceding claim, wherein the impurities are selected from isobutyraldehyde, either as isobutyraldehyde or in a compound which regenerates isobutyraldehyde when exposed to the sulphonic acid ion exchange resin, optionally substituted C₆-C₂₀ trienes, optionally substituted unsaturated aldehydes and ketones, divinyl ketone, ethyl vinyl ketone, diethyl ketone, ethyl isopropenyl ketone, 3-methylene
15 1-hexen-4-one, methacrolein, isobutanol, toluene, and pentenals such as 3-pentenal.
15. A process for purifying methyl methacrylate according to any preceding claim, wherein the process is carried out in the presence of at least one suitable
20 stabilizer.
16. A process for purifying methyl methacrylate (MMA) comprising contacting liquid MMA having impurities therein with a sulphonic acid resin, in the presence of formaldehyde or a suitable source of methylene or
25 ethylene of formula I as defined below:



where R^5 and R^6 are independently selected from C_1-C_{12} hydrocarbons or H;

X is either O or S;


n is an integer from 1 to 100;

5 and m is 1 or 2; wherein the sulphonic acid resin is at least partially deactivated.

17 Methyl methacrylate purified by a process according to any of claims 1-16.

10

18 A polymer comprising methyl methacrylate residues, which methyl methacrylate residues have contacted a sulphonic acid resin in the presence of formaldehyde or a suitable source of methylene or ethylene of formula I as defined below:




where R^5 and R^6 are independently selected from C_1-C_{12} hydrocarbons or H;

20 X is either O or S;

n is an integer from 1 to 100;

and m is 1 or 2; when in the liquid phase.

Figure 1



INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2009/051693

A. CLASSIFICATION OF SUBJECT MATTER
INV. C07C67/60 C07C69/54

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C07C

1

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, CHEM ABS Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 625 059 A (SHIBANO TAKESHI [JP] ET AL) 25 November 1986 (1986-11-25) cited in the application column 3, line 26 – line 33 column 4, line 22 – line 30 column 5, line 5 – line 32 column 6 – column 7; examples 8,10-14,22; tables 1-2	1,5-6, 10-17
A	WO 2005/003063 A2 (SOLUTIA INC [US]; WARD GREGORY J [US]; BLANCHARD BRYAN [US]; MOFFATT S) 13 January 2005 (2005-01-13) page 4, paragraph 17 page 5, paragraph 19 page 6, paragraph 23 – page 8, paragraph 29; examples 1-3; tables 1-3	1-16

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
25 March 2010	01/04/2010
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Patteux, Claudine

INTERNATIONAL SEARCH REPORT

International application No
PCT/GB2009/051693

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 99/26915 A1 (IMPERIAL CHEMICAL INDUSTRIES PLC, UK) 3 June 1999 (1999-06-03) abstract page 2, line 9 – page 3, line 2 page 5; examples 1-6 -----	2-4, 7-9
X	GB 783 073 A (ESTEBAN DOMINGO SEGUI; BIENVENIDO CABANERO ALARCON) 18 September 1957 (1957-09-18) the whole document -----	17-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/GB2009/051693

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 4625059	A	25-11-1986	JP	1740239 C		15-03-1993
			JP	4029658 B		19-05-1992
			JP	60006635 A		14-01-1985
WO 2005003063	A2	13-01-2005	CN	1812953 A		02-08-2006
			EP	1638911 A2		29-03-2006
			JP	2007516942 T		28-06-2007
			KR	20060086845 A		01-08-2006
			MX	PA05014189 A		24-02-2006
			US	2004267054 A1		30-12-2004
			US	2007135653 A1		14-06-2007
WO 9926915	A1	03-06-1999	AU	1047899 A		15-06-1999
			ZA	9810592 A		20-05-1999
GB 783073	A	18-09-1957		NONE		