

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2016204905 B2**

(54) Title
Gesture recognizers with delegates for controlling and modifying gesture recognition

(51) International Patent Classification(s)
G06F 9/44 (2006.01) **G06F 3/048** (2006.01)

(21) Application No: **2016204905** (22) Date of Filing: **2016.07.13**

(43) Publication Date: **2016.08.04**

(43) Publication Journal Date: **2016.08.04**

(44) Accepted Journal Date: **2018.07.05**

(62) Divisional of:
2014213525

(71) Applicant(s)
Apple Inc.

(72) Inventor(s)
SHAFFER, Joshua H.;MOORE, Bradford Allen;BEAVER, Jason Clay

(74) Agent / Attorney
FPA Patent Attorneys Pty Ltd, ANZ Tower 161 Castlereagh Street, Sydney, NSW, 2000, AU

(56) Related Art
WO 2009/111189 A1
KennyTm: "UIGestureRecognizer - iPhone Development Wiki",
31 Oct 2009, p 1-3, URL:[http://iphonedevwiki.net/index.php?](http://iphonedevwiki.net/index.php?title=UIGestureRecognizer&oldid=319)
[http://iphonedevwiki.net/index.php?](http://iphonedevwiki.net/index.php?title=UIGestureRecognizer&oldid=319)
[http://iphonedevwiki.net/index.php?](http://iphonedevwiki.net/index.php?title=UIGestureRecognizer&action=history)
US 2006/0026521 A1

2016204905 13 Jul 2016

ABSTRACT

A method is performed at an electronic device having a touch-sensitive surface and configured to execute a software application. The method includes displaying one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers. The plurality of gesture recognizers includes at least one discrete gesture recognizer and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The method also includes detecting one or more touches, and processing each of the touches using one or more of the gesture recognizers. The processing of a respective touch includes processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer. The method further includes executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches.

GESTURE RECOGNIZERS WITH DELEGATES FOR CONTROLLING AND MODIFYING GESTURE RECOGNITION

TECHNICAL FIELD

[0001] This relates generally to user interface processing, including but not limited to, apparatuses and methods for recognizing gesture inputs.

RELATED APPLICATIONS

[0001a] This application is related to PCT application no. PCT/US2011/022516, filed on 26 January 2011, the contents of which are incorporated herein by reference.

BACKGROUND

[0002] An electronic device typically includes a user interface that may be used to interact with the computing device. The user interface may include a display and/or input devices such as a keyboard, mice, and touch-sensitive surfaces for interacting with various aspects of the user interface. In some devices with a touch-sensitive surface as an input device, a first set of touch-based gestures (e.g., two or more of: tap, double tap, horizontal swipe, vertical swipe, pinch, depinch, two finger swipe) are recognized as proper inputs in a particular context (e.g., in a particular mode of a first application), and other, different sets of touch-based gestures are recognized as proper inputs in other contexts (e.g., different applications and/or different modes or contexts within the first application). As a result, the software and logic required for recognizing and responding to touch-based gestures can become complex, and can require revision each time an application is updated or a new application is added to the computing device. These and similar issues may arise in user interfaces that utilize input sources other than touch-based gestures.

[0003] Thus, it would be desirable to have a comprehensive framework or mechanism for recognizing touch-based gestures and events, as well as gestures and events from other input sources, that is easily adaptable to virtually all contexts or modes of all application programs on a computing device, and that requires little or no revision when an application is updated or a new application is added to the computing device.

[0003a] Reference to any prior art in the specification is not, and should not be taken as, an acknowledgment or any form of suggestion that this prior art forms part of the common general

knowledge in Australia or that this prior art could reasonably be expected to be ascertained, understood and regarded as relevant by a person skilled in the art.

SUMMARY

[0003b] According to a first aspect of the invention there is provided a method, comprising: at an electronic device having one or more event sensors and configured to execute a software application: displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including: at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture; detecting, using the one or more event sensors, one or more events; processing each of the events using one or more of the gesture recognizers, the processing of a respective event including: processing the respective event at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events; wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.

[0003c] According to a second aspect of the invention there is provided an electronic device, comprising: one or more event sensors; one or more processors; and memory storing one or more programs for execution by the one or more processors, the one or more programs including a software application, and the software application including instructions for: displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including: at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture; detecting, using the one or more event sensors, one or more events; processing each of the events using one or more of the gesture recognizers, the processing of a respective event including: processing the respective event at a respective

gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events; wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.

[0003d] According to a third aspect of the invention there is provided a computer readable storage medium storing one or more programs for execution by one or more processors of an electronic device having one or more event sensors, the one or more programs including a software application, the software application including instructions for: displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including: at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture; detecting, using the one or more event sensors, one or more events; processing each of the events using one or more of the gesture recognizers, the processing of a respective event including: processing the respective event at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events; wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.

[0004] To address the aforementioned drawbacks, in accordance with some embodiments, a method is performed at an electronic device having one or more event

2016204905 13 Jul 2016

sensors and configured to execute a software application that includes a plurality of views and an application state of the software application. The method includes displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The method includes detecting one or more events, and processing a respective event of the one or more events using the respective gesture recognizer. The processing of the respective event includes: processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the respective gesture recognizer's corresponding delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate. The method furthermore includes executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event.

[0005] In accordance with some embodiments, an electronic device includes: one or more event sensors for detecting events, one or more processors, memory, and one or more programs stored in the memory and configured to be executed by the one or more processors. The one or more programs include a software application having a plurality of views and an application state. The software application includes instructions for displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The software application further includes instructions for detecting one or more events and instructions for processing a respective event of the detected events using the respective gesture recognizer. The instructions for processing of the respective event include instructions for: processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the corresponding delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate. The software

application furthermore includes instructions for executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event.

[0006] In accordance with some embodiments, a computer readable storage medium stores one or more programs for execution by one of more processors of an electronic device having one or more event sensors for detecting events. The one or more programs include a software application including a plurality of views and an application state of the software application. The software application includes instructions for displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more respective gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The software application further includes instructions for detecting one or more events and instructions for processing a respective event of the detected events using the respective gesture recognizer. The instructions for processing of the respective event include instructions for: processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the corresponding delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate. The software application furthermore includes instructions for executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event.

[0007] In accordance with some embodiments, a method is performed at an electronic device having a touch-sensitive surface and configured to execute a software application that includes a plurality of views and an application state of the software application. The method includes displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes a respective gesture recognizer. The respective gesture recognizer has a corresponding delegate. The method also includes detecting one or more touches, on the touch-sensitive surface, each having a touch position that falls within one or more of the displayed views. The method further includes processing a respective touch of the one or more touches. Processing the respective touch includes executing the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in

accordance with the application state, and when the receive touch value meets predefined criteria, processing the respective touch at the respective gesture recognizer. Processing the respective touch also includes conditionally sending information corresponding to the respective touch to the software application. The method furthermore includes executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch.

[0008] In accordance with some embodiments, an electronic device includes a touch-sensitive surface, one or more processors, memory, and one or more programs stored in the memory and configured to be executed by the one or more processors. The one or more programs include a software application including a plurality of views and an application state of the software application. The software application includes instructions for displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more respective gesture recognizers. A respective gesture recognizer has a corresponding delegate. The software application also includes instructions for detecting one or more touches, on the touch-sensitive surface, each having a touch position that falls within one or more of the displayed views. The software application further includes instructions for processing a respective touch of the one or more touches. The instructions for processing the respective touch include instructions for: executing the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in accordance with the application state, and when the receive touch value meets predefined criteria, processing the respective touch at the respective gesture recognizer. The instructions for processing the respective touch also include instructions for conditionally sending information corresponding to the respective touch to the software application. The software application furthermore includes instructions for executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch.

[0009] In accordance with some embodiments, a computer readable storage medium stores one or more programs for execution by one or more processors of an electronic device having a touch-sensitive surface. The one or more programs include a software application including a plurality of views and an application state of the software application. The software application includes instructions for displaying one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more respective gesture recognizers. The respective gesture recognizer has a corresponding

2016204905 13 Jul 2016

delegate. The software application also includes instructions for detecting one or more touches, on the touch-sensitive surface, each having a touch position that falls within one or more of the displayed views. The software application further includes instructions for processing a respective touch of the one or more touches. The instructions for processing the respective touch include instructions for: executing the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in accordance with the application state, and when the receive touch value meets predefined criteria, processing the respective touch at the respective gesture recognizer. The instructions for processing the respective touch also include instructions for conditionally sending information corresponding to the respective touch to the software application. The software application furthermore includes instructions for executing the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch.

[0010] In accordance with some embodiments, a method is performed at an electronic device having a touch-sensitive surface and configured to execute a software application. The method includes displaying one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers. The plurality of gesture recognizers includes at least one discrete gesture recognizer and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The method also includes detecting one or more touches, and processing each of the touches using one or more of the gesture recognizers. The processing of a respective touch includes processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer. The method further includes executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches.

[0011] In accordance with some embodiments, an electronic device includes a touch-sensitive surface, one or more processors, memory, and one or more programs stored in the memory and configured to be executed by the one or more processors. The one or more

2016204905 13 Jul 2016

programs include a software application, and the software application includes instructions for displaying one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers. The plurality of gesture recognizers includes at least one discrete gesture recognizer and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The software application also includes instructions for detecting one or more touches and processing each of the touches using one or more of the gesture recognizers. The instructions for processing of a respective touch include instructions for: processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer. The software application further includes instructions for executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches.

[0012] In accordance with some embodiments, a computer readable storage medium stores one or more programs for execution by one of more processors of an electronic device having a touch-sensitive surface. The one or more programs include a software application, and the software application includes instructions for displaying one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers. The plurality of gesture recognizers includes at least one discrete gesture recognizer, and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The software application also includes instructions for: detecting one or more touches, and processing each of the touches using one or more of the gesture recognizers. The instructions for the processing of a respective touch includes instructions for processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the

respective gesture recognizer. The software application further includes instructions for executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches.

[0013] In accordance with some embodiments, an electronic device includes one or more event sensing units configured to sense one or more events, and a processing unit coupled to the one or more event sensing units. The processing unit is configured to: execute a software application that includes a plurality of views and an application state of the software application, and enable display of one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more respective gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The processing unit is configured to detect the one or more events sensed by the one or more event sensing units, and process a respective event of the one or more events using the respective gesture recognizer by processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the corresponding delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate. The processing unit is configured to execute the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event.

[0014] In accordance with some embodiments, an electronic device includes a touch-sensitive surface unit configured to receive one or more touches, and a processing unit coupled to the touch-sensitive surface unit. The processing unit is configured to: execute a software application that includes a plurality of views and an application state of the software application, and enable display of one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more respective gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The processing unit is configured to detect the one or more touches received on the touch-sensitive surface unit. Each of the one or more touches has a touch position that falls within one or more of the displayed views. The processing unit is configured to process a respective touch of the one or more touches by: executing the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in accordance with the application state, when the receive

touch value meets predefined criteria, processing the respective touch at the respective gesture recognizer, and conditionally sending information corresponding to the respective touch to the software application. The processing unit is configured to execute the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch.

[0015] In accordance with some embodiments, an electronic device includes a touch-sensitive surface unit configured to receive one or more touches, and a processing unit coupled to the touch-sensitive surface unit. The processing unit is configured to: execute a software application, and enable display of one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers, and the plurality of gesture recognizers include: at least one discrete gesture recognizer and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The processing unit is configured to detect the one or more touches received on the touch-sensitive surface unit, and process each of the touches using one or more of the gesture recognizers. The processing unit is configured to process a respective touch by: processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer. The processing unit is configured to execute the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] Figures 1A and 1B are block diagrams illustrating electronic devices, according to some embodiments.

[0017] Figure 2 is a diagram of an input/output processing stack of an exemplary electronic device according to some embodiments.

[0018] Figure 3A illustrates an exemplary view hierarchy, according to some embodiments.

[0019] Figure 3B is a block diagram illustrating exemplary components for event handling in accordance with some embodiments.

[0020] Figure 3C is a block diagram illustrating exemplary classes and instances of gesture recognizers in accordance with some embodiments.

[0021] Figures 4A-4D are flow charts illustrating exemplary state machines, according to some embodiments.

[0022] Figure 5A is a block diagram illustrating the flow of event information, according to some embodiments.

[0023] Figures 5B and 5C are high-level flow charts illustrating gesture recognition methods, according to some embodiments.

[0024] Figures 6A-6B are flow charts illustrating an exemplary method of processing a respective event in accordance with information obtained from a delegate, according to some embodiments.

[0025] Figures 7A-7B are flow charts illustrating an exemplary method of processing a respective touch in accordance with a receive touch value obtained from a delegate, according to some embodiments.

[0026] Figures 8A-8B are flow charts illustrating an exemplary method of processing a respective touch in a software application including a discrete gesture recognizer and a continuous gesture recognizer, according to some embodiments.

[0027] Figure 9 is a functional block diagram of an electronic device in accordance with some embodiments.

[0028] Figure 10 is a functional block diagram of an electronic device in accordance with some embodiments.

[0029] Figure 11 is a functional block diagram of an electronic device in accordance with some embodiments.

[0030] Like reference numerals refer to corresponding parts throughout the drawings.

DESCRIPTION OF EMBODIMENTS

[0031] Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

[0032] It will also be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first contact could be termed a second contact, and, similarly, a second contact could be termed a first contact, without departing from the scope of the present invention. The first contact and the second contact are both contacts, but they are not the same contact.

[0033] The terminology used in the description of the invention herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the invention. As used in the description of the invention and the appended claims, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will also be understood that the term "and/or" as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms "comprises" and/or "comprising," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0034] As used herein, the term "if" may be construed to mean "when" or "upon" or "in response to determining" or "in response to detecting," depending on the context. Similarly, the phrase "if it is determined" or "if [a stated condition or event] is detected" may be construed to mean "upon determining" or "in response to determining" or "upon detecting (the stated condition or event)" or "in response to detecting (the stated condition or event)," depending on the context.

2016204905 13 Jul 2016

[0035] As used herein, the term “event” refers to an input detected by one or more sensors of the device. In particular, the term “event” includes a touch on a touch-sensitive surface. An event comprises one or more sub-events. Sub-events typically refer to changes to an event (e.g., a touch-down, touch-move, and lift-off of the touch can be sub-events). Sub-events in the sequence of one or more sub-events can include many forms, including without limitation, key presses, key press holds, key press releases, button presses, button press holds, button press releases, joystick movements, mouse movements, mouse button presses, mouse button releases, pen stylus touches, pen stylus movements, pen stylus releases, oral instructions, detected eye movements, biometric inputs, and detected physiological changes in a user, among others. Since an event may comprise a single sub-event (e.g., a short lateral motion of the device), the term “sub-event” as used herein also refers to an event.

[0036] As used herein, the terms “event recognizer” and “gesture recognizer” are used interchangeably to refer to a recognizer that can recognize a gesture or other events (e.g., motion of the device).

[0037] As noted above, in some devices with a touch-sensitive surface as an input device, a first set of touch-based gestures (e.g., two or more of: tap, double tap, horizontal swipe, vertical swipe) are recognized as proper inputs in a particular context (e.g., in a particular mode of a first application), and other, different sets of touch-based gestures are recognized as proper inputs in other contexts (e.g., different applications and/or different modes or contexts within the first application). Furthermore, two or more proper inputs (or gestures) may interfere with, or conflict with, each other (e.g., after detecting a single tap, it needs to be decided whether to recognize the single tap as a complete single tap gesture, or as part of a double tap gesture). As a result, the software and logic required for recognizing and responding to touch-based gestures can become complex, and can require revision each time an application is updated or a new application is added to the computing device.

[0038] When using touch-based gestures to control an application running in a device having a touch-sensitive surface, touches have both temporal and spatial aspects. The temporal aspect, called a phase, indicates when a touch has just begun, whether it is moving or stationary, and when it ends—that is, when the finger is lifted from the screen. A spatial aspect of a touch is the set of views or user interface windows in which the touch occurs. The views or windows in which a touch is detected may correspond to programmatic levels within a view hierarchy. For example, the lowest level view in which a touch is detected may be called the hit view, and the set of events that are recognized as proper inputs may be

determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0039] Figures 1A and 1B are block diagrams illustrating different embodiments of an electronic device 102, 104, according to some embodiments. The electronic device 102 or 104 may be any electronic device including, but not limited to, a desktop computer system, a laptop computer system, a netbook computer system, mobile phone, a smart phone, a personal digital assistant, or a navigation system. The electronic device may also be a portable electronic device with a touch screen display (e.g., touch-sensitive display 156, Figure 1B) configured to present a user interface, a computer with a touch screen display configured to present a user interface, a computer with a touch sensitive surface and a display configured to present a user interface, or any other form of computing device, including without limitation, consumer electronic devices, mobile telephones, video game systems, electronic music players, tablet PCs, electronic book reading systems, e-books, PDAs, electronic organizers, email devices, laptops, netbooks or other computers, kiosk computers, vending machines, smart appliances, etc. The electronic device 102 or 104 includes a user interface 113.

[0040] In some embodiments, electronic device 104 includes a touch screen display. In these embodiments, user interface 113 may include an on-screen keyboard (not depicted) that is used by a user to interact with electronic devices 102 and 104. Alternatively, a keyboard may be separate and distinct from electronic device 104 (or electronic device 102). For example, a keyboard may be a wired or wireless keyboard coupled to electronic device 102 or 104.

[0041] In some embodiments, electronic device 102 includes display 126 and one or more input devices 128 (e.g., keyboard, mouse, trackball, microphone, physical button(s), touchpad, etc.) that are coupled to electronic device 102. In these embodiments, one or more of input devices 128 may optionally be separate and distinct from electronic device 102. For example, the one or more input devices may include one or more of: a keyboard, a mouse, a trackpad, a trackball, and an electronic pen, any of which may optionally be separate from the electronic device. Optionally, device 102 or 104 may include one or more sensors 130, such as one or more accelerometers, gyroscopes, GPS systems, speakers, infrared (IR) sensors, biometric sensors, cameras, etc. It is noted that the description above of various exemplary devices as input devices 128 or as sensors 130 is of no significance to the operation of the embodiments described herein, and that any input or sensor device herein described as an

input device may equally well be described as a sensor, and vice versa. In some embodiments, signals produced by one or more sensors 130 are used as input sources for detecting events.

[0042] In some embodiments, electronic device 104 includes touch-sensitive display 156 (i.e., a display having a touch-sensitive surface) and one or more input devices 128 that are coupled to electronic device 104. In some embodiments, touch-sensitive display 156 has the ability to detect two or more distinct, concurrent (or partially concurrent) touches, and in these embodiments, display 156 is sometimes herein called a multitouch display or multitouch-sensitive display.

[0043] In some embodiments of electronic device 102 or 104 discussed herein, input devices 128 are disposed in electronic device 102 or 104. In other embodiments, one or more of input devices 128 is separate and distinct from electronic device 102 or 104; for example, one or more of input devices 128 may be coupled to electronic device 102 or 104 by a cable (e.g., USB cable) or wireless connection (e.g., Bluetooth connection).

[0044] When using input devices 128, or when performing a touch-based gesture on touch-sensitive display 156 of electronic device 104, the user generates a sequence of sub-events that are processed by one or more CPUs 110 of electronic device 102 or 104. In some embodiments, one or more CPUs 110 of electronic device 102 or 104 process the sequence of sub-events to recognize events.

[0045] Electronic device 102 or 104 typically includes one or more single- or multi-core processing units (“CPU” or “CPUs”) 110 as well as one or more network or other communications interfaces 112, respectively. Electronic device 102 or 104 includes memory 111 and one or more communication buses 115, respectively, for interconnecting these components. Communication buses 115 may include circuitry (sometimes called a chipset) that interconnects and controls communications between system components (not depicted herein). As discussed briefly above, electronic device 102 or 104 includes a user interface 113, including a display (e.g., display 126, or touch-sensitive display 156). Further, electronic device 102 or 104 typically includes input devices 128 (e.g., keyboard, mouse, touch sensitive surfaces, keypads, etc.). In some embodiments, the input devices 128 include an on-screen input device (e.g., a touch-sensitive surface of a display device). Memory 111 may include high-speed random access memory, such as DRAM, SRAM, DDR RAM or other random access solid state memory devices; and may include non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices,

flash memory devices, or other non-volatile solid state storage devices. Memory 111 may optionally include one or more storage devices remotely located from the CPU(s) 110. Memory 111, or alternately the non-volatile memory device(s) within memory 111, comprise a computer readable storage medium. In some embodiments, memory 111 (of electronic device 102 or 104) or the computer readable storage medium of memory 111 stores the following programs, modules and data structures, or a subset thereof:

- operating system 118, which includes procedures for handling various basic system services and for performing hardware dependent tasks;
- communication module 120, which is used for connecting electronic device 102 or 104, respectively, to other devices via their one or more respective communication interfaces 112 (wired or wireless) and one or more communication networks, such as the Internet, other wide area networks, local area networks, metropolitan area networks, and so on;
- user interface module 122, which is used for displaying user interfaces including user interface objects on display 126 or touch-sensitive display 156;
- control application 124, which is used for controlling processes (e.g., hit view determination, thread management, and/or event monitoring, etc.); in some embodiments, control application 124 includes a run-time application; in other embodiments, the run-time application includes control application 124;
- event delivery system 130, which may be implemented in various alternate embodiments within operating system 118 or in application software 132; in some embodiments, however, some aspects of event delivery system 130 may be implemented in operating system 118 while other aspects (e.g., at least a subset of event handlers) are implemented in application software 132;
- application software 132, which may include one or more software applications (e.g., an email application, a web browser application, a text messaging application, etc.); a respective software application typically has, at least when executing, an application state, indicating the state of the software application and its components (e.g., gesture recognizers and delegates); see application internal state 317 (Figure 3B), described below; and
- device/global internal state 134, which includes one or more of: application state, indicating the state of software applications and their components (e.g., gesture

recognizers and delegates); display state, indicating what applications, views or other information occupy various regions of touch-sensitive display 156 or display 126; sensor state, including information obtained from the device's various sensors 130, input devices 128, and/or touch-sensitive display 156; and location information concerning the device's location and/or attitude.

[0046] Each of the above identified elements may be stored in one or more of the previously mentioned memory devices, and corresponds to a set of instructions for performing functions described herein. The set of instructions can be executed by one or more processors (e.g., one or more CPUs 110). The above identified modules or programs (i.e., sets of instructions) need not be implemented as separate software programs, procedures or modules, and thus various subsets of these modules may be combined or otherwise rearranged in various embodiments. In some embodiments, memory 111 may store a subset of the modules and data structures identified above. Furthermore, memory 111 may store additional modules and data structures not described above.

[0047] Figure 2 is a diagram of input/output processing stack 200 of an exemplary electronic device or apparatus (e.g., device 102 or 104) according to some embodiments of the invention. Hardware (e.g., electronic circuitry) 212 of the device is at the base level of the input/output processing stack 200. Hardware 212 can include various hardware interface components, such as the components depicted in Figures 1A and/or 1B. Hardware 212 can also include one or more of above mentioned sensors 130. All the other elements (132, 204-210) of input/output processing stack 200 are software procedures, or portions of software procedures, that process inputs received from hardware 212 and generate various outputs that are presented through a hardware user interface (e.g., one or more of a display, speakers, device vibration actuator).

[0048] A driver or a set of drivers 210 communicates with hardware 212. Drivers 210 can receive and process input data received from hardware 212. Core Operating System ("OS") 208 can communicate with driver(s) 210. Core OS 208 can process raw input data received from driver(s) 210. In some embodiments, drivers 210 can be considered to be a part of core OS 208.

[0049] A set of OS application programming interfaces ("OS APIs") 206, are software procedures that communicate with core OS 208. In some embodiments, APIs 206 are included in the device's operating system, but at a level above core OS 208. APIs 206

are designed for use by applications running on the electronic devices or apparatuses discussed herein. User interface (UI) APIs 204 can utilize OS APIs 206. Application software (“applications”) 132 running on the device can utilize UI APIs 204 in order to communicate with the user. UI APIs 204 can, in turn, communicate with lower level elements, ultimately communicating with various user interface hardware, *e.g.*, multitouch display 156.

[0050] While each layer input/output processing stack 200 can utilize the layer underneath it, that is not always required. For example, in some embodiments, applications 132 can occasionally communicate with OS APIs 206. In general, layers at or above OS API layer 206 may not directly access Core OS 208, driver(s) 210, or hardware 212, as these layers are considered private. Applications in layer 132 and UI API 204 usually direct calls to the OS API 206, which in turn, accesses the layers Core OS 208, driver(s) 210, and hardware 212.

[0051] Stated in another way, one or more hardware elements 212 of electronic device 102 or 104, and software running on the device, such as, for example, drivers 210 (depicted in Figure 2), core OS (operating system) 208 (depicted in Figure 2), operating system API software 206 (depicted in Figure 2), and Application and User Interface API software 204 (depicted in Figure 2) detect input events (which may correspond to sub-events in a gesture) at one or more of the input device(s) 128 and/or a touch-sensitive display 156 and generate or update various data structures (stored in memory of device 102 or 104) used by a set of currently active event recognizers to determine whether and when the input events correspond to an event to be delivered to application 132. Embodiments of event recognition methodologies, apparatus and computer program products are described in more detail below.

[0052] Figure 3A depicts an exemplary view hierarchy 300, which in this example is a search program displayed in outermost view 302. Outermost view 302 generally encompasses the entire user interface a user may directly interact with, and includes subordinate views, *e.g.*,

- search results panel 304, which groups search results and can be scrolled vertically;
- search field 306, which accepts text inputs; and
- a home row 310, which groups applications for quick access.

2016204905 13 Jul 2016

[0053] In this example, each subordinate view includes lower-level subordinate views. In other examples, the number of view levels in the hierarchy 300 may differ in different branches of the hierarchy, with one or more subordinate views having lower-level subordinate views, and one or more other subordinate views not have any such lower-level subordinate views. Continuing with the example shown in Figure 3A, search results panel 304 contains separate subordinate views 305 (subordinate to panel 304) for each search result. Here, this example shows one search result in a subordinate view called the maps view 305. Search field 306 includes a subordinate view herein called clear contents icon view 307, which clears the contents of the search field when a user performs a particular action (e.g., a single touch or tap gesture) on the clear contents icon in view 307. Home row 310 includes subordinate views 310-1, 310-2, 310-3, and 310-4, which respectively correspond to a contacts application, an email application, a web browser, and an iPod music interface.

[0054] A touch sub-event 301-1 is represented in outermost view 302. Given the location of touch sub-event 301-1 over both the search results panel 304, and maps view 305, the touch sub-event is also represented over those views as 301-2 and 301-3, respectively. Actively involved views of the touch sub-event include the views search results panel 304, maps view 305 and outermost view 302. Additional information regarding sub-event delivery and actively involved views is provided below with reference to Figures 3B and 3C.

[0055] Views (and corresponding programmatic levels) can be nested. In other words, a view can include other views. Consequently, the software element(s) (e.g., event recognizers) associated with a first view can include or be linked to one or more software elements associated with views within the first view. While some views can be associated with applications, others can be associated with high level OS elements, such as graphical user interfaces, window managers, etc.

[0056] Figure 3B is a block diagram illustrating exemplary components for event handling (e.g., event handling components 390) in accordance with some embodiments. In some embodiments, memory 111 (in Figures 1A and 1B) includes event recognizer global methods 311 (e.g., in operating system 118) and a respective application 132-1.

[0057] In some embodiments, event recognizer global methods 311 include event monitor 312, hit view determination module 313, active event recognizer determination module 314, and event dispatcher module 315. In some embodiments, event recognizer global methods 311 are located within event delivery system 130. In some embodiments, event recognizer global methods 311 are implemented in operating system 118.

Alternatively, event recognizer global methods 311 are implemented in application 132-1. In yet other embodiments, event recognizer global methods 311 are implemented as a stand-alone module, or a part of another module stored in memory 111 (e.g., a contact/motion module (not depicted)).

[0058] Event monitor 312 receives event information from sensors 130, touch-sensitive display 156, and/or input devices 128. Event information includes information about an event (e.g., a user touch on touch-sensitive display 156, as part of a multi-touch gesture or a motion of device 102 or 104) and/or a sub-event (e.g., a movement of a touch across touch-sensitive display 156). For example, event information for a touch event includes one or more of: a location and time stamp of a touch. Similarly, event information for a swipe event includes two or more of: a location, time stamp, direction, and speed of a swipe. Sensors 130, touch-sensitive display 156, and input devices 128 transmit information event and sub-event information to event monitor 312 either directly or through a peripherals interface, which retrieves and stores event information. Sensors 130 include one or more of: proximity sensor, accelerometer(s), gyroscopes, microphone, and video camera. In some embodiments, sensors 130 also include input devices 128 and/or touch-sensitive display 156.

[0059] In some embodiments, event monitor 312 sends requests to sensors 130 and/or the peripherals interface at predetermined intervals. In response, sensors 130 and/or the peripherals interface transmit event information. In other embodiments, sensors 130 and the peripheral interface transmit event information only when there is a significant event (e.g., receiving an input beyond a predetermined noise threshold and/or for more than a predetermined duration).

[0060] Event monitor 312 receives event information and determines the application 132-1 and application view 316-2 of application 132-1 to which to deliver the event information.

[0061] In some embodiments, event recognizer global methods 311 also include a hit view determination module 313 and/or an active event recognizer determination module 314.

[0062] Hit view determination module 313 provides software procedures for determining where an event or a sub-event has taken place within one or more views, when touch-sensitive display 156 displays more than one view. Views are made up of controls and other elements that a user can see on the display.

2016204905 13 Jul 2016

[0063] Another aspect of the user interface associated with an application 132-1 is a set views 316, sometimes herein called application views or user interface windows, in which information is displayed and touch-based gestures occur. The application views (of a respective application) in which a touch is detected may correspond to a particular view within a view hierarchy of the application. For example, the lowest level view in which a touch is detected may be called the hit view, and the set of events that are recognized as proper inputs may be determined based, at least in part, on the hit view of the initial touch that begins a touch-based gesture.

[0064] Hit view determination module 313 receives information related to events and/or sub-events. When an application has multiple views organized in a hierarchy, hit view determination module 313 identifies a hit view as the lowest view in the hierarchy which should handle the event or sub-event. In most circumstances, the hit view is the lowest level view in which an initiating event or sub-event occurs (i.e., the first event or sub-event in the sequence of events and/or sub-events that form a gesture). Once the hit view is identified by the hit view determination module, the hit view typically receives all events and/or sub-events related to the same touch or input source for which it was identified as the hit view.

[0065] Active event recognizer determination module 314 determines which view or views within a view hierarchy should receive a particular sequence of events and/or sub-events. In some application contexts, active event recognizer determination module 314 determines that only the hit view should receive a particular sequence of events and/or sub-events. In other application contexts, active event recognizer determination module 314 determines that all views that include the physical location of an event or sub-event are actively involved views, and therefore determines that all actively involved views should receive a particular sequence of events and/or sub-events. In other application contexts, even if touch events and/or sub-events are entirely confined to the area associated with one particular view, views higher in the hierarchy still remain as actively involved views.

[0066] Event dispatcher module 315 dispatches the event information to an event recognizer (also called herein “gesture recognizer”) (e.g., event recognizer 320-1). In embodiments including active event recognizer determination module 314, event dispatcher module 315 delivers the event information to an event recognizer determined by active event recognizer determination module 314. In some embodiments, event dispatcher module 315

stores in an event queue the event information, which is retrieved by a respective event recognizer 320 (or event receiver 331 in a respective event recognizer 320).

[0067] In some embodiments, application 132-1 includes application internal state 317, which indicates the current application view(s) displayed on touch-sensitive display 156 when the application is active or executing. In some embodiments, device/global internal state 134 is used by event recognizer global methods 311 to determine which application(s) is(are) currently active, and application internal state 317 is used by event recognizer global methods 311 to determine application views 316 to which to deliver event information.

[0068] In some embodiments, application internal state 317 includes additional information (e.g., 344, Figure 3C), such as one or more of: resume information to be used when application 132-1 resumes execution, user interface state information that indicates information being displayed or that is ready for display by application 132-1, a state queue for enabling the user to go back to a prior state or view of application 132-1, and a redo/undo queue of previous actions taken by the user. In some embodiments, application internal state 317 further includes contextual information/text and metadata 318.

[0069] In some embodiments, application 132-1 includes one or more application views 316, each of which includes instructions for handling touch events that occur within a respective view of the application's user interface. At least one application view 316 of the application 132-1 includes one or more event recognizers 320 and one or more event handlers 322. Typically, a respective application view 316 includes a plurality of event recognizers 320 and a plurality of event handlers 322. In other embodiments, one or more of event recognizers 320 are part of a separate module, such as a user interface kit (not shown) or a higher level object from which application 132-1 inherits methods and other properties. In some embodiments, a respective application view 316 also includes one or more of: data updater, object updater, GUI updater, and/or event data received.

[0070] A respective event recognizer 320-1 receives event information from event dispatcher module 315, and identifies an event from the event information. Event recognizer 320-1 includes event receiver 331 and event comparator 332.

[0071] The event information includes information about an event (e.g., a touch) or a sub-event (e.g., a touch movement). Depending on the event or sub-event, the event information also includes additional information, such as location of the event or sub-event. When the event or sub-event concerns motion of a touch, the event information may also

include speed and direction of the sub-event. In some embodiments, events include rotation of the device from one orientation to another (e.g., from a portrait orientation to a landscape orientation, or vice versa), and the event information includes corresponding information about the current orientation (also called device attitude) of the device.

[0072] Event comparator 332 compares the event information to one or more predefined gesture definitions (also called herein “event definitions”) and, based on the comparison, determines an event or sub-event, or determines or updates the state of an event or sub-event. In some embodiments, event comparator 332 includes one or more gesture definitions 333 (as described above, also called herein “event definitions”). Gesture definitions 333 contain definitions of gestures (e.g., predefined sequences of events and/or sub-events), for example, gesture 1 (334-1), gesture 2 (334-2), and others. In some embodiments, sub-events in gesture definitions 333 include, for example, touch begin, touch end, touch movement, touch cancellation, and multiple touching. In one example, the definition for gesture 1 (334-1) is a double tap on a displayed object. The double tap, for example, comprises a first touch (touch begin) on the displayed object for a predetermined phase of the gesture, a first lift-off (touch end) for a next predetermined phase of the gesture, a second touch (touch begin) on the displayed object for a subsequent predetermined phase of the gesture, and a second lift-off (touch end) for a final predetermined phase of the gesture. In another example, the definition for gesture 2 (334-2) is a dragging on a displayed object. The dragging, for example, comprises a touch (or contact) on the displayed object, a movement of the touch across touch-sensitive display 156, and lift-off of the touch (touch end).

[0073] In some embodiments, event recognizer 320-1 also includes information for event delivery 335. Information for event delivery 335 includes references to corresponding event handlers 322. Optionally, information for event delivery 335 includes action-target pair(s). In some embodiments, in response to recognizing a gesture (or a part of a gesture), event information (e.g., action message(s)) is sent to one or more targets identified by the action-target pair(s). In other embodiments, in response to recognizing a gesture (or a part of a gesture), the action-target pair(s) are activated.

[0074] In some embodiments, gesture definitions 333 include a definition of a gesture for a respective user-interface object. In some embodiments, event comparator 332 performs a hit test to determine which user-interface object is associated with a sub-event. For example, in an application view in which three user-interface objects are displayed on touch-

sensitive display 156, when a touch is detected on touch-sensitive display 156, event comparator 332 performs a hit test to determine which of the three user-interface objects, if any, is associated with the touch (event). If each displayed object is associated with a respective event handler 322, event comparator 332 uses the result of the hit test to determine which event handler 322 should be activated. For example, event comparator 332 selects an event handler 322 associated with the event and the object triggering the hit test.

[0075] In some embodiments, the definition for a respective gesture 333 also includes delayed actions that delay delivery of the event information until after it has been determined whether the sequence of events and/or sub-events does or does not correspond to the event recognizer's event type.

[0076] When a respective event recognizer 320-1 determines that the series of events and/or sub-events do not match any of the events in gesture definitions 333, the respective event recognizer 320-1 enters an event failed state, after which the respective event recognizer 320-1 disregards subsequent events and/or sub-events of the touch-based gesture. In this situation, other event recognizers, if any, that remain active for the hit view continue to track and process events and/or sub-events of an ongoing touch-based gesture.

[0077] In some embodiments, a respective event recognizer 320-1 includes event recognizer state 336. Event recognizer state 336 includes a state of the respective event recognizer 320-1. Examples of event recognizer states are described in more detail below with reference to Figures 4A-4D.

[0078] In some embodiments, event recognizer state 336 includes recognizer metadata and properties 337-1. In some embodiments, recognizer metadata and properties 337-1 include one or more of the following: A) configurable properties, flags, and/or lists that indicate how the event delivery system should perform event and/or sub-event delivery to actively involved event recognizers; B) configurable properties, flags, and/or lists that indicate how event recognizers interact with one another; C) configurable properties, flags, and/or lists that indicate how event recognizers receive event information; D) configurable properties, flags, and/or lists that indicate how event recognizers may recognize a gesture; E) configurable properties, flags, and/or lists that indicate whether events and/or sub-events are delivered to varying levels in the view hierarchy; and F) references to corresponding event handlers 322.

[0079] In some embodiments, event recognizer state 336 includes event/touch metadata 337-2. Event/touch metadata 337-2 includes event/touch information about a respective event/touch that has been detected and corresponds to gesture definitions 333. The event/touch information includes one or more of: a location, time stamp, speed, direction, distance, scale (or change in scale), and angle (or change in angle) of the respective event/touch.

[0080] In some embodiments, a respective application view includes one or more delegates 321. A respective delegate 321 is assigned to a respective event recognizer 320. Alternately, a respective event recognizer 320 has a corresponding delegate 321, but the delegate 321 is not necessarily assigned to the respective recognizer 320 at a runtime, and instead the delegate for an event recognizer may be established prior to execution of the application (e.g., the delegate for an event recognizer may be indicated by the delegate property of an application view, established when the corresponding applicative view 316 is initialized). In some embodiments, some event recognizers do not have an assigned (or corresponding) delegate. Event recognizers lacking corresponding delegates perform in accordance with default rules, such as default rules governing event recognition exclusivity. In some embodiments, some event recognizers have multiple assigned (or corresponding) delegates. Delegates modify the behavior of the corresponding event recognizer, and can also be used to coordinate the behavior of multiple event recognizers. In some embodiments described below, a delegate, when assigned to a respective event recognizer, modifies multiple aspects of the behavior of the respective event recognizer.

[0081] In some embodiments, a respective event recognizer 320 activates event handler 322 associated with the respective event recognizer 320 when one or more particular events and/or sub-events of a gesture are recognized. In some embodiments, respective event recognizer 320 delivers event information associated with the event to event handler 322.

[0082] Event handler 322, when activated, performs one or more of: creating and/or updating data, creating and updating objects, and preparing display information and sending it for display on display 126 or touch-sensitive display 156.

[0083] In some embodiments, a respective application view 316-2 includes view metadata 323. View metadata 323 include data regarding a view. Optionally, view metadata includes the following properties, which influence event and/or sub-event delivery to event recognizers:

- stop property 324-1, which, when set for a view prevents event and/or sub-event delivery to event recognizers associated with the view as well as its ancestors in the view hierarchy;
- skip property 324-2, which, when set for a view prevents event and/or sub-event delivery to event recognizers associated with that view, but permits event and/or sub-event delivery to its ancestors in the view hierarchy;
- NoHit skip property 324-3, which, when set for a view, prevents delivery of events and/or sub-events to event recognizers associated with the view unless the view is the hit view; as discussed above, the hit view determination module 313 identifies a hit-view as the lowest view in the hierarchy which should handle the sub-event; and
- other view metadata 324-4.

[0084] In some embodiments, a first actively involved view within the view hierarchy may be configured to prevent delivery of a respective sub-event to event recognizers associated with that first actively involved view. This behavior can implement the skip property 324-2. When the skip property is set for an application view, delivery of the respective sub-event is still performed for event recognizers associated with other actively involved views in the view hierarchy.

[0085] Alternately, a first actively involved view within the view hierarchy may be configured to prevent delivery of a respective sub-event to event recognizers associated with that first actively involved view unless the first actively involved view is the hit view. This behavior can implement the conditional NoHit skip property 324-3.

[0086] In some embodiments, a second actively involved view within the view hierarchy is configured to prevent delivery of the respective sub-event to event recognizers associated with the second actively involved view and to event recognizers associated with ancestors of the second actively involved view. This behavior can implement the stop property 324-1.

[0087] It shall be understood that the foregoing discussion regarding event handling of user touches on touch-sensitive displays also applies to other forms of user inputs to operate electronic device 102 or 104 with input-devices, not all of which are initiated on touch screens, *e.g.*, coordinating mouse movement and mouse button presses with or without single or multiple keyboard presses or holds, user movements, taps, drags, scrolls, etc., on

touch-pads, pen stylus inputs, movement (e.g., rotation) of the device, oral instructions, detected eye movements, biometric inputs, and/or any combination thereof, which may be utilized as inputs corresponding to events and/or sub-events which define a gesture to be recognized.

[0088] Figure 3C is a block diagram illustrating exemplary classes and instances of gesture recognizers (e.g., event handling components 390) in accordance with some embodiments.

[0089] A software application (e.g., application 132-1) has one or more event recognizers 340. In some embodiments, a respective event recognizer (e.g., 340-2) is an event recognizer class. The respective event recognizer (e.g., 340-2) includes event recognizer specific code 341 (e.g., a set of instructions defining the operation of event recognizers) and state machine 342.

[0090] In some embodiments, application state 317 of a software application (e.g., application 132-1) includes instances of event recognizers. Each instance of an event recognizer is an object having a state (e.g., event recognizer state 336). "Execution" of a respective event recognizer instance is implemented by executing corresponding event recognizer specific code (e.g., 341) and updating or maintaining the state 336 of the event recognizer instance 343. The state 336 of event recognizer instance 343 includes the state 338 of the event recognizer instance's state machine 342.

[0091] In some embodiments, application state 317 includes a plurality of event recognizer instances 343, each corresponding to an event recognizer that has been bound (also called "attached") to a view of the application. In some embodiments, application state 317 includes a plurality of instances (e.g., 343-1 to 343-L) of a respective event recognizer (e.g., 340-2). In some embodiments, application state 317 includes instances 343 of a plurality of event recognizers (e.g., 340-1 to 340-R).

[0092] In some embodiments, a respective instance 343-2 of a gesture recognizer includes event recognizer state 336. As discussed above, event recognizer state 336 includes recognizer metadata and properties 337-1 and event/touch metadata 337-2. Event recognizer state 336 also includes view hierarchy reference(s) 337-3, indicating to which view the respective instance 343-2 of the gesture recognizer is attached.

[0093] In some embodiments, recognizer metadata and properties 337-1 include the following, or a subset or superset thereof:

- exclusivity flag 339, which, when set for an event recognizer, indicates that upon recognition of a gesture by the event recognizer, the event delivery system should stop delivering events and/or sub-events to any other event recognizers of the actively involved views (with the exception of any other event recognizers listed in an exception list 353); when receipt of an event or sub-event causes a particular event recognizer to enter the exclusive state, as indicated by its corresponding exclusivity flag 339, then subsequent events and/or sub-events are delivered only to the event recognizer in the exclusive state (as well as any other event recognizers listed in an exception list 353);
- exclusivity exception list 353; when included in the event recognizer state 336 for a respective event recognizer, this list 353 indicates the set of event recognizers, if any, that are to continue receiving events and/or sub-events even after the respective event recognizer has entered the exclusive state; for example, if the event recognizer for a single tap event enters the exclusive state, and the currently involved views include an event recognizer for a double tap event, then the list 353 would list the double tap event recognizer so that a double tap event can be recognized even after a single tap event has been detected. Accordingly, the exclusivity exception list 353 permits event recognizers to recognize different gestures that share common sequences of events and/or sub-events, *e.g.*, a single tap gesture recognition does not preclude subsequent recognition of a double or triple tap gesture by other event recognizers;
- wait-for list 351; when included in the event recognizer state 336 for a respective event recognizer, this list 351 indicates the set of event recognizers, if any, that must enter the event failed or event canceled state before the respective event recognizer can recognize a respective event; in effect, the listed event recognizers have higher priority for recognizing an event than the event recognizer with the wait-for list 351;
- delay touch began flag 352, which, when set for an event recognizer, causes the event recognizer to delay sending events and/or sub-events (including a touch begin or finger down sub-event, and subsequent events) to the event recognizer's respective hit view until after it has been determined that the sequence of events and/or sub-events does not correspond to this event recognizer's gesture type; this flag can be used to prevent the hit view from ever seeing any of the events and/or sub-events in the case where the gesture is recognized; when the event recognizer fails to recognize a gesture, the touch began sub-event (and subsequent touch end sub-event) can be

delivered to the hit view; in one example, delivering such sub-events to the hit view causes the user interface to briefly highlight an object, without invoking the action associated with that object;

- delay touch end flag 363, which, when set for an event recognizer, causes the event recognizer to delay sending a sub-event (e.g., a touch end sub-event) to the event recognizer's respective hit view or level until it has been determined that the sequence of sub-events does not correspond to this event recognizer's event type; this can be used to prevent the hit view from acting upon a touch end sub-event, in case the gesture is recognized late; as long as the touch end sub-event is not sent, a touch canceled can be sent to the hit view or level; if an event is recognized, the corresponding action by an application is preformed, and the touch end sub-event is delivered to the hit view or level; and
- touch cancellation flag 364, which, when set for an event recognizer, causes the event recognizer to send touch or input cancellation to the event recognizer's respective hit view when it has been determined that the sequence of events and/or sub-events does not correspond to this event recognizer's gesture type; the touch or input cancellation sent to the hit view indicates that a prior event and/or sub-event (e.g., a touch began sub-event) has been cancelled; the touch or input cancellation may cause the event recognizer's state to enter the event canceled state 418 (in Figure 4B).

[0094] In some embodiments, one or more event recognizers may be adapted to delay delivering one or more sub-events of the sequence of sub-events until after the event recognizer recognizes the event. This behavior reflects a delayed event. For example, consider a single tap gesture in a view for which multiple tap gestures are possible. In that case, a tap event becomes a "tap + delay" recognizer. In essence, when an event recognizer implements this behavior, the event recognizer will delay event recognition until it is certain that the sequence of sub-events does in fact correspond to its event definition. This behavior may be appropriate when a recipient view is incapable of appropriately responding to cancelled events. In some embodiments, an event recognizer will delay updating its event recognition status to its respective actively involved view until the event recognizer is certain that the sequence of sub-events does not correspond to its event definition. Delay touch began flag 352, delay touch end flag 363, and touch cancellation flag 364 are provided to tailor sub-event delivery techniques, as well as event recognizer and view status information updates to specific needs.

[0095] In some embodiments, recognizer metadata and properties 337-1 include the following, or a subset or superset thereof:

- state machine state/phase 338, which indicates the state of a state machine (e.g., 342) for the respective event recognizer instance (e.g., 343-2); state machine state/phase 338 can have various state values, such as “event possible”, “event recognized”, “event failed”, and others, as described below; alternatively or additionally, state machine state/phase 338 can have various phase values, such as “touch phase began” which can indicate that the touch data structure defines a new touch that has not been referenced by previous touch data structures; a “touch phase moved” value can indicate that the touch being defined has moved from a prior position; a “touch phase stationary” value can indicate that the touch has stayed in the same position; a “touch phase ended” value can indicate that the touch has ended (e.g., the user has lifted his/her finger from the surface of a multi touch display); a “touch phase cancelled” value can indicate that the touch has been cancelled by the device; a cancelled touch can be a touch that is not necessarily ended by a user, but which the device has determined to ignore; for example, the device can determine that the touch is being generated inadvertently (i.e., as a result of placing a portable multi touch enabled device in one’s pocket) and ignore the touch for that reason; each value of state machine state/phase 338 can be an integer number (called herein “gesture recognizer state value”);
- action-target pair(s) 345, where each pair identifies a target to which the respective event recognizer instance send the identified action message in response to recognizing an event or touch as a gesture or a part of a gesture;
- delegate 346, which is a reference to a corresponding delegate when a delegate is assigned to the respective event recognizer instance; when a delegate is not assigned to the respective event recognizer instance, delegate 346 contains a null value; and
- enabled property 347, indicating whether the respective event recognizer instance is enabled; in some embodiments, when the respective event recognizer instance is not enabled (e.g., disabled), the respective event recognizer instance does not process events or touches.

[0096] In some embodiments, exception list 353 can also be used by non-exclusive event recognizers. In particular, when a non-exclusive event recognizer recognizes an event or sub-event, subsequent events and/or sub-events are not delivered to the exclusive event recognizers associated with the currently active views, except for those exclusive event recognizers listed in exception list 353 of the event recognizer that recognized the event or sub-event.

[0097] In some embodiments, event recognizers may be configured to utilize the touch cancellation flag 364 in conjunction with the delay touch end flag 363 to prevent unwanted events and/or sub-events from being delivered to the hit view. For example, the definition of a single tap gesture and the first half of a double tap gesture are identical. Once a single tap event recognizer successfully recognizes a single tap, an undesired action could take place. If the delay touch end flag is set, the single tap event recognizer is prevented from sending sub-events to the hit view until a single tap event is recognized. In addition, the wait-for list of the single tap event recognizer may identify the double-tap event recognizer, thereby preventing the single tap event recognizer from recognizing a single tap until the double-tap event recognizer has entered the event impossible state. The use of the wait-for list avoids the execution of actions associated with a single tap when a double tap gesture is performed. Instead, only actions associated with a double tap will be executed, in response to recognition of the double tap event.

[0098] Turning in particular to forms of user touches on touch-sensitive surfaces, as noted above, touches and user gestures may include an act that need not be instantaneous, *e.g.*, a touch can include an act of moving or holding a finger against a display for a period of time. A touch data structure, however, defines the state of a touch (or, more generally, the state of any input source) at a particular time. Therefore, the values stored in a touch data structure may change over the course of a single touch, enabling the state of the single touch at different points in time to be conveyed to an application.

[0099] Each touch data structure can comprise various entries. In some embodiments, touch data structures may include data corresponding to at least the touch-specific entries in event/touch metadata 337-2 such as the following, or a subset or superset thereof:

- “first touch for view” entry 348, indicating whether the touch data structure defines the first touch for the particular view (since the view was instantiated);
- “per touch info” entry 349, including “time stamp” information, which indicates the particular time to which the touch data structure relates (e.g., the time of touch); optionally, “per touch info” entry 349 includes other information, such as a location of a corresponding touch; and
- optional “tap count” entry 350, indicating how many taps have been sequentially performed at the position of the initial touch; a tap can be defined as a quick pressing and lifting of a finger against a touch-sensitive panel at a particular position; multiple sequential taps can occur if the finger is again pressed and released in quick succession at the same position of the panel; an event delivery system 130 can count taps and relay this information to an application through “tap count” entry 350; multiple taps at the same location are sometimes considered to be a useful and easy to remember command for touch enabled interfaces; thus, by counting taps, event delivery system 130 can again alleviate some data processing from the application.

[00100] Thus, each touch data structure can define what is happening with a respective touch (or other input source) at a particular time (e.g., whether the touch is stationary, being moved, etc.) as well as other information associated with the touch (such as position). Accordingly, each touch data structure can define the state of a particular touch at a particular moment in time. One or more touch data structures referencing the same time can be added in a touch event data structure that can define the states of all touches a particular view is receiving at a moment in time (as noted above, some touch data structures may also reference touches that have ended and are no longer being received). Multiple touch event data structures can be sent to the software implementing a view as time passes, in order to provide the software with continuous information describing the touches that are happening in the view.

[00101] The ability to handle complex touch-based gestures, optionally including multi-touch gestures, can add complexity to the various software applications. In some cases, such additional complexity can be necessary to implement advanced and desirable interface features. For example, a game may require the ability to handle multiple simultaneous

2016204905 13 Jul 2016

touches that occur in different views, as games often require the pressing of multiple buttons at the same time, or combining accelerometer data with touches on a touch-sensitive surface. However, some simpler applications and/or views need not require advanced interface features. For example, a simple soft button (i.e., a button that is displayed on a touch-sensitive display) may operate satisfactorily with single touches, rather than multi-touch functionality. In these cases, the underlying OS may send unnecessary or excessive touch data (e.g., multi-touch data) to a software component associated with a view that is intended to be operable by single touches only (e.g., a single touch or tap on a soft button). Because the software component may need to process this data, it may need to feature all the complexity of a software application that handles multiple touches, even though it is associated with a view for which only single touches are relevant. This can increase the cost of development of software for the device, because software components that have been traditionally easy to program in a mouse interface environment (i.e., various buttons, etc.) may be much more complex in a multi-touch environment.

[00102] In order to reduce the complexity in recognizing complex touch-based gestures, delegates can be used to control the behavior of event recognizers in accordance with some embodiments. As described below, delegates can determine, for example, whether a corresponding event recognizer (or gesture recognizer) can receive the event (e.g., touch) information; whether the corresponding event recognizer (or gesture recognizer) can transition from an initial state (e.g., event possible state) of state machine to another state; and/or whether the corresponding event recognizer (or gesture recognizer) can simultaneously recognize the event (e.g., touch) as a corresponding gesture without blocking other event recognizer(s) (or gesture recognizer(s)) from recognizing the event or getting blocked by other event recognizer(s) (or gesture recognizer(s)) recognizing the event.

[00103] It shall be understood, however, that the foregoing discussion regarding the complexity of evaluating and processing user touches on touch-sensitive surfaces also applies to all forms of user inputs to operate electronic device 102 or 104, not all of which are initiated on touch screens, e.g., coordinating mouse movement and mouse button presses with or without single or multiple keyboard presses or holds, device rotations or other movements, user movements such as taps, drags, scrolls, etc., on touch-pads, pen stylus inputs, oral instructions, detected eye movements, biometric inputs, detected physiological change in a user, and/or any combination thereof, which may be utilized as inputs corresponding to events and/or sub-events which define an event to be recognized.

2016204905 13 Jul 2016

[00104] Figures 4A-4D are flow charts for exemplary state machines, according to some embodiments. Gesture recognizers may include a discrete gesture recognizer and a continuous gesture recognizer. A discrete gesture recognizer is typically useful in recognizing a brief gesture occurring within a predefined time period (e.g., tap or swipe gesture), but more fundamentally is for recognizing a gesture for which only one action message or one set of action messages needs to be delivered to the application upon recognition of the gesture. A continuous gesture recognizer is useful in recognizing a gesture that includes a movement of a touch (and therefore requires tracking of the touch location) (e.g., pan, pinch, or rotate gesture), and more fundamentally is for recognizing a gesture for which a sequence of action messages need to be delivered to the application over the course of the gesture. In some embodiments, discrete event recognizer state machine 400 and continuous event recognizer state machine 402 have different states.

[00105] Figure 4A depicts discrete event recognizer state machine 400 containing three states in accordance with some embodiments. By managing state transitions in event recognizer state machine 342 based on received events and/or sub-events, an event recognizer effectively expresses an event definition. For example, a tap gesture may be effectively defined by a sequence of two, or optionally, three sub-events. First, a touch should be detected, and this will be sub-event 1. For example, the touch sub-event may be a user's finger touching a touch-sensitive surface in a view that includes the event recognizer having event recognizer state machine 342. Second, an optional measured delay where the touch does not substantially move in any given direction (e.g., any movement of the touch position is less than a predefined threshold, which may be measured as a distance (e.g., 5 mm) or as a number of pixels (e.g., 5 pixels) on the display), and the delay is sufficiently short, would serve as sub-event 2. Finally, termination of the touch (e.g., liftoff of the user's finger from the touch-sensitive surface) will serve as sub-event 3. By coding the event recognizer state machine 342 to transition between states based upon receiving these sub-events, the event recognizer state machine 342 effectively expresses a tap gesture event definition. Discrete event recognizer state machine 400 is an exemplary implementation of event recognizer state machine 342 configured to recognize a tap gesture, described above.

[00106] Regardless of event type, event recognizer state machine 342 (including event recognizer state machine implemented as discrete event recognizer state machine 400) begins in event possible state 410, which indicates an initial state of the event recognizer state

machine. Event recognizer state machine 342 may progress to any of the remaining states depending on what event and/or sub-event is received.

[00107] Starting from event possible state 410, if an event or sub-event is received that is not the first event or sub-event in a gesture definition, discrete event recognizer state machine 400 will transition to event failed state 430.

[00108] Starting from event possible state 410, if an event or sub-event is received that, by itself comprises the gesture definition for a gesture, discrete event recognizer state machine 400 will transition to event recognized state 420. However, even if the received event or sub-event comprises the gesture definition for the gesture, discrete event recognized state machine 400 may nevertheless transition to event failed state 430 in accordance with metadata (e.g., a property) of the corresponding event recognizer, one or more values determined by a corresponding delegate, and/or the application state.

[00109] In some embodiments, after transitioning to event recognized state 420, the corresponding event recognizer checks (441) a delay flag (e.g., delay touch end flag 363). If the delay flag is raised (441=yes), the corresponding event recognizer delays (442) delivering event information until the delay flag is lowered.

[00110] In some embodiments, the corresponding event recognizer includes wait-for list 351, and the corresponding event recognizer waits for the event recognizers listed in wait-for list 351 to reach a certain state. For example, when a view includes a single tap gesture recognizer and a double tap gesture recognizer, a single tap gesture recognizer can be configured to wait for a double tap gesture recognizer to fail. In effect, transition of the single tap gesture recognizer to event recognized state 420 requires (or is conditioned upon) the failure of the double tap gesture recognizer to recognize the event. As a result, when there is a tap event, the single tap gesture recognizer recognizes the tap event as long as the tap event is not part of a multi-tap gesture.

[00111] After the delay and wait (442), if any, the corresponding gesture recognizer delivers events to the application (443). In some embodiments, events are delivered in the form of action messages. In some embodiments, action messages are delivered in accordance with action-target pair(s) 345. In some embodiments, the corresponding gesture recognizer activates action-target pair(s) 345.

[00112] Figure 4B depicts continuous event recognizer state machine 402 containing six states in accordance with some embodiments.

2016204905 13 Jul 2016

[00113] As discussed above, continuous event recognizer state machines 402 starts from event possible state 410.

[00114] Starting from event possible state 410, if an event or sub-event is received that is not part of a begin sequence of event(s) and/or sub-event(s) in a gesture definition, discrete event recognizer state machine 400 will transition to event failed state 430.

[00115] Starting from event possible state 410, if an event or sub-event is received that is part of a begin sequence of event(s) and/or sub-event(s) in a given gesture definition, continuous event recognizer state machine 402 will transition to event began state 412. Similar to discrete gesture recognizer 400, even if the received event or sub-event comprises part of a begin sequence of event(s) and/or sub-event(s) in the gesture definition, continuous event recognized state machine 402 may transition to event failed state 430 in accordance with metadata (e.g., a property) of the corresponding event recognizer, one or more values determined by a corresponding delegate, and/or the application state.

[00116] From event began state 412, if the next event or sub-event received is an intermediate event or sub-event, but not the final event or sub-event in the given gesture definition, continuous event recognizer state machine 402 will transition to and remain in event changed state 414. Continuous event recognizer state machine 402 can remain in event changed state 414 for as long as the sequence of received events and/or sub-events continues to be part of the gesture definition. If, at any time continuous event recognizer state machine 402 is in event changed state 414, and continuous event recognizer state machine 402 receives an event or sub-event that is not part of the gesture definition, it will transition to event failed state 430, thereby determining that the current event (if any) is not the type of event that corresponds to this event recognizer (i.e., the event recognizer corresponding to continuous event recognizer state machine 402). If, on the other hand, continuous event recognizer state machine 402 is in event began state 412 or event changed state 414, and continuous event recognizer state machine 402 receives the last event or sub-event in a gesture definition, it will transition to event ended state 416, thereby completing a successful event recognition.

[00117] In some embodiments, each gesture recognizer state has a gesture recognizer state value. In some embodiments, event recognized state 420 (for discrete event recognizer state machine 400) and event ended state 416 (for continuous event recognizer state machine 402) have an identical gesture recognizer state value, such that a software component

configured to response a recognition of a gesture by one type of gesture recognizer can also respond to the other type of gesture recognizer.

[00118] While in event began state 412 or event changed state 414, when a predefined interruption event (e.g., predefined in operating system 118 or control application 124, such as an incoming phone call) occurs, continuous event recognizer state machine 402 transitions to event canceled state 418.

[00119] Regardless of the gesture recognizer type, each gesture recognizer (e.g., 343) can be reset such that a corresponding event recognizer state machine returns (e.g., 342) to event possible state 410.

[00120] Figures 4C and 4D depict the role of delegates in state transitions in accordance with some embodiments. In Figures 4C and 4D, the actions (or decisions made) by one or more delegates is indicated by boxes with shadows (e.g., 450-456).

[00121] Figure 4C depicts the role of delegates in state transitions for discrete event recognizer state machine 400 in accordance with some embodiments. In the examples discussed below, state machine 400 corresponds to a particular discrete event recognizer that has a corresponding delegate.

[00122] Starting from event possible state 410, if an event or sub-event is detected, the delegate corresponding to an event recognizer decides whether the event recognizer should receive (450) the event or sub-event. If the delegate returns a value that prevents the corresponding event recognizer from receiving the event or sub-event, the corresponding event recognizer does not receive the event or sub-event (or disregards the event or sub-event). As a result, the corresponding event recognizer remains in event possible state 410. If there is no delegate preventing the corresponding event recognizer from receiving the event or sub-event, the default behavior for the corresponding event recognizer is to receive the event or sub-event.

[00123] It is noted that the "should receive" operation 450 by the delegates of a set of event recognizers can be used to determine which event recognizers receive which touches on a touch-sensitive display or surface. For example, in a view that allows a user to use two touches to individually and simultaneously reposition two objects, or to select two different objects, the delegates of two event recognizers can be configured to allow one event recognizer to receive only a first one of the two touches and to allow a second event recognizer to receive only a second one of the two touches. All information about each of

the two touches is therefore directed to only the event recognizer allowed, by its corresponding delegate, to receive that touch. Much more complex multi-touch inputs can also be recognized and processed through the use of multiple event recognizers and corresponding delegates that determine which touches are processed by which event recognizers.

[00124] If the event recognizer is allowed to receive the event or sub-event, the delegate corresponding to the event recognizer (or the control application 124 or operating system 118) decides whether the recognition of the event or sub-event by the event recognizer is blocked (451) by another event recognizer having already recognized the event. This initial level of blocking is based on a default exclusivity rule, and can be overridden by the delegate. If the recognition of the event or sub-event is blocked, the corresponding delegate (or operating system 118 or control application 124) also decides whether simultaneous recognition of the event by the event recognizer is allowed (452) in accordance with one or more values determined by the delegate. For example, if the event recognizer is on the exclusivity exception list 353 of the event recognizer that initially recognized the event, the delegate allows simultaneous recognition by both event recognizers. In another example, if the exclusivity flag 339 of the event recognizer is not set, the delegate allows simultaneous recognition by both event recognizers. If the simultaneous recognition is not allowed, the event recognizer transitions to event failed state 430.

[00125] If the corresponding event recognizer is not blocked (451-No) from recognizing the event or sub-event, or if simultaneous recognition is allowed (452-Yes), the corresponding event recognizer determines whether the event or sub-event matches (453) a corresponding gesture definition. If the event or sub-event does not match (453-No) the corresponding gesture definition, the corresponding gesture recognizer transitions to event failed state 430.

[00126] If the event or sub-event matches (453-Yes) the corresponding gesture definition, the corresponding delegate (or operating system 118 or control application 124) decides whether it can transition (“should begin” 454) out of event possible state 410 in accordance with one or more values determined by the delegate. If the event recognizer is not allowed (454-No) by the delegate to transition out of event possible state 410, the corresponding event recognizer is put into event failed state 430. If the event recognizer is allowed (454-Yes) to transition out of event possible state 410, the corresponding event recognizer transitions into event recognized state 420.

2016204905 13 Jul 2016

[00127] When the corresponding event recognizer transitions into event recognized state 420, the corresponding event recognizer (or operating system 118 or control application 124) also decides whether to allow the recognition of the event or sub-event by the other event recognizers (455). In some embodiments, the default is to prevent all other event recognizers from recognizing the same event, unless the delegate (or the application) of at least one of the event recognizers sets a property to allow simultaneous recognition. If the delegate corresponding to the event recognizer which has recognized the event or sub-event determined that the delegate will allow (455-Yes) other event recognizers to recognize the event or sub-event, the delegate (or operating system 118 or control application 124) sets (456) a property of the other event recognizers such that they can recognize the event or sub-event simultaneously. If the delegate does not allow other event recognizers to recognize the event or sub-event, the other event recognizers are prevented from recognizing the event or sub-event.

[00128] In some embodiments, prior to preventing a respective event recognizer from recognizing an event or sub-event, the delegate of that event recognizer is also invoked (see 452) to see if it will allow simultaneous recognition of the event or sub-event. In these embodiments, simultaneous recognition can be enabled by either the delegate of the first event recognizer to recognize the event, or the delegate of a second event recognizer. As shown by 452 and 455 in Figure 4C, in these embodiments decisions about whether to allow simultaneous recognition are made only when an event matches the event definition of at least one event recognizer.

[00129] The above described delegate operations, when implemented in the delegates for a set of event recognizers used by an application view (or set of simultaneously displayed views), can be used to customize the interaction of the event recognizers. The delegates can implement exceptions to a default exclusivity rule, which otherwise allows only one event recognizer to recognize a gesture based on the same received event(s). The user of delegates to implement exceptions to the default exclusivity rule, and thereby allow simultaneous event recognition by compatible event recognizers, facilitates the implementation of many useful functions in software applications. The use of delegates to modify and control the behavior of event recognizers allows for a compact representation and implementation of complex relationships, such as mutually exclusive sets of mutually compatible gestures.

[00130] Figure 4D depicts the role of delegates in state transition for continuous event recognizer state machine 402 in accordance with some embodiments. In the examples

discussed below, state machine 402 corresponds to a particular continuous event recognizer that has a corresponding delegate. All the delegate operations shown in Figure 4C and discussed above with reference to Figure 4C are equally applicable to a continuous event recognizer that has a corresponding delegate, and therefore the delegate operations shown in Figure 4D have the same reference numbers as those in Figure 4C. The only difference is that the name of one state in the state machine has changed, from "event recognized" 420 in state machine 400 to "event began" 412 in state machine 402.

[00131] From event began state 412, the corresponding event recognizer transitions into other states as described above. For brevity, the transition from event changed state 414 to event failed state 416 is not depicted.

[00132] The following table presents in a tabular format the processing of an exemplary sub-event sequence (e.g., a single tap) as related to the states of event recognizers described above. In this example, the sub-event sequence comprises a single tap, and the view has two tap gesture recognizers: a single tap gesture recognizer and a double tap gesture recognizer. Also in this example, both gesture recognizers are configured to simultaneously receive and recognize the sub-event sequence. Simultaneous recognition can be allowed by a delegate assigned to the single tap gesture recognizer or a delegate assigned to the second tap gesture recognizer.

Sequence #	Sub-Event Sequence (single tap)	Single Tap Gesture Recognizer	Double Tap Gesture Recognizer
0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Possible
2	measure delay	Event Possible	Event Possible
3	detect finger liftoff	Event Recognized	Event Possible
4	measure delay	Event Recognized	Event Failed

[00133] Before delivery of sub-event information starts (sequence # 0), both gesture recognizers are in event possible state 410. Even after detecting a finger down sub-event (sequence #1) and measuring a delay (sequence # 2), both gesture recognizers remain in event possible state 410. In response to detecting a finger liftoff (sequence #3), the single

tap gesture recognizer transitions into event recognized state 420. After detecting additional delay, the single tap gesture recognizer remains in event recognized state 420 until it is reset, in which case the single tap gesture recognizer returns to event possible state 410. On the other hand, the double tap gesture recognizer transitions into event failed state 430 when the measured additional delay exceeds a predefined duration (e.g., during which the double tap gesture recognizer anticipates a second finger down sub-event).

[00134] The following table presents in a tabular format the processing of the exemplary sub-event sequence when the behavior of one gesture recognizer is modified. In this example, the sub-event sequence comprises a single tap, and the view has two tap gesture recognizers: a single tap gesture recognizer and a double tap gesture recognizer. Also in this example, the single tap gesture recognizer is not allowed by its delegate to receive the sub-events.

Sequence #	Sub-Event Sequence (single tap)	Single Tap Gesture Recognizer	Double Tap Gesture Recognizer
0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Possible
2	measure delay	Event Possible	Event Possible
3	detect finger liftoff	Event Possible	Event Possible
4	measure delay	Event Possible	Event Failed

[00135] Because the single tap gesture recognizer is not allowed by its delegate to receive the sub-events, the single tap gesture recognizer remains in event possible state 410. The double tap gesture recognizer transitions into event failed state 430 when the measured second delay exceeds the predefined threshold (sequence # 4).

[00136] The following table presents in a tabular format the processing of the exemplary sub-event sequence when the behavior of one gesture recognizer is modified. In this example, the sub-event sequence comprises a single tap, and the view has two tap gesture recognizers: a single tap gesture recognizer and a double tap gesture recognizer. Also in this

example, both gesture recognizers are not allowed to simultaneously recognize the sub-event sequence.

Sequence #	Sub-Event Sequence (single tap)	Single Tap Gesture Recognizer	Double Tap Gesture Recognizer
0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Possible
2	measure delay	Event Possible	Event Possible
3	detect finger liftoff	Event Recognized	Event Failed
4	measure delay	Event Recognized	Event Failed

[00137] Similar to what was described above, after detecting finger liftoff (sequence # 3), single tap gesture recognizer transitions from event possible state 410 to event recognized state 420. In general, a first gesture recognizer that recognizes the sub-event sequence blocks other gesture recognizers that have not yet recognized the sub-event sequence from recognizing the sub-event sequence. Unless a simultaneous recognition is allowed, blocked gesture recognizers transition into event failed state 430. In this case, because simultaneous recognition is not allowed, when the single tap gesture recognizer recognizes the sub-event sequence (at sequence # 3), the double tap gesture recognizer transitions into, and remains in, event failed state 430 until it is reset.

[00138] The following table presents in a tabular format the processing of the exemplary sub-event sequence when the behavior of one gesture recognizer is modified by its delegate, and operation of the two gesture recognizers is coordinated in accordance with actions taken by the delegate(s) of one or both recognizers. In this example, the sub-event sequence comprises a single tap, and the view has two tap gesture recognizers: a single tap gesture recognizer and a double tap gesture recognizer. Also in this example, the single tap gesture recognizer is not allowed to begin (or transition out of event possible state 410).

Sequence #	Sub-Event Sequence (single tap)	Single Tap Gesture Recognizer	Double Tap Gesture Recognizer
------------	---------------------------------	-------------------------------	-------------------------------

0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Possible
2	measure delay	Event Possible	Event Possible
3	detect finger liftoff	Event Failed	Event Possible
4	measure delay	Event Failed	Event Failed

[00139] After detecting finger liftoff (sequence # 3), single tap gesture recognizer attempts to transition from event possible state 410 to event recognized state 420. However, the delegate assigned to the single tap gesture recognizer does not allow the state transition into the event recognized state 420, and as a result, the single tap gesture recognizer transitions into event failed state 430. The double tap gesture recognizer transitions into event failed state 430 when the measured delay exceeds the predefined threshold (sequence # 4).

[00140] The following table presents in a tabular format the processing of the exemplary sub-event sequence when the behavior of one gesture recognizer is modified, and operation of two gesture recognizers is coordinated in accordance with actions taken by the delegate(s) of one or both recognizers. In this example, the sub-event sequence comprises a single tap, and the view has two tap gesture recognizers: a single tap gesture recognizer and a double tap gesture recognizer. Also in this example, the single tap gesture recognizer waits for (or requires) a failure of the double tap gesture recognizer.

Sequence #	Sub-Event Sequence (single tap)	Single Tap Gesture Recognizer	Double Tap Gesture Recognizer
0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Possible
2	measure delay	Event Possible	Event Possible
3	detect finger liftoff	Event Possible	Event Possible
4	measure delay	Event Recognized	Event Failed

[00141] After detecting finger liftoff (sequence # 3), single tap gesture recognizer attempts to transition from event possible state 410 to event recognized state 420. However, due to the “wait-for” requirement or the failure requirement (that the double tap gesture recognizer fail), the single tap gesture recognizer delays transitioning into event recognized state 420. When the double tap gesture recognizer fails because the measured second delay exceeds the predefined threshold (sequence # 4), the single tap gesture recognizer transitions into event recognized state 420. The “wait-for” requirement and/or the failure requirement may be implemented using delegates or in gesture recognizers.

[00142] The following table presents in a tabular format the processing of the exemplary sub-event sequence. In this example, the sub-event sequence comprises a pan gesture involving multiple intermediary sub-events, and the view has two gesture recognizers: a single tap gesture recognizer and a pan gesture recognizer. Also in this example, both gesture recognizers are allowed to simultaneously recognize the sub-event sequence.

Sequence #	Sub-Event Sequence (pan gesture)	Single Tap Gesture Recognizer	Pan Gesture Recognizer
0	before delivery starts	Event Possible	Event Possible
1	detect finger down	Event Possible	Event Began
2	measure delay	Event Possible	Event Began
3	detect finger movement	Event Failed	Event Changed
4	detect finger movement	Event Failed	Event Changed
5	detect finger movement	Event Failed	Event Changed
6	detect finger liftoff	Event Failed	Event Ended

2016204905 13 Jul 2016

[00143] Before delivery of sub-event information starts (sequence # 0), both gesture recognizers are in event possible state 410. Even after detecting a finger down sub-event (sequence #1) and measuring a delay (sequence # 2), the single tap gesture recognizer remains in event possible state 410, while the pan gesture recognizer transitions into event began state 412. In response to detecting a finger movement (sequence # 3), the single tap gesture recognizer transitions into event failed state 430 as the sub-event does not match with the gesture definition for a single tap. The single tap gesture recognizer remains in event failed state 430 thereafter until it is reset. However, the pan gesture recognizer transitions into event changed state 414 in response to detecting the finger movement (sequence #4), and in some embodiments, sends action message(s) including the new location of the finger contact. After detecting additional finger movements (sequence # 4 and 5), the pan gesture recognizer remains in event changed state 414, while sending action message(s) every time a finger movement is detected. When a finger liftoff is detected (sequence # 6), the pan gesture recognizer transitions into event ended state 416.

[00144] Turning to the flow of event information and the interaction between event recognizers, Figure 5A is a block diagram illustrating the flow of event information, according to some embodiments. Event dispatcher module 315 (e.g., in operating system 118 or control application 124) receives event information, and sends the event information to application (e.g., 132-1). In some embodiments, application 132-1 includes a plurality of views (e.g., 508, 510, and 512 corresponding to views 316) in view hierarchy 506 and a plurality of gesture recognizers (516-1 through 516-6) in the plurality of views. Application 132-1 also includes one or more event handlers 520, which correspond to the target values in target-action pairs (e.g., 522-1, 522-2, and 522-3). Event dispatcher module 315 receives hit view information from hit view determination module 313 and sends event information to the hit view (e.g., 512) or event recognizer(s) attached to the hit view (e.g., 512). In some embodiments, only a subset of gesture recognizers attached to the hit view are allowed to (or configured to) receive the event information (or touch information). Those gesture recognizers allowed to receive the event information are called herein “receiving gesture recognizers”. In Figure 5A, gesture recognizers 516-1 and 516-2 are in a set of receiving gesture recognizers 514. As a result, event dispatcher module 315 sends event information to both gesture recognizers 516-1 and 516-2 in the set of receiving gesture recognizers.

[00145] In some embodiments, gesture recognizers may block or prevent one another from recognizing the event or sub-event as a corresponding gesture. In this example, gesture

recognizer 1 (516-1) prevents gesture recognizer 2 (516-2) from recognizing the event or sub-event as a corresponding gesture. As a result, in this example, only gesture recognizer 1 (516-1) sends an action message (518) to a corresponding target-action pair (e.g., target:action 1 (522-1)).

[00146] Figures 5B and 5C are flow charts illustrating gesture recognition methods, according to some embodiments. Figure 5B illustrates a flow chart where a gesture recognizer invokes a corresponding delegate, and Figure 5C illustrates a flow chart where a software application invokes a delegate corresponding to a respective gesture recognizer. In Figures 5B and 5C, each column represents processes performed at each entity or component (e.g., software application, gesture recognizer, or delegate).

[00147] In Figure 5B, a software application (e.g., application 132-1) displays (530) one or more views of the plurality of views (e.g., 506, 508, 510). The plurality of views includes a plurality of gesture recognizers (e.g., 516-1 through 516-6). The software application (e.g., application 132-1) assigns (532) distinct delegates to at least a subset of the plurality of gesture recognizers. In some embodiments, a respective gesture recognizer is assigned (533-1) to a corresponding delegate. In some embodiments, a respective delegate is assigned (533-2) to a corresponding gesture recognizer. Alternately, the correspondence between a delegate and a gesture recognizer may be established prior to runtime. Throughout the following discussion, each reference to an assigned delegate may also mean a corresponding delegate, and each reference to a gesture recognizer to which a delegate has been assigned may also mean a gesture recognizer corresponding to a particular delegate.

[00148] The software application (e.g., application 132-1) detects (534) one or more events, and processes (536) each of the events using one or more of the gesture recognizers (e.g., 320).

[00149] The respective event is processed (538) at a respective gesture recognizer (of the one or more gesture recognizers (e.g., 320)). In order to explain operation of the delegates, we assume that a respective gesture recognizer that processes the event has a corresponding delegate. The respective gesture recognizer calls the assigned delegate, and the assigned delegate is executed (540) to determine one or more values in accordance with the application state. In response, the respective gesture recognizer conditionally sends (542) information corresponding to the respective event to the software application, in accordance with the one or more values determined by the assigned delegate.

[00150] The software application is executed (544) in accordance with information received from one or more of the gesture recognizers corresponding to one or more of the events.

[00151] In other words, in these embodiments, a respective gesture recognizer invokes an assigned delegate to obtain one or more values that determine the behavior of the gesture recognizer. As described above, the behavior of the gesture recognizer modified by its corresponding delegate includes whether to receive touch/event information, whether to transition out of the event possible state, and/or whether to allow simultaneous recognition. Operations by the delegate (sometimes with the coordinated action of the delegates of other gesture recognizers) also coordinate the operation of two or more gesture recognizers by controlling which gesture recognizers receive which touches, by determining which gesture recognizer is allowed to transition to the "event recognized" or "event began" state, and by allowing or disabling simultaneous recognition.

[00152] In Figure 5C, a software application (e.g., application 132-1) displays (530) one or more views of the plurality of views (e.g., 506, 508, 510). The plurality of views includes a plurality of gesture recognizers (e.g., 516-1 through 516-6). The software application (e.g., application 132-1) assigns (532) distinct delegates to at least a subset of the plurality of gesture recognizers. In some embodiments, a respective gesture recognizer is assigned (533-1) to a corresponding delegate. In some embodiments, a respective delegate is assigned (533-2) to a corresponding gesture recognizer. Alternately, the correspondence between a delegate and a gesture recognizer may be established prior to runtime.

[00153] The software application (e.g., application 132-1) detects (535) one or more touches, and processes (546) each of the one or more touches, using one or more of the gesture recognizers. In processing each of the one or more touches, the software application identifies (548) a set of candidate gesture recognizers of the plurality of gesture recognizers. In some embodiments, the candidate gesture recognizers are gesture recognizers attached to the hit view (e.g., gesture recognizers 516-1, 516-2, and 516-3 in Figure 5A).

[00154] The delegate assigned to a respective candidate gesture recognizer is executed (550) to obtain a "receive touch value" in accordance with the application state. The "receive touch value" is used to determine whether the respective candidate gesture recognizer can receive the event/touch information (e.g., "should receive" step 450 in Figures 4C-4D).

[00155] Based on the receive touch value obtained from a respective delegate, a set of receiving gesture recognizers is identified (552). The set of receiving gesture recognizers comprise (552) a subset of the candidate gesture recognizers. In some embodiments, the set of receiving gesture recognizers include all candidate gesture recognizers that do not have respective assigned delegates. If more than one of the candidate gesture recognizers has a corresponding delegate, the delegate of each such candidate gesture recognizer is executed to determine whether the candidate gesture recognizer can receive the event/touch information. The "receive touch values" obtained from the delegates corresponding to the candidate gesture recognizers are used to identify the set of receiving gesture recognizers.

[00156] The respective touch is processed (554) at the set of receiving gesture recognizers. If processing of the respective touch by a respective gesture recognizer results in the recognition of an event or gesture (see match definition 453, Figures 4C and 4D), the delegate (if any) corresponding to the respective gesture recognizer is called to determine if recognition of the event or gesture is allowed. This corresponds to the "should begin" operation 454, discussed above with reference to Figures 4C and 4D. The delegate returns one or more values indicating whether the state transition is to be allowed. The respective gesture recognizer conditionally sends (542) information corresponding to the respective event to the software application, in accordance with the one or more values determined by the assigned delegate. The software application is executed (545) in accordance with information received from one or more of the gesture recognizers corresponding to the respective touch.

[00157] In other words, in these embodiments, a software application (or the operating system 118 or control application 124) invokes the delegates corresponding to respective candidate gesture recognizers to obtain values that indicate which of the respective candidate gesture recognizers (if any) should process the respective touch. In addition, other aspects of the behavior of the gesture recognizers can be further modified by the assigned delegate.

[00158] Figures 6A-6B are flow charts illustrating an exemplary method of processing a respective event in accordance with information obtained from a delegate, according to some embodiments.

[00159] Method 600 is performed (602) at an electronic device (e.g., device 102 or 104) having one or more event sensors (e.g., 130) and configured to execute a software

application (e.g., 132) that includes a plurality of views (e.g., application views 316) and an application state of the software application (e.g., 317).

[00160] The device (604) displays one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more gesture recognizers (e.g., event recognizer 320-1). In some embodiments, at least a subset of the one or more displayed views includes one or more gesture recognizers, and the rest of the one or more displayed views do not include gesture recognizers.

[00161] A respective gesture recognizer of the one or more gesture recognizers has a corresponding delegate. In some embodiments, not all gesture recognizers have corresponding delegates (i.e., in some embodiments, some gesture recognizers do not have corresponding delegates). In some embodiments, the respective gesture recognizer corresponds to two or more delegates, where each delegate determines distinct values for the corresponding gesture recognizer for distinct conditions (e.g., a first delegate determines “should receive” 450, a second delegate determines “recognition blocked” 451, etc.). In some embodiments, two or more gesture recognizers correspond to (e.g., utilize) a same delegate.

[00162] In some embodiments, the device assigns (606) a respective delegate (e.g., delegate 321-1) to the respective gesture recognizer (e.g., 320-1) (e.g., see the description of step 532 in Figure 5B). Alternately, the respective gesture recognizer has a corresponding delegate, and thus a delegate does not need to be assigned at runtime. All references herein to the assigned delegate of an event/gesture recognizer shall be understood to be equally applicable to a corresponding delegate of an event/gesture recognizer, and all references to a corresponding delegate shall be understood to be equally applicable to an assigned delegate.

[00163] In some embodiments, the one or more displayed views include (608) a plurality of gesture recognizers, and the device assigns distinct delegates to at least a subset of the plurality of gesture recognizers. In other words, the device may have fewer delegates than the number of gesture recognizers, since some gesture recognizers may not have assigned delegates.

[00164] The device detects (610) one or more events. In some embodiments, the device detects one or more events using sensors 130, input devices 128, and/or touch-sensitive display 156.

2016204905 13 Jul 2016

[00165] The device processes (612) a respective event of the one or more events using the respective gesture recognizer. The processing of the respective event includes processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer (e.g., comparing the event and gesture definitions 333 using event comparator 332), executing the corresponding delegate to determine one or more values in accordance with the application state (e.g., 540 in Figure 5B), and conditionally sending information corresponding to the respective event (e.g., whether the gesture recognizer recognizes the event, such as “tap gesture” or “swipe gesture”, related event information, such as the location and time stamp of the event, and/or other additional information) to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate.

[00166] In some embodiments, the delegate has instructions for determining event recognizer properties (such as “should begin”, “should receive”, and “simultaneous recognition”), and when executed, returns one or more corresponding values. In some embodiments, values for the event recognizer properties can be set by the software application in accordance with the application state. In some embodiments, the values for the properties are predefined by developers. In some embodiments, the internal properties of a respective event/gesture recognizer have default values that can be overridden by the delegate corresponding to the event/gesture recognizer.

[00167] For example, the device sends information corresponding to the respective event when the gesture recognizer is allowed to recognize the event (e.g., based on the one or more values determined by the gesture recognizer's corresponding delegate, the one or more values indicating whether the gesture recognizer can transition out of event possible state 410 to event recognized state 420 or event began state 412 or whether the gesture recognizer can simultaneously recognize the event despite the presence of a blocking gesture recognizer). In some embodiments, the device sends information corresponding to the respective event only when the event matches a corresponding gesture definition or a part thereof. Furthermore, application states or other conditions may prevent the respective gesture recognizer from sending information corresponding to the respective event.

[00168] The device executes (614) the software application (e.g., 132-1) in accordance with information, received from the respective gesture recognizer, corresponding to the

respective event. For example, the software application (e.g., 132-1) includes a plurality of event handlers 322, and one or more of event handlers 322 are activated according to information received from the respective gesture recognizer (e.g., event handlers 322 listed in action-target pairs 345 are activated).

[00169] In some embodiments, the one or more event sensors (e.g., 130) include a touch-sensitive surface (e.g., 156 or a separate touch-sensitive surface) configured to detect one or more touches, and the one or more events include the one or more touches, and processing the respective event comprises processing a respective touch (616). In some embodiments, the one or more event sensors (e.g., 130) include accelerometers and the one or more events also include rotation or other movement of the electronic device.

[00170] In some embodiments, the device conditionally receives (618) the respective touch at the respective gesture recognizer in accordance with the one or more values determined by the assigned delegate. For example, the respective gesture recognizer receives the respective touch only when the one or more values (e.g., “receive touch value”) determined by the corresponding delegate allows the respective gesture recognizer to receive the respective touch (e.g., “should receive” 450 in Figures 4C-4D).

[00171] In some embodiments, processing the respective touch includes (620) the respective gesture recognizer disregarding the respective touch when the one or more values determined by the corresponding delegate matches predefined touch disregard criteria. In these embodiments, instead of conditionally receiving the respective touch as described in step 618, the respective gesture recognizer disregards the respective touch.

[00172] In some embodiments, processing the respective touch includes (622) blocking the respective gesture recognizer from receiving the respective touch when the one or more values determined by the corresponding delegate match predefined touch disregard criteria. In these embodiments, the gesture recognizer does not have a need for conditionally receiving or disregarding the respective touch, since the respective touch is blocked and therefore does not reach the respective gesture recognizer. In some embodiments, the blocking the respective gesture recognizer from receiving the respective touch includes instructing event dispatcher module 315 not to send event information to the corresponding gesture recognizer.

[00173] In some embodiments, processing the respective touch at the respective gesture recognizer includes (624), when the detected touch is consistent with the respective

gesture definition (e.g., the respective touch matches the gesture definition or a part thereof), enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate (e.g., “should begin” 454 in Figures 4C-4D). In some embodiments, the state transition is enabled when a state transition enable value (e.g., “should begin” value) is determined by the corresponding delegate to meet state transition criteria.

[00174] In some embodiments, processing the respective touch at the respective gesture recognizer includes (626), when the detected touch is consistent with the respective gesture definition, conditionally enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate. In other words, the state transition is conditionally enabled even if the corresponding delegate enables (e.g., does not block) the transition. For example, the condition for the state transition includes: whether the respective touch/event matches the gesture definition or a part thereof, whether the respective gesture recognizer is allowed to receive the respective touch/event, and/or whether the recognition of the respective touch/event is blocked.

[00175] In some embodiments, processing the respective touch at the respective gesture recognizer includes, when the detected touch is consistent with the respective gesture definition, (conditionally) disabling a corresponding state transition in the respective gesture recognizer when the state transition is prevented/disabled by another gesture recognizer that has also recognized a gesture. In particular, gesture recognizers can be paired (or grouped) so that one gesture recognizer can prevent the other gesture recognizer(s) from make a transition into event recognized state 420 or event began state 412 (e.g., when a first gesture recognizer is configured to prevent a second gesture recognizer, the first gesture recognizer, in recognizing an event/touch, prevents the second gesture recognizer from recognizing the event/touch, regardless of the values returned by the delegate corresponding to the second gesture recognizer).

[00176] In some embodiments, multiple gesture recognizers are listed based on priority (e.g., based on the sequence of the code, sequence of instantiation, view hierarchy corresponding to the respective gesture recognizer, or priority assigned by a developer or the software application). When two or more gesture recognizers simultaneously recognize a respective touch, the highest priority gesture recognizer blocks all other gesture recognizers from recognizing the respective touch.

2016204905 13 Jul 2016

[00177] In some embodiments, processing the respective touch at the respective gesture recognizer includes (628) simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by a delegate corresponding to the second gesture recognizer. For example, the delegate corresponding to the second gesture recognizer may allow the second gesture recognizer to process the gesture at the second gesture recognizer (e.g., step 452 in Figures 4C-4D), even though another gesture recognizer blocks the recognition of the event.

[00178] In some embodiments, processing the respective touch at the respective gesture recognizer includes (630) simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by the delegate corresponding to the respective gesture recognizer. For example, the delegate corresponding to the gesture recognizer may allow the second gesture recognizer to process the gesture at the second gesture recognizer (e.g., steps 455 and 456 in Figures 4C-4D), even though another gesture recognizer blocks the recognition of the event.

[00179] In some embodiments, processing the respective touch at the respective gesture recognizer includes simultaneously processing the respective touch at a second gesture recognizer in accordance with values determined by the delegates corresponding respectively to the first and second gesture recognizers.

[00180] Figures 7A-7B are flow charts illustrating an exemplary method of processing a respective touch in accordance with a receive touch value obtained from a delegate, according to some embodiments.

[00181] Method 700 is performed (702) at an electronic device (e.g., device 104) having a touch-sensitive surface (e.g., 156) and configured to execute a software application that includes a plurality of views (e.g., 316) and an application state of the software application (e.g., 317).

[00182] The device displays (704) one or more views of the plurality of views (e.g., 316). A respective view of the one or more displayed views includes one or more gesture recognizers (e.g., 320-1 or 343-2), and a respective gesture recognizer of the one or more gesture recognizers has a corresponding delegate (e.g., 321-1 or 346).

[00183] The device detects (706) one or more touches, on the touch-sensitive surface (e.g., 156 or 130). The one or more touches each have a touch position that falls within one or more of the displayed views.

[00184] The device processes (708) a respective touch of the one or more touches (e.g., determining (453) whether the respective touch matches gesture definitions 333 by using event comparator 332). The processing a respective touch includes: executing (710) the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in accordance with the application state (e.g., 550 in Figure 5C); when the receive touch value meets predefined criteria (e.g., the predefined criteria is that the respective gesture recognizer is a receiving gesture recognizer 552 in some embodiments), processing the respective touch at the respective gesture recognizer (e.g., 554); and conditionally sending information corresponding to the respective touch to the software application (e.g., 542).

[00185] In some embodiments, the plurality of views includes (712) a plurality of gesture recognizers (e.g., application views 316 and recognizers 320 in Figure 3B; views 508, 510, and 512 and gesture recognizers 516 in Figure 5A). Distinct delegates correspond to at least a subset of the plurality of gesture recognizers. Optionally, the device assigns the distinct delegates (e.g., 321) to at least a subset of the plurality of gesture recognizers (e.g., 320). Processing the respective touch of the one or more touches includes: identifying a set of candidate gesture recognizers of the plurality of gesture recognizers (e.g., 548); for each candidate gesture recognizer having a corresponding delegate, executing the corresponding delegate to obtain a receive touch value in accordance with the application state (e.g., 550); identifying one or more receiving gesture recognizers, comprising a subset of the candidate gesture recognizers, in accordance with the obtained receive touch values (e.g., 552); and processing the respective touch at each gesture recognizer of the one or more of receiving gesture recognizers (e.g., 554).

[00186] In some embodiments, identifying the set of candidate gesture recognizers of the plurality of gesture recognizers includes identifying a set of gesture recognizers attached to the hit view. Optionally, identifying the set of candidate gesture recognizers of the plurality of gesture recognizers includes identifying a set of gesture recognizers that include a gesture definition corresponding to the respective touch. Furthermore, in some embodiments, identifying the set of receiving gesture recognizers includes identifying a subset of candidate gesture recognizers for which corresponding delegates provide respective receive touch

values meeting receive touch criteria (e.g., the receive touch value indicates that the corresponding gesture recognizer can receive the respective touch).

[00187] In some embodiments, processing the respective touch at each gesture recognizer of the one or more receiving gesture recognizers includes (718) processing the respective touch at a respective receiving gesture recognizer having a corresponding delegate in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective touch to the software application in accordance with an outcome of the processing of the respective touch by the respective gesture recognizer and in accordance with the one or more values determined by the delegate. The device executes the software application in accordance with information, received from one or more of the receiving gesture recognizers, corresponding to one or more of the touches.

[00188] In some embodiments, processing the respective touch at the respective receiving gesture recognizer includes (720), when the detected touch is consistent with the respective gesture definition (e.g., the respective touch matches the gesture definition or a part thereof), enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate (e.g., “should begin” 454 in Figures 4C-4D).

[00189] In some embodiments, processing the respective touch at the respective receiving gesture recognizer includes (722), when the detected touch is consistent with the respective gesture definition, conditionally enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate. For example, the condition for the state transition includes: whether the respective touch/event matches the gesture definition or a part thereof, whether the respective gesture recognizer is allowed to receive the respective touch/event, whether the recognition of the respective touch/event is blocked, and/or whether system level instructions (e.g., a shutdown process or other process having higher priority than the application) prevent the state transition.

[00190] In some embodiments, processing the respective touch at the respective receiving gesture recognizer includes (724) simultaneously processing the respective touch at

a second gesture recognizer in accordance with one or more values determined by the delegate corresponding to the second gesture recognizer. For example, the delegate corresponding to the second gesture recognizer may allow the second gesture recognizer to process the gesture at the second gesture recognizer (e.g., step 452 in Figures 4C-4D).

[00191] In some embodiments, processing the respective touch at the respective receiving gesture recognizer includes (726) simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by the delegate corresponding to the respective gesture recognizer (e.g., steps 455 and 456 in Figures 4C-4D).

[00192] The device executes (716) the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch (e.g., 545). For example, the software application (e.g., 132-1) includes a plurality of event handlers 322, and one or more of event handlers 322 are activated according to information received from the respective gesture recognizer (e.g., event handlers 322 listed in action-target pairs 345 are activated)..

[00193] Figures 8A-8B are flow charts illustrating an exemplary method of processing a respective touch in a software application including a discrete gesture recognizer and a continuous gesture recognizer, according to some embodiments.

[00194] Method 800 is performed (802) at an electronic device (e.g., device 104) having a touch-sensitive surface and configured to execute a software application.

[00195] The device displays (804) one or more views (e.g., 316) of the software application (e.g., 132-1). The one or more displayed views include a plurality of gesture recognizers (e.g., 320). The plurality of gesture recognizers includes at least one discrete gesture recognizer (e.g., Figures 4A and 4C), and at least one continuous gesture recognizer (e.g., Figures 4B and 4D).

[00196] In some embodiments, the discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture.

[00197] In some embodiments, a discrete gesture recognizer is configured send a single set of action messages in response to a respective gesture. When a plurality of target-

action pairs are assigned to the respective discrete gesture recognizer, the single set of action messages includes a plurality of action messages. When a single target-action pair is assigned to the respective discrete gesture recognizer, the single set of action messages includes a single action message.

[00198] In some embodiments, each gesture recognizer has (822) a set of gesture recognizer states (e.g., Figures 4A-4D).

[00199] In some embodiments, the discrete gesture recognizer has (824) a first set of gesture recognizer states including:

- gesture possible state 410, corresponding to an initial state of the discrete gesture recognizer;
- gesture recognized state 420, corresponding to recognition of the respective gesture; and
- gesture failed state 430, corresponding to failure of the discrete gesture recognizer to recognize the one or more touches as the respective gesture.

[00200] In some embodiments, the continuous gesture recognizer has a second set of gesture recognizer states including:

- gesture possible state 410, corresponding to an initial state of the continuous gesture recognizer;
- gesture began state 412, corresponding to initial recognition of the respective gesture;
- gesture changed state 414, corresponding to a respective change in location of the respective touch;
- gesture ended state 416, corresponding to completion of the respective recognized gesture;
- gesture canceled state 418, corresponding to interruption of the recognition of the respective gesture; and
- gesture failed state 430, corresponding to failure of the continuous gesture recognizer to recognize the one or more touches as the respective gesture.

[00201] In some embodiments, gesture recognizer states have assigned values (e.g., gesture recognizer state values). In some embodiments, the gesture recognized state and the gesture ended state have (826) an identical gesture recognizer state value.

[00202] In some embodiments, the at least one discrete gesture recognizer includes (828): one or more of a tap gesture recognizer, and a swipe gesture recognizer; and the at least one continuous gesture recognizer includes: one or more of a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

[00203] In some embodiments, the at least one discrete gesture recognizer includes (830): a tap gesture recognizer, and a swipe gesture recognizer; and the at least one continuous gesture recognizer includes: a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

[00204] A tap gesture recognizer is configured to recognize a tap gesture; a swipe gesture recognizer is configured to recognize a swipe gesture (e.g., a flick of a touch on a touch-sensitive surface); a long press gesture recognizer is configured to recognize a long press gesture (e.g., a press and hold of a touch); a pinch gesture recognizer is configured to recognize a pinch gesture (e.g., contact and relative movement of two or more touches); a pan gesture recognizer is configured to recognize a pan gesture (e.g., touch and coherent movement of one or more touches); a rotate gesture recognizer is configured to recognize a rotation (e.g., contact and rotational movement of two or more touches); and a transform gesture recognizer is configured to recognize a transform gesture (e.g., a simultaneous movement of two or more touches representing panning, rotation, and pinch).

[00205] In some embodiments, at least one discrete gesture recognizer (e.g., one or more of the aforementioned discrete gesture recognizers) and at least one continuous gesture recognizer (e.g., one or more of the aforementioned continuous gesture recognizers) are distributed in a software library such that software developers can incorporate them into any third party software using the software library. In comparison, views have view styles (e.g., color, size, and shape of user interface objects and frames). In some embodiments, predefined view styles are distributed as a part of UI Interface API (e.g., 204 in Figure 2) such that software developers can develop a software application having the predefined view styles by using the software library (or template).

[00206] The device detects (808 in Figure 8A) one or more touches. In some embodiments, the device detects one or more events using sensors 130, input devices 128, and/or touch-sensitive display 156.

[00207] The device processes (810) each of the touches using one or more of the gesture recognizers. The processing of a respective touch includes (812) processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer (e.g., comparing the event and gesture definitions 333 using event comparator 332 and determining whether the event matches the gesture definitions 333 or a part thereof), and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer (e.g., sending an action message when the respective touch matches the gesture definition).

[00208] In some embodiments, the software application has (814) an application state. Conditionally sending the one or more respective action messages includes conditionally sending the one or more respective action messages further in accordance with the application state of the software application. For example, the application state of the software application may delay or prevent sending the one or more respective action messages (e.g., when the system resources are overused, when a higher priority process needs to be processed, etc.).

[00209] The device executes (816) the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches. For example, the software application (e.g., 132-1) includes a plurality of event handlers 322, and one or more of event handlers 322 are activated according to action message received from one or more of the gesture recognizers.

[00210] In some embodiments, the device requests (818) additional information from the respective gesture recognizer. Executing the software application includes executing the software application further in accordance with the additional information. For example, the respective gesture recognizer can provide additional information (e.g., detailed information, such as a time stamp for each sub-event, the amount of jitter, speed, direction, duration, scale factor, angle, etc.).

[00211] In some embodiments, the additional information includes (820) the number and locations of respective touches processed at the respective gesture recognizer.

2016204905 13 Jul 2016

[00212] In accordance with some embodiments, Figure 9 shows a functional block diagram of an electronic device 900 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in Figure 9 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[00213] As shown in Figure 9, an electronic device 900 includes one or more event sensing units 902 configured to sense one or more events, and a processing unit 906 coupled to the one or more event sensing units 902. In some embodiments, the electronic device also includes a display unit 904 coupled to the processing unit 906. In some embodiments, the processing unit 906 includes an executing unit 908, a display enabling unit 910, a detecting unit 912, an event processing unit 914, a sending unit 916, a recognizer enabling unit 918, a blocking unit 920, and an assigning unit 922.

[00214] The processing unit 906 is configured to: execute a software application that includes a plurality of views and an application state of the software application (e.g., with the executing unit 908), and enable display of one or more views of the plurality of views (e.g., with the display enabling unit 910 on the display unit 904). A respective view of the one or more displayed views includes a respective gesture recognizer, and the respective gesture recognizer has a corresponding delegate. The processing unit 906 is configured to detect the one or more events sensed by the one or more event sensing units 902 (e.g., with the detecting unit 912), and process a respective event of the one or more events using the respective gesture recognizer (e.g., with the event processing unit 914) by: processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer (e.g., with the event processing unit 914), executing the corresponding delegate to determine one or more values in accordance with the application state (e.g., with the executing unit 908), and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate (e.g., with the sending unit 916). The processing unit 906 is

configured to execute the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event (e.g., with the executing unit 908).

[00215] In some embodiments, the one or more event sensing units 908 include a touch sensitive surface unit (e.g., a touch-sensitive surface unit 1002, Figure 10) configured to detect one or more touches, and the one or more events include the one or more touches, and the processing unit 906 is configured to process a respective touch (e.g., with the event processing unit 914).

[00216] In some embodiments, the processing unit 906 is configured to enable the respective gesture recognizer to conditionally receive the respective touch in accordance with the one or more values determined by the corresponding delegate (e.g., with the recognizer enabling unit 918).

[00217] In some embodiments, the processing unit 906 is configured to process the respective touch by enabling the respective gesture recognizer to disregard the respective touch when the one or more values determined by the corresponding delegate matches predefined touch disregard criteria (e.g., with the event processing unit 914 and/or the recognizer enabling unit 918).

[00218] In some embodiments, the processing unit 906 is configured to process the respective touch by blocking the respective gesture recognizer from receiving the respective touch when the one or more values determined by the corresponding delegate match predefined touch disregard criteria (e.g., with the event processing unit 914 and/or the blocking unit 920).

[00219] In some embodiments, the processing unit 906 is configured to process the respective touch at the respective gesture recognizer by, when the detected touch is consistent with the respective gesture definition, enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate (e.g., with the event processing unit 914 and/or the recognizer enabling unit 918).

[00220] In some embodiments, the processing unit 906 is configured to process the respective touch at the respective gesture recognizer by, when the detected touch is consistent with the respective gesture definition, conditionally enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the corresponding delegate (e.g., with the event processing unit 914 and/or the enabling unit 918).

[00221] In some embodiments, the processing unit 906 is configured to process the respective touch at the respective gesture recognizer by simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by a delegate corresponding to the second gesture recognizer (e.g., with the event processing unit 914).

[00222] In some embodiments, the processing unit 906 is configured to process the respective touch at the respective gesture recognizer by simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by the delegate corresponding to the respective gesture recognizer (e.g., with the event processing unit 914).

[00223] In some embodiments, the one or more displayed views include a plurality of gesture recognizers, and the processing unit 906 is configured to assign distinct delegates to at least a subset of the plurality of gesture recognizers (e.g., with the assigning unit 922).

[00224] In accordance with some embodiments, Figure 10 shows a functional block diagram of an electronic device 1000 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks described in Figure 10 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[00225] As shown in Figure 10, an electronic device 1000 includes a touch-sensitive surface unit 1002 configured to receive one or more touches, and a processing unit 1006 coupled to the touch-sensitive surface unit 1002. In some embodiments, the electronic device 1000 also includes a display unit 1004 coupled to the processing unit 1006. In some embodiments, the processing unit 1006 includes an executing unit 1008, a display enabling unit 1010, a detecting unit 1012, a touch processing unit 1014, a sending unit 1016, an assigning unit 1018, an identifying unit 1020, and a recognizer enabling unit 1022.

[00226] The processing unit 1006 is configured to: execute a software application that includes a plurality of views and an application state of the software application (e.g., with the executing unit 1008), and enable display of one or more views of the plurality of views

(e.g., with the display enabling unit 1010 on the display unit 1004). A respective view of the one or more displayed views includes one or more respective gesture recognizers, and a respective gesture recognizer has a corresponding delegate. The processing unit 1006 is configured to detect the one or more touches, received on the touch-sensitive surface unit 1002 (e.g., with the detecting unit 1012). Each touch has a touch position that falls within one or more of the displayed views. The processing unit 1006 is configured to process a respective touch of the one or more touches by: executing the delegate corresponding to the respective gesture recognizer to obtain a receive touch value in accordance with the application state (e.g., with the executing unit 1008); when the receive touch value meets predefined criteria, processing the respective touch at the respective gesture recognizer (e.g., with the touch processing unit 1014); and conditionally sending information corresponding to the respective touch to the software application (e.g., with the sending unit 1016). The processing unit 1006 is configured to execute the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective touch (e.g., with the executing unit 1008).

[00227] In some embodiments, the plurality of views includes a plurality of gesture recognizers. The processing unit 1006 is configured to: assign distinct delegates to at least a subset of the plurality of gesture recognizers (e.g., with the assigning unit 1018), and process the respective touch of the one or more touches by: identifying a set of candidate gesture recognizers of the plurality of gesture recognizers (e.g., with the identifying unit 1020); for each candidate gesture recognizer having an assigned delegate, executing the assigned delegate to obtain a receive touch value in accordance with the application state (e.g., with the executing unit 1008); identifying one or more receiving gesture recognizers, comprising a subset of the candidate gesture recognizers, in accordance with the obtained receive touch values (e.g., with the identifying unit 1020); and processing the respective touch at each gesture recognizer of the one or more of receiving gesture recognizers (e.g., with the touch processing unit 1014).

[00228] In some embodiments, the processing unit 1006 is configured to process the respective touch at each gesture recognizer of the one or more receiving gesture recognizers by: processing the respective touch at a respective receiving gesture recognizer to which a delegate has been assigned in accordance with a respective gesture definition corresponding to the respective gesture recognizer (e.g., with the touch processing unit 1014), executing the assigned delegate to determine one or more values in accordance with the application state

(e.g., with the executing unit 1008), and conditionally sending information corresponding to the respective touch to the software application in accordance with an outcome of the processing of the respective touch by the respective gesture recognizer and in accordance with the one or more values determined by the assigned delegate (e.g., with the sending unit 1016); and execute the software application in accordance with information, received from one or more of the receiving gesture recognizers, corresponding to one or more of the touches (e.g., with the executing unit 1008).

[00229] In some embodiments, the processing unit 1006 is configured to process the respective touch at the respective receiving gesture recognizer by, when the detected touch is consistent with the respective gesture definition, enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the assigned delegate (e.g., with the recognizer enabling unit 1022).

[00230] In some embodiments, the processing unit 1006 is configured to process the respective touch at the respective receiving gesture recognizer by, when the detected touch is consistent with the respective gesture definition, conditionally enabling a corresponding state transition in the respective gesture recognizer when the state transition is enabled by the assigned delegate (e.g., with the recognizer enabling unit 1022).

[00231] In some embodiments, the processing unit 1006 is configured to process the respective touch at the respective receiving gesture recognizer by simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by the delegate assigned to the second gesture recognizer (e.g., with the touch processing unit 1014).

[00232] In some embodiments, the processing unit 1006 is configured to process the respective touch at the respective receiving gesture recognizer by simultaneously processing the respective touch at a second gesture recognizer in accordance with one or more values determined by the delegate assigned to the respective gesture recognizer (e.g., with the touch processing unit 1014).

[00233] In accordance with some embodiments, Figure 11 shows a functional block diagram of an electronic device 1100 configured in accordance with the principles of the invention as described above. The functional blocks of the device may be implemented by hardware, software, or a combination of hardware and software to carry out the principles of the invention. It is understood by persons of skill in the art that the functional blocks

described in Figure 11 may be combined or separated into sub-blocks to implement the principles of the invention as described above. Therefore, the description herein may support any possible combination or separation or further definition of the functional blocks described herein.

[00234] As shown in Figure 11, an electronic device 1100 includes a touch-sensitive surface unit 1102 configured to receive one or more touches; and a processing unit 1106 coupled to the touch-sensitive surface unit 1102. In some embodiments, the electronic device 1100 also includes a display unit 1104 coupled to the processing unit 1106. In some embodiments, the processing unit 1106 includes an executing unit 1108, a display enabling unit 1110, a detecting unit 1112, a touch processing unit 1114, a sending unit 1116, and a requesting unit 1118.

[00235] The processing unit 1106 is configured to: execute a software application (e.g., with the executing unit 1108), and enable display of one or more views of the software application (e.g., with the display enabling unit 1110 on the display unit 1104). The one or more displayed views include a plurality of gesture recognizers, and the plurality of gesture recognizers including at least one discrete gesture recognizer and at least one continuous gesture recognizer. The discrete gesture recognizer is configured to send a single action message in response to a respective gesture, and the continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture. The processing unit 1106 is configured to detect the one or more touches received on the touch-sensitive surface unit 1102 (e.g., with the detecting unit 1112), and process each of the touches using one or more of the gesture recognizers (e.g., with the touch processing unit 1114). The processing unit 1106 is configured to process a respective touch by: processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer (e.g., with the touch processing unit 1114), and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer (e.g., with the sending unit 1116). The processing unit 1106 is configured to execute the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches (e.g., with the executing unit 1108).

[00236] In some embodiments, each gesture recognizer has a set of gesture recognizer states.

[00237] In some embodiments, the discrete gesture recognizer has a first set of gesture recognizer states including: a gesture possible state, corresponding to an initial state of the discrete gesture recognizer; a gesture recognized state, corresponding to recognition of the respective gesture; and a gesture failed state, corresponding to failure of the discrete gesture recognizer to recognize the one or more touches as the respective gesture. The continuous gesture recognizer has a second set of gesture recognizer states including: a gesture possible state; a gesture began state, corresponding to initial recognition of the respective gesture; a gesture changed state, corresponding to a respective change in location of the respective touch; a gesture ended state, corresponding to completion of the respective recognized gesture; a gesture canceled state, corresponding to interruption of the recognition of the respective gesture; and a gesture failed state, corresponding to failure of the continuous gesture recognizer to recognize the one or more touches as the respective gesture.

[00238] In some embodiments, the gesture recognized state and the gesture ended state have an identical gesture recognizer state value.

[00239] In some embodiments, the software application has an application state; and the processing unit 1106 is configured to conditionally send the one or more respective action messages further in accordance with the application state of the software application (e.g., with the sending unit 1116).

[00240] In some embodiments, the processing unit 1106 is configured to: request additional information from the respective gesture recognizer (e.g., with the requesting unit 1118); and execute the software application further in accordance with the additional information (e.g., with the executing unit 1108).

[00241] In some embodiments, the additional information includes the number and locations of respective touches processed at the respective gesture recognizer.

[00242] In some embodiments, the at least one discrete gesture recognizer includes: one or more of a tap gesture recognizer, and a swipe gesture recognizer; and the at least one continuous gesture recognizer includes: one or more of a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

[00243] In some embodiments, the at least one discrete gesture recognizer includes: a tap gesture recognizer, and a swipe gesture recognizer; and the at least one continuous

gesture recognizer includes: a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

[00244] The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS

1. A method, comprising:
at an electronic device having one or more event sensors and configured to execute a software application:
displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including:
at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and
at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture;
detecting, using the one or more event sensors, one or more events;
processing each of the events using one or more of the gesture recognizers, the processing of a respective event including:
processing the respective event at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and
conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and
executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events;
wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.
2. The method of claim 1, wherein the one or more event sensors further include a camera configured to detect one or more eye movements, and the one or more events include

the one or more eye movements, and processing the respective event comprises processing a respective eye movement.

3. The method of claim 1, wherein the one or more event sensors include a touch sensitive surface configured to detect one or more touches, and the one or more events include the one or more touches, and processing the respective event comprises processing a respective touch.

4. The method of any of claims 1-3, wherein the one or more action messages received from the at least one continuous gesture recognizer cause a scrolling of at least a portion of a displayed view of the software application.

5. The method of any of claims 1-4, wherein each gesture recognizer has a set of gesture recognizer states.

6. The method of claim 5, wherein:

a respective discrete gesture recognizer of the at least one discrete gesture recognizer maintains a corresponding gesture recognizer state selected from a first set of states that includes a first discrete gesture recognizer state in which recognition of a corresponding gesture by the respective discrete gesture recognizer remains possible, a second discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has failed, and a third discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has been successful; and

a respective continuous gesture recognizer of the at least one continuous gesture recognizer maintains a corresponding gesture recognizer state selected from a second set of states that includes a first continuous gesture recognizer state in which recognition of a corresponding gesture by the respective continuous gesture recognizer remains possible, a second continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has been determined to have failed, a third continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has begun, and a fourth continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer continues with said recognized sub-events after an initial

determination that recognition of the corresponding gesture by the respective continuous gesture recognizer has begun.

7. The method of any of claims 1-6, wherein the software application has an application state; and

conditionally sending the one or more respective action messages includes conditionally sending the one or more respective action messages further in accordance with the application state of the software application.

8. The method of any of claims 1-6, further comprising requesting additional information from the respective gesture recognizer, wherein executing the software application includes executing the software application further in accordance with the additional information.

9. The method of any of claims 1-6, wherein:

the at least one discrete gesture recognizer includes one or more of:

a tap gesture recognizer and a swipe gesture recognizer; and

the at least one continuous gesture recognizer includes one or more of:

a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

10. The method of any of claims 1-6, wherein:

the at least one discrete gesture recognizer includes:

a tap gesture recognizer, and a swipe gesture recognizer; and

the at least one continuous gesture recognizer includes:

a long press gesture recognizer, a pinch gesture recognizer, a pan gesture recognizer, a rotate gesture recognizer, and a transform gesture recognizer.

11. An electronic device, comprising:

one or more event sensors;

one or more processors; and

memory storing one or more programs for execution by the one or more processors, the one or more programs including a software application, and the software application including instructions for:

2016204905 01 Jun 2018

displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including:

at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and

at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture;

detecting, using the one or more event sensors, one or more events;

processing each of the events using one or more of the gesture recognizers, the processing of a respective event including:

processing the respective event at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and

conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and

executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events;

wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.

12. The electronic device of claim 11, wherein the one or more event sensors further include a camera configured to detect one or more eye movements, and the one or more events include the one or more eye movements, and processing the respective event comprises processing a respective eye movement.

13. The electronic device of claim 11, wherein the one or more event sensors include a touch sensitive surface configured to detect one or more touches, and the one or more events

include the one or more touches, and processing the respective event comprises processing a respective touch.

14. The electronic device of any of claims 11-13, wherein the one or more action messages received from the at least one continuous gesture recognizer cause a scrolling of at least a portion of a displayed view of the software application.

15. The electronic device of any of claims 11-14, wherein
each gesture recognizer has a set of gesture recognizer states;
a respective discrete gesture recognizer of the at least one discrete gesture recognizer maintains a corresponding gesture recognizer state selected from a first set of states that includes a first discrete gesture recognizer state in which recognition of a corresponding gesture by the respective discrete gesture recognizer remains possible, a second discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has failed, and a third discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has been successful; and

a respective continuous gesture recognizer of the at least one continuous gesture recognizer maintains a corresponding gesture recognizer state selected from a second set of states that includes a first continuous gesture recognizer state in which recognition of a corresponding gesture by the respective continuous gesture recognizer remains possible, a second continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has been determined to have failed, a third continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has begun, and a fourth continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer continues with said recognized sub-events after an initial determination that recognition of the corresponding gesture by the respective continuous gesture recognizer has begun.

16. A computer readable storage medium storing one or more programs for execution by one or more processors of an electronic device having one or more event sensors, the one or more programs including a software application, the software application including instructions for:

displaying one or more views of the software application, wherein the one or more displayed views include a plurality of gesture recognizers, the plurality of gesture recognizers including:

at least one discrete gesture recognizer, the discrete gesture recognizer configured to send a single action message in response to a respective gesture; and

at least one continuous gesture recognizer, the continuous gesture recognizer configured to send action messages at successive recognized sub-events of a respective recognized gesture;

detecting, using the one or more event sensors, one or more events;

processing each of the events using one or more of the gesture recognizers, the processing of a respective event including:

processing the respective event at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and

conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective event at the respective gesture recognizer; and

executing the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the events;

wherein the one or more event sensors include a camera or accelerometer or gyroscope configured to detect one or more movements of the electronic device, and the one or more events include the one or more movements of the electronic device, and processing the respective event comprises processing at the respective gesture recognizer a respective movement of the electronic device.

17. The computer readable storage medium of claim 16, wherein the one or more event sensors further include a camera configured to detect one or more eye movements, and the one or more events include the one or more eye movements, and processing the respective event comprises processing a respective eye movement.

18. The computer readable storage medium of claim 16, wherein the one or more event sensors include a touch sensitive surface configured to detect one or more touches, and the one or more events include the one or more touches, and processing the respective event comprises processing a respective touch.

19. The computer readable storage medium of any of claims 16-18, wherein the one or more action messages received from the at least one continuous gesture recognizer cause a scrolling of at least a portion of a displayed view of the software application.

20. The computer readable storage medium of any of claims 16-19, wherein each gesture recognizer has a set of gesture recognizer states;

a respective discrete gesture recognizer of the at least one discrete gesture recognizer maintains a corresponding gesture recognizer state selected from a first set of states that includes a first discrete gesture recognizer state in which recognition of a corresponding gesture by the respective discrete gesture recognizer remains possible, a second discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has failed, and a third discrete gesture recognizer state in which recognition of the corresponding gesture by the respective discrete gesture recognizer has been successful; and

a respective continuous gesture recognizer of the at least one continuous gesture recognizer maintains a corresponding gesture recognizer state selected from a second set of states that includes a first continuous gesture recognizer state in which recognition of a corresponding gesture by the respective continuous gesture recognizer remains possible, a second continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has been determined to have failed, a third continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer has begun, and a fourth continuous gesture recognizer state in which recognition of the corresponding gesture by the respective continuous gesture recognizer continues with said recognized sub-events after an initial determination that recognition of the corresponding gesture by the respective continuous gesture recognizer has begun.

2016204905 13 Jul 2016




Figure 1A




Figure 1B

2016204905 13 Jul 2016




Figure 2





Figure 3A






Figure 3C

2016204905 13 Jul 2016

Discrete Event
Recognizer State
Machine 400




Figure 4A

Continuous Event
Recognizer State
Machine 402




Figure 4B

Discrete Event
Recognizer State
Machine 400




Figure 4C




Figure 4D

2016204905 13 Jul 2016




Figure 5A

2016204905 13 Jul 2016




Figure 5B

2016204905 13 Jul 2016




Figure 5C

2016204905 13 Jul 2016

600

At an electronic device having one or more event sensors and configured to execute a software application that includes a plurality of views and an application state of the software application

602

Display one or more views of the plurality of views. A respective view of the one or more displayed views includes one or more gesture recognizers.

604

Assign a respective delegate to the respective gesture recognizer.

606

The one or more displayed views include a plurality of gesture recognizers. Assign distinct delegates to at least a subset of the plurality of gesture recognizers.

608

Detect one or more events.

610

Process a respective event of the one or more events using the respective gesture recognizer. The processing of the respective event includes processing the respective event at the respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, executing the corresponding delegate to determine one or more values in accordance with the application state, and conditionally sending information corresponding to the respective event to the software application in accordance with an outcome of the processing of the respective event by the respective gesture recognizer and in accordance with the one or more values determined by the corresponding delegate.

612

Execute the software application in accordance with information, received from the respective gesture recognizer, corresponding to the respective event.


614

The one or more event sensors include a touch sensitive surface configured to detect one or more touches. The one or more events include the one or more touches. Processing the respective event comprises processing a respective touch.


616

Figure 6A


2016204905 13 Jul 2016

**Figure 6B**

2016204905 13 Jul 2016

700**Figure 7A**

2016204905 13 Jul 2016



2016204905 13 Jul 2016

800

At an electronic device having a touch-sensitive surface and configured to execute a software application

Display one or more views of the software application. The one or more displayed views include a plurality of gesture recognizers. The plurality of gesture recognizers include at least one discrete gesture recognizer, and at least one continuous gesture recognizer.

The discrete gesture recognizer is configured to send a single action message in response to a respective gesture. The continuous gesture recognizer is configured to send action messages at successive recognized sub-events of a respective recognized gesture.

Detect one or more touches.

Process each of the touches using one or more of the gesture recognizers.

The processing of a respective touch includes processing the respective touch at a respective gesture recognizer in accordance with a respective gesture definition corresponding to the respective gesture recognizer, and conditionally sending one or more respective action messages to the software application in accordance with an outcome of the processing of the respective touch at the respective gesture recognizer.

The software application has an application state. Conditionally sending the one or more respective action messages includes conditionally sending the one or more respective action messages further in accordance with the application state of the software application.


Execute the software application in accordance with one or more action messages received from one or more of the gesture recognizers corresponding to one or more of the touches

Request additional information from the respective gesture recognizer. Executing the software application includes executing the software application further in accordance with the additional information.

The additional information includes the number and locations of respective touches processed at the respective gesture recognizer.

Figure 8A
17/21

2016204905 13 Jul 2016

**Figure 8B**

2016204905 13 Jul 2016




Figure 9

2016204905 13 Jul 2016




Figure 10

2016204905 13 Jul 2016




Figure 11