

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/072398 A2

(51) International Patent Classification: Not classified

(21) International Application Number:
PCT/US2005/002684

(22) International Filing Date: 27 January 2005 (27.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/539,929 28 January 2004 (28.01.2004) US
60/630,613 23 November 2004 (23.11.2004) US

(71) Applicant (for all designated States except US): **BAM-BURGH MARRSH LLC** [US/US]; 15720 NE 31st Avenue, Vancouver, WA 98686 (US).

(72) Inventors: **SLOWEY, Paul, D.**; 15720 NE 31st Avenue, Vancouver, WA 98666 (US). **HERRIG, Richard**; 3009 East Lupine, Phoenix, AZ 85028 (US). **WICKSTEAD, James**; 185 Ridgedale Avenue, Cedar Knolls, NJ 07927

(US). **ENNIS, John**; 5601 E. 18th Street #305, Vancouver, WA 98661 (US). **SMITH, Paul**; 5601 E. 18th Street, #305, Vancouver, WA 98661 (US).


(74) Agent: **RYLANDER, Kurt, M.**; K.M. Rylander Trial & Patent Attorney at Law PC, 1014 Franklin Street, Vancouver, WA 98660 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: SPECIMEN SAMPLE COLLECTION DEVICE AND TEST SYSTEM



(57) Abstract: A specimen sample collection device includes a handle having a sufficiency indicator and an absorbent pad partially contained within said handle. A specimen sample collection device and test system includes a handle having a sufficiency indicator, an absorbent pad partially contained within said handle, a pad compression tube insertable over said absorbent pad within said handle and around an end of said handle, and a collection tube having one or more sample chambers, attachable to said pad compression tube, and wherein said compression tube defines one or more chambers, and wherein when said collection tube is attached to said pad compression tube, the chambers are in fluid communication with said pad compression tube. A specimen sample collection device including a sufficiency indicator made up of a light pipe indicator window. A specimen sample collection device including an absorbent pad split and divided into two lengths connected at a base. A specimen sample collection device including a bar code identification. A specimen sample collection device and test system including a lock and key securing mechanism. A specimen sample collection device including a handle one or more analyte test strips. A specimen sample

collection device and test system including a reader.

WO 2005/072398 A2



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations* AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ,

EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

5

SPECIMEN SAMPLE COLLECTION DEVICE AND TEST SYSTEM

10

CROSS-REFERENCE TO RELATED APPLICATION

The present application claims the benefit of and priority to prior co-pending U.S. Provisional Patent Application Serial No. 60/539,929 filed on January 28, 2004, and 60/630,613 filed on November 23, 2004

15

FIELD OF THE INVENTION

The present invention relates to devices and methods for the collection of fluids, and more particularly to devices and methods for the collection of fluids and methods for testing samples so obtained for fluids including bodily fluids such as saliva.

20

BACKGROUND

Traditional methods of testing for diseases, drugs and other antigens in humans have up until the last few years been predominantly done using blood samples. These samples collected in laboratories at the request of physicians require that blood drawn by a trained phlebotomist is sent to a laboratory and the
25 serum component comprising a predominance of immunoglobulins, containing antibodies to the disease or disease state in question, is tested using a variety of

available test kits to assist in the diagnosis of various diseases including infectious diseases, cardiovascular diseases, cancers and many others. Such samples can also be tested for the presence of non-disease analytes such as metals, minerals, DNA, bacteria and organic molecules among others.

5 Under current standardized laboratory practices, it is necessary to confirm any initially positive result obtained from diagnostic or analytical testing with a more sensitive (accurate) method. This, in fact is true for most, if not all diagnostic tests used today, including, as an example, HIV tests, which are confirmed by more definitive methods such as Western blot techniques or immunofluorescence
10 (IFA) assays. In the case of drug tests, for instance, performed in criminal justice settings (at the police car, in correctional facilities, in drug courts, etc.) or at the workplace, by way of two examples, confirmation is carried out using gas chromatography-mass spectrometry (GC-MS), gas chromatography-mass spectrometry-mass-spectrometry (GC-MS-MS) or liquid chromatography-mass
15 spectrometry-mass spectrometry (LC-MS-MS) on a second sample taken from the subject. Other diagnostic and screening methods require similarly accurate methods for confirmatory purposes.

The United States Substance Abuse Mental Health Services Administration (SAMHSA), the designated body responsible for regulating Federal drug testing in
20 the United States, has recently prepared guidelines for the introduction of new tests and sample collection procedures for drug tests using so-called, "alternate" specimens. These sample types include saliva (or oral fluids), hair and sweat. These guidelines define the need for (1) a confirmatory specimen to be collected

at the time of the initial sampling, (2) defined specimen volumes to be collected and (3) expected drug cut-off values, among other requirements.

The need for duplicate, or a multiplicity of mutually distinct samples taken from the same source at the same time is part of a general trend being observed in many areas of the diagnostic and analytical testing businesses. The main reason for this increasingly important trend is the legal implication of being able to definitively rule out any potential contamination of the test sample during the testing process. The obvious consequences of an incorrect diagnosis of HIV for a patient or erroneous DNA results in the case of a criminal case are just two examples of where 100% certainty of sample integrity are paramount and are contributing reasons for the development of this particular invention. This potential legal implication has had an impact on general testing protocols and as a result healthcare and other professionals are now more cognizant than ever of the need to collect a "pure" sample or samples then ensure that those samples are analyzed to produce accurate results. During the testing process absolute "chain-of-custody" rules are enforced to ensure that no adulteration or contamination of the specimen occurs. This is not always possible in current testing protocols as there are opportunities for sample contamination or sample tampering. This is true for any test whether done on blood, serum, saliva, nasal secretions, vaginal discharge or any other sample where information obtained relates to a diagnosis of disease or disease state. Such information is taken in conjunction with any additional information available to the person making a decision relating to interpretation of the results obtained.

Despite the fact that saliva has been used as a diagnostic fluid since Ancient Chinese times, when the "Rice Test" (which relied on the inhibition of saliva as a determinate of guilt) was used, it is only over the last few years that salivary testing has taken on much greater significance. There are several
5 important factors, which have contributed to this change: (1) The increase in popularity of non- or less-invasive testing methods; (2) the availability of more sensitive antibodies and antigens for detection of immunoglobulins in saliva; (3) new technologies in the area of point-of-care testing; (4) a need for more rapid results; (5) acquisition of serum / blood involves patient discomfort and can cause
10 difficulty particularly where young children or intravenous drug users are concerned; (6) use of venous blood to collect serum requires capital equipment and involves an initial processing step, which adds significant time to result turnaround and has additional cost implications and also; (7) a general movement away from centralized laboratory testing towards "near-patient" testing, also called
15 "point-of-care" testing.

The National Institutes of Health (NIH) recognized the value of salivary testing as early as 1993 and recent symposia orchestrated by this organization, for instance a meeting held in 1999, organized by NIH's National Institute of Dental and Craniofacial Research (NIDCR) division has helped increase the profile of
20 testing using oral fluids. NIH, through various divisions, has since been encouraging companies with expertise in this area to apply for funding for new projects aimed at introducing novel tests using non-invasive samples for laboratory and point-of-care applications.

The insurance testing industry uses saliva as a sample matrix for applicants wishing to purchase specific life insurance policies as a safeguard measure prior to writing policies. In these situations applicants are tested for HIV, cotinine (nicotine) and cocaine using a testing device called "OraSure" from OraSure Technologies, which collects oral fluids for subsequent testing under laboratory conditions. Each of the major insurance testing laboratories in the United States performs a significant number of oral fluid tests on an annual basis.

In April 2004 OraSure Technologies was successful in gaining FDA approval for its OraQuick® HIV 1 / 2 rapid test for oral fluid diagnosis of the HIV viruses type 1 and type 2. Previously the test had been approved by the agency for whole blood, serum and plasma only.

In a separate area drugs of abuse are routinely detected from oral fluids collected in the workplace, in criminal justice settings and in hospitals using OraSure Technologies' "Intercept™" device and associated range of ELISA microplate assays. In this case a panel of 5 "abused" drugs or more are measured under laboratory conditions.

Rapid testing devices using saliva have recently appeared, which may be used at the "point-of-care". These devices can collect and perform immediate testing for several drugs of abuse but these suffer from poor performance for certain tests at the present time, particularly Tetrahydrocannabinol (THC) or its major metabolite 11-nor- Δ^9 -Tetrahydrocannabinol. Examples of this type of device are the OraTect™ test from Branan Medical Corporation, the OraLine assay from Sun Biomedical and the Cozart BioScience RapiScan device, among others.

Up until now urine based rapid drug testing has been performed preferentially due to availability, cost, and to a certain extent, a lack of salivary tools incorporating some of the features described in this invention. While rapid urine kits are widespread they suffer from issues related to “chain-of-custody”, the
5 need for facilities to collect urine specimens discreetly under appropriate supervision and are easily adulterated by knowledgeable users, who can “cheat” such tests.

Electronic reading, hand-held devices, such as the Cozart BioSciences RapiScan instrument are also now available outside of the United States, that
10 allow immediate drug testing to be done from oral fluids at the roadside and other field settings. This technology requires sample collection from the donor then immediate testing on site. This concept may well be duplicated in the future, as technologies to “miniaturize” testing platforms, improves.

The FDA has approved a laboratory HIV test, OraSure HIV-1 for testing for
15 the HIV-1 virus from oral fluid as well as a Western blot confirmatory test, which also uses oral fluids. Both have been used in a Public Health setting in the United States for over five (5) years.

In addition the FDA has also approved saliva tests for pre-term labor (SalEst™, salivary estriol, from Biex, Inc), a salivary alcohol test (QED®, OraSure
20 Technologies), a cortisol assay (Salimetrics, Inc.) as well as a panel of saliva-based drug assays (Intercept, OraSure Technologies) through the 510(k) clearance system. A number of other oral fluid drug testing products are undergoing regulatory approval, so in the next 12-24 months we might expect to see several other products available in the U.S. Furthermore, “investigational use”

tests are available for immunoglobulins, for example sIgA (for use in psychological disorders, stress and athletic performance), therapeutic drugs (for instance lithium, theophylline, AZT), tumor markers (e.g. Her-2 / neu), bacterial antibodies such as *helicobacter pylori* and even genomic detection of mitochondrial DNA (for criminal
5 justice applications) using oral fluids as the preferred specimen matrix.

Emerging methodologies based on microfluidic technology requiring only small quantities of specimen samples are approaching the market. These devices work on virtually any specimen matrix including, but not limited to, saliva, urine, whole blood, serum, and other fluids. Such techniques have already found use in
10 the arena of biodefense monitoring, high throughput screening methods, high performance liquid chromatography (HPLC) and other analytical techniques. These devices, which are being developed in one particular area for use by special intelligence forces, who are required to test for chemical and biological agents in soil, water and other samples before troops arrive at a battle site or
15 during peacekeeping to monitor biological or environmental samples, may be seen as another area where this invention will find application.

These are a few of the many instances where saliva is viewed as a viable sample matrix for testing purposes. A number of devices in use today have provided means for the collection of bodily fluids including saliva and urine among
20 others. One FDA-cleared fluid collection device used predominantly for saliva collection and testing has been shown to be potentially unsafe in pediatric patients. The Saliva•Sampler™ device from SDS, Inc. utilizes perforations present on filter paper to facilitate removal of the filter paper for subsequent saliva separation and testing. The device is placed under the tongue to accumulate

sublingual whole saliva, collected by leaving the sampling device, consisting of a filter paper material attached to a plastic stem, in position until a sample indicator built into the device changes color confirming sample sufficiency. The process requires that the subject not chew, bite or unnecessarily move the device during the collection procedure. In pediatric patients, particularly, this can be a problem as children have a tendency to chew on materials placed in the oral cavity. In infants, separation of the filter paper prematurely can result in choking.

In another previously described example, an alternate FDA-approved oral fluid collection system from OraSure Technologies, Inc., known as OraSure®, incorporates salts impregnated on to the collection medium in the form of a “hypertonic” solution. According to the manufacturers, the purpose of the salts is to facilitate ready absorption of oral fluids (oral mucosal transudate) from the gingival crevices and thereby reduce sampling time. In practice when the OraSure® device is placed in the oral cavity, the taste of the salts on the device medium may be distasteful to potential users.

These and other currently available devices fail to address a growing need for efficient collection of bodily fluids including saliva for applications including analytical or diagnostic testing under laboratory, field or point-of-care testing conditions, for instance, whereby a pure sample of fluid, for example saliva, is collected from a subject and split into multiple chambers, thereby providing a means for initial specimen testing analysis or storage, for confirmation or supplementary testing and simultaneously providing a mechanism for confirming sample sufficiency prior to any subsequent testing or analysis of the constituents of the bodily fluid so collected.

Lateral flow immunochromatography (ICT) tests have been around for over a decade and are a direct descendent of thin-layer chromatography (TLC) techniques pioneered during the 1970s. The technology offers some benefits including cost efficiencies, user-friendliness and the availability of immediate test results. Over the last decade in particular, the availability of high quality raw material components, the growing movement towards near patient or point-of-care ("POC") testing, coupled with a need for rapid results, has led to an "explosion" in the development and commercialization of both flow-through and lateral flow devices based on immunochromatographic test principles. These devices form part of a rapidly growing industry for diagnostic tests performed outside of the laboratory.

A variety of ICT tests are now available including as examples OraSure Technologies' rapid oral fluid test, OraQuick HIV 1/ 2, Quidel Corporation's Quick-Vue Streptococcus A and *Helicobacter pylori* rapid tests, Meridian BioSciences' ImmunoCard assays for Respiratory Syncytial Virus (RSV) and Clostridium Difficile (*C. Difficile*) and Roche Diagnostics' TestCup drugs of abuse tests among a multitude of others.

Technologies other than ICT are equally adaptable to rapid testing. These include latex agglutination, dot-blot tests, microarrays and others.

Of the above rapid test examples and those currently in existence, only OraSure Technologies has been successful in commercializing a rapid, oral fluid test, OraQuick HIV 1 / 2, despite the fact that oral fluid, point-of-care tests represent an attractive alternative to current testing methodologies. This may be due, in part, to current data requirements for approval of rapid tests in the U.S.

This is expected to change as a result of OraSure's success with OraQuick® HIV 1 / 2 and the emergence of saliva-based drug testing assays.

In order to meet the needs of a growing Public Health demand in the U.S. it is important for would-be manufacturers to integrate test strip technologies similar
5 to those mentioned above with a simple-to-use, integrated platform system that can deliver rapid test results, safely and cost-effectively, for a range of diseases or analytes in a non-invasive manner. This is especially important in view of Centers for Disease Control (CDC) estimates that suggest that, of 2 .1 million people tested at Publicly-funded Government testing sites using traditional (laboratory) testing
10 methods in the US for the HIV virus, approximately 33% do not return to receive their results and may unwittingly go on to infect others if they are in fact HIV-positive. As the key to all disease prevention is early detection, accurate and early detection using rapid tests can have a major impact on reducing disease incidence.

15 In needle-averse populations, for instance, small children, pregnant women and hemophiliacs, the opportunity to provide oral fluid or saliva collection and immediate testing as an alternative to blood-based systems would be welcomed. Similarly general practitioners and health professionals would see an opportunity to provide testing opportunities in non-traditional testing sites, such as in the
20 privacy of the patient's home, in nursing homes, remote clinic settings and even over the counter in a pharmacy environment.

Cozart BioSciences (UK, www.Cozart.co.uk) has described the use of a hand-held device known as RapiScan, which tests for several illicit drug entities from oral fluids. This reading system is not fully integrated and requires a separate

collection step prior to testing the specimen. OraSure Technologies (www.OraSure.com) has also described in a recent US Patent Application (Application Number XXXX), the use of a sample collector and test device. In this example also, sample collection is distinct from the specimen testing process.

5 SAMHSA has proposed in its 2004 guidelines for alternate specimen testing that minimum oral fluid collection volumes are to be 2mL of clean specimen.

None of the available prior art provides for expressing an oral fluid sample from a subject directly onto a diagnostic test strip, providing a mechanism for determining sample volume adequacy and visually reading qualitative and/or
10 quantitative results from the test strip through a small window in an integrated one-step manner.

The following represents a list of known related art U.S. Pat. 5,283,038 issued Feb. 1, 1994, U.S. Pat. 5,260,031 issued Nov. 9, 1993, U.S. Pat. 5,268,148 issued Dec. 7, 1993, U.S. Pat. 5,393,496 issued Feb. 23, 1995, U.S. Pat.
15 5,380,492 issued Jan. 10, 1995, U.S. Pat. 5,376,337 issued Dec. 27, 1994, U.S. Pat. 6,267,722, U.S. Pat. 6,027,943, U.S. Pat. 6,187,598, U.S. Pat. 5,965,453, U.S. Pat. 5,393,496, U.S. Pat. 4,943,522, U.S. Pat. 4,895,808, U.S. Pat. 6,372,516, U.S. Pat. 6,046,058, U.S. Pat. 5,962,336, U.S. Pat. 5,238,652, US Pat. App. No. 10/061036 by Lloyd Simonson, US Pat. App. No. 10/060605 by Lloyd
20 Simonson, U.S. Pat. 6,627,152, U.S. Pat. 6,727,879, U.S. Pat. 5,922,614 to Edward Cesarczyk, U.S. Pat. 6,489,172. None of the above inventions and patents, taken either singularly or in combination, is seen to describe the instant invention as claimed.

SUMMARY AND ADVANTAGES

A specimen sample collection device includes a handle having a sufficiency indicator and an absorbent pad partially contained within said handle. A specimen sample collection device and test system includes a handle having a sufficiency indicator, an absorbent pad partially contained within said handle, a pad compression tube insertable over said absorbent pad within said handle and around an end of said handle, and a collection tube having one or more sample chambers, attachable to said pad compression tube, and wherein said compression tube defines one or more chambers, and wherein when said collection tube is attached to said pad compression tube, the chambers are in fluid communication with said pad compression tube. A specimen sample collection device including a sufficiency indicator made up of a light pipe indicator window. A specimen sample collection device including an absorbent pad split and divided into two lengths connected at a base. A specimen sample collection device including a bar code identification. A specimen sample collection device and test system including a lock and key securing mechanism. A specimen sample collection device including a handle one or more analyte test strips. A specimen sample collection device and test system including a reader.

The specimen sample collection device and test system of the present invention presents numerous advantages, including: (1) ability to collect appropriate volumes of specimen sample and confirmation sample using a split (fork-shaped) collection medium; (2) ergonomically correct design; (3) simple to use; (4) ability to adapt to new testing requirements; (5) sample containment with minimized chance of contamination; (6) utilizes an absorbent pad collection medium rather than a filter paper collection medium; (7) provides a unique sample

indicator design that does not utilize a compressible sponge or polymeric bead; (8) provides a unique sample indicator design that does not involve disposing an indicator on filter paper; (9) provides a unique sample indicator design that does not require an adequacy indicator separate from the collection medium; (10) utilizes a collection medium that does not require a rectangular or paddle shape; (11) allows for samples to be removed from individual compartments or chambers and channeled directly or pipetted if necessary, directly into an alternate receptacle for further analysis or testing; (12) allows for removal of the specimen directly using high-throughput automated equipment, which can speed up sampling and analysis tremendously. (13) allows for collection of mutually distinct samples for initial testing or analysis and follow up or supplementary testing either immediately or at a later date; (14) allows for use of "tailored" buffer solutions designed to protect the integrity of various different analytes or samples collected; (15) utilizes multiple absorbent materials to maximize the retention and release properties of the invention; (16) allows for testing samples collected immediately using available lateral flow immunochromatographic test strips to deliver test results at the point of care; (17) allows for collection of specimen without the need for an additional filtration or centrifugation step; (18) requires no expensive capital equipment to collect and process the sample; (19) allows for individual sample identification; (20) allows for a variety of sample collection tubes to be attached to the end of the invention depending upon sample volume requirements and whether single or dual sampling is required; (21) requires minimum manipulation of fluid specimen; (22) minimizes the chance for contamination of the sample collected; (23) minimizes the chance of tampering with the sample collected; (24)

provides the ability to rule out contamination; (25) reduces the opportunity for misdiagnosis; (26) provides the ability to work within "chain-of-custody" protocols; (27) provides the ability to a rapid test result and a confirmatory result; (28) utilizes an intact pad material and does not require that the absorbent pad material be separated from the main sampling device, so there is a significantly reduced chance of the pad separating in the subject's mouth when used in normal practice; (29) does not require the use of any salts or hypotonic solutions impregnated in the collection medium to improve collection time; (30) ability to deliver fluids to two test strips or two separate receiving ports at the same time.

Additional advantages of the invention will be set forth in part in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims. Further benefits and advantages of the embodiments of the invention will become apparent from consideration of the following detailed description given with reference to the accompanying drawings, which specify and show preferred embodiments of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows an embodiment of a specimen sample collection device and test system.

FIG. 2 shows a light pipe indicator window over a dry absorbent pad.

FIG. 3 shows a light pipe indicator window over a saturated absorbent pad

FIG. 4 shows another view of a specimen sample collection device.

FIGs. 5a, 5b, and 5c show different views of a pad compression tube.

FIG. 5c shows the view of Figure 5a from the side.

FIGs. 6a, 6b, and 6c show different views of a chambered collection tube.

FIG. 6b shows the view of Figure 6a from the side.

FIG. 7 shows a schematic view of a specimen sample collection device and
5 test system with a pad compression tube attached to a handle.

FIG. 8 shows another embodiment of a specimen sample collection device
and test system.

FIG. 9 shows another embodiment of a specimen sample collection device
and test system.

10 FIG 10. shows the interior layout of a specimen sample collection device.

FIG. 11 shows an embodiment of an absorbent pad.

FIG. 12 shows another embodiment of an absorbent pad.

DETAILED DESCRIPTION

Before beginning a detailed description of the subject invention, mention of
15 the following is in order. When appropriate, like reference materials and
characters are used to designate identical, corresponding, or similar components
in differing figure drawings. The figure drawings associated with this disclosure
typically are not drawn with dimensional accuracy to scale, i.e., such drawings
have been drafted with a focus on clarity of viewing and understanding rather than
20 dimensional accuracy.

As shown in FIGs. 1, 4, a specimen sample collection device 10 includes a
handle 14 with a sufficiency indicator, such as a light pipe indicator window 18,
and an absorbent pad, which can be a rounded tongue absorbent pad 15. As
shown in FIG. 1, a specimen sample collection device and test system 12 includes

a specimen sample collection device 10, a pad compression tube, which can be a dual outlet single channel compression tube 20, and a collection tube, which can be a chambered collection tube 26

Absorbent pad fits partially within the handle. As shown in FIGs. 1, 4, 7, 5 and 10 at 15, absorbent pad can be rounded to provide the advantage of comfort to the sample subject. As show in Figures 8 and 9 at 115, the absorbent pad can be split, i.e., divided into two parts and connected at the base of the pad to allow for dual sample collection. The split absorbent pad 115 can be prong- or fork-shaped or have splits of varying length. Those of skill in the art are aware that the 10 absorbent pad can be divided into more than two parts. In this embodiment the split absorbent pad 115 is configured such that one prong of the pad can absorb at least 1.0 mL of specimen, and the other pad can absorb at least 0.5 mL of specimen, when a highly absorbent pad material e.g. Ahlstrom 320 or Schleicher & Schuell 300 grades are chosen. When a split, divided, prong or fork shaped 15 absorbent pad is placed into the test subject's mouth each split or division of said absorbent pad absorbs saliva at the same time, thus collecting identical saliva samples. One of skill in the art would also realize that the absorbent pad could be two or more separate and distinct absorbent pads. Absorbent pad can also be provided with a bifurcated-end in a smooth "m" shape on the end of the pad 20 interior of the handle to deliver saliva to the ends of two test strips simultaneously.

The absorbent pad soaks up specimen when placed in a specimen atmosphere, such as for example, soaking up saliva when placed in a subject's mouth, preferably under the tongue. Absorbent pad is not filter paper. Filter paper is designed specifically to have porous openings to have control or "filter"

the size of material passing through it. The purpose of the absorbent pad is to collect and disperse a high volume of liquid sample yet remain relatively rigid through the sample collection procedure. Thus, an advantage is obtained by using an absorbent pad rather than filter paper. Absorbent pad may be a variety of
5 different materials that will absorb liquid and release or transmit said liquid following an action carried out to facilitate removal of said liquid from the pad.

Pad materials have a variety of properties, which may affect the ability of a substance to adhere (or bind) to that specific absorbent pad material effectively, and also for that material to be suitably released from the pad when required. One
10 particular property is a material's hydrophobic or hydrophilic characteristics. Hydrophilic materials are readily "wet" with aqueous solutions and so aqueous based fluids, such as saliva, urine, whole blood, vaginal fluid, etc. (containing antibodies, minerals, and other analytes of interest, will be readily absorbed by hydrophilic pad materials and released effectively. In the preferred embodiment of
15 this invention for example, absorbent pad material is made up of hydrophilic materials from a list including Ahlstrom materials catalog numbers 270 and 320, Schleicher & Schuell catalog numbers 300 and 900 among others. Experimentation has shown that a large cross-section of substances to be detected or measured in fluids can be carried out using one of these versatile
20 products. Hydrophobic pad materials will not adequately "wet" in aqueous solutions but will be wetted in low surface tension liquids such as alcohols, hence the need for the addition of low alcohol concentrations in any buffering system used.

Those skilled in the art know that numerous materials meeting these requirements exist, such as various cotton linters, for example Schleicher & Schuell (US) papers 300, 900, 903 or 2992, fiber composite materials such as materials available from Ahlstrom (US) for instance Ahlstrom 270, a multi-purpose
5 cellulose material that has been used for fluid collection and release and Ahlstrom grade 320 material, a material with hydrophobic characteristics. Also glass fiber, certain polymeric materials, spunbound polyester materials (e.g. Hollytex brand from Ahlstrom, (US), extruded fibers, other cellulose papers manufactured from raw material cellulose (e.g. Ahlstrom Paper group (US) and Filtrona (US)
10 Transorb® materials), mixed fiber papers (e.g. Whatman (UK) Pads S9036-2009) as well as two-ply materials for example. The properties of these materials vary from absorbent materials with low protein binding capability to those with high binding capacity. Materials are available in various thicknesses and sizes and may be easily customized to suit the specific intended application for the pad
15 material. Already, a diverse range of product materials is available from several sources including Schleicher & Schuell, Ahlstrom, Filtrona, Porex, Whatman and others as described above. These materials are typically manufactured under strictly controlled conditions to ensure uniform composition and absorption/release of fluids from the pad. Several of the afore-mentioned materials have been widely
20 used as diagnostic and analytical testing components and have been certified as suitable for these purposes. Those skilled in the art know that absorbent pad materials may also include hydrophilic or hydrophobic components bound, or integrated into the material, such components being capable of modifying the absorption and release characteristics of the absorbent pad as well as the speed

of uptake of the sample fluid under consideration. In the majority of cases antibodies minerals and substances will be readily removed from the absorbent pad upon squeezing the pad in the compression tube according to the operational instructions supplied herein. However, in certain instances, materials that are
5 difficult to remove e.g. hydrophobic materials including progesterone, testosterone, estradiol, other steroid hormones and Δ^9 -Tetrahydrocannabinol (THC), will be collected in a further embodiment using a pad with hydrophobic properties. In this embodiment a small percentage of low molecular weight alcohol (ethanol, methanol or butanol, for instance) at a concentration of 0.1%- 4.0% is added.

10 The binding characteristics of various protein and other molecules to the absorbent pad is another important factor. This particular property influences the nature of the binding of a given material to absorbent pad materials and is carefully considered when choosing products for a given application. Materials with high-binding characteristics may in some instances be used to encourage removal of
15 certain analytes from the oral cavity, which may be difficult to obtain using pad materials with lower binding characteristics. In these cases, release agents such as alcohols, Tween 20 and others may be used.

Other properties, which can impact the performance of absorbent materials and hence the ability to collect an optimum fluid specimen include thermal stability,
20 pore size and pad size. The dimensions and materials used in the preferred embodiments of this invention including Ahlstrom 270 & 320, Schleicher & Schuell 300 & 900 cellulose materials and others have been well characterized by the manufacturers and are also available in published works.

To one skilled in the art there are also a spread of materials, which offer a choice of "wicking rate", meaning the rate at which sample fluid is absorbed by the paper or pad material, so it is important for optimization purposes to work with individual manufacturers of such products to choose the optimum characteristics
5 necessary to achieve the best results.

To one skilled in the art it is further apparent that modification of the properties of the absorbent pad can be made by the addition of various agents at the time of manufacturing the pad material. This invention has been conceived as a means of providing a method for customization and optimization of the properties
10 of pad materials for a wide range of specific applications for which fluid collection is required. Further it is understood by one skilled in the art that modification of the dimensions of the pad (for instance thickness, width, height and others) can modify the absorption characteristics of the pad material. Materials such as those cited here are available through a number of companies including Whatman (UK),
15 Ahlstrom (Finland), Schleicher and Schuell (US), Porex and Filtrona (US), which are chosen here by way of examples. While the above list of materials is considerable, these may or may not be suitable for the collection of certain types of specimens in fluids, for example steroid hormones, THC and certain other drug substances and others, for instance, which have a tendency to "stick to" certain
20 pad materials and can be bound tightly. An embodiment of this invention therefore, teaches a method of using alternate pad materials in order to obtain the optimum system for collection and subsequent testing or analysis of certain hormones, drugs and any materials likely to cause difficulty in analyte removal from the pad. The ability to provide flexible options for pad materials is a novel

invention. An advantage of this is that the pad material may be modified and optimized to suit the subsequent analysis, testing, or other action to be performed.

In an alternative embodiment, as shown in FIGs. 11, 12, absorbent pad can be a folded in half providing a double layer absorbent pad to provide additional structure for the absorbent pad and increase the surface area and absorption volume. Figure 11 at 200 shows one possible shape, with the pad folded upon itself along the fold line at 202, which can be used with the specimen sample collective device 10. Figure 12 at 204 shows a split absorbent pad shape, with the pad folded upon itself along the fold line at 206. Those skilled in the art will know that absorbent pads can be folded in a number of ways to reach the result of providing a double layer absorbent pad for additional structure and an increase in the surface area and absorption volume.

As shown in FIGs. 2, 3, 4, sufficiency indicator is preferably a shaped light pipe 18 with a color or indicator on one end 18a, which is placed in contact with the absorbent pad 15. It is preferably made of styrolux. As show in FIGs. 2, 3, when the absorbent pad is saturated with sufficient sample, the reflectance of the pad changes causing a change in the refractive properties of the light pipe, seen as an altering of the color or indicator, which is seen as a line 18b. The indicator is capable of distinguishing and providing a visual indication between a dry and wet absorbent pad. The absorbent pad is opaque when dry and provides a good reflecting surface. However, when the absorbent pad becomes wet, the pad develops a surface film of liquid and also become translucent. This reduces the absorbent pad's reflective ability and the line 18b is no longer visible to the user.

Alternatively, the sufficiency indicator can be a molded or otherwise manufactured window, convex side downward, and frosted or textured such that when absorbent pad expands by absorption of sufficient sample, the wet absorbent pad touches the inside of the indicator resulting in a change in window clarity, clear spot or symbol indicating that adequate sample volume has been achieved. In this embodiment, an expandable material in contact with an absorbent pad, expands behind and obscures an indicator providing a visual indication that sample volume is adequate when an adequate sample content is reached.

Alternatively, the sufficiency indicator can be a clear window with a small absorbent pad with a colored dot on the inward side, attached on the inside of the window. When the absorbent pad expands against the absorbent paper, the liquid from that pad is transferred to the absorbent paper. Becoming wet, the absorbent pad becomes translucent during which time the colored dot becomes visible through the absorbent paper and becomes visible in the sample adequacy indicator.

Alternatively, the sufficiency indicator can be coated on the inside with a chemically neutral hydrochromic material such that when absorbent pad swells with sample it absorbs, the swollen pad touches the inside of the indicator, reacting with the coating and causing a color change or graphic symbol to appear. Those skilled in the art know that many different chemically neutral hydrochromic coating materials can be used which would not alter the test samples.

Alternatively, the sufficiency indicator is a simple Liquid Crystal Display (LCD) device with two bi polar metal leads pressing into the absorbent pad. When

the pad is of adequate saturation, galvanic action causes a small electrical current to flow between the metal leads causing the LCD to darken.

Alternatively, the sufficiency indicator is configured as a snap-up indicator that includes a plastic spring set in a sponge-like material. Sponge-like material
5 can be any material that when moistened loses structural rigidity and softens. When material is softened by sample, for instance saliva, one part of the "spring" disengages from the sponge and snaps providing visual indication that sample volume is adequate.

Fluids are removed from absorbent pads by squeezing sample from the pad
10 material through compression tubes. Alternate methods of fluid removal may be envisaged as necessary to facilitate removal of said liquid from the pad. Such techniques include vortexing, squeezing, centrifugation and treatment with an agent to promote removal of non-constituent components of the pad material among others. Pushing the handle into the pad compression tube compresses
15 the absorbent pad expelling specimen from absorbent pad into the pad compression tube. As shown in Figure 7, pad compression tube 20 when inserted over absorbent pad 15 and on end of handle 14 is in fluid communication with absorbent pad 15.

Pad compression tube can have one or more channels and one or more
20 outlets. Figure 8 shows a dual outlet dual channel pad compression tube 120 having two outlets 122a, 122b. Figure 9 shows a single outlet single channel pad compression tube 150 with a single outlet 152. Figures 1, 5a, 5b, 5c, and 7 show a dual outlet single channel pad compression tube 20 with two outlets 22a, 22b.

As seen in Figures 7, pad compression tube 20 fits over and around the absorbent pad 15, which is partially contained within the handle 14 (see also Figure 10), and tube 20 goes over the end of the handle 14. As shown in the embodiment in Figure 8, handle 114 can be provided with a ridged lock 160 which fits in a depressed key 162 on a pad compression tube 120. Pad is pushed into pad compression tube until "locked" into place for safety preventing contamination and infectious transfer.

Pad compression tubes are made of polypropylene or acrylic or other suitable material. Pad compression tubes can be provided with a tube cap, see 24 in Figure 1 made of polypropylene or other suitable material.

A dual outlet dual channel pad compression tube 120 fits around a split absorbent pad 115. Pushing the handle 114 into the dual outlet dual channel pad compression tube 120 compresses the split absorbent pad 115, expelling specimen from split absorbent pad 115 into the dual outlet dual channel pad compression tube 120. Dual outlet dual channel pad compression tube 120 when inserted over split absorbent pad 115 and on end of handle 114 is in fluid communication with split absorbent pad 115. As shown in Figure 8, the dual outlet dual channel pad compression tube 120 includes a structural barrier 140 that separates the two parts of the split absorbent pad 115, such that when the pad 115 is compressed upon entry into the compression tube 120, the saliva sample from each said part of the pad 115 remains distinct and separate. Next, each separated saliva sample flows or is compressed into its own Eppendorf-style collection tube 126, which is attached to a compression tube, see 120 in Figure 8 and 150 in Figure 9.

The pad compression tube outlets can also each contain a particulate filter (not shown). Each distinct and separate saliva sample passes through its own particulate filter remaining distinct and separate.

The pad compression tube can contain a buffer solution to stabilize the sample obtained for analysis or testing. Suitable buffers include an aqueous solution with any of a variety of salts including sodium chloride, sodium phosphate, ethylene diamine tetra acetic acid (EDTA) salts or others. Buffer solution may contain a preservative to maintain the integrity of the sample and minimize degradation. This preservative serves to inhibit proteolytic properties of enzyme materials that can cause destruction of the antibody molecules being tested with the device over time. The types of compounds that can be considered as conferring preservative properties include enzyme inhibitors, anti-bacterial agents, bacteriostatic molecules, and anti-fungal compounds among others. Within the sub-group of bacteriostatic molecules, there are a number which can be added to also inhibit the growth of microorganisms. Such compounds include ProClin® (in various formulations) sodium azide and thimerosal.

The buffer solution may also include a detergent material, which improves antibody removal from the absorbent pad material, when desired. Preferred examples of this are Tween-20 (chemical name polyoxyethylene sorbitan monooleate) and sodium dodecyl sulfate (SDS), although other examples, e.g. Triton X-100, chlorhexidine and others may also be used. Tween-20 for example, is also useful for prevention of non-specific binding of required antibody molecules to unwanted solid surfaces. Typical concentrations of Tween-20, for instance, necessary to achieve the desired effect, range from 0.1%-1%. Similarly, low

molecular weight alcohols (ethanol, methanol, butanol, etc.) in low concentrations (0.1-4.0%) can be introduced as additional analyte-releasing agents, depending upon the material under investigation.

Those skilled in the art will know that there are many possible agents capable of being used as "buffering components". Alternately the pad collection tube may contain no reagent or liquid whatsoever. Alternately, the pad collection tube may contain a non-fluid containing buffer, i.e. a buffer without liquid, commonly referred to as a "dry buffer". The permutation and concentrations of any agents used as part of the collection procedure will be optimized for the collection of specific target molecules. In the case of analytes or materials that are difficult to release from the pad material under "normal" buffer conditions, for example "sticky" materials such as the drug THC, or steroid hormones (including testosterone, estradiol, progesterone and others), various reagents including small quantities (less than 5%) of an alcohol, e.g. methanol, ethanol, propanol, isopropanol may be added to facilitate analyte release.

Typical buffers include phosphate buffered saline consisting of, for example: 10mmol/L Sodium Phosphate Dibasic; 150mmol/L Sodium Chloride; 5mmol/L Disodium Ethylenediamine Tetraacetate (EDTA); 31mmol/L Sodium Azide; Adjusted to neutral pH of 7.2

Collection tubes can be a chambered collection tube 26, as shown in Figures 1, 6a, 6b, and 6c, or individual collection tubes 126, as shown in Figures 8 and 9.

Chambered collection tube 26 is shown in different views in FIGs 6a, 6b, 6c.. Ccollection tubes fit over the end of the pad compression tube and have one

or more more chambers for receiving and holding collected samples. These chambers or compartments are separated allowing samples to remain distinct and free from contamination. In any embodiment, collection tube, at 26 in Figure 1 and at 126 in Figures 8 and 9, when inserted on end of pad compression tube, 20 in Figure 1, 120 in Figure 8, and 150 in Figure 9 is in fluid communication with pad compression tube. Collection tube, at 26 in Figure 1 and at 126 in Figures 8 and 9, can be provided with a tube cap, at 28 in Figure 1, and at 128 in Figures 8 and 9, sealing the tubes.

Eppendorf-type collection tubes 126, in Figures 8 and 9, collect the separate and distinct saliva samples once they pass through a pad compression tube. Eppendorf-type collection tubes 126 are conical at their closed end, round at the open end, and comprised of flexible lids 128 that remain attached to the tube 126 whether open or closed. The Eppendorf-type collection tubes 126 may be attached together on the outside surface. The Eppendorf-type collection tubes 126 remain inwardly distinct in that each receives one of the distinct and separate saliva samples and said samples remain separate and distinct once in the Eppendorf-type collection tubes 126. The Eppendorf-type collection tube lid 128 is then closed, retaining the fluid sample's integrity and quantity.

Handles, pad compression tubes, and collection tube can be made using any number of different processes familiar to those with skill in the art, such as by injection molding, compression molding, casting; incorporating materials such as thermoplastics, thermosets, glass, metal, etc. The light pipe indicator window can be made of clear material-glass, plastic, Perspex; sample sufficiency indicator changes color or when something is moved, i.e., changes condition.

In the preferred embodiment, handle is made of two elongated pieces of General Purpose Styrene which fit together over a portion of the absorbent pad. See Figure 10. Handle is preferably made of two pin and ultrasonically assembled halves. Those of skill in the art know that the handle can be made of any one of
5 numerous materials.

In the preferred embodiment collecting saliva, though other embodiments for collecting samples other than saliva exist (such as collection of water for environmental testing purposes, urine analysis for drug testing, bioavailability testing in the pharmaceutical industry and many others), absorbent pad is placed
10 in the mouth under the tongue. Absorbent pad expands when a specimen sample is received. When indicator indicates sufficient sample has been obtained, Indicator provides a visual indication of the same.

In order to enrich the specimen with immunoglobulins, which are present under the lip line at the end of the collection process, the specimen sample
15 collection device is taken and "swabbed" once across the gums from one side to the other, then reversed and swabbed across the gum line a second time in the opposite direction.

In order to collect saliva, the specimen sample collection device is placed under the tongue and allowed to remain there until the visual indicator in the
20 device—a light pipe showing a blue coloration—disappears completely. The typical collection time for sample adequacy is in the range of 1–2 minutes. The disappearance of the visual indicator may be observed by a second person or in the event of the sample being collected in the privacy of the home, by a donor in isolation. The device may be removed from the mouth to visually inspect for the

disappearance of the color and replaced under the tongue immediately without detriment to the collection or subsequent test procedure.

In operation using a split absorbent pad 115 and a dual outlet dual channel pad compression tube 120, the user places the pad 115 into the dual outlet pad compression tube 115 with the split end facing downwards, and places the
5 Eppendorf-type collection tube 126 on the outlets 122 of the dual outlet pad compression tube 120, and pushes on handle 114, forcing the pad 115 all the way down to the bottom of the compression tube 120 until the end of the handle 114 can be pushed no closer to the bottom of the compression tube 120. Pushing
10 expels specimen from split absorbent pad 115, which then travels in fluid communication through the dual outlet pad compression tube 120, through the outlets 122 and into collection tubes 126. The collection tubes 126 thus provide samples for supplemental or confirmatory testing as well as for independent storage or transportation. Two samples are thus provided. Depending upon the
15 dimensions and type of pad material used the individual forks of the absorbent material will release between 0.3 ml and 2 ml of pure saliva. In instances where the individual samples, are to be transported to a laboratory or remote location, or are not for immediate testing, a preservative buffer may be introduced either in the compression tube or the collection receptacles to maintain the integrity of the
20 sample so collected. The buffer may be a liquid or dry buffer. In instances where the samples are to be tested immediately, or at the point-of-care, the device may be supplied without buffer. In order to determine the volume of specimen received by this action, graduated tubes, such as small Eppendorf tubes, available "off the shelf" from a number of vendors, may be used. Alternatively, where no duplicate

sampling is required, the collection tube can be a single channel collection receptacle or Eppendorf tube. Depending upon sampling requirements alternative customized collection tubes may be adapted for use with the invention. Each of the tubes used in connection with the collection tool are fitted with individual caps
5 for sealing purposes. These caps may be tamper-proof for evidentiary purposes. Similarly, the pad compression tube can be provided with a cap or caps for sealing.

The specimen sample collection device 10 can be provided with one or more lateral flow test strips 16a, 16b in the handle 14 in fluid communication with
10 the absorbent pad 15 by one or more membranes 17a, 17b. Such tests strips, for example ICT strips are commonly used in the diagnostic industry today, to screen for a plethora of diseases including HIV, streptococcus A & B, hepatitis A, B & C, cardiac markers (e.g. troponin I, troponin T, myoglobin), tumor markers (e.g. prostate specific antigen (PSA), alpha-fetoprotein (AFP), etc.), glucose, cholesterol
15 and others.

The test strip is coated or "striped" with one or more analyte of interest, together with a control material usually Protein A-gold coated to human IgG to verify that the test strip is working appropriately. Such strips are now very commonly available and well characterized. After a short period of time (which
20 may vary from 2 to 20 minutes), a Control Line will appear on the test strip, and in instances of a positive specimen a second line (the Test Line) will appear indicating positivity for the analyte of interest.

The test strip is comprised of reagents that test qualitatively (for the presence or absence of analytes or substances) and/or semi-quantitatively

(providing an estimate of the quantity) of the chemical(s) / substances for which the device tests within the fluid sample. In the preferred embodiment the test strip is located in the collector handle housing, above the attachment loci of the absorbent pad. The collector handle housing has a window-type opening above a
5 portion of the test strip through which results from the test strip can be viewed.

A reagent test strip comprised of at least one reagent chemical that upon contact with the chemical for which it tests or a by-product of the chemical for which it tests in the testing fluid, undergoes a chemical reaction which produces or activates an indicator, preferably visual, of the presence or absence and/or
10 quantity of the chemical for which it tests.

The test system may be applied to a number of different diseases, and analytical tests, which includes HIV, drugs of abuse, bacteria, viruses, environmental toxins and others. Reaction times and run times will vary depending upon the characteristics of individual test strips, which are optimized to
15 achieved maximum sensitivity and specificity. The characteristics of each individual test will be defined in the respective package insert for the products, however, as an example, an HIV test optimized for oral fluid detection using the specimen sample collection device will provide results within a period of 10 – 20 minutes with a sensitivity greater than 95% and a specificity of greater than 99%.
20 What should be understood in the case of an HIV test is that the appearance of a Test Line in the presence of a Control Line is indicative of an initially positive or non-negative result.

When more than one test strip is provided they are arranged side-by-side on the handle 14, as shown in Figures 4 and 10, at 16a, 16b. In this embodiment,

saliva collected in identical fashion to the embodiments described above, is transferred to two test strips instead of one by two membranes, 17a, 17b. Using this configuration, a multiplicity of analytes, for instance drugs of abuse, including but not limited to the NIDA-5 series of drugs, benzodiazepines, Oxycodone, and
5 others, as well as therapeutic drugs and multiple infectious diseases for instance may be detected simultaneously using a single oral fluid collection device and test system. Test strips for the NIDA-5 series of drugs have been optimized in the specimen sample collection device to run within 15 minutes from the time sample adequacy has been achieved.

10 In this embodiment, the reagent test strips 16 are located in the collector handle 14 housing with a window-type opening 60 above each test strip 16, or, alternatively, a single window-type opening above all the test strips. Each test strip contains a reagent test for analyzing the qualitative (presence or absence) and/or quantitative data of the chemical for which it tests within the fluid sample.
15 One of skill in the art would understand that each test strip may test for a different chemical or the same chemical as any other test strip. In the preferred embodiment, the test strips extend linearly down the length of the collector handle housing, parallel to one another. In another embodiment, the test strips may be adjacent to one, two or more additional test strips.

20 In embodiments including a test strip 16 under a test strip opening 60, the results may be read visually or may be read by electronic reading devices including pocket-PC devices, PDAs and others. In the preferred embodiment of this invention a pocket-PC driven system, utilizes proprietary software to digitally record images from the lateral flow test strips. The reader combines a "Pocket

PC" (PDA-sized) reading system, printing device, camera and software, capable of reading multiple lines within a pre-set reading window. Once the specimen sample collection device incorporating one or more test strips has run and the immunochromatographic test results have been observed visually, (after the pre-

5 established reaction time is over), a plastic cap is placed over the absorbent collection pad of the specimen sample collection device, if desired, then the opposite end of the device (handle-first) is inserted into the port of the hand-held reading device. The reading device initially does a diagnostic "self test" to ensure that the reader is working appropriately then performs a read out of the intensity of

10 the coloration of the individual line (or lines) on the test strip (or strips). The results of this are fed automatically to a printing device, which prints out a permanent record of the results for each drug or other analyte being tested. The visual appearance of a line, or the confirmation of a line in the case of drug tests using the hand-held reading system is an indication that the test is negative or non-

15 positive for that particular analyte or drug. This is the opposite of what one would find for similar tests for HIV and other analytes where the presence of a Test Line in the presence of a Control Line is indicative of a positive or non-negative result. The invention provides visually read, qualitative results, which may be quantitated using available electronic, digital or other format readers. These in turn may be

20 either small, PDA-sized (hand-held) systems or portable and non portable instruments that utilize electromagnetic radiation, chemiluminescence, digital photography and other techniques, while providing a digital printout of the quantitative results obtained.

Fluid forced through separate porous filters in pad compression tube and into mutually distinct graduated Eppendorf-type tubes attached to the pad compression tube outlets. Each Eppendorf tube is then bar coded. A bar code may further be provided on the specimen sample collection device handle. A
5 recess is molded into the specimen sample collection device handle and the bar code is imprinted thereon.

Those skilled in the art will recognize that numerous modifications and changes may be made to the preferred embodiment without departing from the scope of the claimed invention. It will, of course, be understood that modifications
10 of the invention, in its various aspects, will be apparent to those skilled in the art, some being apparent only after study, others being matters of routine mechanical, chemical and electronic design. No single feature, function or property of the preferred embodiment is essential. Other embodiments are possible, their specific designs depending upon the particular application. As such, the scope of the
15 invention should not be limited by the particular embodiments herein described but should be defined only by the appended claims and equivalents thereof.

CLAIMS

We claim:

1. A specimen sample collection device, comprising:
 - a handle having a sufficiency indicator; and
 - 5 an absorbent pad partially contained within said handle.
2. A specimen sample collection device and test system, comprising:
 - a handle having a sufficiency indicator;
 - an absorbent pad partially contained within said handle;
 - a pad compression tube insertable over said absorbent pad within
 - 10 said handle and around an end of said handle; and
 - a collection tube having one or more sample chambers, attachable to said pad compression tube, and wherein said compression tube defines one or more chambers, and wherein when said collection tube is attached to said pad compression tube, the chambers are in fluid communication with
 - 15 said pad compression tube.
3. The apparatus of claims 1 or 2, wherein said indicator is a lightpipe having first, second, and third surfaces, wherein the first surface is marked, and wherein the second surface is in contact with an absorbent pad, and wherein the third surface is in visible proximity to an indicator, wherein when absorbent pad absorbs
- 20 a particular amount of liquid, which changes the refracting properties of the light pipe, such change altering the ability of the light pipe to transfer the symbol or "marking" to the sample, and wherein the resulting appearance or disappearance of the symbol or marking indicating that adequate sample has been achieved.

4. The apparatus of claims 1 or 2, wherein said indicator is a spring set into sponge-like material, wherein said sponge-like material is in contact with an absorbent pad, and wherein when the sponge-like material is softened by an adequate amount of saliva, spring partially or completely disengages from sponge-like material and snaps providing visual and audible indication that sample volume is adequate.

5. The apparatus of claims 1 or 2, wherein said indicator is an expandable material in contact with an absorbent pad and a clear window, wherein when an adequate sample content is reached, the expandable material expands behind and obscures the window providing a visual indication that sample volume is adequate.

6. The apparatus of claims 1 or 2, wherein said indicator is a LCD with bi-polar pins, which rest on the absorbent pad, wherein when sufficient liquid touches both bi-polar pins a small electrical current flows through the LCD causing it to change states from clear to black, providing a visual indication that sample volume is adequate.

7. The apparatus of claims 1 or 2, wherein said indicator is an absorbent paper with a colored dot located on the inward side can be attached to the inside of a clear window, wherein when an absorbent pad expands against the absorbent paper, the liquid from that pad is transferred to the absorbent paper, wherein becoming wet, the absorbent pad becomes translucent during which time the colored dot becomes visible through the absorbent paper and becomes visible in the window .

8. The apparatus of claims 1 or 2, wherein the indicator is a window coated on the inside with a hydrochromic material such that when absorbent pad swells with

sample it absorbs, the wet, swollen pad touches the inside of the window, reacting with the coating and causing a color change or graphic symbol to appear.

9. A specimen collection device, comprising,

Means for providing immediate test results of tests on specimens;

5 and

Means for providing two or more liquid samples for later analysis of said specimens.

10. The specimen sample collection device of claims 1 or 2, wherein said absorbent pad is rounded in that portion protruding from said handle.

10 11 The specimen sample collection device of claims 1 or 2, wherein said absorbent pad is split, divided into two parts and connected at a base of said absorbent pad.

12. The specimen sample collection device and test system of claims 2, wherein said pad compression tube is provided with two chambers into which a
15 split absorbent pad can be placed and each chamber has an outlet.

13. The specimen sample collection device and test system of claims 9, wherein collection tubes mate to outlets on pad compression tube.

14. The specimen sample collection device of claims 1 or 2, wherein said handle is further provided with a bar code number uniquely identifying said handle.

20 15. The specimen sample collection device of claims 1 or 2, further comprising a single analyte test strip in said handle and a membrane in said handle, wherein said membrane is in fluid communication with said test strip and said absorbent pad.

16. The specimen sample collection device of claims 1 or 2, further comprising two or more analyte test strips in said handle and two or more membrane in said handle, wherein said membranes are in fluid communication with said test strips and said absorbent pad.

5 17. The specimen sample collection device of claims 1 or 2, further comprising one or more analyte test strips in said handle and a membrane in said handle, wherein said membrane is in fluid communication with each of said test strip and said absorbent pad.

18. The specimen sample collection device and test system of claims 1 or 2,
10 further comprising a reader.

19. The specimen sample collection device and test system of claim 2, wherein said handle is further provided with a ridged lock and said pad compression tube is provided with a depressed key to lock the handle into the pad compression tube.

20. The apparatus of claims 1 or 2, wherein the absorbent pad is folded over
15 upon itself.




Fig. 2




Fig. 3





Fig. 4








FIG. 6a




FIG. 6b




FIG. 6c





FIG. 7






Fig. 8




Fig. 9

FIG. 10




FIG. 11




FIG. 12

